

# RF Exposure Evaluation

## FCC ID: 2AHVWSKC-BKA050

### 1. Client Information

**Applicant** : Shenzhen Sunkong Technology Development Co., Ltd  
**Address** : West, 4th Floor, 16 Building, Majialong Industrial Zone, Nanshan District, Shenzhen, China  
**Manufacturer** : Shenzhen Sunkong Technology Development Co., Ltd  
**Address** : West, 4th Floor, 16 Building, Majialong Industrial Zone, Nanshan District, Shenzhen, China

### 2. General Description of EUT

<b>EUT Name</b>	:	MOCUTE GAMEPAD	
<b>Models No.</b>	:	SKC-BKA050	
<b>Model Difference</b>	:	N/A	
<b>Product Description</b>	:	Operation Frequency: Bluetooth 3.0:2402~2480MHz	
		Number of Channel:	Bluetooth:79 Channels
		Max Peak Output Power:	Bluetooth: 1.785 dBm(GFSK)
		Antenna Gain:	0 dBi PCB Antenna
		Modulation Type:	GFSK 1Mbps(1 Mbps)
<b>Power Supply</b>	:	DC Voltage supplied from Host System by USB cable. DC power by Li-ion Battery.	
<b>Power Rating</b>	:	DC 5.0V by USB cable. DC 3.7V 350mAh by Li-ion Battery.	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	

#### Note:

More test information about the EUT please refer the RF Test Report.

## SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v05r02.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance  $\leq 5$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR}$$
$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 7.5.0 \text{ for 10-g SAR}$$

2.

**Calculation:**

Test separation: 5mm					
Bluetooth Mode (GFSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	1.785	$\pm 0.5$	1.692	0.525	3.0
2.441	1.183	$\pm 0.5$	1.473	0.460	3.0
2.480	0.974	$\pm 0.5$	1.404	0.442	3.0

So standalone SAR measurements are not required.