



FCC RADIO TEST REPORT

FCC ID : 2AHXCBC2500
Equipment : BC2500
Brand Name : BlueCats
Model Name : BC2500
Marketing Name : BC2500
Applicant : BlueCats US LLC
6767 Old Madison Pike NW, Suite 300,
Huntsville, AL 35806
Manufacturer : BlueCats US LLC
6767 Old Madison Pike NW, Suite 300,
Huntsville, AL 35806
Standard : FCC Part 15 Subpart C §15.247

The product was received on Dec. 17, 2019 and testing was started from Dec. 18, 2019 and completed on Dec. 19, 2019. We, Sporton International (USA) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (USA) Inc., the test report shall not be reproduced except in full.

Approved by: Ken Chen

Sporton International (USA) Inc.
1175 Montague Expressway, Milpitas, CA 95035



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	5
2 Test Configuration of Equipment Under Test	6
2.1 Carrier Frequency Channel	6
2.2 Test Mode.....	7
2.3 Connection Diagram of Test System.....	8
2.4 EUT Operation Test Setup	8
2.5 Measurement Results Explanation Example.....	8
3 Test Result.....	9
3.1 6dB and 99% Bandwidth Measurement	9
3.2 Output Power Measurement.....	18
3.3 Power Spectral Density Measurement	19
3.4 Conducted Band Edges and Spurious Emission Measurement	28
3.5 Radiated Band Edges and Spurious Emission Measurement	37
3.6 Antenna Requirements.....	41
4 List of Measuring Equipment	42
5 Uncertainty of Evaluation.....	43
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FR191217001	01	Initial issue of report	Jan. 23, 2020

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Peak Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 3.49 dB at 2483.560 MHz
-	15.207	AC Conducted Emission	Not Required	-
3.6	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Remark: Not required means after assessing, test items are not necessary to carry out.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Product Feature of Equipment Under Test

Bluetooth - LE and GNSS

Product Specification subjective to this standard	
Antenna Type	Bluetooth LE: PCB Antenna GPS: Patch Antenna

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	Sporton International (USA) Inc.	
Test Site Location	1175 Montague Expressway, Milpitas, CA 95035 TEL : 408 9043300	
Test Site No.	Sporton Site No.	
	TH01-CA	03CH01-CA

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps

2.3 Connection Diagram of Test System



2.4 EUT Operation Test Setup

The RF test items, make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

<1 Mbps>


6 dB Bandwidth Plot on Channel 00



Date: 18 DEC 2019 11:44:31




6 dB Bandwidth Plot on Channel 19



Date: 18 DEC 2019 12:00:24

6 dB Bandwidth Plot on Channel 39




Date: 18 DEC 2019 13:14:32



<2 Mbps>


6 dB Bandwidth Plot on Channel 00



Date: 18 DEC 2019 13:23:53




6 dB Bandwidth Plot on Channel 19



Date: 18.DEC.2019 13:30:33

6 dB Bandwidth Plot on Channel 39



Date: 18.DEC.2019 13:43:21




3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

<1 Mbps>


99% Bandwidth Plot on Channel 00



Date: 18.DEC.2019 11:56:54




99% Occupied Bandwidth Plot on Channel 19



Date: 18.DEC.2019 12:06:28

99% Occupied Bandwidth Plot on Channel 39





Date: 18.DEC.2019 13:19:35




<2 Mbps>

99% Bandwidth Plot on Channel 00



99% Occupied Bandwidth Plot on Channel 19


Date: 18.DEC.2019 13:34:14

99% Occupied Bandwidth Plot on Channel 39


Date: 18.DEC.2019 13:50:06

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for average output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the average output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 30dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.




PSD 100kHz Plot on Channel 00



Date: 18.DEC.2019 12:02:30



PSD 100kHz Plot on Channel 39




Date: 18.DEC.2019 13:15:37




<2 Mbps>

PSD 100kHz Plot on Channel 00



Date: 18.DEC.2019 13:24:51


PSD 100kHz Plot on Channel 19



Date: 18.DEC.2019 13:32:08



PSD 100kHz Plot on Channel 39




Date: 18.DEC.2019 13:44:30

3.3.7 Test Result of Power Spectral Density Plots (3kHz)


<1 Mbps>

PSD 3kHz Plot on Channel 00



Date: 18.DEC.2019 11:45:22


PSD 3kHz Plot on Channel 19



Date: 18.DEC.2019 12:02:15



PSD 3kHz Plot on Channel 39




Date: 18.DEC.2019 13:15:17




<2 Mbps>

PSD 3kHz Plot on Channel 00



Date: 18.DEC.2019 13:24:36


PSD 3kHz Plot on Channel 19



Date: 18.DEC.2019 13:31:24



PSD 3kHz Plot on Channel 39



Date: 18 DEC 2019 13:43:49

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots


<1 Mbps>

Low Band Edge Plot on Channel 00



Date: 18.DEC.2019 11:46:36

High Band Edge Plot on Channel 39




Date: 18.DEC.2019 13:16:02




<2 Mbps>

Low Band Edge Plot on Channel 00



Date: 18.DEC.2019 13:26:11


High Band Edge Plot on Channel 39



Date: 18.DEC.2019 13:48:43


3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 18.DEC.2019 11:55:15

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 18.DEC.2019 11:56:05

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 18.DEC.2019 12:05:04

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 18.DEC.2019 12:05:33

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39




Date: 18.DEC.2019 13:18:36

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39




Date: 18.DEC.2019 13:18:47


Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00



Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00




Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19




Date: 18.DEC.2019 13:32:53

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19




Date: 18.DEC.2019 13:33:27

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Date: 18.DEC.2019 13:49:04

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps FSK Channel 39



Date: 18.DEC.2019 13:49:23

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


See list of measuring equipment of this test report.

3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.



3.6 Antenna Requirements

3.6.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	45142595	N/A	Aug. 07, 2019	Dec. 18, 2019	Aug. 06, 2020	Conducted (TH01-CA)
Signal Analyzer	Rohde & Schwarz	FSV40	101089	10Hz~40GHz	Aug. 29, 2019	Dec. 18, 2019	Aug. 28, 2020	Conducted (TH01-CA)
Power meter	Anritsu	ML2495A	1804004	N/A	Aug. 14, 2019	Dec. 18, 2019	Aug. 13, 2020	Conducted (TH01-CA)
Power Sensor	Anritsu	MA2411B	1726149	300MHz~40GHz	Aug. 15, 2019	Dec. 18, 2019	Aug. 14, 2020	Conducted (TH01-CA)
Bilog Antenna	TESEQ	6111D	50391	30MHz~1GHz	Jun. 26, 2019	Dec. 19, 2019	Jun. 25, 2020	Radiation (03CH01-CA)
Horn Antenna	SCHWARZBECK	BBHA 9120D	02140	1GHz~18GHz	Aug. 19, 2019	Dec. 19, 2019	Aug. 18, 2020	Radiation (03CH01-CA)
Amplifier	SONOMA	310N	372241	N/A	Jul. 26, 2019	Dec. 19, 2019	Jul. 25, 2020	Radiation (03CH01-CA)
Preamplifier	Jet-Power	JPA0118-55-303	1710001800055007	1GHz~18GHz	Apr. 01, 2019	Dec. 19, 2019	Mar. 31, 2020	Radiation (03CH01-CA)
Preamplifier	Keysight	83017A	MY53270323	1GHz~26.5GHz	Jul. 26, 2019	Dec. 19, 2019	Jul. 25, 2020	Radiation (03CH01-CA)
EMI Test Receiver	R&S	ESU26	100049	20Hz~26.5GHz	Jul. 31, 2019	Dec. 19, 2019	Jul. 30, 2020	Radiation (03CH01-CA)
Filter	Wainwright	WLK12-1200-1272-11000-40SS	SN1	1.2G Low Pass	Aug. 02, 2019	Dec. 19, 2019	Aug. 01, 2020	Radiation (03CH01-CA)
Filter	Wainwright	WHKX12-2700-3000-18000-60ST	SN9	3G High pass	Aug. 02, 2019	Dec. 19, 2019	Aug. 01, 2020	Radiation (03CH01-CA)
Filter	Wainwright	WHKX8-5872.5-6750-18000-40ST	SN8	6.75 High pass	Aug. 02, 2019	Dec. 19, 2019	Aug. 01, 2020	Radiation (03CH01-CA)
Notch Filter	Wainwright	WRCJV10-2375-2400-2483-2508-40SS	SN4	Notch Filter	Aug. 02, 2019	Dec. 19, 2019	Aug. 01, 2020	Radiation (03CH01-CA)
Notch Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	SN14	Notch Filter	Aug. 02, 2019	Dec. 19, 2019	Aug. 01, 2020	Radiation (03CH01-CA)
Hygrometer	TESEO	608-H1	45142559	N/A	Aug. 06, 2019	Dec. 19, 2019	Aug. 05, 2020	Radiation (03CH01-CA)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Dec. 19, 2019	N/A	Radiation (03CH01-CA)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Dec. 19, 2019	N/A	Radiation (03CH01-CA)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Dec. 19, 2019	N/A	Radiation (03CH01-CA)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.4
--	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.5
--	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.9
--	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Tommy Lee	Temperature:	21~25	°C
Test Date:	2019/12/18	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.041	0.707	0.50	Pass
BLE	1Mbps	1	19	2440	1.045	0.719	0.50	Pass
BLE	1Mbps	1	39	2480	1.047	0.709	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	6.80	30.00	1.00	7.80	36.00	Pass
BLE	1Mbps	1	19	2440	6.88	30.00	1.00	7.88	36.00	Pass
BLE	1Mbps	1	39	2480	6.87	30.00	1.00	7.87	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	6.65	-9.80	1.00	8.00	Pass
BLE	1Mbps	1	19	2440	6.63	-9.82	1.00	8.00	Pass
BLE	1Mbps	1	39	2480	6.58	-9.96	1.00	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	2.026	1.171	0.50	Pass
BLE5.0	2Mbps	1	19	2440	2.034	1.171	0.50	Pass
BLE5.0	2Mbps	1	39	2480	2.038	1.167	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE5.0	2Mbps	1	0	2402	6.70	30.00	1.00	7.70	36.00	Pass
BLE5.0	2Mbps	1	19	2440	6.77	30.00	1.00	7.77	36.00	Pass
BLE5.0	2Mbps	1	39	2480	6.75	30.00	1.00	7.75	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	6.60	-11.41	1.00	8.00	Pass
BLE5.0	2Mbps	1	19	2440	6.60	-11.39	1.00	8.00	Pass
BLE5.0	2Mbps	1	39	2480	6.55	-11.40	1.00	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.



Appendix B. Radiated Spurious Emission

Test Engineer :	Daniel Lee	Temperature :	21~23°C
		Relative Humidity :	38~44%



<1 Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2381.505	61.7	-12.3	74	48.32	27.77	6.94	31.31	293	1	P	H
		2377.515	50.45	-3.55	54	37.06	27.8	6.93	31.32	293	1	A	H
	*	2402	105.93	-	-	92.62	27.66	6.97	31.3	293	1	P	H
	*	2402	104.91	-	-	91.6	27.66	6.97	31.3	293	1	A	H
													H
													H
		2352	62.01	-11.99	74	48.42	28.06	6.89	31.34	375	280	P	V
		2370.06	50.17	-3.83	54	36.63	27.96	6.92	31.32	375	280	A	V
	*	2402	104.16	-	-	90.72	27.79	6.97	31.3	375	280	P	V
	*	2402	103.08	-	-	89.64	27.79	6.97	31.3	375	280	A	V
													V
													V
BLE CH 19 2440MHz		2362.16	61.3	-12.7	74	47.86	27.88	6.91	31.33	284	1	P	H
		2375.92	50.21	-3.79	54	36.82	27.8	6.93	31.32	284	1	A	H
	*	2440	105.14	-	-	91.8	27.61	7.04	31.29	284	1	P	H
	*	2440	103.27	-	-	89.93	27.61	7.04	31.29	284	1	A	H
		2484.32	61.78	-12.22	74	48.36	27.61	7.11	31.28	284	1	P	H
		2491.28	49.61	-4.39	54	36.17	27.61	7.12	31.27	284	1	A	H
		2386	61.22	-12.78	74	47.72	27.88	6.95	31.31	323	272	P	V
		2376.08	50.09	-3.91	54	36.57	27.93	6.93	31.32	323	272	A	V
	*	2440	103.4	-	-	90.09	27.58	7.04	31.29	323	272	P	V
	*	2440	102.17	-	-	88.86	27.58	7.04	31.29	323	272	A	V
		2485.52	61.05	-12.95	74	47.63	27.61	7.11	31.28	323	272	P	V
		2486.88	49.79	-4.21	54	36.36	27.62	7.11	31.28	323	272	A	V



BLE CH 39 2480MHz	*	2480	103.13	-	-	89.72	27.61	7.1	31.28	273	0	P	H
	*	2480	102.01	-	-	88.6	27.61	7.1	31.28	273	0	A	H
		2493.16	60.76	-13.24	74	47.31	27.62	7.12	31.27	273	0	P	H
		2483.52	50.03	-3.97	54	36.61	27.61	7.11	31.28	273	0	A	H
													H
													H
	*	2480	101.73	-	-	88.33	27.6	7.1	31.28	355	274	P	V
	*	2480	100.59	-	-	87.19	27.6	7.1	31.28	355	274	A	V
		2488.16	60.97	-13.03	74	47.52	27.62	7.12	31.27	355	274	P	V
		2488.96	49.76	-4.24	54	36.31	27.62	7.12	31.27	355	274	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	46.76	-27.24	74	70.87	31.44	10.23	66.29	100	0	P	H
													H
													H
													H
		4804	47.22	-26.78	74	71.21	31.56	10.23	66.29	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	43.91	-30.09	74	67.9	31.35	10.27	66.14	100	0	P	H
		7320	55.92	-18.08	74	72.8	36.19	12.43	65.86	100	255	P	H
		7320	49.02	-4.98	54	65.9	36.19	12.43	65.86	100	255	A	H
													H
		4880	42.63	-31.37	74	66.56	31.41	10.27	66.14	100	0	P	V
		7320	56.08	-17.92	74	72.89	36.26	12.43	65.86	216	128	P	V
		7320	49.93	-4.07	54	66.74	36.26	12.43	65.86	216	128	A	V
													V
BLE CH 39 2480MHz		4960	43.36	-30.64	74	67.09	31.38	10.31	65.98	100	0	P	H
		7440	53.95	-20.05	74	70.61	36.33	12.57	65.89	100	253	P	H
		7440	46.25	-7.75	54	62.91	36.33	12.57	65.89	100	253	A	H
													H
		4960	44.3	-29.7	74	67.98	31.43	10.31	65.98	100	0	P	V
		7440	54.58	-19.42	74	71.2	36.37	12.57	65.89	116	166	P	V
		7440	46.38	-7.62	54	63	36.37	12.57	65.89	116	166	A	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		30	21.01	-18.99	40	27.24	25	1.15	32.43	-	-	P	H
		497.54	22.94	-23.06	46	28.32	23.85	3.34	32.73	-	-	P	H
		579.99	26.54	-19.46	46	29.6	25.9	3.76	32.84	-	-	P	H
		736.16	27.77	-18.23	46	28.57	27.67	4.05	32.77	-	-	P	H
		802.12	29.79	-16.21	46	29.49	28.26	4.3	32.57	-	-	P	H
		942.77	31.66	-14.34	46	27.61	30.57	4.64	31.58	100	0	P	H
													H
													H
													H
													H
													H
													H
													H
		30	21.15	-18.85	40	27.38	25	1.15	32.43	-	-	P	V
		520.82	23.92	-22.08	46	29.2	23.92	3.45	32.77	-	-	P	V
		638.19	26.91	-19.09	46	29.29	26.36	3.85	32.87	-	-	P	V
		746.83	28.4	-17.6	46	28.83	28.04	4.05	32.76	-	-	P	V
		826.37	29.46	-16.54	46	29.21	27.95	4.34	32.46	-	-	P	V
		955.38	32.82	-13.18	46	28.15	31.01	4.65	31.44	100	0	P	V
													V
													V
													V
													V
													V
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



<2 Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preampl Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2380.665	61.71	-12.29	74	48.33	27.78	6.94	31.32	293	1	P	H
		2377.62	50.13	-3.87	54	36.75	27.79	6.93	31.32	293	1	A	H
	*	2402	105.85	-	-	92.54	27.66	6.97	31.3	293	1	P	H
	*	2402	103.38	-	-	90.07	27.66	6.97	31.3	293	1	A	H
													H
													H
		2331.735	61.47	-12.53	74	47.93	28.05	6.86	31.35	375	279	P	V
		2370.06	50.15	-3.85	54	36.61	27.96	6.92	31.32	375	279	A	V
	*	2402	104.05	-	-	90.61	27.79	6.97	31.3	375	279	P	V
	*	2402	101.47	-	-	88.03	27.79	6.97	31.3	375	279	A	V
													V
													V
BLE CH 19 2440MHz		2311.76	61.28	-12.72	74	47.72	28.12	6.82	31.36	283	2	P	H
		2384.56	49.75	-4.25	54	36.39	27.75	6.94	31.31	283	2	A	H
	*	2440	105.19	-	-	91.85	27.61	7.04	31.29	283	2	P	H
	*	2440	102.64	-	-	89.3	27.61	7.04	31.29	283	2	A	H
		2488.08	60.91	-13.09	74	47.47	27.61	7.12	31.27	283	2	P	H
		2484.64	49.82	-4.18	54	36.4	27.61	7.11	31.28	283	2	A	H
		2347.92	61.86	-12.14	74	48.27	28.07	6.88	31.34	323	274	P	V
		2375.76	50.06	-3.94	54	36.54	27.93	6.93	31.32	323	274	A	V
	*	2440	103.46	-	-	90.15	27.58	7.04	31.29	323	274	P	V
	*	2440	100.84	-	-	87.53	27.58	7.04	31.29	323	274	A	V
		2496.48	60.75	-13.25	74	47.27	27.64	7.13	31.27	323	274	P	V
		2498.72	49.74	-4.26	54	36.25	27.65	7.13	31.27	323	274	A	V



BLE CH 39 2480MHz	*	2480	103.08	-	-	89.67	27.61	7.1	31.28	274	360	P	H
	*	2480	101.2	-	-	87.79	27.61	7.1	31.28	274	360	A	H
		2491.88	60.92	-13.08	74	47.48	27.61	7.12	31.27	274	360	P	H
		2483.56	50.51	-3.49	54	37.09	27.61	7.11	31.28	274	360	A	H
													H
													H
	*	2480	101.6	-	-	88.2	27.6	7.1	31.28	355	274	P	V
	*	2480	98.95	-	-	85.55	27.6	7.1	31.28	355	274	A	V
		2485.88	62.37	-11.63	74	48.95	27.61	7.11	31.28	355	274	P	V
		2483.68	50.37	-3.63	54	36.95	27.61	7.11	31.28	355	274	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	46.95	-27.05	74	71.06	31.44	10.23	66.29	100	0	P	H
													H
													H
													H
		4804	48.26	-25.74	74	72.25	31.56	10.23	66.29	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	42.76	-31.24	74	66.75	31.35	10.27	66.14	100	0	P	H
		7320	55.32	-18.68	74	72.2	36.19	12.43	65.86	100	255	P	H
		7320	47.02	-6.98	54	63.9	36.19	12.43	65.86	100	255	A	H
													H
		4880	43.89	-30.11	74	67.82	31.41	10.27	66.14	100	0	P	V
		7320	56.68	-17.32	74	73.49	36.26	12.43	65.86	224	135	P	V
		7320	48.58	-5.42	54	65.39	36.26	12.43	65.86	224	135	A	V
													V
BLE CH 39 2480MHz		4960	43.13	-30.87	74	66.86	31.38	10.31	65.98	100	0	P	H
		7440	53.55	-20.45	74	70.21	36.33	12.57	65.89	100	254	P	H
		7440	44.57	-9.43	54	61.23	36.33	12.57	65.89	100	254	A	H
													H
		4960	43.58	-30.42	74	67.26	31.43	10.31	65.98	100	0	P	V
		7440	53.98	-20.02	74	70.6	36.37	12.57	65.89	100	165	P	V
		7440	45.08	-8.92	54	61.7	36.37	12.57	65.89	100	165	A	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		30	21.46	-18.54	40	27.69	25	1.15	32.43	-	-	P	H
		485.9	23.2	-22.8	46	28.72	23.7	3.31	32.72	-	-	P	H
		561.56	26.27	-19.73	46	29.23	26.1	3.66	32.81	-	-	P	H
		673.11	28.31	-17.69	46	30.45	26.46	3.94	32.85	-	-	P	H
		777.87	28.58	-17.42	46	28.47	28.3	4.19	32.65	-	-	P	H
		920.46	31.65	-14.35	46	28.87	29.62	4.59	31.81	100	0	P	H
													H
													H
													H
													H
													H
													H
													H
		510.15	23.45	-22.55	46	28.66	24	3.4	32.75	-	-	P	V
		628.49	26	-20	46	28.66	26.11	3.85	32.86	-	-	P	V
		706.09	27.21	-18.79	46	29.1	26.62	4.06	32.85	-	-	P	V
		768.17	28.76	-17.24	46	28.8	28.26	4.14	32.7	-	-	P	V
		884.57	30.65	-15.35	46	28.65	29.2	4.49	32.08	-	-	P	V
		939.86	31.72	-14.28	46	27.89	30.39	4.63	31.61	100	0	P	V
													V
													V
													V
													V
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	
												V	

Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)

2. Level(dBμV/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Daniel Lee	Temperature :	21~23°C
		Relative Humidity :	38~44%

Note symbol





-L	Low channel location
-R	High channel location











<1 Mbps>

2.4GHz 2400~2483.5MHz



BLE (Band Edge @ 3m)





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 191217001 Power : Real Battery Plane : X
Avg.	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : AVG_54 3m HORN 91200-HF_01894 HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 191217001 Power : Real Battery Plane : X

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X
Avg	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : AVG_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 9120D-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 9120D-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X
Avg.	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 9120D-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : AVG_54 3m HORN 9120D-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 191217001 Power : Real Battery Plane : X	Left blank
Avg.	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 191217001 Power : Real Battery Plane : X	Left blank





BLE		2.4GHz 2400~2483.5MHz Band Edge @ 3m	
		BLE CH19 2440MHz - L	
	Vertical	Fundamental	
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	
	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : AVG_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	Left blank
Avg.	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X
Avg.	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : AVG_54 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X
Avg.	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : AVG_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 12-19-2019 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	Level (dBuV/m) Date: 12-19-2019 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	Level (dBuV/m) Date: 12-19-2019 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	Level (dBuV/m) Date: 12-19-2019 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X

Emission below 1GHz
2.4GHz BLE (LF)





BLE	2.4GHz 2400~2483.5MHz	
	BLE LF	
	Horizontal	Vertical
QP / Peak	 Site : 03CH01-CA Condition : QP 3m BTL06 6111D-LF_50391 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : QP 3m BTL06 6111D-LF_50391 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X











<2 Mbps>

2.4GHz 2400~2483.5MHz



BLE (Band Edge @ 3m)





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X
Avg.	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : AVG_54 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X
Avg	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : AVG_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 9120D-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 9120D-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X
Avg.	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 9120D-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : AVG_54 3m HORN 9120D-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	Left blank
Avg.	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X
Avg.	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : AVG_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	Left blank
Avg.	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X
Avg.	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : AVG_54 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	 Site : 03CH01-CA Condition : PEAK_BE_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X
Avg.	 Site : 03CH01-CA Condition : AVG_BE_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : AVG_54 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X



2.4GHz 2400~2483.5MHz



BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 12-19-2019 Frequency (MHz) Site : 03C401-CA Condition : PEAK_74 3m HORN 9120D-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	Level (dBuV/m) Date: 12-19-2019 Frequency (MHz) Site : 03C401-CA Condition : PEAK_74 3m HORN 9120D-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 12-19-2019 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	Level (dBuV/m) Date: 12-19-2019 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03CH01-CA Condition : PEAK_74 3m HORN 91200-HF_01894 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X



Emission below 1GHz

2.4GHz BLE (LF)

BLE	2.4GHz 2400~2483.5MHz	
	BLE LF	
	Horizontal	Vertical
QP / Peak	 Site : 03C401-CA Condition : QP 3m B1LOG 6111D-LF_50391 HORIZONTAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X	 Site : 03C401-CA Condition : QP 3m B1LOG 6111D-LF_50391 VERTICAL Detector : Peak Project : 191217001 Power : Real Battery Plane : X




Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth –LE for 1Mbps	87.47	1640	0.61	1kHz	0.58
Bluetooth –LE for 2Mbps	80.88	1015	0.99	1kHz	0.92

<1 Mbps>


Bluetooth - LE



Date: 18.DEC.2019 11:23:04

<2 Mbps>

Bluetooth - LE



Date: 18.DEC.2019 11:28:27