



TEST REPORT

Report No. : CHTEW19110189 Report Verification: 
Project No..... : SHT1911019301EW
FCC ID..... : 2AHY3-EXCELLO
Applicant's name..... : Simbans Limited
Address..... : 806, 8th Floor, Tai Tak Industrial Building 2-12 Kwai Fat Road,HONG KONG
Manufacturer..... : Simbans Limited
Address..... : 806, 8th Floor, Tai Tak Industrial Building 2-12 Kwai Fat Road,HONG KONG
Test item description : Excello 10.1 Inch Android Tablet PC
Trade Mark : Simbans
Model/Type reference..... : ExcelloTab
Listed Model(s) : -
Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of receipt of test sample..... : Nov.13,2019
Date of testing : Nov.13,2019 ~ Nov.27,2019
Date of issue..... : Nov.28,2019
Result..... : PASS

Compiled by
(Position+Printed name+Signature): File administrator Yueming Li

Yueming Li

Supervised by
(Position+Printed name+Signature): Project Engineer Kiki Kong

Kiki Kong

Approved by
(Position+Printed name+Signature): RF Manager Hans Hu

Hans Hu

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd.

Address..... : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road,
Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

1.	TEST STANDARDS AND REPORT VERSION	3
1.1.	Test Standards	3
1.2.	Report version	3
2.	TEST DESCRIPTION	4
3.	SUMMARY	5
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Radio Specification Description	5
3.4.	Testing Laboratory Information	6
4.	TEST CONFIGURATION	7
4.1.	Test frequency list	7
4.2.	Descriptions of Test mode	7
4.3.	Test mode	7
4.4.	Support unit used in test configuration and system	8
4.5.	Testing environmental condition	8
4.6.	Measurement uncertainty	8
4.7.	Equipment Used during the Test	9
5.	TEST CONDITIONS AND RESULTS	11
5.1.	Antenna Requirement	11
5.2.	AC Conducted Emission	12
5.3.	Peak Output Power	15
5.4.	Power Spectral Density	16
5.5.	6dB bandwidth	17
5.6.	99% Occupied Bandwidth	18
5.7.	Duty Cycle	19
5.8.	Conducted Band edge and Spurious Emission	20
5.9.	Radiated Band edge Emission	22
5.10.	Radiated Spurious Emission	27
6.	TEST SETUP PHOTOS	37
7.	EXTERANAL AND INTERNAL PHOTOS	39
8.	APPENDIX REPORT	46

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

- [FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- [ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices
- [KDB 558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2019-11-28	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result
5.1	Antenna Requirement	15.203/15.247(c)	PASS
5.2	AC Conducted Emission	15.207	PASS
5.3	Peak Output Power	15.247(b)(3)	PASS
5.4	Power Spectral Density	15.247(e)	PASS
5.5	6dB Bandwidth	15.247(a)(2)	PASS
5.6	99% Occupied Bandwidth	-	PASS ^{*1}
5.7	Duty cycle	-	PASS ^{*1}
5.8	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS
5.9	Radiated Band Edge Emission	15.205/15.209	PASS
5.10	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS

Note:

- The measurement uncertainty is not included in the test result.
- ^{*1}: No requirement on standard, only report these test data.

3. SUMMARY

3.1. Client Information

Applicant:	Simbans Limited
Address:	806, 8th Floor, Tai Tak Industrial Building 2-12 Kwai Fat Road,HONG KONG
Manufacturer:	Simbans Limited
Address:	806, 8th Floor, Tai Tak Industrial Building 2-12 Kwai Fat Road,HONG KONG

3.2. Product Description

Name of EUT:	Excello 10.1 Inch Android Tablet PC
Trade Mark:	Simbans
Model No.:	ExcelloTab
Listed Model(s):	-
Power supply:	DC 3.7V
Adapter :	Model:KA23-0502000DEU Input:100-240Va.c.50/60Hz 0.35A Output:5Vd.c.2000mA
Hardware version:	EM_T6318_V2.0_EM21
Software version:	Base_ExcelloTab_mt8163_Android9_V001_20191121161734

3.3. Radio Specification Description

Support type ^{*2} :	802.11b, 802.11g, 802.11n(HT20), 802.11n(H4T0)
Modulation:	DSSS for 802.11b OFDM for 802.11g/802.11n(HT20)/802.11n(HT40)
Operation frequency:	2412MHz~2462MHz for 802.11b/802.11g/802.11n(HT20) 2422MHz~2452MHz for 802.11n(HT40)
Channel number:	11 for 802.11b/802.11g/802.11n(HT20) 9 for 802.11n(HT40)
Channel separation:	5MHz
Antenna type:	FPCB
Antenna gain:	≥0dBi±0.5 dBi

Note:

*2: only show the RF function associated with this report.

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Qualifications	Type	Accreditation Number
	CNAS	L1225
	A2LA	3902.01
	FCC	762235
	Canada	5377A

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

802.11b/802.11g/802.11n(HT20)		802.11n(HT40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	03	2422
02	2417	04	2427
· :	· :	· :	· :
06	2437	06	2437
· :	· :	· :	· :
10	2457	08	2447
11	2462	09	2452

4.2. Descriptions of Test mode

Preliminary tests were performed in different data rates, final test modes are considering the modulation and worse data rates as below table.

Modulation	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	MCS0
802.11n(HT40)	MCS0

4.3. Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

4.4. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?					
✓ No					
Item	Equipement	Trade Name	Model No.	FCC ID	Power cord
1					
2					

4.5. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.6. Measurement uncertainty

Test Item	Measurement Uncertainty
AC Conducted Emission (150kHz~30MHz)	3.02 dB
Radiated Emission (30MHz~1000MHz)	4.90 dB
Radiated Emissions (1GHz~25GHz)	4.96 dB
Peak Output Power	0.51 dB
Power Spectral Density	0.51 dB
Conducted Spurious Emission	0.51 dB
6dB Bandwidth	70 Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4.7. Equipment Used during the Test

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2019/10/26	2020/10/25
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2019/10/23	2020/10/22
●	Pulse Limiter	R&S	HTWE0033	ESH3-Z2	100499	2019/10/23	2020/10/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLEX 142	EF-NM-BNCM-2M	2019/10/23	2020/10/22
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-6th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2021/09/29
●	EMI Test Receiver	R&S	HTWE0099	ESCI	100900	2019/10/26	2020/10/25
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2018/04/02	2021/04/01
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	546	2017/04/05	2020/04/04
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2019/11/14	2020/11/13
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-01	N/A	N/A	2019/08/21	2020/08/20
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-02	SUCOFLEX 104	501184/4	2019/05/27	2020/05/26
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-7th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	N/A	2018/09/27	2021/09/26
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2019/10/26	2020/10/25
●	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2017/04/01	2020/03/31
●	Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	25841	2017/03/27	2020/03/26
●	Broadband Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2018/10/11	2021/10/11
●	Pre-amplifier	CD	HTWE0071	PAP-0102	12004	2019/11/14	2020/11/13
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2019/05/23	2020/05/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-01	6m 18GHz S Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-02	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-03	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-04	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0121-01	6m 18GHz S Serisa	N/A	2019/05/10	2020/05/09
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

● RF Conducted Method						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	FSV40	100048	2019/10/26	2020/10/25
●	Spectrum Analyzer	Agilent	N9020A	MY50510187	2019/10/26	2020/10/25
○	Radio communication tester	R&S	CMW500	137688-Lv	2019/10/26	2020/10/25

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):


(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

The antenna type is a FPCB antenna, the directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.

I



5.2. AC Conducted Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:


Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

Test Line:

L

**MEASUREMENT RESULT: "GM1911255060_fin"**

11/25/2019 3:13PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.181500	18.00	10.1	64	46.4	QP	L1	GND
0.478500	45.10	10.1	56	11.3	QP	L1	GND
0.852000	40.30	10.1	56	15.7	QP	L1	GND
2.526000	34.70	10.1	56	21.3	QP	L1	GND
6.085500	33.70	10.2	60	26.3	QP	L1	GND
19.108500	31.60	10.2	60	28.4	QP	L1	GND


MEASUREMENT RESULT: "GM1911255060_fin2"

11/25/2019 3:13PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.375000	10.90	10.1	48	37.5	AV	L1	GND
0.487500	29.40	10.1	46	16.8	AV	L1	GND
0.843000	28.70	10.1	46	17.3	AV	L1	GND
2.697000	13.60	10.1	46	32.4	AV	L1	GND
6.927000	19.70	10.2	50	30.3	AV	L1	GND
19.099500	23.30	10.2	50	26.7	AV	L1	GND

Test Line:

N

**MEASUREMENT RESULT: "GM1911255059_fin"**

11/25/2019 3:10PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.163500	45.30	10.1	65	20.0	QP	N	GND
0.483000	42.40	10.1	56	13.9	QP	N	GND
1.725000	31.00	10.1	56	25.0	QP	N	GND
2.787000	28.80	10.1	56	27.2	QP	N	GND
7.705500	26.80	10.2	60	33.2	QP	N	GND
19.621500	30.20	10.2	60	29.8	QP	N	GND

MEASUREMENT RESULT: "GM1911255059_fin2"

11/25/2019 3:10PM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.204000	25.40	10.1	53	28.0	AV	N	GND
0.483000	34.10	10.1	46	12.2	AV	N	GND
0.915000	22.00	10.1	46	24.0	AV	N	GND
3.498000	12.50	10.1	46	33.5	AV	N	GND
6.882000	17.60	10.2	50	32.4	AV	N	GND
19.581000	21.90	10.2	50	28.1	AV	N	GND

5.3. Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10 and KDB 558074 D01 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.
4. Record the measurement data.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data

Please refer to appendix A on the appendix report


5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
Center frequency=DTS channel center frequency
Span =1.5 times the DTS bandwidth
 $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$, $VBW \geq 3 \times RBW$
Sweep time = auto couple
Detector = peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data

Please refer to appendix B on the appendix report


5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency =DTS channel center frequency
Span=2 x DTS bandwidth
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Sweep time= auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data


Please refer to appendix C on the appendix report

5.6. 99% Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = channel center frequency
Span $\geq 1.5 \times \text{OBW}$
RBW = 1%~5%OBW
VBW $\geq 3 \times \text{RBW}$
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data


Please refer to appendix D on the appendix report

5.7. Duty Cycle

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span=zero span, Frequency=centered channel, RBW= 1 MHz, VBW $\geq$ RBW
Sweep=as necessary to capture the entire dwell time,
Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

TEST MODE:

Please refer to the clause 4.2

TEST Data


Please refer to appendix E on the appendix report

5.8. Conducted Band edge and Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure
Center frequency=DTS channel center frequency
The span = 1.5 times the DTS bandwidth.
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum PSD level

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

3. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST Data

Please refer to appendix F on the appendix report


5.9. Radiated Band edge Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
 - a) Span shall wide enough to fully capture the emission being measured
 - b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

 - VBW=10Hz, When duty cycle is no less than 98 percent
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.6 duty cycle.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

Note:

- 1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Margin = Limit – Level
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).

Type	802.11b	Test channel	CH01	Polarity	Horizontal			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	25.59	35.78	61.37	74.00	12.63	Horizontal	PK
2	2390.009	25.08	35.50	60.58	74.00	13.42	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	14.39	35.78	50.17	54.00	3.83	Horizontal	AV
2	2390.009	14.84	35.50	50.34	54.00	3.66	Horizontal	AV

Type	802.11b	Test channel	CH01	Polarity	Vertical			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	24.96	35.78	60.74	74.00	13.26	Vertical	PK
2	2390.009	25.42	35.50	60.92	74.00	13.08	Vertical	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	14.64	35.78	50.42	54.00	3.58	Vertical	AV
2	2390.009	15.20	35.50	50.70	54.00	3.30	Vertical	AV

Type	802.11b	Test channel	CH11	Polarity	Horizontal			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	27.13	35.31	62.44	74.00	11.56	Horizontal	PK
2	2500.000	26.57	35.28	61.85	74.00	12.15	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	15.60	35.31	50.91	54.00	3.09	Horizontal	AV
2	2500.000	15.44	35.28	50.72	54.00	3.28	Horizontal	AV

Type	802.11b	Test channel	CH11	Polarity	Vertical			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	25.14	35.31	60.45	74.00	13.55	Vertical	PK
2	2500.000	25.79	35.28	61.07	74.00	12.93	Vertical	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	15.38	35.31	50.69	54.00	3.31	Vertical	AV
2	2500.000	15.44	35.28	50.72	54.00	3.28	Vertical	AV

Type	802.11g	Test channel	CH01	Polarity	Horizontal			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	25.52	35.78	61.30	74.00	12.70	Horizontal	PK
2	2390.009	25.02	35.50	60.52	74.00	13.48	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	14.73	35.78	50.51	54.00	3.49	Horizontal	AV
2	2390.009	15.13	35.50	50.63	54.00	3.37	Horizontal	AV

Type	802.11g	Test channel	CH01	Polarity	Vertical			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	24.92	35.78	60.70	74.00	13.30	Vertical	PK
2	2390.009	25.21	35.50	60.71	74.00	13.29	Vertical	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	14.65	35.78	50.43	54.00	3.57	Vertical	AV
2	2390.009	15.27	35.50	50.77	54.00	3.23	Vertical	AV

Type	802.11g	Test channel	CH11	Polarity	Horizontal			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	26.41	35.31	61.72	74.00	12.28	Horizontal	PK
2	2500.000	25.22	35.28	60.50	74.00	13.50	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	15.31	35.31	50.62	54.00	3.38	Horizontal	AV
2	2500.000	15.75	35.28	51.03	54.00	3.01	Horizontal	AV

Type	802.11g	Test channel	CH11	Polarity	Vertical			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	25.24	35.31	60.55	74.00	13.45	Vertical	PK
2	2500.000	25.32	35.28	60.60	74.00	13.40	Vertical	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	15.40	35.31	50.71	54.00	3.29	Vertical	AV
2	2500.000	15.48	35.28	50.76	54.00	3.24	Vertical	AV

Type	802.11n(HT20)		Test channel		CH01		Polarity		Horizontal	
Suspected Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector		
1	2310.000	24.80	35.78	60.58	74.00	13.42	Horizontal	PK		
2	2390.009	24.85	35.50	60.35	74.00	13.65	Horizontal	PK		
Suspected Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector		
1	2310.000	14.51	35.78	50.29	54.00	3.71	Horizontal	AV		
2	2390.009	14.90	35.50	50.40	54.00	3.60	Horizontal	AV		

Type	802.11n(HT20)		Test channel		CH01		Polarity		Vertical	
Suspected Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector		
1	2310.000	25.79	35.78	61.57	74.00	12.43	Vertical	PK		
2	2390.009	25.25	35.50	60.75	74.00	13.25	Vertical	PK		
Suspected Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector		
1	2310.000	14.50	35.78	50.28	54.00	3.72	Vertical	AV		
2	2390.009	15.03	35.50	50.53	54.00	3.47	Vertical	AV		

Type	802.11n(HT20)	Test channel	CH11	Polarity	Horizontal			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	26.16	35.31	61.47	74.00	12.53	Horizontal	PK
2	2500.000	25.00	35.28	60.28	74.00	13.72	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	15.26	35.31	50.57	54.00	3.43	Horizontal	AV
2	2500.000	15.82	35.28	51.10	54.00	3.00	Horizontal	AV

Type	802.11n(HT20)	Test channel	CH11	Polarity	Vertical			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	26.24	35.31	61.55	74.00	12.45	Vertical	PK
2	2500.000	27.06	35.28	62.34	74.00	11.66	Vertical	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.514	15.57	35.31	50.88	54.00	3.12	Vertical	AV
2	2500.000	15.40	35.28	50.68	54.00	3.32	Vertical	AV

Type	802.11n(HT40)	Test channel	CH03	Polarity	Horizontal			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	25.17	35.78	60.95	74.00	13.05	Horizontal	PK
2	2390.108	26.09	35.50	61.59	74.00	12.41	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	14.55	35.78	50.33	54.00	3.67	Horizontal	AV
2	2390.108	15.00	35.50	50.50	54.00	3.50	Horizontal	AV

Type	802.11n(HT40)	Test channel	CH03	Polarity	Vertical			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	25.17	35.78	60.95	74.00	13.05	Vertical	PK
2	2390.108	25.70	35.50	61.20	74.00	12.80	Vertical	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2310.000	14.78	35.78	50.56	54.00	3.44	Vertical	AV
2	2390.108	14.89	35.50	50.39	54.00	3.61	Vertical	AV

Type	802.11n(HT40)	Test channel	CH09	Polarity	Horizontal			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.500	25.87	35.31	61.18	74.00	12.82	Horizontal	PK
2	2500.000	27.12	35.28	62.40	74.00	11.60	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.500	15.30	35.31	50.61	54.00	3.39	Horizontal	AV
2	2500.000	15.49	35.28	50.77	54.00	3.23	Horizontal	AV

Type	802.11n(HT40)	Test channel	CH09	Polarity	Vertical			
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.500	25.60	35.31	60.91	74.00	13.09	Vertical	PK
2	2500.000	26.44	35.28	61.72	74.00	12.28	Vertical	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	2483.500	15.27	35.31	50.58	54.00	3.42	Vertical	AV
2	2500.000	15.58	35.28	50.86	54.00	3.14	Vertical	AV

5.10. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40*log(30/3)= Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


➤ 9 kHz ~ 30 MHz



➤ 30 MHz ~ 1 GHz



➤ Above 1 GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;

If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

 - VBW=10Hz, When duty cycle is no less than 98 percent
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.6 duty cycle.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

Note:

- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Margin = Limit – Level
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

TEST DATA FOR 9 kHz ~ 30 MHz


The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.

TEST DATA FOR 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH39 which it was worst case, so only show the worst case's data on this report.

Polarization:

Horizontal


**MEASUREMENT RESULT: "GM1911186115_red"**

11/18/2019 8:50PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
45.520000	19.50	-8.4	40.0	20.5	QP	300.0	281.00	HORIZONTAL
61.040000	18.60	-9.7	40.0	21.4	QP	100.0	231.00	HORIZONTAL
171.620000	19.20	-12.5	43.5	24.3	QP	100.0	114.00	HORIZONTAL
183.260000	20.80	-11.5	43.5	22.7	QP	300.0	321.00	HORIZONTAL
549.920000	27.10	0.2	46.0	18.9	QP	300.0	88.00	HORIZONTAL
953.440000	36.80	8.2	46.0	9.2	QP	300.0	38.00	HORIZONTAL

Polarization:

Vertical

**MEASUREMENT RESULT: "GM1911186116_red"**

11/18/2019 8:53PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
33.880000	24.50	-12.1	40.0	15.5	QP	100.0	23.00	VERTICAL
55.220000	18.70	-8.4	40.0	21.3	QP	100.0	327.00	VERTICAL
99.840000	19.10	-10.3	43.5	24.4	QP	100.0	0.00	VERTICAL
202.660000	22.50	-9.5	43.5	21.0	QP	100.0	161.00	VERTICAL
549.920000	25.80	0.2	46.0	20.2	QP	100.0	276.00	VERTICAL
941.800000	33.70	8.0	46.0	12.3	QP	100.0	23.00	VERTICAL

TEST DATA FOR 1 GHz ~ 25 GHz

Type	802.11b	Test channel	CH00					
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1221.781	35.87	-5.77	30.10	74.00	43.90	Horizontal	PK
2	3176.687	34.31	0.72	35.03	74.00	38.97	Horizontal	PK
3	4840.781	31.87	7.10	38.97	74.00	35.03	Horizontal	PK
4	6957.250	31.61	14.14	45.75	74.00	28.25	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1182.125	36.04	-6.02	30.02	74.00	43.98	Vertical	PK
2	3213.406	34.74	0.68	35.42	74.00	38.58	Vertical	PK
3	5122.781	32.24	8.84	41.08	74.00	32.92	Vertical	PK
4	7052.718	32.06	14.31	46.37	74.00	27.63	Vertical	PK

Type	802.11b				Test channel		CH06	
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1190.937	36.01	-5.93	30.08	74.00	43.92	Horizontal	PK
2	3195.781	34.83	0.82	35.65	74.00	38.35	Horizontal	PK
3	4970.031	31.75	7.65	39.40	74.00	34.60	Horizontal	PK
4	6847.093	31.28	13.62	44.90	74.00	29.10	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1179.187	35.49	-6.05	29.44	74.00	44.56	Vertical	PK
2	3181.093	34.67	0.74	35.41	74.00	38.59	Vertical	PK
3	4715.937	31.83	6.49	38.32	74.00	35.68	Vertical	PK
4	7005.718	31.20	14.18	45.38	74.00	28.62	Vertical	PK

Type	802.11b	Test channel	CH11					
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1214.437	35.33	-5.79	29.54	74.00	44.46	Horizontal	PK
2	3194.312	34.99	0.81	35.80	74.00	38.20	Horizontal	PK
3	4787.906	31.56	6.97	38.53	74.00	35.47	Horizontal	PK
4	7024.812	31.25	14.23	45.48	74.00	28.52	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1221.781	35.69	-5.77	29.92	74.00	44.08	Vertical	PK
2	3084.156	34.94	0.25	35.19	74.00	38.81	Vertical	PK
3	4707.125	31.52	6.43	37.95	74.00	36.05	Vertical	PK
4	7134.968	32.02	14.63	46.65	74.00	27.35	Vertical	PK

Type	802.11g				Test channel		CH00	
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1208.562	36.75	-5.81	30.94	74.00	43.06	Horizontal	PK
2	3195.781	35.03	0.82	35.85	74.00	38.15	Horizontal	PK
3	4814.343	32.21	7.07	39.28	74.00	34.72	Horizontal	PK
4	6938.156	30.80	14.13	44.93	74.00	29.07	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1218.843	35.82	-5.78	30.04	74.00	43.96	Vertical	PK
2	3185.500	34.89	0.76	35.65	74.00	38.35	Vertical	PK
3	4792.312	32.25	7.00	39.25	74.00	34.75	Vertical	PK
4	6886.750	31.78	13.98	45.76	74.00	28.24	Vertical	PK

Type	802.11g				Test channel		CH06	
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1210.031	35.60	-5.80	29.80	74.00	44.20	Horizontal	PK
2	3195.781	36.56	0.82	37.38	74.00	36.62	Horizontal	PK
3	4818.750	31.87	7.07	38.94	74.00	35.06	Horizontal	PK
4	7085.031	31.62	14.39	46.01	74.00	27.99	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1176.250	36.68	-6.08	30.60	74.00	43.40	Vertical	PK
2	3090.031	34.71	0.28	34.99	74.00	39.01	Vertical	PK
3	4830.500	31.76	7.09	38.85	74.00	35.15	Vertical	PK
4	6546.000	31.67	12.81	44.48	74.00	29.52	Vertical	PK

Type	802.11g				Test channel		CH11	
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1189.468	35.97	-5.94	30.03	74.00	43.97	Horizontal	PK
2	3184.031	34.50	0.76	35.26	74.00	38.74	Horizontal	PK
3	4889.250	31.99	7.17	39.16	74.00	34.84	Horizontal	PK
4	6889.687	30.13	14.01	44.14	74.00	29.86	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1212.968	36.39	-5.80	30.59	74.00	43.41	Vertical	PK
2	3194.312	34.92	0.81	35.73	74.00	38.27	Vertical	PK
3	4771.750	32.25	6.86	39.11	74.00	34.89	Vertical	PK
4	6823.593	31.47	13.41	44.88	74.00	29.12	Vertical	PK

Type	802.11n(HT20)				Test channel		CH00	
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1242.343	35.72	-5.72	30.00	74.00	44.00	Horizontal	PK
2	3209.000	34.84	0.73	35.57	74.00	38.43	Horizontal	PK
3	4657.187	32.86	6.12	38.98	74.00	35.02	Horizontal	PK
4	6742.812	31.09	13.35	44.44	74.00	29.56	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1258.500	36.44	-5.68	30.76	74.00	43.24	Vertical	PK
2	3173.750	35.14	0.70	35.84	74.00	38.16	Vertical	PK
3	4768.812	32.50	6.84	39.34	74.00	34.66	Vertical	PK
4	6910.250	30.63	14.11	44.74	74.00	29.26	Vertical	PK

Type	802.11n(HT20)				Test channel		CH06	
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1223.250	35.22	-5.77	29.45	74.00	44.55	Horizontal	PK
2	3043.031	35.82	0.07	35.89	74.00	38.11	Horizontal	PK
3	4663.062	32.50	6.15	38.65	74.00	35.35	Horizontal	PK
4	7325.906	31.27	15.13	46.40	74.00	27.60	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1199.750	36.55	-5.83	30.72	74.00	43.28	Vertical	PK
2	3173.750	35.26	0.70	35.96	74.00	38.04	Vertical	PK
3	4950.937	32.46	7.52	39.98	74.00	34.02	Vertical	PK
4	7327.375	30.64	15.14	45.78	74.00	28.22	Vertical	PK

Type	802.11n(HT20)				Test channel		CH11	
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1312.843	35.71	-5.57	30.14	74.00	43.86	Horizontal	PK
2	3195.781	36.19	0.82	37.01	74.00	36.99	Horizontal	PK
3	5224.125	33.30	8.85	42.15	74.00	31.85	Horizontal	PK
4	7471.312	31.32	15.40	46.72	74.00	27.28	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1207.093	36.12	-5.81	30.31	74.00	43.69	Vertical	PK
2	3201.656	35.44	0.82	36.26	74.00	37.74	Vertical	PK
3	4696.843	32.18	6.36	38.54	74.00	35.46	Vertical	PK
4	6782.468	31.80	13.25	45.05	74.00	28.95	Vertical	PK



Type	802.11n(HT40)				Test channel		CH03	
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1271.718	35.89	-5.64	30.25	74.00	43.75	Horizontal	PK
2	3032.750	36.04	0.02	36.06	74.00	37.94	Horizontal	PK
3	4858.406	32.53	7.13	39.66	74.00	34.34	Horizontal	PK
4	7303.875	30.90	15.06	45.96	74.00	28.04	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1221.781	36.20	-5.77	30.43	74.00	43.57	Vertical	PK
2	3123.812	35.85	0.44	36.29	74.00	37.71	Vertical	PK
3	4779.093	31.95	6.91	38.86	74.00	35.14	Vertical	PK
4	7192.250	32.34	14.95	47.29	74.00	26.71	Vertical	PK

Type	802.11n(HT40)				Test channel		CH06	
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1237.937	35.83	-5.73	30.10	74.00	43.90	Horizontal	PK
2	3179.625	35.45	0.73	36.18	74.00	37.82	Horizontal	PK
3	4787.906	31.74	6.97	38.71	74.00	35.29	Horizontal	PK
4	6863.250	31.24	13.77	45.01	74.00	28.99	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1186.531	36.62	-5.97	30.65	74.00	43.35	Vertical	PK
2	3213.406	35.40	0.68	36.08	74.00	37.92	Vertical	PK
3	4812.875	31.78	7.07	38.85	74.00	35.15	Vertical	PK
4	7466.906	31.28	15.40	46.68	74.00	27.32	Vertical	PK

Type	802.11n(HT40)				Test channel		CH09	
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1208.562	36.08	-5.81	30.27	74.00	43.73	Horizontal	PK
2	3195.781	38.62	0.82	39.44	74.00	34.56	Horizontal	PK
3	4752.656	32.02	6.73	38.75	74.00	35.25	Horizontal	PK
4	6663.500	31.63	13.35	44.98	74.00	29.02	Horizontal	PK
Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	1264.375	36.59	-5.66	30.93	74.00	43.07	Vertical	PK
2	3195.781	35.94	0.82	36.76	74.00	37.24	Vertical	PK
3	4668.937	32.90	6.19	39.09	74.00	34.91	Vertical	PK
4	7478.656	31.38	15.40	46.78	74.00	27.22	Vertical	PK

6. TEST SETUP PHOTOS

Radiated Emission






AC Conducted Emission








7. EXTERANAL AND INTERNAL PHOTOS

External Photo

















Internal Photo










8. APPENDIX REPORT

-----End of Report-----

APPENDIX REPORT

Project No.	SHT1911019301EW	Radio Specification	WIFI 2.4G
Test sample No.	YPHT19110193002	Model No.	T1045L (Simbans)
Start test date	2019/11/18	Finish date	2019/11/18
Temperature	25°C	Humidity	50%
Test Engineer	JiongSheng.Feng	Auditor	




Appendix clause	Test item	Result
A	Conducted Peak Output Power	PASS
B	Power Spectral Density	PASS
C	6 dB Bandwidth	PASS
D	99% Occupied Bandwidth	PASS
E	Duty Cycle	PASS
F	Band edge and Spurious Emissions (conducted)	PASS




Appendix A: Conducted Peak Output Power




Type	Channel	Peak Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
802.11b	01	16.65	14.21	≤30.00	Pass
	06	16.38	13.91		
	11	16.52	14.08		
802.11g	01	19.37	16.42	≤30.00	Pass
	06	19.19	16.33		
	11	19.51	16.66		
802.11n(HT20)	01	19.01	16.03	≤30.00	Pass
	06	19.12	16.11		
	11	19.67	16.67		
802.11n(HT40)	03	19.12	16.15	≤30.00	Pass
	06	19.24	16.32		
	09	19.37	16.47		




Appendix B: Power Spectral Density

Type	Channel	Power Spectral Density (dBm/30KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-2.00	≤8.00	Pass
	06	-2.42		
	11	-2.40		
802.11g	01	-6.14	≤8.00	Pass
	06	-6.26		
	11	-6.67		
802.11n(HT20)	01	-7.32	≤8.00	Pass
	06	-5.51		
	11	-6.09		
802.11n(HT40)	03	-9.33	≤8.00	Pass
	06	-8.56		
	09	-10.08		

Type:	802.11 b
CH01	 Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWI 1.78 ms VBW 100 kHz Mode Auto Sweep Count 100/100 M1[1] 2.416 GHz 2.416099 GHz 2.416 dBm 2.416099 GHz CF 2.412 GHz 1001 pts 1.6 MHz/ Span 16.0 MHz Date: 18/NOV/2019 19:57:24
CH06	 Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWI 1.78 ms VBW 100 kHz Mode Auto Sweep Count 100/100 M1[1] 2.440 GHz 2.440099 GHz 2.440 dBm 2.440099 GHz CF 2.437 GHz 1001 pts 1.6 MHz/ Span 16.0 MHz Date: 18/NOV/2019 19:59:59
CH11	 Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWI 1.78 ms VBW 100 kHz Mode Auto Sweep Count 100/100 M1[1] 2.466 GHz 2.466099 GHz 2.466 dBm 2.466099 GHz CF 2.462 GHz 1001 pts 1.6 MHz/ Span 16.0 MHz Date: 18/NOV/2019 20:02:00

Type:	802.11 g
CH01	 18/NOV/2019 20:05:40
CH06	 18/NOV/2019 20:09:35
CH11	 18/NOV/2019 20:12:01

Type:	802.11n(HT20)
CH01	 Ref Level 20.00 dBm Offset 1.00 dB BW 30 kHz Att 30 dB SWI 279 us (-15 dB) VBW 100 kHz Mode Auto FFT Count 100/100 M1[1] 7.32 dBm 2.4126240 GHz CF 2.412 GHz 1001 pts 2.5 MHz/ Span 25.0 MHz Date: 18/NOV/2019 20:15:43
CH06	 Ref Level 20.00 dBm Offset 1.00 dB BW 30 kHz Att 30 dB SWI 279 us (-15 dB) VBW 100 kHz Mode Auto FFT Count 100/100 M1[1] 5.51 dBm 2.4376240 GHz CF 2.437 GHz 1001 pts 2.5 MHz/ Span 25.0 MHz Date: 18/NOV/2019 20:17:49
CH11	 Ref Level 20.00 dBm Offset 1.00 dB BW 30 kHz Att 30 dB SWI 279 us (-15 dB) VBW 100 kHz Mode Auto FFT Count 100/100 M1[1] 6.09 dBm 2.4626240 GHz CF 2.462 GHz 1001 pts 2.5 MHz/ Span 25.0 MHz Date: 18/NOV/2019 20:18:48

Type:	802.11n(HT40)
CH03	 Ref Level 20.00 dBm Offset 30 dB Att 30 dB SWI 558 uS (-27 ms) BW 100 kHz Mode Auto FFT Count 100/100 1 Frequency Sweep 2.422 GHz 1001 pts 5.5 MHz/ Span 55.0 MHz Date: 18/NOV/2019 20:22:44
CH06	 Ref Level 20.00 dBm Offset 30 dB Att 30 dB SWI 558 uS (-27 ms) BW 100 kHz Mode Auto FFT Count 100/100 1 Frequency Sweep 2.437 GHz 1001 pts 5.5 MHz/ Span 55.0 MHz Date: 18/NOV/2019 20:25:01
CH09	 Ref Level 20.00 dBm Offset 30 dB Att 30 dB SWI 558 uS (-27 ms) BW 100 kHz Mode Auto FFT Count 100/100 1 Frequency Sweep 2.452 GHz 1001 pts 5.5 MHz/ Span 55.0 MHz Date: 18/NOV/2019 20:26:46


Appendix C: 6dB bandwidth

Type	Channel	6dB Bandwidth (MHz)	Limit (kHz)	Result
802.11b	01	9.18	≥500	Pass
	06	9.15		
	11	9.15		
802.11g	01	16.65	≥500	Pass
	06	16.65		
	11	16.65		
802.11n(HT20)	01	17.85	≥500	Pass
	06	17.88		
	11	17.85		
802.11n(HT40)	03	36.42	≥500	Pass
	06	36.42		
	09	36.24		

Type:


802.11 b

CH01




Date: 18/NOV/2019 19:57:09

CH06




Date: 18/NOV/2019 19:58:59

CH11




Date: 18/NOV/2019 20:01:21




Type:

802.11n(HT20)


CH01



CH06




CH11



Type:


802.11n(HT40)

CH03




Date: 18/NOV/2019 20:22:29

CH06



Date: 18/NOV/2019 20:24:20


CH09




Date: 18/NOV/2019 20:27:58

Appendix D: 99% Occupied Bandwidth

Type	Channel	99% Bandwidth (MHz)	Limit (kHz)	Result
802.11b	01	12.20	≥500	Pass
	06	12.26		
	11	12.26		
802.11g	01	17.02	≥500	Pass
	06	16.99		
	11	17.02		
802.11n(HT20)	01	17.80	≥500	Pass
	06	17.77		
	11	17.80		
802.11n(HT40)	03	35.90	≥500	Pass
	06	35.96		
	09	35.96		






Type:		802.11n(HT20)
CH01		

Type:

802.11n(HT40)

CH03



Date: 18/NOV/2019 20:22:39

CH06





Date: 18/NOV/2019 20:24:26

CH09



Date: 18/NOV/2019 20:28:06

Appendix E: Duty Cycle




11b-CH6	 Ref Level 30.00 dBm Att 40 dB RBW 1 MHz VBW 1 MHz SWT 10 ms 1 Zero Span 10 dB CF 2.437 GHz 8000 pts 1.0 ms Date: 18 NOV 2019 20:30:47
11g-CH6	 Ref Level 30.00 dBm Att 40 dB RBW 1 MHz VBW 1 MHz SWT 10 ms 1 Zero Span 10 dB CF 2.437 GHz 8000 pts 1.0 ms Date: 18 NOV 2019 20:31:33


Appendix F: Band edge and Spurious Emissions (conducted)



Test Item:	Bandedge	Type:	802.11 b
CH01			
CH11			




Test Item:	Bandedge	Type:	802.11 n(HT20)
CH01	Spectrum Ref Level 20.00 dBm Offset 1.00 dB = RBW 100 kHz # ATT 30 dB SWT 1.12 ms = VBW 300 kHz Mode Auto Sweep Count 200/300 9.15E3 1 Frequency Sweep <		




Test Item:	Bandedge	Type:	802.11 n(HT40)
CH03			


Test Item:	SE	Type:	802.11b
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			







CH11 Reference level	 Ref Level 30.00 dBm Offset 1.00 dB RBW 100 kHz Att 30.0 dB SWF 1.04 ms VBW 300 kHz Mode Auto Sweep Count 100/100 M[1] -1.25 dBm 2.4614910 GHz CF 2.462 GHz 1001 pts 3.0 MHz/ Span 30.0 MHz Date: 18/NOV/2019 20:02:17
CH11 30MHz~1000MHz	 Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30.0 dB SWF 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 M[1] -6.142 dBm 568.5100 MHz 30.0 MHz 30001 pts 97.0 MHz/ 1.0 GHz Date: 18/NOV/2019 20:02:33
CH11 1GHz~26GHz	 Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30.0 dB SWF 250.0 ms VBW 300 kHz Mode Auto Sweep Count 10/10 M[1] -52.01 dBm 25.060000 GHz 1.0 GHz 30001 pts 2.5 GHz/ 26.0 GHz Date: 18/NOV/2019 20:02:49




Test Item:	SE	Type:	802.11g
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			




CH06 Reference level	
CH06 30MHz~1000MHz	
CH06 1GHz~26GHz	




Test Item:	SE	Type:	802.11n(HT20)
CH01 Reference level		 Ref Level 30.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SWI 1.04 ms VBW 300 kHz Mode Auto Sweep Count 100/100 M1[1] 2.412 GHz 2.4091209 GHz 2.414 GHz 2.4091209 GHz 2.412 GHz 1001 pts 3.0 MHz/ Span 30.0 MHz Date: 18.NOV.2019 20:16:00	
CH01 30MHz~1000MHz		 Ref Level 20.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SWI 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 M1[1] 30.0 MHz 30.0000000 GHz 30.0000000 GHz 30.0 MHz 30001 pts 97.0 MHz/ Span 1.0 GHz Date: 18.NOV.2019 20:16:16	
CH01 1GHz~26GHz		 Ref Level 20.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SWI 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10 M1[1] 1.0 GHz 1.0000000 GHz 1.0000000 GHz 1.0 GHz 30001 pts 2.5 GHz/ Span 26.0 GHz Date: 18.NOV.2019 20:16:33	




CH11 Reference level	 Ref Level 30.00 dBm Offset 1.00 dB RBW 100 kHz Mode Auto Sweep Count 100/100 M1[1] -6.10 dBm 2.4591230 GHz CF 2.462 GHz 1001 pts 3.0 MHz/ Span 30.0 MHz Date: 18/NOV/2019 20:20:05
CH11 30MHz~1000MHz	 Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Mode Auto Sweep Count 10/10 M1[1] -60.41 dBm 552.3760 MHz 30.0 MHz 30001 pts 97.0 MHz/ 1.0 GHz Date: 18/NOV/2019 20:20:22
CH11 1GHz~26GHz	 Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Mode Auto Sweep Count 10/10 M1[1] -51.50 dBm 25.984167 GHz 1.0 GHz 30001 pts 2.5 GHz/ 26.0 GHz Date: 18/NOV/2019 20:20:30


Test Item:	SE	Type:	802.11n(HT40)
CH03 Reference level		 Ref Level 30.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SWI 1.07 ms VBW 300 kHz Mode Auto Sweep Count 100/100 M1[1] -57.72 dBm 2.4205019 GHz CF 2.422 GHz 1001 pts 6.0 MHz/ Span 60.0 MHz Date: 18/NOV/2019 20:23:01	
CH03 30MHz~1000MHz		 Ref Level 20.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SWI 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 M1[1] -60.76 dBm 995.6270 MHz 30.0 MHz 30001 pts 97.0 MHz/ 1.0 GHz Date: 18/NOV/2019 20:23:17	
CH03 1GHz~26GHz		 Ref Level 20.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SWI 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10 M1[1] -52.75 dBm 25.999162 GHz 1.0 GHz 30001 pts 2.5 GHz/ 26.0 GHz Date: 18/NOV/2019 20:23:33	




CH09
Reference level



CH09
30MHz~1000MHz



CH09
1GHz~26GHz



-----End of Report-----