RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2AHY7ZO-011

EUT Specification

EUT	BLUETOOTH SPEAKER				
Frequency band	☐ WLAN: 2.412GHz ~ 2.462GHz				
(Operating)	☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz				
	☐ WLAN: 5.745GHz ~ 5825GHz				
	⊠ Bluetooth 2.402GHz ~ 2.480GHz				
Device category	☐ Portable (<20cm separation)				
	⊠ Mobile (>20cm separation)				
	□ Others				
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm2)				
	□ General Population/Uncontrolled exposure				
	(S=1mW/cm2)				
Antenna diversity	⊠ Single antenna				
	☐ Multiple antennas				
	☐ Tx diversity				
	☐ Rx diversity				
	☐ Tx/Rx diversity				
Antenna gain (Max)	-0.68dBi				
Evaluation applied	⊠MPE Evaluation				
	☐ SAR Evaluation				

Limits for Maximum Permissible Exposure(MPE)

Frequency	Electric Field	Magnetic Field	Power	Average		
Range(MHz)	Strength(V/m)	Strength(A/m)	Density(mW/cm²)	Time		
(A) Limits for Occupational/Control Exposures						
300-1500			F/300	6		
1500-100000			5	6		
(B) Limits for General Population/Uncontrol Exposures						
300-1500			F/1500	6		
1500-100000			1	30		

Friis transmission formula: Pd=(Pout*G)\(4*pi*R²)

Where

Pd= Power density in mW/cm²
Pout=output power to antenna in Mw
G= gain of antenna in linear scale
Pi=3.1416

R= distance between observation point and center of the radiator in cm Pd the limit of MPE, 1mW/cm2. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

For BLE

Channel Frequency	Peak Power
(MHz)	Output(dBm)
2480	3.82

Channel Frequency (MHz)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (nume ric)	Power density at 20cm (mW/cm²)	Power density Limits (mW/cm²)
2480	2.82±1	3.82	2.41	-0.68	0.86	0.0004	1

For DSS With GFSK 2480MHz Worstcase

Channel Frequency	Peak Power
(MHz)	Output(dBm)
2480	3.34

Channel Frequency (MHz)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (nume ric)	Power density at 20cm (mW/cm²)	Power density Limits (mW/cm²)
2480	2.34±1	3.34	2.158	-0.68	0.86	0.0004	1

Signature

Chris Du

EMC Manager

Date: 2019-11-1