

FCC ID: 2AHYINLK

Date: September 23, 2019

Standalone SAR test exclusion considerations: BLE

RF feauture	Mode	Transmitting Frequency(MHz)	Test separation distance (mm) ^{Note2}	ANT Gain (dBi)	Max. power with tune-up tolerance (dBm) ^{Note1}	Max. power with tune-up tolerance (mW)	Power thresholds	SAR test exclusion thresholds
BLE	1Mbps	2480.00	25.34	3.00	3.50	2.2387	0.14	3.00
BLE	2Mbps	2480.00	25.34	3.00	3.50	2.2387	0.14	3.00

Note1. Please refer to the operation description for Max tune-up.

Note2. The minimum separation distance between antenna and user is 25.34mm. Please refer to the attestation letter.

KDB 447498 D01 clasue 4.3.1 Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separationn distances ≤ 50 mm

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] \cdot [$\sqrt{f(GHz)}$] \leq 3.0 for 1g SAR and \leq 7.5 for 10g extremity SAR **Sample Calculation**

 $= [(2.2387 \text{mW} / 25.34 \text{mm})] \text{ X } [\sqrt{2.48 \text{GHz}}] = 0.14$

Note. The calculation result was rounded to two decimal place for comparison.

Conclusion: SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required