


6.4. Band Edge and Conducted Spurious Emission Measurement

6.4.1 Test Specification

| | |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC part22.917(a) and FCC part24.238(a) |
| Test Method: | FCC part2.1051 |
| Operation mode: | Refer to item 4.1 |
| Limit: | -13dBm |
| Test Setup: |  |
| Test Procedure: | <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 v02r02 Section 6.0. 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider. 3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement. 4. The band edges of low and high channels for the highest RF powers were measured. 5. The conducted spurious emission for the whole frequency range was taken. 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band. 7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power $P(\text{Watts}) = P(W) - [43 + 10\log(P)] \text{ (dB)} = [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$ |
| Test Result: | PASS |

6.4.2 Test Instruments

| Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|-------------------|--------------|--------|---------------|-----------------|
| System simulator | R&S | CMU200 | 111382 | Sep. 11, 2016 |
| Spectrum Analyzer | Agilent | N9020A | MY49100060 | Sep. 12, 2016 |
| RF cable | TCT | RE-06 | N/A | Sep. 12, 2016 |
| Antenna Connector | TCT | RFC-01 | N/A | Sep. 12, 2016 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



6.4.3 Test data


Test plots as follows:

| | | | |
|-------|---------|------------|-----|
| Band: | GSM 850 | Test Mode: | GSM |
|-------|---------|------------|-----|

Lower Band Edge Plot on Channel 128



Higher Band Edge Plot on Channel 251




Band:

GSM 1900


Test Mode:

GSM

Lower Band Edge Plot on Channel 512



Higher Band Edge Plot on Channel 810



Band:

GPRS 850

Test Mode:

 GPRS Class 8 Link
(GMSK)

Lower Band Edge Plot on Channel 128



Higher Band Edge Plot on Channel 251



Band:

GPRS 1900


Test Mode:

 GPRS Class 8 Link
(GMSK)

Lower Band Edge Plot on Channel 512



Higher Band Edge Plot on Channel 810



Band:

GSM850

Test Mode:

 EDGE Class 8 Link
(8PSK)

Lower Band Edge Plot on Channel 128



Lower Band Edge Plot on Channel 251



Band:

GPRS 1900

Test Mode:

 EDGE Class 8 Link
(8PSK)

Lower Band Edge Plot on Channel 512



Lower Band Edge Plot on Channel 810



Band:

WCDMA Band V

Test Mode:

 RMC 12.2Kbps Link
(QPSK)

Lower Band Edge Plot on Channel 4132



Higher Band Edge Plot on Channel 4233



Band:

WCDMA Band II

Test Mode:

 RMC 12.2Kbps Link
(QPSK)

Lower Band Edge Plot on Channel 9262



Higher Band Edge Plot on Channel 9538




Band:

GSM 850


Test Mode:

GSM

Conducted Spurious Emission on Channel 128



Conducted Spurious Emission on Channel 190



Conducted Spurious Emission on Channel 251



Band:

GSM 1900

Test Mode:

GSM

Conducted Spurious Emission on Channel 512



Conducted Spurious Emission on Channel 661



Conducted Spurious Emission on Channel 810



Band:

GPRS 850


Test Mode:

 GPRS Class 8 Link
(GMSK)


Conducted Spurious Emission on Channel 128



Conducted Spurious Emission on Channel 190



Conducted Spurious Emission on Channel 251




Band:

GPRS 1900

Test Mode:

 GPRS Class 8 Link
(GMSK)

Conducted Spurious Emission on Channel 512



Conducted Spurious Emission on Channel 661



Conducted Spurious Emission on Channel 810



Band:

GPRS 850

Test Mode:

 EDGE Class 8 Link
(8PSK)

Conducted Spurious Emission on Channel 128



Conducted Spurious Emission on Channel 190



Conducted Spurious Emission on Channel 251



Band:

GPRS 1900

Test Mode:

 EDGE Class 8 Link
(8PSK)

Conducted Spurious Emission on Channel 512



Conducted Spurious Emission on Channel 661



Conducted Spurious Emission on Channel 810



Band:

WCDMA Band V


Test Mode:

 RMC 12.2Kbps Link
(QPSK)

Conducted Spurious Emission on Channel 4132



Conducted Spurious Emission on Channel 4183



Conducted Spurious Emission on Channel 4233



Band:

WCDMA Band II

Test Mode:

 RMC 12.2Kbps Link
(QPSK)

Conducted Spurious Emission on Channel 9262



Conducted Spurious Emission on Channel 9400




Conducted Spurious Emission on Channel 9538



6.5 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

6.5.1 Test Specification

| | | | |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------|
| Test Requirement: | FCC part 22.913(a) and FCC part 24.232(b) | | |
| Test Method: | FCC part 2.1046 | | |
| Receiver Setup: | | GSM/GPRS/EDGE | WCDMA/HSPA |
| | SPAN | 500kHz | 10MHz |
| | RBW | 10kHz | 100kHz |
| | VBW | 30kHz | 300kHz |
| | Detector | RMS | RMS |
| | Trace | Average | Average |
| | Average Type | Power | Power |
| | Sweep Count | 100 | 100 |
| Limit: | GSM850 7W ERP PCS1900 2W EIRP WCDMA Band V: 7W ERP WCDMA Band II: 2W EIRP | | |
| Test Setup: |  | | |
| Test Procedure: | <ol style="list-style-type: none"> The testing follows FCC KDB 971168 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-C-2004 Section 2.2.17. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01. During the measurement, the system simulator parameters were set to force the EUT transmitting at | | |

| | |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | <p>maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.</p> <p>4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-C. The EUT was replaced by dipole antenna (substitution antenna) at the same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$.</p> |
| Test results: | PASS |



6.5.2 Test Instruments

| Radiated Emission Test Site (966) | | | | |
|-----------------------------------------------|------------------------------------|------------|---------------|-----------------|
| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
| ESPI Test Receiver | ROHDE&SCHW ARZ | ESVD | 100008 | Sep. 11, 2016 |
| System simulator | R&S | CMU200 | 111382 | Sep. 11, 2016 |
| Spectrum Analyzer | ROHDE&SCHW ARZ | FSEM | 848597/001 | Sep. 11, 2016 |
| Spectrum Analyzer | Agilent | N9020A | MY49100060 | Sep. 12, 2016 |
| Pre-amplifier | EM Electronics Corporation CO.,LTD | EM30265 | 07032613 | Sep. 11, 2016 |
| Pre-amplifier | HP | 8447D | 2727A05017 | Sep. 11, 2016 |
| Broadband Antenna | Schwarzbeck | VULB9163 | 340 | Sep. 13, 2016 |
| Horn Antenna | Schwarzbeck | BBHA 9120D | 631 | Sep. 13, 2016 |
| Broadband Antenna | Schwarzbeck | VULB9163 | 412 | Sep. 13, 2016 |
| Horn Antenna | Schwarzbeck | BBHA 9120D | 813 | Sep. 13, 2016 |
| Dipole Antenna | TCT | TCT-RF | N/A | Sep. 13, 2016 |
| Coax cable | TCT | RE-low-01 | N/A | Sep. 11, 2016 |
| Coax cable | TCT | RE-high-02 | N/A | Sep. 11, 2016 |
| Coax cable | TCT | RE-low-03 | N/A | Sep. 11, 2016 |
| Coax cable | TCT | RE-High-04 | N/A | Sep. 11, 2016 |
| Antenna Mast | CCS | CC-A-4M | N/A | Sep. 12, 2016 |
| EMI Test Software | Shurples Technology | EZ-EMC | N/A | N/A |
| UNIVERSAL RADIO COMMUNICATION TESTER | CMU200 | R&S | Sep. 12, 2015 | Sep. 11, 2016 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.5.3 Test Data

Test Result of ERP

| GSM850 Radiated Power ERP | | | | |
|---------------------------|-----------|------------------------|-----------|---------|
| Horizontal Polarization | | | | |
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | ERP (dBm) | ERP (W) |
| 824.4 | 13.09 | 21.66 | 32.60 | 1.818 |
| 836.4 | 13.08 | 21.54 | 32.47 | 1.766 |
| 848.8 | 13.60 | 21.46 | 32.91 | 1.953 |
| Vertical Polarization | | | | |
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | ERP (dBm) | ERP (W) |
| 824.4 | 11.26 | 22.42 | 31.53 | 1.422 |
| 836.4 | 11.86 | 22.65 | 32.36 | 1.720 |
| 848.8 | 11.45 | 22.26 | 31.56 | 1.434 |

ERP = LVL (dBm) + Correction Factor (dB) - 2.15

Correction Factor= S.G. Power - Cable loss + Substitution Antenna Gain- SPA. Reading

GPRS850 Radiated Power ERP

| Horizontal Polarization | | | | |
|-------------------------|-----------|------------------------|-----------|---------|
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | ERP (dBm) | ERP (W) |
| 824.4 | 7.47 | 21.66 | 26.98 | 0.499 |
| 836.4 | 7.21 | 21.54 | 26.60 | 0.457 |
| 848.4 | 7.47 | 21.66 | 26.98 | 0.499 |
| Vertical Polarization | | | | |
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | ERP (dBm) | ERP (W) |
| 824.4 | 7.44 | 22.42 | 27.71 | 0.590 |
| 836.4 | 7.17 | 22.65 | 27.67 | 0.585 |
| 848.8 | 7.12 | 22.26 | 27.23 | 0.528 |

ERP = LVL (dBm) + Correction Factor (dB) - 2.15

Correction Factor= S.G. Power - Cable loss + Substitution Antenna Gain- SPA. Reading

EDGE850 Radiated Power ERP
Horizontal Polarization

| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | ERP (dBm) | ERP (W) |
|-----------------|-----------|------------------------|-----------|---------|
| 824.4 | 5.36 | 21.66 | 24.87 | 0.307 |
| 836.4 | 5.61 | 21.54 | 25.00 | 0.316 |
| 824.4 | 5.77 | 21.46 | 25.08 | 0.322 |

Vertical Polarization

| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | ERP (dBm) | ERP (W) |
|-----------------|-----------|------------------------|-----------|---------|
| 824.4 | 6.14 | 22.42 | 26.41 | 0.437 |
| 836.4 | 6.43 | 22.65 | 26.93 | 0.494 |
| 848.8 | 6.34 | 22.26 | 26.45 | 0.442 |

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP
Horizontal Polarization

| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | ERP (dBm) | ERP (W) |
|-----------------|-----------|------------------------|-----------|---------|
| 826.4 | 3.18 | 21.54 | 22.57 | 0.181 |
| 836.4 | 2.59 | 21.48 | 21.92 | 0.156 |
| 846.6 | 2.65 | 21.62 | 22.12 | 0.163 |

Vertical Polarization

| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | ERP (dBm) | ERP (W) |
|-----------------|-----------|------------------------|-----------|---------|
| 826.4 | 2.51 | 22.74 | 23.10 | 0.204 |
| 836.4 | 2.24 | 22.62 | 22.71 | 0.187 |
| 846.6 | 2.11 | 22.56 | 22.52 | 0.179 |

* $ERP = LVL (dBm) + Correction Factor (dB) - 2.15$

Correction Factor= S.G. Power - Cable loss + Substitution Antenna Gain- SPA. Reading

Test Result of EIRP

| GSM1900 Radiated Power EIRP | | | | |
|-----------------------------|-----------|------------------------|------------|----------|
| Horizontal Polarization | | | | |
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | EIRP (dBm) | EIRP (W) |
| 1850.2 | -2.11 | 30.15 | 28.04 | 0.637 |
| 1880 | -2.18 | 31.01 | 28.83 | 0.764 |
| 1909.8 | -1.72 | 30.34 | 28.62 | 0.728 |
| Vertical Polarization | | | | |
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | EIRP (dBm) | EIRP (W) |
| 1850.2 | -2.95 | 30.52 | 27.57 | 0.571 |
| 1880 | -2.87 | 31.47 | 28.60 | 0.724 |
| 1909.8 | -2.38 | 30.67 | 28.29 | 0.675 |

EIRP = LVL (dBm) + Correction Factor (dB)

Correction Factor= S.G. Power - Cable loss + Substitution Antenna Gain- SPA. Reading

GPRS1900 (class 8) Radiated Power EIRP

| Horizontal Polarization | | | | |
|-------------------------|-----------|------------------------|------------|----------|
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | EIRP (dBm) | EIRP (W) |
| 1850.2 | -6.67 | 30.15 | 23.48 | 0.223 |
| 1880 | -6.53 | 31.01 | 24.48 | 0.281 |
| 1909.8 | -6.39 | 30.34 | 23.95 | 0.248 |
| Vertical Polarization | | | | |
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | EIRP (dBm) | EIRP (W) |
| 1850.2 | -6.78 | 30.52 | 23.74 | 0.237 |
| 1880 | -6.26 | 31.47 | 25.21 | 0.332 |
| 1909.8 | -6.67 | 30.67 | 24.00 | 0.251 |

EIRP = LVL (dBm) + Correction Factor (dB)

Correction Factor= S.G. Power - Cable loss + Substitution Antenna Gain- SPA. Reading

| EDGE1900 (class 8) Radiated Power EIRP | | | | |
|----------------------------------------|-----------|------------------------|------------|----------|
| Horizontal Polarization | | | | |
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | EIRP (dBm) | EIRP (W) |
| 1850.2 | -7.25 | 30.15 | 22.90 | 0.195 |
| 1880 | -7.25 | 31.01 | 23.76 | 0.238 |
| 1909.8 | -7.38 | 30.34 | 22.96 | 0.198 |
| Vertical Polarization | | | | |
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | EIRP (dBm) | EIRP (W) |
| 1850.2 | -7.03 | 30.52 | 23.49 | 0.224 |
| 1880 | -7.08 | 31.47 | 24.39 | 0.275 |
| 1909.8 | -7.13 | 30.67 | 23.54 | 0.226 |



| WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP | | | | |
|--------------------------------------------------|-----------|------------------------|------------|----------|
| Horizontal Polarization | | | | |
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | EIRP (dBm) | EIRP (W) |
| 1852.4 | -14.24 | 31.78 | 17.54 | 0.057 |
| 1880 | -14.23 | 31.63 | 17.40 | 0.055 |
| 1907.6 | -14.51 | 31.75 | 17.24 | 0.053 |
| Vertical Polarization | | | | |
| Frequency (MHz) | LVL (dBm) | Correction Factor (dB) | EIRP (dBm) | EIRP (W) |
| 1852.4 | -15.24 | 31.85 | 16.61 | 0.046 |
| 1880 | -15.37 | 31.39 | 16.02 | 0.040 |
| 1907.6 | -15.49 | 31.67 | 16.18 | 0.041 |

* EIRP = LVL (dBm) + Correction Factor (dB)

Correction Factor= S.G. Power - Cable loss + Substitution Antenna Gain- SPA. Reading

6.6 Field Strength of Spurious Radiation Measurement

6.6.1 Test Specification

| | |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC part 22.917(a) and FCC part 24.238(a) |
| Test Method: | FCC part 2.1053 |
| Operation mode: | Refer to item 4.1 |
| Limit: | -13dBm |
| Test setup: | <p>For 30MHz~1GHz</p>  <p>Above 1GHz</p>  |
| Test Procedure: | <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12. 2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground. 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower. 4. The table was rotated 360 degrees to determine the position of the highest spurious emission. |

| | |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | <p>5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.</p> <p>6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.</p> <p>7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.</p> <p>8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.</p> <p>9. Taking the record of output power at antenna port.</p> <p>10. Repeat step 7 to step 8 for another polarization.</p> <p>11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain</p> <p>12. ERP (dBm) = EIRP - 2.15</p> <p>13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.</p> <p>14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)</p> $= P(W) - [43 + 10\log(P)] \text{ (dB)}$ $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$ $= -13 \text{ dBm.}$ |
| Test results: | PASS |



6.6.2 Test Instruments

| Radiated Emission Test Site (966) | | | | |
|-----------------------------------|------------------------------------|------------|---------------|-----------------|
| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
| ESPI Test Receiver | ROHDE&SCHW ARZ | ESVD | 100008 | Sep. 11, 2016 |
| System simulator | R&S | CMU200 | 111382 | Sep. 11, 2016 |
| Spectrum Analyzer | ROHDE&SCHW ARZ | FSEM | 848597/001 | Sep. 11, 2016 |
| Spectrum Analyzer | Agilent | N9020A | MY49100060 | Sep. 12, 2016 |
| Pre-amplifier | EM Electronics Corporation CO.,LTD | EM30265 | 07032613 | Sep. 11, 2016 |
| Pre-amplifier | HP | 8447D | 2727A05017 | Sep. 11, 2016 |
| Loop antenna | ZHINAN | ZN30900A | 12024 | Sep. 13, 2016 |
| Broadband Antenna | Schwarzbeck | VULB9163 | 340 | Sep. 13, 2016 |
| Horn Antenna | Schwarzbeck | BBHA 9120D | 631 | Sep. 13, 2016 |
| Horn Antenna | Schwarzbeck | BBHA 9170 | 373 | Sep. 13, 2016 |
| Dipole Antenna | TCT | TCT-RF | N/A | Sep. 13, 2016 |
| Coax cable | TCT | RE-low-01 | N/A | Sep. 11, 2016 |
| Coax cable | TCT | RE-high-02 | N/A | Sep. 11, 2016 |
| Coax cable | TCT | RE-low-03 | N/A | Sep. 11, 2016 |
| Coax cable | TCT | RE-High-04 | N/A | Sep. 11, 2016 |
| Antenna Mast | CCS | CC-A-4M | N/A | Sep. 12, 2016 |
| EMI Test Software | Shurples Technology | EZ-EMC | N/A | N/A |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.6.3 Test Data

Frequency Range (9 kHz-30MHz)

| Frequency (MHz) | Level@3m (dB μ V/m) | Limit@3m (dB μ V/m) |
|-----------------|-------------------------|-------------------------|
| -- | -- | -- |
| -- | -- | -- |
| -- | -- | -- |
| -- | -- | -- |

Note: 1. Emission Level=Reading+ Cable loss-Antenna factor-Amp factor

2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement



Above 1GHz

| Band | GSM 850 | | Test channel: | Lowest |
|-----------------|----------------------------------------------------------------------------------|-------------|---------------|---------|
| Test mode: | GPRS Link (GPRS Class 8) | | Temperature : | 25°C |
| | Relative Humidity: | | | 56% |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | | |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| | Polarization | Level (dBm) | | |
| 1648.40 | Vertical | -43.26 | -13.00 | PASS |
| 2472.60 | V | -40.29 | | |
| 3296.80 | V | -50.18 | | |
| 1648.40 | Horizontal | -43.61 | | |
| 2472.60 | H | -39.54 | | |
| 3296.80 | H | -52.09 | | |
| Band | GSM 850 | | Test channel: | Middle |
| Test mode: | GPRS Link (GPRS Class 8) | | Temperature : | 25°C |
| | Relative Humidity: | | | 56% |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | | |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| | Polarization | Level (dBm) | | |
| 1673.20 | Vertical | -42.06 | -13.00 | PASS |
| 2509.80 | V | -43.94 | | |
| 3346.40 | V | -51.46 | | |
| 1673.20 | Horizontal | -40.28 | | |
| 2509.80 | H | -41.43 | | |
| 3346.40 | H | -51.22 | | |
| Band | GSM 850 | | Test channel: | Highest |
| Test mode: | GPRS Link (GPRS Class 8) | | Temperature : | 25°C |
| | Relative Humidity: | | | 56% |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | | |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| | Polarization | Level (dBm) | | |
| 1697.60 | Vertical | -41.34 | -13.00 | PASS |
| 2546.40 | V | -42.64 | | |
| 3395.20 | V | -51.73 | | |
| 1697.60 | Horizontal | -42.46 | | |
| 2546.40 | H | -41.98 | | |
| 3395.20 | H | -52.41 | | |

| Band | PCS 1900 | | Test channel: | Lowest |
|-------------------|----------------------------------------------------------------------------------|--------|---------------------------|----------------|
| Test mode: | GPRS Link (Class 8) | | Temperature : | 25°C |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | Relative Humidity: | 56% |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 3700.40 | Vertical | -48.36 | -13.00 | PASS |
| 5550.60 | V | -46.53 | | |
| 7400.80 | V | -51.95 | | |
| 3700.40 | Horizontal | -48.29 | | |
| 5550.60 | H | -51.24 | | |
| 7400.80 | H | -51.61 | | |
| Test mode: | PCS 1900 | | Test channel: | Middle |
| Test mode: | GPRS Link (Class 8) | | Temperature : | 25°C |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | Relative Humidity: | 56% |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 3760.00 | Vertical | -48.59 | -13.00 | PASS |
| 5640.00 | V | -54.26 | | |
| 7520.00 | V | -42.65 | | |
| 3760.00 | Horizontal | -46.37 | | |
| 5640.00 | H | -54.33 | | |
| 7520.00 | H | -54.15 | | |
| Test mode: | PCS 1900 | | Test channel: | Highest |
| Test mode: | GPRS Link (Class 8) | | Temperature : | 25°C |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | Relative Humidity: | 56% |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 3819.60 | Vertical | -46.38 | -13.00 | PASS |
| 5729.40 | V | -49.62 | | |
| 7639.20 | V | -51.56 | | |
| 3819.60 | Horizontal | -49.61 | | |
| 5729.40 | H | -53.26 | | |
| 7639.20 | H | -53.31 | | |

| Band | GSM 850 | | Test channel: | Lowest |
|-----------------|----------------------------------------------------------------------------------|--------|--------------------|---------|
| Test mode: | EDGE Link (EDGE Class 8) | | Temperature : | 25°C |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | Relative Humidity: | 56% |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 1648.40 | Vertical | -43.43 | -13.00 | PASS |
| 2472.60 | V | -40.46 | | |
| 3296.80 | V | -50.26 | | |
| 1648.40 | Horizontal | -43.94 | | |
| 2472.60 | H | -39.53 | | |
| 3296.80 | H | -51.93 | | |
| Band | GSM 850 | | Test channel: | Middle |
| Test mode: | EDGE Link (EDGE Class 8) | | Temperature : | 25°C |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | Relative Humidity: | 56% |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 1673.20 | Vertical | -42.07 | -13.00 | PASS |
| 2509.80 | V | -43.80 | | |
| 3346.40 | V | -51.48 | | |
| 1673.20 | Horizontal | -40.70 | | |
| 2509.80 | H | -41.33 | | |
| 3346.40 | H | -51.08 | | |
| Band | GSM 850 | | Test channel: | Highest |
| Test mode: | EDGE Link (EDGE Class 8) | | Temperature : | 25°C |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | Relative Humidity: | 56% |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 1697.60 | Vertical | -41.87 | -13.00 | PASS |
| 2546.40 | V | -42.79 | | |
| 3395.20 | V | -51.62 | | |
| 1697.60 | Horizontal | -42.74 | | |
| 2546.40 | H | -41.99 | | |
| 3395.20 | H | -52.32 | | |

| Band | PCS 1900 | | Test channel: | Lowest |
|-----------------|----------------------------------------------------------------------------------|-------------|--------------------|---------|
| Test mode: | EDGE Link (Class 8) | | Temperature : | 25°C |
| | | | Relative Humidity: | 56% |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | | |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 3700.40 | Polarization | Level (dBm) | | |
| 3700.40 | Vertical | -49.07 | -13.00 | PASS |
| 5550.60 | V | -46.47 | | |
| 7400.80 | V | -52.21 | | |
| 3700.40 | Horizontal | -48.46 | | |
| 5550.60 | H | -51.11 | | |
| 7400.80 | H | -52.06 | | |
| Test mode: | PCS 1900 | | Test channel: | Middle |
| Test mode: | EDGE Link (Class 8) | | Temperature : | 25°C |
| | | | Relative Humidity: | 56% |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | | |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 3760.00 | Polarization | Level (dBm) | | |
| 3760.00 | Vertical | -48.93 | -13.00 | PASS |
| 5640.00 | V | -54.48 | | |
| 7520.00 | V | -42.98 | | |
| 3760.00 | Horizontal | -46.32 | | |
| 5640.00 | H | -54.35 | | |
| 7520.00 | H | -54.17 | | |
| Test mode: | PCS 1900 | | Test channel: | Highest |
| Test mode: | EDGE Link (Class 8) | | Temperature : | 25°C |
| | | | Relative Humidity: | 56% |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | | |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 3819.60 | Polarization | Level (dBm) | | |
| 3819.60 | Vertical | -46.32 | -13.00 | PASS |
| 5729.40 | V | -49.86 | | |
| 7639.20 | V | -51.88 | | |
| 3819.60 | Horizontal | -50.14 | | |
| 5729.40 | H | -53.76 | | |
| 7639.20 | H | -53.93 | | |

| Band | WCDMA Band V | | Test channel: | Lowest |
|-------------------|---------------------|----------------------------------------------------------------------------------|----------------------|---------------------------|
| Test mode: | | RMC 12.2Kbps Link (QPSK) | | Temperature : 25°C |
| Note: | | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 1652.80 | Polarization | Level (dBm) | | |
| 1652.80 | Vertical | -53.19 | -13.00 | PASS |
| 2479.20 | V | -52.91 | | |
| 3305.60 | V | -53.06 | | |
| 1652.80 | Horizontal | -54.72 | | |
| 2479.20 | H | -52.15 | | |
| 3305.60 | H | -54.50 | | |
| Test mode: | WCDMA Band V | | Test channel: | Middle |
| Test mode: | | RMC 12.2Kbps Link (QPSK) | | Temperature : 25°C |
| Note: | | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 1673.20 | Polarization | Level (dBm) | | |
| 1673.20 | Vertical | -56.18 | -13.00 | PASS |
| 2509.80 | V | -51.45 | | |
| 3346.40 | V | -53.54 | | |
| 1673.20 | Horizontal | -53.16 | | |
| 2509.80 | H | -51.80 | | |
| 3346.40 | H | -54.45 | | |
| Test mode: | WCDMA Band V | | Test channel: | Highest |
| Test mode: | | RMC 12.2Kbps Link (QPSK) | | Temperature : 25°C |
| Note: | | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 1693.20 | Polarization | Level (dBm) | | |
| 1693.20 | Vertical | -52.49 | -13.00 | PASS |
| 2539.80 | V | -53.59 | | |
| 3386.40 | V | -53.31 | | |
| 1693.20 | Horizontal | -53.51 | | |
| 2539.80 | H | -51.03 | | |
| 3386.40 | H | -53.59 | | |

| Band | WCDMA Band II | | Test channel: | Lowest |
|-------------------|----------------------------------------------------------------------------------|--------|---------------------------|----------------|
| Test mode: | RMC 12.2Kbps Link (QPSK) | | Temperature : | 25°C |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | Relative Humidity: | 56% |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 3704.80 | Vertical | -51.99 | -13.00 | PASS |
| 5557.20 | V | -53.18 | | |
| 7409.60 | V | -53.07 | | |
| 3704.80 | Horizontal | -53.97 | | |
| 5557.20 | H | -52.39 | | |
| 7409.60 | H | -53.10 | | |
| Test mode: | WCDMA Band II | | Test channel: | Middle |
| Test mode: | RMC 12.2Kbps Link (QPSK) | | Temperature : | 25°C |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | Relative Humidity: | 56% |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 3760.00 | Vertical | -53.77 | -13.00 | PASS |
| 5640.00 | V | -52.68 | | |
| 7520.00 | V | -52.71 | | |
| 3760.00 | Horizontal | -54.77 | | |
| 5640.00 | H | -51.39 | | |
| 7520.00 | H | -53.30 | | |
| Test mode: | WCDMA Band II | | Test channel: | Highest |
| Test mode: | RMC 12.2Kbps Link (QPSK) | | Temperature : | 25°C |
| Note: | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | Relative Humidity: | 56% |
| Frequency (MHz) | Spurious Emission | | Limit (dBm) | Result |
| 3815.20 | Vertical | -56.05 | -13.00 | PASS |
| 5722.80 | V | -52.34 | | |
| 7630.40 | V | -52.03 | | |
| 3815.20 | Horizontal | -52.92 | | |
| 5722.80 | H | -52.01 | | |
| 7630.40 | H | -54.80 | | |

6.7 Frequency Stability Measurement

6.7.1 Test Specification

| | |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part 2.1055(a)(1)(b) |
| Test Method: | FCC Part 2.1055(a)(1)(b) |
| Operation mode: | Refer to item 4.1 |
| Limit: | ±2.5 ppm |
| Test Setup: | |
| Test Procedure: | <p>Test Procedures for Temperature Variation</p> <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 v02r02 Section 9.0. 2. The EUT was set up in the thermal chamber and connected with the system simulator. 3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute. 4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute. <p>Test Procedures for Voltage Variation</p> <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 v02r02 Section 9.0. 2. The EUT was placed in a temperature chamber at $25\pm5^{\circ}\text{C}$ and connected with the system simulator. 3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT. 4. The variation in frequency was measured for the worst case. |
| Test Result: | PASS |

6.7.2 Test Instruments

| Equipment | Manufacturer | Model | Serial Number | Calibration Due |
|------------------|--------------|--------|---------------|-----------------|
| System simulator | R&S | CMU200 | 111382 | Sep. 11, 2016 |

| | | | | |
|-------------------|-----|--------|-----|---------------|
| RF cable | TCT | RE-06 | N/A | Sep. 12, 2016 |
| Antenna Connector | TCT | RFC-01 | N/A | Sep. 12, 2016 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



6.7.3 Test Data

Test Result of Temperature Variation

| Band : | GSM 850 | Channel: | 190 |
|------------------|--------------------------|---------------------------|----------|
| Limit (ppm) : | 2.5ppm | Frequency: | 836.6MHz |
| Temperature (°C) | Frequency Deviation (Hz) | Frequency Deviation (ppm) | Result |
| 50 | 16 | 0.019 | PASS |
| 40 | 27 | 0.032 | |
| 30 | 13 | 0.016 | |
| 20 | 36 | 0.043 | |
| 10 | 37 | 0.044 | |
| 0 | 47 | 0.056 | |
| -10 | 40 | 0.048 | |
| -20 | 35 | 0.042 | |
| -30 | 44 | 0.053 | |

| Band : | PCS 1900 | Channel: | 661 |
|------------------|--------------------------|---------------------------|---------|
| Limit (ppm) : | Note | Frequency: | 1880MHz |
| Temperature (°C) | Frequency Deviation (Hz) | Frequency Deviation (ppm) | Result |
| 50 | 47 | 0.025 | PASS |
| 40 | 45 | 0.024 | |
| 30 | 43 | 0.023 | |
| 20 | 43 | 0.023 | |
| 10 | 27 | 0.014 | |
| 0 | 26 | 0.014 | |
| -10 | 37 | 0.020 | |
| -20 | 22 | 0.012 | |
| -30 | 36 | 0.019 | |

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

| | | | |
|-------------------------|---------------------------------|----------------------------------|-----------------|
| Band : | EDGE 850 | Channel: | 190 |
| Limit (ppm) : | 2.5ppm | Frequency: | 836.6MHz |
| Temperature (°C) | Frequency Deviation (Hz) | Frequency Deviation (ppm) | Result |
| 50 | 29 | 0.035 | |
| 40 | 28 | 0.033 | |
| 30 | 14 | 0.017 | |
| 20 | 29 | 0.035 | |
| 10 | 32 | 0.038 | PASS |
| 0 | 43 | 0.051 | |
| -10 | 30 | 0.036 | |
| -20 | 46 | 0.055 | |
| -30 | 41 | 0.049 | |

| | | | |
|-------------------------|---------------------------------|----------------------------------|----------------|
| Band : | EDGE 1900 | Channel: | 661 |
| Limit (ppm) : | Note | Frequency: | 1880MHz |
| Temperature (°C) | Frequency Deviation (Hz) | Frequency Deviation (ppm) | Result |
| 50 | 49 | 0.026 | |
| 40 | 46 | 0.024 | |
| 30 | 35 | 0.019 | |
| 20 | 38 | 0.020 | |
| 10 | 38 | 0.020 | PASS |
| 0 | 20 | 0.011 | |
| -10 | 31 | 0.016 | |
| -20 | 22 | 0.012 | |
| -30 | 43 | 0.023 | |

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

| Band : | WCDMA Band V | Channel: | 4183 |
|------------------|--------------------------|---------------------------|----------|
| Limit (ppm) : | 2.5ppm | Frequency: | 836.6MHz |
| Temperature (°C) | Frequency Deviation (Hz) | Frequency Deviation (ppm) | Result |
| 50 | 16 | 0.019 | PASS |
| 40 | 27 | 0.032 | |
| 30 | 15 | 0.018 | |
| 20 | 32 | 0.038 | |
| 10 | 33 | 0.039 | |
| 0 | 38 | 0.045 | |
| -10 | 44 | 0.053 | |
| -20 | 36 | 0.043 | |
| -30 | 32 | 0.038 | |

| Band : | WCDMA Band II | Channel: | 9400 |
|------------------|--------------------------|---------------------------|---------|
| Limit (ppm) : | Note | Frequency: | 1880MHz |
| Temperature (°C) | Frequency Deviation (Hz) | Frequency Deviation (ppm) | Result |
| 50 | 43 | 0.023 | PASS |
| 40 | 51 | 0.027 | |
| 30 | 38 | 0.020 | |
| 20 | 35 | 0.019 | |
| 10 | 40 | 0.021 | |
| 0 | 14 | 0.007 | |
| -10 | 40 | 0.021 | |
| -20 | 20 | 0.011 | |
| -30 | 39 | 0.021 | |

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Test Result of Voltage Variation

| Band & Channel | Mode | Voltage (Volt) | Deviation (ppm) | Limit (ppm) | Result |
|----------------------------|-----------------|----------------|-----------------|-------------|--------|
| GSM 850 CH190 | GSM | 4.2 | 0.035 | 2.5 | |
| | | 3.7 | 0.022 | | |
| | | BEP | 0.015 | | |
| GSM 850 CH190 | GPRS | 4.2 | 0.031 | 2.5 | |
| | | 3.7 | 0.019 | | |
| | | BEP | 0.019 | | |
| GSM 850 CH190 | EDGE | 4.2 | 0.012 | 2.5 | |
| | | 3.7 | 0.009 | | |
| | | BEP | 0.001 | | |
| GSM 1900 CH661 | GSM | 4.2 | 0.013 | (Note 3.) | PASS |
| | | 3.7 | 0.001 | | |
| | | BEP | -0.004 | | |
| GSM 1900 CH661 | GPRS | 4.2 | -0.003 | (Note 3.) | |
| | | 3.7 | 0.011 | | |
| | | BEP | 0.017 | | |
| GSM 1900 CH661 | EDGE | 4.2 | 0.002 | (Note 3.) | |
| | | 3.7 | 0.014 | | |
| | | BEP | 0.02 | | |
| WCDMA Band V CH4182 | RMC 12.2Kbps | 4.2 | 0.019 | 2.5 | |
| | | 3.7 | 0.019 | | |
| | | BEP | 0.026 | | |
| WCDMA Band II CH9400 | RMC 12.2Kbps | 4.2 | 0.006 | (Note 3.) | |
| | | 3.7 | 0.024 | | |
| | | BEP | 0.014 | | |

Note:

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.5 V.
3. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

*****END OF REPORT*****