

FCC CERTIFICATION TEST REPORT

FOR

Applicant	:	PEAG, LLC dba JLab Audio
Address	:	5927 Landau Ct. Carlsbad, CA 92008, USA
Equipment under Test	:	TWS Earbuds
Model No.	:	JBuds Air Pro ANC
Trade Mark	:	JLab
FCC ID	:	2AHYV-JAPNC
Manufacturer	:	PEAG, LLC dba JLab Audio
Address	:	5927 Landau Ct. Carlsbad, CA 92008, USA

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

	Test report declares.....	4
1.	Summary of Test Results.....	6
2.	General Test Information	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT.....	8
2.3.	Assistant equipment used for test.....	8
2.4.	Block diagram of EUT configuration for test	8
2.5.	Deviations of test standard.....	8
2.6.	Test environment conditions	9
2.7.	Test laboratory	9
2.8.	Measurement uncertainty.....	9
3.	Equipment Used During Test.....	10
4.	Maximum Peak Output Power	11
4.1.	Block diagram of test setup.....	11
4.2.	Limits	11
4.3.	Test procedure	11
4.4.	Test result.....	11
4.5.	Original test data	12
5.	20 dB Bandwidth and 99% Bandwidth.....	19
5.1.	Block diagram of test setup.....	19
5.2.	Limits	19
5.3.	Test procedure	19
5.4.	Test result.....	19
5.5.	Original test data	20
6.	Carrier Frequency Separation.....	34
6.1.	Block diagram of test setup.....	34
6.2.	Limits	34
6.3.	Test procedure	34
6.4.	Test result.....	34
6.5.	Original test data	35
7.	Number of Hopping Channel	38
7.1.	Block diagram of test setup.....	38
7.2.	Limits	38
7.3.	Test procedure	38
7.4.	Test result.....	38
7.5.	Original test data	39
8.	Dwell Time.....	42

8.1.	Block diagram of test setup.....	42
8.2.	Limits	42
8.3.	Test procedure	42
8.4.	Test result.....	42
8.5.	Original test data	43
9.	Band Edge Compliance (Conducted Method)	56
9.1.	Block diagram of test setup.....	56
9.2.	Limit.....	56
9.3.	Test result.....	56
9.4.	Test procedure	56
9.5.	Original test data	57
10.	RF Conducted Spurious Emissions	66
10.1.	Block diagram of test setup.....	66
10.2.	Limits	66
10.3.	Test procedure	66
10.4.	Test result.....	67
10.5.	Original test data	67
11.	Radiated Emission	86
11.1.	Block diagram of test setup.....	86
11.2.	Limit.....	87
11.3.	Test Procedure.....	88
11.4.	Test result.....	90
12.	Band Edge Compliance (Radiated Method)	107
12.1.	Block diagram of test setup.....	107
12.2.	Limit.....	107
12.3.	Test Procedure.....	107
12.4.	Test result.....	107
13.	Power Line Conducted Emission	132
13.1.	Block diagram of test setup.....	132
13.2.	Power line conducted emission limits	132
13.3.	Test procedure	132
13.4.	Test result.....	133
14.	Antenna Requirements	138
14.1.	Limit.....	138
14.2.	Result	138
15.	Test Setup Photograph	139
16.	Photos of the EUT	142

Test Report Declare

Applicant	:	PEAG, LLC dba JLab Audio
Address	:	5927 Landau Ct. Carlsbad, CA 92008, USA
Equipment under Test	:	TWS Earbuds
Model No.	:	JBuds Air Pro ANC
Trade Mark	:	JLab
Manufacturer	:	PEAG, LLC dba JLab Audio
Address	:	5927 Landau Ct. Carlsbad, CA 92008, USA

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C.

Test Procedure Used:

ANSI C63.10:2013.

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No.:	DDT-R22120512-2E01		
Date of Receipt:	Feb. 09, 2023	Date of Test:	Feb. 09, 2023 ~ Mar. 08, 2023

Prepared By:**Johnny Wang/Engineer****Approved By:****Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Mar. 08, 2023	

1. Summary of Test Results

Description of Test Item	Standard	Verdict
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10:2013	Pass
20 dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.247(a)(1) ANSI C63.10:2013	Pass
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10:2013	Pass
Number of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10:2013	Pass
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10:2013	Pass
RF Conducted Spurious Emissions	FCC Part 15: 15.247(d)	Pass
Radiated Emission	FCC Part 15: 15.205(a) FCC Part 15: 15.209(a) FCC Part 15: 15.247(d) ANSI C63.10:2013	Pass
Band Edge Compliance	FCC Part 15: 15.205(a) FCC Part 15: 15.209(a) FCC Part 15: 15.247(d) ANSI C63.10:2013	Pass
Power Line Conducted Emissions	FCC Part 15: 15.207(a) ANSI C63.10:2013	Pass
Antenna Requirement	FCC Part 15: 15.203	Pass

2. General Test Information

2.1. Description of EUT

EUT* Name	: TWS Earbuds
Model Number	: JBuds Air Pro ANC
EUT Function Description	: Please reference user manual of this device
Power supply	: Charging case: DC 5V by external AC Adapter or 3.7V built-in lithium battery Wireless Headphones: DC 3.7V built-in lithium battery
Radio Specification	: Bluetooth V5.0
Operation Frequency	: 2402 MHz - 2480 MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data Rate	: 1 Mbps, 2 Mbps, 3 Mbps
Antenna Gain	: Left side: -2.05 dBi Right side: -2.05 dBi
Sample Number	: S22120512-02 for conductive, S22120512-03 for radiation

Note: EUT is the abbreviation of equipment under test.

Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	27	2429	54	2456
1	2403	28	2430	55	2457
2	2404	29	2431	56	2458
3	2405	30	2432	57	2459
4	2406	31	2433	58	2460
5	2407	32	2434	59	2461
6	2408	33	2435	60	2462
7	2409	34	2436	61	2463
8	2410	35	2437	62	2464
9	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Description	Remark
N/A	N/A	N/A	N/A	N/A

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
Adapter	SAMSUNG	EP-TA200	R37R41C1CF2S E3	N/A

2.4. Block diagram of EUT configuration for test

EUT

Test software: FCC_assist_1.0.2.2.exe

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table.

Tested mode, channel, information			
Mode	Setting Tx Power	Channel	Frequency (MHz)
GFSK hopping on Tx mode	10	CH0 to CH78	2402 to 2480
$\pi/4$ -DQPSK hopping on Tx mode	10	CH0 to CH78	2402 to 2480
8DPSK hopping on Tx mode	10	CH0 to CH78	2402 to 2480
GFSK hopping off Tx mode	10	CH0	2402
	10	CH39	2441
	10	CH78	2480
$\pi/4$ -DQPSK hopping off Tx mode	10	CH0	2402
	10	CH39	2441
	10	CH78	2480
8DPSK hopping off Tx mode	10	CH0	2402
	10	CH39	2441
	10	CH78	2480

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25 °C
Humidity range:	40-75%
Pressure range:	86-106 kPa

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB (10 MHz ≤ f < 3.6 GHz); 1.38 dB (3.6 GHz ≤ f < 8 GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB (10 MHz ≤ f < 3.6 GHz); 1.38 dB (3.6 GHz ≤ f < 8 GHz)
Frequencies Stability	6.7 × 10 ⁻⁸ (Antenna couple method) 5.5 × 10 ⁻⁸ (Conducted method)
Conducted spurious emissions	0.86 dB (10 MHz ≤ f < 3.6 GHz); 1.40 dB (3.6 GHz ≤ f < 8 GHz) 1.66 dB (8 GHz ≤ f < 26.5 GHz)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10 ⁻⁸
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V) 4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz) 4.40 dB (6 GHz - 18 GHz) 3.54 dB (18 GHz - 26 GHz) 4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.32 dB (150 kHz - 30 MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☑RF Connected Test (Tonscend RF Measurement System 3#)					
Signal & Spectrum analyzer	R&S	FSV40	101407	Jul. 21, 2022	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	May 18, 2022	1 Year
Vector Signal Generator	Agilent	N5182A	MY19060405	May 18, 2022	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180912	May 18, 2022	1 Year
RF Control Unit	Tonscend	JS0806-2	20C8060230	May 18, 2022	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	May 26, 2022	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.3.2.22	N/A	N/A
☑Radiation 3#chamber					
EMI Test Receiver	R&S	ESU26	100472	May 19, 2022	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	May 17, 2022	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Sep. 29, 2022	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	01429	Jul. 22, 2022	1 Year
Double Ridged Horn Antenna	Schwarzbeck	BBHA9120 D	02468	Sep. 29, 2022	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	May 06, 2022	1 Year
Pre-amplifier	COM-POWER	PAM-118A	18040084	Aug.17, 2022	1 Year
Pre-amplifier	COM-POWER	PAM-840A	461369	Apr. 11, 2022	1 Year
RE Cable	N/A	W23.02 CP1-X2 + W23.09 AP1-X8+ JCT26S-NJ- NJ-1.5M+ JCT26S-NJ- NJ-1.5M	4.5M+8M+1.5M+1.5M	Aug.17, 2022	1 Year
RF Cable	Yuhu Technology	JCTB810-NJ-NJ-9M	21123964	May. 19, 2022	1 Year
RF Cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	21073466	Aug.17, 2022	1 Year
Test software	Tonscend	JS32-RE	V 5.0.0.1	N/A	N/A
☑Power Line Conducted Emissions Test 1#					
Test Receiver	R&S	ESCI	100551	Aug. 26, 2022	1 Year
LISN 1	R&S	ENV216	101109	Aug. 26, 2022	1 Year
LISN 2	R&S	ESH2-Z5	100309	Aug. 26, 2022	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Aug. 26, 2022	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Aug. 26, 2022	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
Test Receiver	R&S	ESCI	100551	Aug. 26, 2022	1 Year

4. Maximum Peak Output Power

4.1. Block diagram of test setup



4.2. Limits

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W.

4.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Measure the maximum output power of EUT by spectrum analyzer with PK detector and RBW = 3 MHz (above 20 dB bandwidth of measured signal), VBW = 10 MHz

Note: The attenuator loss was inputted into spectrum analyzer as amplitude offset.

4.4. Test result

Left side:

Mode	Antenna	Freq. (MHz)	Result (dBm)	Limit (dBm)	Verdict
GFSK	ANT1	2402	3.51	21	Pass
	ANT1	2441	3.23	21	Pass
	ANT1	2480	2.05	21	Pass
$\pi/4$ -DQPSK	ANT1	2402	4.24	21	Pass
	ANT1	2441	3.83	21	Pass
	ANT1	2480	2.69	21	Pass
8DPSK	ANT1	2402	4.49	21	Pass
	ANT1	2441	4.28	21	Pass
	ANT1	2480	3.07	21	Pass


Right side:

Mode	Antenna	Freq. (MHz)	Result (dBm)	Limit (dBm)	Verdict
GFSK	ANT1	2402	3.35	21	Pass
	ANT1	2441	2.83	21	Pass
	ANT1	2480	1.45	21	Pass
$\pi/4$ -DQPSK	ANT1	2402	3.97	21	Pass
	ANT1	2441	3.50	21	Pass
	ANT1	2480	2.14	21	Pass
8DPSK	ANT1	2402	4.05	21	Pass
	ANT1	2441	3.63	21	Pass
	ANT1	2480	2.32	21	Pass


4.5. Original test data

Left side:







2DH5 Ant1 2402




2DH5 Ant1 2441




2DH5 Ant1 2480




3DH5 Ant1 2402





3DH5 Ant1 2441




3DH5 Ant1 2480




Right side:




DH5_Ant1_2480




2DH5_Ant1_2402




2DH5_Ant1_2441




2DH5_Ant1_2480




3DH5 Ant1 2402



3DH5 Ant1 2441



3DH5 Ant1 2480



5. 20 dB Bandwidth and 99% Bandwidth

5.1. Block diagram of test setup

Same as section 4.1

5.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

5.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 kHz RBW and 100 kHz VBW. The 20 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20 dB.

5.4. Test result

Left side:

Mode	Freq. (MHz)	20 dB bandwidth Result (MHz)	99% bandwidth Result (MHz)	Verdict
GFSK	2402	1.02	0.902	Pass
	2441	1.02	0.905	Pass
	2480	1.00	0.899	Pass
$\pi/4$ -DQPSK	2402	1.32	1.190	Pass
	2441	1.32	1.187	Pass
	2480	1.30	1.187	Pass
8DPSK	2402	1.30	1.187	Pass
	2441	1.30	1.190	Pass
	2480	1.30	1.187	Pass

Right side:


Mode	Freq. (MHz)	20 dB bandwidth Result (MHz)	99% bandwidth Result (MHz)	Verdict
GFSK	2402	1.01	0.896	Pass
	2441	1.01	0.899	Pass
	2480	0.99	0.893	Pass
$\pi/4$ -DQPSK	2402	1.29	1.187	Pass
	2441	1.30	1.187	Pass
	2480	1.30	1.181	Pass
8DPSK	2402	1.30	1.184	Pass
	2441	1.30	1.187	Pass
	2480	1.30	1.184	Pass

5.5. Original test data


Left side:

20 dB bandwidth







2DH5 Ant1 2402




2DH5 Ant1 2441




2DH5 Ant1 2480




3DH5 Ant1 2402





3DH5 Ant1 2441




3DH5 Ant1 2480



99% bandwidth




DH5_Ant1_2480



2DH5 Ant1 2402




2DH5 Ant1 2441




2DH5 Ant1 2480




3DH5 Ant1 2402



3DH5 Ant1 2441




3DH5 Ant1 2480




Right side:

20 dB bandwidth







2DH5 Ant1 2402




2DH5 Ant1 2441




2DH5 Ant1 2480




3DH5 Ant1 2402





3DH5 Ant1 2441




3DH5 Ant1 2480




99% bandwidth




DH5_Ant1_2480




2DH5 Ant1 2402




2DH5 Ant1 2441



2DH5 Ant1 2480




3DH5 Ant1 2402



3DH5 Ant1 2441



3DH5 Ant1 2480



6. Carrier Frequency Separation

6.1. Block diagram of test setup

Same as section 4.1

6.2. Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

6.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The carrier frequency was measured by spectrum analyzer with 300 kHz RBW and 300 kHz VBW.

6.4. Test result

Left side:

Mode	Channel separation (MHz)	20 dB bandwidth (MHz) (worse case)	Limit (MHz) 2/3 of 20 dB bandwidth	Verdict
GFSK	1.006	1.02	≥ 0.680	Pass
$\pi/4$ -DQPSK	1.003	1.32	≥ 0.880	Pass
8DPSK	1.012	1.30	≥ 0.867	Pass


Right side:

Mode	Channel separation (MHz)	20 dB bandwidth (MHz) (worse case)	Limit (MHz) 2/3 of 20 dB bandwidth	Verdict
GFSK	1.148	1.01	≥ 0.673	Pass
$\pi/4$ -DQPSK	0.983	1.30	≥ 0.867	Pass
8DPSK	1.009	1.30	≥ 0.867	Pass



6.5. Original test data


Left side:





Right side:





7. Number of Hopping Channel

7.1. Block diagram of test setup

Same as section 4.1

7.2. Limits

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

7.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The number of hopping channels was measured by spectrum analyzer with 300 kHz RBW and 300 kHz VBW.

7.4. Test result

Left side:

Mode	Number of hopping channels	Limit	Verdict
GFSK	79	>15	Pass
$\pi/4$ -DQPSK	79	>15	Pass
8DPSK	79	>15	Pass


Right side:

Mode	Number of hopping channels	Limit	Verdict
GFSK	79	>15	Pass
$\pi/4$ -DQPSK	79	>15	Pass
8DPSK	79	>15	Pass



7.5. Original test data


Left side:





Right side:





8. Dwell Time

8.1. Block diagram of test setup

Same as section 4.1

8.2. Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

8.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$
- (3) Measure the hopping number and on time of each pulse with spectrum analyzer in zero span set, and calculate dwell time with formula Dwell time = total hops *pulse's on time.

8.4. Test result

Left side:

Mode	Dwell time (s)	Pulse's on time (ms)	Total hops	Limit	Verdict
DH1	0.114	0.36	318	<400ms	Pass
DH3	0.266	1.62	164	<400ms	Pass
DH5	0.307	2.87	107	<400ms	Pass
2DH1	0.118	0.37	319	<400ms	Pass
2DH3	0.267	1.63	164	<400ms	Pass
2DH5	0.307	2.87	107	<400ms	Pass
3DH1	0.119	0.37	321	<400ms	Pass
3DH3	0.262	1.63	161	<400ms	Pass
3DH5	0.296	2.87	103	<400ms	Pass

Note: Dwell time = total hops *pulse's on time.


Right side:


Mode	Dwell time (s)	Pulse's on time (ms)	Total hops	Limit	Verdict
DH1	0.114	0.36	318	<400ms	Pass
DH3	0.258	1.62	159	<400ms	Pass
DH5	0.296	2.87	103	<400ms	Pass
2DH1	0.118	0.37	320	<400ms	Pass
2DH3	0.254	1.63	156	<400ms	Pass
2DH5	0.317	2.88	110	<400ms	Pass
3DH1	0.118	0.37	320	<400ms	Pass
3DH3	0.262	1.62	162	<400ms	Pass
3DH5	0.34	2.88	118	<400ms	Pass

Note: Dwell time = total hops * pulse's on time.


8.5. Original test data

Left side:






Date: 21 FEB 2023 22:41:20



Date: 21 FEB 2023 22:41:53

DH5_Ant1_Hop



Date: 21 FEB 2023 22:40:25