

FCC REPORT

(GSM & WCDMA)

Applicant: Shenzhen Huafurui Technology Co., Ltd.

Address of Applicant: Unit 1401 14/F, Jin qi zhi gu mansion Liu xian street, Xili, Nan shan district Shenzhen, China

Equipment Under Test (EUT)

Product Name: Smart Phone

Model No.: P40

Trade mark: CUBOT

FCC ID: 2AHZ5P40

Applicable standards: FCC CFR Title 47 Part 2
FCC CFR Title 47 Part 22 Subpart H
FCC CFR Title 47 Part 24 Subpart E
FCC CFR Title 47 Part 27 Subpart L

Date of sample receipt: 07 Jul., 2020

Date of Test: 07 Jul., to 05 Aug., 2020

Date of report issued: 06 Aug., 2020

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2. Version

Version No.	Date	Description
00	06 Aug., 2020	Original

Tested by:

YT Yang

Test Engineer

Date:

06 Aug., 2020

Reviewed by:

Winner Zhang

Project Engineer

Date:

06 Aug., 2020

3. Contents

Page

1.	COVER PAGE	1
2.	VERSION.....	2
3.	CONTENTS.....	3
4.	TEST SUMMARY	4
5.	GENERAL INFORMATION	5
5.1	CLIENT INFORMATION.....	5
5.2	GENERAL DESCRIPTION OF E.U.T.....	5
5.3	TEST ENVIRONMENT AND MODE, AND TEST SAMPLES PLANS	7
5.4	DESCRIPTION OF SUPPORT UNITS.....	7
5.5	MEASUREMENT UNCERTAINTY.....	7
5.6	ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD.....	7
5.7	LABORATORY FACILITY.....	7
5.8	LABORATORY LOCATION	8
5.9	TEST INSTRUMENTS LIST.....	8
6.	TEST RESULTS.....	9
6.1	CONDUCTED OUTPUT POWER, ERP AND EIRP	9
6.2	PEAK-TO-AVERAGE POWER RATIO	13
6.3	OCCUPY BANDWIDTH	16
6.4	MODULATION CHARACTERISTIC.....	25
6.5	OUT OF BAND EMISSION AT ANTENNA TERMINALS	25
6.6	FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT.....	35
6.7	FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT.....	41
6.8	FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT	45
7	TEST SETUP PHOTO.....	48
8	EUT CONSTRUCTIONAL DETAILS	49

4. Test Summary

Test Item	Section in CFR 47	Result
RF Exposure (SAR)	Part 1.1307 Part 2.1093	Pass (Please refer to SAR Report)
RF Output Power	Part 2.1046 Part 22.913 (a)(5) Part 24.232 (c) Part 27.50 (d)(4)	Pass
Peak-to-Average Power Ratio	Part 24.232 (d) Part 27.50(d)(5)	Pass
Modulation Characteristics	Part 2.1047	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917(b) Part 24.238(b) Part 27.53(h)	Pass
Out of band emission at antenna terminals	Part 2.1053 Part 22.917 (a) Part 24.238 (a) Part 27.53 (h)	Pass
Field strength of spurious radiation	Part 22.917 (a) Part 24.238 (a) Part 27.53 (h)	Pass
Frequency stability vs. temperature	Part 22.355 Part 24.235 Part 27.54 Part 2.1055(a)(1)(b)	Pass
Frequency stability vs. voltage	Part 22.355 Part 24.235 Part 27.54 Part 2.1055(d)(2)	Pass
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB(Fundamental Frequency below 1GHz)/1.0dB(Fundamental Frequency above 1GHz) (provided by the customer).		
Test Method:	ANSI/TIA-603-E-2016 ANSI C63.26-2015	

5. General Information

5.1 Client Information

Applicant:	Shenzhen Huafurui Technology Co., Ltd.
Address:	Unit 1401 14/F, Jin qi zhi gu mansion Liu xian street, Xili, Nan shan district Shenzhen, China
Manufacturer/ Factory:	Shenzhen Huafurui Technology Co., Ltd.
Address:	Unit 1401 14/F, Jin qi zhi gu mansion Liu xian street, Xili, Nan shan district Shenzhen, China

5.2 General Description of E.U.T.

Product Name:	Smart Phone
Model No.:	P40
Operation Frequency range:	GSM 850: 824.20MHz-848.80MHz PCS1900: 1850.20MHz-1909.80MHz WCDMA Band V: 826.4MHz-846.6MHz WCDMA Band II: 1852.4 MHz-1907.6 MHz WCDMA Band IV: 1712.4 MHz-1752.6 MHz
Modulation type:	GSM/GPRS: GMSK, EGPRS: 8PSK, UMTS: QPSK
Antenna type:	Internal Antenna
Antenna gain:	GSM 850: 0.96 dBi PCS 1900: 1.02 dBi WCDMA Band V: 1.01 dBi WCDMA Band II: 1.02 dBi WCDMA Band IV: 1.11 dBi
Power supply:	Rechargeable Li-ion Battery DC3.85V-4200mAh
AC adapter:	Model: HJ-0502000W2-US Input: AC100-240V, 50/60Hz, 0.3A Output: DC 5.0V, 2000mA
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

Operation Frequency List:

GSM 850		PCS1900	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
128	824.20	512	1850.20
129	824.40	513	1850.40
....			
189	836.40	660	1879.80
190	836.60	661	1880.00
191	836.80	662	1880.20
...	...	...	...
250	848.60	809	1909.60
251	848.80	810	1909.80
WCDMA Band V		WCDMA Band II	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
4132	826.40	9262	1852.40
4133	826.60	9263	1852.60
....			
4182	836.40	9399	1879.80
4183	836.60	9400	1880.00
4184	836.80	9401	1880.20
...	...	...	...
4232	846.40	9537	1907.40
4233	846.60	9538	1907.60
WCDMA Band IV			
Channel	Frequency (MHz)		
1312	1712.40		
1313	1712.60		
....			
1412	1732.40		
1413	1732.60		
1414	1732.80		
...	...		
1512	1752.40		
1513	1752.60		

Regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

GSM850			PCS1900		
Channel		Frequency(MHz)	Channel		Frequency(MHz)
Lowest	128	824.20	Lowest	512	1850.20
Middle	190	836.60	Middle	661	1880.00
Highest	251	848.80	Highest	810	1909.80
WCDMA Band V			WCDMA Band II		
Channel		Frequency(MHz)	Channel		Frequency(MHz)
Lowest	4132	826.40	Lowest	9262	1852.40
Middle	4183	836.60	Middle	9400	1880.00
Highest	4233	846.60	Highest	9538	1907.60
WCDMA Band IV					
Channel		Frequency(MHz)			
Lowest	1312	1712.40			
Middle	1413	1732.60			
Highest	1513	1752.60			

5.3 Test environment and mode, and test samples plans

Operating Environment:	
Temperature:	Normal: 15°C ~ 35°C, Extreme: -30°C ~ +50°C
Humidity:	20 % ~ 75 % RH
Atmospheric Pressure:	1008 mbar
Voltage:	Nominal: 3.85Vdc, Extreme: Low 3.50 Vdc, High 4.40 Vdc
Test mode:	
GSM mode	Keep the EUT communication with simulated station in GSM mode
GPRS mode	Keep the EUT communication with simulated station in GPRS mode
EGPRS mode	Keep the EUT communication with simulated station in EGPRS mode
RMC mode	Keep the EUT communication with simulated station in RMC mode
HSDPA	Keep the EUT communication with simulated station in HSDPA mode
HSUPA	Keep the EUT communication with simulated station in HSUPA mode
Remark: The EUT has been tested under continuous transmitting mode. Channel Low, Mid and High for each type band with rated data rate were chosen for full testing. The field strength of spurious radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for these modes. Just the worst case position (H mode) shown in report.	
Test Samples Plans:	
Samples Number	Used for Test Items
1#	EUT constructional details
Remark: Shenzhen Zhongjian Nanfang Testing Co., Ltd. is only responsible for the test project data of the above samples, and will keep the above samples for a month.	

5.4 Description of Support Units

Test Equipment	Manufacturer	Model No.	Serial No.
Simulated Station	Anritsu	MT8820C	6201026545

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.16 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.20 dB (k=2)

5.6 Additions to, deviations, or exclusions from the method

No

5.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.8 Laboratory Location


Shenzhen Zhongjian Nanfang Testing Co., Ltd.
 Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road, Bao'an District,
 Shenzhen, Guangdong, China
 Tel: +86-755-23118282, Fax: +86-755-23116366
 Email: info@ccis-cb.com, Website: <http://www.ccis-cb.com>

5.9 Test Instruments list

Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
				07-22-2020	07-21-2023
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-18-2020	03-17-2021
Biconical Antenna	SCHWARZBECK	VUBA9117	359	06-22-2020	06-21-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2020	06-21-2021
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-18-2019	11-17-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2020	03-06-2021
Pre-amplifier	CD	PAP-1G18	11804	03-07-2020	03-06-2021
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-05-2020	03-04-2021
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-18-2019	11-17-2020
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-05-2020	03-04-2021
Spectrum Analyzer	Agilent	N9020A	MY50510123	11-18-2019	11-17-2020
Signal Generator	Rohde & Schwarz	SMX	835454/016	03-05-2020	03-04-2021
Signal Generator	R&S	SMR20	1008100050	03-05-2020	03-04-2021
RF Switch Unit	MWRFTTEST	MW200	N/A	N/A	N/A
Test Software	MWRFTTEST	MTS8200	Version: 2.0.0.0		
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2020	03-06-2021
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2020	03-06-2021
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2020	03-06-2021
DC Power Supply	XinNuoEr	WYK-10020K	1409050110020	09-25-2019	09-24-2020
Temperature Humidity Chamber	HengPu	HPGDS-500	20140828008	11-01-2019	11-31-2020
Simulated Station	Rohde & Schwarz	CMW500	140493	07-22-2019	07-21-2020
				07-22-2020	07-21-2023

6. Test results

6.1 Conducted Output Power, ERP and EIRP

Test Requirement:	FCC part 22.913(a)(5), FCC part 24.232(c), FCC part 27.50(d)(4)
Limit:	GSM 850: 7W, PCS 1900: 2W WCDMA Band V: 7W, WCDMA Band II: 2W, WCDMA Band IV: 1W
Test setup:	 The diagram illustrates the test setup. On the left is a blue box labeled 'System simulator'. A line connects it to a small black rectangle labeled 'ATT' (attenuator). Another line connects the 'ATT' to a black rectangle labeled 'EUT' (Equipment Under Test).
Test Procedure:	The transmitter output was connected to a calibrated attenuator, the other end of which was connected to the simulated station. Transmitter output power was read off in dBm.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Measurement Data:

EUT Mode	Burst Average power (dBm)		
	128	190	251
	824.20 (MHz)	836.60 (MHz)	848.80 (MHz)
GSM 850	33.95	33.74	33.62
GPRS 850 (1 Uplink slot)	33.94	33.72	33.60
GPRS 850 (2 Uplink slot)	33.04	33.00	33.12
GPRS 850 (3 Uplink slot)	32.12	31.89	31.84
GPRS 850 (4 Uplink slot)	30.16	30.61	30.51
Antenna Gain (dBi)	0.96		
Max. ERP (dBm)	32.76		
ERP Limit (dBm)	38.45		
EGPRS 850 (1 Uplink slot)	27.32	27.06	26.58
EGPRS 850 (2 Uplink slot)	26.00	25.66	25.46
EGPRS 850 (3 Uplink slot)	24.69	23.68	23.44
EGPRS 850 (4 Uplink slot)	22.66	22.47	22.59
Antenna Gain (dBi)	0.96		
Max. ERP (dBm)	26.13		
ERP Limit (dBm)	38.45		
EUT Mode	Burst Average power (dBm)		
	512	661	810
	1850.20 (MHz)	1880.00 (MHz)	1909.80 (MHz)
PCS 1900	31.56	31.59	31.62
GPRS 1900 (1 Uplink slot)	31.54	31.51	31.60
GPRS 1900 (2 Uplink slot)	30.88	30.92	30.68
GPRS 1900 (3 Uplink slot)	29.30	29.35	29.42
GPRS 1900 (4 Uplink slot)	28.14	28.16	28.26
Antenna Gain (dBi)	1.02		
Max. EIRP (dBm)	32.64		
EIRP Limit (dBm)	33.00		
EGPRS 1900 (1 Uplink slot)	28.16	28.20	28.76
EGPRS 1900 (2 Uplink slot)	26.94	27.03	27.58
EGPRS 1900 (3 Uplink slot)	24.88	25.02	25.62
EGPRS 1900 (4 Uplink slot)	23.82	23.95	24.36
Antenna Gain (dBi)	1.02		
Max. EIRP (dBm)	29.78		
EIRP Limit (dBm)	33.00		
Note: EIRP (dBm) = Burst Average power (dBm) + Antenna Gain (dBi).			
ERP (dBm) = EIRP (dBm) - 2.15 (dB).			

EUT Mode		Burst Average power (dBm)		
		4132	4183	4233
		826.40 (MHz)	836.60 (MHz)	846.60 (MHz)
UMTS 850 HSDPA	Subtest 1	23.45	23.55	23.41
	Subtest 2	23.15	23.14	23.03
	Subtest 3	24.64	21.47	21.53
	Subtest 4	21.62	21.59	21.67
UMTS 850 HSUPA	Subtest 1	23.45	23.12	23.14
	Subtest 2	22.94	22.04	22.95
	Subtest 3	22.65	22.41	22.33
	Subtest 4	21.60	21.39	21.44
	Subtest 5	22.03	22.09	22.43
UMTS 850 RMC	12.2kbps	24.40	24.15	24.03
UMTS 850 AMR	12.2kbps	24.33	24.06	24.00
Antenna Gain (dBi)		1.01		
Max. ERP (dBm)		22.86		
ERP Limit (dBm)		38.45		
EUT Mode		Burst Average power (dBm)		
		9262	9400	9538
		1852.40 (MHz)	1880.00 (MHz)	1907.60 (MHz)
UMTS 1900 HSDPA	Subtest 1	24.04	24.02	23.97
	Subtest 2	23.78	23.62	23.14
	Subtest 3	22.06	21.96	22.10
	Subtest 4	22.05	21.95	21.15
UMTS 1900 HSUPA	Subtest 1	24.13	24.03	24.00
	Subtest 2	23.43	23.14	23.06
	Subtest 3	23.15	23.06	22.25
	Subtest 4	22.26	22.65	22.44
	Subtest 5	21.96	21.46	21.58
UMTS 1900 RMC	12.2kbps	24.35	24.36	24.48
UMTS 1900 AMR	12.2kbps	24.26	24.22	24.40
Antenna Gain (dBi)		1.02		
Max. EIRP (dBm)		25.50		
EIRP Limit (dBm)		33.00		
Note: EIRP (dBm) = Burst Average power (dBm) + Antenna Gain (dBi).				
ERP (dBm) = EIRP (dBm) - 2.15 (dB).				

EUT Mode		Burst Average power (dBm)		
		1312	1412	1513
		1712.40 (MHz)	1732.40 (MHz)	1752.60 (MHz)
UMTS 1700 HSDPA	Subtest 1	23.76	23.34	23.41
	Subtest 2	23.40	22.85	23.04
	Subtest 3	21.88	21.36	21.56
	Subtest 4	21.91	21.32	21.41
UMTS 1700 HSUPA	Subtest 1	23.26	23.14	23.58
	Subtest 2	22.65	22.47	22.69
	Subtest 3	23.65	23.03	23.44
	Subtest 4	22.14	21.98	22.06
	Subtest 5	22.05	22.90	22.16
UMTS 1700 RMC	12.2kbps	24.16	24.36	24.43
UMTS 1700 AMR	12.2kbps	24.03	24.25	24.33
Antenna Gain (dBi)		1.11		
Max. EIRP (dBm)		25.54		
EIRP Limit (dBm)		30.00		
Note: EIRP (dBm) = Burst Average power (dBm) + Antenna Gain (dBi).				

6.2 Peak-to-Average Power Ratio


Test Requirement:	FCC part 24.232(d), FCC part 27.50(d)(5)
Limit:	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.
Test setup:	 The diagram shows a test setup where a System simulator and a Spectrum Analyzer are connected to a Splitter. The Splitter is connected to an ATT (attenuator), which is then connected to the EUT (Equipment Under Test).
Test Procedure:	1 The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. 2 Set the CCDF option in spectrum analyzer, RBW $\geq$ OBW, 3 Set the EUT working in highest power level, measured and recorded the 0.1% as PAPR level. 4 Repeat step 1~3 at other frequency and modulations.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Modulation	Test channel	PAPR
GSM 850	190	2.67
EGPRS 850	190	5.37
PCS 1900	661	2.69
EGPRS 1900	661	5.42
UMTS 850 RMC	4183	2.95
UMTS 1900 RMC	9400	2.86
UMTS1700 RMC	1413	3.04


Test plots as below:

GSM 850




Middle channel

PCS 1900




Middle channel

EGPRS 850




Middle channel

EGPRS 1900



Middle channel

UMTS 850 RMC




Middle channel

UMTS 1900 RMC




Middle channel

UMTS1700 RMC



Middle channel


6.3 Occupy Bandwidth

Test Requirement:	FCC part 22.917(b), FCC part 24.238(b), FCC Part 27.53(h)
Test setup:	 The diagram illustrates the test setup. On the left, there are two blue rectangular units: the top one is labeled 'System simulator' and the bottom one is labeled 'Spectrum Analyzer'. Both have a single output port. These two ports are connected to a single input port of a white rectangular unit labeled 'Splitter'. The other output port of the 'Splitter' is connected to a black rectangular unit labeled 'ATT' (Attenuator). Finally, the output of the 'ATT' is connected to the input of a black rectangular unit labeled 'EUT' (Equipment Under Test).
Test Procedure:	1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer 2. RBW was set to about 1% of emission BW, VBW= 3 times RBW. 3. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:


EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (kHz)	-26dB bandwidth (kHz)
GSM 850	128	824.2	246	322
	190	836.6	244	318
	251	848.8	238	324
EGPRS850	128	824.2	256	330
	190	836.6	252	330
	251	848.8	254	320
PCS 1900	512	1850.2	248	314
	661	1880.0	250	312
	810	1909.8	248	318
EGPRS1900	512	1850.2	246	306
	661	1880.0	248	324
	810	1909.8	254	318
UMTS 850 12.2k RMC	4132	826.4	4180	4760
	4183	836.6	4180	4740
	4233	846.6	4180	4700
UMTS 1900 12.2k RMC	9262	1852.4	4200	4760
	9400	1880.0	4180	4740
	9538	1907.6	4200	4740
UMTS 1700 12.2k RMC	1312	1712.40	4200	4720
	1413	1732.60	4180	4720
	1513	1752.60	4180	4720
Note: GSM & GPRS use the same modulation technical (GMSK), and with the same channels, so the 99% OBW and the -26dB of GPRS not performed.				

Test plot as follows:




EGPRS 850

99% Occupancy bandwidth




Date: 10.JUL.2020 10:44:05

26dB Emission Bandwidth




Date: 10.JUL.2020 10:44:16

Lowest channel




Date: 10.JUL.2020 10:49:14

Lowest channel




Date: 10.JUL.2020 10:49:24

Middle channel



Date: 10.JUL.2020 10:49:50

Middle channel




Date: 10.JUL.2020 10:49:41

Highest channel

Highest channel


PCS 1900

99% Occupy bandwidth




Date: 10.JUL.2020 10:39:48

Lowest channel



Date: 10.JUL.2020 10:40:22


Middle channel



Date: 10.JUL.2020 10:40:34


Highest channel

26dB Emission Bandwidth




Date: 10.JUL.2020 10:39:58

Lowest channel



Date: 10.JUL.2020 10:40:13

Middle channel




Date: 10.JUL.2020 10:40:45

Highest channel


EGPRS 1900

99% Occupy bandwidth




Date: 10.JUL.2020 10:41:51

26dB Emission Bandwidth




Date: 10.JUL.2020 10:41:39

Lowest channel




Date: 10.JUL.2020 10:42:08

Lowest channel




Date: 10.JUL.2020 10:42:19

Middle channel



Date: 10.JUL.2020 10:42:54

Middle channel




Date: 10.JUL.2020 10:42:37

Highest channel

Highest channel


UMTS 850 12.2k RMC

99% Occupancy bandwidth




Date: 10.JUL.2020 11:07:27

26dB Emission Bandwidth




Date: 10.JUL.2020 11:07:20

Lowest channel




Date: 10.JUL.2020 11:07:42

Lowest channel




Date: 10.JUL.2020 11:07:52

Middle channel



Date: 10.JUL.2020 11:08:16

Middle channel




Date: 10.JUL.2020 11:08:08

Highest channel

Highest channel


UMTS 1900 12.2k RMC

99% Occupancy bandwidth




Date: 10.JUL.2020 11:10:40

26dB Emission Bandwidth




Date: 10.JUL.2020 11:10:33

Lowest channel




Date: 10.JUL.2020 11:10:55

Lowest channel




Date: 10.JUL.2020 11:11:04

Middle channel



Date: 10.JUL.2020 11:11:24

Middle channel




Date: 10.JUL.2020 11:11:16

Highest channel

Highest channel


UMTS 1700 12.2k RMC

99% Occupancy bandwidth




Date: 10.JUL.2020 11:09:04

26dB Emission Bandwidth




Date: 10.JUL.2020 11:09:12

Lowest channel




Date: 10.JUL.2020 11:09:33

Lowest channel




Date: 10.JUL.2020 11:09:26

Middle channel



Date: 10.JUL.2020 11:09:45

Middle channel



Date: 10.JUL.2020 11:09:54


Highest channel

Highest channel

6.4 Modulation Characteristic


According to FCC § 2.1047(d), Part 22H & 24E & 27L there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

6.5 Out of band emission at antenna terminals


Test Requirement:	FCC part 22.917(a), FCC part 24.238(a), FCC Part 27.53 (h)
Limit:	-13dBm
Test setup:	 The diagram illustrates the test setup. On the left, there are two blue rectangular units: the top one is labeled 'System simulator' and the bottom one is labeled 'Spectrum Analyzer'. Both have a single output port. These two ports are connected to a single input port of a white rectangular unit labeled 'Splitter'. The 'Splitter' has two output ports. One output port is connected to a black rectangular unit labeled 'ATT' (attenuator). The other output port of the 'Splitter' is connected to the input of a black rectangular unit labeled 'EUT' (Equipment Under Test).
Test Procedure:	1 The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. 2 For the out of band: For GSM850&WCDMA850 set the RBW=100 kHz, VBW=300 kHz and for PCS1900 & WCDMA1900 set the RBW=1MHz, VBW=3MHz when below 1 GHz, RBW =1 MHz, VBW=3 MHz when above 1 GHz, Start=30MHz, Stop= 10th harmonic. 3 Band Edge Requirements: In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plots as follows (Spurious emission):

GSM 850 Lowest Channel




Date: 10.JUL.2020 11:00:26




Date: 14.JUL.2020 09:04:50

Middle channel




Date: 10.JUL.2020 11:00:40




Date: 14.JUL.2020 09:05:16


Highest Channel




Date: 10.JUL.2020 11:00:54



Date: 14.JUL.2020 09:05:39


PCS 1900
Lowest Channel

Date: 10.JUL.2020 10:58:52




Date: 14.JUL.2020 08:59:15

Middle Channel




Date: 10.JUL.2020 10:59:01




Date: 14.JUL.2020 09:03:18


Highest Channel




Date: 10.JUL.2020 10:59:13



Date: 14.JUL.2020 09:03:55


UMTS 850 12.2k RMC
Lowest Channel

Date: 10.JUL.2020 11:04:43




Date: 14.JUL.2020 08:57:12

Middle Channel




Date: 10.JUL.2020 11:04:57




Date: 14.JUL.2020 08:57:33


Highest Channel




Date: 10.JUL.2020 11:05:10



Date: 14.JUL.2020 08:57:44


UMTS 1900 12.2k RMC
Lowest Channel

Date: 10.JUL.2020 11:02:51




Date: 14.JUL.2020 08:53:46

Middle Channel




Date: 10.JUL.2020 11:03:04




Date: 14.JUL.2020 08:54:01

Highest Channel




Date: 10.JUL.2020 11:03:22




Date: 14.JUL.2020 08:54:18

UMTS 1700 12.2k RMC
Lowest Channel




Date: 10.JUL.2020 11:03:51




Date: 14.JUL.2020 08:55:40

Middle Channel




Date: 10.JUL.2020 11:04:02




Date: 14.JUL.2020 08:56:04

Highest Channel




Date: 10.JUL.2020 11:04:13



Date: 14.JUL.2020 08:56:19


Band edge emission:

GSM850



Date: 10.JUL.2020 10:52:42


Lowest channel



Date: 10.JUL.2020 10:53:16


Highest channel

PCS1900




Date: 10.JUL.2020 10:57:26

Lowest channel




Date: 10.JUL.2020 10:57:45

Highest channel

EGPRS850


Date: 10.JUL.2020 10:50:49

Lowest channel




Date: 10.JUL.2020 10:51:17

Highest channel

EGPRS1900

Date: 10.JUL.2020 10:54:27


Lowest channel



Date: 10.JUL.2020 10:54:59


Highest channel

UMTS 850 RMC 12.2kbps



Date: 10.JUL.2020 11:24:07


Lowest channel



Date: 10.JUL.2020 11:23:38


Highest channel

UMTS 1900 RMC 12.2kbps




Date: 10.JUL.2020 11:22:07

Lowest channel





Date: 10.JUL.2020 11:22:33

Highest channel



6.6 Field strength of spurious radiation measurement

Test Requirement:	FCC part 22.917(a), FCC part 24.238(a), FCC part 27.53(h)
Limit:	-13dBm
Test setup:	Below 1GHz  Above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8m(below 1GHz)/1.5m(above 1GHz) above the ground at a 3 meter camber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations. 3. The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission was identified, the power of the emission was determined using the substitution method. 4. The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency. $ERP / EIRP = S.G. \text{ output (dBm)} + \text{Antenna Gain(dB/dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details.
Test results:	Passed

Measurement Data (worst case):

GSM850							
Lowest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
1648.40	-64.08	9.57	0.19	-54.70	-13.00	-41.70	Vertical
2472.60	-56.03	10.86	0.42	-45.59	-13.00	-32.59	Vertical
3296.80	-52.70	10.49	0.64	-42.85	-13.00	-29.85	Vertical
1648.40	-58.48	9.57	0.19	-49.10	-13.00	-36.10	Horizontal
2472.60	-52.48	10.86	0.42	-42.04	-13.00	-29.04	Horizontal
3296.80	-54.64	10.49	0.64	-44.79	-13.00	-31.79	Horizontal
Middle channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
1673.20	-62.70	9.66	0.21	-53.25	-13.00	-40.25	Vertical
2509.80	-54.60	10.91	0.46	-44.15	-13.00	-31.15	Vertical
3346.40	-52.96	12.09	0.66	-41.53	-13.00	-28.53	Vertical
1673.20	-58.77	9.66	0.21	-49.32	-13.00	-36.32	Horizontal
2509.80	-53.00	10.91	0.46	-42.55	-13.00	-29.55	Horizontal
3346.40	-55.11	12.09	0.66	-43.68	-13.00	-30.68	Horizontal
Highest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
1697.60	-61.66	9.74	0.24	-52.16	-13.00	-39.16	Vertical
2546.40	-55.78	10.95	0.50	-45.33	-13.00	-32.33	Vertical
3395.20	-54.30	12.19	0.68	-42.79	-13.00	-29.79	Vertical
1697.60	-58.35	9.74	0.24	-48.85	-13.00	-35.85	Horizontal
2546.40	-51.60	10.95	0.50	-41.15	-13.00	-28.15	Horizontal
3395.20	-54.18	12.19	0.68	-42.67	-13.00	-29.67	Horizontal
Remark:							
1. The emission levels of below 1 GHz are lower than the limit 20dB and not show in test report.							

PCS1900							
Lowest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
3700.40	-60.43	12.64	0.74	-48.53	-13.00	-35.53	Vertical
5550.60	-52.46	12.76	1.12	-40.82	-13.00	-27.82	Vertical
3700.40	-55.26	12.64	0.74	-43.36	-13.00	-30.36	Horizontal
5550.60	-55.03	12.76	1.12	-43.39	-13.00	-30.39	Horizontal
Middle channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
3760.00	-59.09	12.71	0.77	-47.15	-13.00	-34.15	Vertical
5640.00	-51.48	12.87	1.15	-39.76	-13.00	-26.76	Vertical
3760.00	-54.56	12.71	0.77	-42.62	-13.00	-29.62	Horizontal
5640.00	-53.31	12.87	1.15	-41.59	-13.00	-28.59	Horizontal
Highest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
3819.60	-58.36	12.78	0.81	-46.39	-13.00	-33.39	Vertical
5729.40	-50.34	12.98	1.20	-38.56	-13.00	-25.56	Vertical
3819.60	-53.12	12.78	0.81	-41.15	-13.00	-28.15	Horizontal
5729.40	-54.51	12.98	1.20	-42.73	-13.00	-29.73	Horizontal
Remark:							
1. The emission levels of below 1 GHz are lower than the limit 20dB and not show in test report.							

WCDMA BAND V 12.2k RMC							
Lowest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
1652.80	-62.91	9.58	0.20	-53.53	-13.00	-40.53	Vertical
2479.20	-63.35	10.87	0.44	-52.92	-13.00	-39.92	Vertical
3305.60	-61.38	12.01	0.65	-50.02	-13.00	-37.02	Vertical
1652.80	-65.68	9.58	0.20	-56.30	-13.00	-43.30	Horizontal
2479.20	-66.59	10.87	0.44	-56.16	-13.00	-43.16	Horizontal
3305.60	-62.50	12.01	0.65	-51.14	-13.00	-38.14	Horizontal
Middle channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
1673.20	-61.60	9.66	0.21	-52.15	-13.00	-39.15	Vertical
2509.80	-60.81	10.91	0.46	-50.36	-13.00	-37.36	Vertical
3346.40	-61.41	12.09	0.66	-49.98	-13.00	-36.98	Vertical
1673.20	-64.90	9.66	0.21	-55.45	-13.00	-42.45	Horizontal
2509.80	-66.77	10.91	0.46	-56.32	-13.00	-43.32	Horizontal
3346.40	-63.60	12.09	0.66	-52.17	-13.00	-39.17	Horizontal
Highest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
1697.60	-63.16	9.74	0.24	-53.66	-13.00	-40.66	Vertical
2546.40	-62.06	12.09	0.50	-50.47	-13.00	-37.47	Vertical
3395.20	-61.32	12.19	0.68	-49.81	-13.00	-36.81	Vertical
1697.60	-64.76	9.74	0.24	-55.26	-13.00	-42.26	Horizontal
2546.40	-65.21	12.09	0.50	-53.62	-13.00	-40.62	Horizontal
3395.20	-62.60	12.19	0.68	-51.09	-13.00	-38.09	Horizontal
Remark: 1. The emission levels of below 1 GHz are lower than the limit 20dB and not show in test report.							

WCDMA Band II 12.2k RMC							
Lowest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
3704.80	-59.44	12.65	0.76	-47.55	-13.00	-34.55	Vertical
5557.20	-56.79	12.77	1.14	-45.16	-13.00	-32.16	Vertical
3704.80	-55.53	12.65	0.76	-43.64	-13.00	-30.64	Horizontal
5557.20	-56.77	12.77	1.14	-45.14	-13.00	-32.14	Horizontal
Middle channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
3760.00	-58.29	12.71	0.77	-46.35	-13.00	-33.35	Vertical
5640.00	-56.94	12.87	1.15	-45.22	-13.00	-32.22	Vertical
3760.00	-54.46	12.71	0.77	-42.52	-13.00	-29.52	Horizontal
5640.00	-55.91	12.87	1.15	-44.19	-13.00	-31.19	Horizontal
Highest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
3815.20	-57.23	12.78	0.80	-45.25	-13.00	-32.25	Vertical
5722.80	-56.47	12.97	1.19	-44.69	-13.00	-31.69	Vertical
3815.20	-55.60	12.78	0.80	-43.62	-13.00	-30.62	Horizontal
5722.80	-56.96	12.97	1.19	-45.18	-13.00	-32.18	Horizontal
Remark:							
1. The emission levels of below 1 GHz are lower than the limit 20dB and not show in test report.							

WCDMA Band IV 12.2k RMC							
Lowest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
3424.40	-56.97	12.25	0.44	-45.15	-13.00	-32.15	Vertical
5136.60	-57.63	12.92	0.71	-45.41	-13.00	-32.41	Vertical
3424.40	-52.23	12.25	0.44	-40.41	-13.00	-27.41	Horizontal
5136.60	-58.07	12.92	0.71	-45.85	-13.00	-32.85	Horizontal
Middle channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
3464.80	-58.20	12.33	0.45	-46.32	-13.00	-33.32	Vertical
5197.20	-55.67	12.88	0.72	-43.51	-13.00	-30.51	Vertical
3464.80	-52.03	12.33	0.45	-40.15	-13.00	-27.15	Horizontal
5197.20	-57.01	12.88	0.72	-44.85	-13.00	-31.85	Horizontal
Highest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
3505.20	-57.31	12.41	0.47	-45.36	-13.00	-32.36	Vertical
5257.80	-54.91	12.85	0.74	-42.79	-13.00	-29.79	Vertical
3505.20	-51.57	12.41	0.47	-39.62	-13.00	-26.62	Horizontal
5257.80	-54.63	12.85	0.74	-42.51	-13.00	-29.51	Horizontal
Remark: 2. The emission levels of below 1 GHz are lower than the limit 20dB and not show in test report.							

6.7 Frequency stability V.S. Temperature measurement

Test Requirement:	FCC Part 22.355, FCC Part 24.235, FCC Part 27.54 FCC Part 2.1055(a)(1)(b)
Limit:	±2.5 ppm for GSM 850 and WCDMA 850 Within authorized band for PCS 1900 and WCDMA 1900 and WCDMA 1700
Test setup:	
Test procedure:	1. The equipment under test was connected to an external DC power supply and input rated voltage. 2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Measurement Data (the worst channel):

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	174	0.207985	±2.5	Pass
	-20	155	0.185274		
	-10	136	0.162563		
	0	125	0.149414		
	10	114	0.136266		
	20	142	0.169735		
	30	139	0.166149		
	40	128	0.153000		
	50	117	0.139852		
Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	179	0.095213	Within authorized band for PCS 1900	Pass
	-20	156	0.082979		
	-10	142	0.075532		
	0	130	0.069149		
	10	126	0.067021		
	20	117	0.062234		
	30	108	0.057447		
	40	139	0.073936		
	50	147	0.078191		
Note: Only the worst case shown in the report.					

Reference Frequency: EGPRS850 Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	174	0.207985	±2.5	Pass
	-20	155	0.185274		
	-10	136	0.162563		
	0	125	0.149414		
	10	114	0.136266		
	20	142	0.169735		
	30	139	0.166149		
	40	128	0.153000		
	50	117	0.139852		
Reference Frequency: EGPRS 1900 Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	179	0.095213	Within authorized band for PCS 1900	Pass
	-20	156	0.082979		
	-10	142	0.075532		
	0	130	0.069149		
	10	126	0.067021		
	20	117	0.062234		
	30	108	0.057447		
	40	139	0.073936		
	50	147	0.078191		
Note: Only the worst case shown in the report.					

Reference Frequency: WCDMA BAND V 12.2k RMC Middle channel=4183 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	169	0.202008	±2.5	Pass
	-20	142	0.169735		
	-10	135	0.161367		
	0	122	0.145828		
	10	108	0.129094		
	20	160	0.191250		
	30	162	0.193641		
	40	138	0.164953		
	50	145	0.173321		
Reference Frequency: WCDMA BAND II 12.2k RMC Middle channel=9400 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	190	0.101064	Within authorized band for WCDMA 1900	Pass
	-20	152	0.080851		
	-10	143	0.076064		
	0	166	0.088298		
	10	145	0.077128		
	20	127	0.067553		
	30	148	0.078723		
	40	136	0.072340		
	50	152	0.080851		
Reference Frequency: UMTS1700 12.2k RMC Middle channel=1413 channel=1732.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	172	0.099273	Within authorized band for WCDMA 1700	Pass
	-20	142	0.081958		
	-10	143	0.082535		
	0	126	0.072723		
	10	108	0.062334		
	20	144	0.083112		
	30	168	0.096964		
	40	158	0.091192		
	50	129	0.074455		
Note: Only the worst case shown in the report.					

6.8 Frequency stability V.S. Voltage measurement

Test Requirement:	FCC Part 22.355, FCC Part 24.235, FCC Part 27.54 FCC Part 2.1055(d)(2)
Limit:	±2.5 ppm for GSM 850 and WCDMA 850 Within authorized band for PCS 1900 and WCDMA 1900 and WCDMA 1700
Test setup:	 The diagram illustrates the test setup. A Signal Source (SS) and a Spectrum Analyzer (SA) are connected to a Divider. The output of the Divider is connected to the EUT (Equipment Under Test) inside a Temperature & Humidity Chamber. A Power Source is also connected to the EUT.
Test procedure:	1. Set chamber temperature to 25°C. Use a variable DC power source to power the EUT and set the voltage to rated voltage. 2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. 3. Reduce the input voltage to specify extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data (the worst channel):

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.40	85	0.101602	±2.5	Pass
	3.85	78	0.093235		
	3.50	68	0.081281		
Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.40	90	0.047872	Within authorized band for PCS 1900	Pass
	3.85	74	0.039362		
	3.50	80	0.042553		
Reference Frequency: EGPRS 850 Middle channel= 190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.40	96	0.114750	±2.5	Pass
	3.85	88	0.105188		
	3.50	70	0.083672		
Reference Frequency: EGPRS 1900 Middle channel= 661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.40	85	0.045213	Within authorized band for PCS 1900	Pass
	3.85	74	0.039362		
	3.50	86	0.045745		
Note: Only the worst case shown in the report.					

Reference Frequency: UMTS 850 12.2k RMC Middle channel=4183 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.40	84	0.100406	±2.5	Pass
	3.85	90	0.107578		
	3.50	63	0.075305		
Reference Frequency: UMTS 1900 12.2k RMC Middle channel=9400 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.40	78	0.041489	Within authorized band for WCDMA 1900	Pass
	3.85	81	0.043085		
	3.50	69	0.036702		
Reference Frequency: UMTS1700 12.2k RMC Middle channel=1413 channel=1732.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.40	90	0.051945	Within authorized band for WCDMA 1700	Pass
	3.85	84	0.048482		
	3.50	57	0.032899		
Note: Only the worst case shown in the report.					