

FCC RF EXPOSURE REPORT

FCC ID: 2AHZL-CT001

Project No. : 1603203

Equipment: Cubic Trigger

Model: Ct001

Applicant : FoneTrend Technology Co., Ltd

Address: 6-15, No. 181, Sec. 2, Taiwan Blvd., West Dist.,

Taichung City 400

According: : FCC Guidelines for Human Exposure IEEE

C95.1

BTL INC.

B1, No.37, Lane 365, Yang Guang St., Nei-Hu District, Taipei City 114, Taiwan. TEL:+886-2-2657-3299 FAX: +886-2- 2657-3331



Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	printed	N/A	4.44

GENERAL CONCULUSION:

Maximum measured transmitter power:

OutputPower	Output Power	Limit (mW)	
(dBm)	(mW)		
-1.66	0.7	10	

According to FCC KDB447498 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and $\leq 50 \text{ mm}$

The maximum measured output peak power of this EUT is 0.7mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold