

ATC

TEST REPORT

Applicant Name : Shenzhen Omni Intelligent Technology Co., Ltd.
Address : 11th Floor, Building 31, Phase III, Lianchuang Technology Park,
Nanwan street, Longgang District, Shenzhen, China
Report Number : SZNS221018-47756E-RF-00B
FCC ID: 2AI2O-M113IOT

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: IOT
Model No.: M113-IOT
Multiple Model(s) No.: N/A
Trade Mark: N/A
Date Received: 2022/10/18
Report Date: 2022/11/24

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Roger Ling
EMC Engineer

Approved By:

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk “**”. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC §1.1307(B) & 2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)	10
FCC §15.203 - ANTENNA REQUIREMENT	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	14
TEST PROCEDURE	14
FACTOR & MARGIN CALCULATION	14
TEST DATA	14
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST DATA	21
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST DATA	22
FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST DATA	23
FCC §15.247(E) - POWER SPECTRAL DENSITY	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST DATA	24

APPENDIX	25
APPENDIX A: DTS BANDWIDTH	25
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	28
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	31
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	34
APPENDIX E: BAND EDGE MEASUREMENTS.....	37
APPENDIX F: DUTY CYCLE	39

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	BLE 1M/2M: 2402-2480MHz
Maximum Conducted Peak Output Power	BLE 1M: -2.34dBm; BLE 2M: -2.31dBm
Modulation Technique	GFSK
Antenna Specification*	3dBi (provided by the applicant)
Voltage Range	DC3.7V from battery or DC 9~90V
Sample serial number	IMLR for Radiated Emissions IMLS for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	5%	
RF Frequency	0.082×10^{-7}	
RF output power, conducted	0.73dB	
Unwanted Emission, conducted	1.6dB	
AC Power Lines Conducted Emissions	2.72dB	
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature	1°C	
Humidity	6%	
Supply voltages	0.4%	

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For BLE 1M/2M mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

“DOGO_VP_2.0.7”* software was used to test and power level as below:

Mode	Data rate	Power Level*		
		Low Channel	Middle Channel	High Channel
BLE	1Mbps	10	10	10
	2Mbps	10	10	10

The software and power level was provided by the applicant.

Duty cycle

Test Result: Compliant. Please refer to the Appendix.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Unknown	Speaker	Unknown	Unknown
Unknown	Resistance 1	Unknown	Unknown
Unknown	Resistance 2	Unknown	Unknown

External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-shielding Detachable DC Cable	1.0	EUT	DC Power
Un-shielding Un-Detachable DC Cable	0.2	EUT	Speaker
Un-shielding Un-Detachable DC Cable	0.2	EUT	Resistance 1
Un-shielding Un-Detachable DC Cable	0.2	EUT	Resistance 2

Block Diagram of Test Setup

For Radiated Emissions:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §1.1307(b) & 2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Not Applicable
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

Not Applicable: The device is intend to use in scooter.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2021/11/09	2022/11/08
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101590	2022/01/19	2023/01/18
Tonscend	RF Control Unit	JS0806-2	19G8060182	2022/10/24	2023/10/23
Unknown	RF Coaxial Cable	No.31	RF-01	Each time	

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(b) & 2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R ² .
1.34-30	3,450 R ² /f ² .
30-300	3.83 R ² .
300-1,500	0.0128 R ² f.
1,500-100,000	19.2R ² .

f = frequency in MHz;

R = minimum separation distance from the body of a nearby person (appropriate units, e.g., m);

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{l=1}^a \frac{P_l}{P_{th,l}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Result

For worst case:

Mode	Frequency (MHz)	Tune up conducted power		Antenna Gain		ERP		Evaluation Distance (m)	ERP Limit (W)
		(dBm)	(dBi)	(dBd)	(dBm)	(W)			
BLE	2402-2480	-2.0	3.0	0.85	-1.15	0.0008	0.2	0.768	
LTE Band 2	1850-1910	22.0	-1.25	-3.4	18.6	0.072	0.2	0.768	
LTE Band 4	1710-1755	22.0	-0.86	-3.01	18.99	0.079	0.2	0.768	
LTE Band 5	824-849	22.0	-1.3	-3.45	18.55	0.072	0.2	0.422	
LTE Band 12	699-716	22.0	-0.93	-3.08	18.92	0.078	0.2	0.358	
LTE Band 13	777-787	22.0	-0.81	-2.96	19.04	0.080	0.2	0.398	

Note 1: The tune-up power and antenna gain was declared by the applicant.

Note 2: 0dBd=2.15dBi.

Simultaneous transmitting consideration (worst case):

The ratio=ERP_{BLE}/limit + ERP_{LTE} /limit = 0.0008/0.768+0.078/0.358=0.219<1.0

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.



Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 3.0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	>1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Over Limit/Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions


Temperature:	24~24.5 °C
Relative Humidity:	50~58 %
ATM Pressure:	101.0 kPa

The testing was performed by Level Li on 2022-11-16 for below 1GHz and Zeki Ma on 2022-11-01 for above 1GHz.

EUT operation mode: Transmitting (Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded)

30MHz-1GHz: (Worst case: BLE IM, Low channel)


Note: When the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded.



Site : chamber
Condition: 3m HORIZONTAL
Job No. : SZNS221018-47756E-RF
Test Mode: BLE Transmitting

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	dBuV/m	
1	53.858	-10.32	40.09	29.77	40.00	-10.23	Peak
2	59.990	-10.62	40.00	29.38	40.00	-10.62	QP
3	71.990	-15.62	47.24	31.62	40.00	-8.38	Peak
4	120.013	-13.53	40.89	27.36	43.50	-16.14	Peak
5	239.987	-10.91	37.35	26.44	46.00	-19.56	Peak
6	900.937	1.42	30.09	31.51	46.00	-14.49	Peak

Vertical



Site : chamber

Condition: 3m VERTICAL

Job No. : SZNS221018-47756E-RF

Test Mode: BLE Transmitting

	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	47.994	-10.00	38.70	28.70	40.00	-11.30	Peak
2	59.990	-10.62	48.20	37.58	40.00	-2.42	QP
3	71.990	-15.62	47.65	32.03	40.00	-7.97	Peak
4	196.768	-11.56	45.21	33.65	43.50	-9.85	Peak
5	462.548	-5.44	38.71	33.27	46.00	-12.73	Peak
6	895.425	0.98	29.38	30.36	46.00	-15.64	Peak

1-25 GHz:

BLE 1M:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel									
2310	62.35	PK	235	1.7	H	-7.24	55.11	74	-18.89
2310	48.34	AV	235	1.7	H	-7.24	41.10	54	-12.90
2310	61.32	PK	82	1	V	-7.24	54.08	74	-19.92
2310	48.48	AV	82	1	V	-7.24	41.24	54	-12.76
2390	71.45	PK	38	1.6	H	-7.22	64.23	74	-9.77
2390	50.40	AV	38	1.6	H	-7.22	43.18	54	-10.82
2390	63.32	PK	73	2.3	V	-7.22	56.10	74	-17.90
2390	50.04	AV	73	2.3	V	-7.22	42.82	54	-11.18
4804	57.81	PK	159	2.3	H	-3.51	54.30	74	-19.70
4804	46.38	AV	159	2.3	H	-3.51	42.87	54	-11.13
4804	58.61	PK	66	1.5	V	-3.51	55.10	74	-18.90
4804	49.39	AV	66	1.5	V	-3.51	45.88	54	-8.12
7206	61.87	PK	1	2.3	H	-2.70	59.17	74	-14.83
7206	52.39	AV	1	2.3	H	-2.70	49.69	54	-4.31
7206	63.54	PK	270	1.6	V	-2.70	60.84	74	-13.16
7206	53.69	AV	270	1.6	V	-2.70	50.99	54	-3.01
Middle Channel									
4880	57.83	PK	24	2.3	H	-3.38	54.45	74	-19.55
4880	45.52	AV	24	2.3	H	-3.38	42.14	54	-11.86
4880	57.84	PK	225	1.3	V	-3.38	54.46	74	-19.54
4880	47.94	AV	225	1.3	V	-3.38	44.56	54	-9.44
7320	55.28	PK	59	1.7	H	3.31	58.59	74	-15.41
7320	45.35	AV	59	1.7	H	3.31	48.66	54	-5.34
7320	54.69	PK	57	1.5	V	3.31	58	74	-16.00
7320	45.31	AV	57	1.5	V	3.31	48.62	54	-5.38
High Channel									
2483.5	77.56	PK	271	2.4	H	-7.20	70.36	74	-3.64
2483.5	50.49	AV	271	2.4	H	-7.20	43.29	54	-10.71
2483.5	71.47	PK	237	1.6	V	-7.20	64.27	74	-9.73
2483.5	52.24	AV	237	1.6	V	-7.20	45.04	54	-8.96
2500	66.75	PK	67	1.2	H	-7.18	59.57	74	-14.43
2500	49.94	AV	67	1.2	H	-7.18	42.76	54	-11.24
2500	63.20	PK	164	2.3	V	-7.18	56.02	74	-17.98
2500	49.83	AV	164	2.3	V	-7.18	42.65	54	-11.35
4960	56.11	PK	281	2	H	-3.01	53.10	74	-20.90
4960	56.33	PK	119	2	V	-3.01	53.32	74	-20.68
7440	55.64	PK	231	2.2	H	3.53	59.17	74	-14.83
7440	45.45	AV	231	2.2	H	3.53	48.98	54	-5.02
7440	54.51	PK	349	1.6	V	3.53	58.04	74	-15.96
7440	44.59	AV	349	1.6	V	3.53	48.12	54	-5.88

BLE 2M:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel									
2310	61.77	PK	326	2.3	H	-7.24	54.53	74	-19.47
2310	49.13	AV	326	2.3	H	-7.24	41.89	54	-12.11
2310	61.45	PK	335	2.3	V	-7.24	54.21	74	-19.79
2310	49.11	AV	335	2.3	V	-7.24	41.87	54	-12.13
2390	69.96	PK	79	1.2	H	-7.22	62.74	74	-11.26
2390	50.70	AV	79	1.2	H	-7.22	43.48	54	-10.52
2390	63.01	PK	163	2.4	V	-7.22	55.79	74	-18.21
2390	50.74	AV	163	2.4	V	-7.22	43.52	54	-10.48
4804	57.14	PK	3	2.2	H	-3.51	53.63	74	-20.37
4804	56.91	PK	223	2.2	V	-3.51	53.40	74	-20.60
7206	64.43	PK	260	1.2	H	-2.70	61.73	74	-12.27
7206	53.66	AV	260	1.2	H	-2.70	50.96	54	-3.04
7206	64.44	PK	137	1.7	V	-2.70	61.74	74	-12.26
7206	53.68	AV	137	1.7	V	-2.70	50.98	54	-3.02
Middle Channel									
4880	56.99	PK	168	2.3	H	-3.38	53.61	74	-20.39
4880	56.53	PK	245	2.3	V	-3.38	53.15	74	-20.85
7320	57.86	PK	113	1.4	H	3.31	61.17	74	-12.83
7320	47.66	AV	113	1.4	H	3.31	50.97	54	-3.03
7320	56.92	PK	214	1.7	V	3.31	60.23	74	-13.77
7320	47.44	AV	214	1.7	V	3.31	50.75	54	-3.25
High Channel									
2483.5	77.21	PK	260	1.6	H	-7.20	70.01	74	-3.99
2483.5	51.30	AV	260	1.6	H	-7.20	44.1	54	-9.90
2483.5	71.34	PK	68	2.4	V	-7.20	64.14	74	-9.86
2483.5	51.39	AV	68	2.4	V	-7.20	44.19	54	-9.81
2500	66.72	PK	272	2.4	H	-7.18	59.54	74	-14.46
2500	50.79	AV	272	2.4	H	-7.18	43.61	54	-10.39
2500	63.31	PK	292	1.6	V	-7.18	56.13	74	-17.87
2500	50.68	AV	292	1.6	V	-7.18	43.5	54	-10.50
4960	57.00	PK	9	1.5	H	-3.01	53.99	74	-20.01
4960	56.74	PK	39	1.5	V	-3.01	53.73	74	-20.27
7440	57.39	PK	340	2.5	H	3.53	60.92	74	-13.08
7440	47.45	AV	340	2.5	H	3.53	50.98	54	-3.02
7440	55.34	PK	357	2.1	V	3.53	58.87	74	-15.13
7440	46.46	AV	357	2.1	V	3.53	49.99	54	-4.01

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude - Limit


The other spurious emission which is in the noise floor level was not recorded.

When the test result of peak was less than the limit of average, just peak values were recorded.


1-18 GHz:



Pre-scan for BLE 1M Low Channel

Horizontal



Vertical



18 -25GHz:**Pre-scan for BLE 1M Low Channel****Horizontal****Vertical**


FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	58 %
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-11-23.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	58 %
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-11-23.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	58 %
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-11-23.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	58 %
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-11-23.

EUT operation mode: Transmitting


Test Result: Compliant. Please refer to the Appendix.


APPENDIX

Appendix A: DTS Bandwidth Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.69	2401.63	2402.32	0.5	PASS
		2440	0.70	2439.63	2440.33	0.5	PASS
		2480	0.70	2479.63	2480.32	0.5	PASS
BLE_2M	Ant1	2402	1.19	2401.38	2402.57	0.5	PASS
		2440	1.20	2439.37	2440.57	0.5	PASS
		2480	1.19	2479.37	2480.56	0.5	PASS

Test Graphs






**Appendix B: Occupied Channel Bandwidth
Test Result**

Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.043	2401.453	2402.496	---	---
		2440	1.043	2439.453	2440.496	---	---
		2480	1.031	2479.457	2480.488	---	---
BLE_2M	Ant1	2402	2.046	2400.969	2403.015	---	---
		2440	2.042	2438.969	2441.011	---	---
		2480	2.030	2478.973	2481.003	---	---

Test Graphs







**Appendix C: Maximum conducted output power
Test Result Peak**

Test Mode	Antenna	Frequency[MHz]	Conducted Peak Power[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-2.34	≤30	PASS
		2440	-2.78	≤30	PASS
		2480	-2.89	≤30	PASS
BLE_2M	Ant1	2402	-2.31	≤30	PASS
		2440	-2.76	≤30	PASS
		2480	-2.88	≤30	PASS

Test Graphs Peak







**Appendix D: Maximum power spectral density
Test Result**

Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-17.94	≤8.00	PASS
		2440	-16.84	≤8.00	PASS
		2480	-17.07	≤8.00	PASS
BLE_2M	Ant1	2402	-18.60	≤8.00	PASS
		2440	-19.03	≤8.00	PASS
		2480	-20.31	≤8.00	PASS


Test Graphs






Appendix E: Band edge measurements

Test Graphs






Appendix F: Duty Cycle Test Result

Test Mode	Antenna	Frequency[MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
BLE_1M	Ant1	2440	0.41	0.62	66.13	1.80
BLE_2M	Ant1	2440	0.23	0.63	36.51	4.38

Test Graphs



***** END OF REPORT *****