SAR Test Report

Report No.: AGC05621160701FH01

FCC ID : 2AI3SAZMOBILEA1

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Mobile Phone

BRAND NAME : AZ mobile

MODEL NAME : AZ mobile A1

CLIENT: Evertrons Technology Co., Limited

DATE OF ISSUE : July 22,2016

IEEE Std. 1528:2013

STANDARD(S) : FCC 47CFR § 2.1093

IEEE/ANSI C95.1:1992

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd.

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report No.: AGC05621160701FH01 Page 2 of 60

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	July 22,2016	Valid	Original Report

Page 3 of 60

	Test Report Certification
Applicant Name	Evertrons Technology Co., Limited
Applicant Address	Flat/RM 1605E, Ho King Commercial Center, 2-16 FA Yuen Streent, Mongkok KL, Hong Kong
Manufacturer Name	Evertrons Technology Co., Limited
Manufacturer Address	Flat/RM 1605E, Ho King Commercial Center, 2-16 FA Yuen Streent, Mongkok KL, Hong Kong
Product Designation	Mobile Phone
Brand Name	AZ mobile
Model Name	AZ mobile A1
Different Description	N/A
EUT Voltage	DC3.7V by battery
Applicable Standard	IEEE Std. 1528:2013 FCC 47CFR § 2.1093 IEEE/ANSI C95.1:1992
Test Date	July 20,2016 to July 21,2016
	Attestation of Global Compliance(Shenzhen) Co., Ltd.
Performed Location	2 F, Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang Street, Bao'an District, Shenzhen, China
Report Template	AGCRT-US-2.5G/SAR (2016-01-01)

	Dobby Wang	
Tested By	Bobby wang(Wang Zhicheng)	July 22,2016
	Angola li	
Checked By	Angela Li(Li Jiao)	July 22,2016
Authorized By	Solya Hong	
Authorized by	Solger Zhang(Zhang Hongyi) Authorized Officer	July 22,2016

TABLE OF CONTENTS

1. SUMMARY OF MAXIMUM SAR VALUE	5
2. GENERAL INFORMATION	6
2.1. EUT DESCRIPTION	6
3. SAR MEASUREMENT SYSTEM	8
3.1. THE DASY5 SYSTEM USED FOR PERFORMING COMPLIANCE TESTS CONSISTS OF FOLLOWING ITEMS	9
3.3. DATA ACQUISITION ELECTRONICS DESCRIPTION	_
3.5. LIGHT BEAM UNIT	10
3.6. DEVICE HOLDER	
3.8. PHANTOM	
4. SAR MEASUREMENT PROCEDURE	13
4.1. SPECIFIC ABSORPTION RATE (SAR)	
4.2. SAR MEASUREMENT PROCEDURE	
5. TISSUE SIMULATING LIQUID	
5.1. THE COMPOSITION OF THE TISSUE SIMULATING LIQUID	
5.2. TISSUE DIELECTRIC PARAMETERS FOR HEAD AND BODY PHANTOMS	17
5.3. TISSUE CALIBRATION RESULT	
6. SAR SYSTEM CHECK PROCEDURE	
6.1. SAR SYSTEM CHECK PROCEDURES	
7. EUT TEST POSITION	22
7.1. DEFINE TWO IMAGINARY LINES ON THE HANDSET	
7.2. CHEEK POSITION	
7.4. BODY WORN POSITION	
8. SAR EXPOSURE LIMITS	25
9. TEST EQUIPMENT LIST	26
10. MEASUREMENT UNCERTAINTY	27
11. CONDUCTED POWER MEASUREMENT	30
12. TEST RESULTS	33
12.1. SAR Test Results Summary	33
APPENDIX A. SAR SYSTEM CHECK DATA	39
APPENDIX B. SAR MEASUREMENT DATA	43
APPENDIX C. TEST SETUP PHOTOGRAPHS & EUT PHOTOGRAPHS	60
APPENDIX D. CALIBRATION DATA	60

Page 5 of 60

1. SUMMARY OF MAXIMUM SAR VALUE

The maximum results of Specific Absorption Rate (SAR) found during testing for EUT are as follows:

Eroguanov Band	Highest Rep	SAR Test Limit	
Frequency Band	Head	Body-worn(with 5mm separation)	(W/Kg)
GSM 850	0.071	0.796	
PCS 1900	0.749	1.063	1.6
Simultaneous Reported SAR	1.168		1.0
SAR Test Result	PASS		

This device is compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6W/Kg) specified in IEEE Std. 1528:2013; FCC 47CFR § 2.1093; IEEE/ANSI C95.1:1992 and the following specific FCC Test Procedures:

- KDB 447498 D01 General RF Exposure Guidance v06
- KDB 648474 D04 Handset SAR v01r03
- KDB 865664 D01 SAR Measurement 100MHz to 6GHz v01r04
- KDB 941225 D01 3G SAR Procedures v03r01

Page 6 of 60

2. GENERAL INFORMATION

2.1. EUT Description

2.1. EUT Description			
General Information			
Product Designation	Mobile Phone		
Test Model	AZ mobile A1		
Hardware Version	HY88+-MB-V1.3		
Software Version	HY88_DLG_D62_V11_PCB(HY88-MB-V0.1)_AZMOBILE_NK_LANGUAGE(Y X)_FLASH(32+32)_LCD(NV3029E-IVO_NV3029H_ST7789S-IVO)_CAMERA(GC6123_GC6133_GC0329_SP0820_SP0829_SP0A19_20160709.pac		
Device Category	Portable		
RF Exposure Environment	Uncontrolled		
Antenna Type	Internal		
GSM and GPRS			
Support Band	☑GSM 850 ☑PCS 1900 ☑GSM 900 ☑DCS 1800		
GPRS Type	Class B		
GPRS Class	Class 12(1Tx+4Rx, 2Tx+3Rx, 3Tx+2Rx, 4Tx+1Rx)		
TX Frequency Range	GSM 850 : 820-850MHz;; PCS 1900: 1850-1910MHz;		
RX Frequency Range	GSM 850 : 869~894MHz; PCS 1900: 1930~1990MHz		
Release Version	R99		
Type of modulation	GMSK for GSM/GPRS		
Antenna Gain	1.0dBi		
Max. Average Power (Max. Peak Power)	GSM850: 31.84dBm(32.43dBm) ;PCS1900: 28.82dBm(29.47dBm)		
Bluetooth			
Bluetooth Version	□V2.0 □V2.1 □V2.1+EDR □V3.0+HS □V4.0		
Operation Frequency	2402~2480MHz		
Type of modulation	⊠GFSK ⊠∏/4-DQPSK ⊠8-DPSK		
Avg. Burst Power	3.72dBm		
Antenna Gain	0.8dBi		

Page 7 of 60

EUT Description(Continue)

Accessories	,		
Accessories	Accessories		
	Brand name: N/A		
Battery	Model No.: BL-4U		
,	Voltage and Capacitance: 3.7 V & 1000mAh		
	Brand name: N/A		
Adapter	Model No. : AZ mobile A1		
	Input: AC 100-240V, 50/60Hz, Output: DC 5V, 500mA		
Fambana	Brand name: N/A		
Earphone	Model No.: N/A		

Note:1.CMU200 can measure the average power and Peak power at the same time


2. The sample used for testing is end product.

Product	Туре		
Product	□ Production unit	☐ Identical Prototype	

Page 8 of 60

3. SAR MEASUREMENT SYSTEM

3.1. The DASY5 system used for performing compliance tests consists of following items



- A standard high precision 6-axis robot with controller, teach pendant and software.
- Data acquisition electronics (DAE) which attached to the robot arm extension. The DAE consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock
- A dosimetric probe equipped with an optical surface detector system.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital Communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- A Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- Phantoms, device holders and other accessories according to the targeted measurement.

Page 9 of 60

3.2. DASY5 E-Field Probe

The SAR measurement is conducted with the dosimetric probe manufactured by SPEAG. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. SPEAG conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528 and relevant KDB files.) The calibration data are in Appendix D.

Isotropic E-Field Probe Specification

Model	ES3DV3		
Manufacture	SPEAG		
frequency	0.15GHz-3 GHz Linearity:±0.2dB(150 MHz-3 GHz)		
Dynamic Range	0.01W/Kg-100W/Kg Linearity:±0.2dB		
Dimensions	Overall length:337mm Tip diameter:4mm Typical distance from probe tip to dipole centers:2mm		
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 3 GHz with precision of better 30%.		

3.3. Data Acquisition Electronics description

The data acquisition electronics (DAE) consist if a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converte and a command decoder with a control logic unit. Transmission to the measurement sever is accomplished through an optical downlink fir data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

DAE4

Input Impedance	200MOhm	ENGINE .
The Inputs	Symmetrical and floating	Witterland
Common mode rejection	above 80 dB	DAGA PANY TO DAMES OF THE PANY

Page 10 of 60

3.4. Robot

The DASY system uses the high precision robots (DASY5:TX60) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version from is used.

The XL robot series have many features that are important for our application:

- ☐ High precision (repeatability 0.02 mm)
- ☐ High reliability (industrial design)
- ☐ Jerk-free straight movements
- ☐ Low ELF interference (the closed metallic construction shields against motor control fields)
- ☐ 6-axis controller



3.5. Light Beam Unit

The light beam switch allows automatic "tooling" of the probe. During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip.

The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned prob.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position. e, the same position will be reached with another aligned probe within 0



Page 11 of 60

3.6. Device Holder

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles. The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity ϵ =3 and loss tangent δ = 0.02. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



3.7. Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chip-disk (DASY5: 128MB), RAM (DASY5: 128MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DAYS I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.



Page 12 of 60

3.8. PHANTOM SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:

□ Left head

☐ Right head

☐ Flat phantom



The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

ELI4 Phantom

☐ Flat phantom a fiberglass shell flat phantom with 2mm+/- 0.2 mm shell thickness. It has only one measurement area for Flat phantom



Page 13 of 60

4. SAR MEASUREMENT PROCEDURE

4.1. Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and occupational/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of given mass density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dV} \right)$$

SAR is expressed in units of Watts per kilogram (W/Kg) SAR can be obtained using either of the following equations:

$$SAR = \frac{\sigma E^2}{\rho}$$

$$SAR = c_h \frac{dT}{dt}\Big|_{t=0}$$

Where

SAR is the specific absorption rate in watts per kilogram;

E is the r.m.s. value of the electric field strength in the tissue in volts per meter;

σ is the conductivity of the tissue in siemens per metre;

ρ is the density of the tissue in kilograms per cubic metre;

ch is the heat capacity of the tissue in joules per kilogram and Kelvin;

 $\frac{dT}{dt}$ | t=0 is the initial time derivative of temperature in the tissue in kelvins per second

Page 14 of 60

4.2. SAR Measurement Procedure

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurement are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface is 2.7mm This distance cannot be smaller than the distance os sensor calibration points to probe tip as `defined in the probe properties,

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in db) is specified in the standards for compliance testing. For example, a 2db range is required in IEEE Standard 1528 and IEC62209 standards, whereby 3db is a requirement when compliance is assessed in accordance with the ARIB standard (Japan) If one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximum are detected, the number of Zoom Scan has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100MHz to 6GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	½·δ·ln(2) ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
	≤2 GHz: ≤15 mm 2 – 3 GHz: ≤12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan

Zoom Scan are used to assess the peak spatial SAR value within a cubic average volume containing 1g abd 10g of simulated tissue. The Zoom Scan measures points(refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1g and 10g and displays these values next to the job's label.

Page 15 of 60

Zoom Scan Parameters extracted from KDB865664 d01 SAR Measurement 100MHz to 6GHz

Maximum zoom scan spatial resolution: Δx _{Zoom} , Δy _{Zoom}		\leq 2 GHz: \leq 8 mm 2 - 3 GHz: \leq 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*	
	uniform grid: Δz _{Zoom} (n)		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
Maximum zoom scan spatial resolution, normal to phantom surface	$\begin{array}{c} \Delta z_{Z00m}(1)\text{: between} \\ 1^{\text{st}} \text{ two points closest} \\ \text{to phantom surface} \\ \\ \Delta z_{Z00m}(n>1)\text{:} \\ \text{between subsequent} \\ \text{points} \end{array}$	1 st two points closest	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$		
Minimum zoom scan volume	zoom scan x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

Step 4: Power Drift Measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the same settings. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

^{*} When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

Page 16 of 60


4.3. RF Exposure Conditions

Test Configuration and setting:

The EUT is a model of GSM Portable Mobile Station (MS). It supports GSM/GPRS, BT.

For GSM/GPRS SAR testing, the device was controlled by using a base station emulator. Communication between the device and the emulator were established by air link. The distance between the EUT and the antenna is larger than 50cm, and the output power radiated from the emulator antenna is at least 30db smaller than the output power of EUT.

Antenna Location: (the front view)



EUT Bottom Edge

For GSM mode:

Test Configurations	Antenna to edges/surface	SAR required	Note
Head			
Left Touch		Yes	
Left Tilt		Yes	
Right Touch		Yes	
Right Tilt		Yes	
Body			
Back	<25mm	Yes	
Front	<25mm	Yes	

Page 17 of 60

5. TISSUE SIMULATING LIQUID

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15cm. For head SAR testing the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15cm For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in 5.2

5.1. The composition of the tissue simulating liquid

Ingredient (% Weight) Frequency (MHz)	Water	Nacl	Sugar	HEC	Bactericide	DGBE	1,2 Propanediol	Triton X-100
835 Head	40.45	1.45	57	1	0.1	0.0	0.0	0.0
835 Body	54.00	1	0.0	0.0	0.0	15	0.0	30
1900 Head	54.9	0.18	0.0	0.0	0.0	44.92	0.0	0.0
1900 Body	70	1	0.0	0.0	0.0	9	0.0	20

5.2. Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE 1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in IEEE 1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in IEEE 1528.

Target Frequency	he	ad	body			
(MHz)	εr	σ (S/m)	εr	σ (S/m)		
300	45.3	0.87	58.2	0.92		
450	43.5	0.87	56.7	0.94		
835	41.5	0.90	55.2	0.97		
900	41.5	0.97	55.0	1.05		
915	41.5	1.01	55.0	1.06		
1450	40.5	1.20	54.0	1.30		
1610	40.3	1.29	53.8	1.40		
1800 – 2000	40.0	1.40	53.3	1.52		
2450	39.2	1.80	52.7	1.95		
3000	38.5	2.40	52.0	2.73		
5800	35.3	5.27	48.2	6.00		

($\epsilon r = relative permittivity$, $\sigma = conductivity and <math>\rho = 1000 \text{ kg/m}3$)

Page 18 of 60

5.3. Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using DASY5 Dielectric Probe Kit and R&S Network Analyzer ZVL6.

	Tissue Stimulant Measurement for 835MHz											
	Fr.	Dielectric Par	ameters (±5%)	Tissue	To at time a							
	(MHz)	εr 41.5 (39.425-43.575) δ[s/m] 0.90(0.855-0.945)		Temp [°C]	Test time							
Head	824.2	42.06	0.87									
	835	41.10	0.90	20.5	July 20,2016							
	836.6	40.67	0.90	20.5								
	848.8	39.77	0.92									
	Fr.	Dielectric Par	Tissue	_								
	(MHz)	εr 55.20(52.44-57-96)	δ[s/m]0.97(0.9215-1.0185)	Temp [°C]	Test time							
Body	824.2	56.13	0.93									
	835	55.28	0.95	20.8	July 20,2016							
	836.6	54.64	0.96	20.0	July 20,2016							
	848.8	53.51	0.98									

	Tissue Stimulant Measurement for 1900MHz											
	Fr.	Dielectric Par	ameters (±5%)	Tissue	To at time a							
	(MHz)	εr40.00(38.00-42.00) δ[s/m]1.40(1.33-1.47)		Temp [°C]	Test time							
Head	1850.2	41.25	1.34									
	1880	40.36	1.37	24.0	July 24 2046							
	1900 39.83		1.40	21.0	July 21,2016							
	1909.8	39.00	1.45									
	Fr.	Dielectric Par	Tissue									
	(MHz) εr53.30(50.635-55.965)		δ[s/m]1.52(1.444-1.596)	Temp [°C]	Test time							
Body	1850.2	55.17	1.46									
	1880	54.22	1.52	21.1	July 21,2016							
	1900	53.69	1.55	Z 1. l	July 21,2016							
	1909.8	52.88	1.57									

Page 19 of 60


6. SAR SYSTEM CHECK PROCEDURE

6.1. SAR System Check Procedures

SAR system check is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are remeasured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

Each DASY system is equipped with one or more system check kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system check and system validation. System kit includes a dipole, and dipole device holder.


The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system check setup is shown as below.



Page 20 of 60

6.2. SAR System Check

6.2.1. Dipoles



The dipoles used is based on the IEEE-1528 standard, and is complied with mechanical and electrical specifications in line with the requirements of IEEE. the table below provides details for the mechanical and electrical Specifications for the dipoles.

Frequency	L (mm)	h (mm)	d (mm)
835MHz	161.0	89.8	3.6
1900MHz	68	39.5	3.6

Page 21 of 60

6.2.2. System Check Result

System Per	System Performance Check at 835MHz & 1900MHz for Head											
Validation Kit: SN 30/14 DIP 0G835-332 & SN 46/11DIP 1G900-187												
Frequency				ce Result 0%)	Tested Value(W/Kg)		Tissue Temp.	Test time				
[MHz]	1g	10g	1g	10g	1g	10g	[°C]					
835	9.63	6.15	8.667-10.593	5.535-6.765	9.921	5.896	20.5	July 20,2016				
1900	39.65	20.24	35.685-43.615	18.216-22.264	38.037	19.177	21.0	July 21,2016				
System Per	formance	Check a	835 MHz & 190	0MHz for Body								
Frequency		get (W/Kg)		ce Result 0%)		sted (W/Kg)	Tissue Temp.	Test time				
[MHz]	1g	10g	1g	10g	1g	10g	[°C]					
835	9.93	6.35	8.937-10.923	5.715-6.985	10.096	6.308	20.8	July 20,2016				
1900	40.74	21.43	36.666-44.814	19.287-23.573	42.475	21.713	21.1	July 21,2016				


Page 22 of 60

7. EUT TEST POSITION

This EUT was tested in Right Cheek, Right Tilted, Left Cheek, Left Tilted, Body back and Body front.

7.1. Define Two Imaginary Lines on the Handset

- (1)The vertical centerline passes through two points on the front side of the handset the midpoint of the width wt of the handset at the level of the acoustic output, and the midpoint of the width wb of the handset.
- (2)The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (3) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Page 23 of 60


7.2. Cheek Position

(1) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center picec in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.

(2) To move the device towards the phantom with the ear piece aligned with the the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost








7.3. Tilt Position

- (1) To position the device in the "cheek" position described above.
- (2) While maintaining the device in the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until with the ear is lost.









Page 24 of 60

7.4. Body Worn Position

- (1) To position the EUT parallel to the phantom surface.
- (2) To adjust the EUT parallel to the flat phantom.
- (3) To adjust the distance between the EUT surface and the flat phantom to 5mm.





Page 25 of 60

8. SAR EXPOSURE LIMITS

SAR assessments have been made in line with the requirements of IEEE-1528, and comply with ANSI/IEEE C95.1-1992 "Uncontrolled Environments" limits. These limits apply to a location which is deemed as "Uncontrolled Environment" which can be described as a situation where the general public may be exposed to an RF source with no prior knowledge or control over their exposure.

Limits for General Population/Uncontrolled Exposure (W/kg)

Type Exposure	Uncontrolled Environment Limit (W/kg)
Spatial Peak SAR (1g cube tissue for brain or body)	1.60
Spatial Average SAR (Whole body)	0.08
Spatial Peak SAR (Limbs)	4.0

Page 26 of 60

9. TEST EQUIPMENT LIST

Equipment description	Manufacturer/ Model	Identification No.	Current calibration date	Next calibration date
Stäubli Robot	Stäubli-TX60	F13/5Q2UD1/A/01	N/A	N/A
Robot Controller	Stäubli-CS8	139522	N/A	N/A
TISSUE Probe	SATIMO	SN 45/11 OCPG45	12/02/2015	12/01/2016
E-Field Probe	Speag- ES3DV3	SN:3337	10/01/2015	09/30/2016
SAM Twin Phantom	Speag-SAM	1790	N/A	N/A
Device Holder	Speag-SD 000 H01 KA	SD 000 H01 KA	N/A	N/A
DAE4	Speag-SD 000 D04 BM	1398	02/02/2016	02/01/2017
SAR Software	Speag-DASY5	DASY52.8	N/A	N/A
Liquid	SATIMO	-	N/A	N/A
Radio Communication Tester	R&S-CMU200	069Y7-158-13-712	02/29/2016	02/28/2017
Dipole	SATIMO SID835	SN30/14 DIP 0G835-332	09/01/2014	08/31/2017
Dipole	SATIMO SID1900	SN46/11 DIP 1G900-187	11/14/2013	11/13/2016
Signal Generator	Agilent-E4438C	US41461365	02/29/2016	02/28/2017
Spectrum Analyzer E4440	Agilent	US41421290	07/23/2015	07/22/2016
Network Analyzer	Rhode & Schwarz ZVL6	SN100132	03/01/2016	02/28/2017
Attenuator	Warison /WATT-6SR1211	N/A	N/A	N/A
Attenuator	Mini-circuits / VAT-10+	N/A	N/A	N/A
Amplifier	EM30180	SN060552	03/04/2016	03/03/2017
Directional Couple	Werlatone/ C5571-10	SN99463	07/29/2015	07/28/2016
Directional Couple	Werlatone/ C6026-10	SN99482	07/29/2015	07/28/2016
Power Sensor	NRP-Z21	1137.6000.02	10/20/2015	10/19/2016
Power Sensor	NRP-Z23	US38261498	03/01/2016	02/28/2017
Power Viewer	R&S	V2.3.1.0	N/A	N/A

Note: Per KDB 865664 Dipole SAR Validation, AGC Lab has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

- 1. There is no physical damage on the dipole;
- 2. System validation with specific dipole is within 10% of calibrated value;
- 3. Return-loss is within 20% of calibrated measurement;
- 4. Impedance is within 5Ω of calibrated measurement.

Page 27 of 60

10. MEASUREMENT UNCERTAINTY

The component of uncertainly may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainly by the statistical analysis of a series of observations is termed a Type An evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table as follow.

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor(a)	1/k(b)	1/√3	1/√6	1/√2

- (a) Standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity
- (b) κ is the coverage factor

Table 13.1 Standard Uncertainty for Assumed Distribution (above table)

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

Page 28 of 60

DAYS5 Measurement Uncertainty											
Measurement	Measurement uncertainty for 150 MHz to 3GHz averaged over 1 gram / 10 gram.										
Error Description	Uncertainty value(±10%)	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard Uncertainty (1g)	Standard Uncertainty (10g)				
Measurement System											
Probe Calibration	6	Normal	1	1	1	6.00	6.00				
Axial Isotropy	0.25	Rectangular	$\sqrt{3}$	1	1	0.14	0.14				
Hemispherical Isotropy	1.3	Rectangular	$\sqrt{3}$	1	1	0.75	0.75				
Linearity	0.3	Rectangular	$\sqrt{3}$	1	1	0.17	0.17				
Probe Modulation Response	1.65	Rectangular	$\sqrt{3}$	1	1	0.95	0.95				
System Detection Limits	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52				
Boundary Effects	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52				
Readout Electronics	0.2	Normal	1	1	1	0.20	0.20				
Response Time	0	Rectangular	$\sqrt{3}$	1	1	0.00	0.00				
Integration Time	0	Rectangular	$\sqrt{3}$	1	1	0.00	0.00				
RF Ambient Noise	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52				
RF Ambient Reflection	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52				
Probe Positioner	0.7	Rectangular	$\sqrt{3}$	1	1	0.40	0.40				
Probe Positioning	6.5	Rectangular	$\sqrt{3}$	1	1	3.75	3.75				
Post-processing	3.8	Rectangular	$\sqrt{3}$	1	1	2.19	2.19				
Test Sample Related											
Device Positioning	3.6	Normal	1	1	1	3.6	3.6				
Device Holder	2.9	Normal	1	1	1	2.9	2.9				
Measurement SAR Drift	5.0	Rectangular	$\sqrt{3}$	1	1	2.89	2.89				
Power Scaling	0.0	Rectangular	$\sqrt{3}$	1	1	0	0				
Phantom and Setup											
Phantom Uncertainty (Shape and thickness tolerances)	0.05	Normal	$\sqrt{3}$	1	1	0.03	0.03				
Uncertainty in SAR correction for deviations in permittivity and conductivity	1.9	Rectangular	1	1	0.84	1.90	1.60				
Liquid conductivity measurement	5	Normal	1	0.78	0.71	3.90	3.55				
Liquid permittivity measurement	5	Rectangular	1	0.23	0.26	1.15	1.30				
Liquid conductivity – temperature uncertainty	5	Rectangular	$\sqrt{3}$	0.78	0.71	2.25	2.05				
Liquid permittivity – temperature uncertainty	5	Rectangular	$\sqrt{3}$	0.23	0.26	0.66	0.75				
Combined Standard Uncerta	10.17	9.89									
Coverage Factor for 95%	K=										
Expanded Uncertainty						±20.34%	±19.779%				

Page 29 of 60

DAYS5 S	System Che	eck Uncertainty	for 150) MHz to	3GHz a	veraged ran	ge	
Error Description	Uncer. value (±10%)	Prob. Dist.	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(v _i) V _{eff}
Measurement System								
Probe Calibration	6	Normal	1	1	1	6.00	6.00	∞
Axial Isotropy	0.25	Rectangular	$\sqrt{3}$	1	1	0.14	0.14	∞
Hemispherical Isotropy	1.3	Rectangular	$\sqrt{3}$	1	1	0.75	0.75	∞
Boundary Effects	0.3	Rectangular	$\sqrt{3}$	1	1	0.17	0.17	∞
Linearity	1.65	Rectangular	$\sqrt{3}$	1	1	0.95	0.95	∞
System Detection Limits	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52	∞
Modulation Response	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52	∞
Readout Electronics	0.2	Normal	1	1	1	0.20	0.20	∞
Response Time	0	Rectangular	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	0	Rectangular	$\sqrt{3}$	1	1	0.00	0.00	∞
RF Ambient Noise	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52	∞
RF Ambient Reflection	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52	∞
Probe Positioner	0.7	Rectangular	$\sqrt{3}$	1	1	0.40	0.40	∞
Probe Positioning	6.5	Rectangular	$\sqrt{3}$	1	1	3.75	3.75	∞
Max. SAR Eval.	3.8	Rectangular	$\sqrt{3}$	1	1	2.19	2.19	∞
Dipole Related								
Deviation of exp. dipole	5.3	Rectangular	$\sqrt{3}$	1	1	3.06	3.06	∞
Dipole Axis to Liquid Dist.	2.0	Rectangular	$\sqrt{3}$	1	1	1.15	1.15	∞
Input power & SAR drift	3.3	Rectangular	$\sqrt{3}$	1	1	1.91	1.91	∞
Phantom and Setup								
Phantom Uncertainty (Shape and thickness tolerances)	0.05	Normal	$\sqrt{3}$	1	1	0.03	0.03	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	1.9	Rectangular	1	1	0.84	1.90	1.60	8
Liquid conductivity measurement	5	Normal	1	0.78	0.71	3.90	3.55	∞
Liquid permittivity measurement	5	Rectangular	1	0.23	0.26	1.15	1.30	∞
Liquid conductivity – temperature uncertainty	5	Rectangular	$\sqrt{3}$	0.78	0.71	2.25	2.05	∞
Liquid permittivity – temperature uncertainty	5	Rectangular	$\sqrt{3}$	0.23	0.26	0.66	0.75	∞
Combined Std. Uncertainty						9.38	9.080	
Expanded STD Uncertainty						±18.77%	±18.16%	

Page 30 of 60

11. CONDUCTED POWER MEASUREMENT

Mode	Frequency(MHz) Avg. Burst Power(dBm)		Duty cycle Factor(dBm)	Frame Power(dBm)	
Maximum Power <1	>	· · · · · · · · · · · · · · · · · · ·	<u> </u>		
	824.2	31.84	-9	22.84	
GSM 850	836.6	31.51	-9	22.51	
	848.8	31.37	-9	22.37	
CDDC 050	824.2	30.17	-9	21.17	
GPRS 850 (1 Slot)	836.6	30.24	-9	21.24	
(1 300)	848.8	30.32	-9	21.32	
0000 050	824.2	28.18	-6	22.18	
GPRS 850 (2 Slot)	836.6	28.64	-6	22.64	
(2 300)	848.8	28.28	-6	22.28	
	824.2	26.57	-4.26	22.31	
GPRS 850	836.6	26.43	-4.26	22.17	
(3 Slot)	848.8	26.38	-4.26	22.12	
GPRS 850 (4 Slot)	824.2	25.41	-3	22.41	
	836.6	25.29	-3	22.29	
	848.8	25.46	-3	22.46	
Maximum Power <2	<u></u> 2>				
	824.2	31.30	-9	22.30	
GSM 850	836.6	31.25	-9	22.25	
	848.8	31.11	-9	22.11	
0000000	824.2	30.12	-9	21.12	
GPRS 850 (1 Slot)	836.6	30.21	-9	21.21	
(1 300)	848.8	30.14	-9	21.14	
0000000	824.2	28.43	-6	22.43	
GPRS 850 (2 Slot)	836.6	28.62	-6	22.62	
(Z 310t)	848.8	28.57	-6	22.57	
0000 050	824.2	26.52	-4.26	22.26	
GPRS 850	836.6	26.40	-4.26	22.14	
(3 Slot)	848.8	26.25	-4.26	21.99	
	824.2	25.14	-3	22.14	
GPRS 850	836.6	25.15	-3	22.15	
(4 Slot)	848.8	25.33	-3	22.33	

Page 31 of 60

GSM BAND CONTINUE

Mode	Frequency(MHz)	Avg. Burst Power(dBm)	Duty cycle Factor(dBm)	Frame Power(dBm)	
Maximum Power <1	>				
	1850.2	28.82	-9	19.82	
PCS1900	1880	28.71	-9	19.71	
	1909.8	28.49	-9	19.49	
CDDC1000	1850.2	27.57	-9	18.57	
GPRS1900 (1 Slot)	1880	27.62	-9	18.62	
(1000)	1909.8	27.27	-9	18.27	
CDDC1000	1850.2	25.39	-6	19.39	
GPRS1900 (2 Slot)	1880	25.42	-6	19.42	
(2 3101)	1909.8	25.33	-6	19.33	
00004000	1850.2	23.26	-4.26	19.00	
GPRS1900 (3 Slot)	1880	23.18	-4.26	18.92	
(3 3101)	1909.8	23.32	-4.26	19.06	
	1850.2	22.29	-3	19.29	
GPRS1900 (4 Slot)	1880	22.41	-3	19.41	
	1909.8	22.31	-3	19.31	
Maximum Power <2	!>			1	
	1850.2	28.44	-9	19.44	
PCS1900	1880	28.40	-9	19.40	
	1909.8	28.26	-9	19.26	
ODD04000	1850.2	27.42	-9	18.42	
GPRS1900 (1 Slot)	1880	27.35	-9	18.35	
(1 3101)	1909.8	27.12	-9	18.12	
ODD04000	1850.2	25.31	-6	19.31	
GPRS1900 (2 Slot)	1880	25.40	-6	19.40	
(2 3101)	1909.8	25.28	-6	19.28	
GPRS1900 (3 Slot)	1850.2	23.14	-4.26	18.88	
	1880	23.05	-4.26	18.79	
	1909.8	23.21	-4.26	18.95	
	1850.2	22.19	-3	19.19	
GPRS1900	1880	22.37	-3	19.37	
(4 Slot)	1909.8	22.25	-3	19.25	

Note 1

The Frame Power (Source-based time-averaged Power) is scaled the maximum burst average power based on time slots. The calculated methods are show as following:

Frame Power = Max burst power (1 Up Slot) - 9 dB

Frame Power = Max burst power (2 Up Slot) - 6 dB

Frame Power = Max burst power (3 Up Slot) – 4.26 dB

Frame Power = Max burst power (4 Up Slot) - 3 dB

Note 2:

SAR is not required for GPRS (1 Slot) Mode because its output power is less than of Voice Mode

Page 32 of 60

Bluetooth_V3.0

Modulation	Channel	Frequency(MHz)	Avg. Burst Power (dBm)
	0	2402	3.52
GFSK	39	2441	3.60
	78	2480	3.72
	0	2402	2.67
π /4-DQPSK	39	2441	2.83
	78	2480	2.85
	0	2402	2.64
8-DPSK	39	2441	2.80
	78	2480	2.81

Page 33 of 60

12. TEST RESULTS

12.1. SAR Test Results Summary

12.1.1. Test position and configuration

Head SAR was performed with the device configured in the positions according to IEEE 1528-2013, and Body SAR was performed with the device 5mm from the phantom.

12.1.2. Operation Mode

- 1. Per KDB 447498 D01 v06 ,for each exposure position, if the highest 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional.
- 2. Per KDB 865664 D01 v01r04,for each frequency band, if the measured SAR is ≥0.8W/Kg, testing for repeated SAR measurement is required, that the highest measured SAR is only to be tested. When the SAR results are near the limit, the following procedures are required for each device to verify these types of SAR measurement related variation concerns by repeating the highest measured SAR configuration in each frequency band.
 - (1) When the original highest measured SAR is \geq 0.8W/Kg, repeat that measurement once.
 - (2) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is >1.20 or when the original or repeated measurement is ≥1.45 W/Kg.
 - (3) Perform a third repeated measurement only if the original, first and second repeated measurement is \geq 1.5 W/Kg and ratio of largest to smallest SAR for the original, first and second measurement is \geq 1.20
- 3. Body-worn exposure conditions are intended to voice call operations, therefore GSM voice call mode is selected to be test.
- 4. Per KDB 648474 D04 v01r03,when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤1.2W/Kg, SAR testing with a headset connected is not required.
- 5. Maximum Scaling SAR in order to calculate the Maximum SAR values to test under the standard Peak Power, Calculation method is as follows:

 Maximum Scaling SAR =tested SAR (Max.) ×[maximum turn-up power (mw)/ maximum measurement output power(mw)]

Page 34 of 60

12.1.3. Test Result

SAR MEASUREMENT										
Depth of Liquid (cm):>15				Relative Humidity (%): 52.4						
Product: Mobile Phone										
Test Mode: GSM850 with GMSK modulation										
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±0.2)	SAR (1g) (W/kg)	Max. Turn-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)	
SIM 1 Card										
Left Cheek	voice	190	836.6	0.11	0.034	32	31.51	0.038	1.6	
Left Tilt	voice	190	836.6	0.04	0.038	32	31.51	0.043	1.6	
Right Cheek	voice	190	836.6	-0.02	0.045	32	31.51	0.050	1.6	
Right Tilt	voice	190	836.6	-0.05	0.048	32	31.51	0.054	1.6	
Body back	voice	190	836.6	0.13	0.601	32	31.51	0.673	1.6	
Body front	voice	190	836.6	-0.05	0.043	32	31.51	0.048	1.6	
Left Cheek	GPRS-2 slot	190	836.6	-0.01	0.046	29	28.64	0.050	1.6	
Left Tilt	GPRS-2 slot	190	836.6	0.07	0.060	29	28.64	0.065	1.6	
Right Cheek	GPRS-2 slot	190	836.6	-0.06	0.062	29	28.64	0.067	1.6	
Right Tilt	GPRS-2 slot	190	836.6	-0.07	0.065	29	28.64	0.071	1.6	
Body back	GPRS-2 slot	190	836.6	-0.08	0.733	29	28.64	0.796	1.6	
Body front	GPRS-2 slot	190	836.6	-0.09	0.042	29	28.64	0.046	1.6	
SIM 2 Card										
Right Tilt	GPRS-2 slot	190	836.6	-0.09	0.061	29	28.62	0.067	1.6	
Body back	GPRS-2 slot	190	836.6	0.04	0.700	29	28.62	0.764	1.6	

Note:

[•] When the 1-g Reported SAR is \leq 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498. • The test separation for body is 5mm of all above table.

Page 35 of 60

SAR MEASUREMENT											
Depth of Liqui	d (cm):>15			Relative Humidity (%): 53.8							
Product: Mobi	Product: Mobile Phone										
Test Mode: PCS1900 with GMSK modulation											
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±0.2)	SAR (1g) (W/kg)	Max. Turn-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)		
SIM 1 Card											
Left Cheek	voice	661	1880.0	0.07	0.252	29	28.71	0.269	1.6		
Left Tilt	voice	661	1880.0	0.03	0.403	29	28.71	0.431	1.6		
Right Cheek	voice	661	1880.0	0.15	0.423	29	28.71	0.452	1.6		
Right Tilt	voice	661	1880.0	0.09	0.614	29	28.71	0.656	1.6		
Body back	voice	661	1880.0	-0.08	0.521	29	28.71	0.557	1.6		
Body front	voice	661	1880.0	0.14	0.327	29	28.71	0.350	1.6		
Left Cheek	GPRS-2 slot	661	1880.0	0.07	0.431	26	25.42	0.493	1.6		
Left Tilt	GPRS-2 slot	661	1880.0	-0.15	0.501	26	25.42	0.573	1.6		
Right Cheek	GPRS-2 slot	661	1880.0	0.14	0.480	26	25.42	0.549	1.6		
Right Tilt	GPRS-2 slot	661	1880.0	0.04	0.655	26	25.42	0.749	1.6		
Body back	GPRS-2 slot	512	1850.2	-0.00	0.891	26	25.39	1.025	1.6		
Body back	GPRS-2 slot	661	1880.0	0.01	0.930	26	25.42	1.063	1.6		
Body back	GPRS-2 slot	810	1909.8	0.03	0.756	26	25.33	0.882	1.6		
Body front	GPRS-2 slot	661	1880.0	-0.12	0.358	26	25.42	0.409	1.6		
SIM 2 Card											
Right Tilt	GPRS-2 slot	661	1880.0	0.01	0.621	26	25.40	0.713	1.6		
Body back	GPRS-2 slot	661	1880.0	0.04	0.830	26	25.40	0.953	1.6		

Note:

• When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.

•The test separation for body is 5mm of all above table.

Repeated SAR										
Product: Mobile Phone										
Test Mode: GSM 850 with GMSK modulation & PCS1900 with GMSK modulation										
Position Mode Ch. Fr. (MHz) Power Drift (<±0.2) Once SAR (1g) (W/kg) Power Drift (<±0.2) (W/kg) Power Drift (<±0.2) (W/kg) Power Drift (<±0.2) (W/kg) Power Drift (×±0.2) (W/kg) Power Drift (×±0.2) (W/kg)										
Body back	GPRS-2 slot	661	1880.0	0.02	0.772					1.6

Page 36 of 60

Simultaneous Multi-band Transmission Evaluation: Application Simultaneous Transmission information:

NO	Simultaneous state	Portable Handset			
NO	Simultaneous state	Head	Body-worn		
1	GSM(voice)+Bluetooth(data)	-	Yes		
2	GSM (Data) + Bluetooth(data)	-	Yes		

NOTE:

- 1. Simultaneous with every transmitter must be the same test position.
- 2. KDB 447498 D01, BT SAR is excluded as below table.
- 3. KDB 447498 D01, for handsets the test separation distance is determined by the smallest distance between the outer surface of the device and the user; which is 0mm for head SAR and 5mm for body-worn SAR.
- 4. According to KDB 447498 D01 4.3.1, Standalone SAR test exclusion is as follow:
 - For 100 MHz to 6 GHz and test separation distances \leq 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] • [$\sqrt{f(GHz)}$] ≤ 3.0 for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR³⁰, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation³¹
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

- 5. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.
- 6. According to KDB 447498 D01 4.3.2, simultaneous transmission SAR test exclusion is as follow:
 - (1) Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.
 - (2) Any transmitters and antennas should be considered when calculating simultaneous mode.
 - (3) For mobile phone and PC, it's the sum of all transmitters and antennas at the same mode with same position in each applicable exposure condition
 - (4)When the standalone SAR test exclusion of section 4.3.2 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to det
 - (max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(GHz)/x}$] W/kg for test separation distances \leq 50 mm; where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.
- where x = 7.5 for 1-g SAR, and x = 16.75 for 10-g SAR.
- 7. When the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR to peak location separation ratio. The simultaneous transmitting antennas in each operating mode and exposure condition combination must be considered one pair at a time to determine the SAR to peak location separation ratio to qualify for test exclusion. The ratio is determined by (SAR1 + SAR2)1.5/Ri, rounded to two decimal digits, and must be ≤ 0.04 for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

Page 37 of 60

Estimated SAR		Max Power inc Toler	luding Tune-up ance	Separation Distance (mm)	Estimated SAR (W/kg)
		dBm	mW	Distance (IIIII)	
ВТ	Head	4	2.512	0	0.105
	Body	4	2.512	5	0.105

Maximum test results (GSM) with BT SAR: BT: Head (0 cm gap): 0.105 W/kg and Body (0.5cm gap): 0.105 W/kg

Page 38 of 60

Sum of the SAR for GSM 850& BT:

RF Exposure	Test Position	Simultaneous Transmission Scenario				
Conditions		GSM 850	Bluetooth	Σ1-g SAR(W/Kg)	SPLSR(Yes/No)	
Body-worn (voice)	Rear	0.673	0.105	0.778	No	
	Front	0.048	0.105	0.153	No	
Body-worn (data)	Rear	0.796	0.105	0.901	No	
	Front	0.046	0.105	0.151	No	

Sum of the SAR for GSM 1900 & BT:

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario				
		GSM 1900	Bluetooth	Σ1-g SAR(W/Kg)	SPLSR(Yes/No)	
Body-worn (voice)	Rear	0.557	0.105	0.662	No	
	Front	0.350	0.105	0.455	No	
Body-worn (data)	Rear	1.063	0.105	1.168	No	
	Front	0.409	0.105	0.514	No	

Note:

⁻According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.

⁻SPLSR mean is "The SAR to Peak Location Separation Ratio "

Page 39 of 60

APPENDIX A. SAR SYSTEM CHECK DATA

Test Laboratory: AGC Lab Date: July 20,2016

System Check Head 835 MHz

DUT: Dipole 835MHz Type: SID 835

Communication System CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1;

Frequency: 835 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.90$ mho/m; $\epsilon r = 41.10$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section; Input Power=18dBm

Ambient temperature ($^{\circ}$): 21.3, Liquid temperature ($^{\circ}$): 20.5

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(6.32, 6.32, 6.32); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


Configuration/System Check 835MHz Head/ Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.790 W/kg

Configuration/System Check 835MHz Head / Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.195 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.626 W/kg; SAR(10 g) = 0.372 W/kg Maximum value of SAR (measured) = 0.855 W/kg



Page 40 of 60

Date: July 20,2016

Test Laboratory: AGC Lab System Check Body 835 MHz

DUT: Dipole 835 MHz Type: SID 835

Communication System CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1;

Frequency: 835 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.95$ mho/m; $\epsilon r = 55.28$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section; Input Power=18dBm

Ambient temperature ($^{\circ}$): 21.3, Liquid temperature ($^{\circ}$): 20.8

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(6.31, 6.31, 6.31); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


Configuration/System Check 835MHz Body/ Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.769 W/kg

Configuration/System Check 835MHz Body/ Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.407 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.637 W/kg; SAR(10 g) = 0.398 W/kg Maximum value of SAR (measured) = 0.759 W/kg



Page 41 of 60

Date: July 21,2016

Test Laboratory: AGC Lab System Check Head 1900MHz

DUT: Dipole 1900 MHz; Type: SID 1900

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle:1:1;

Frequency: 1900 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.40$ mho/m; $\epsilon r = 39.83$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section; Input Power=18dBm

Ambient temperature ($^{\circ}$):21.9, Liquid temperature ($^{\circ}$): 21.0

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(5.23, 5.23, 5.23); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


Configuration/System Check 1900MHz Head/ Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 2.59 W/kg

Configuration/System Check 1900MHz Head/Zoom Scan (5x5x7)/ Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 46.045 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 4.41 W/kg

SAR(1 g) = 2.40 W/kg; SAR(10 g) = 1.21 W/kg Maximum value of SAR (measured) = 3.01 W/kg



Page 42 of 60

Date: July 21,2016

Test Laboratory: AGC Lab System Check Body 1900MHz

DUT: Dipole 1900 MHz; Type: SID 1900

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle:1:1;

Frequency: 1900 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.55 \text{ mho/m}$; $\epsilon r = 53.69$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section; Input Power=18dBm

Ambient temperature ($^{\circ}$):21.9, Liquid temperature ($^{\circ}$): 21.1

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(4.83,4.83, 4.83); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


Configuration/System Check 1900MHz Body/ Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 2.87 W/kg

Configuration/System Check 1900MHz Body/Zoom Scan (5x5x7)/ Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 48.369 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 4.91 W/kg

SAR(1 g) = 2.68 W/kg; SAR(10 g) = 1.37 W/kgMaximum value of SAR (measured) = 3.311 W/kg



Page 43 of 60

APPENDIX B. SAR MEASUREMENT DATA

Test Laboratory: AGC Lab Date: July 20,2016

GSM 850 Mid-Tilt-Right <SIM 1>

DUT: Mobile Phone; Type: AZ mobile A1

Communication System: UID 0, Generic GSM (0); Communication System Band: GSM 850; Duty Cycle: 1:8.3; Frequency: 836.6 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.90 \text{ mho/m}$; $\epsilon r = 40.67$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Right Section

Ambient temperature (°C):21.3, Liquid temperature (°C): 20.5

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(6.32, 6.32, 6.32); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

RIGHT HEAD/R-T/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.0564 W/kg

RIGHT HEAD/R-T/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.163 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.108 W/kg

SAR(1 g) = 0.048 W/kg; SAR(10 g) = 0.024 W/kg Maximum value of SAR (measured) = 0.0601 W/kg



Page 44 of 60

Test Laboratory: AGC Lab Date: July 20,2016

GSM 850 Mid- Body- Back(MS)<SIM 1> DUT: Mobile Phone; Type: AZ mobile A1

Communication System: UID 0, Generic GSM (0); Communication System Band: GSM 850; Duty Cycle: 1:8.3; Frequency: 836.6 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.96 \text{ mho/m}$; $\epsilon r = 54.64$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$):21.3, Liquid temperature ($^{\circ}$): 20.8

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(6.31, 6.31, 6.31); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QDOVA002AA;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


BODY/BACK/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.692 W/kg

BODY/BACK/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.841 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.08 W/kg

SAR(1 g) = 0.601 W/kg; SAR(10 g) = 0.391 W/kg Maximum value of SAR (measured) = 0.723 W/kg



Page 45 of 60

Test Laboratory: AGC Lab Date: July 20,2016

GPRS 850 Mid-Tilt - Right (2up) <SIM 1> DUT: Mobile Phone; Type: AZ mobile A1

Communication System: : GPRS-2 Slot; Communication System Band: GSM 850; Duty Cycle: 1:4.2; Frequency: 836.6 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.90$ mho/m; $\epsilon = 40.67$; $\rho = 1000$ kg/m³;

Phantom section: Right Section

Ambient temperature ($^{\circ}$):21.3, Liquid temperature ($^{\circ}$): 20.5

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(6.32, 6.32, 6.32); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


RIGHT HEAD/2ST-R-T/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0945 W/kg

RIGHT HEAD/2ST-R-T/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 6.368 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.152 W/kg

SAR(1 g) = 0.065 W/kg; SAR(10 g) = 0.033 W/kg Maximum value of SAR (measured) = 0.0855 W/kg



Page 46 of 60



Page 47 of 60

Test Laboratory: AGC Lab Date: July 20,2016

GPRS 850 Mid- Body- Back (2up) < SIM 1> DUT: Mobile Phone; Type: AZ mobile A1

Communication System: GPRS-2 Slot; Communication System Band: GSM 850; Duty Cycle: 1:4.2;

Frequency: 836.6 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.96$ mho/m; $\epsilon r = 54.64$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$ C):21.3, Liquid temperature ($^{\circ}$ C): 20.8

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(6.31, 6.31, 6.31); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QDOVA002AA;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

BODY/2ST-BACK/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.775 W/kg

BODY/2ST-BACK/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 25.764 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 0.733 W/kg; SAR(10 g) = 0.455 W/kg



Page 48 of 60



Page 49 of 60

Test Laboratory: AGC Lab Date: July 20,2016

GPRS 850 Mid- Tilt - Right (2up) <SIM 2> DUT: Mobile Phone; Type: AZ mobile A1

Communication System: : GPRS-2 Slot; Communication System Band: GSM 850; Duty Cycle: 1:4.2; Frequency: 836.6 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.90$ mho/m; $\epsilon = 40.67$; $\rho = 1000$ kg/m³;

Phantom section: Right Section

Ambient temperature ($^{\circ}$):21.3, Liquid temperature ($^{\circ}$): 20.5

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(6.32, 6.32, 6.32); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


RIGHT HEAD/2ST-R-T 2/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0945 W/kg

RIGHT HEAD/2ST-R-T 2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.824 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.141 W/kg

SAR(1 g) = 0.061 W/kg; SAR(10 g) = 0.031 W/kg Maximum value of SAR (measured) = 0.0896 W/kg



Page 50 of 60

Test Laboratory: AGC Lab Date: July 20,2016

GPRS 850 Mid- Body- Back (2up) < SIM 2> DUT: Mobile Phone; Type: AZ mobile A1

Communication System: GPRS-2 Slot; Communication System Band: GSM 850; Duty Cycle: 1:4.2;

Frequency: 836.6 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.96$ mho/m; $\epsilon r = 54.64$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$):21.3, Liquid temperature ($^{\circ}$): 20.8

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(6.31, 6.31, 6.31); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QDOVA002AA;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

BODY/2ST-BACK 2/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.669 W/kg

BODY/2ST-BACK 2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.964 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.48 W/kg

SAR(1 g) = 0.700 W/kg; SAR(10 g) = 0.413 W/kg Maximum value of SAR (measured) = 0.838 W/kg



Page 51 of 60

Test Laboratory: AGC Lab Date: July 21,2016

PCS 1900 Mid-Tilt-Right <SIM 1>

DUT: Mobile Phone; Type: AZ mobile A1

Communication System: UID 0, Generic GSM (0); Communication System Band: PCS 1900; Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.37 \text{ mho/m}$; $\epsilon = 40.36$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Right Section

Ambient temperature ($^{\circ}$):21.9, Liquid temperature ($^{\circ}$): 21.0

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(5.23, 5.23, 5.23); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


RIGHT HEAD/R-T/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.915 W/kg

RIGHT HEAD/R-T/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.314 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.40 W/kg

SAR(1 g) = 0.614 W/kg; SAR(10 g) = 0.285 W/kg Maximum value of SAR (measured) = 0.852 W/kg



Page 52 of 60

Test Laboratory: AGC Lab Date: July 21,2016

PCS 1900 Mid-Body- Back(MS)<SIM 1> DUT: Mobile Phone; Type: AZ mobile A1

Communication System: UID 0, Generic GSM (0); Communication System Band: PCS 1900; Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.52 \text{ mho/m}$; $\epsilon = 54.22$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$):21.9, Liquid temperature ($^{\circ}$): 21.1

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(4.83,4.83, 4.83); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


BODY/BACK/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.635 W/kg

BODY/BACK/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.518 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.974 W/kg

SAR(1 g) = 0.521 W/kg; SAR(10 g) = 0.331 W/kg Maximum value of SAR (measured) = 0.699 W/kg



Page 53 of 60

Test Laboratory: AGC Lab Date: July 21,2016

GPRS 1900 Mid-Tilt-Right (2up) < SIM 1> DUT: Mobile Phone; Type: AZ mobile A1

Communication System: GPRS-2 Slot; Communication System Band: PCS 1900; Duty Cycle: 1:4.2;

Frequency: 1880 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.37 \text{ mho/m}$; $\epsilon r = 40.36$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Right Section

Ambient temperature ($^{\circ}$ C):21.9, Liquid temperature ($^{\circ}$ C): 21.0

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(5.23, 5.23, 5.23); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


RIGHT HEAD/2ST-R-T/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.948 W/kg

RIGHT HEAD/2ST-R-T/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 18.360 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 0.655 W/kg; SAR(10 g) = 0.319 W/kg Maximum value of SAR (measured) = 0.885 W/kg



Report No.: AGC05621160701FH01 Page 54 of 60



Page 55 of 60

Test Laboratory: AGC Lab Date: July 21,2016

GPRS 1900 Mid-Body- Back (2up) < SIM 1> DUT: Mobile Phone; Type: AZ mobile A1

Communication System: GPRS-2 Slot; Communication System Band: PCS 1900; Duty Cycle: 1:4.2;

Frequency: 1880 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.52 \text{ mho/m}$; $\epsilon r = 54.22$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$):21.9, Liquid temperature ($^{\circ}$): 21.1

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(4.83,4.83, 4.83); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398: Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

BODY/2ST-BACK/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 1.06 W/kg

BODY/2ST-BACK/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 22.888 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.72 W/kg

SAR(1 g) = 0.930 W/kg; SAR(10 g) = 0.530 W/kg Maximum value of SAR (measured) = 1.18 W/kg



Page 56 of 60



Page 57 of 60

Test Laboratory: AGC Lab Date: July 21,2016

GPRS 1900 Mid-Tilt-Right (2up) < SIM 2> DUT: Mobile Phone; Type: AZ mobile A1

Communication System: GPRS-2 Slot; Communication System Band: PCS 1900; Duty Cycle: 1:4.2;

Frequency: 1880 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.37$ mho/m; $\epsilon r = 40.36$; $\rho = 1000$ kg/m³;

Phantom section: Right Section

Ambient temperature ($^{\circ}$):21.9, Liquid temperature ($^{\circ}$): 21.0

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(5.23, 5.23, 5.23); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


RIGHT HEAD/2ST-R-T 2/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.881 W/kg

RIGHT HEAD/2ST-R-T 2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.101 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.30 W/kg

SAR(1 g) = 0.621 W/kg; SAR(10 g) = 0.312 W/kg Maximum value of SAR (measured) = 0.828 W/kg



Page 58 of 60

Date: July 21,2016

Test Laboratory: AGC Lab

GPRS 1900 Mid-Body- Back (2up) < SIM 2> DUT: Mobile Phone; Type: AZ mobile A1

Communication System: GPRS-2 Slot; Communication System Band: PCS 1900; Duty Cycle: 1:4.2;

Frequency: 1880 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.52 \text{ mho/m}$; $\epsilon r = 54.22$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$ C):21.9, Liquid temperature ($^{\circ}$ C): 21.1

DASY Configuration:

- Probe: ES3DV3 SN3337; ConvF(4.83,4.83, 4.83); Calibrated:10/01/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398: Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

BODY/2ST-BACK 2/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.984 W/kg

BODY/2ST-BACK 2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.149 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.47 W/kg

SAR(1 g) = 0.830 W/kg; SAR(10 g) = 0.495 W/kg Maximum value of SAR (measured) = 1.03 W/kg



Page 59 of 60

Repeated SAR

Test Laboratory: AGC Lab Date: July 21,2016

GPRS 1900 Mid-Body- Back (2up) < SIM 1> DUT: Mobile Phone; Type: AZ mobile A1

Communication System: GPRS-2 Slot; Communication System Band: PCS 1900; Duty Cycle: 1:4.2;

Frequency: 1880 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.52 \text{ mho/m}$; $\epsilon r = 54.22$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$):21.9, Liquid temperature ($^{\circ}$): 21.1

DASY Configuration:

• Probe: ES3DV3 – SN3337; ConvF(4.83,4.83, 4.83); Calibrated:10/01/2015;

- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 02/02/2016
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

BODY/2ST-BACK-REPEATED/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.922 W/kg

BODY/2ST-BACK-REPEATED/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.555 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.772 W/kg; SAR(10 g) = 0.467 W/kg Maximum value of SAR (measured) = 0.955 W/kg



Page 60 of 60

APPENDIX C. TEST SETUP PHOTOGRAPHS & EUT PHOTOGRAPHS

Refer to Attached files.

APPENDIX D. CALIBRATION DATA

Refer to Attached files.