

RF TEST REPORT

Report No.: 20250517G11391X-W2

Product Name: BLUETOOTH DIGITAL SMART KEY

Model No. : XSBTK0

FCC ID: 2AI4T-XSBTK0

Applicant: Shenzhen Xhorse Electronics Co., Ltd.

Address: Floor 28, Block A, Building NO.6, International Innovation Valley, Nanshan District, Shenzhen

Dates of Testing: 05/20/2025–06/19/2025

Issued by: CCIC Southern Testing Co., Ltd.

Lab Location: Electronic Testing Building, No.43, Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China.

Query E-Mail: manager@ccic-set.com

Feedback E-Mail: integrity@ccic-set.com

Report Query Tel: 0755-26627338

Feedback Tel: 0755-86185963

This test report consists of 41 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.

Test Report

Product.....: BLUETOOTH DIGITAL SMART KEY

Trade Name: Xhorse

Applicant.....: Shenzhen Xhorse Electronics Co., Ltd.


Applicant Address.....: Floor 28, Block A, Building NO.6, International Innovation Valley, Nanshan District, Shenzhen

Manufacturer.....: Shenzhen Xhorse Electronics Co., Ltd.


Manufacturer Address.....: Floor 28, Block A, Building NO.6, International Innovation Valley, Nanshan District, Shenzhen

Test Standards.....: 47 CFR Part 15 Subpart C 15.247
ANSI C63.10-2020

Test Result.....: Pass

Tested by:  2025.06.19

Chuiwang Zhang, Test Engineer

Reviewed by:  2025.06.19
Sun Jiaohui, Senior Engineer


Approved by:  2025.06.19
Chris You, Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1. EUT Description	5
1.2. Test Standards and Results	6
1.3. Table for Supporting Units	7
1.4. EUT Operation Test Setup	7
1.5. Test environment and mode	7
1.6. Laboratory Facilities and Accreditation Certificate	8
2. TEST REQUIREMENTS	9
2.1. Antenna requirement	9
2.2. Maximum Conducted Output Power	10
2.3. 6 dB and 99% Bandwidth	12
2.4. Power spectral density (PSD)	14
2.5. Conducted Band Edges and Spurious Emissions	16
2.6. Radiated Band Edge and Spurious Emission	18
2.7. AC Power Line Conducted Emission	25
3. LIST OF MEASURING EQUIPMENT	27
4. UNCERTAINTY OF EVALUATION	28
APPENDIX A	29

Change History		
Issue	Date	Reason for change
1.0	2025.06.19	First edition

1. General Information

1.1. EUT Description

Product Name	BLUETOOTH DIGITAL SMART KEY
EUT supports Radios application	Bluetooth LE
Frequency Range	2402 MHz–2480 MHz
Channel Number	3
Bit Rate of Transmitter	1 Mbps
Modulation Type	GFSK
Antenna Type	Internal antenna
Antenna Gain	2.87 dBi
Power supply	DC 12 V

Note 1: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

Note 2: The information of antenna gain and cable loss is provided by the manufacturer and our lab is not responsible for the accuracy of the antenna gain and cable loss information.

1.2. Test Standards and Results

The purpose of the report is to conduct testing according to the following FCC certification standards:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart C	Radio Frequency Devices
2	ANSI C63.10-2020	American National Standard for Testing Unlicensed Wireless Devices
3	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for Compliance Measurement on Digital Transmission Systems, Frequency Hopping Spread Spectrum Systems, and Hybrid System Devices Operating under Section 15.247 of the FCC Rules

Test detailed items/section required by FCC rules and results are as below:

No.	Section in CFR 47	Description	Result
1	15.203 15.247(c)	Antenna Requirement	PASS
2	15.247(b)(3)	Maximum Conducted Output Power	PASS
3	15.247(a)(2)	6 dB and 99% Bandwidth	PASS
4	15.247(d)	Conducted Band Edges and Spurious Emission	PASS
5	15.247(e)	Power spectral density (PSD)	PASS
6	15.207	AC Power Line Conducted Emission	N/A ^{Note 3}
7	15.209 15.205 15.247(d)	Radiated Band Edges and Spurious Emission	PASS

Note 1: The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10-2020.

Note 2: These RF tests were performed according to the method of measurements prescribed in KDB 558074 D01 15.247 Meas Guidance v05r02.

Note 3: Not applicable, the EUT is powered by a DC12 V supply.

40 channels are provided for Bluetooth LE.

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note: The EUT only supports channels 0, 12 and 39.

Test Items	Modulation Type	Data Rate	Channel
Maximum Conducted Output Power Power Spectral Density 6 dB and 99% Bandwidth Conducted Spurious Emission Radiated Spurious Emission	GFSK	1 Mbps	0/12/39
Band Edge	GFSK	1 Mbps	0/39

1.3. Table for Supporting Units

No.	Equipment	Model Name	Manufacturer	FCC ID
1	KEY TOOL MIDI	XDKMD	Xhorse	2AI4T-XDKMD

1.4. EUT Operation Test Setup

For RF test items, an engineering test program was provided and enable to make EUT transmitting.

1.5. Test environment and mode

During the measurement, the environmental conditions were within the listed ranges:

Operating Environment:	
Temperature	15°C–35°C
Humidity	30%–60%
Atmospheric Pressure	86 kPa–106 kPa
Test mode:	
Continuously transmitting mode	Keep the EUT in continuous transmitting with modulation

1.6. Laboratory Facilities and Accreditation Certificate

CCIC-SET Lab 1

Address: Electronic Testing Building, No.43, Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China

FCC-Registration No.: CN1283

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until Jun. 30th, 2025.

ISED Registration: 11185A, CAB number: CN0064

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A on Aug. 04, 2016, valid time is until Jun. 30th, 2025.

A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

CNAS L1659

CCIC Southern Testing Co., Ltd. CCIC is a third party testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

CCIC-SET Lab 4

Address: No.125, Hongmei Section, Wangsha Road, Hongmei Town, Dongguan City, Guangdong Province, China

CNAS L1659

CCIC Southern Testing Co., Ltd. CCIC is a third party testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

2. Test Requirements

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

And according to FCC 47 CFR Section 15.247(c), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

2.1.2. Antenna Information

Antenna Category: Internal Antenna

A internal Antenna was soldered to the antenna port of EUT via an adaptor cable, can't be removed.

Antenna General Information:

No.	EUT	Operating frequency range	Ant. Type	Ant. Gain
1	BLUETOOTH DIGITAL SMART KEY	2402–2480MHz	Internal	2.87 dBi

2.1.3. Result: comply

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Maximum Conducted Output Power


2.2.1. Limit of Maximum Conducted Output Power

For DTSs employing digital modulation techniques operating in the bands 2400–2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W.

2.2.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.2.3. Test Setup



2.2.4. Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 Section 11.9.1.1.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings:
RBW \geq DTS bandwidth / VBW \geq 3*RBW / Sweep time: Auto couple / Detector mode: Peak / Trace mode: Max hold / Allow trace to fully stabilize / Use peak marker function to determine the peak amplitude level.
5. Record the measurement results in the test report.

2.2.5. Test Result of Maximum Conducted Output Power

Please refer to Appendix A for detail.

2.3. 6 dB and 99% Bandwidth


2.3.1. Limit of 6 dB and 99% Bandwidth

The minimum 6 dB Occupied bandwidth shall be at least 500 kHz.

2.3.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.3.3. Test Setup



2.3.4. Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 Section 11.8.1.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the spectrum analyzer “Channel Bandwidth” function to easurement the 6 dB EBW and 99% OBW.
For 6 dB EBW Use the following spectrum analyzer settings:
RBW: 100 kHz / VBW: 300 kHz / Detector: Peak / Trace mode: Max hold / Sweep time: Auto couple / Allow trace to fully stabilize.
5. For 99% OBW Use the following spectrum analyzer settings:
Set RBW = approximately 1% EBW or 1.5 times to 5.0 times the OBW, $VBW \geq 3 \times RBW$.
6. Record the measurement results in the test report.

2.3.5. Test Results of 6 dB and 99% Bandwidth

Please refer to Appendix A for detail.

2.4. Power spectral density (PSD)


2.4.1. Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

2.4.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.4.3. Test Setup



2.4.4. Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 Section 11.10.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings:

Set instrument center frequency to DTS channel center frequency / Set the span to 1.5 times the DTS bandwidth / RBW: 3 kHz / VBW: 10 kHz / Detector: Peak / Sweep time: Auto couple / Trace mode: Max hold / Allow trace to fully stabilize / Use the peak marker function to determine the maximum power level.

5. Record the measurement results in the test report.

2.4.5. Test Results of Power spectral density

Please refer to Appendix A for detail.

2.5. Conducted Band Edges and Spurious Emissions


2.5.1. Limit of Conducted Band Edges and Spurious Emissions

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that.

2.5.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.5.3. Test Setup



2.5.4. Test Procedure

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 Section 11.11 and 11.13.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings:

Reference level measurement: Set spectrum analyzer center frequency to DTS channel center frequency / Set the span to ≥ 1.5 times the DTS bandwidth / RBW: 100 kHz / VBW: 300 kHz / Detector: Peak / Sweep time: Auto couple / Trace mode: Max hold / Allow trace to fully stabilize / Use the peak marker function to determine the maximum PSD level and attenuate it by 20 dB.

Emission level measurement: Set the center frequency and span to encompass frequency range to be measured / RBW: 100 kHz / VBW: 300 kHz / Detector: Peak / Sweep time: Auto couple / Trace mode: Max hold / Allow trace to fully stabilize / Use the peak marker function to determine the maximum amplitude level.
5. Record the measurement results in the test report.

2.5.5. Test Results of Conducted Band Edges and Spurious Emissions

Please refer to Appendix A for detail.

2.6. Radiated Band Edge and Spurious Emission

2.6.1. Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level. If the transmitter uses an RMS average conducted power limit, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

§15.209(a) Radiated emission limits:

Frequency (MHz)	Field Strength (μ V/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Restricted bands of operation refer to §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41	/	/	/

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.


²Above 38.6.

2.6.2. Measuring Instruments


The measuring equipment is listed in the section 3 of this test report.

2.6.3. Test Setup


For radiated emissions from 9 kHz to 30 MHz



For radiated emissions from 30 MHz to 1 GHz



For radiated emissions above 1 GHz



2.6.4. Test Procedures

1. The EUT was placed on the top of a rotating table 0.8 m for below 1 GHz and 1.5 m for above 1 GHz above the ground at a 3 meters semi-anechoic chamber.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then

reported in a data sheet.

7. For the radiated emission test above 1 GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $> 98\%$) for Average detection (AV) at frequency above 1 GHz.
4. All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


2.6.5. Test Results of Radiated Band Edge and Spurious Emission

For 9 kHz to 30 MHz, The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

For 30 MHz to 1 GHz, All of the EUT Configure mode were tested and found 1 Mbps_2426 MHz channel is the worst mode, the worst case is recorded in this report.

For 30 MHz to 1000 MHz

Test site:	3 M anechoic chamber	Environment:	Temp: 23°C; Humi: 48%; 101 kPa
Operator:	Huang Chaoming	Test Date:	2025.05.27
Test Mode:	BLE - TX	Test Result:	Pass




Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Height (cm)	Polarity	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dB μ V/m)
41.680000	29.00	120.000	100.0	H	13.3	11.00	40.0
92.200000	21.07	120.000	100.0	H	9.2	22.43	43.5
98.040000	25.81	120.000	100.0	H	10.0	17.69	43.5
162.200000	26.30	120.000	100.0	H	12.0	17.20	43.5
169.960000	23.93	120.000	100.0	H	11.9	19.57	43.5
210.800000	18.71	120.000	100.0	H	12.1	24.79	43.5

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB).
3. Margin value = Limit value - Emission Level.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Only the antenna height (from 1 m to 4 m) at maximum reading are recorded.

Test site:	3 M anechoic chamber	Environment:	Temp: 23°C; Humi: 48%; 101 kPa
Operator:	Huang Chaoming	Test Date:	2025.05.27
Test Mode:	BLE - TX	Test Result:	Pass



Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Height (cm)	Polarity	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dB μ V/m)
31.960000	21.00	120.000	100.0	V	18.3	19.00	40.0
41.680000	36.68	120.000	100.0	V	13.3	3.32	40.0
51.400000	14.62	120.000	100.0	V	8.4	25.38	40.0
61.120000	12.11	120.000	100.0	V	5.6	27.89	40.0
162.200000	26.01	120.000	100.0	V	12.0	17.49	43.5
208.840000	17.01	120.000	100.0	V	12.1	26.49	43.5

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB).
3. Margin value = Limit value - Emission Level.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Only the antenna height (from 1 m to 4 m) at maximum reading are recorded.

For 1 GHz to 25 GHz

GFSK_2402 MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
2390.00	55.22	74.00	-18.78	1.50	200	58.31	-3.09	Horizontal	Peak
2390.00	44.86	54.00	-9.14	1.50	200	47.95	-3.09	Horizontal	Average
4804.00	58.08	74.00	-15.92	1.50	200	56.82	1.26	Horizontal	Peak
4804.00	51.05	54.00	-2.95	1.50	200	49.79	1.26	Horizontal	Average
7206.00	52.81	74.00	-21.19	1.50	200	46.64	6.17	Horizontal	Peak
7206.00	43.22	54.00	-10.78	1.50	200	37.05	6.17	Horizontal	Average
2390.00	54.69	74.00	-19.31	1.50	180	57.78	-3.09	Vertical	Peak
2390.00	45.01	54.00	-8.99	1.50	180	48.10	-3.09	Vertical	Average
4804.00	48.02	74.00	-25.98	1.50	180	46.76	1.26	Vertical	Peak
4804.00	38.61	54.00	-15.39	1.50	180	37.35	1.26	Vertical	Average
7206.00	54.83	74.00	-19.17	1.50	180	48.66	6.17	Vertical	Peak
7206.00	44.91	54.00	-9.09	1.50	180	38.74	6.17	Vertical	Average

GFSK_2480 MHz

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
2483.50	55.82	74.00	-18.18	1.50	200	60.57	-4.75	Horizontal	Peak
2483.50	45.61	54.00	-8.39	1.50	200	50.36	-4.75	Horizontal	Average
4960.00	47.14	74.00	-26.86	1.50	200	46.90	0.24	Horizontal	Peak
4960.00	38.10	54.00	-15.90	1.50	200	37.86	0.24	Horizontal	Average
7440.00	50.98	74.00	-23.02	1.50	200	45.16	5.82	Horizontal	Peak
7440.00	42.24	54.00	-11.76	1.50	200	36.42	5.82	Horizontal	Average
2483.50	55.05	74.00	-18.95	1.50	180	59.80	-4.75	Vertical	Peak
2483.50	45.51	54.00	-8.49	1.50	180	50.26	-4.75	Vertical	Average
4960.00	59.58	74.00	-14.42	1.50	180	59.34	0.24	Vertical	Peak
4960.00	51.71	54.00	-2.29	1.50	180	51.47	0.24	Vertical	Average
7440.00	51.37	74.00	-22.63	1.50	180	45.55	5.82	Vertical	Peak
7440.00	42.23	54.00	-11.77	1.50	180	36.41	5.82	Vertical	Average

Remark:

1. *Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)*
2. *Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB)*
3. *Margin value = Emission Level – Limit value*
4. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
5. *Only the antenna height (from 1 m to 4 m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.*

2.7. AC Power Line Conducted Emission

2.7.1. Limit of AC Power Line Conducted Emission


For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15–0.50	66 to 56	56 to 46
0.50–5	56	46
5–30	60	50

2.7.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.7.3. Test Setup



2.7.4. Test Procedures

1. The EUT was placed 0.4 meters from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 micrometry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

2.7.5. Test Results of Conducted Emission

Note: Not applicable, the EUT is powered by a DC 12 V supply.

3. List of measuring equipment

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	5M Anechoic Chamber	Albatross	SAC-5MAC 12.8x6.8x6.4m	A0304210	2023.08.01	2026.07.31
2	EMI Test Receiver	ROHDE&SCHWARZ	ESW26	A180502935	2024.12.26	2025.12.25
3	Loop Antenna	SCHWARZBECK	FMZB 1519-60 C	A240204134	2023.12.13	2026.12.12
4	Broadband antenna (30MHz~1GHz)	R&S	HL562	A0304224	2023.06.08	2026.06.07
5	EMI Horn Ant. (1-18G)	ETC	MCTD-1209	A150402241	2023.05.16	2026.05.15
6	Horn antenna (18GHz~26.5GHz)	AR	AT4510	A0804450	2023.06.01	2026.05.31
7	Amplifier 30M~1GHz	TESEQ	CBA1G-600B	A190503534	2024.09.05	2025.09.04
8	Amplifier 1G~18GHz	MILMEGA	AS0104R-800/400	A160302517	2024.12.26	2025.12.25
9	Spectrum Analyzer	KEYSIGHT	N9020A	A240604409	2024.08.22	2025.08.21
10	Test Receiver	R&S	ESIB7	A0501375	2025.01.13	2026.01.12
11	Broadband Ant.	ETC	MCTD 2786	A150402240	2023.05.22	2026.05.21
12	3M Anechoic Chamber	Albatross	SAC-3MAC 9*6*6m	A0412375	2024.02.27	2027.02.26
13	Test Receiver	KEYSIGHT	N9038A	A141202036	2024.06.05	2025.06.04
					2025.06.04	2026.06.03
14	LISN	ROHDE&SCHWARZ	ENV216	A140701847	2025.04.14	2026.04.13
15	Cable(9kHz~30MHz)	/	/	C230800587	2023.08.21	2026.08.20
16	Cable(30MHz~18GHz)	/	XSMJA750-SMN M(RA)-12M	C230800588	2023.08.21	2026.08.20
17	Cable(18GHz~40GHz)	/	SUCOFLEX102	C230800590	2023.08.21	2026.08.20
18	10dB Attenuator (Radiated)	Schwarzbeck	DGA 9552 N	A181103396	2024.12.31	2025.12.30
19	10dB Attenuator (Conducted)	XINQY	XQY-SMAJKS-08- 2W-10dB	A250204143	2025.04.29	2026.04.28

4. Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2020. All the measurement uncertainty value were shown with a coverage $K = 2$ to indicate 95% level of confidence . The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of AC Power Line Conducted Emission Measurement (150 kHz~30 MHz)

Measuring Uncertainty for a level of confidence of 95% ($U = 2U_{C(y)}$)	2.8 dB
--	--------

Uncertainty of Radiated Emission Measurement (9 kHz~30 MHz)

Measuring Uncertainty for a level of confidence of 95% ($U = 2U_{C(y)}$)	3.5 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz~1 GHz)

Measuring Uncertainty for a level of confidence of 95% ($U = 2U_{C(y)}$)	3.91 dB
--	---------

Uncertainty of Radiated Emission Measurement (1 GHz~18 GHz)

Measuring Uncertainty for a level of confidence of 95% ($U = 2U_{C(y)}$)	4.5 dB
--	--------

Uncertainty of Radiated Emission Measurement (18 GHz~40 GHz)

Measuring Uncertainty for a level of confidence of 95% ($U = 2U_{C(y)}$)	4.9 dB
--	--------

Uncertainty of RF Conducted Measurement (9 kHz~40 GHz)

Measuring Uncertainty for a level of confidence of 95% ($U = 2U_{C(y)}$)	1.3 dB
--	--------

Appendix A

Duty Cycle

Test Result and Data


Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	DC Factor
BLE_1M	Ant1	2402	0.40	25.00	1.60	17.96
BLE_1M	Ant1	2426	0.50	27.50	1.82	17.40
BLE_1M	Ant1	2480	0.40	27.50	1.45	18.39

Maximum Conducted Output Power

Test Result and Data

Test Mode	Antenna	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Verdict
BLE_1M	Ant1	2402	6.70	≤30	PASS
BLE_1M	Ant1	2426	7.14	≤30	PASS
BLE_1M	Ant1	2480	6.81	≤30	PASS

Test Graphs




6dB Bandwidth

Test Result and Data

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	0.588	0.5	PASS
BLE_1M	Ant1	2426	0.561	0.5	PASS
BLE_1M	Ant1	2480	0.609	0.5	PASS

Test Graphs



99% Occupied Bandwidth

Test Result and Data

Test Mode	Antenna	Frequency [MHz]	99% OBW [MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	1.0187	---	---
BLE_1M	Ant1	2426	1.0196	---	---
BLE_1M	Ant1	2480	1.0048	---	---

Test Graphs




Power Spectral Density

Test Result and Data

Test Mode	Antenna	Frequency [MHz]	Result [dBm/3 kHz]	Limit [dBm/3 kHz]	Verdict
BLE_1M	Ant1	2402	-7.61	≤8.00	PASS
BLE_1M	Ant1	2426	-7.81	≤8.00	PASS
BLE_1M	Ant1	2480	-7.87	≤8.00	PASS

Test Graphs




Conducted Band Edges

Test Result and Data

Test Mode	Antenna	ChName	Frequency [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
BLE_1M	Ant1	Low	2402	4.27	-50.41	≤-15.73	PASS
BLE_1M	Ant1	High	2480	4.73	-53.07	≤-15.27	PASS

Test Graphs




Conducted Spurious Emissions

Test Result and Data

Test Mode	Antenna	Frequency [MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
BLE_1M	Ant1	2402	0~Reference	6.58	6.58	---	PASS
BLE_1M	Ant1	2402	30~25000	6.58	-45.75	≤-13.42	PASS
BLE_1M	Ant1	2426	0~Reference	6.78	6.78	---	PASS
BLE_1M	Ant1	2426	30~25000	6.78	-42.49	≤-13.22	PASS
BLE_1M	Ant1	2480	0~Reference	6.52	6.52	---	PASS
BLE_1M	Ant1	2480	30~25000	6.52	-39.43	≤-13.48	PASS

Test Graphs



END OF REPORT