

FCC RADIO TEST REPORT FCC ID: 2AI97-K19

Product: Mobile phone

Trade Name: N/A

Model No.: K19

Serial Model: N/A

Report No.: NTEK-2016NT06166528F3

Issue Date: 05 Jul. 2016

Prepared for

SHENZHEN HUATONG TECHNOLOGY CO.,LTD.

Room2088, 20th Floor, CBlock, Electronic Technology Building,
Huaqiang North, Futian Area, Shenzhen

Prepared by

NTEK TESTING TECHNOLOGY CO., LTD.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen, P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599 Website: www.ntek.org.cn



TABLE OF CONTENTS

1	TE	ST RESULT CERTIFICATION	3
2	SU	MMARY OF TEST RESULTS	4
3	FA	CILITIES AND ACCREDITATIONS	5
	3.1	FACILITIES	
	3.2 3.3	LABORATORY ACCREDITATIONS AND LISTINGS	
4	GE	ENERAL DESCRIPTION OF EUT	6
5	DE	SCRIPTION OF TEST MODES	8
6	SE	TUP OF EQUIPMENT UNDER TEST	9
	6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM	
	6.2 6.3	SUPPORT EQUIPMENTEQUIPMENTS LIST FOR ALL TEST ITEMS	10
7	TE	ST REQUIREMENTS	
	7.1	CONDUCTED EMISSIONS TEST	12
	7.2	FIELD STRENGTH OF SPURIOUS RADIATION	
	7.3	EFFECTIVE RADIATED POWER AND EFFECTIVE ISOTROPIC RADIATED POWER	
	7.4	CONDUCTED OUTPUT POWER	
	7.5	FREQUENCY STABILITY	
	7.6	PEAK-TO-AVERAGE RATIO	
	7.7	26DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH	
	7.8	CONDUCTED BAND EDGE	
	7.9	CONDUCTED SPURIOUS EMISSION AT ANTENNA TERMINAL	47



1 TEST RESULT CERTIFICATION

Applicant's name:	SHENZHEN HUATONG TECHNOLOGY CO.,LTD.		
Address:	Room2088, 20th Floor, CBlock, Electronic Technology Building,		
	Huaqiang North, Futian Area, Shenzhen		
Manufacture's Name:	SHENZHEN HUATONG TECHNOLOGY CO.,LTD.		
Address:	Room2088, 20th Floor, CBlock, Electronic Technology Building,		
	Huaqiang North, Futian Area, Shenzhen		
Product description			
Product name:	Mobile phone		
Model and/or type reference:	K19		
Serial Model:	N/A		

Measurement Procedure Used:

APPLICABLE STANDARDS				
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT			
47 CFR Part 2, Part 22H, Part 24E				
ANSI/ TIA/ EIA-603-D-2010	Complied			
FCC KDB 971168 D01 Power Meas. License Digital Systems v02v02				

This device described above has been tested by NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK Testing Technology Co., Ltd., this document may be altered or revised by NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test	: <u> </u>	:16 Jun. 2016 ~ 05 Jul. 2016		
Testing Engineer	:	(Susan Su)		
Technical Manager	:	Jusen chen)		
Authorized Signatory	:	Sam. Chew (Sam Chen)		



2 SUMMARY OF TEST RESULTS

FCC Part22, Subpart H/ FCC Part24, Subpart E					
FCC Rule	FCC Rule Test Item				
2.1046	Conducted Output Power	PASS			
24.232(d)	Peak-to-Average Ratio	PASS			
2.1049 22.917(b) 24.238(b)	Occupied Bandwidth	PASS			
2.1051 22.917(a) 24.238(a)	1051 917(a) Band Edge				
22.913(a)(2)	22.913(a)(2) Effective Radiated Power				
24.232(c)	24.232(c) Equivalent Isotropic Radiated Power				
2.1053 22.917(a) 24.238(a)	Field Strength of Spurious Radiation	PASS			
2.1055 22.355 24.235	2.1055 22.355 Frequency Stability for Temperature &				
2.1051 22.917(a) 24.238(a)	Conducted Emission	PASS			

Remark:

- "N/A" denotes test is not applicable in this Test Report.
 All test items were verified and recorded according to the standards and without any deviation during the test.
- No modifications are made to the EUT during all test items.
 This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab. : Accredited by CNAS, 2014.09.04

The certificate is valid until 2017.09.03

The Laboratory has been assessed and proved to be in compliance with

CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)

The Certificate Registration Number is L5516.

Accredited by Industry Canada, August 29, 2012 The Certificate Registration Number is 9270A-1.

Name of Firm : NTEK Testing Technology Co., Ltd

Site Location : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang

Street, Bao'an District, Shenzhen P.R. China.

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

		: -: -: -: -: -: -: -: -: -: -: -: -:
No.	Item	Uncertainty
1	Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5dB

Page 6 of 53



4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification						
Equipment	Mobile phone					
Trade Name N/A						
FCC ID 2AI97-K19						
Model No.	K19					
Serial Model	N/A					
Model Difference	N/A					
Operating Frequency	☑GSM850: TX824.2MHz~848.8MHz /RX869.2MHz~893.8MHz; ☑PCS1900: TX1850.2MHz~1909.8MHz /RX1930.2MHz~1989.8MHz;					
Modulation ⊠GMSK for GSM/GPRS;						
Number of Channels						
GPRS Class						
SIM CARD	The Phone has dual SIM Card sockets but only one of the dual SIM Card can be transmitting when the two SIM Cards are inserting the phone together ☐IMEI Code 1: 352751019523267 IMEI Code 2: 352273017386340					
Antenna Type	FPCB Antenna					
Antenna Gain	1 dBi					
Power supply	⊠Adapter supply: Model: YTL0501000EU-1A Input: 100-240V~, 50/60Hz 0.15A Output: DC 5V1000mA					
HW Version	Z3108-MB-V1.0					
SW Version	sc6531D_32X32_Z3108_K19_1_Welcome_YXP_Sam_VB_whatsapp_Tourch_20160713					

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual. The High Voltage 4.2V and Low Voltage 3.2V was declared by manufacturer, The EUT couldn't be operate normally with higher or lower voltage.



Revision History

Version	Description	Issued Date
Rev.01	Initial issue of report	Jul 05, 2016
		· · · · · · · · · · · · · · · · · · ·



5 DESCRIPTION OF TEST MODES

During the testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication Tester(CMU 200) to ensure max power transmission and proper modulation. Three channels (The low channel, the middle channel and the high channel) were chosen for testing on both GPRS850 and GPRS1900 frequency band.

Note: GSM/GPRS 850, GSM/GPRS 1900, HSDPA band II, HSUPA band II, HSDPA band V, HSUPA band V modes have been tested during the test. the worst condition (GSM850, GSM1900 RMC 12.2k) be recorded in the test report if no other modes test data.

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

- 1. 30 MHz to 10th harmonic for GSM850/UMTS FDD Band V.
- 2. 30 MHz to 10th harmonic for GSM1900/UMTS FDD Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

	Test Modes					
Band	For Conducted Test Cases	For Radiated Test Cases				
GSM 850 GSM Link		GSM Link				
GSM 1900 GSM Link		GSM Link				


Test Frequency and Channels:


Frequency	⊠ GSM 850		⊠GSM 1900	
Band	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH_H	251	848.8	810	1909.8
CH_M	189	836.4	661	1880.0
CH_L	128	824.2	512	1850.2





6 SETUP OF EQUIPMENT UNDER TEST


6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM
















6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Note
E-1	Mobile phone	N/A	K19	XXXX-K19	EUT
E-2.	Adapter	N/A	YTL0501000EU-1A	N/A	Peripherals
E-3.	Earphone	N/A	2688	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	USB Cable	NO	NO	1.0m
C-2	Earphone	NO	NO	0.8m
C-3	RF Cable	NO	NO	0.5m
C-4	RF Cable	NO	NO	0.5m
C-5	RF Cable	NO	NO	0.5m

Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>[Length]</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".



6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Item	Kind of	Manufacturer	Type No.	Serial No.	Last	Calibrated	Calibration
ILEIII	Equipment	Manufacture	Type No.	Seliai IVO.	calibration	until	period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2015.07.06	2016.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2016.06.07	2017.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2015.07.06	2016.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2016.06.07	2017.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2016.06.07	2017.06.06	1 year
6	Horn Antenna	EM	EM-AH-1018 0	2011071402	2015.07.06	2016.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2015.07.06	2016.07.05	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2016.06.08	2017.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2015.07.06	2016.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.0 5	2015.07.06	2016.07.05	1 year
12	Test Cable	N/A	R-01	N/A	2015.07.06	2016.07.05	1 year
13	Test Cable	N/A	R-02	N/A	2015.07.06	2016.07.05	1 year
14	Test Receiver	R&S	ESCI	101160	2016.06.06	2017.06.05	1 year
15	LISN	R&S	ENV216	101313	2015.08.24	2016.08.23	1 year
16	LISN	EMCO	3816/2	00042990	2015.08.24	2016.08.23	1 year
17	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2016.06.07	2017.06.06	1 year
18	Passive Voltage Probe	R&S	ESH2-Z3	100196	2016.06.07	2017.06.06	1 year
19	Absorbing clamp	R&S	MOS-21	100423	2016.06.08	2017.06.07	1 year
20	Test Cable	N/A	C01	N/A	2016.06.08	2017.06.07	1 year
21	Test Cable	N/A	C02	N/A	2016.06.08	2017.06.07	1 year
22	Test Cable	N/A	C03	N/A	2016.06.08	2017.06.07	1 year
23	Attenuation	MCE	24-10-34	BN9258	2016.06.08	2017.06.07	1 year
24	Spectrum Analyzer	agilent	e4440a	us44300399	2016.06.08	2017.06.07	1 year
25	test receiver	R&S	esCl	a0304218	2016.06.08	2017.06.07	1 year
26	Communication Tester	R&S	CMU200	A0304247	2016.06.08	2017.06.07	1 year
27	Thermal Chamber	Ten Billion	TTC-B3C	TBN-960502	2016.06.08	2017.06.07	1 year

Note: Each piece of equipment is scheduled for calibration once a year.



7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard

According to FCC KDB 971168 D01 v02r02 Section 6.0

7.1.2 Conformance Limit

Fraguanov/MHz)	Conducted	I Emission Limit
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50


Note: 1. *Decreases with the logarithm of the frequency

- 2. The lower limit shall apply at the transition frequencies
- 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.1.4 Test Configuration



7.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.


- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
- 2. The EUT was placed on a table which is 0.8m above ground plane.
- 3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- 4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
- 5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- 6. LISN at least 80 cm from nearest part of EUT chassis.
- 7. The frequency range from 150KHz to 30MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
- 9. For the actual test configuration, please refer to the related Item -EUT Test Photos.

Humidity:

51 %



7.1.6 Test Results



Site CONDUCTION #1

Limit: FCC Part15 CE-Class B_QP

Mode: GSM Link

Note:

No. MI	k. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1720	32.98	10.12	43.10	64.86	-21.76	QP	
2	0.1720	23.21	10.12	33.33	54.86	-21.53	AVG	
3	0.3339	31.37	10.11	41.48	59.35	-17.87	QP	
4	0.3339	29.57	10.11	39.68	49.35	-9.67	AVG	
5	0.7178	29.68	9.78	39.46	56.00	-16.54	QP	
6	0.7178	24.46	9.78	34.24	46.00	-11.76	AVG	
7	1.2740	30.69	9.82	40.51	56.00	-15.49	QP	
8 *	1.2740	27.17	9.82	36.99	46.00	-9.01	AVG	
9	1.7740	30.44	9.76	40.20	56.00	-15.80	QP	
10	1.7740	26.10	9.76	35.86	46.00	-10.14	AVG	
11	2.3220	29.75	9.73	39.48	56.00	-16.52	QP	
12	2.3220	25.94	9.73	35.67	46.00	-10.33	AVG	


Power:

AC 120V/60Hz

^{*:}Maximum data x:Over limit !:over margin

Humidity:





Power:

AC 120V/60Hz

5116 CONDOCTION #1

Limit: FCC Part15 CE-Class B_QP


Mode: GSM Link

Note:

No. N	Иk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.3860	31.65	10.05	41.70	58.15	-16.45	QP	
2		0.3860	29.97	10.05	40.02	58.15	-18.13	AVG	
3		0.7177	30.90	9.78	40.68	56.00	-15.32	QP	
4		0.7177	28.91	9.78	38.69	56.00	-17.31	AVG	
5		1.3260	30.80	9.81	40.61	56.00	-15.39	QP	
6		1.3260	27.36	9.81	37.17	56.00	-18.83	AVG	
7 *	k	1.7660	31.18	9.76	40.94	56.00	-15.06	QP	
8		1.7660	27.76	9.76	37.52	56.00	-18.48	AVG	
9		2.2620	30.48	9.73	40.21	56.00	-15.79	QP	
10		2.2620	27.71	9.73	37.44	56.00	-18.56	AVG	
11		2.7580	29.46	9.74	39.20	56.00	-16.80	QP	
12		2.7580	25.93	9.74	35.67	56.00	-20.33	AVG	

^{*:}Maximum data x:Over limit !:over margin





Limit: FCC PART15_Class B _Main_QP

Mode: GSM Link


Note:

Power: AC 240V/50Hz Humidity: 51 %

No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1620	43.49	10.12	53.61	65.36	-11.75	QP	
2	0.1620	27.27	10.12	37.39	55.36	-17.97	AVG	
3	0.2020	41.48	10.13	51.61	63.52	-11.91	QP	
4	0.2020	25.71	10.13	35.84	53.52	-17.68	AVG	
5	0.2779	36.54	10.14	46.68	60.88	-14.20	QP	
6	0.2779	26.02	10.14	36.16	50.88	-14.72	AVG	
7	0.7258	33.98	9.79	43.77	56.00	-12.23	QP	
8	0.7258	25.47	9.79	35.26	46.00	-10.74	AVG	
9	1.2138	34.12	9.82	43.94	56.00	-12.06	QP	
10 *	1.2138	25.93	9.82	35.75	46.00	-10.25	AVG	
11	1.6938	33.12	9.77	42.89	56.00	-13.11	QP	
12	1.6938	23.42	9.77	33.19	46.00	-12.81	AVG	

^{*:}Maximum data x:Over limit !:over margin





Limit: FCC PART15_Class B _Main_QP

Mode: GSM Link

Note:

No. I	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1620	43.13	10.07	53.20	65.36	-12.16	QP	
2		0.1620	29.26	10.07	39.33	55.36	-16.03	AVG	
3		0.2020	41.75	10.02	51.77	63.52	-11.75	QP	
4		0.2020	28.88	10.02	38.90	53.52	-14.62	AVG	
5		0.2819	35.58	10.11	45.69	60.76	-15.07	QP	
6		0.2819	24.80	10.11	34.91	50.76	-15.85	AVG	
7		0.7219	34.32	9.81	44.13	56.00	-11.87	QP	
8	*	0.7219	26.88	9.81	36.69	46.00	-9.31	AVG	
9		1.2099	34.80	9.84	44.64	56.00	-11.36	QP	
10		1.2099	25.83	9.84	35.67	46.00	-10.33	AVG	
11		2.6979	33.81	9.74	43.55	56.00	-12.45	QP	
12		2.6979	22.64	9.74	32.38	46.00	-13.62	AVG	

^{*:}Maximum data x:Over limit !:over margin



7.2 FIELD STRENGTH OF SPURIOUS RADIATION

7.2.1 Applicable Standard

According to FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI/ TIA-603-D-2010 Section 2.2.12

7.2.2 Conformance Limit


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

7.2.3 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration

(a) For radiated emissions from 30MHz to 1000MHz



(b) For radiated emissions above 1000MHz





7.2.5 Test Procedure

The measurements procedures specified in TIA-603-D-2010 were used for testing. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The measurements were performed on all modes(GPRS850, GPRS1900, HSDPA band V) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for each band.Only shown the worst data.

The procedure of radiated spurious emissions is as follows:

- a) Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as, RSE=Rx(dBuV)+CL(dB)+SA(dB)+Gain(dBi)-107(dBuV to dBm)The SA is calibrated using following setup.
- b) EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 0.8m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS 1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz), GSM850 band (824.2MHz, 836.6MHz, 848.8MHz), UMTS band II(1852.4MHz, 1880MHz, 1907.6MHz), UMTS band V(826.4MHz, 835.0MHz, 846.6MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of any band into any of the other blocks.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the ARpl is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below: Power=PMea+ARpl

7.2.6 Test Results

EUT:	Mobile phone	Model No.:	K19
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	GSM850/GSM1900	Test By:	Susan Su



■ Radiated Spurious Emission

			GSN	1850							
Frequenc y	Power	Pcl	Pag	Ga Antenna Gain	Limit	Over Limit	Polarity				
(MHz)	(dBm)	(dBm)	(dBm)	(dBm)	(dBm)	(dBm)					
	Test Results for Channel 128/824.2 MHz										
1648.4	-31.68	1.23	40.13	25.57	-13	-5.35	Vertical				
1648.4	-31.44	1.23	40.13	25.57	-13	-5.11	Horizontal				
2472.6	-31.24	2.52	40.19	27.01	-13	-7.58	Vertical				
2472.6	-31.43	2.52	40.19	27.01	-13	-7.77	Horizontal				
3296.2	-31.15	3.74	40.29	29.24	-13	-10.84	Vertical				
3296.2	-31.26	3.74	40.29	29.24	-13	-10.95	Horizontal				
	Test Results for Channel 190/836.6 MHz										
1673.2	-32.26	1.25	40.15	25.93	-13	-6.29	Vertical				
1673.2	-32.63	1.25	40.15	25.93	-13	-6.66	Horizontal				
2509.8	-32.24	2.56	40.21	27.7	-13	-9.29	Vertical				
2509.8	-31.52	2.56	40.21	27.7	-13	-8.57	Horizontal				
3346.4	-31.31	3.78	40.32	29.64	-13	-11.41	Vertical				
3346.4	-31.56	3.78	40.32	29.64	-13	-11.66	Horizontal				
		Test Res	ults for Cha	nnel 251/84	48.8 MHz						
1697.6	-31.76	1.29	40.17	26.09	-13	-5.97	Vertical				
1697.6	-31.25	1.29	40.17	26.09	-13	-5.46	Horizontal				
2546.4	-31.38	2.63	40.24	27.52	-13	-8.29	Vertical				
2546.4	-31.17	2.63	40.24	27.52	-13	-8.08	Horizontal				
3395.2	-31.46	3.81	40.35	30.15	-13	-12.07	Vertical				
3395.2	-31.62	3.81	40.35	30.15	-13	-12.23	Horizontal				

Note:

The cable loss (Pcl) , the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.

Over Limit(dBm) = Power-Pc1+PAg-Ga-Limit



			GSM	1900							
Frequenc y	Power	Pcl	Pag	Ga Antenna Gain	Limit	Over Limit	Polarity				
(MHz)	(dBm)	(dBm)	(dBm)	(dBm)	(dBm)	(dBm)					
Test Results for Channel 512/1850.2MHz											
3700.4	-32.82	4.26	40.33	31.04	-13	-14.79	Vertical				
3700.4	-31.43	4.26	40.33	31.04	-13	-13.4	Horizontal				
5550.6	-31.78	5.41	40.59	34.43	-13	-18.03	Vertical				
5550.6	-30.81	5.41	40.59	34.43	-13	-17.06	Horizontal				
7400.8	-34.47	7.02	40.82	36.32	-13	-23.99	Vertical				
7400.8	-35.62	7.02	40.82	36.32	-13	-25.14	Horizontal				
	Test Results for Channel 661/1880.0MHz										
3760	-33.45	4.31	40.34	31.45	-13	-15.87	Vertical				
3760	-33.55	4.31	40.34	31.45	-13	-15.97	Horizontal				
5640	-34.24	5.46	40.62	33.84	-13	-19.92	Vertical				
5640	-35.43	5.46	40.62	33.84	-13	-21.11	Horizontal				
7520	-36.57	7.13	40.83	36.42	-13	-26.29	Vertical				
7520	-37.56	7.13	40.83	36.42	-13	-27.28	Horizontal				
		Test Res	ults for Cha	nnel 810/19	909.8MHz						
3819.6	-32.75	4.35	40.36	32.11	-13	-15.85	Vertical				
3819.6	-32.63	4.35	40.36	32.11	-13	-15.73	Horizontal				
5729.4	-34.48	5.49	40.63	34.23	-13	-20.57	Vertical				
5729.4	-34.52	5.49	40.63	34.23	-13	-20.61	Horizontal				
7639.2	-37.26	7.21	40.84	37.56	-13	-28.19	Vertical				
7639.2	-36.59	7.21	40.84	37.56	-13	-27.52	Horizontal				

Note:

The cable loss (Pc1) , the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.

Over Limit(dBm) = Power-Pc1+PAg-Ga-Limit



7.3 EFFECTIVE RADIATED POWER AND EFFECTIVE ISOTROPIC RADIATED POWER

7.3.1 Applicable Standard

According to FCC KDB 971168 D01 v02r02 Section 5.2.1/ Section 5.2.2.2 and ANSI/ TIA-603-D-2010 Section 2.2.17

7.3.2 Conformance Limit


The substitution method, in ANSI / TIA / EIA-603-D-2010, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band).

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Configuration

(a) For E.R.P and E.I.R.P Measurements



7.3.5 Test Procedure

The measurements procedures specified in TIA-603-D-2010 were applied.

In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (Pin) is applied to the input of the dipole, and the power received (Pr) at the chamber's probe antenna is recorded.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established as ARpl=Pin + 2.15 - Pr. The ARpl is the attenuation of "reference path loss", and including the gain of receive antenna, the cable loss and the air loss. The measurement results are obtained as described below: Power=PMea+ARpl



The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.

From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.

The EUT is then put into continuously transmitting mode at its maximum power level.

Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step1 is added to this result.

This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (Pin).

ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

Use the following spectrum analyzer settings:

ode the renewing operation analyzer certaings.									
	GSM/GPRS/EGPRS	UMTS band							
Span	500KHz	10MHz							
RBW	10KHz	300KHz							
VBW	30KHz	1MHz							
Detector	RMS	RMS							
Trace	Average	Average							
Average Type	Power	Power							
Sweep Count	100	100							

7.3.6 Test Results

EUT:	Mobile phone	Model No.:	K19
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	GSM850/GSM1900	Test By:	Susan Su



■ Effective Radiated Power

		F	Radiated Po	wer (ERP)	for GSM85	0		
Frequenc		PMea	Pcl	PAg	Ga	Correction	ERP	ERP
(MHz)	Polarizatio n	(dBm)	(dB)	(dB)	Antenna Gain	(dB)	(dBm)	(W)
					(dB)			
824.2	Н	-16.84	2.11	-52.73	0.87	2.15	30.76	1.191
836.6	Н	-18.44	2.13	-52.73	0.93	2.15	29.08	0.809
848.8	Н	-18.56	2.13	-52.73	0.97	2.15	28.92	0.780
824.2	V	-18.67	2.11	-52.73	0.87	2.15	28.93	0.782
836.6	V	-18.69	2.13	-52.73	0.93	2.15	28.83	0.764
848.8	V	-18.81	2.13	-52.73	0.97	2.15	28.67	0.736
		R	adiated Po	wer (ERP) f	or GPRS85	50		
824.2	Н	-17.12	2.11	-52.73	0.87	2.15	30.48	1.117
836.6	Н	-17.84	2.13	-52.73	0.93	2.15	29.68	0.929
848.8	Н	-18.52	2.13	-52.73	0.97	2.15	28.96	0.787
824.2	V	-19.36	2.11	-52.73	0.87	2.15	28.24	0.667
836.6	V	-19.62	2.13	-52.73	0.93	2.15	27.9	0.617
848.8	V	-19.84	2.13	-52.73	0.97	2.15	27.64	0.581

Page 23 of 53

Note:

The cable loss (PcI) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded

after test.

Peak ERP(dBm)= PMea-Pcl-PAg-Ga-Correction



■ Effective Isotropic Radiated Power

Radiated Power (E.I.R.P) for GSM 1900 MHZ				
	Result			
Mode	Frequency	Max. Peak	Polarization	Conclusion
		E.I.R.P.(dBm)	Of Max. E.I.R.P.	
	1850.2	29.23	Horizontal	Pass
	1850.2	29.18	Vertical	Pass
CCM1000	1880.0	28.46	Horizontal	Pass
GSM1900	1880.0	28.37	Vertical	Pass
	1909.8	28.22	Horizontal	Pass
	1909.8	28.18	Vertical	Pass

	Radiated Power (E.I.R.P) for GPRS 1900 MHZ				
	Result				
Mode	Frequency	Max. Peak	Polarization	Conclusion	
		E.I.R.P.(dBm)	Of Max. E.I.R.P.		
	1850.2	28.26	Horizontal	Pass	
	1850.2	28.03	Vertical	Pass	
GPRS1900	1880.0	28.17	Horizontal	Pass	
GPK31900	1880.0	28.24	Vertical	Pass	
	1909.8	27.85	Horizontal	Pass	
	1909.8	27.79	Vertical	Pass	



7.4 CONDUCTED OUTPUT POWER

7.4.1 Applicable Standard

According to FCC Part 2.1046 and FCC Part 22.913(a)(2) and FCC Part 24.232(c) and FCC KDB 971168 D01 v02r02 Section 5.2

7.4.2 Conformance Limit

Extend coverage on a secondary basis into cellular unserved areas, as those areas are defined in §22.949, the ERP of base transmitters and cellular repeaters of such systems must not exceed 1000 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts(38.5dBm).

Mobile and portable stations are limited to 2 watts (33dBm)EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

Connect the EUT to Universal Radio Communication Tester CMU200 or CMU500 via the antenna connector. A call is set up by the SS according to the generic call set up procedure on a channel with ARFCN in the ARFCN range, power control level set to Max power. The frequency band is set as selected frequency,

The RF output of the transmitter was connected to base station simulator.

Set EUT at maximum average power by base station simulator.

Set RBW = 1-5% of the OBW, not to exceed 1 MHz.

Set VBW ≥ 3 × RBW.

Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This gives bin-to-bin spacing $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)

Sweep time = auto.

Detector = RMS (power averaging).

Set sweep trigger to "free run".

Trace average at least 100 traces in power averaging (i.e., RMS) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the on and off periods of the transmitter.

Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

Add 10 log (1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add 10 log (1/0.25) = 6 dB if the duty cycle is a constant 25%.

Measure lowest, middle, and highest channels for each bandwidth and different modulation.

Measure and record the results in the test report.



7.4.6 Test Results

EUT:	Mobile phone	Model No.:	K19
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	GSM850/GSM1900	Test By:	Susan Su

Output Power for GSM850

Mode	Frequency(MHz)	Maximum Burst-Average Output Power
	824.2	31.68
GSM850	836.6	31.76
	848.8	31.83
	824.2	31.81
GPRS850(1 Slot)	836.6	31.76
	848.8	31.71
	824.2	30.39
GPRS850(2 Slot)	836.6	30.45
	848.8	30.58
	824.2	28.10
GPRS850(3 Slot)	836.6	28.03
	848.8	27.95
	824.2	25.86
GPRS850(4 Slot)	836.6	25.86
	848.8	25.81



Output	Power for	PCS1900

Mode	Frequency(MHz)	Maximum Burst-Average Output Power
	1850.2	29.28
GSM1900	1880	29.62
	1909.8	28.85
	1850.2	29.58
GPRS1900(1 Slot)	1880	29.25
	1909.8	28.82
	1850.2	27.40
GPRS1900(2 Slot)	1880	27.04
	1909.8	26.58
	1850.2	25.22
GPRS1900(3 Slot)	1880	24.91
	1909.8	24.48
	1850.2	23.25
GPRS1900(4 Slot)	1880	22.82
	1909.8	22.28



7.5 FREQUENCY STABILITY

7.5.1 Applicable Standard

According to FCC Part 2.1055 and FCC Part 22.355 and FCC Part 24.235 and FCC KDB 971168 D01 Section 9.0

7.5.2 Conformance Limit

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

7.5.5 Test Procedure

Connect the EUT to Universal Radio Communication Tester CMU200 or CMU500 via the antenna connector. A call is set up by the SS according to the generic call set up procedure on a channel with ARFCN in the ARFCN range, power control level set to Max power. MS TXPWR_MAX_CCH is set to the maximum value supported by the Power Class of the Mobile under test.

EUT was placed at temperature chamber and connected to an external power supply.

Temperature and voltage condition shall be tested to confirm frequency stability.

For Temperature Variation

- 1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
- 2. The EUT was set up in the thermal chamber and connected with the system simulator.
- 3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
- 4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

For Voltage Variation

- 1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
- 2. The EUT was placed in a temperature chamber at 25±5° C and connected with the system simulator.
- 3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
- 4. The variation in frequency was measured for the worst case.

7.5.6 Test Results

EUT:	Mobile phone	Model No.:	K19
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2	Test By:	Susan Su
Results: PASS			



Frequency Error Against Voltage for GSM 850 band			
Voltage (V) Frequency Error (Hz) Frequency Error (ppm)			
3.5	24	0.029	
3.7	21	0.025	
4.2	17	0.020	

Frequency Error Against Temperature for GSM 850 band			
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)	
-10	27	0.032	
0	26	0.031	
10	14	0.017	
20	16	0.019	
30	13	0.016	
40	19	0.023	
50	37	0.044	

Frequency Error Against Voltage for GSM 850 band			
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)	
3.145	22	0.026	
3.7	19	0.023	
4.255	15	0.018	

Frequency Error Against Temperature for GSM 850 band			
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)	
-10	25	0.030	
0	23	0.027	
10	16	0.019	
20	14	0.017	
30	17	0.020	
40	21	0.025	
50	39	0.047	

Note: The EUT doesn't work below -10 $^{\circ}\mathrm{C}$



Frequency Error Against Voltage for PCS 1900 band			
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)	
3.5	35	0.019	
3.7	26	0.014	
4.2	23	0.012	

Frequency Error Against Temperature for PCS 1900 band						
Temperature (℃)	Frequency Error (Hz) Frequency Error (pp					
-10	33	0.018				
0	21	0.011				
10	17	0.009				
20	21	0.011				
30	16	0.009				
40	12	0.006				
50	20	0.011				

Frequency Error Against Voltage for PCS 1900 band					
Voltage (V) Frequency Error (Hz) Frequency Error (ppm)					
3.145	33	0.018			
3.7	28	0.015			
4.255	24	0.013			

Frequency Error Against Temperature for PCS 1900 band						
Temperature (℃)	perature (℃) Frequency Error (Hz) Frequ					
-10	35	0.021				
0	24	0.013				
10	19	0.010				
20	17	0.009				
30	14	0.007				
40	21	0.011				
50	24	0.013				

Note: The EUT doesn't work below -10°C



7.6 PEAK-TO-AVERAGE RATIO

7.6.1 Applicable Standard

According to FCC 22.913 and FCC 24.232(d) and FCC KDB 971168 D01 Section 5.7.1

7.6.2 Conformance Limit

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The EUT was connected to Spectrum Analyzer and Base Station via power divider.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set the number of counts to a value that stabilizes the measured CCDF curve.

Set the measurement interval to 1 ms.

Record the maximum PAPR level associated with a probability of 0.1%.

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval as follows:
- 1) for continuous transmissions, set to 1 ms,
- 2) for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
- e) Record the maximum PAPR level associated with a probability of 0.1%.

7.6.6 Test Results

EUT:	Mobile phone	Model No.:	K19
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2	Test By:	Susan Su
Results: PASS			



Cellular Band						
Modes	GSM850			GSM1900		
Channel	128 (Low)	190 (Mid)	251 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency(MHz)	824.2	836.6	848.8	1850.2	1880	1909.8
Peak-to-Average Ratio (dB)	9.63	9.58	9.61	9.20	9.84	9.54


Page 32 of 53

Cellular Band						
Modes	GPRS850			GPRS1900		
Channel	128 (Low)	190 (Mid)	251 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency(MHz)	824.2	836.6	848.8	1850.2	1880	1909.8
Peak-to-Average Ratio (dB)	9.50	9.08	9.15	9.482	9.68	9.00

All the modulation modes and Channels have been tested, the data of the worst mode (GSM) are recorded in the following pages.





























7.7 26DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

7.7.1 Applicable Standard

According to FCC Part 2.1049 and FCC Part 22H and FCC Part 24E and FCC KDB 971168 D01 Section 4.0

7.7.2 Conformance Limit

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows FCC KDB 971168 v02r02 Section 4.0.

The EUT was connected to Spectrum Analyzer and Base Station via power divider.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.

The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.

Set the detection mode to peak, and the trace mode to max hold.

Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.

(this is the reference value)

Determine the "-26 dB down amplitude" as equal to (Reference Value – X).

Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the "–X dB down amplitude" determined in step 6. If a marker is below this "-X dB down amplitude" value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.

Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

N/A

PASS



7.7.6 Test Results

810

EUT:	Mobile phone	Model No.:	K19
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2	Test By:	Susan Su
Results: PASS			

99% Channel 26dB Operation Channel Occupied Limit Frequency Bandwidth Verdict Mode Number Bandwidth (kHz) (MHz) (kHz) (kHz) 128 824.2 314.0 247.71 N/A PASS GSM850 189 836.4 318.2 245.03 N/A **PASS** 251 848.8 314.9 243.33 N/A **PASS** 512 1850.2 319.4 244.88 N/A **PASS** GSM1900 661 1880.0 318.5 245.82 N/A **PASS** 810 1909.8 321.6 247.98 N/A PASS 128 824.2 N/A PASS 320.7 247.64 GPRS850 189 836.4 320.1 246.33 N/A **PASS** 251 848.8 317.3 245.46 N/A **PASS** 512 1850.2 320.1 247.07 N/A PASS **GPRS1900** 661 1880.0 323.8 244.82 N/A PASS


All the modulation modes and Channels have been tested, the data of the worst mode (GSM) are recorded in the following pages.


308.5

246.71


1909.8





































7.8 CONDUCTED BAND EDGE

7.8.1 Applicable Standard

According to FCC Part 2.1051 and FCC Part 22.917(a) and 24.238(a) and FCC KDB 971168 D01 Section6.0

7.8.2 Conformance Limit

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

7.8.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.4 Test Setup

Please refer to Section 6.1 of this test report.

7.8.5 Test Procedure

The testing follows FCC KDB 971168 v02r02 Section 6.0.

The EUT was connected to Spectrum Analyzer and Base Station via power divider.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

The band edges of low and high channels for the highest RF powers were measured.

The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

- = P(W) [43 + 10log(P)] (dB)
- = [30 + 10log(P)] (dBm) [43 + 10log(P)] (dB)
- = -13dBm.

7.8.6 Test Results

EUT:	Mobile phone	Model No.:	K19
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2	Test By:	Susan Su
Results: PASS			











7.9 CONDUCTED SPURIOUS EMISSION AT ANTENNA TERMINAL

7.9.1 Applicable Standard

According to FCC Part 2.1051 and FCC Part 22.917(a) and Part 24.238(a) and FCC KDB 971168 D01 Section6.0

7.9.2 Conformance Limit

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

7.9.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.9.4 Test Setup

Please refer to Section 6.1 of this test report.

7.9.5 Test Procedure

The testing follows FCC KDB 971168 v02r02 Section 6.0.

The EUT was connected to Spectrum Analyzer and Base Station via power divider.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

The middle channel for the highest RF power within the transmitting frequency was measured.

The conducted spurious emission for the whole frequency range was taken.

The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

- = P(W) [43 + 10log(P)] (dB)
- $= [30 + 10\log(P)] (dBm) [43 + 10\log(P)] (dB)$
- = -13dBm.

7.9.6 Test Results

EUT:	Mobile phone	Model No.:	K19
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2	Test By:	Susan Su
Results: PASS			




Conducted Emission Transmitting Mode CH 128 30MHz - 5GHz



Conducted Emission Transmitting Mode CH 128 5GHz - 10GHz











Conducted Emission Transmitting Mode CH 190 5GHz - 10GHz





Conducted Emission Transmitting Mode CH 251 30MHz - 5GHz




Conducted Emission Transmitting Mode CH 251 5GHz - 10GHz





Conducted Emission Transmitting Mode CH 512 30MHz - 10GHz



Conducted Emission Transmitting Mode CH 512 10GHz – 20GHz





Conducted Emission Transmitting Mode CH 661 30MHz - 10GHz



Conducted Emission Transmitting Mode CH 661 10GHz - 20GHz





Conducted Emission Transmitting Mode CH 810 30MHz - 10GHz



Conducted Emission Transmitting Mode CH 810 10GHz - 20GHz



END OF REPORT