





RADIO TEST REPORT

Report No: STS1903100W03

Issued for

Estone Group LLC

6th Floor, East Shunheda Building, LiuXianDong Industrial Park, XiLi Town NanShan, Shenzhen China

Product Name:	MD-100
Brand Name:	N/A
Model Name:	MD-100
Series Model:	N/A
FCC ID:	2AI99MD-100
Test Standard:	FCC Part 15.247

Any reproduction of this document must be done in full. No single part of this document may be reproduced we permission from STS, All Test Data Presented in this report is only applicable to presented Test Sample VAL



TEST RESULT CERTIFICATION

Applicant's Name:	Estone Group LLC
Address:	6th Floor, East Shunheda Building, LiuXianDong Industrial Park,XiLi Town NanShan, Shenzhen China
Manufacture's Name:	Estone Group LLC
Address:	6th Floor, East Shunheda Building, LiuXianDong Industrial Park,XiLi Town NanShan, Shenzhen China
Product Description	
Product Name:	MD-100
Brand Name:	N/A
Model Name:	MD-100
Series Model:	N/A
Test Standards:	FCC Part15.247
Test Procedure:	ANSI C63.10-2013
under test (EUT) is in compliance sample identified in the report. This report shall not be reproduce	been tested by STS, the test results show that the equipment with the FCC requirements. And it is applicable only to the tested ed except in full, without the written approval of STS, this document, personal only, and shall be noted in the revision of the document.
Date of Test:	
Date (s) of performance of tests:	29 Mar. 2019 ~ 13 Apr. 2019

Testing Engineer :

Date of Issue 17 Apr. 2019

Test Result: Pass

(Chris Chen)

Technical Manager :

(Sunday Hu)

Authorized Signatory:

(Vita Li)



Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF THE TEST MODES	10
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	10
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	12
2.6 EQUIPMENTS LIST	13
3. EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.2 RADIATED EMISSION MEASUREMENT	18
4. CONDUCTED SPURIOUS & BAND EDGE EMISSION	29
4.1 LIMIT	29
4.2 TEST PROCEDURE	29
4.3 TEST SETUP	29
4.4 EUT OPERATION CONDITIONS	29
4.5 TEST RESULTS	30
5. NUMBER OF HOPPING CHANNEL	42
5.1 LIMIT	42
5.2 TEST PROCEDURE	42
5.3 TEST SETUP	42
5.4 EUT OPERATION CONDITIONS	42
5.5 TEST RESULTS	43
6. AVERAGE TIME OF OCCUPANCY	44
6.1 LIMIT	44
6.2 TEST PROCEDURE	44
6.3 TEST SETUP	44
6.4 EUT OPERATION CONDITIONS	44
6.5 TEST RESULTS	45
7. HOPPING CHANNEL SEPARATION MEASUREMEN	51
7.1 LIMIT	51







Table of Contents	Page
7.2 TEST PROCEDURE	51
7.3 TEST SETUP	51
7.4 EUT OPERATION CONDITIONS	51
7.5 TEST RESULTS	52
8. BANDWIDTH TEST	58
8.1 LIMIT	58
8.2 TEST PROCEDURE	58
8.3 TEST SETUP	58
8.4 EUT OPERATION CONDITIONS	58
8.5 TEST RESULTS	59
9. OUTPUT POWER TEST	65
9.1 LIMIT	65
9.2 TEST PROCEDURE	65
9.3 TEST SETUP	65
9.4 EUT OPERATION CONDITIONS	65
9.5 TEST RESULTS	66
10. ANTENNA REQUIREMENT	67
10.1 STANDARD REQUIREMENT	67
10.2 EUT ANTENNA	67



Page 5 of 68 Report No.: STS1903100W03

Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	17 Apr. 2019	STS1903100W03	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards: KDB 558074 D01 15.247 Meas Guidance v05r01

FCC Part 15.247,Subpart C				
Standard Section	Test Item Judgment Remark			
15.207	Conducted Emission	PASS		
15.247(a)(1)	Hopping Channel Separation	PASS		
15.247(a)(1)&(b)(1)	Output Power	PASS		
15.247(c)	Radiated Spurious Emission	PASS		
15.247(d)	Conducted Spurious & Band Edge Emission	PASS		
15.247(a)(iii)	Number of Hopping Frequency	PASS		
15.247(a)(iii)	Dwell Time	PASS		
15.247(a)(1)	Bandwidth	PASS		
15.205	Restricted Band Edge Emission	PASS		
Part 15.247(d)/part 15.209(a)	Band Edge Emission	PASS		
15.203	Antenna Requirement	PASS		

NOTE:

- (1)" N/A" denotes test is not applicable in this Test Report
- (2) All tests are according to ANSI C63.10-2013



1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add.: 1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,

Fuyong Street, Bao'an District, Shenzhen, Guangdong, China

FCC test Firm Registration Number: 625569

A2LA Certificate No.: 4338.01;

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	RF output power, conducted	±0.71dB
2	Unwanted Emissions, conducted	±0.63dB
3	All emissions, radiated 30-200MHz	±3.43dB
4	All emissions, radiated 200MHz-1GHz	±3.57dB
5	All emissions, radiated>1G	±4.13dB
6	Conducted Emission (9KHz-150KHz)	±3.18dB
7	Conducted Emission (150KHz-30MHz)	±2.70dB



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	MD-100
Trade Name	N/A
Model Name	MD-100
Series Model	N/A
Model Difference	N/A
Channel List	Please refer to the Note 2.
Bluetooth	Frequency:2402 – 2480 MHz Modulation: GFSK(1Mbps), π/4-DQPSK(2Mbps), 8DPSK(3Mbps)
Bluetooth Version	4.2 BR+EDR
Adapter	Adapter 1: Input: AC100-240V, 1700 mA, 50/60Hz Output: DC19 V, 3000mA Adapter 2: Input: 100-240V, 50/60Hz, 1.5A Output: 18V, 3.4A
Battery	Battery 1: Rated Voltage: 11.1 V Charge Limit: 12.6 V Capacity: 3700 mAh Battery 2: Rated Voltage: 7.4 V Charge Limit: 8.4 V Capacity: 440 mAh
Hardware version number	MD100_MB_VerC
Software version number	Windows 10 Pro
Connecting I/O Port(s)	Please refer to the User's Manual

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

	Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	
00	2402	27	2429	54	2456	
01	2403	28	2430	55	2457	
02	2404	29	2431	56	2458	
03	2405	30	2432	57	2459	
04	2406	31	2433	58	2460	
05	2407	32	2434	59	2461	
06	2408	33	2435	60	2462	
07	2409	34	2436	61	2463	
80	2410	35	2437	62	2464	
09	2411	36	2438	63	2465	
10	2412	37	2439	64	2466	
11	2413	38	2440	65	2467	
12	2414	39	2441	66	2468	
13	2415	40	2442	67	2469	
14	2416	41	2443	68	2470	
15	2417	42	2444	69	2471	
16	2418	43	2445	70	2472	
17	2419	44	2446	71	2473	
18	2420	45	2447	72	2474	
19	2421	46	2448	73	2475	
20	2422	47	2449	74	2476	
21	2423	48	2450	75	2477	
22	2424	49	2451	76	2478	
23	2425	50	2452	77	2479	
24	2426	51	2453	78	2480	
25	2427	52	2454			
26	2428	53	2455			

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	MD-100	PIFA	N/A	0 dBi	BT Antenna



2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate/Modulation
Mode 1	TX CH00	1Mbps/GFSK
Mode 2	TX CH39	1Mbps/GFSK
Mode 3	TX CH78	1Mbps/GFSK
Mode 4	TX CH00	2 Mbps/π/4-DQPSK
Mode 5	TX CH39	2 Mbps/π/4-DQPSK
Mode 6	TX CH78	2 Mbps/π/4-DQPSK
Mode 7	TX CH00	3 Mbps/8DPSK
Mode 8	TX CH39	3 Mbps/8DPSK
Mode 9	TX CH78	3 Mbps/8DPSK

Note:

- (1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported
- (2) We have be tested for all avaiable U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V/60Hz is shown in the report

For AC Conducted Emission

	Test Case
AC Conducted	Mode 10 : Keeping BT TX
Emission	

2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS.

Test software Version	Test program: Bluetooth				
Frequency	2402 MHz	2441 MHz	2480 MHz		
(Power control software) Parameters(1/2/3Mbps)	Power class: 1 M rate:4:27 2 M rate:11:183	Power class: 1 M rate:4:27 2 M rate:11:183	Power class: 1 M rate:4:27 2 M rate:11:183		
	3 M rate:15:339	3 M rate:15:339	3 M rate:15:339		




2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Radiated Spurious Emission Test

E-1 EUT

Conducted Emission Test





2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-2	Adapter	N/A	SOY-1900300	N/A	N/A
C-1	DC Cable	N/A	100cm	N/A	N/A

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
N/A	N/A	N/A	N/A	N/A	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>"Length_"</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".



2.6 EQUIPMENTS LIST

Radiation Test equipment

tadiation root equipm	0110				
Kind of Equipment	nd of Equipment Manufacturer Type No.		Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2018.10.13	2019.10.12
Signal Analyzer	Agilent	N9020A	MY51110105	2019.03.02	2020.03.01
Active loop Antenna	ZHINAN	ZN30900C	16035	2018.03.11	2021.03.10
Bilog Antenna	TESEQ	CBL6111D	34678	2017.11.02	2020.11.01
Horn Antenna	SCHWARZBECK	BBHA 9120D(1201)	9120D-1343	2018.10.19	2021.10.18
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	J211020657	2018.03.11	2021.03.10
Pre-Amplifier(0.1M-3G Hz)	EM	EM330	060665	2018.10.13	2019.10.12
Pre-Amplifier (1G-18GHz)	SKET	LNPA-01018G-45	SK201808090 1	2018.10.13	2019.10.12
Temperature & Humidity	HH660	Mieo	N/A	2018.10.11	2019.10.10
turn table	EM	SC100_1	60531	N/A	N/A
Antenna mast	EM	SC100	N/A	N/A	N/A

Conduction Test equipment

Conduction rest equipment							
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until		
Test Receiver	R&S	ESCI	101427	2018.10.13	2019.10.12		
LISN	R&S	ENV216	101242	2018.10.11	2019.10.10		
LISN	EMCO	3810/2NM	23625	2018.10.11	2019.10.10		
Temperature & Humidity	HH660	Mieo	N/A	2018.10.11	2019.10.10		

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2018.10.13	2019.10.12
Signal Analyzer	Agilent	N9020A	MY49100060	2018.10.13	2019.10.12
Temperature & Humidity	HH660	Mieo	N/A	2018.10.11	2019.10.10



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

Operating frequency band. In case the emission fall within the restricted band specified on Part 207(a) limit in the table below has to be followed.

EDECLIENCY (MLI-)	Conducted Emissionlimit (dBuV)			
FREQUENCY (MHz)	Quasi-peak	Average		
0.15 -0.5	66 - 56 *	56 - 46 *		
0.50 -5.0	56.00	46.00		
5.0 -30.0	60.00	50.00		

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver


Receiver Parameters	Setting		
Attenuation	10 dB		
Start Frequency	0.15 MHz		
Stop Frequency	30 MHz		
IF Bandwidth	9 kHz		



3.1.2 TEST PROCEDURE

- a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.1.3 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




3.1.5 TEST RESULT


Temperature:	20.7℃	Relative Humidity:	64%
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode:	Mode 10		

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB)	(dBuV)	(dBuV)	(dB)	
1	0.1500	32.28	20.23	52.51	66.00	-13.49	QP
2	0.1500	7.22	20.23	27.45	56.00	-28.55	AVG
3	0.2220	28.10	20.34	48.44	62.74	-14.30	QP
4	0.2220	11.55	20.34	31.89	52.74	-20.85	AVG
5	0.5900	28.36	20.37	48.73	56.00	-7.27	QP
6	0.5900	19.19	20.37	39.56	46.00	-6.44	AVG
7	1.7260	23.81	20.09	43.90	56.00	-12.10	QP
8	1.7260	12.00	20.09	32.09	46.00	-13.91	AVG
9	12.3500	22.04	20.07	42.11	60.00	-17.89	QP
10	12.3500	11.78	20.07	31.85	50.00	-18.15	AVG
11	28.4260	21.50	19.39	40.89	60.00	-19.11	QP
12	28.4260	11.44	19.39	30.83	50.00	-19.17	AVG

Remark:

1. All readings are Quasi-Peak and Average values.






Page 17 of 68 Report No.: STS1903100W03

Temperature:	20.7℃	Relative Humidity:	64%
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode:	Mode 10		

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB)	(dBuV)	(dBuV)	(dB)	
1	0.1620	33.19	20.23	53.42	65.36	-11.94	QP
2	0.1620	5.63	20.23	25.86	55.36	-29.50	AVG
3	0.2620	27.65	20.54	48.19	61.37	-13.18	QP
4	0.2620	9.30	20.54	29.84	51.37	-21.53	AVG
5	0.5940	28.11	20.37	48.48	56.00	-7.52	QP
6	0.5940	18.68	20.37	39.05	46.00	-6.95	AVG
7	1.8020	24.18	20.08	44.26	56.00	-11.74	QP
8	1.8020	9.51	20.08	29.59	46.00	-16.41	AVG
9	10.8740	21.53	20.11	41.64	60.00	-18.36	QP
10	10.8740	12.38	20.11	32.49	50.00	-17.51	AVG
11	28.1220	23.77	19.39	43.16	60.00	-16.84	QP
12	28.1220	14.38	19.39	33.77	50.00	-16.23	AVG

Remark:

- 1. All readings are Quasi-Peak and Average values.
- 2. Margin = Result (Result = Reading + Factor)-Limit 100.0 dBuV





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)		
	PEAK	AVERAGE	
Above 1000	74	54	

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak)
Stop Frequency	10th carrier hamonic(Peak)
RB / VB (emission in restricted	DIC 4MILE / 4MILE AV/ 4 MILE /40 LIE
band)	PK=1MHz / 1MHz, AV=1 MHz /10 Hz

For Band edge

Spectrum Parameter	Setting	
Detector	Peak	
Chart/Char Francisco	Lower Band Edge: 2300 to 2403 MHz	
Start/Stop Frequency	Upper Band Edge: 2479 to 2500 MHz	
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz / 10 Hz	

Page 19 of 68 Report No.: STS1903100W03

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz/9kHz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- b. The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then QuasiPeak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos. Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD No deviation




3.2.4 TESTSETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz




(B) Radiated Emission Test-Up Frequency 30MHz~1GHz





(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBµV/m)	(dBµV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

Factor=AF+CL-AG



3.2.7 TEST RESULTS

(9KHz-30MHz)

Temperature:	220.5℃	Relative Humidity:	60%
Test Voltage:	DC 11.1V	Test Mode:	TX Mode

Freq.	Reading	Limit	Margin	State	Toot Dooult	
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	Test Result	
					PASS	
					PASS	

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =40 log (specific distance/test distance)(dB);

Limit line = specific limits (dBuv) + distance extrapolation factor.




(30MHz-1000MHz)

Temperature:	220.5℃	Relative Humidity:	60%	
Test Voltage:	DC 11.1V	Phase:	Horizontal	
Test Mode:	Mode 1/2/3/4/5/6/7/8/9(Mode 5 worst mode)			

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	31.5093	26.44	-11.96	14.48	40.00	-25.52	QP
2	129.0146	37.46	-17.56	19.90	43.50	-23.60	QP
3	295.1470	38.83	-15.11	23.72	46.00	-22.28	QP
4	407.5144	41.44	-11.10	30.34	46.00	-15.66	QP
5	528.2458	34.51	-8.09	26.42	46.00	-19.58	QP
6	839.1816	29.46	-2.78	26.68	46.00	-19.32	QP

Remark:

1. Margin = Result (Result = Reading + Factor)-Limit






Temperature:	220.5℃	Relative Humidity:	60%	
Test Voltage:	DC 11.1V	Phase:	Vertical	
Test Mode:	Mode 1/2/3/4/5/6/7/8/9(Mode 5 worst mode)			

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	31.6202	25.85	-12.02	13.83	40.00	-26.17	QP
2	100.2286	35.43	-19.17	16.26	43.50	-27.24	QP
3	414.7223	36.79	-10.99	25.80	46.00	-20.20	QP
4	475.4991	34.60	-9.57	25.03	46.00	-20.97	QP
5	714.1734	31.97	-4.84	27.13	46.00	-18.87	QP
6	903.3094	32.02	-2.14	29.88	46.00	-16.12	QP

Remark:

1. Margin = Result (Result = Reading + Factor)-Limit





(1GHz~25GHz) Restricted band and Spurious emission Requirements

π/4-DQPSK

Prequency Meter Comment Comm		11/4-DQF3K									
MHz	Frequency		Amplifier	Loss				Limits	Margin	Detector	Comment
3284.76 61.56 44.70 6.70 28.20 -9.80 51.76 74.00 -22.24 PK Vertical 3284.76 51.49 44.70 6.70 28.20 -9.80 41.69 54.00 -12.31 AV Vertical 3284.64 61.41 44.70 6.70 28.20 -9.80 51.61 74.00 -22.39 PK Horizontal 3264.64 51.25 44.70 6.70 28.20 -9.80 51.61 74.00 -12.55 AV Horizontal 4804.50 51.65 44.20 9.04 31.60 -3.56 55.00 74.00 -19.00 PK Vertical 4804.50 49.20 44.20 9.04 31.60 -3.56 45.64 54.00 -19.21 PK Horizontal 4804.43 49.22 44.20 9.04 31.60 -3.56 45.69 54.00 -8.36 AV Vertical 4804.43 49.22 44.20 9.04 31.60 -3.56 55.00 74.00 -19.21 PK Horizontal 4804.43 49.22 44.20 9.04 31.60 -3.56 45.66 54.00 -8.34 AV Horizontal 5359.76 48.22 44.20 9.86 32.00 -2.34 45.88 74.00 -28.12 PK Vertical 5359.76 48.22 44.20 9.86 32.00 -2.34 55.36 74.00 -16.74 AV Vertical 5359.67 47.70 44.20 9.86 32.00 -2.34 55.36 74.00 -28.84 PK Horizontal 5359.67 39.39 44.20 9.86 32.00 -2.34 45.86 74.00 -28.84 PK Horizontal 5359.67 39.39 44.20 9.86 32.00 -2.34 45.86 74.00 -16.74 AV Vertical 5359.67 39.39 44.20 9.86 32.00 -2.34 37.26 54.00 -16.74 AV Vertical 5359.67 39.39 44.20 9.86 32.00 -2.34 37.05 54.00 -16.64 PK Horizontal 7205.85 43.61 43.50 11.40 35.50 3.40 57.86 74.00 -16.95 AV Horizontal 7205.85 43.61 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Vertical 7205.85 43.61 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Horizontal 7205.85 50.79 44.70 6.70 28.20 9.80 52.33 74.00 -21.67 PK Vertical 848.25 7 59.12 44.20 9.04 31.60 -3.56 45.86 54.00 -13.27 AV Vertical 4882.57 59.12 44.20 9.04 31.60 -3.56 55.66 74.00 -18.84 PK Horizontal 4882.57 59.12 44.20 9.04 31.60 -3.56 55.66 74.00 -18.84 PK Horizontal 4882.50 59.92 44.20 9.04 31.60 -3.56 55.66 74.00 -18.84 PK Horizontal 4882.50 59.92 44.20 9.04 31.60 -3.56 55.66 74.00 -18.84 PK Vertical 5359.86 39.20 44.20 9.04 31.60 -3.56 46.07 54.00 -7.93 AV Horizontal 5359.86 39.20 44.20 9.04 31.60 -3.56 55.66	(MHz)	(dBµV)	(dB)	(dB)	(dB/m)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре	Comment
3264.76 51.49 44.70 6.70 28.20 -9.80 41.69 54.00 -12.31 AV Vertical 3264.64 61.41 44.70 6.70 28.20 -9.80 51.61 74.00 -22.39 PK Horizontal 3264.64 51.25 44.70 6.70 28.20 -9.80 51.61 74.00 -22.39 PK Horizontal 4804.50 58.56 44.20 9.04 31.60 -3.56 55.00 74.00 -19.00 PK Vertical 4804.50 58.56 44.20 9.04 31.60 -3.56 55.00 74.00 -19.00 PK Vertical 4804.50 49.20 44.20 9.04 31.60 -3.56 55.00 74.00 -19.21 PK Horizontal 4804.43 58.35 44.20 9.04 31.60 -3.56 54.79 74.00 -19.21 PK Horizontal 4804.43 49.22 44.20 9.04 31.60 -3.56 54.66 54.00 -8.34 AV Horizontal 4804.43 49.22 44.20 9.04 31.60 -3.56 54.66 54.00 -8.34 AV Horizontal 5359.76 39.60 44.20 9.86 32.00 -2.34 45.88 74.00 -28.12 PK Vertical 5359.76 39.60 44.20 9.86 32.00 -2.34 45.88 74.00 -28.12 PK Vertical 5359.67 47.70 44.20 9.86 32.00 -2.34 45.86 74.00 -28.84 PK Horizontal 5359.67 39.39 44.20 9.86 32.00 -2.34 37.26 54.00 -16.74 AV Vertical 7205.85 54.46 43.50 11.40 35.50 3.40 57.86 74.00 -16.95 AV Horizontal 7205.85 43.61 43.50 11.40 35.50 3.40 57.86 74.00 -16.11 PK Vertical 7205.85 43.61 43.50 11.40 35.50 3.40 47.70 54.00 -6.99 AV Vertical 7205.86 44.32 43.50 11.40 35.50 3.40 47.72 54.00 -6.28 AV Horizontal 7205.86 54.49 43.50 11.40 35.50 3.40 47.72 54.00 -6.28 AV Horizontal 7205.86 54.49 43.50 11.40 35.50 3.40 47.72 54.00 -6.28 AV Horizontal 3264.77 50.53 44.70 6.70 28.20 9.80 40.99 54.00 -13.01 AV Horizontal 3264.87 50.53 44.70 6.70 28.20 9.80 40.99 54.00 -13.01 AV Horizontal 3264.85 50.79 44.70 6.70 28.20 9.80 40.99 54.00 -13.01 AV Horizontal 482.57 59.12 44.20 9.04 31.60 -3.56 55.56 74.00 -13.44 PK Vertical 482.50 58.92 44.20 9.04 31.60 -3.56 55.56 74.00 -13.01 AV Horizontal 5359.66 49.44 44.20 9.86 32.00 -2.34 47.10 74.00 -22.23 PK Horizontal 5359.66 49.44 44.20 9.86 32.00 -2.34 47.10 74.00 -20.80 PK Horizontal 5359.66 49.44 44.20 9.86 32.00 -2.34 47.10 74.00 -20.80 PK Horizontal 5359.66 49.44 44.20 9.86 32.00 -2.34 45.86 54.00 -11.714 AV Vertical 5359.86 49.44 44.20 9.86 32.00 -2.34 45.86 54.00 -11.714 AV Vertical 5359.86 49.44 44.20 9.86 32.00 -2.34 45.86 54.0		Low Channel (2402 MHz)									
3264.64 61.41 44.70 6.70 28.20 9.80 51.61 74.00 -22.39 PK Horizontal 3264.64 51.25 44.70 6.70 28.20 9.80 41.45 54.00 -12.55 AV Horizontal 4804.50 58.56 44.20 9.04 31.60 -3.56 55.00 74.00 -19.00 PK Vertical 4804.50 49.20 44.20 9.04 31.60 -3.56 55.00 74.00 -19.00 PK Vertical 4804.50 49.20 44.20 9.04 31.60 -3.56 54.79 74.00 -19.21 PK Horizontal 4804.43 58.35 44.20 9.04 31.60 -3.56 54.79 74.00 -19.21 PK Horizontal 4804.43 49.22 44.20 9.04 31.60 -3.56 45.66 54.70 -8.34 AV Horizontal 4804.43 49.22 44.20 9.04 31.60 -3.56 45.66 54.00 -8.34 AV Horizontal 5359.76 48.22 44.20 9.86 32.00 -2.34 45.88 74.00 -28.12 PK Vertical 5359.76 48.22 44.20 9.86 32.00 -2.34 45.86 74.00 -16.74 AV Vertical 5359.67 39.80 44.20 9.86 32.00 -2.34 37.26 54.00 -16.74 AV Vertical 5359.67 39.39 44.20 9.86 32.00 -2.34 45.86 74.00 -28.64 PK Horizontal 55359.67 39.39 44.20 9.86 32.00 -2.34 37.26 54.00 -16.74 AV Vertical 7205.85 54.46 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Vertical 7205.85 43.61 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Vertical 7205.85 43.61 43.50 11.40 35.50 3.40 47.70 54.00 -6.28 AV Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 47.70 54.00 -6.28 AV Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 47.70 54.00 -6.28 AV Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 47.70 54.00 -76.28 AV Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 47.70 54.00 -16.11 PK Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 57.89 74.00 -16.11 PK Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 57.89 74.00 -16.11 PK Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 57.89 74.00 -16.14 PK Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 57.89 74.00 -16.14 PK Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 57.89 74.00 -16.11 PK Horizontal 7205.68 54.49 43.50 11.40 35.50 58.50 59.80 52.33 74.00 -22.23 PK Horizontal 7205.68 54.40 44.20 9.04 31.60 -3.56 55.56 74.00 -13.27 AV Vertical 7205.68 54.90 44.20 9.04 31.60 -3.56 55.56 74.00 -13.27 AV Vertical 482.57 59.12 44.20 9.04 31.60 -3.56 55.56 74.00 -13.01 AV Horizontal 482.57 59.12 44.20 9.04 31.60 -3.56	3264.76	61.56	44.70	6.70	28.20	-9.80	51.76	74.00	-22.24	PK	Vertical
3264.64 51.25 44.70 6.70 28.20 -9.80 41.45 54.00 -12.55 AV Horizontal 4804.50 58.56 44.20 9.04 31.60 -3.56 55.00 74.00 -19.00 PK Vertical 4804.50 49.20 44.20 9.04 31.60 -3.56 55.00 74.00 -19.00 PK Vertical 4804.43 58.35 44.20 9.04 31.60 -3.56 45.64 54.00 -8.36 AV Vertical 4804.43 58.35 44.20 9.04 31.60 -3.56 45.66 54.00 -8.34 AV Horizontal 5359.76 48.22 44.20 9.86 32.00 -2.34 45.88 74.00 -28.12 PK Vertical 5359.76 49.22 44.20 9.86 32.00 -2.34 45.88 74.00 -28.12 PK Vertical 5359.76 39.80 44.20 9.86 32.00 -2.34 37.26 54.00 -16.74 AV Vertical 5359.67 39.39 44.20 9.86 32.00 -2.34 45.86 74.00 -28.64 PK Horizontal 5359.67 39.39 44.20 9.86 32.00 -2.34 37.05 54.00 -16.95 AV Horizontal 5359.67 39.39 44.20 9.86 32.00 -2.34 37.05 54.00 -16.96 AV Horizontal 7205.85 54.46 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Vertical 7205.68 54.49 43.50 11.40 35.50 3.40 47.01 54.00 -6.99 AV Vertical 7205.68 44.32 43.50 11.40 35.50 3.40 47.01 54.00 -6.99 AV Vertical 7205.68 54.49 43.50 11.40 35.50 3.40 47.01 54.00 -6.28 AV Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 47.01 54.00 -6.28 AV Horizontal 7205.68 54.49 63.50 11.40 35.50 3.40 47.01 54.00 -6.28 AV Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 47.01 54.00 -6.28 AV Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 47.01 54.00 -6.28 AV Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 47.01 54.00 -6.28 AV Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 57.89 74.00 -16.11 PK Horizontal 7205.68 44.32 43.50 11.40 35.50 3.40 47.01 54.00 -6.28 AV Horizontal 7205.68 44.32 43.50 11.40 35.50 3.40 57.89 74.00 -16.11 PK Horizontal 7205.68 44.32 43.50 11.40 35.50 3.40 57.89 74.00 -16.14 PK Vertical 74.70 6.70 28.20 9.80 40.73 54.00 -16.28 AV Horizontal 74.70 6.70 28.20 9.80 40.73 54.00 -13.27 AV Vertical 74.70 6.70 28.20 9.80 40.73 54.00 -13.01 AV Horizontal 4882.50 59.50 44.20 9.04 31.60 -3.56 55.56 74.00 -18.64 PK Horizontal 4882.50 59.92 44.20 9.04 31.60 -3.56 55.56 74.00 -18.64 PK Horizontal 4882.50 49.83 44.20 9.86 32.00 -2.34 45.10 74.00 -28.90 PK Horizontal 5359.86 49.44 44.20 9.86	3264.76	51.49	44.70	6.70	28.20	-9.80	41.69	54.00	-12.31	AV	Vertical
4804.50 58.56 44.20 9.04 31.60 -3.56 55.00 74.00 -19.00 PK Vertical 4804.50 49.20 44.20 9.04 31.60 -3.56 45.64 54.00 -8.36 AV Vertical 4804.43 58.35 44.20 9.04 31.60 -3.56 54.79 74.00 -19.21 PK Horizontal 5359.76 48.22 44.20 9.86 32.00 -2.34 45.88 74.00 -28.12 PK Vertical 5359.76 48.22 44.20 9.86 32.00 -2.34 45.88 74.00 -28.64 PK Horizontal 5359.76 47.70 44.20 9.86 32.00 -2.34 45.36 74.00 -28.64 PK Horizontal 5359.76 43.50 11.40 35.50 3.40 57.86 74.00 -28.64 PK Horizontal 7205.85 54.46 43.50 11.40 35.50 3.40	3264.64	61.41	44.70	6.70	28.20	-9.80	51.61	74.00	-22.39	PK	Horizontal
4804.50 49.20 44.20 9.04 31.60 -3.56 45.64 54.00 -8.36 AV Vertical 4804.43 58.35 44.20 9.04 31.60 -3.56 54.79 74.00 -19.21 PK Horizontal 4804.43 49.22 44.20 9.04 31.60 -3.56 45.66 54.00 -8.34 AV Horizontal 5359.76 48.22 44.20 9.86 32.00 -2.34 45.88 74.00 -28.12 PK Vertical 5359.76 39.60 44.20 9.86 32.00 -2.34 45.36 74.00 -28.64 PK Horizontal 5359.67 47.70 44.20 9.86 32.00 -2.34 45.36 74.00 -28.64 PK Horizontal 7205.85 54.46 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Vertical 7205.68 54.49 43.50 11.40 35.50	3264.64	51.25	44.70	6.70	28.20	-9.80	41.45	54.00	-12.55	AV	Horizontal
4804.43 58.35 44.20 9.04 31.60 -3.56 54.79 74.00 -19.21 PK Horizontal 4804.43 49.22 44.20 9.04 31.60 -3.56 45.66 54.00 -8.34 AV Horizontal 5359.76 48.22 44.20 9.86 32.00 -2.34 45.88 74.00 -28.12 PK Vertical 5359.67 39.60 44.20 9.86 32.00 -2.34 37.26 54.00 -16.74 AV Vertical 5359.67 47.70 44.20 9.86 32.00 -2.34 45.36 74.00 -28.64 PK Horizontal 5359.67 39.39 44.20 9.86 32.00 -2.34 45.36 74.00 -16.14 PK Vertical 7205.85 54.46 43.50 11.40 35.50 3.40 57.89 74.00 -16.11 PK Horizontal 7205.68 54.49 43.50 11.40 35.5	4804.50	58.56	44.20	9.04	31.60	-3.56	55.00	74.00	-19.00	PK	Vertical
4804.43 49.22 44.20 9.04 31.60 -3.56 45.66 54.00 -8.34 AV Horizontal 5359.76 48.22 44.20 9.86 32.00 -2.34 45.88 74.00 -28.12 PK Vertical 5359.76 39.60 44.20 9.86 32.00 -2.34 37.26 54.00 -16.74 AV Vertical 5359.67 39.39 44.20 9.86 32.00 -2.34 37.05 54.00 -16.95 AV Horizontal 7205.85 54.46 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Vertical 7205.85 54.49 43.50 11.40 35.50 3.40 47.01 54.00 -6.99 AV Vertical 7205.68 54.49 43.50 11.40 35.50 3.40 47.72 54.00 -6.28 AV Horizontal 3264.77 62.13 44.70 6.70 28.20 <td>4804.50</td> <td>49.20</td> <td>44.20</td> <td>9.04</td> <td>31.60</td> <td>-3.56</td> <td>45.64</td> <td>54.00</td> <td>-8.36</td> <td>AV</td> <td>Vertical</td>	4804.50	49.20	44.20	9.04	31.60	-3.56	45.64	54.00	-8.36	AV	Vertical
5359.76 48.22 44.20 9.86 32.00 -2.34 45.88 74.00 -28.12 PK Vertical 5359.76 39.60 44.20 9.86 32.00 -2.34 37.26 54.00 -16.74 AV Vertical 5359.67 47.70 44.20 9.86 32.00 -2.34 45.36 74.00 -28.64 PK Horizontal 5359.67 39.39 44.20 9.86 32.00 -2.34 37.05 54.00 -16.95 AV Horizontal 7205.85 54.46 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Vertical 7205.68 54.49 43.50 11.40 35.50 3.40 57.89 74.00 -16.11 PK Horizontal 7205.68 54.49 43.50 11.40 35.50 3.40 47.72 54.00 -6.28 AV Horizontal 3264.77 50.53 44.70 6.70 28.20	4804.43	58.35	44.20	9.04	31.60	-3.56	54.79	74.00	-19.21	PK	Horizontal
5359.76 39.60 44.20 9.86 32.00 -2.34 37.26 54.00 -16.74 AV Vertical 5359.67 47.70 44.20 9.86 32.00 -2.34 45.36 74.00 -28.64 PK Horizontal 5359.67 39.39 44.20 9.86 32.00 -2.34 37.05 54.00 -16.95 AV Horizontal 7205.85 54.46 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Vertical 7205.85 43.61 43.50 11.40 35.50 3.40 47.01 54.00 -6.99 AV Vertical 7205.68 54.49 43.50 11.40 35.50 3.40 57.89 74.00 -16.11 PK Horizontal 7205.68 44.32 43.50 11.40 35.50 3.40 47.72 54.00 -6.28 AV Horizontal 3264.77 50.53 44.70 6.70 28.20<	4804.43	49.22	44.20	9.04	31.60	-3.56	45.66	54.00	-8.34	AV	Horizontal
5359.67 47.70 44.20 9.86 32.00 -2.34 45.36 74.00 -28.64 PK Horizontal 5359.67 39.39 44.20 9.86 32.00 -2.34 37.05 54.00 -16.95 AV Horizontal 7205.85 54.46 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Vertical 7205.85 43.61 43.50 11.40 35.50 3.40 47.01 54.00 -6.99 AV Vertical 7205.68 54.49 43.50 11.40 35.50 3.40 47.72 54.00 -6.28 AV Horizontal Hiddle Channel (2441 MHz) 3264.77 62.13 44.70 6.70 28.20 -9.80 52.33 74.00 -21.67 PK Vertical 3264.85 61.57 44.70 6.70 28.20 -9.80 51.77 74.00 -22.23 PK Horizontal 3	5359.76	48.22	44.20	9.86	32.00	-2.34	45.88	74.00	-28.12	PK	Vertical
5359.67 39.39 44.20 9.86 32.00 -2.34 37.05 54.00 -16.95 AV Horizontal 7205.85 54.46 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Vertical 7205.85 43.61 43.50 11.40 35.50 3.40 47.01 54.00 -6.99 AV Vertical 7205.68 54.49 43.50 11.40 35.50 3.40 57.89 74.00 -16.11 PK Horizontal Middle Channel (2441 MHz) 3264.77 62.13 44.70 6.70 28.20 -9.80 52.33 74.00 -21.67 PK Vertical 3264.77 50.53 44.70 6.70 28.20 -9.80 51.77 74.00 -22.23 PK Horizontal 3264.85 61.57 44.70 6.70 28.20 -9.80 51.77 74.00 -22.23 PK Horizontal 4882.57	5359.76	39.60	44.20	9.86	32.00	-2.34	37.26	54.00	-16.74	AV	Vertical
7205.85 54.46 43.50 11.40 35.50 3.40 57.86 74.00 -16.14 PK Vertical 7205.85 43.61 43.50 11.40 35.50 3.40 47.01 54.00 -6.99 AV Vertical 7205.68 54.49 43.50 11.40 35.50 3.40 57.89 74.00 -16.11 PK Horizontal Middle Channel (2441 MHz) Widdle Channel (2441 MHz) 3264.77 62.13 44.70 6.70 28.20 -9.80 52.33 74.00 -21.67 PK Vertical 3264.77 50.53 44.70 6.70 28.20 -9.80 52.33 74.00 -21.67 PK Vertical 3264.85 61.57 44.70 6.70 28.20 -9.80 51.77 74.00 -22.23 PK Horizontal 4882.57 59.12 44.20 9.04 31.60 -3.56 55.56 74.00 -18.44 PK	5359.67	47.70	44.20	9.86	32.00	-2.34	45.36	74.00	-28.64	PK	Horizontal
7205.85 43.61 43.50 11.40 35.50 3.40 47.01 54.00 -6.99 AV Vertical 7205.68 54.49 43.50 11.40 35.50 3.40 57.89 74.00 -16.11 PK Horizontal Middle Channel (2441 MHz) 3264.77 62.13 44.70 6.70 28.20 -9.80 52.33 74.00 -21.67 PK Vertical 3264.77 50.53 44.70 6.70 28.20 -9.80 40.73 54.00 -13.27 AV Vertical 3264.85 61.57 44.70 6.70 28.20 -9.80 51.77 74.00 -22.23 PK Horizontal 4882.57 59.12 44.70 6.70 28.20 -9.80 45.77 74.00 -22.23 PK Horizontal 4882.57 59.12 44.20 9.04 31.60 -3.56 55.56 74.00 -18.44 PK Vertical 4882.50	5359.67	39.39	44.20	9.86	32.00	-2.34	37.05	54.00	-16.95	AV	Horizontal
7205.68 54.49 43.50 11.40 35.50 3.40 57.89 74.00 -16.11 PK Horizontal 7205.68 44.32 43.50 11.40 35.50 3.40 47.72 54.00 -6.28 AV Horizontal Middle Channel (2441 MHz) 3264.77 62.13 44.70 6.70 28.20 -9.80 52.33 74.00 -21.67 PK Vertical 3264.77 50.53 44.70 6.70 28.20 -9.80 40.73 54.00 -13.27 AV Vertical 3264.85 61.57 44.70 6.70 28.20 -9.80 51.77 74.00 -22.23 PK Horizontal 3264.85 50.79 44.70 6.70 28.20 -9.80 40.99 54.00 -13.01 AV Horizontal 4882.57 59.12 44.20 9.04 31.60 -3.56 55.56 74.00 -18.44 PK Vertical 4882.50 <td< td=""><td>7205.85</td><td>54.46</td><td>43.50</td><td>11.40</td><td>35.50</td><td>3.40</td><td>57.86</td><td>74.00</td><td>-16.14</td><td>PK</td><td>Vertical</td></td<>	7205.85	54.46	43.50	11.40	35.50	3.40	57.86	74.00	-16.14	PK	Vertical
7205.68 44.32 43.50 11.40 35.50 3.40 47.72 54.00 -6.28 AV Horizontal Middle Channel (2441 MHz) 3264.77 62.13 44.70 6.70 28.20 -9.80 52.33 74.00 -21.67 PK Vertical 3264.77 50.53 44.70 6.70 28.20 -9.80 40.73 54.00 -13.27 AV Vertical 3264.85 61.57 44.70 6.70 28.20 -9.80 51.77 74.00 -22.23 PK Horizontal 3264.85 50.79 44.70 6.70 28.20 -9.80 40.99 54.00 -13.01 AV Horizontal 4882.57 59.12 44.20 9.04 31.60 -3.56 55.56 74.00 -18.44 PK Vertical 4882.57 49.42 44.20 9.04 31.60 -3.56 45.86 54.00 -8.14 AV Vertical 4882.50 58	7205.85	43.61	43.50	11.40	35.50	3.40	47.01	54.00	-6.99	AV	Vertical
Middle Channel (2441 MHz) 3264.77 62.13 44.70 6.70 28.20 -9.80 52.33 74.00 -21.67 PK Vertical 3264.77 50.53 44.70 6.70 28.20 -9.80 40.73 54.00 -13.27 AV Vertical 3264.85 61.57 44.70 6.70 28.20 -9.80 40.99 54.00 -13.01 AV Horizontal 4882.57 59.12 44.20 9.04 31.60 -3.56 55.56 74.00 -18.44 PK Vertical 4882.57 49.42 44.20 9.04 31.60 -3.56 55.56 74.00 -8.14 AV Vertical 4882.50 58.92 44.20 9.04 31.60 -3.56 55.36 74.00 -18.64 PK Horizontal 4882.50 49.63 44.20 9.04 31.60 -3.56 55.36 74.00 -18.64 PK Horizontal 5359.66 3	7205.68	54.49	43.50	11.40	35.50	3.40	57.89	74.00	-16.11	PK	Horizontal
3264.77 62.13 44.70 6.70 28.20 -9.80 52.33 74.00 -21.67 PK Vertical 3264.77 50.53 44.70 6.70 28.20 -9.80 40.73 54.00 -13.27 AV Vertical 3264.85 61.57 44.70 6.70 28.20 -9.80 51.77 74.00 -22.23 PK Horizontal 3264.85 50.79 44.70 6.70 28.20 -9.80 40.99 54.00 -13.01 AV Horizontal 4882.57 59.12 44.20 9.04 31.60 -3.56 55.56 74.00 -18.44 PK Vertical 4882.57 49.42 44.20 9.04 31.60 -3.56 45.86 54.00 -8.14 AV Vertical 4882.50 49.63 44.20 9.04 31.60 -3.56 45.86 54.00 -7.93 AV Horizontal 5359.66 49.44 44.20 9.86 32.00 <td>7205.68</td> <td>44.32</td> <td>43.50</td> <td>11.40</td> <td>35.50</td> <td>3.40</td> <td>47.72</td> <td>54.00</td> <td>-6.28</td> <td>AV</td> <td>Horizontal</td>	7205.68	44.32	43.50	11.40	35.50	3.40	47.72	54.00	-6.28	AV	Horizontal
3264.77 50.53 44.70 6.70 28.20 -9.80 40.73 54.00 -13.27 AV Vertical 3264.85 61.57 44.70 6.70 28.20 -9.80 51.77 74.00 -22.23 PK Horizontal 3264.85 50.79 44.70 6.70 28.20 -9.80 40.99 54.00 -13.01 AV Horizontal 4882.57 59.12 44.20 9.04 31.60 -3.56 55.56 74.00 -18.44 PK Vertical 4882.57 49.42 44.20 9.04 31.60 -3.56 45.86 54.00 -8.14 AV Vertical 4882.50 58.92 44.20 9.04 31.60 -3.56 55.36 74.00 -18.64 PK Horizontal 4882.50 49.63 44.20 9.04 31.60 -3.56 46.07 54.00 -7.93 AV Horizontal 5359.66 49.44 44.20 9.86 32.00<					Middle	Channel (244	1 MHz)				
3264.85 61.57 44.70 6.70 28.20 -9.80 51.77 74.00 -22.23 PK Horizontal 3264.85 50.79 44.70 6.70 28.20 -9.80 40.99 54.00 -13.01 AV Horizontal 4882.57 59.12 44.20 9.04 31.60 -3.56 55.56 74.00 -18.44 PK Vertical 4882.57 49.42 44.20 9.04 31.60 -3.56 45.86 54.00 -8.14 AV Vertical 4882.50 58.92 44.20 9.04 31.60 -3.56 55.36 74.00 -18.64 PK Horizontal 4882.50 49.63 44.20 9.04 31.60 -3.56 55.36 74.00 -18.64 PK Horizontal 5359.66 49.44 44.20 9.86 32.00 -2.34 47.10 74.00 -26.90 PK Vertical 5359.86 47.44 44.20 9.86 32.00	3264.77	62.13	44.70	6.70	28.20	-9.80	52.33	74.00	-21.67	PK	Vertical
3264.85 50.79 44.70 6.70 28.20 -9.80 40.99 54.00 -13.01 AV Horizontal 4882.57 59.12 44.20 9.04 31.60 -3.56 55.56 74.00 -18.44 PK Vertical 4882.57 49.42 44.20 9.04 31.60 -3.56 45.86 54.00 -8.14 AV Vertical 4882.50 58.92 44.20 9.04 31.60 -3.56 55.36 74.00 -18.64 PK Horizontal 4882.50 49.63 44.20 9.04 31.60 -3.56 46.07 54.00 -7.93 AV Horizontal 5359.66 49.44 44.20 9.86 32.00 -2.34 47.10 74.00 -26.90 PK Vertical 5359.86 39.20 44.20 9.86 32.00 -2.34 45.10 74.00 -28.90 PK Horizontal 5359.86 38.65 44.20 9.86 32.00<	3264.77	50.53	44.70	6.70	28.20	-9.80	40.73	54.00	-13.27	AV	Vertical
4882.57 59.12 44.20 9.04 31.60 -3.56 55.56 74.00 -18.44 PK Vertical 4882.57 49.42 44.20 9.04 31.60 -3.56 45.86 54.00 -8.14 AV Vertical 4882.50 58.92 44.20 9.04 31.60 -3.56 55.36 74.00 -18.64 PK Horizontal 4882.50 49.63 44.20 9.04 31.60 -3.56 46.07 54.00 -7.93 AV Horizontal 5359.66 49.44 44.20 9.86 32.00 -2.34 47.10 74.00 -26.90 PK Vertical 5359.86 39.20 44.20 9.86 32.00 -2.34 36.86 54.00 -17.14 AV Vertical 5359.86 37.44 44.20 9.86 32.00 -2.34 45.10 74.00 -28.90 PK Horizontal 5359.86 38.65 44.20 9.86 32.00 <td>3264.85</td> <td>61.57</td> <td>44.70</td> <td>6.70</td> <td>28.20</td> <td>-9.80</td> <td>51.77</td> <td>74.00</td> <td>-22.23</td> <td>PK</td> <td>Horizontal</td>	3264.85	61.57	44.70	6.70	28.20	-9.80	51.77	74.00	-22.23	PK	Horizontal
4882.57 49.42 44.20 9.04 31.60 -3.56 45.86 54.00 -8.14 AV Vertical 4882.50 58.92 44.20 9.04 31.60 -3.56 55.36 74.00 -18.64 PK Horizontal 4882.50 49.63 44.20 9.04 31.60 -3.56 46.07 54.00 -7.93 AV Horizontal 5359.66 49.44 44.20 9.86 32.00 -2.34 47.10 74.00 -26.90 PK Vertical 5359.66 39.20 44.20 9.86 32.00 -2.34 36.86 54.00 -17.14 AV Vertical 5359.86 47.44 44.20 9.86 32.00 -2.34 45.10 74.00 -28.90 PK Horizontal 5359.86 38.65 44.20 9.86 32.00 -2.34 36.31 54.00 -17.69 AV Horizontal 7323.92 54.44 43.50 11.40 35.50	3264.85	50.79	44.70	6.70	28.20	-9.80	40.99	54.00	-13.01	AV	Horizontal
4882.50 58.92 44.20 9.04 31.60 -3.56 55.36 74.00 -18.64 PK Horizontal 4882.50 49.63 44.20 9.04 31.60 -3.56 46.07 54.00 -7.93 AV Horizontal 5359.66 49.44 44.20 9.86 32.00 -2.34 47.10 74.00 -26.90 PK Vertical 5359.66 39.20 44.20 9.86 32.00 -2.34 36.86 54.00 -17.14 AV Vertical 5359.86 47.44 44.20 9.86 32.00 -2.34 45.10 74.00 -28.90 PK Horizontal 5359.86 38.65 44.20 9.86 32.00 -2.34 36.31 54.00 -17.69 AV Horizontal 7323.92 54.44 43.50 11.40 35.50 3.40 57.84 74.00 -16.16 PK Vertical 7323.81 54.70 43.50 11.40 35.5	4882.57	59.12	44.20	9.04	31.60	-3.56	55.56	74.00	-18.44	PK	Vertical
4882.50 49.63 44.20 9.04 31.60 -3.56 46.07 54.00 -7.93 AV Horizontal 5359.66 49.44 44.20 9.86 32.00 -2.34 47.10 74.00 -26.90 PK Vertical 5359.66 39.20 44.20 9.86 32.00 -2.34 36.86 54.00 -17.14 AV Vertical 5359.86 47.44 44.20 9.86 32.00 -2.34 45.10 74.00 -28.90 PK Horizontal 5359.86 38.65 44.20 9.86 32.00 -2.34 36.31 54.00 -17.69 AV Horizontal 7323.92 54.44 43.50 11.40 35.50 3.40 57.84 74.00 -16.16 PK Vertical 7323.92 44.64 43.50 11.40 35.50 3.40 58.10 74.00 -15.90 PK Horizontal	4882.57	49.42	44.20	9.04	31.60	-3.56	45.86	54.00	-8.14	AV	Vertical
5359.66 49.44 44.20 9.86 32.00 -2.34 47.10 74.00 -26.90 PK Vertical 5359.66 39.20 44.20 9.86 32.00 -2.34 36.86 54.00 -17.14 AV Vertical 5359.86 47.44 44.20 9.86 32.00 -2.34 45.10 74.00 -28.90 PK Horizontal 5359.86 38.65 44.20 9.86 32.00 -2.34 36.31 54.00 -17.69 AV Horizontal 7323.92 54.44 43.50 11.40 35.50 3.40 57.84 74.00 -16.16 PK Vertical 7323.92 44.64 43.50 11.40 35.50 3.40 48.04 54.00 -5.96 AV Vertical 7323.81 54.70 43.50 11.40 35.50 3.40 58.10 74.00 -15.90 PK Horizontal	4882.50	58.92	44.20	9.04	31.60	-3.56	55.36	74.00	-18.64	PK	Horizontal
5359.66 39.20 44.20 9.86 32.00 -2.34 36.86 54.00 -17.14 AV Vertical 5359.86 47.44 44.20 9.86 32.00 -2.34 45.10 74.00 -28.90 PK Horizontal 5359.86 38.65 44.20 9.86 32.00 -2.34 36.31 54.00 -17.69 AV Horizontal 7323.92 54.44 43.50 11.40 35.50 3.40 57.84 74.00 -16.16 PK Vertical 7323.92 44.64 43.50 11.40 35.50 3.40 48.04 54.00 -5.96 AV Vertical 7323.81 54.70 43.50 11.40 35.50 3.40 58.10 74.00 -15.90 PK Horizontal	4882.50	49.63	44.20	9.04	31.60	-3.56	46.07	54.00	-7.93	AV	Horizontal
5359.86 47.44 44.20 9.86 32.00 -2.34 45.10 74.00 -28.90 PK Horizontal 5359.86 38.65 44.20 9.86 32.00 -2.34 36.31 54.00 -17.69 AV Horizontal 7323.92 54.44 43.50 11.40 35.50 3.40 57.84 74.00 -16.16 PK Vertical 7323.92 44.64 43.50 11.40 35.50 3.40 48.04 54.00 -5.96 AV Vertical 7323.81 54.70 43.50 11.40 35.50 3.40 58.10 74.00 -15.90 PK Horizontal	5359.66	49.44	44.20	9.86	32.00	-2.34	47.10	74.00	-26.90	PK	Vertical
5359.86 38.65 44.20 9.86 32.00 -2.34 36.31 54.00 -17.69 AV Horizontal 7323.92 54.44 43.50 11.40 35.50 3.40 57.84 74.00 -16.16 PK Vertical 7323.92 44.64 43.50 11.40 35.50 3.40 48.04 54.00 -5.96 AV Vertical 7323.81 54.70 43.50 11.40 35.50 3.40 58.10 74.00 -15.90 PK Horizontal	5359.66	39.20	44.20	9.86	32.00	-2.34	36.86	54.00	-17.14	AV	Vertical
7323.92 54.44 43.50 11.40 35.50 3.40 57.84 74.00 -16.16 PK Vertical 7323.92 44.64 43.50 11.40 35.50 3.40 48.04 54.00 -5.96 AV Vertical 7323.81 54.70 43.50 11.40 35.50 3.40 58.10 74.00 -15.90 PK Horizontal	5359.86	47.44	44.20	9.86	32.00	-2.34	45.10	74.00	-28.90	PK	Horizontal
7323.92 44.64 43.50 11.40 35.50 3.40 48.04 54.00 -5.96 AV Vertical 7323.81 54.70 43.50 11.40 35.50 3.40 58.10 74.00 -15.90 PK Horizontal	5359.86	38.65	44.20	9.86	32.00	-2.34	36.31	54.00	-17.69	AV	Horizontal
7323.81 54.70 43.50 11.40 35.50 3.40 58.10 74.00 -15.90 PK Horizontal	7323.92	54.44	43.50	11.40	35.50	3.40	57.84	74.00	-16.16	PK	Vertical
	7323.92	44.64	43.50	11.40	35.50	3.40	48.04	54.00	-5.96	AV	Vertical
7222.94 42.00 42.50 44.40 25.50 2.40 47.00 54.00 0.04 AV Usingst	7323.81	54.70	43.50	11.40	35.50	3.40	58.10	74.00	-15.90	PK	Horizontal
7323.01 43.99 43.90 11.40 35.90 3.40 47.39 54.00 -0.61 AV Horizontal	7323.81	43.99	43.50	11.40	35.50	3.40	47.39	54.00	-6.61	AV	Horizontal

Page 26 of 68 Report No.: STS1903100W03

	High Channel (2480 MHz)									
3264.65	61.47	44.70	6.70	28.20	-9.80	51.67	74.00	-22.33	PK	Vertical
3264.65	50.85	44.70	6.70	28.20	-9.80	41.05	54.00	-12.95	AV	Vertical
3264.62	62.24	44.70	6.70	28.20	-9.80	52.44	74.00	-21.56	PK	Horizontal
3264.62	49.84	44.70	6.70	28.20	-9.80	40.04	54.00	-13.96	AV	Horizontal
4960.55	59.49	44.20	9.04	31.60	-3.56	55.93	74.00	-18.07	PK	Vertical
4960.55	49.57	44.20	9.04	31.60	-3.56	46.01	54.00	-7.99	AV	Vertical
4960.58	58.56	44.20	9.04	31.60	-3.56	55.00	74.00	-19.00	PK	Horizontal
4960.58	49.65	44.20	9.04	31.60	-3.56	46.09	54.00	-7.91	AV	Horizontal
5359.85	49.16	44.20	9.86	32.00	-2.34	46.82	74.00	-27.18	PK	Vertical
5359.85	39.08	44.20	9.86	32.00	-2.34	36.74	54.00	-17.26	AV	Vertical
5359.75	47.79	44.20	9.86	32.00	-2.34	45.45	74.00	-28.55	PK	Horizontal
5359.75	38.18	44.20	9.86	32.00	-2.34	35.84	54.00	-18.16	AV	Horizontal
7439.87	54.00	43.50	11.40	35.50	3.40	57.40	74.00	-16.60	PK	Vertical
7439.87	44.40	43.50	11.40	35.50	3.40	47.80	54.00	-6.20	AV	Vertical
7439.94	54.20	43.50	11.40	35.50	3.40	57.60	74.00	-16.40	PK	Horizontal
7439.94	44.82	43.50	11.40	35.50	3.40	48.22	54.00	-5.78	AV	Horizontal

Note:

3)

- 1) Scan with GFSK, $\pi/4$ -DQPSK,8DPSK,the worst case is $\pi/4$ -DQPSK Mode
- 2) Factor = Antenna Factor + Cable Loss Pre-amplifier.

Emission Level = Reading + Factor


The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency

emission is mainly from the environment noise.




Restricted band Requirements

GFSK-Low Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2383.616	58.11	-10.52	47.59	74.00	-26.41	peak
2	2390.000	56.02	-10.48	45.54	74.00	-28.46	peak


Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2381.536	57.13	-10.54	46.59	74.00	-27.41	peak
2	2390.000	55.36	-10.48	44.88	74.00	-29.12	peak




GFSK-High Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.500	56.17	-9.99	46.18	74.00	-27.82	peak
2	2488.440	58.17	-9.97	48.20	74.00	-25.80	peak

Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.500	56.95	-9.99	46.96	74.00	-27.04	peak
2	2491.176	58.19	-9.95	48.24	74.00	-25.76	peak

Note: GFSK, $\pi/4$ -DQPSK, 8DPSK of the nohopping and hopping mode all have been test, the worst case is GFSK of the nohopping mode, this report only show the worst case.



4. CONDUCTED SPURIOUS & BAND EDGE EMISSION

4.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

4.2 TEST PROCEDURE

Spectrum Parameter	Setting			
Detector	Peak			
Start/Stop Frequency	30 MHz to 10th carrier harmonic			
RB / VB (emission in restricted band)	100 KHz/300 KHz			
Trace-Mode:	Max hold			

For Band edge

Spectrum Parameter	Setting			
Detector	Peak			
Stort/Stop Fraguancy	Lower Band Edge: 2300– 2403 MHz			
Start/Stop Frequency	Upper Band Edge: 2479 – 2500 MHz			
RB / VB (emission in restricted band)	100 KHz/300 KHz			
Trace-Mode:	Max hold			

Remark: Hopping on and Hopping off mode all have been tested, only worst case hopping off is reported.

4.3 TEST SETUP



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.


4.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.





4.5 TEST RESULTS

Temperature:	25 ℃	Relative Humidity:	50%
Test Mode:	GFSK(1Mbps)-00/39/78 CH	Test Voltage:	DC 11.1V



39 CH








For Band edge

00 CH









For Hopping Band edge

00 CH









Page 34 of 68 Report No.: STS1903100W03


Temperature:	25℃	Relative Humidity:	50%
TAGE MINANA	π/4-DQPSK(2Mbps)– 00/39/78 CH	Test Voltage:	DC 11.1V

00 CH












For Band edge

00 CH








For Hopping Band edge

00 CH














Temperature:	25 ℃	Relative Humidity:	50%
Test Mode:	8DPSK(3Mbps) -00/39/78 CH	Test Voltage:	DC 11.1V

00 CH












For Band edge

00 CH









For Hopping Band edge

00 CH







5. NUMBER OF HOPPING CHANNEL

5.1 LIMIT

FCC Part 15.247,Subpart C				
Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating FrequencyRange
RB	100KHz
VB	100KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

5.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

5.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.








5.5 TEST RESULTS

Temperature:	25 ℃	Relative Humidity:	60%
Test Mode:	Hopping Mode -GFSK Mode	Test Voltage:	DC 11.1V

Number of Hopping Channel

79

Hopping channel





6. AVERAGE TIME OF OCCUPANCY

6.1 LIMIT

FCC Part 15.247,Subpart C				
Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

6.2 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW =1MHz/VBW =3MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.

 Set the center frequency on any frequency would be measure and set the frequency span to
- e. zero span.
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. DH5 Packet permit maximum 1600/79 / 6 = 3.37 hops per second in each channel (5 time slots RX, 1 time slot TX). Sothe dwell time is the time duration of the pulse times 3.37 x 31.6 = 106.6 within 31.6 seconds.
- j. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots RX, 1 time slot TX). Sothe dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds.
- k. DH1 Packet permit maximum 1600 / 79 / 2 = 10.12 hops per second in each channel (1 time slot RX, 1 time slot TX). So the dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds.

6.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

6.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.







6.5 TEST RESULTS


Temperature:	25 ℃	Relative Humidity:	50%
Test Mode:	GFSK(1Mbps)-DH1/DH3/DH5	Test Voltage:	DC 11.1V

Data Packet	Channel	pulse time(ms)	Dwell Time(s)	Limits(s)
DH1	middle	0.382	0.122	0.4
DH3	middle	1.645	0.263	0.4
DH5	middle	2.892	0.308	0.4






CH39-DH1



CH39-DH3



CH39-DH5





Page 47 of 68 Report No.: STS1903100W03

Temperature:	25 ℃	Relative Humidity:	50%
LAST MICHAE.	π/4-DQPSK(2Mbps)– 2DH1/2DH3/2DH5	Test Voltage:	DC 11.1V

Data Packet	Channel	pulse time(ms)	Dwell Time(s)	Limits(s)
2DH1	middle	0.391	0.125	0.4
2DH3	middle	1.650	0.264	0.4
2DH5	middle	2.900	0.309	0.4





CH39-2DH1


Page 48 of 68



CH39-2DH3



CH39-2DH5





Page 49 of 68 Report No.: STS1903100W03


Temperature:	25 ℃	Relative Humidity:	50%
I DEL IMOND.	8DPSK(3Mbps)- 3DH1/3DH3/3DH5	Test Voltage:	DC 11.1V

Data Packet	Channel	pulse time(ms)	Dwell Time(s)	Limits(s)
3DH1	middle	0.391	0.125	0.4
3DH3	middle	1.648	0.264	0.4
3DH5	middle	2.897	0.309	0.4







CH39-3DH1



CH39-3DH3



CH39-3DH5





7. HOPPING CHANNEL SEPARATION MEASUREMEN

7.1 LIMIT


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> 20 dB Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.2 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- b. The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
- c. The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

7.3 TEST SETUP



7.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.



7.5 TEST RESULTS

Temperature:	25 ℃	Relative Humidity:	50%
I LOCT IVIDAD.	CH00 / CH39 / CH78 (GFSK(1Mbps) Mode)	Test Voltage:	DC 11.1V

Frequency	Ch. Separation (MHz)	Limit (MHz)	Result
2402 MHz	0.996	0.747	Complies
2441 MHz	0.999	0.742	Complies
2480 MHz	1.002	0.744	Complies

For GFSK: Ch. Separation Limits: > 20dB bandwidth

CH00 -1Mbps



CH39 -1Mbps



CH78 -1Mbps





Temperature:	25 ℃	Relative Humidity:	50%
LIAST IVIDAA'	CH00 / CH39 / CH78 (π/4-DQPSK(2Mbps) Mode)	Test Voltage:	DC 11.1V

Frequency	Ch. Separation (MHz)	Limit (MHz)	Result
2402 MHz	0.999	0.881	Complies
2441 MHz	0.999	0.883	Complies
2480 MHz	1.002	0.883	Complies

For $\pi/4$ -DQPSK(2Mbps): Ch. Separation Limits: > two-thirds 20dB bandwidth

CH00 -2Mbps





CH39 -2Mbps



CH78 -2Mbps





Page 56 of 68 Report No.: STS1903100W03

Temperature:	25℃	Relative Humidity:	50%
I LAST IVIDAA'	CH00 / CH39 / CH78 (8DPSK(3Mbps)Mode)	Test Voltage:	DC 11.1V


Frequency	Ch. Separation (MHz)	Limit (MHz)	Result
2402 MHz	0.996	0.946	Complies
2441 MHz	1.002	0.946	Complies
2480 MHz	1.002	0.947	Complies

For 8DPSK(3Mbps):Ch. Separation Limits: > two-thirds 20dB bandwidth CH00 -3Mbps





CH39 -3Mbps



CH78 -3Mbps





8. BANDWIDTH TEST

8.1 LIMIT

FCC Part15 15.247,Subpart C				
Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting	
Attenuation	Auto	
Span Frequency	> Measurement Bandwidth or Channel Separation	
RB	30 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)	
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)	
Detector	Peak	
Trace	Max Hold	
Sweep Time	Auto	

8.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

8.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

8.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



8.5 TEST RESULTS

Temperature:	25℃	Relative Humidity:	50%
I DEL IVIDAD.	GFSK(1Mbps) CH00 / CH39 / C78	Test Voltage:	DC 11.1V

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	0.747	PASS
2441 MHz	0.742	PASS
2480 MHz	0.744	PASS

CH00 -1Mbps





CH39 -1Mbps



CH78 -1Mbps





Page 61 of 68 Report No.: STS1903100W03

Temperature:	25℃	Relative Humidity:	50%
I DEL IMOND.	π/4-DQPSK(2Mbps) CH00 / CH39 / C78	Test Voltage:	DC 11.1V


Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.322	PASS
2441 MHz	1.324	PASS
2480 MHz	1.324	PASS

CH00 -2Mbps






CH39 -2Mbps



CH78 -2Mbps






Page 63 of 68 Report No.: STS1903100W03

Temperature:	25 ℃	Relative Humidity:	50%
LIDST MINOUD.	8DPSK(3Mbps) CH00 / CH39 / CH78	Test Voltage:	DC 11.1V


Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.419	PASS
2441 MHz	1.419	PASS
2480 MHz	1.421	PASS

CH00 -3Mbps





CH39 -3Mbps



CH78 -3Mbps





9. OUTPUT POWER TEST


9.1 LIMIT

FCC Part 15.247,Subpart C					
Section	Test Item	Limit	FrequencyRange (MHz)	Result	
15 247		1 W or 0.125W			
15.247 Output (a)(1)&(b)(1) Power	if channel separation > 2/3 bandwidthprovided thesystems operatewith an output power no greater than125 mW(20.97dBm)	2400-2483.5	PASS		

9.2 TEST PROCEDURE

a. The EUT was directly connected to the Power Sensor&PC

9.3 TEST SETUP



9.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

Page 66 of 68 Report No.: STS1903100W03

9.5 TEST RESULTS

Temperature:	25 ℃	Relative Humidity:	60%
Test Voltage:	DC 11.1V		

Mode Channel Number		Frequency		Peak Power	Average Power	Limit
	(MHz)	(dBm)	(dBm)	(dBm)		
	0	2402	5.10	-0.17	30.00	
GFSK(1M)	39	2441	6.23	0.98	30.00	
	78	2480	4.38	-0.94	30.00	

Note: the channel separation >20dB bandwidth

Mode Channel Number		Frequency	Peak Power	Average Power	Limit
	(MHz) (dBm)	(dBm)	(dBm)		
	0	2402	6.89	-0.12	20.97
π/4-DQPSK(2bps)	39	2441	8.19	1.09	20.97
	78	2480	6.60	-0.83	20.97

Note: the channel separation >2/3 20dB bandwidth

Mode Channel Number		Frequency	Peak Power	Average Power	Limit
	(MHz) (dBm)	(dBm)	(dBm)	(dBm)	
	0	2402	6.17	-0.95	20.97
8-DPSK(3Mb ps)	39	2441	7.51	0.24	20.97
. ,	78	2480	5.95	-1.56	20.97

Note: the channel separation >2/3 20dB bandwidth



10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA

The EUT antenna is PIFA Antenna. It comply with the standard requirement.





APPENDIX-PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

* * * * * END OF THE REPORT * * * * *

