



No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM160800662601

Page: 1 of 49

## FCC REPORT

**Application No:** SZEM1608006626CR

**Applicant:** Notch Interfaces Inc.

**Manufacturer:** PC Partner Limited

**Factory:** PC Partner Limited

**Product Name:** Notch Motion Capture Sensor Kit

**Model No.(EUT):** NSBL1

**Trade Mark:** NOTCH

**FCC ID:** 2AI9F-NSBL1

**Standards:** 47 CFR Part 15, Subpart C (2015)

**Date of Receipt:** 2016-08-11

**Date of Test:** 2016-08-15 to 2016-08-24

**Date of Issue:** 2016-08-25

<b>Test Result:</b>	<b>PASS *</b>
---------------------	---------------

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:




Jack Zhang  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

## 2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2016-08-25		Original

Authorized for issue by:			
Tested By		2016-08-24	Date
	(Edison Li) /Project Engineer		
Checked By		2016-08-25	Date
	(Eric Fu) /Reviewer		

### 3 Test Summary

Test Item	Test Requirement	Test method	Result
<b>Antenna Requirement</b>	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
<b>AC Power Line Conducted Emission</b>	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
<b>Conducted Peak Output Power</b>	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
<b>6dB Occupied Bandwidth</b>	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
<b>Power Spectral Density</b>	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
<b>Band-edge for RF Conducted Emissions</b>	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
<b>RF Conducted Spurious Emissions</b>	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
<b>Radiated Spurious Emissions</b>	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
<b>Restricted bands around fundamental frequency (Radiated Emission)</b>	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

## 4 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 VERSION .....</b>	<b>2</b>
<b>3 TEST SUMMARY .....</b>	<b>3</b>
<b>4 CONTENTS .....</b>	<b>4</b>
<b>5 GENERAL INFORMATION .....</b>	<b>5</b>
5.1 CLIENT INFORMATION .....	5
5.2 GENERAL DESCRIPTION OF EUT .....	5
5.3 TEST ENVIRONMENT .....	7
5.4 DESCRIPTION OF SUPPORT UNITS .....	7
5.5 TEST LOCATION .....	7
5.6 TEST FACILITY .....	8
5.7 DEVIATION FROM STANDARDS .....	8
5.8 ABNORMALITIES FROM STANDARD CONDITIONS .....	8
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	8
5.10 EQUIPMENT LIST .....	9
<b>6 TEST RESULTS AND MEASUREMENT DATA .....</b>	<b>11</b>
6.1 ANTENNA REQUIREMENT .....	11
6.2 CONDUCTED EMISSIONS .....	12
6.3 CONDUCTED PEAK OUTPUT POWER .....	16
6.4 6dB OCCUPY BANDWIDTH .....	19
6.5 POWER SPECTRAL DENSITY .....	22
6.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS .....	25
6.7 SPURIOUS RF CONDUCTED EMISSIONS .....	27
6.8 RADIATED SPURIOUS EMISSION .....	34
6.8.1 <i>Spurious Emissions</i> .....	34
6.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY .....	42
<b>7 PHOTOGRAPHS - EUT TEST SETUP .....</b>	<b>48</b>
7.1 CONDUCTED EMISSION .....	48
7.2 RADIATED EMISSION .....	48
7.3 RADIATED SPURIOUS EMISSION .....	49
<b>8 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS .....</b>	<b>49</b>

## 5 General Information

### 5.1 Client Information

Applicant:	Notch Interfaces Inc.
Address of Applicant:	630 Flushing Ave Brooklyn NY 11206 USA
Manufacturer:	PC Partner Limited
Address of Manufacturer:	19/F., Shatin Galleria, 18-24 Shan Mei Street, Fo Tan, Shatin, N.T. Hong Kong
Factory:	PC Partner Limited
Address of Factory:	19/F., Shatin Galleria, 18-24 Shan Mei Street, Fo Tan, Shatin, N.T. Hong Kong

### 5.2 General Description of EUT

Product Name:	Notch Motion Capture Sensor Kit
Model No.:	NSBL1
Trade Mark:	NOTCH
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	Bluetooth 4.0 BLE
Modulation Type:	GFSK
Number of Channel:	40
Antenna Type:	Integral
Antenna Gain:	3dBi
Battery:	DC 3.7V, 70mAh, Li-polymer battery

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

**Note:**

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel (CH0)	2402MHz
The middle channel (CH19)	2440MHz
The highest channel (CH39)	2480MHz

### **5.3 Test Environment**

<b>Operating Environment:</b>	
Temperature:	25.0 °C
Humidity:	53 % RH
Atmospheric Pressure:	1010mbar

### **5.4 Description of Support Units**

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
Adapter	Apple	A1357 W010A051

### **5.5 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch  
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
518057.  
Tel: +86 755 2601 2053 Fax: +86 755 2671 0594  
No tests were sub-contracted.

## 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

## 5.7 Deviation from Standards

None.

## 5.8 Abnormalities from Standard Conditions

None.

## 5.9 Other Information Requested by the Customer

None.

## 5.10 Equipment List

<b>Conducted Emission</b>						
<b>Item</b>	<b>Test Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Inventory No.</b>	<b>Cal. date (yyyy-mm-dd)</b>	<b>Cal.Due date (yyyy-mm-dd)</b>
1	Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2016-05-13	2017-05-13
2	LISN	Rohde & Schwarz	ENV216	SEM007-01	2015-10-09	2016-10-09
3	LISN	ETS-LINDGREN	3816/2	SEM007-02	2016-04-25	2017-04-25
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2015-10-30	2016-10-30
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2015-10-30	2016-10-30
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	EMC0122	2015-10-30	2016-10-30
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2016-04-25	2017-04-25
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2015-10-09	2016-10-09

<b>RF connected test</b>						
<b>Item</b>	<b>Test Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Inventory No.</b>	<b>Cal. date (yyyy-mm-dd)</b>	<b>Cal.Due date (yyyy-mm-dd)</b>
1	DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2015-10-09	2016-10-09
2	Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2015-10-17	2016-10-17
3	Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
4	Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2015-10-09	2016-10-09


RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2016-05-13	2017-05-13
2	EMI Test Receiver (9k-3GHz)	Rohde & Schwarz	ESCI	SEM004-01	2016-04-25	2017-04-25
3	Trilog-Broadband Antenna(30M-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-06-29	2019-06-29
4	Pre-amplifier	Sonoma Instrument Co	310N	SEM005-03	2016-07-06	2017-07-06
5	Loop Antenna	ETS-Lindgren	6502	SEM003-08	2015-08-14	2018-08-14

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2016-05-13	2017-05-13
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEM004-04	2016-04-25	2017-04-25
3	BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2014-11-15	2017-11-15
4	Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2015-10-09	2016-10-09
5	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
6	Low Noise Amplifier	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2015-10-09	2016-10-09
7	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A
8	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2014-11-24	2017-11-24

## 6 Test results and Measurement Data

### 6.1 Antenna Requirement

<b>Standard requirement:</b>	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
15.247(b) (4) requirement:	The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
<b>EUT Antenna:</b>	The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3dBi.



## 6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)		Limit (dBuV)
	Quasi-peak	Average	
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	<ol style="list-style-type: none"> <li>1) The mains terminal disturbance voltage test was conducted in a shielded room.</li> <li>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a <math>50\Omega/50\mu\text{H} + 5\Omega</math> linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li> <li>3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.</li> <li>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li> <li>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</li> </ol>		
Test Setup:			
Test Mode:	<p>Transmitting with GFSK modulation.  a. Charge + Transmitting mode.</p>		



**SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch**

Report No.: SZEM160800662601  
Page: 13 of 49


Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

**Measurement Data**

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:



Site : Shielding Room


Condition : CE LINE

Job No. : 6626CR

Test Mode : Charge+TX

Freq	Cable	LISN	Read	Over		Remark
	Loss	Factor	Level	Level	Limit	
	MHz	dB	dBuV	dBuV	dB	
1	0.15240	0.02	9.59	33.48	43.09	-12.78 Peak
2	0.20075	0.02	9.60	32.83	42.45	-11.13 Peak
3	0.24945	0.02	9.60	29.14	38.76	-13.02 Peak
4	0.39553	0.02	9.60	26.36	35.97	-11.97 Peak
5	0.61726	0.02	9.61	27.63	37.27	-8.73 Peak
6	7.213	0.08	9.68	21.12	30.88	-19.12 Peak

Neutral line:



Site : Shielding Room

Condition : CE NEUTRAL

Job No. : 6626CR


Test Mode : Charge+TX

	Freq	Cable	LISN	Read	Over	Remark
		Loss	Factor	Level	Level	
	MHz	dB	dB	dBuV	dBuV	dB
1	0.15240	0.02	9.62	34.03	43.67	-12.20 Peak
2	0.19863	0.02	9.62	31.26	40.90	-12.77 Peak
3	0.24552	0.02	9.61	28.20	37.83	-14.08 Peak
4	0.59478	0.02	9.63	27.60	37.26	-8.74 Peak
5	1.544	0.03	9.64	19.59	29.26	-16.74 Peak
6	7.566	0.09	9.75	22.13	31.97	-18.03 Peak

**Notes:**

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

### 6.3 Conducted Peak Output Power


Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10 :2013 Section 11.9.1
Test Setup:	 <p><b>Spectrum Analyzer</b> E.U.T Non-Conducted Table Ground Reference Plane</p> <p><i>Remark:</i> <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Limit:	30dBm
Test Mode:	Transmitting with GFSK modulation.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

#### Measurement Data


GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	1.88	30.00	Pass
Middle	0.02	30.00	Pass
Highest	-2.40	30.00	Pass

**Test plot as follows:**


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------



Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------



## 6.4 6dB Occupy Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013 Section 11.8
Test Setup:	
Limit:	$\geq 500$ kHz
Test Mode:	Transmitting with GFSK modulation.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

### Measurement Data


GFSK mode			
Test channel	6dB Occupy Bandwidth (kHz)	Limit (kHz)	Result
Lowest	693	$\geq 500$	Pass
Middle	603	$\geq 500$	Pass
Highest	618	$\geq 500$	Pass

**Test plot as follows:**


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------



Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------



## 6.5 Power Spectral Density


Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10 :2013 Section 11.10.2
Test Setup:	
Limit:	$\le 8.00\text{dBm}/3\text{kHz}$
Test Mode:	Transmitting with GFSK modulation.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

### Measurement Data


GFSK mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	0.02	$\le 8.00$	Pass
Middle	-2.36	$\le 8.00$	Pass
Highest	-5.07	$\le 8.00$	Pass

**Test plot as follows:**


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------



Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------




## 6.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 11.13
Test Setup:	 <p>Diagram illustrating the test setup for RF Conducted Emissions. A Spectrum Analyzer is connected to the E.U.T (Equipment Under Test) via a cable. The E.U.T is placed on a Non-Conducted Table. The entire setup is positioned above a Ground Reference Plane.</p> <p>Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</p>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Transmitting with GFSK modulation.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass


**Test plot as follows:**

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Date: 18.AUG.2016 10:36:14

Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------





Date: 18.AUG.2016 10:51:00


## 6.7 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 11.11
Test Setup:	 <p>The diagram illustrates the test setup for spurious RF conducted emissions. A Spectrum Analyzer is connected to the E.U.T (Equipment Under Test) via a cable. The setup is placed on a Non-Conducted Table, which sits above a Ground Reference Plane. The Spectrum Analyzer shows a signal spectrum.</p>
Remark:	Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Transmitting with GFSK modulation.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass



**Test plot as follows:**


Test mode: GFSK Test channel: Lowest








Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------





Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------



**Remark:**

Use 100kHz RBW to determine the relative limit in the band 2.4GHz to 2.5GHz, and Use 1MHz RBW to measure spurious emissions in the band 30MHz to 10GHz and 10GHz to 25GHz. The sweep points set to 30001.

## 6.8 Radiated Spurious Emission

<b>6.8.1 Spurious Emissions</b>					
Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 :2013 Section 11.12				
Test Site:	Measurement Distance: 3m (fully Anechoic Chamber) Measurement Distance: 10m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	29.9	29.5	Quasi-peak	10
	88MHz-216MHz	44.7	33	Quasi-peak	10
	216MHz-960MHz	60.3	35.5	Quasi-peak	10
	960MHz-1GHz	100	43.5	Quasi-peak	10
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					


Test Setup:		
	Figure 1. Below 30MHz	Figure 2. 30MHz to 1GHz
Test Procedure:	<p>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 and 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3meter fully anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or</p>	

	<p>average method as specified and then reported in a data sheet.</p> <p>h. Test the EUT in the lowest channel (2402MHz), the middle channel (2440MHz), the Highest channel (2480MHz)</p> <p>i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>j. Repeat above procedures until all frequencies measured was complete.</p>
Exploratory Test Mode:	<p>Transmitting with GFSK modulation.</p> <p>a. Charge + Transmitting mode.</p> <p>b. Transmitting mode.</p>
Final Test Mode:	<p>Transmitting with GFSK modulation.</p> <p>Pretest the EUT at Charge + Transmitting mode and Transmitting mode, found the Charge + Transmitting mode which it is worse case.</p> <p>For below 1GHz part, through pre-scan, the worst case is the lowest channel.</p> <p>Only the worst case is recorded in the report.</p>
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

**Radiated Emission below 1GHz**


30MHz~1GHz (QP)

Test mode: Charge + Transmitting mode Vertical

**Condition: 10m Vertical****Job No. : 6626CR****Test Mode: charge+TX mode**

Freq	Cable	Ant	Preamp	Read	Limit	Over		
	Loss	Factor	Factor	Level				
	MHz	dB	dB/m	dB	dB <sub>UV</sub>	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	dB
1	41.57	6.80	13.18	32.99	26.27	13.26	29.50	-16.24
2	52.76	6.96	12.55	32.98	27.56	14.09	29.50	-15.41
3	160.35	7.50	13.36	32.73	27.11	15.24	33.10	-17.86
4	294.11	8.04	12.51	32.60	28.39	16.34	35.60	-19.26
5	425.03	8.36	15.55	32.60	28.34	19.65	35.60	-15.95
6 pp	916.07	9.50	22.44	32.50	27.17	26.61	35.60	-8.99

Test mode:	Charge + Transmitting mode	Horizontal
------------	----------------------------	------------



Condition: 10m HORIZONTAL

Job No. : 6626CR

Test Mode: charge+TX mode

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	38.35	6.77	13.10	32.98	27.09	13.98	29.50	-15.52
2	57.39	7.00	12.19	32.96	26.82	13.05	29.50	-16.45
3	156.46	7.48	13.40	32.74	26.40	14.54	33.10	-18.56
4	272.28	7.96	11.92	32.62	27.59	14.85	35.60	-20.75
5	475.50	8.49	16.46	32.60	27.20	19.55	35.60	-16.05
6 pp	903.31	9.50	22.27	32.50	27.15	26.42	35.60	-9.18

Transmitter Emission above 1GHz									
Test mode:		GFSK		Test channel:		Lowest		Remark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3584.372	32.45	7.66	38.51	44.15	45.75	74	-28.25	Vertical	
4804.000	34.16	8.87	39.03	49.62	53.62	74	-20.38	Vertical	
6034.386	34.73	10.52	38.98	45.18	51.45	74	-22.55	Vertical	
7206.000	36.42	10.68	38.18	48.32	57.24	74	-16.76	Vertical	
9608.000	37.52	12.50	36.99	39.81	52.84	74	-21.16	Vertical	
11538.550	38.14	14.06	37.85	39.16	53.51	74	-20.49	Vertical	
4166.444	33.60	8.02	38.77	45.81	48.66	74	-25.34	Horizontal	
4804.000	34.16	8.87	39.03	54.68	58.68	74	-15.32	Horizontal	
5803.188	34.59	10.01	39.02	45.89	51.47	74	-22.53	Horizontal	
7206.000	36.42	10.68	38.18	52.49	61.41	74	-12.59	Horizontal	
9608.000	37.52	12.50	36.99	40.26	53.29	74	-20.71	Horizontal	
12102.870	38.66	14.47	38.41	38.61	53.33	74	-20.67	Horizontal	

Test mode:		GFSK		Test channel:		Lowest		Remark:	Average
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
7206.000	36.42	10.68	38.18	37.28	46.2	54	-7.8	Vertical	
4804.000	34.16	8.87	39.03	44.49	48.49	54	-5.51	Horizontal	
7206.000	36.42	10.68	38.18	41.98	50.9	54	-3.1	Horizontal	

Test mode:		GFSK		Test channel:		Middle		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
3257.913	31.78	7.57	38.34	44.57	45.58	74	-28.42	Vertical		
4136.410	33.60	7.98	38.76	45.80	48.62	74	-25.38	Vertical		
4880.000	34.29	8.97	39.06	47.39	51.59	74	-22.41	Vertical		
6087.002	34.77	10.45	38.94	44.93	51.21	74	-22.79	Vertical		
7320.000	36.37	10.72	38.07	43.75	52.77	74	-21.23	Vertical		
9760.000	37.55	12.58	36.92	39.06	52.27	74	-21.73	Vertical		
4196.696	33.60	8.06	38.79	44.88	47.75	74	-26.25	Horizontal		
4880.000	34.29	8.97	39.06	51.72	55.92	74	-18.08	Horizontal		
6060.637	34.75	10.48	38.96	44.93	51.20	74	-22.80	Horizontal		
7320.000	36.37	10.72	38.07	47.88	56.90	74	-17.10	Horizontal		
9760.000	37.55	12.58	36.92	40.74	53.95	74	-20.05	Horizontal		
12261.500	38.76	14.34	38.57	38.80	53.33	74	-20.67	Horizontal		

Test mode:		GFSK		Test channel:		Middle		Remark:		Average
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
4880.000	34.29	8.97	39.06	39.82	44.02	54	-9.98	Horizontal		
7320.000	36.37	10.72	38.07	35.7	44.72	54	-9.28	Horizontal		

Test mode:		GFSK		Test channel:		Highest		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
3966.435	33.51	7.80	38.69	44.73	47.35	74	-26.65	Vertical		
4960.000	34.43	9.09	39.09	46.69	51.12	74	-22.88	Vertical		
5836.872	34.60	10.10	39.02	45.48	51.16	74	-22.84	Vertical		
7440.000	36.32	10.77	37.94	43.64	52.79	74	-21.21	Vertical		
9920.000	37.58	12.67	36.84	39.69	53.10	74	-20.90	Vertical		
12261.500	38.76	14.34	38.57	39.22	53.75	74	-20.25	Vertical		
3716.403	32.83	7.71	38.57	44.85	46.82	74	-27.18	Horizontal		
4960.000	34.43	9.09	39.09	49.29	53.72	74	-20.28	Horizontal		
5964.939	34.68	10.46	39.00	44.70	50.84	74	-23.16	Horizontal		
7440.000	36.32	10.77	37.94	43.75	52.90	74	-21.10	Horizontal		
9920.000	37.58	12.67	36.84	38.89	52.30	74	-21.70	Horizontal		
12015.620	38.61	14.55	38.32	38.54	53.38	74	-20.62	Horizontal		

**Remark:**

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

## 6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2013 Section 11.12		
Test Site:	Measurement Distance: 3m (fully Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			

Figure 1. 30MHz to 1GHz


Figure 2. Above 1 GHz

Test Procedure:	<ol style="list-style-type: none"> <li>For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</li> <li>Test the EUT in the lowest channel, the Highest channel</li> <li>The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</li> <li>Repeat above procedures until all frequencies measured was complete.</li> </ol>
-----------------	--

Exploratory Test Mode:	Transmitting with GFSK modulation. a. Charge + Transmitting mode. b. Transmitting mode.
Final Test Mode:	Transmitting with GFSK modulation. Pretest the EUT at Charge + Transmitting mode and Transmitting mode, found the Charge + Transmitting mode which it is worse case. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass


**Test plot as follows:**

Worse case mode:	GFSK	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	------	---------------	--------	---------	------	----------

**Condition: 3m Vertical****Job No: : 6626CR****Mode: : 2402 Band edge****: BLE**

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2334.414	5.29	28.91	38.14	49.26	45.32	74.00	-28.68
2	2389.127	5.34	29.07	38.14	47.86	44.13	74.00	-29.87
3	2390.000	5.34	29.08	38.14	46.06	42.34	74.00	-31.66
4 pp	2401.831	5.35	29.11	38.15	83.64	79.95	74.00	5.95

Worse case mode:	GFSK	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	------	---------------	--------	---------	------	------------



Condition: 3m Horizontal


Job No: : 6626CR

Mode: : 2402 Band edge

: BLE

Freq	Cable	Ant	Preamp	Read	Limit	Over	Over
	Loss	Factor	Factor	Level			
1 2334.414	5.29	28.91	38.14	49.91	45.97	74.00	-28.03
2 2389.016	5.34	29.07	38.14	48.77	45.04	74.00	-28.96
3 2390.000	5.34	29.08	38.14	44.70	40.98	74.00	-33.02
4 pp 2402.278	5.35	29.11	38.15	83.57	79.88	74.00	5.88

Worse case mode:	GFSK	Test channel:	Highest	Remark:	Peak	Vertical
------------------	------	---------------	---------	---------	------	----------



Condition: 3m Vertical

Job No: : 6626CR


Mode: : 2480 Band edge  
: BLE

	Cable	Ant	Preamp	Read	Limit	Over
Freq	Loss	Factor	Factor	Level	Level	Line
1 pp	2479.779	5.41	29.34	38.15	82.32	78.92
2	2483.500	5.41	29.35	38.15	50.77	47.38

MHz dB dB/m dB dBuV dBuV/m dBuV/m dB

1 pp 2479.779 5.41 29.34 38.15 82.32 78.92 74.00 4.92  
2 2483.500 5.41 29.35 38.15 50.77 47.38 74.00 -26.62

Worse case mode:	GFSK	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	------	---------------	---------	---------	------	------------



Condition: 3m Horizontal

Job No: : 6626CR

Mode: : 2480 Band edge  
: BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2479.829	5.41	29.34	38.15	85.02	81.62	74.00	7.62
2	2483.500	5.41	29.35	38.15	53.63	50.24	74.00	-23.76

**Note:**

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

## 7 Photographs - EUT Test Setup

Test model No.: NSBL1


### 7.1 Conducted Emission



### 7.2 Radiated Emission



### 7.3 Radiated Spurious Emission



## 8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1608006626CR.