

TEST REPORT

FCC ID: 2AI9RCOLOR

Product: Remote control

Model No.: RMT1

Additional Model: N/A



Trade Mark:

Report No.: TCT160708E010 Issued Date: July 21, 2016

Issued for:

#33, HuaRong Road, Dalang, Longhua, Shenzhen

Issued By:

Shenzhen Tongce Testing Lab.

1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

TEL: +86-755-27673339 FAX: +86-755-27673332

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com





TABLE OF CONTENTS

1.	Test Certification	3
2.	Test Result Summary	4
3.	EUT Description	5
4.	Genera Information	6
	4.1. Test Environment and Mode	6
	4.2. Description of Support Units	6
5.		
	5.1. Facilities	7
	5.2. Location	7
	5.3. Measurement Uncertainty	7
6.	Test Results and Measurement Data	8
	6.1. Antenna Requirement	8
	6.2. Conducted Emission	
	6.3. Radiated Emission Measurement	10
	6.4. Occupied Bandwidth	17
Αp	opendix A: Photographs of Test Setup	
Ap	opendix B: Photographs of EUT	



1. Test Certification

Product:	Remote control				
Model No.:	RMT1				
Additional Model:	Luminoodle Basecamp				
Applicant:	Alli Prouducts Co., Ltd				
Address:	#33, HuaRong Road, Dalang, Longhua, Shenzhen				
Manufacturer:	Shenzhen HeChengXin Lighting Technology Co., LTD				
Address:	11F, Buliding C, PengYiFa Industrial Park, Baihua, Guangmin, Shenzhen				
Date of Test:	July 08 – July 20, 2016				
Applicable Standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.231				

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:

Garen

Date: July 20, 2016

Date: July 21, 2016

Joe Zhou

Approved By: Date: July 21, 2016

Tomsin



2. Test Result Summary

Requirement	CFR 47 Section	Result
Conduction Emission, 0.15MHz to 30MHz	§15.207	PASS
Manually Activated Transmitter	§15.231(a)	PASS
Radiation Emission	§15.231(b), §15.205, §15.209, §15.35	PASS
Occupied Bandwidth	§15.231(c)	PASS

Note:

- 1. PASS: Test item meets the requirement.
- 2. Fail: Test item does not meet the requirement.
- 3. N/A: Test case does not apply to the test object.
- 4. The test result judgment is decided by the limit of test standard.





3. EUT Description

Hotline: 400-6611-140

Product Name:	Remote control
Model No.:	RMT1
Additional Model:	N/A
Trade Mark:	POWER® PRACTICAL
Operation Frequency:	433.92MHz
Modulation Technology:	ASK
Antenna Type:	Internal PCB Antenna
Antenna Gain:	10dBi
Power Supply:	DC 3V(The button battery *1)
Remark:	All models above are identical in interior structure, electrical circuits and components, and just model names are different for the marketing requirement.



Fax: 86-755-27673332

Tel: 86-755-27673339

http://www.tct-lab.com





4. Genera Information

4.1. Test Environment and Mode

Operating Environment:				
Temperature:	24.0 °C			
Humidity:	54 % RH			
Atmospheric Pressure:	1010 mbar			
Test Mode:				
Operation mode:	Keep the EUT in continuous transmitting with modulation			

The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
E		I	(3)1	

Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



5. Facilities and Accreditations

5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 572331

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

CNAS - Registration No.: CNAS L6165
 Shenzhen TCT Testing Technology Co., Ltd. is accredited to ISO/IEC 17025:2005
 General Requirements for the Competence of Testing and Calibration laboratories for

5.2. Location

Shenzhen Tongce Testing Lab

Address: 1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

the competence of testing. The Registration No. is CNAS L6165.

Tel: 86-755-36638142

5.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	±2.56dB
2	RF power, conducted	±0.12dB
3	Spurious emissions, conducted	±0.11dB
4	All emissions, radiated(<1G)	±3.92dB
5	All emissions, radiated(>1G)	±4.28dB
6	Temperature	±0.1°C
7	Humidity	±1.0%





6. Test Results and Measurement Data

6.1. Antenna Requirement

Standard requirement: FCC Part15 C Section 15.203 /247(c)

15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

E.U.T Antenna:

The Bluetooth antenna is an internal PCB antenna which permanently attached, and the best case gain of the antenna is 10dBi.





6.2. Conducted Emission

6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207		
Test Method:	ANSI C63.4:2014		
Frequency Range:	150 kHz to 30 MHz		
Receiver setup:	RBW=9 kHz, VBW=30	kHz, Sweep time	=auto
Limits:	Frequency range (MHz) 0.15-0.5 0.5-5 5-30	Limit (c Quasi-peak 66 to 56* 56 60	Average 56 to 46* 46 50
Test Setup:	Reference Plane LISN 40cm 80cm Filter AC power Equipment Test table/Insulation plane Remark E.U.T: Equipment Under Test LISN: Line Impedence Stabilization Network Test table height=0.8m		
Test Mode:	Mode 3		
Test Procedure:	 The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2009 on conducted measurement. 		
Test Result:	N/A;The EUT powered by battery, so this test item is not applicable		




6.3. Radiated Emission Measurement

6.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.231(a) and 15.209			
Test Method:	ANSI C63.4: 2014 and ANSI C63.10:2013			
Frequency Range:	9 kHz to 5 G	Hz		
Measurement Distance:	3 m			
Antenna Polarization:	Horizontal &	Vertical		
Receiver Setup:	Frequency 9kHz- 150kHz 150kHz- 30MHz- 30MHz-1GHz	Detector Quasi-peak Quasi-peak Quasi-peak	RBW 200Hz 9kHz 100KHz	
	Above 1GHz	Peak		Peak Value
	30MHz 30MHz-1GHz Quasi-peak 100KHz 300KHz Quasi-peak Value Peak 1MHz 3MHz Peak Value			







6.3.2. Limit

Fundamental Frequency (MHz)	Filed Strength of Fundamental (microvolts/meter)	Filed Strength of Spurious Emission (microvolts/meter)	
40.66-40.70	2250	225	
70-130	1250	125	
130-174	1250 to 3750*	125 to 375*	
174-260	3750	375	
260-470	3750 to 12500*	375 to 1250*	
Above 470	12500	1250	
Horn Antenna	Schwarzbeck	BBHA 9120D	

^{*}Linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows:

For the band 130-174 MHz, μ V/m at 3 meters = 56.81818(F) - 6136.3636; for the band 260-470 MHz, μ V/m at 3 meters = 41.6667(F) - 7083.3333. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

For EUT

	Fundamental Frequency (MHz)	Filed Strength of Fundamental (microvolts/meter)	Filed Strength of Spurious Emission(dBµV/m)
)	433.92	80.8	60.8

Note:

- Intentional radiators operating under the provisions of this Section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions.
- 2.According to 15.35, on any frequency or frequencies below or equal to 1000 MHz, the limits Shown are based on measuring equipment employing a CISPR quasi-peak detector function and related measurement bandwidths, unless otherwise specified the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test.
- 3. According to 15.231(b), The limits on the field strength of the spurious emissions in the above table is based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in Section 15.209, whichever limit permits one higher field strength.



Frequencies in restricted band are complied to limit on Paragraph 15.209

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
0.009-0.490	3	20log 2400/F (kHz) + 80
0.490-1.705	3	20log 24000/F (kHz) + 40
1.705-30	3 (0)	20log 30 + 40
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 5. If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula Ld1 = Ld2 * (d2/d1)

6.3.3. Test Instruments

	Radiated Emission Test Site (966)								
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due					
ESPI Test Receiver	ROHDE&SCHWARZ	ESVD	100008	Sep. 11, 2016					
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	Sep. 11, 2016					
Pre-amplifier	EM Electronics Corporation CO.,LTD	EM30265	07032613	Sep. 11, 2016					
Pre-amplifier	HP	8447D	2727A05017	Sep. 11, 2016					
Loop antenna	ZHINAN	ZN30900A	12024	Sep. 13, 2016					
Broadband Antenna	Schwarzbeck	VULB9163	340	Sep. 13, 2016					
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Sep. 13, 2016					
Coax cable	TCT	N/A	N/A	Sep. 12, 2016					
Coax cable	TCT	N/A	N/A	Sep. 12, 2016					
Coax cable	TCT	N/A	N/A	Sep. 12, 2016					
Coax cable	TCT	N/A	N/A	Sep. 12, 2016					
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A					

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).




6.3.4. Test Data

Duty Cycle Test Data:

Total time one cycle(ms)	Effective time one cycle(ms)	Duty Cycle	AV Factor(dB)
100	28.24	0.54	-5.40

Note: Effective time one cycle= 1.36*17+0.64*8= 28.24

Duty Cycle= Effective time one cycle/ Total time one cycle= 0.54 AV Factor = 20 log(Duty Cycle)





Field Strength of Fundamental

	Frequency (MHz)	Emission PK (dBuV/m)	Horizontal /Vertical	Limits PK (dBuV/m)	Margin (dB)
	433.92	80.14	Н	100.8	-20.66
Ī	433.92	78.16	V	100.8	-22.64

Frequency (MHz)	Emission PK (dBuV/m)	AV Factor (dB)	Horizontal /Vertical	Emission AVG (dBuV/m)	Limits AV (dBuV/m)	Margin (dB)
433.92	80.14	-5.40	(C)	74.74	80.8	-6.06
433.92	78.16	-5.40	V	72.76	80.8	-8.04

Harmonics and Spurious Emissions

Frequency Range (9 kHz-30MHz)

Frequency (MHz)	Level@3m (dBµV/m)	Limit@3m (dBµV/m)
(, G)	(6)	(, Č)
🔍		
	1	-1
	-	

Note: 1. Emission Level=Reading+ Cable loss-Antenna factor-Amp factor

2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement



Frequency Range (30MHz-5GHz)

F	requency (MHz)	Emission Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)	Remark	Conclusion
	867.84	49.51	Н	80.8	Peak	PASS
	1301.76	48.28) н	80.8	Peak	PASS
	867.84	46.61	V	80.8	Peak	PASS
	1301.76	45.75	V	80.8	Peak	PASS

Frequency (MHz)	Emission Level@3m (dBµV/m)	AV Factor (dB)	Antenna Polarity	Limit@3m (dBµV/m)	Remark	Conclusion
867.84	49.51	-5.40	Н	60.8	Average	PASS
1301.76	48.28	-5.40	Н	60.8	Average	PASS
867.84	46.61	-5.40	V	60.8	Average	PASS
1301.76	45.75	-5.40	C V	60.8	Average	PASS

Note: Emission Level=Reading+ Cable loss+ Antenna factor-Amp factor

AV=Average

AV Emission level = Peak Emissions level +AV Factor



6.4. Occupied Bandwidth

6.4.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.215(c)			
Test Method:	ANSI C63.10: 2013			
Limit:	According to 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the centre frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the centre frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.			
	 According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. Set to the maximum power setting and enable the EUT transmit continuously. Use the following spectrum analyzer settings for 20dB Bandwidth measurement. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel; RBW≥ 1% of the 20 dB bandwidth; VBW≥RBW; Sweep = auto; Detector function = peak; Trace = max hold. Measure and record the results in the test report. 			
Test setup:	Spectrum Analyzer EUT			
Test Mode:				
Test results:	PASS			

6.4.2. Test Instruments

RF Test Room						
Equipment Manufacturer Model Serial Number Calibration Du						
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 12, 2016		

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).




6.4.3. Test data

Test Channel	20dB Occupy Bandwidth (kHz)	Limit (kHz)	Conclusion
Lowest	16.35	1084.8	PASS

Note: Limit = 433.92MHz *0.25% = 1084.8 kHz

Test plots as follows:



Date: 18.JUL.2016 20:38:23

*****END OF REPORT****




Page 18 of 24

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com



Appendix A: Photographs of Test Setup Product: Remote control

Product: Remote contro Model: RMT1 Radiated Emission










Appendix B: Photographs of EUT
Product: Remote control
Model: RMT1
External Photos





TCT通测检测 testing centre technology

Report No.: TCT160708E010













Product: Remote control Model: RMT1 Internal Photos

