

### **TEST REPORT**

Report No.: 16060881HKG-001

**CE NORTH AMERICA LLC** 

**Application** For Certification (Original Grant) (FCC ID: 2AI9VCE-CM02)

Transceiver

	•	•	• •	•
C:~	unad On Eila			
OIG	ned On File			
- 3	,			

Koo Wai Ip **Assistant Supervisor** Date: July 13, 2016

Approved by:

Prepared and Checked by:

Wong Cheuk Ho, Herbert

Lead Engineer

Intertek's standard Terms and Conditions can be obtained at our website http://www.intertek.com/terms/.

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material product or service is or the sever been under an Intertek certification program. material, product, or service is or has ever been under an Intertek certification program. © 2016 Intertek

# **GENERAL INFORMATION**

Grantee:	CE NORTH AMERICA LLC
Grantee Address:	6950 NORTHWEST 77TH COURT
	MIAMI FLORIDA 33166 USA
Contact Person:	JORGE GARCIA
Tel:	1-(305) 392-2200
Fax:	N/A
e-mail:	N/A
Manufacturer:	Ningbo Jinyu Electrical Appliance Co.,Ltd
Manufacturer Address:	No.88, Jinfeng Road, Southern Economic
	Development Zone, Yuyao, Zhejiang, China
Brand Name:	For Model CE-CM021, CE-CM022, CE-CM023, CE-
	CM024, CE-CM025, CE-CM027, CE-CM028, CE-
	CM029: Continental/Professional Series
	Fair Madal CE CMO44, CE CMO49, CE CMO49, CE
	For Model CE-CM041, CE-CM042, CE-CM043, CE-
	CM044, CE-CM045, CE-CM047, CE-CM048, CE- CM049: Continental
	Civi049: Continental
	For Model PS-CM041, PS-CM042, PS-CM043, PS-
	CM044, PS-CM045, PS-CM047, PS-CM048, PS-
	CM049: Professional Series
Model:	CE-CM029
Additional Model:	CE-CM021, CE-CM022, CE-CM023, CE-CM024,
	CE-CM025, CE-CM027, CE-CM028, CE-CM041,
	CE-CM042, CE-CM043, CE-CM044, CE-CM045,
	CE-CM047, CE-CM048, CE-CM049, PS-CM041,
	PS-CM042, PS-CM043, PS-CM044, PS-CM045,
	PS-CM047, PS-CM048, PS-CM049
Type of EUT:	Transceiver
Description of EUT:	Drip Type coffee maker
Serial Number:	N/A
FCC ID:	2AI9VCE-CM02
Date of Sample Submitted:	June 14, 2016
Date of Test:	June 14, 2016 to July 06, 2016
Report No.:	16060881HKG-001
Report Date:	July 13, 2016
Environmental Conditions:	Temperature: +10 to 40°C
	Humidity: 10 to 90%

i

Report No.: 16060881HKG-001

### **SUMMARY OF TEST RESULT**

TEST SPECIFICATION	REFERENCE	RESULTS
Transmitter Power Line Conducted Emissions	15.207	Pass
Radiated Emission Radiated Emission on the Bandedge	15.249, 15.209	Pass
Radiated Emission in Restricted Bands	15.205	Pass

The equipment under test is found to be complying with the following standards: FCC Part 15, October 1, 2014 Edition

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the pervisions of this section.

Report No.: 16060881HKG-001 ii

<sup>2.</sup> Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

# **Table of Contents**

1.0	General Description	1
1.1	Product Description	1
1.2	Related Submittal(s) Grants	1
1.3	Test Methodology	1
1.4	Test Facility	
2.0	System Test Configuration	_
2.0 2.1	System Test Configuration  Justification	2
2.1		
2.2	EUT Exercising Software	
2.3	Special Accessories Measurement Uncertainty	
2.5	Support Equipment List and Description	2
2.5	Support Equipment List and Description	2
3.0	Emission Results	3
3.1	Field Strength Calculation	3
3.2	Radiated Emission Configuration Photograph	
3.3	Radiated Emission Data	
3.4	Conducted Emission Configuration Photograph	
3.5	Conducted Emission Data	
4.0	Equipment Photographs	10
4.0	Equipment Photographs	10
5.0	Product Labelling	10
6.0	Technical Specifications	10
7.0	Instruction Manual	10
8.0	Miscellaneous Information	11
8.1	Radiated Emission on the Bandedge	11
8.2	Discussion of Pulse Desensitization	14
8.3	Calculation of Average Factor	14
8.4	Emissions Test Procedures	15
0.0	For the contribute	10
un	Fauinment List	10

Report No.: 16060881HKG-001

#### 1.0 **General Description**

### 1.1 Product Description

The Equipment-Under-Test (EUT) is a Coffee Maker with Bluetooth. The EUT contains a boiler, a 5V USB charging port and a Bluetooth 3.0 radio with audio playback. The EUT can accept wireless audio signal via Bluetooth devices. The EUT has internal power amplifier and loudspeaker. It is powered 120VAC.

The Model: CE-CM021, CE-CM022, CE-CM023, CE-CM024, CE-CM025, CE-CM027, CE-CM028, CE-CM041, CE-CM042, CE-CM043, CE-CM044, CE-CM045, CE-CM047, CE-CM048, CE-CM049, PS-CM041, PS-CM042, PS-CM043, PS-CM044, PS-CM045, PS-CM047, PS-CM048, PS-CM049 are the same as the Model: CE-CM029 in hardware aspect. The difference in model number serves as marketing strategy. The models are different in color, trade name and model number only.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

## 1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

#### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application.

#### 1.4 Test Facility

The 3m Chamber and conducted measurement facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

Report No.: 16060881HKG-001 1 of 19

#### 2.0 System Test Configuration

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The device was powered by 120VAC.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

### 2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

#### 2.5 Support Equipment List and Description

- 1. USB cable of 0.5m long (Provided by Intertek)
- 2. 5 ohm resistive load (Provided by Intertek)

Report No.: 16060881HKG-001 2 of 19

#### 3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG - AV

where  $FS = Field Strength in dB\mu V/m$ 

RA = Receiver Amplitude (including preamplifier) in dBµV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

FS = RR + LF

where  $FS = Field Strength in dB\mu V/m$ 

 $RR = RA - AG - AV \text{ in } dB\mu V$ 

LF = CF + AF in dB

Assume a receiver reading of 52.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 32 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

 $RA = 52.0 dB\mu V/m$ 

AF = 7.4 dB  $RR = 18.0 \text{ dB}\mu\text{V}$ 

CF = 1.6 dB LF = 9.0 dB

AG = 29.0 dBAV = 5.0 dB

FS = RR + LF

 $FS = 18 + 9 = 27 dB\mu V/m$ 

Level in  $\mu$ V/m = Common Antilogarithm [(27 dB $\mu$ V/m)/20] = 22.4  $\mu$ V/m

Report No.: 16060881HKG-001 3 of 19

#### 3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 64,778 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

#### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 11.6 dB

## 3.4 Conducted Emission Configuration Photograph

The worst case in line-conducted emission was found at 0.150 MHz

For electronic filing, the worst case line-conducted configuration photographs are saved with filename: conducted photo.pdf.

## 3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.

Judgment: Pass by 11.5 dB


Report No.: 16060881HKG-001 4 of 19

Date of Test: July 06, 2016

Applicant: CE NORTH AMERICA LLC

Model: CE-CM029

Worst-Case Operating Mode: Bluetooth Audio Playing and Charging



	EI	DIT PEAK LIST (Fi	nal Measurement	Results)
Tra	ce1:	CF15MQP		
Tra	ce2:	CF15MAV		
Tra	ce3:	===		
	TRACE	FREQUENCY	LEVEL dBµV	DELTA LIMIT dB
1	Quasi Peak	150 kHz	54.49 L1	-11.50
2	CISPR Aver	age177 kHz	35.20 N	-19.42
1	Quasi Peak	231 kHz	43.95 N	-18.45
2	CISPR Aver	age258 kHz	25.93 N	-25.56
1	Quasi Peak	316.5 kHz	39.80 N	-19.98
2	CISPR Aver	age375 kHz	21.68 N	-26.70
1	Quasi Peak	460.5 kHz	39.73 L1	-16.94
2	CISPR Aver	age492 kHz	19.28 L1	-26.85
1	Quasi Peak	577.5 kHz	29.09 L1	-26.90
1	Quasi Peak	919.5 kHz	29.63 L1	-26.36

Note: Measurement Uncertainty is ±4.2dB at a level of confidence of 95%.

Report No.: 16060881HKG-001 5 of 19

Applicant: CE NORTH AMERICA LLC Date of Test: July 06, 2016

Model: CE-CM029

Worst-Case Operating Mode: Transmitting (Bluetooth 3.0)

# Table 1 Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

#### **Lowest Channel**

			Pre-Amp	Antenna	Net at	Average	Calculated	Average Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	Factor	at 3m	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2402.000	94.7	33	29.4	91.1	24	67.1	94.0	-26.9
Н	4804.000	47.5	33	34.9	49.4	24	25.4	54.0	-28.6
Н	7206.000	39.7	33	37.9	44.6	24	20.6	54.0	-33.4
Н	9608.000	40.3	33	40.4	47.7	24	23.7	54.0	-30.3
Н	12010.000	42.5	33	40.5	50.0	24	26.0	54.0	-28.0
Н	14412.000	44.2	33	40.0	51.2	24	27.2	54.0	-26.8

			Pre-Amp	Antenna	Net at	Peak Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2402.000	94.7	33	29.4	91.1	114.0	-22.9
Н	4804.000	47.5	33	34.9	49.4	74.0	-24.6
Н	7206.000	39.7	33	37.9	44.6	74.0	-29.4
Н	9608.000	40.3	33	40.4	47.7	74.0	-26.3
Н	12010.000	42.5	33	40.5	50.0	74.0	-24.0
Н	14412.000	44.2	33	40.0	51.2	74.0	-22.8

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 16060881HKG-001 6 of 19

Applicant: CE NORTH AMERICA LLC Date of Test: July 06, 2016

Model: CE-CM029

Worst-Case Operating Mode: Transmitting (Bluetooth 3.0)

# Table 2 Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

#### Middle Channel

			Pre-Amp	Antenna	Net at	Average	Calculated	Average Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	Factor	at 3m	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2440.000	93.9	33	29.4	90.3	24	66.3	94.0	-27.7
Н	4880.000	46.4	33	34.9	48.3	24	24.3	54.0	-29.7
Н	7320.000	40.1	33	37.9	45.0	24	21.0	54.0	-33.0
Н	9760.000	40.1	33	40.4	47.5	24	23.5	54.0	-30.5
Н	12200.000	42.3	33	40.5	49.8	24	25.8	54.0	-28.2
Н	14640.000	45.4	33	38.4	50.8	24	26.8	54.0	-27.2

			Pre-Amp	Antenna	Net at	Peak Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2440.000	93.9	33	29.4	90.3	114.0	-23.7
Н	4880.000	46.4	33	34.9	48.3	74.0	-25.7
Н	7320.000	40.1	33	37.9	45.0	74.0	-29.0
Н	9760.000	40.1	33	40.4	47.5	74.0	-26.5
Н	12200.000	42.3	33	40.5	49.8	74.0	-24.2
Н	14640.000	45.4	33	38.4	50.8	74.0	-23.2

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
- 6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 16060881HKG-001 7 of 19

Applicant: CE NORTH AMERICA LLC Date of Test: July 06, 2016

Model: CE-CM029

Worst-Case Operating Mode: Transmitting (Bluetooth 3.0)

# Table 3 Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

#### **Highest Channel**

			Pre-Amp	Antenna	Net at	Average	Calculated	Average Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	Factor	at 3m	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2480.000	92.0	33	29.4	88.4	24	64.4	94.0	-29.6
Н	4960.000	46.2	33	34.9	48.1	24	24.1	54.0	-29.9
Н	7440.000	40.6	33	37.9	45.5	24	21.5	54.0	-32.5
Н	9920.000	39.9	33	40.4	47.3	24	23.3	54.0	-30.7
Н	12400.000	42.2	33	40.5	49.7	24	25.7	54.0	-28.3
Н	14880.000	45.6	33	38.4	51.0	24	27.0	54.0	-27.0

			Pre-Amp	Antenna	Net at	Peak Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2480.000	92.0	33	29.4	88.4	114.0	-25.6
Н	4960.000	46.2	33	34.9	48.1	74.0	-25.9
Н	7440.000	40.6	33	37.9	45.5	74.0	-28.5
Н	9920.000	39.9	33	40.4	47.3	74.0	-26.7
Н	12400.000	42.2	33	40.5	49.7	74.0	-24.3
Н	14880.000	45.6	33	38.4	51.0	74.0	-23.0

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 16060881HKG-001 8 of 19

Applicant: CE NORTH AMERICA LLC Date of Test: July 06, 2016

Model: CE-CM029

Worst-Case Operating Mode: Bluetooth Audio Playing and Charging

# Table 4 Radiated Emissions Pursuant to FCC Part 15 Section 15.209 Requirement

			Pre-	Antenna	Net	Limit	
	Frequency	Reading	amp	Factor	at 3m	at 3m	Margin
Polarization	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
V	38.345	32.4	16	10.0	26.4	40.0	-13.6
V	64.778	35.4	16	9.0	28.4	40.0	-11.6
Н	72.947	36.4	16	7.0	27.4	40.0	-12.6
Н	97.788	29.5	16	12.0	25.5	43.5	-18.0
Н	145.564	26.7	16	14.0	24.7	43.5	-18.8
Н	221.876	22.8	16	17.0	23.8	46.0	-22.2

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
- 6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 16060881HKG-001 9 of 19

## 4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

### 5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

## 6.0 <u>Technical Specifications</u>

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

## 7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

Report No.: 16060881HKG-001 10 of 19

#### 8.0 **Miscellaneous Information**

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).


### 8.1 Radiated Emission on the Bandedge


From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.10 (2013) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

Report No.: 16060881HKG-001 11 of 19

## Peak Measurement





Report No.: 16060881HKG-001 12 of 19

#### **Peak Measurement**

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower bandedge

Peak Resultant field strength = Fundamental emissions (peak value) - delta from the plot

```
=91.1 \text{ dB}\mu\text{V/m} - 47.3 \text{ dB}
=43.8 dB\mu\text{V/m}
```

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

```
=67.1 dB\mu V/m - 47.3 dB
=19.8 dB\mu V/m
```

Upper bandedge

Peak Resultant field strength = Fundamental emissions (peak value) - delta from the plot

```
=88.4 \text{ dB}\mu\text{V/m} - 49.0 \text{ dB}
=39.4 dB\mu\text{V/m}
```

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

```
=64.4 dB\mu V/m - 49.0 dB
=15.4 dB\mu V/m
```

The resultant field strength meets the general radiated emission limit in Section 15.209, which does not exceed 74 dB $\mu$ V/m (Peak Limit) and 54 dB $\mu$ V/m (Average Limit).

Report No.: 16060881HKG-001 13 of 19

#### 8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (Teff) is approximately  $625\,\mu s$  for a digital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

#### 8.3 Calculation of Average Factor

Based on the Bluetooth Specification Version 3.0 + EDR, the transmitter ON time for each timeslot of Bluetooth is  $625\mu s$ . DH5 has the maximum duty cycle, which consists of 5 continuous Tx slots and 1 Rx slot. Therefore one hopset take (5+1) x  $625\mu s = 3.75ms$ . For one period for a pseudo-random hopping through at least 20 RF channels in adaptive mode (worse case), it take:  $20 \times 3.75ms = 75ms$ .

The dwell time for DH5 is  $5 \times 625 \mu s = 3.125 ms$ .

For the worst case calculation, there are two transmissions might occur in 100ms. Therefore,

Duty Cycle (DC) = Maximum On time in 100ms/100ms = 3.125ms x 2/100ms = 0.0625

Average Factor (AF) of Bluetooth in dB =  $20 \log_{10} (0.0625)$ = -24 dB

Report No.: 16060881HKG-001 14 of 19

#### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

Report No.: 16060881HKG-001 15 of 19

#### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.10 (2013).


The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.


Report No.: 16060881HKG-001 16 of 19

## 8.4.1 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.



Test setup of radiated emissions up to 1GHz



Test setup of radiated emissions above 1GHz


Report No.: 16060881HKG-001 17 of 19

#### 8.4.2 Conducted Emission Test Procedures

For tabletop equipment, the EUT along with its peripherals were placed on a 1.0m(W)×1.5m(L) and 0.8m in height wooden table. For floor-standing equipment, the EUT and all cables were insulated, if required, from the ground plane by up to 12 mm of insulating material. The EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled.

All connecting cables of EUT and peripherals were moved to find the maximum emission.

## 8.4.3 Conducted Emission Test Setup



Report No.: 16060881HKG-001 18 of 19

## 9.0 **Equipment List**

### 1) Radiated Emissions Test

Equipment	EMI Test Receiver	Spectrum Analyzer	Biconical Antenna
Registration No.	EW-3156	EW-2466	EW-0571
Manufacturer	R&S	R&S	EMCO
Model No.	ESR26	FSP30	3104C
Calibration Date	Nov. 03, 2015	Sep. 16, 2015	Jun. 23, 2015
Calibration Due Date	Nov. 03, 2016	Aug. 20, 2016	Dec. 23, 2016

Equipment	Pyramidal Horn	Double Ridged	Log Periodic Antenna
	Antenna	Guide Antenna	
Registration No.	EW-0905	EW-1133	EW-0447
Manufacturer	EMCO	EMCO	EMCO
Model No.	3160-09	3115	3146
Calibration Date	Feb. 12, 2016	Nov. 05, 2015	Mar. 16, 2015
Calibration Due Date	Aug. 12, 2017	May 05, 2017	Sep. 16, 2016

## 2) Conducted Emissions Test

Equipment	EMI Test Receiver	LISN
Registration No.	EW-2500	EW-2501
Manufacturer	R&S	R&S
Model No.	ESCI	ENV-216
Calibration Date	Jan. 28, 2016	Jan. 28, 2016
Calibration Due Date	Jan. 28, 2017	Jan. 28, 2017

## 3) Bandedge Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-2249
Manufacturer	R&S
Model No.	FSP30
Calibration Date	Nov. 27, 2015
Calibration Due Date	Nov. 27, 2016

# **END OF TEST REPORT**

Report No.: 16060881HKG-001 19 of 19