




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 96

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05




Site no. : 3m Chamber Data no. : 96
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH106 5530MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5530.000	34.42	11.95	35.45	85.69	96.61	74.00	-22.61	Peak
2	11060.000	38.66	13.45	36.11	29.64	45.64	54.00	8.36	Average
3	11060.000	38.66	13.45	36.11	42.25	58.25	74.00	15.75	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 5
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-04


Site no. : 3m Chamber Data no. : 5
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH100 5500MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5446.390	34.30	11.94	35.48	45.83	56.59	74.00	17.41	Peak
2	5460.000	34.33	11.94	35.47	44.19	54.99	74.00	19.01	Peak
3	5502.660	34.40	11.95	35.45	94.72	105.62	74.00	-31.62	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 6

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-04



Site no. : 3m Chamber Data no. : 6
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH100 5500MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5448.260	34.31	11.94	35.48	32.68	43.45	54.00	10.55	Average
2	5460.000	34.33	11.94	35.47	32.53	43.33	54.00	10.67	Average
3	5502.150	34.40	11.95	35.45	83.91	94.81	54.00	-40.81	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Ant Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 7

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-04



Site no. : 3m Chamber Data no. : 7
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH100 5500MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5450.300	34.31	11.94	35.48	43.59	54.36	74.00	19.64	Peak
2	5460.000	34.33	11.94	35.47	41.96	52.76	74.00	21.24	Peak
3	5497.390	34.40	11.95	35.45	86.41	97.31	74.00	-23.31	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 8

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-04



Site no. : 3m Chamber Data no. : 8
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH100 5500MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5448.940	34.31	11.94	35.48	30.25	41.02	54.00	12.98	Average
2	5460.000	34.33	11.94	35.47	30.06	40.86	54.00	13.14	Average
3	5503.340	34.40	11.95	35.45	75.90	86.80	54.00	-32.80	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 17

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 17
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH140 5700MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5705.360	34.52	11.97	35.45	92.99	104.03	74.00	-30.03	Peak
2	5850.000	34.61	11.98	35.45	42.70	53.84	74.00	20.16	Peak
3	7163.440	35.89	12.41	35.55	43.66	56.41	74.00	17.59	Peak
4	7250.000	36.10	12.48	35.56	40.31	53.33	74.00	20.67	Peak
5	7718.800	36.83	12.77	35.54	43.65	57.71	74.00	16.29	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 18

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 18
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH140 5700MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5705.360	34.52	11.97	35.45	84.76	95.80	74.00	-21.80	Peak
2	5850.000	34.61	11.98	35.45	41.99	53.13	74.00	20.87	Peak
3	7250.000	36.10	12.48	35.56	40.73	53.75	74.00	20.25	Peak
4	7735.440	36.84	12.77	35.53	43.23	57.31	74.00	16.69	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 19

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 19
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH140 5700MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5697.040	34.52	11.97	35.45	72.86	83.90	54.00	-29.90	Average
2	5850.000	34.61	11.98	35.45	29.49	40.63	54.00	13.37	Average
3	7250.000	36.10	12.48	35.56	28.81	41.83	54.00	12.17	Average
4	7714.640	36.83	12.77	35.54	30.27	44.33	54.00	9.67	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 20

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05




Site no. : 3m Chamber Data no. : 20
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH140 5700MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5697.040	34.52	11.97	35.45	80.60	91.64	54.00	-37.64	Average
2	5850.000	34.61	11.98	35.45	29.69	40.83	54.00	13.17	Average
3	7250.000	36.10	12.48	35.56	28.78	41.80	54.00	12.20	Average
4	7712.560	36.83	12.77	35.54	30.27	44.33	54.00	9.67	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 25
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-05



Site no. : 3m Chamber Data no. : 25
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH100 5500MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5448.090	34.31	11.94	35.48	45.19	55.96	74.00	18.04	Peak
2	5460.000	34.33	11.94	35.47	43.37	54.17	74.00	19.83	Peak
3	5502.490	34.40	11.95	35.45	93.01	103.91	74.00	-29.91	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 26
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-05


Site no. : 3m Chamber Data no. : 26
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH100 5500MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5438.060	34.29	11.94	35.48	43.89	54.64	74.00	19.36	Peak
2	5460.000	34.33	11.94	35.47	41.89	52.69	74.00	21.31	Peak
3	5496.540	34.39	11.95	35.45	84.84	95.73	74.00	-21.73	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 27

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05




Site no. : 3m Chamber Data no. : 27
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH100 5500MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5437.890	34.29	11.94	35.48	30.31	41.06	54.00	12.94	Average
2	5460.000	34.33	11.94	35.47	30.01	40.81	54.00	13.19	Average
3	5498.240	34.40	11.95	35.45	72.92	83.82	54.00	-29.82	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 28
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-05


Site no. : 3m Chamber Data no. : 28
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH100 5500MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5448.090	34.31	11.94	35.48	32.13	42.90	54.00	11.10	Average
2	5460.000	34.33	11.94	35.47	31.98	42.78	54.00	11.22	Average
3	5497.390	34.40	11.95	35.45	82.46	93.36	54.00	-39.36	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 37

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 37
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH140 5700MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5697.040	34.52	11.97	35.45	91.70	102.74	74.00	-28.74	Peak
2	5850.000	34.61	11.98	35.45	43.09	54.23	74.00	19.77	Peak
3	7240.400	36.08	12.47	35.56	43.51	56.50	74.00	17.50	Peak
4	7250.000	36.10	12.48	35.56	41.29	54.31	74.00	19.69	Peak
5	7587.760	36.75	12.72	35.58	43.90	57.79	74.00	16.21	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 38

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 38
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH140 5700MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5697.040	34.52	11.97	35.45	80.47	91.51	54.00	-37.51	Average
2	5850.000	34.61	11.98	35.45	30.28	41.42	54.00	12.58	Average
3	7250.000	36.10	12.48	35.56	29.00	42.02	54.00	11.98	Average
4	7708.400	36.83	12.77	35.54	30.40	44.46	54.00	9.54	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 39

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 39
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH140 5700MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5697.040	34.52	11.97	35.45	84.00	95.04	74.00	-21.04	Peak
2	5850.000	34.61	11.98	35.45	41.45	52.59	74.00	21.41	Peak
3	6986.640	35.48	12.26	35.51	43.65	55.88	74.00	18.12	Peak
4	7250.000	36.10	12.48	35.56	40.21	53.23	74.00	20.77	Peak
5	7693.840	36.82	12.76	35.55	44.04	58.07	74.00	15.93	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Ant Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 40

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05




Site no. : 3m Chamber Data no. : 40
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH140 5700MHz Tx
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5697.040	34.52	11.97	35.45	74.16	85.20	54.00	-31.20	Average
2	5850.000	34.61	11.98	35.45	29.58	40.72	54.00	13.28	Average
3	7032.400	35.58	12.30	35.53	30.38	42.73	54.00	11.27	Peak
4	7250.000	36.10	12.48	35.56	28.92	41.94	54.00	12.06	Average
5	7712.560	36.83	12.77	35.54	30.28	44.34	54.00	9.66	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 57
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-05



Site no. : 3m Chamber Data no. : 57
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT20 CH100 5500MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5434.150	34.28	11.94	35.49	44.37	55.10	74.00	18.90	Peak
2	5460.000	34.33	11.94	35.47	40.65	51.45	74.00	22.55	Peak
3	5498.410	34.40	11.95	35.45	84.91	95.81	74.00	-21.81	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 58
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-05


Site no. : 3m Chamber Data no. : 58
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT20 CH100 5500MHz Tx
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5388.590	34.20	11.93	35.51	44.83	55.45	74.00	18.55	Peak
2	5460.000	34.33	11.94	35.47	43.04	53.84	74.00	20.16	Peak
3	5498.240	34.40	11.95	35.45	92.05	102.95	74.00	-28.95	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 59

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 59
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT20 CH100 5500MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5446.390	34.30	11.94	35.48	31.73	42.49	54.00	11.51	Average
2	5460.000	34.33	11.94	35.47	31.54	42.34	54.00	11.66	Average
3	5497.390	34.40	11.95	35.45	80.72	91.62	54.00	-37.62	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 60

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 60
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT20 CH100 5500MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5440.950	34.29	11.94	35.48	30.22	40.97	54.00	13.03	Average
2	5459.990	34.33	11.94	35.47	29.88	40.68	54.00	13.32	Average
3	5503.000	34.40	11.95	35.45	73.67	84.57	54.00	-30.57	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 41

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 41
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT20 CH140 5700MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5697.040	34.52	11.97	35.45	85.59	96.63	74.00	-22.63	Peak
2	5850.000	34.61	11.98	35.45	40.99	52.13	74.00	21.87	Peak
3	7130.160	35.81	12.38	35.54	43.69	56.34	74.00	17.66	Peak
4	7250.000	36.10	12.48	35.56	40.96	53.98	74.00	20.02	Peak
5	7722.960	36.83	12.77	35.54	43.42	57.48	74.00	16.52	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 42

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 42
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT20 CH140 5700MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5694.960	34.52	11.97	35.45	73.86	84.90	54.00	-30.90	Average
2	5850.000	34.61	11.98	35.45	29.61	40.75	54.00	13.25	Average
3	7032.400	35.58	12.30	35.53	30.33	42.68	54.00	11.32	Average
4	7250.000	36.10	12.48	35.56	28.88	41.90	54.00	12.10	Average
5	7712.560	36.83	12.77	35.54	30.26	44.32	54.00	9.68	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 43

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 43
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT20 CH140 5700MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5697.040	34.52	11.97	35.45	90.18	101.22	74.00	-27.22	Peak
2	5850.000	34.61	11.98	35.45	43.18	54.32	74.00	19.68	Peak
3	7205.040	35.99	12.44	35.55	42.40	55.28	74.00	18.72	Peak
4	7250.000	36.10	12.48	35.56	40.86	53.88	74.00	20.12	Peak
5	7525.360	36.72	12.70	35.59	43.94	57.77	74.00	16.23	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 44

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05




Site no. : 3m Chamber Data no. : 44
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT20 CH140 5700MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5694.960	34.52	11.97	35.45	79.23	90.27	54.00	-36.27	Average
2	5850.000	34.61	11.98	35.45	29.70	40.84	54.00	13.16	Average
3	7026.160	35.56	12.29	35.52	30.33	42.66	54.00	11.34	Average
4	7250.000	36.10	12.48	35.56	28.85	41.87	54.00	12.13	Average
5	7712.560	36.83	12.77	35.54	30.22	44.28	54.00	9.72	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 65
File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-05



Site no. : 3m Chamber Data no. : 65
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH102 5510MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5449.000	34.31	11.94	35.48	44.64	55.41	74.00	18.59	Peak
2	5460.000	34.33	11.94	35.47	43.09	53.89	74.00	20.11	Peak
3	5501.740	34.40	11.95	35.45	89.57	100.47	74.00	-26.47	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 66
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-05



Site no. : 3m Chamber Data no. : 66
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH102 5510MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5446.660	34.30	11.94	35.48	43.32	54.08	74.00	19.92	Peak
2	5460.000	34.33	11.94	35.47	41.44	52.24	74.00	21.76	Peak
3	5500.300	34.40	11.95	35.45	79.70	90.60	74.00	-16.60	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 67
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-05



Site no. : 3m Chamber Data no. : 67
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH102 5510MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5443.600	34.30	11.94	35.48	30.16	40.92	54.00	13.08	Average
2	5460.000	34.33	11.94	35.47	29.95	40.75	54.00	13.25	Average
3	5498.860	34.40	11.95	35.45	69.54	80.44	54.00	-26.44	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 68
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-05


Site no. : 3m Chamber Data no. : 68
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH102 5510MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5450.440	34.31	11.94	35.48	31.41	42.18	54.00	11.82	Average
2	5460.000	34.33	11.94	35.47	31.28	42.08	54.00	11.92	Average
3	5498.860	34.40	11.95	35.45	76.78	87.68	54.00	-33.68	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 73

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 73
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH134 5670MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5661.100	34.50	11.96	35.45	91.97	102.98	74.00	-28.98	Peak
2	5850.000	34.61	11.98	35.45	43.50	54.64	74.00	19.36	Peak
3	6403.820	34.78	12.06	35.35	43.99	55.48	74.00	18.52	Peak
4	7250.000	36.10	12.48	35.56	40.45	53.47	74.00	20.53	Peak
5	7745.780	36.85	12.78	35.53	43.58	57.68	74.00	16.32	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 74

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 74
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH134 5670MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5661.100	34.50	11.96	35.45	84.89	95.90	74.00	-21.90	Peak
2	5850.000	34.61	11.98	35.45	42.22	53.36	74.00	20.64	Peak
3	6984.070	35.48	12.26	35.51	44.34	56.57	74.00	17.43	Peak
4	7250.000	36.10	12.48	35.56	41.29	54.31	74.00	19.69	Peak
5	7743.670	36.85	12.78	35.53	43.10	57.20	74.00	16.80	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 75

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 75
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH134 5670MHz Tx
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5656.880	34.49	11.96	35.45	73.45	84.45	54.00	-30.45	Average
2	5850.000	34.61	11.98	35.45	29.44	40.58	54.00	13.42	Average
3	7032.600	35.58	12.30	35.53	30.24	42.59	54.00	11.41	Average
4	7250.000	36.10	12.48	35.56	28.78	41.80	54.00	12.20	Average
5	7712.020	36.83	12.77	35.54	30.18	44.24	54.00	9.76	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 76

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05




Site no. : 3m Chamber Data no. : 76
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH134 5670MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5661.100	34.50	11.96	35.45	79.81	90.82	54.00	-36.82	Average
2	5851.000	34.61	11.98	35.45	29.64	40.78	54.00	13.22	Average
3	7028.380	35.57	12.29	35.52	30.25	42.59	54.00	11.41	Average
4	7250.000	36.10	12.48	35.56	28.78	41.80	54.00	12.20	Average
5	7712.020	36.83	12.77	35.54	30.17	44.23	54.00	9.77	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 81
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-05


Site no. : 3m Chamber Data no. : 81
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT40 CH102 5510MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5459.260	34.33	11.94	35.47	45.07	55.87	74.00	18.13	Peak
2	5460.000	34.33	11.94	35.47	43.92	54.72	74.00	19.28	Peak
3	5498.500	34.40	11.95	35.45	90.01	100.91	74.00	-26.91	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 82

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no.	: 3m Chamber	Data no.	: 82
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.6%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11ac VHT40 CH102 5510MHz Tx		
	M/N:NS-P11W7100		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5419.300	34.25	11.94	35.49	43.55	54.25	74.00	19.75	Peak
2	5460.000	34.33	11.94	35.47	41.73	52.53	74.00	21.47	Peak
3	5499.760	34.40	11.95	35.45	80.79	91.69	74.00	-17.69	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 83

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 83
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT40 CH102 5510MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5442.700	34.30	11.94	35.48	30.04	40.80	54.00	13.20	Average
2	5460.000	34.33	11.94	35.47	29.83	40.63	54.00	13.37	Average
3	5501.200	34.40	11.95	35.45	70.11	81.01	54.00	-27.01	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Ant Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 84

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 84
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT40 CH102 5510MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5452.060	34.31	11.94	35.48	31.76	42.53	54.00	11.47	Average
2	5460.000	34.33	11.94	35.47	31.60	42.40	54.00	11.60	Average
3	5513.260	34.41	11.95	35.45	77.02	87.93	54.00	-33.93	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Ant Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 89

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05




Site no.	: 3m Chamber	Data no.	: 89
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.6%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11ac VHT40 CH134 5670MHz Tx		
	M/N: NS-P11W7100		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5661.100	34.50	11.96	35.45	86.16	97.17	74.00	-23.17	Peak
2	5850.000	34.61	11.98	35.45	42.57	53.71	74.00	20.29	Peak
3	7036.820	35.59	12.30	35.53	44.25	56.61	74.00	17.39	Peak
4	7250.000	36.10	12.48	35.56	42.19	55.21	74.00	18.79	Peak
5	7701.470	36.82	12.76	35.54	43.99	58.03	74.00	15.97	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 90
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-05


Site no. : 3m Chamber Data no. : 90
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT40 CH134 5670MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5671.650	34.50	11.96	35.45	92.01	103.02	74.00	-29.02	Peak
2	5850.000	34.61	11.98	35.45	42.31	53.45	74.00	20.55	Peak
3	6403.820	34.78	12.06	35.35	44.39	55.88	74.00	18.12	Peak
4	7250.000	36.10	12.48	35.56	41.62	54.64	74.00	19.36	Peak
5	7707.800	36.82	12.76	35.54	43.89	57.93	74.00	16.07	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 91

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 91
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT40 CH134 5670MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5656.880	34.49	11.96	35.45	80.02	91.02	54.00	-37.02	Average
2	5850.000	34.61	11.98	35.45	29.94	41.08	54.00	12.92	Average
3	7028.380	35.57	12.29	35.52	30.37	42.71	54.00	11.29	Average
4	7250.000	36.10	12.48	35.56	28.89	41.91	54.00	12.09	Average
5	7712.020	36.83	12.77	35.54	30.26	44.32	54.00	9.68	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 92

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 92
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT40 CH134 5670MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5656.880	34.49	11.96	35.45	73.25	84.25	54.00	-30.25	Average
2	5850.000	34.61	11.98	35.45	29.55	40.69	54.00	13.31	Average
3	7028.380	35.57	12.29	35.52	30.37	42.71	54.00	11.29	Average
4	7250.000	36.10	12.48	35.56	28.89	41.91	54.00	12.09	Average
5	7712.020	36.83	12.77	35.54	30.28	44.34	54.00	9.66	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 97

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 97
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH106 5530MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5455.110	34.32	11.94	35.47	51.71	62.50	74.00	11.50	Peak
2	5460.000	34.33	11.94	35.47	51.25	62.05	74.00	11.95	Peak
3	5510.310	34.41	11.95	35.45	86.91	97.82	74.00	-23.82	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 98

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05




Site no.	: 3m Chamber	Data no.	: 98
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.6%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11ac VHT80 CH106 5530MHz Tx		
	M/N:NS-P11W7100		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5457.410	34.32	11.94	35.47	45.75	56.54	74.00	17.46	Peak
2	5460.000	34.33	11.94	35.47	44.81	55.61	74.00	18.39	Peak
3	5551.940	34.43	11.95	35.45	78.64	89.57	74.00	-15.57	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 99
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-05



Site no. : 3m Chamber Data no. : 99
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH106 5530MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.000	34.33	11.94	35.47	32.11	42.91	54.00	11.09	Average
2	5547.110	34.43	11.95	35.45	66.19	77.12	54.00	-23.12	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 100
File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 3.EM6 (104)
Date: 2016-07-05


Site no. : 3m Chamber Data no. : 100
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH106 5530MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.000	34.33	11.94	35.47	36.36	47.16	54.00	6.84	Average
2	5507.550	34.40	11.95	35.45	73.23	84.13	54.00	-30.13	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 101

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 101
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH106 5530MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5507.240	34.40	11.95	35.45	73.63	84.53	74.00	-10.53	Peak
2	5850.000	34.61	11.98	35.45	29.24	40.38	74.00	33.62	Peak
3	7028.140	35.57	12.29	35.52	30.28	42.62	74.00	31.38	Peak
4	7250.000	36.10	12.48	35.56	28.77	41.79	74.00	32.21	Peak
5	7711.410	36.83	12.77	35.54	30.19	44.25	74.00	29.75	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 102

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 102
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH106 5530MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5514.050	34.41	11.95	35.45	86.27	97.18	74.00	-23.18	Peak
2	5850.000	34.61	11.98	35.45	42.45	53.59	74.00	20.41	Peak
3	7221.090	36.03	12.46	35.56	42.92	55.85	74.00	18.15	Peak
4	7250.000	36.10	12.48	35.56	40.93	53.95	74.00	20.05	Peak
5	7629.690	36.78	12.74	35.56	43.66	57.62	74.00	16.38	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 103

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 103
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH106 5530MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5541.290	34.42	11.95	35.45	77.58	88.50	74.00	-14.50	Peak
2	5850.000	34.61	11.98	35.45	41.46	52.60	74.00	21.40	Peak
3	7030.410	35.57	12.30	35.52	44.02	56.37	74.00	17.63	Peak
4	7250.000	36.10	12.48	35.56	41.75	54.77	74.00	19.23	Peak
5	7704.600	36.82	12.76	35.54	43.47	57.51	74.00	16.49	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 104

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 3.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 104
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.6%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH106 5530MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5548.100	34.43	11.95	35.45	65.52	76.45	54.00	-22.45	Average
2	5850.000	34.61	11.98	35.45	29.27	40.41	54.00	13.59	Average
3	7028.140	35.57	12.29	35.52	30.29	42.63	54.00	11.37	Average
4	7250.000	36.10	12.48	35.56	28.78	41.80	54.00	12.20	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 13

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)


Date: 2016-07-06



Site no.	: 3m Chamber	Data no.	: 13
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11a CH149 5745MHz Tx		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 14
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-06


Site no. : 3m Chamber Data no. : 14
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5745.000	34.55	11.97	35.45	83.43	94.50	74.00	-20.50	Peak
2	11490.000	39.09	13.49	35.36	30.85	48.07	54.00	5.93	Average
3	11490.000	39.09	13.49	35.36	43.88	61.10	74.00	12.90	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 15

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06




Site no.	: 3m Chamber	Data no.	: 15
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11a CH149 5745MHz Tx		
	M/N:NS-P11W7100		


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 16

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no.	: 3m Chamber	Data no.	: 16
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11a CH149 5745MHz Tx		
	M/N: NS-P11W7100		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5745.000	34.55	11.97	35.45	94.32	105.39	74.00	-31.39	Peak
2	11490.000	39.09	13.49	35.36	30.81	48.03	54.00	5.97	Average
3	11490.000	39.09	13.49	35.36	43.57	60.79	74.00	13.21	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor

2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 21

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06




Site no.	: 3m Chamber	Data no.	: 21
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11a CH157 5785MHz Tx		
	M/N:NS-P11W7100		


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 22

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 22
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH157 5785MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.000	34.57	11.97	35.45	93.60	104.69	74.00	-30.69	Peak
2	11570.000	39.14	13.50	35.35	32.03	49.32	54.00	4.68	Average
3	11570.000	39.14	13.50	35.35	46.00	63.29	74.00	10.71	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 23

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)


Date: 2016-07-06



Site no.	: 3m Chamber	Data no.	: 23
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11a CH157 5785MHz Tx		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 24
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-06


Site no. : 3m Chamber Data no. : 24
Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.4°C/52.8%
Engineer : zack_zhu
EUT : 11.6'' windows tablet
Power rating : DC 5V From Adapter Input AC 120V/60Hz
Test Mode : IEEE802.11a CH157 5785MHz Tx
M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.000	34.57	11.97	35.45	82.75	93.84	74.00	-19.84	Peak
2	11570.000	39.14	13.50	35.35	29.64	46.93	54.00	7.07	Average
3	11570.000	39.14	13.50	35.35	42.81	60.10	74.00	13.90	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
-Amp Factor
2. The emission levels that are 20dB below the official
limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 25

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06




Site no.	: 3m Chamber	Data no.	: 25
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11a CH165 5825MHz Tx		
	M/N:NS-P11W7100		


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 26

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 26
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH165 5825MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.000	34.60	11.98	35.45	82.18	93.31	74.00	-19.31	Peak
2	11650.000	39.19	13.52	35.37	29.81	47.15	54.00	6.85	Average
3	11650.000	39.19	13.52	35.37	42.59	59.93	74.00	14.07	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 27

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)


Date: 2016-07-06



Site no.	: 3m Chamber	Data no.	: 27
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11a CH165 5825MHz Tx		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 28
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-06



Site no. : 3m Chamber Data no. : 28
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH165 5825MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.000	34.60	11.98	35.45	93.19	104.32	74.00	-30.32	Peak
2	11650.000	39.19	13.52	35.37	32.02	49.36	54.00	4.64	Average
3	11650.000	39.19	13.52	35.37	46.68	64.02	74.00	9.98	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 33
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-06


Site no.	: 3m Chamber	Data no.	: 33
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT20 CH165 5825MHz Tx		
	M/N:NS-P11W7100		




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 34

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 34
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH165 5825MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.000	34.60	11.98	35.45	81.32	92.45	74.00	-18.45	Peak
2	11650.000	39.19	13.52	35.37	30.03	47.37	54.00	6.63	Average
3	11650.000	39.19	13.52	35.37	42.77	60.11	74.00	13.89	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 35

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)


Date: 2016-07-06



Site no.	: 3m Chamber	Data no.	: 35
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT20 CH165 5825MHz Tx		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 36
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-06


Site no. : 3m Chamber Data no. : 36
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH165 5825MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.000	34.60	11.98	35.45	92.47	103.60	74.00	-29.60	Peak
2	11650.000	39.19	13.52	35.37	33.32	50.66	54.00	3.34	Average
3	11650.000	39.19	13.52	35.37	45.50	62.84	74.00	11.16	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 41

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no.	: 3m Chamber	Data no.	: 41
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT20 CH157 5785MHz Tx		
	M/N:NS-P11W7100		




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 42

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 42
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH157 5785MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.000	34.57	11.97	35.45	92.65	103.74	74.00	-29.74	Peak
2	11570.000	39.14	13.50	35.35	32.48	49.77	54.00	4.23	Average
3	11570.000	39.14	13.50	35.35	45.59	62.88	74.00	11.12	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 43

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)


Date: 2016-07-06



Site no.	: 3m Chamber	Data no.	: 43
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT20 CH157 5785MHz Tx		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 44
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-06


Site no. : 3m Chamber Data no. : 44
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH157 5785MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.000	34.57	11.97	35.45	82.24	93.33	74.00	-19.33	Peak
2	11570.000	39.14	13.50	35.35	29.59	46.88	54.00	7.12	Average
3	11570.000	39.14	13.50	35.35	42.88	60.17	74.00	13.83	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 45

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no.	: 3m Chamber	Data no.	: 45
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT20 CH149 5745MHz Tx		
	M/N:NS-P11W7100		




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 46

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 46
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5745.000	34.55	11.97	35.45	82.23	93.30	74.00	-19.30	Peak
2	11490.000	39.09	13.49	35.36	30.58	47.80	54.00	6.20	Average
3	11490.000	39.09	13.49	35.36	43.53	60.75	74.00	13.25	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 47

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06




Site no.	: 3m Chamber	Data no.	: 47
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT20 CH149 5745MHz Tx		
	M/N:NS-P11W7100		


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 48

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 48
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5745.000	34.55	11.97	35.45	94.10	105.17	74.00	-31.17	Peak
2	11490.000	39.09	13.49	35.36	32.95	50.17	54.00	3.83	Average
3	11490.000	39.09	13.49	35.36	46.29	63.51	74.00	10.49	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 57

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)


Date: 2016-07-07



Site no.	: 3m Chamber	Data no.	: 57
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT20 CH157 5785MHz Tx		
	M/N: NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 58
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-07


Site no. : 3m Chamber Data no. : 58
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT20 CH157 5785MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.000	34.57	11.97	35.45	83.42	94.51	74.00	-20.51	Peak
2	11570.000	39.14	13.50	35.35	29.68	46.97	54.00	7.03	Average
3	11570.000	39.14	13.50	35.35	43.06	60.35	74.00	13.65	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 59

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no.	: 3m Chamber	Data no.	: 59
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT20 CH157 5785MHz Tx		
	M/N:NS-P11W7100		




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 60

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 60
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT20 CH157 5785MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.000	34.57	11.97	35.45	92.74	103.83	74.00	-29.83	Peak
2	11570.000	39.14	13.50	35.35	34.12	51.41	54.00	2.59	Average
3	11570.000	39.14	13.50	35.35	42.57	59.86	74.00	14.14	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 61

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07




Site no.	: 3m Chamber	Data no.	: 61
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT20 CH149 5745MHz Tx		
	M/N:NS-P11W7100		


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 62

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no.	: 3m Chamber	Data no.	: 62
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT20 CH149 5745MHz Tx		
	M/N:NS-P11W7100		


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5745.000	34.55	11.97	35.45	92.87	103.94	74.00	-29.94	Peak
2	11490.000	39.09	13.49	35.36	33.29	50.51	54.00	3.49	Average
3	11490.000	39.09	13.49	35.36	47.57	64.79	74.00	9.21	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor

2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 63
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-07


Site no.	: 3m Chamber	Data no.	: 63
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT20 CH149 5745MHz Tx		
	M/N:NS-P11W7100		




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 64

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07




Site no. : 3m Chamber Data no. : 64
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT20 CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5745.000	34.55	11.97	35.45	82.37	93.44	74.00	-19.44	Peak
2	11490.000	39.09	13.49	35.36	30.76	47.98	54.00	6.02	Average
3	11490.000	39.09	13.49	35.36	43.31	60.53	74.00	13.47	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 65
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-07


Site no.	: 3m Chamber	Data no.	: 65
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT20 CH165 5825MHz Tx		
	M/N:NS-P11W7100		




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 66

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 66
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT20 CH165 5825MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.000	34.60	11.98	35.45	83.26	94.39	74.00	-20.39	Peak
2	11650.000	39.19	13.52	35.37	29.95	47.29	54.00	6.71	Average
3	11650.000	39.19	13.52	35.37	43.01	60.35	74.00	13.65	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 67

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07




Site no.	: 3m Chamber	Data no.	: 67
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT20 CH165 5825MHz Tx		
	M/N:NS-P11W7100		


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 68

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07




Site no. : 3m Chamber Data no. : 68
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT20 CH165 5825MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.000	34.60	11.98	35.45	92.28	103.41	74.00	-29.41	Peak
2	11650.000	39.19	13.52	35.37	33.06	50.40	54.00	3.60	Average
3	11650.000	39.19	13.52	35.37	47.29	64.63	74.00	9.37	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 73
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-07


Site no.	: 3m Chamber	Data no.	: 73
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT40 CH151 5755MHz Tx		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 74
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-07


Site no. : 3m Chamber Data no. : 74
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH151 5755MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5755.000	34.55	11.97	35.45	80.64	91.71	74.00	-17.71	Peak
2	11510.000	39.11	13.49	35.34	29.58	46.84	54.00	7.16	Average
3	11510.000	39.11	13.49	35.34	42.43	59.69	74.00	14.31	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 75

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)


Date: 2016-07-07



Site no.	: 3m Chamber	Data no.	: 75
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT40 CH151 5755MHz Tx		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 76
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-07


Site no. : 3m Chamber Data no. : 76
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH151 5755MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5755.000	34.55	11.97	35.45	89.61	100.68	74.00	-26.68	Peak
2	11510.000	39.11	13.49	35.34	31.64	48.90	54.00	5.10	Average
3	11510.000	39.11	13.49	35.34	44.44	61.70	74.00	12.30	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 81

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)


Date: 2016-07-07



Site no.	: 3m Chamber	Data no.	: 81
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT40 CH159 5795MHz Tx		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 82
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-07


Site no. : 3m Chamber Data no. : 82
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH159 5795MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5795.000	34.58	11.97	35.45	90.38	101.48	74.00	-27.48	Peak
2	11590.000	39.15	13.51	35.36	32.89	50.19	54.00	3.81	Average
3	11590.000	39.15	13.51	35.36	45.99	63.29	74.00	10.71	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 83

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07




Site no.	: 3m Chamber	Data no.	: 83
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT40 CH159 5795MHz Tx		
	M/N:NS-P11W7100		


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 84

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07




Site no. : 3m Chamber Data no. : 84
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH159 5795MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5795.000	34.58	11.97	35.45	79.93	91.03	74.00	-17.03	Peak
2	11590.000	39.15	13.51	35.36	30.07	47.37	54.00	6.63	Average
3	11590.000	39.15	13.51	35.36	43.26	60.56	74.00	13.44	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 89
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-07


Site no.	: 3m Chamber	Data no.	: 89
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT40 CH159 5795MHz Tx		
	M/N:NS-P11W7100		




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 90

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 90
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT40 CH159 5795MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5795.000	34.58	11.97	35.45	80.66	91.76	74.00	-17.76	Peak
2	11590.000	39.15	13.51	35.36	29.94	47.24	54.00	6.76	Average
3	11590.000	39.15	13.51	35.36	42.57	59.87	74.00	14.13	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 91

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)


Date: 2016-07-07



Site no.	: 3m Chamber	Data no.	: 91
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT40 CH159 5795MHz Tx		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 92
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-07


Site no. : 3m Chamber Data no. : 92
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT40 CH159 5795MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5795.000	34.58	11.97	35.45	91.55	102.65	74.00	-28.65	Peak
2	11590.000	39.15	13.51	35.36	32.10	49.40	54.00	4.60	Average
3	11590.000	39.15	13.51	35.36	44.91	62.21	74.00	11.79	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 97

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no.	: 3m Chamber	Data no.	: 97
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT40 CH151 5755MHz Tx		
	M/N:NS-P11W7100		




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 98

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07




Site no. : 3m Chamber Data no. : 98
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT40 CH151 5755MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5755.000	34.55	11.97	35.45	89.81	100.88	74.00	-26.88	Peak
2	11510.000	39.11	13.49	35.34	31.86	49.12	54.00	4.88	Average
3	11510.000	39.11	13.49	35.34	45.46	62.72	74.00	11.28	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 99
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-07


Site no.	: 3m Chamber	Data no.	: 99
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT40 CH151 5755MHz Tx		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 100
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-07


Site no. : 3m Chamber Data no. : 100
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT40 CH151 5755MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5755.000	34.55	11.97	35.45	82.07	93.14	74.00	-19.14	Peak
2	11510.000	39.11	13.49	35.34	30.77	48.03	54.00	5.97	Average
3	11510.000	39.11	13.49	35.34	43.79	61.05	74.00	12.95	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 1

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)


Date: 2016-07-05



Site no.	: 3m Chamber	Data no.	: 1
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11ac VHT80 CH155 5775MHz Tx		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 2
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-05


Site no. : 3m Chamber Data no. : 2
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH155 5775MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5775.000	34.57	11.97	35.45	78.86	89.95	74.00	-15.95	Peak
2	11550.000	39.13	13.50	35.35	30.45	47.73	54.00	6.27	Average
3	11550.000	39.13	13.50	35.35	45.31	62.59	74.00	11.41	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 3

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)


Date: 2016-07-05



Site no.	: 3m Chamber	Data no.	: 3
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11ac VHT80 CH155 5775MHz Tx		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 4
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-05


Site no. : 3m Chamber Data no. : 4
Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.4°C/52.8%
Engineer : zack_zhu
EUT : 11.6'' windows tablet
Power rating : DC 5V From Adapter Input AC 120V/60Hz
Test Mode : IEEE802.11ac VHT80 CH155 5775MHz Tx
M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5775.000	34.57	11.97	35.45	87.98	99.07	74.00	-25.07	Peak
2	11550.000	39.13	13.50	35.35	31.76	49.04	54.00	4.96	Average
3	11550.000	39.13	13.50	35.35	44.38	61.66	74.00	12.34	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
-Amp Factor
2. The emission levels that are 20dB below the official
limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 17

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 17
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5426.670	34.27	11.94	35.49	43.90	54.62	74.00	19.38	Peak
2	5460.000	34.33	11.94	35.47	43.25	54.05	74.00	19.95	Peak
3	5715.000	34.53	11.97	35.45	43.56	54.61	74.00	19.39	Peak
4	5725.000	34.53	11.97	35.45	53.19	64.24	74.00	9.76	Peak
5	5742.780	34.55	11.97	35.45	95.51	106.58	74.00	-32.58	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 18

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 18
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5453.320	34.32	11.94	35.48	44.20	54.98	74.00	19.02	Peak
2	5460.000	34.33	11.94	35.47	42.70	53.50	74.00	20.50	Peak
3	5715.000	34.53	11.97	35.45	42.58	53.63	74.00	20.37	Peak
4	5725.000	34.53	11.97	35.45	46.87	57.92	74.00	16.08	Peak
5	5749.750	34.55	11.97	35.45	84.71	95.78	74.00	-21.78	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 19

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 19
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.000	34.33	11.94	35.47	29.70	40.50	54.00	13.50	Average
2	5715.000	34.53	11.97	35.45	29.23	40.28	54.00	13.72	Average
3	5725.000	34.53	11.97	35.45	31.20	42.25	54.00	11.75	Average
4	5746.470	34.55	11.97	35.45	73.63	84.70	54.00	-30.70	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 20

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 20
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.000	34.33	11.94	35.47	29.96	40.76	54.00	13.24	Average
2	5715.000	34.53	11.97	35.45	31.71	42.76	54.00	11.24	Average
3	5725.000	34.53	11.97	35.45	37.29	48.34	54.00	5.66	Average
4	5742.780	34.55	11.97	35.45	82.41	93.48	54.00	-39.48	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 29

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 29
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH165 5825MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5823.580	34.59	11.98	35.45	83.45	94.57	74.00	-20.57	Peak
2	5850.000	34.61	11.98	35.45	42.10	53.24	74.00	20.76	Peak
3	5860.000	34.62	11.98	35.45	42.35	53.50	74.00	20.50	Peak
4	7138.900	35.83	12.39	35.54	43.47	56.15	74.00	17.85	Peak
5	7250.000	36.10	12.48	35.56	41.24	54.26	74.00	19.74	Peak
6	7270.820	36.15	12.50	35.56	42.91	56.00	74.00	18.00	Peak
7	7691.800	36.82	12.76	35.55	43.78	57.81	74.00	16.19	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 30

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 30
Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.4°C/52.8%
Engineer : zack_zhu
EUT : 11.6'' windows tablet
Power rating : DC 5V From Adapter Input AC 120V/60Hz
Test Mode : IEEE802.11a CH165 5825MHz Tx
M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5819.700	34.59	11.98	35.45	93.78	104.90	74.00	-30.90	Peak
2	5850.000	34.61	11.98	35.45	46.90	58.04	74.00	15.96	Peak
3	5860.000	34.62	11.98	35.45	44.72	55.87	74.00	18.13	Peak
4	7250.000	36.10	12.48	35.56	42.93	55.95	74.00	18.05	Peak
5	7707.320	36.82	12.76	35.54	43.67	57.71	74.00	16.29	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
- Amp Factor
2. The emission levels that are 20dB below the official
limit are not reported.


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 31

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no.	: 3m Chamber	Data no.	: 31
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C AV		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11a CH165 5825MHz Tx		
	M/N:NS-P11W7100		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5823.580	34.59	11.98	35.45	81.97	93.09	54.00	-39.09	Average
2	5850.000	34.61	11.98	35.45	33.07	44.21	54.00	9.79	Average
3	5860.000	34.62	11.98	35.45	32.45	43.60	54.00	10.40	Average
4	7250.000	36.10	12.48	35.56	28.83	41.85	54.00	12.15	Average
5	7711.200	36.83	12.77	35.54	30.22	44.28	54.00	9.72	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 32

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 32
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11a CH165 5825MHz Tx
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5823.580	34.59	11.98	35.45	72.14	83.26	54.00	-29.26	Average
2	5850.000	34.61	11.98	35.45	29.76	40.90	54.00	13.10	Average
3	5860.000	34.62	11.98	35.45	29.90	41.05	54.00	12.95	Average
4	7028.320	35.57	12.29	35.52	30.31	42.65	54.00	11.35	Average
5	7250.000	36.10	12.48	35.56	28.83	41.85	54.00	12.15	Average
6	7711.200	36.83	12.77	35.54	30.23	44.29	54.00	9.71	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 49

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 49
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5419.700	34.26	11.94	35.49	43.62	54.33	74.00	19.67	Peak
2	5460.000	34.33	11.94	35.47	42.49	53.29	74.00	20.71	Peak
3	5715.000	34.53	11.97	35.45	43.93	54.98	74.00	19.02	Peak
4	5725.000	34.53	11.97	35.45	56.85	67.90	74.00	6.10	Peak
5	5746.880	34.55	11.97	35.45	95.26	106.33	74.00	-32.33	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 50

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 50
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH149 5745MHz Tx
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5420.930	34.26	11.94	35.49	44.60	55.31	74.00	18.69	Peak
2	5460.000	34.33	11.94	35.47	42.08	52.88	74.00	21.12	Peak
3	5715.000	34.53	11.97	35.45	40.94	51.99	74.00	22.01	Peak
4	5725.000	34.53	11.97	35.45	47.05	58.10	74.00	15.90	Peak
5	5747.700	34.55	11.97	35.45	83.37	94.44	74.00	-20.44	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 51

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 51
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.000	34.33	11.94	35.47	29.64	40.44	54.00	13.56	Average
2	5715.000	34.53	11.97	35.45	29.21	40.26	54.00	13.74	Average
3	5725.000	34.53	11.97	35.45	32.34	43.39	54.00	10.61	Average
4	5742.370	34.55	11.97	35.45	72.14	83.21	54.00	-29.21	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 52

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 52
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.000	34.33	11.94	35.47	29.87	40.67	54.00	13.33	Average
2	5715.000	34.53	11.97	35.45	31.55	42.60	54.00	11.40	Average
3	5725.000	34.53	11.97	35.45	39.33	50.38	54.00	3.62	Average
4	5743.600	34.55	11.97	35.45	82.19	93.26	54.00	-39.26	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 37

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06




Site no. : 3m Chamber Data no. : 37
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH165 5825MHz Tx
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5823.580	34.59	11.98	35.45	93.89	105.01	74.00	-31.01	Peak
2	5850.000	34.61	11.98	35.45	46.54	57.68	74.00	16.32	Peak
3	5860.000	34.62	11.98	35.45	45.48	56.63	74.00	17.37	Peak
4	7250.000	36.10	12.48	35.56	40.95	53.97	74.00	20.03	Peak
5	7695.680	36.82	12.76	35.55	43.35	57.38	74.00	16.62	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 38
File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-06


Site no. : 3m Chamber Data no. : 38
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH165 5825MHz Tx
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5829.400	34.60	11.98	35.45	82.92	94.05	74.00	-20.05	Peak
2	5850.000	34.61	11.98	35.45	42.30	53.44	74.00	20.56	Peak
3	5860.000	34.62	11.98	35.45	42.75	53.90	74.00	20.10	Peak
4	7113.680	35.77	12.37	35.54	43.34	55.94	74.00	18.06	Peak
5	7250.000	36.10	12.48	35.56	41.28	54.30	74.00	19.70	Peak
6	7707.320	36.82	12.76	35.54	43.89	57.93	74.00	16.07	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 39

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no.	: 3m Chamber	Data no.	: 39
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C AV		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT20 CH165 5825MHz Tx		
	M/N:NS-P11W7100		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5823.580	34.59	11.98	35.45	71.08	82.20	54.00	-28.20	Average
2	5850.000	34.61	11.98	35.45	29.76	40.90	54.00	13.10	Average
3	5860.000	34.62	11.98	35.45	29.93	41.08	54.00	12.92	Average
4	7032.200	35.58	12.30	35.53	30.29	42.64	54.00	11.36	Average
5	7250.000	36.10	12.48	35.56	28.84	41.86	54.00	12.14	Average
6	7711.200	36.83	12.77	35.54	30.24	44.30	54.00	9.70	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 40

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-06



Site no. : 3m Chamber Data no. : 40
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 CH165 5825MHz Tx
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5823.580	34.59	11.98	35.45	82.09	93.21	54.00	-39.21	Average
2	5850.000	34.61	11.98	35.45	33.33	44.47	54.00	9.53	Average
3	5860.000	34.62	11.98	35.45	32.59	43.74	54.00	10.26	Average
4	7250.000	36.10	12.48	35.56	28.83	41.85	54.00	12.15	Average
5	7715.080	36.83	12.77	35.54	30.21	44.27	54.00	9.73	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 53

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 53
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT20 CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.000	34.33	11.94	35.47	30.34	41.14	54.00	12.86	Average
2	5715.000	34.53	11.97	35.45	32.99	44.04	54.00	9.96	Average
3	5725.000	34.53	11.97	35.45	39.59	50.64	54.00	3.36	Average
4	5743.600	34.55	11.97	35.45	84.44	95.51	54.00	-41.51	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 54

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 54
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT20 CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.000	34.33	11.94	35.47	41.29	52.09	74.00	21.91	Peak
2	5686.200	34.51	11.96	35.45	44.89	55.91	74.00	18.09	Peak
3	5715.000	34.53	11.97	35.45	43.23	54.28	74.00	19.72	Peak
4	5725.000	34.53	11.97	35.45	54.86	65.91	74.00	8.09	Peak
5	5740.730	34.54	11.97	35.45	94.43	105.49	74.00	-31.49	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 55

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 55
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT20 CH149 5745MHz Tx
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.000	34.33	11.94	35.47	29.78	40.58	54.00	13.42	Average
2	5715.000	34.53	11.97	35.45	29.45	40.50	54.00	13.50	Average
3	5725.000	34.53	11.97	35.45	32.21	43.26	54.00	10.74	Average
4	5742.370	34.55	11.97	35.45	73.90	84.97	54.00	-30.97	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 56

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 56
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT20 CH149 5745MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.000	34.33	11.94	35.47	40.49	51.29	74.00	22.71	Peak
2	5611.170	34.47	11.96	35.45	43.59	54.57	74.00	19.43	Peak
3	5715.000	34.53	11.97	35.45	41.88	52.93	74.00	21.07	Peak
4	5725.000	34.53	11.97	35.45	46.93	57.98	74.00	16.02	Peak
5	5742.370	34.55	11.97	35.45	84.60	95.67	74.00	-21.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 69

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07




Site no. : 3m Chamber Data no. : 69
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT20 CH165 5825MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.520	34.60	11.98	35.45	93.85	104.98	74.00	-30.98	Peak
2	5850.000	34.61	11.98	35.45	45.95	57.09	74.00	16.91	Peak
3	5860.000	34.62	11.98	35.45	45.01	56.16	74.00	17.84	Peak
4	5868.200	34.62	11.98	35.45	46.08	57.23	74.00	16.77	Peak
5	7250.000	36.10	12.48	35.56	41.92	54.94	74.00	19.06	Peak
6	7717.020	36.83	12.77	35.54	42.85	56.91	74.00	17.09	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 70
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)
Date: 2016-07-07


Site no. : 3m Chamber Data no. : 70
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT20 CH165 5825MHz Tx
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5823.580	34.59	11.98	35.45	82.37	93.49	54.00	-39.49	Average
2	5850.000	34.61	11.98	35.45	33.04	44.18	54.00	9.82	Average
3	5860.000	34.62	11.98	35.45	32.57	43.72	54.00	10.28	Average
4	7250.000	36.10	12.48	35.56	28.91	41.93	54.00	12.07	Average
5	7715.080	36.83	12.77	35.54	30.22	44.28	54.00	9.72	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 71

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 71
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT20 CH165 5825MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.520	34.60	11.98	35.45	84.39	95.52	74.00	-21.52	Peak
2	5850.000	34.61	11.98	35.45	42.36	53.50	74.00	20.50	Peak
3	5860.000	34.62	11.98	35.45	42.53	53.68	74.00	20.32	Peak
4	7171.880	35.91	12.41	35.55	43.95	56.72	74.00	17.28	Peak
5	7250.000	36.10	12.48	35.56	41.31	54.33	74.00	19.67	Peak
6	7736.420	36.84	12.78	35.53	43.28	57.37	74.00	16.63	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 72

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no.	: 3m Chamber	Data no.	: 72
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C AV		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT20 CH165 5825MHz Tx		
	M/N:NS-P11W7100		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5823.580	34.59	11.98	35.45	73.61	84.73	54.00	-30.73	Average
2	5850.000	34.61	11.98	35.45	30.08	41.22	54.00	12.78	Average
3	5860.000	34.62	11.98	35.45	30.13	41.28	54.00	12.72	Average
4	7028.320	35.57	12.29	35.52	30.31	42.65	54.00	11.35	Average
5	7250.000	36.10	12.48	35.56	28.84	41.86	54.00	12.14	Average
6	7711.200	36.83	12.77	35.54	30.20	44.26	54.00	9.74	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 77

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 77
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH151 5755MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5417.940	34.25	11.94	35.49	43.44	54.14	74.00	19.86	Peak
2	5460.000	34.33	11.94	35.47	41.83	52.63	74.00	21.37	Peak
3	5680.240	34.51	11.96	35.45	45.16	56.18	74.00	17.82	Peak
4	5715.000	34.53	11.97	35.45	50.57	61.62	74.00	12.38	Peak
5	5725.000	34.53	11.97	35.45	54.28	65.33	74.00	8.67	Peak
6	5751.190	34.55	11.97	35.45	91.27	102.34	74.00	-28.34	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 78

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 78
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH151 5755MHz Tx
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5415.360	34.25	11.94	35.50	43.35	54.04	74.00	19.96	Peak
2	5460.000	34.33	11.94	35.47	41.70	52.50	74.00	21.50	Peak
3	5713.350	34.53	11.97	35.45	44.45	55.50	74.00	18.50	Peak
4	5715.000	34.53	11.97	35.45	43.79	54.84	74.00	19.16	Peak
5	5725.000	34.53	11.97	35.45	48.45	59.50	74.00	14.50	Peak
6	5745.600	34.55	11.97	35.45	81.76	92.83	74.00	-18.83	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 79

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 79
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH151 5755MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5439.440	34.29	11.94	35.48	30.02	40.77	54.00	13.23	Average
2	5460.080	34.33	11.94	35.47	29.73	40.53	54.00	13.47	Average
3	5715.000	34.53	11.97	35.45	31.73	42.78	54.00	11.22	Average
4	5725.000	34.53	11.97	35.45	35.25	46.30	54.00	7.70	Average
5	5743.450	34.55	11.97	35.45	70.52	81.59	54.00	-27.59	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 80

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 80
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH151 5755MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5430.410	34.27	11.94	35.49	30.47	41.19	54.00	12.81	Average
2	5460.080	34.33	11.94	35.47	30.13	40.93	54.00	13.07	Average
3	5715.000	34.53	11.97	35.45	37.70	48.75	54.00	5.25	Average
4	5725.000	34.53	11.97	35.45	42.81	53.86	54.00	0.14	Average
5	5743.450	34.55	11.97	35.45	79.01	90.08	54.00	-36.08	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 85

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 85
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH159 5795MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.840	34.57	11.97	35.45	82.72	93.81	74.00	-19.81	Peak
2	5850.000	34.61	11.98	35.45	42.23	53.37	74.00	20.63	Peak
3	5860.000	34.62	11.98	35.45	44.08	55.23	74.00	18.77	Peak
4	7159.960	35.88	12.40	35.55	43.60	56.33	74.00	17.67	Peak
5	7250.000	36.10	12.48	35.56	40.59	53.61	74.00	20.39	Peak
6	7736.140	36.84	12.78	35.53	43.76	57.85	74.00	16.15	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 86

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 86
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH159 5795MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5795.740	34.58	11.97	35.45	92.28	103.38	74.00	-29.38	Peak
2	5850.000	34.61	11.98	35.45	46.29	57.43	74.00	16.57	Peak
3	5860.000	34.62	11.98	35.45	45.29	56.44	74.00	17.56	Peak
4	6981.760	35.47	12.26	35.51	44.45	56.67	74.00	17.33	Peak
5	7250.000	36.10	12.48	35.56	41.74	54.76	74.00	19.24	Peak
6	7734.160	36.84	12.77	35.53	43.47	57.55	74.00	16.45	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 87

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no.	: 3m Chamber	Data no.	: 87
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C AV		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT40 CH159 5795MHz Tx		
	M/N: NS-P11W7100		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5803.660	34.58	11.97	35.45	79.83	90.93	54.00	-36.93	Average
2	5850.000	34.61	11.98	35.45	32.78	43.92	54.00	10.08	Average
3	5860.000	34.62	11.98	35.45	32.69	43.84	54.00	10.16	Average
4	7250.000	36.10	12.48	35.56	28.93	41.95	54.00	12.05	Average
5	7714.360	36.83	12.77	35.54	30.27	44.33	54.00	9.67	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 88

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 88
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 CH159 5795MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5803.660	34.58	11.97	35.45	70.72	81.82	54.00	-27.82	Average
2	5850.000	34.61	11.98	35.45	29.92	41.06	54.00	12.94	Average
3	5860.000	34.62	11.98	35.45	30.07	41.22	54.00	12.78	Average
4	7031.260	35.58	12.30	35.53	30.34	42.69	54.00	11.31	Average
5	7250.000	36.10	12.48	35.56	28.88	41.90	54.00	12.10	Average
6	7528.240	36.72	12.70	35.59	29.39	43.22	54.00	10.78	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 101

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 101
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT40 CH151 5755MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5376.660	34.18	11.93	35.52	43.53	54.12	74.00	19.88	Peak
2	5460.000	34.33	11.94	35.47	41.96	52.76	74.00	21.24	Peak
3	5715.000	34.53	11.97	35.45	43.37	54.42	74.00	19.58	Peak
4	5725.000	34.53	11.97	35.45	46.23	57.28	74.00	16.72	Peak
5	5744.310	34.55	11.97	35.45	82.62	93.69	74.00	-19.69	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 102

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 102
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT40 CH151 5755MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5446.750	34.30	11.94	35.48	44.72	55.48	74.00	18.52	Peak
2	5460.000	34.33	11.94	35.47	42.70	53.50	74.00	20.50	Peak
3	5715.000	34.53	11.97	35.45	51.90	62.95	74.00	11.05	Peak
4	5725.000	34.53	11.97	35.45	55.57	66.62	74.00	7.38	Peak
5	5745.600	34.55	11.97	35.45	91.34	102.41	74.00	-28.41	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 103

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 103
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT40 CH151 5755MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5439.010	34.29	11.94	35.48	30.27	41.02	54.00	12.98	Average
2	5460.000	34.33	11.94	35.47	29.95	40.75	54.00	13.25	Average
3	5715.000	34.53	11.97	35.45	37.06	48.11	54.00	5.89	Average
4	5725.000	34.53	11.97	35.45	42.28	53.33	54.00	0.67	Average
5	5745.600	34.55	11.97	35.45	79.65	90.72	54.00	-36.72	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 104

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 104
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT40 CH151 5755MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5440.300	34.29	11.94	35.48	29.92	40.67	54.00	13.33	Average
2	5460.000	34.33	11.94	35.47	29.64	40.44	54.00	13.56	Average
3	5715.000	34.53	11.97	35.45	30.99	42.04	54.00	11.96	Average
4	5725.000	34.53	11.97	35.45	33.95	45.00	54.00	9.00	Average
5	5743.450	34.55	11.97	35.45	70.18	81.25	54.00	-27.25	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 93

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no.	: 3m Chamber	Data no.	: 93
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT40 CH159 5795MHz Tx		
	M/N: NS-P11W7100		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5805.640	34.58	11.97	35.45	91.97	103.07	74.00	-29.07	Peak
2	5850.000	34.61	11.98	35.45	45.29	56.43	74.00	17.57	Peak
3	5860.000	34.62	11.98	35.45	45.18	56.33	74.00	17.67	Peak
4	7250.000	36.10	12.48	35.56	41.50	54.52	74.00	19.48	Peak
5	7720.300	36.83	12.77	35.54	43.29	57.35	74.00	16.65	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 94

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no.	: 3m Chamber	Data no.	: 94
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11acVHT40 CH159 5795MHz Tx		
	M/N: NS-P11W7100		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5799.700	34.58	11.97	35.45	82.25	93.35	74.00	-19.35	Peak
2	5850.000	34.61	11.98	35.45	42.68	53.82	74.00	20.18	Peak
3	5860.000	34.62	11.98	35.45	42.59	53.74	74.00	20.26	Peak
4	7221.340	36.03	12.46	35.56	43.56	56.49	74.00	17.51	Peak
5	7250.000	36.10	12.48	35.56	40.66	53.68	74.00	20.32	Peak
6	7744.060	36.85	12.78	35.53	44.14	58.24	74.00	15.76	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 95

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 95
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT40 CH159 5795MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5799.700	34.58	11.97	35.45	70.40	81.50	54.00	-27.50	Average
2	5850.000	34.61	11.98	35.45	29.81	40.95	54.00	13.05	Average
3	5860.000	34.62	11.98	35.45	30.00	41.15	54.00	12.85	Average
4	7031.260	35.58	12.30	35.53	30.30	42.65	54.00	11.35	Average
5	7250.000	36.10	12.48	35.56	28.80	41.82	54.00	12.18	Average
6	7710.400	36.83	12.77	35.54	30.21	44.27	54.00	9.73	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 96

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-07



Site no. : 3m Chamber Data no. : 96
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11acVHT40 CH159 5795MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5799.700	34.58	11.97	35.45	79.12	90.22	54.00	-36.22	Average
2	5850.000	34.61	11.98	35.45	32.34	43.48	54.00	10.52	Average
3	5860.000	34.62	11.98	35.45	32.33	43.48	54.00	10.52	Average
4	7250.000	36.10	12.48	35.56	28.79	41.81	54.00	12.19	Average
5	7714.360	36.83	12.77	35.54	30.17	44.23	54.00	9.77	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 5

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 5
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH155 5775MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.000	34.33	11.94	35.47	30.34	41.14	54.00	12.86	Average
2	5715.000	34.53	11.97	35.45	45.12	56.17	54.00	-2.17	Average
3	5725.000	34.53	11.97	35.45	44.64	55.69	54.00	-1.69	Average
4	5751.850	34.55	11.97	35.45	75.42	86.49	54.00	-32.49	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 6

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 6
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH155 5775MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5436.950	34.29	11.94	35.48	43.66	54.41	74.00	19.59	Peak
2	5460.000	34.33	11.94	35.47	41.75	52.55	74.00	21.45	Peak
3	5715.000	34.53	11.97	35.45	59.11	70.16	74.00	3.84	Peak
4	5721.300	34.53	11.97	35.45	62.30	73.35	74.00	0.65	Peak
5	5725.000	34.53	11.97	35.45	60.01	71.06	74.00	2.94	Peak
6	5750.910	34.55	11.97	35.45	88.07	99.14	74.00	-25.14	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 7

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-05



Site no.	: 3m Chamber	Data no.	: 7
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.4°C/52.8%		
Engineer	: zack_zhu		
EUT	: 11.6'' windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11ac VHT80 CH155 5775MHz Tx		
	M/N:NS-P11W7100		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5450.110	34.31	11.94	35.48	42.88	53.65	74.00	20.35	Peak
2	5460.000	34.33	11.94	35.47	41.58	52.38	74.00	21.62	Peak
3	5715.000	34.53	11.97	35.45	51.14	62.19	74.00	11.81	Peak
4	5719.890	34.53	11.97	35.45	54.02	65.07	74.00	8.93	Peak
5	5725.000	34.53	11.97	35.45	52.97	64.02	74.00	9.98	Peak
6	5797.910	34.58	11.97	35.45	78.65	89.75	74.00	-15.75	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 8

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 8
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH155 5775MHz Tx
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.000	34.33	11.94	35.47	29.71	40.51	54.00	13.49	Average
2	5715.000	34.53	11.97	35.45	36.64	47.69	54.00	6.31	Average
3	5725.000	34.53	11.97	35.45	35.59	46.64	54.00	7.36	Average
4	5798.850	34.58	11.97	35.45	65.54	76.64	54.00	-22.64	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 9

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 9
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH155 5775MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5796.660	34.58	11.97	35.45	67.17	78.27	54.00	-24.27	Average
2	5850.000	34.61	11.98	35.45	34.45	45.59	54.00	8.41	Average
3	5860.000	34.62	11.98	35.45	32.67	43.82	54.00	10.18	Average
4	7250.000	36.10	12.48	35.56	28.80	41.82	54.00	12.18	Average
5	7709.600	36.83	12.77	35.54	30.15	44.21	54.00	9.79	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 10

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 10
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH155 5775MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5796.660	34.58	11.97	35.45	80.11	91.21	74.00	-17.21	Peak
2	5850.000	34.61	11.98	35.45	49.27	60.41	74.00	13.59	Peak
3	5860.000	34.62	11.98	35.45	48.82	59.97	74.00	14.03	Peak
4	7250.000	36.10	12.48	35.56	40.38	53.40	74.00	20.60	Peak
5	7705.560	36.82	12.76	35.54	43.64	57.68	74.00	16.32	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 11

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 11
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH155 5775MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5754.240	34.55	11.97	35.45	74.80	85.87	54.00	-31.87	Average
2	5850.000	34.61	11.98	35.45	41.27	52.41	54.00	1.59	Average
3	5860.000	34.62	11.98	35.45	38.91	50.06	54.00	3.94	Average
4	7250.000	36.10	12.48	35.56	28.79	41.81	54.00	12.19	Average
5	7713.640	36.83	12.77	35.54	30.14	44.20	54.00	9.80	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 12

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-5GHz-Band 4.EM6 (104)

Date: 2016-07-05



Site no. : 3m Chamber Data no. : 12
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.4°C/52.8%
 Engineer : zack_zhu
 EUT : 11.6'' windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11ac VHT80 CH155 5775MHz Tx
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5750.200	34.55	11.97	35.45	87.95	99.02	74.00	-25.02	Peak
2	5850.000	34.61	11.98	35.45	55.71	66.85	74.00	7.15	Peak
3	5860.000	34.62	11.98	35.45	55.71	66.86	74.00	7.14	Peak
4	7250.000	36.10	12.48	35.56	40.41	53.43	74.00	20.57	Peak
5	7715.660	36.83	12.77	35.54	42.90	56.96	74.00	17.04	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.

Prüfbericht - Nr.: 50050527 010

Test Report No.

Seite 454 von 479

Page 454 of 479

5.1.8 Dynamic Frequency Selection


RESULT:**Pass**

Date of testing	:	2016-07-05
Test standard	:	FCC part 15.407(h)(2) RSS-247 clause 6.3 KDB905462 D02 v02
Basic standard	:	ANSI C63.10: 2013
Limits	:	FCC part 15.407(h)(2)(iii)
Kind of test site	:	Shield room


Test setup

Test Channel	:	All channel
Operation mode	:	B.1, C.1 (802.11ac)
Ambient temperature	:	23.4°C
Relative humidity	:	53.3%
Atmospheric pressure	:	102.6kPa


For details refer to following test plot.

Table 28: Test result of Dynamic Frequency Selection of 802.11ac VHT20, 5260MHz



Date: 5.JUL.2016 17:17:14




Date: 5.JUL.2016 17:18:27




Date: 5.JUL.2016 17:18:57



Date: 5.JUL.2016 10:36:00


Table 29: Test result of Dynamic Frequency Selection of 802.11ac VHT20, 5500MHz


Date: 5.JUL.2016 16:21:01




Date: 5.JUL.2016 16:22:26


Date: 5.JUL.2016 10:37:25

Table 30: Test result of Dynamic Frequency Selection of 802.11ac VHT40, 5270MHz



Date: 5.JUL.2016 16:28:08




Date: 5.JUL.2016 10:39:50




Date: 5.JUL.2016 16:28:43




Date: 5.JUL.2016 16:30:09

Table 31: Test result of Dynamic Frequency Selection of 802.11ac VHT40, 5510MHz



Date: 5.JUL.2016 17:26:51




Date: 5.JUL.2016 17:27:38




Date: 5.JUL.2016 17:28:21




Date: 5.JUL.2016 10:42:39

Table 32: Test result of Dynamic Frequency Selection of 802.11ac VHT80, 5290MHz



Date: 5.JUL.2016 16:54:02




Date: 5.JUL.2016 16:54:50




Date: 5.JUL.2016 16:55:14




Date: 5.JUL.2016 10:40:22

Table 33: Test result of Dynamic Frequency Selection of 802.11ac VHT80, 5530MHz



Date: 5.JUL.2016 17:11:54



Date: 5.JUL.2016 17:12:53



Date: 5.JUL.2016 17:13:22



Date: 5.JUL.2016 10:42:41

Prüfbericht - Nr.: 50050527 010

Test Report No.

Seite 467 von 479

Page 467 of 479

5.1.9 Conducted emissions**RESULT:****Pass**

Date of testing	:	2016-07-08
Test standard	:	FCC Part 15.207 FCC part 15.407(b)(6) RSS-Gen Clause 8.8
Basic standard	:	ANSI C63.10: 2013
Frequency range	:	0.15 – 30MHz
Limits	:	FCC Part 15.207
Kind of test site	:	Shield room


Test setup

Input Voltage	:	AC 120V, 60Hz
Operation Mode	:	A.1, B.1, C.1, D.1
Earthing	:	Not Connected
Ambient temperature	:	24.2°C
Relative humidity	:	53%
Atmospheric pressure	:	101kPa

For details refer to following test plot.



No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Nantou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057




Site no :1# Conduction Data No :1
Dis./Lisn :2015 ESH2-Z5 LINE LISN phase:
Limit :FCC PART 15 C
Env./Ins. :24.2°C/53% Engineer :Evan
EUT :11.6" windows tablet M/N:NS-P11W7100
Power Rating :DC 5V From Adapter Input AC 120V/60Hz
Test Mode :TX Mode WIFI 5G(Band1)

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.154	0.12	0.02	44.17	44.31	65.78	21.47	QP
2	0.154	0.12	0.02	33.89	34.03	55.78	21.75	Average
3	0.198	0.12	0.02	30.16	30.30	53.72	23.42	Average
4	0.198	0.12	0.02	41.78	41.92	63.71	21.79	QP
5	0.350	0.13	0.02	39.27	39.42	58.96	19.54	QP
6	0.351	0.17	0.02	29.46	29.65	48.94	19.29	Average
7	0.451	0.43	0.03	28.47	28.93	46.85	17.92	Average
8	0.454	0.43	0.03	38.69	39.15	56.80	17.65	QP
9	0.595	0.14	0.04	28.11	28.29	46.00	17.71	Average
10	0.595	0.14	0.04	38.51	38.69	56.00	17.31	QP
11	0.671	0.15	0.04	26.31	26.50	46.00	19.50	Average
12	0.683	0.15	0.04	38.48	38.67	56.00	17.33	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
2.If the average limit is met when using a quasi-peak detector.
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.



No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Nantou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 2
File: E:\1#CE\2016 Report Data\TUV\TUV莱茵EM6 (14)
Date: 2016-07-07


Site no :1# Conduction Data No :2
Dis./Lisn :2015 ESH2-25 NEUTRAL LISN phase:
Limit :FCC PART 15 C
Env./Ins. :24.2°C/53% Engineer :Evan
EUT :11.6" windows tablet M/N:NS-P11W7100
Power Rating :DC 5V From Adapter Input AC 120V/60Hz
Test Mode :TX Mode WIFI 5G(Band1)

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.150	0.12	0.02	46.48	46.62	66.00	19.38	QP
2	0.150	0.12	0.02	35.14	35.28	55.98	20.70	Average
3	0.191	0.12	0.02	32.17	32.31	53.98	21.67	Average
4	0.198	0.12	0.02	42.55	42.69	63.71	21.02	QP
5	0.350	0.13	0.02	39.44	39.59	58.96	19.37	QP
6	0.352	0.13	0.02	28.15	28.30	48.92	20.62	Average
7	0.453	0.14	0.03	27.16	27.33	46.83	19.50	Average
8	0.454	0.14	0.03	38.73	38.90	56.80	17.90	QP
9	0.571	0.15	0.04	27.16	27.35	46.00	18.65	Average
10	0.585	0.15	0.04	37.63	37.82	56.00	18.18	QP
11	0.675	0.15	0.04	28.17	28.36	46.00	17.64	Average
12	0.679	0.15	0.04	39.79	39.98	56.00	16.02	QP


Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
2.If the average limit is met when using a quasi-peak detector.
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Nantou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 3

File: E:\1#CE\2016 Report Data\TUV\TUV莱茵测试\EM6 (14)

Date: 2016-07-07




Site no	:1# Conduction	Data No	:3
Dis./Lisn	:2015 ESH2-Z5 NEUTRAL	LISN phase:	
Limit	:FCC PART 15 C		
Env./Ins.	:24.2°C/53%	Engineer	:Evan
EUT	:11.6" windows tablet M/N:NS-P11W7100		
Power Rating	:DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	:TX Mode WIFI 5G(Band2)		

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.150	0.12	0.02	45.07	45.21	66.00	20.79	QP
2	0.152	0.12	0.02	35.17	35.31	55.86	20.55	Average
3	0.197	0.12	0.02	30.14	30.28	53.73	23.45	Average
4	0.198	0.12	0.02	41.65	41.79	63.71	21.92	QP
5	0.352	0.13	0.02	38.17	38.32	58.92	20.60	QP
6	0.352	0.13	0.02	27.17	27.32	48.92	21.60	Average
7	0.451	0.14	0.03	27.17	27.34	46.85	19.51	Average
8	0.454	0.14	0.03	37.88	38.05	56.80	18.75	QP
9	0.601	0.15	0.04	38.28	38.47	56.00	17.53	QP
10	0.601	0.15	0.04	27.16	27.35	46.00	18.65	Average
11	0.681	0.15	0.04	30.17	30.36	46.00	15.64	Average
12	0.683	0.15	0.04	40.29	40.48	56.00	15.52	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
 2.If the average limit is met when using a quasi-peak detector.
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Nantou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057



Site no :1# Conduction Data No :4
Dis./Lisn :2015 ESH2-Z5 LINE LISN phase:
Limit :FCC PART 15 C
Env./Ins. :24.2°C/53% Engineer :Evan
EUT :11.6" windows tablet M/N:NS-P11W7100
Power Rating :DC 5V From Adapter Input AC 120V/60Hz
Test Mode :TX Mode WIFI 5G(Band2)

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.150	0.12	0.02	44.84	44.98	66.00	21.02	QP
2	0.153	0.12	0.02	33.16	33.30	55.83	22.53	Average
3	0.190	0.12	0.02	31.02	31.16	54.03	22.87	Average
4	0.190	0.12	0.02	42.30	42.44	64.02	21.58	QP
5	0.332	0.13	0.02	28.17	28.32	49.41	21.09	Average
6	0.337	0.13	0.02	39.41	39.56	59.27	19.71	QP
7	0.381	0.56	0.03	27.16	27.75	48.25	20.50	Average
8	0.385	0.60	0.03	38.00	38.63	58.17	19.54	QP
9	0.451	0.43	0.03	28.16	28.62	46.85	18.23	Average
10	0.454	0.43	0.03	37.56	38.02	56.80	18.78	QP
11	0.671	0.15	0.04	28.46	28.65	46.00	17.35	Average
12	0.675	0.15	0.04	39.84	40.03	56.00	15.97	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
2.If the average limit is met when using a quasi-peak detector.
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Nantou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057



Site no :1# Conduction Data No :5
 Dis./Lisn :2015 ESH2-Z5 LINE LISN phase:
 Limit :FCC PART 15 C
 Env./Ins. :24.2°C/53% Engineer :Evan
 EUT :11.6" windows tablet M/N:NS-P11W7100
 Power Rating :DC 5V From Adapter Input AC 120V/60Hz
 Test Mode :TX Mode WIFI 5G(Band3)

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.153	0.12	0.02	35.17	35.31	55.81	20.50	Average
2	0.154	0.12	0.02	46.37	46.51	65.78	19.27	QP
3	0.190	0.12	0.02	30.17	30.31	54.04	23.73	Average
4	0.198	0.12	0.02	41.57	41.71	63.71	22.00	QP
5	0.340	0.13	0.02	38.47	38.62	49.20	10.58	Average
6	0.350	0.13	0.02	39.27	39.42	58.96	19.54	QP
7	0.451	0.43	0.03	27.49	27.95	46.85	18.90	Average
8	0.454	0.43	0.03	38.99	39.45	56.80	17.35	QP
9	0.590	0.14	0.04	27.14	27.32	46.00	18.68	Average
10	0.598	0.14	0.04	38.01	38.19	56.00	17.81	QP
11	0.671	0.15	0.04	28.16	28.35	46.00	17.65	Average
12	0.675	0.15	0.04	39.14	39.33	56.00	16.67	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
 2.If the average limit is met when using a quasi-peak detector.
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.



No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Nantou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057




Site no :1# Conduction Data No :6
Dis./Lisn :2015 ESH2-25 NEUTRAL LISN phase:
Limit :FCC PART 15 C
Env./Ins. :24.2°C/53% Engineer :Evan
EUT :11.6" windows tablet M/N:NS-P11W7100
Power Rating :DC 5V From Adapter Input AC 120V/60Hz
Test Mode :TX Mode WIFI 5G(Band3)

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.150	0.12	0.02	42.85	42.99	66.00	23.01	QP
2	0.151	0.12	0.02	33.17	33.31	55.93	22.62	Average
3	0.193	0.12	0.02	31.02	31.16	53.89	22.73	Average
4	0.194	0.12	0.02	42.89	43.03	63.84	20.81	QP
5	0.350	0.13	0.02	38.27	38.42	58.96	20.54	QP
6	0.352	0.13	0.02	27.17	27.32	48.92	21.60	Average
7	0.450	0.14	0.03	27.15	27.32	46.88	19.56	Average
8	0.459	0.14	0.03	38.32	38.49	56.71	18.22	QP
9	0.590	0.15	0.04	25.16	25.35	46.00	20.65	Average
10	0.595	0.15	0.04	36.65	36.84	56.00	19.16	QP
11	0.680	0.15	0.04	28.17	28.36	46.00	17.64	Average
12	0.686	0.15	0.04	39.32	39.51	56.00	16.49	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
2.If the average limit is met when using a quasi-peak detector.
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Nantou,ShenZhen,GuangDong,China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057



Site no :1# Conduction Data No :7
Dis./Lisn :2015 ESH2-25 NEUTRAL LISN phase:
Limit :FCC PART 15 C
Env./Ins. :24.2°C/53% Engineer :Evan
EUT :11.6" windows tablet M/N:NS-P11W7100
Power Rating :DC 5V From Adapter Input AC 120V/60Hz
Test Mode :TX Mode WIFI 5G(Band4)

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.153	0.12	0.02	35.17	35.31	55.83	20.52	Average
2	0.154	0.12	0.02	45.50	45.64	65.78	20.14	QP
3	0.193	0.12	0.02	30.17	30.31	53.89	23.58	Average
4	0.194	0.12	0.02	40.91	41.05	63.84	22.79	QP
5	0.330	0.13	0.02	37.17	37.32	49.45	12.13	Average
6	0.337	0.13	0.02	38.13	38.28	59.27	20.99	QP
7	0.441	0.14	0.03	37.16	37.33	47.04	9.71	Average
8	0.442	0.14	0.03	38.94	39.11	57.02	17.91	QP
9	0.595	0.15	0.04	38.89	39.08	56.00	16.92	QP
10	0.598	0.15	0.04	28.16	28.35	46.00	17.65	Average
11	0.671	0.15	0.04	27.50	27.69	46.00	18.31	Average
12	0.679	0.15	0.04	38.77	38.96	56.00	17.04	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
2.If the average limit is met when using a quasi-peak detector.
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.


 No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Nantou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057


Site no :1# Conduction Data No :8
 Dis./Lisn :2015 ESH2-Z5 LINE LISN phase:
 Limit :FCC PART 15 C
 Env./Ins. :24.2°C/53% Engineer :Evan
 EUT :11.6" windows tablet M/N:NS-P11W7100
 Power Rating :DC 5V From Adapter Input AC 120V/60Hz
 Test Mode :TX Mode WIFI 5G(Band4)

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.153	0.12	0.02	35.17	35.31	55.81	20.50	Average
2	0.154	0.12	0.02	46.73	46.87	65.78	18.91	QP
3	0.194	0.12	0.02	42.81	42.95	63.84	20.89	QP
4	0.195	0.12	0.02	33.17	33.31	53.84	20.53	Average
5	0.350	0.13	0.02	39.28	39.43	58.96	19.53	QP
6	0.352	0.17	0.02	28.66	28.85	48.92	20.07	Average
7	0.453	0.43	0.03	29.16	29.62	46.82	17.20	Average
8	0.454	0.43	0.03	39.40	39.86	56.80	16.94	QP
9	0.593	0.14	0.04	27.16	27.34	46.00	18.66	Average
10	0.598	0.14	0.04	37.38	37.56	56.00	18.44	QP
11	0.672	0.15	0.04	28.47	28.66	46.00	17.34	Average
12	0.675	0.15	0.04	39.45	39.64	56.00	16.36	QP


Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
 2.If the average limit is met when using a quasi-peak detector.
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

6. Photographs of the Test Set-Up

Photograph 1: Set-up for Conducted Emissions




Photograph 2: Set-up for Spurious Emissions for 30 - 1000MHz



Photograph 3: Set-up for Spurious Emissions for 1 - 18GHz



Photograph 4: Set-up for Dynamic Frequency Selection



7. List of Tables

Table 1: List of Test and Measurement Equipment.....	5
Table 2: Measurement Uncertainty	7
Table 3: Technical Specification of EUT	9
Table 4: Technical Specification of 5GHz, 802.11a/n.....	9
Table 5: Technical Specification of 5GHz, 802.11ac.....	10
Table 6: List of WLAN Channel of 5GHz 802.11a/n	10
Table 7: List of WLAN Channel of 5GHz 802.11ac	11
Table 8: Test result of Peak Output Power of Band U-NII-1	17
Table 9: Test result of Peak Output Power of Band U-NII-2A.....	18
Table 10: Test result of Peak Output Power of Band U-NII-2C.....	18
Table 11: Test result of Peak Output Power of Band U-NII-3	19
Table 12: Test result of 26dB Bandwidth Band U-NII-1.....	20
Table 13: Test result of 26dB Bandwidth of Band U-NII-2A.....	20
Table 14: Test result of 26dB Bandwidth of Band U-NII-2C	21
Table 15: Test result of 26dB Bandwidth of Band U-NII-3.....	21
Table 16: Test result of 99% Bandwidth Band U-NII-1	22
Table 17: Test result of 99% Bandwidth of Band U-NII-2A.....	22
Table 18: Test result of 99% Bandwidth of Band U-NII-2C.....	23
Table 19: Test result of 99% Bandwidth of Band U-NII-3	23
Table 20: Test result of 6dB Bandwidth Band U-NII-1.....	24
Table 21: Test result of 6dB Bandwidth of Band U-NII-2A.....	24
Table 22: Test result of 6dB Bandwidth of Band U-NII-2C	25
Table 23: Test result of 6dB Bandwidth of Band U-NII-3.....	25
Table 24: Test result of power spectral density of Band U-NII-1.....	26
Table 25: Test result of power spectral density of Band U-NII-2A	27
Table 26: Test result of power spectral density of Band U-NII-2C	27
Table 27: Test result of power spectral density of Band U-NII-3.....	28
Table 28: Test result of Dynamic Frequency Selection of 802.11ac VHT20, 5260MHz	455
Table 29: Test result of Dynamic Frequency Selection of 802.11ac VHT20, 5500MHz	457
Table 30: Test result of Dynamic Frequency Selection of 802.11ac VHT40, 5270MHz	459
Table 31: Test result of Dynamic Frequency Selection of 802.11ac VHT40, 5510MHz	461
Table 32: Test result of Dynamic Frequency Selection of 802.11ac VHT80, 5290MHz	463
Table 33: Test result of Dynamic Frequency Selection of 802.11ac VHT80, 5530MHz	465

Prüfbericht - Nr.: 50050527 010

Test Report No.

Seite 479 von 479

Page 479 of 479

8. List of Photographs

Photograph 1: Set-up for Conducted Emissions	476
Photograph 2: Set-up for Spurious Emissions for 30 - 1000MHz	476
Photograph 3: Set-up for Spurious Emissions for 1 - 18GHz	477
Photograph 4: Set-up for Dynamic Frequency Selection.....	477