



## FCC Test Report

**FCC ID: 2AIBY-AX3008T**

**Product:** Feature Phone

**Trade Name:** Artex

**Model Number:** AX3008T

**Serial Model:** AX3008S, AX3008R

**Report No.:** NTEK- 2016NT05045508F3

**Prepared for**

ARTEX COMPUTER LLC.

2874 NW 72 AVE, Miami FL 33122 USA

**Prepared by**

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street,  
Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599

Website: [www.ntek.org.cn](http://www.ntek.org.cn)

## TEST RESULT CERTIFICATION

**Applicant's name** ..... : Artex Computer LLC.

Address ..... : 2874 NW 72 AVE, Miami FL 33122 USA

**Manufacturer's Name** ..... : Shenzhen Topsky Digital Technology Limited

Address ..... : 6/F, B6 Building, Hengfeng Industry Park, Xixiang, Bao'an District, Shenzhen, China

### Product description

Product name ..... : Feature Phone

Model and/or type reference : AX3008T

FCC Part15B:01 Oct.2016

**Standards** ..... : ANSI C63.4:2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with Part 15 of FCC Rules. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

**Date of Test** ..... :

Date (s) of performance of tests ..... : 04 May. 2016 ~ 23 May. 2016

Date of Issue ..... : 23 May. 2016


Test Result ..... : **Pass**

Testing Engineer : 

(Jack Li)

Technical Manager : 

(Jason Chen)

Authorized Signatory : 

(Sam Chen)

Table of Contents	Page
1 . TEST SUMMARY	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST SETUP	8
2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	9
2.4 MEASUREMENT INSTRUMENTS LIST	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION	11
3.1.2 TEST PROCEDURE	12
3.1.3 TEST SETUP	12
3.1.4 EUT OPERATING CONDITIONS	12
3.1.5 TEST RESULTS	13
3.2 RADIATED EMISSION MEASUREMENT	15
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	15
3.2.2 TEST PROCEDURE	15
3.2.3 TEST SETUP	16
3.2.4 TEST RESULTS	16
3.2.5 TEST RESULTS(1000~12400MHz)	19
4 . EUT TEST PHOTO	20

**1. TEST SUMMARY**

Test procedures according to the technical standards:

<b>EMC Emission</b>				
Standard	Test Item	Limit	Judgment	Remark
FCC Part15B:2014 ANSI C63.4: 2014	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.

### 1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration Number:238937; IC Registration Number:9270A-1

CNAS Registration Number:L5516

### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
NTEKC01	ANSI	150 KHz ~ 30MHz	3.2	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
NTEKA01	ANSI	30MHz ~ 1000MHz	4.7	
		1GHz ~12.4GHz	5.0	

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Feature Phone						
Trade Name	Artex						
Model Name	AX3008T						
Serial Model	AX3008S, AX3008R						
Model Difference	All the model are the same circuit and RF module, except the model No. and colour.						
Product Description	<p>The EUT is a Feature Phone.</p> <table border="1"><tr><td>Connecting I/O port:</td><td>USB, DC in</td></tr><tr><td>Operation Frequency:</td><td>BT:2402~2480 MHz GSM: 824.2-848.8MHz/1850.2-1909.8MHz</td></tr><tr><td>Modulation Type:</td><td>BT(1Mbps): GFSK BT EDR(2Mbps): <math>\pi/4</math>-DQPSK BT EDR(3Mbps): 8-DPSK GSM / DCS: GMSK</td></tr></table>	Connecting I/O port:	USB, DC in	Operation Frequency:	BT:2402~2480 MHz GSM: 824.2-848.8MHz/1850.2-1909.8MHz	Modulation Type:	BT(1Mbps): GFSK BT EDR(2Mbps): $\pi/4$ -DQPSK BT EDR(3Mbps): 8-DPSK GSM / DCS: GMSK
Connecting I/O port:	USB, DC in						
Operation Frequency:	BT:2402~2480 MHz GSM: 824.2-848.8MHz/1850.2-1909.8MHz						
Modulation Type:	BT(1Mbps): GFSK BT EDR(2Mbps): $\pi/4$ -DQPSK BT EDR(3Mbps): 8-DPSK GSM / DCS: GMSK						
Power Source	DC Voltage						
Adapter	Model: AX3008T Input: 90-260V~, 50/60Hz, 0.1A Output: 5.0V---, 500mA						
Battery	DC 3.7V/600mAh						

### 2.1.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Pretest Mode	Description
Mode 1	Connect to PC
Mode 2	REC
Mode 3	BT
Mode 4	GPS
Mode 5	GSM

For Conducted Test	
Final Test Mode	Description
Mode 1	Connect to PC
Mode 2	REC
Mode 3	BT
Mode 4	GPS
Mode 5	GSM


For Radiated Test	
Final Test Mode	Description
Mode 1	Connect to PC
Mode 2	REC
Mode 3	BT
Mode 4	GPS
Mode 5	GSM

Note: Final Test Mode: Through Pre-scan, find the mode 1 is the worst case.  
Only the worst case mode is recorded in the report.

## 2.2 DESCRIPTION OF TEST SETUP



CE



### 2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Feature Phone	Artex	AX3008T	N/A	EUT
E-2	Printer	Canon	L11121E	LBP2900	
E-3	Earphone	N/A	L662	N/A	Peripherals
E-4	Personal computer	DELL	FT4Y23X	34413561645	PC
E-5	Monitor	DELL	IN2020MB	cn-0y6mhx-74261-11f-67es	
E-6	Mouse	DELL	MS111-P	cn-011d3v-71581-11e-1th7	
E-7	Keyboard	DELL	SK-8185	OY526KUS	

Item	Cable Type	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable	unshielded	NO	1.0m	
C-2	Earphone	unshielded	NO	0.8m	
C-3	USB Cable	unshielded	NO	1.5m	
C-4	USB Cable	unshielded	NO	1.5m	
C-5	USB Cable	unshielded	NO	1.0m	
C-6	Power Line	unshielded	NO	1.2m	
C-7	Power Line	unshielded	NO	1.2m	
C-8	Power Line	unshielded	NO	1.2m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" means "shielded" "with core"; "NO" means "unshielded" "without core".

## 2.4 MEASUREMENT INSTRUMENTS LIST

### Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2015.07.06	2016.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2015.06.07	2016.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2015.07.06	2016.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.07	2016.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.07	2016.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2015.07.06	2016.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2015.07.06	2016.07.05	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2015.07.06	2016.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2015.07.06	2016.07.05	1 year
12	Test Cable	N/A	R-01	N/A	2015.07.06	2016.07.05	1 year
13	Test Cable	N/A	R-02	N/A	2015.07.06	2016.07.05	1 year

### Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2015.06.06	2016.06.05	1 year
2	LISN	R&S	ENV216	101313	2015.08.24	2016.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2015.08.24	2016.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.07	2016.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2015.06.07	2016.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2015.06.08	2016.06.07	1 year
7	Test Cable	N/A	C01	N/A	2015.06.08	2016.06.07	1 year
8	Test Cable	N/A	C02	N/A	2015.06.08	2016.06.07	1 year
9	Test Cable	N/A	C03	N/A	2015.06.08	2016.06.07	1 year

### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 TEST SETUP



**Note: 1. Support units were connected to second LISN.**


**2. Both of LISNs (AMH) are 80 cm from EUT and at least 80 cm from other units and other metal planes**

### 3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **2.3** Unless otherwise a special operating condition is specified in the follows during the testing.

## 3.1.5 TEST RESULTS

EUT:	Feature Phone	Model Name. :	AX3008T- Adapter1
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2016-5-23
Test Mode:	Mode 1	Phase :	L
Test Voltage:	DC 5V From PC AC 120V/60Hz		




Site: **L1** Temperature: 22  
 Limit: FCC Part 15B\_(0.15-30MHz) \_Main\_QP Power: AC 230V/50Hz Humidity: 51 %  
 Mode: PC  
 Note:

No.	Mk.	Freq. MHz	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level dBuV	Factor dB	ment dBuV				
1		0.2300	31.35	10.13	41.48	62.45	-20.97	QP	
2		0.2300	17.78	10.13	27.91	52.45	-24.54	AVG	
3		0.5620	37.86	9.79	47.65	56.00	-8.35	QP	
4		0.5620	19.85	9.79	29.64	46.00	-16.36	AVG	
5		0.7140	37.30	9.78	47.08	56.00	-8.92	QP	
6		0.7140	22.08	9.78	31.86	46.00	-14.14	AVG	
7	*	1.0140	38.44	9.85	48.29	56.00	-7.71	QP	
8		1.0140	21.44	9.85	31.29	46.00	-14.71	AVG	
9		1.4819	35.32	9.79	45.11	56.00	-10.89	QP	
10		1.4819	23.58	9.79	33.37	46.00	-12.63	AVG	
11		4.2259	36.20	9.75	45.95	56.00	-10.05	QP	
12		4.2259	24.99	9.75	34.74	46.00	-11.26	AVG	

\*:Maximum data    x:Over limit    !:over margin

EUT:	Feature Phone	Model Name. :	AX3008T- Adapter1
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2016-5-23
Test Mode:	Mode 1	Phase :	N
Test Voltage:	DC 5V From PC AC 120V/60Hz		



Site Phase: **N** Temperature: 22

Limit: FCC Part 15B\_(0.15-30MHz) \_Main\_QP Power: AC 230V/50Hz Humidity: 51 %

Mode: PC

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.2300	33.65	10.13	43.78	62.45	-18.67	QP	
2		0.2300	20.27	10.13	30.40	52.45	-22.05	AVG	
3		0.3580	34.52	10.08	44.60	58.77	-14.17	QP	
4		0.3580	19.47	10.08	29.55	48.77	-19.22	AVG	
5	*	0.5299	41.47	9.80	51.27	56.00	-4.73	QP	
6		0.5299	20.94	9.80	30.74	46.00	-15.26	AVG	
7		0.7180	39.75	9.78	49.53	56.00	-6.47	QP	
8		0.7180	23.27	9.78	33.05	46.00	-12.95	AVG	
9		1.0339	38.92	9.85	48.77	56.00	-7.23	QP	
10		1.0339	22.17	9.85	32.02	46.00	-13.98	AVG	
11		4.2538	35.91	9.75	45.66	56.00	-10.34	QP	
12		4.2538	25.72	9.75	35.47	46.00	-10.53	AVG	

\*:Maximum data    x:Over limit    !:over margin

### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 3m)
	dBuV/m	dBuV/m
30 ~ 88	39.0	40.0
88 ~ 216	43.5	43.5
216 ~ 960	46.5	46.0
Above 960	49.5	54.0

Notes:

- (1) The limit for radiated test was performed according to as following:  
FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

#### 3.2.2 TEST PROCEDURE

##### Test Arrangement for Radiated Emissions up to 1 GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency below 1GHz.

##### Test Arrangement for Radiated Emissions above 1 GHz.

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.


Note: For the hand-held device, the EUT should be measured for all 3 axes and only the worst case is recorded in the report

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Avg	1 MHz	10 Hz

### 3.2.3 TEST SETUP

For Radiated Emission 30~1000MHz




(B) Radiated Emission Test Set-Up Frequency Above 1GHz



### 3.2.4 TEST RESULTS

TEST RESULTS (30~1000 MHz)


EUT:	Feature Phone	Model Name:	AX3008T
Temperature:	24 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2016-5-23
Test Mode :	Mode 1	Polarization :	Horizontal
Test Power :	DC 5V From PC AC 120V/60Hz		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1		30.1053	6.55	19.53	26.08	40.00	-13.92	QP		
2		177.5092	22.48	12.11	34.59	43.50	-8.91	QP		
3	*	207.8501	24.65	11.26	35.91	43.50	-7.59	QP		
4		348.0274	21.49	14.07	35.56	46.00	-10.44	QP		
5		408.9460	21.73	11.72	36.15	46.00	9.55	QP		
6		665.8035	17.17	20.77	37.94	46.00	-8.06	QP		

\*:Maximum data    x:Over limit    !:over margin

EUT:	Feature Phone	Model Name :	AX3008T
Temperature:	24 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2016-5-23
Test Mode :	Mode 1	Polarization :	Vertical
Test Power :	DC 5V From PC AC 120V/60Hz		



Site Polarization: **Vertical** Temperature: 24

Limit: FCC\_PART15\_B\_03m\_QP Power: AC 120V/60Hz Humidity: 50 %

Mode: PC

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit		Over	Antenna Height	Table Degree					
						MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		37.4164	13.20	16.09	29.37	40.00	40.00	-10.63	QP						
2		62.2128	21.51	5.81	27.32	40.00	40.00	-12.68	QP						
3		125.0066	24.17	10.66	34.83	43.50	43.50	-8.67	QP						
4	*	143.8295	25.07	11.22	36.29	43.50	43.50	-7.21	QP						
5		204.2376	20.99	11.56	32.55	43.50	43.50	-10.95	QP						
6		665.8034	17.01	20.77	37.78	46.00	46.00	-8.22	QP						

\*:Maximum data    x:Over limit    !:over margin

## 3.2.5 TEST RESULTS

EUT:	Feature Phone	Model Name :	AX3008T
Temperature:	24 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2016-5-23
Test Mode :	Mode 1	Polarization :	Vertical
Test Power :	DC 5V From PC AC 120V/60Hz		

The Testing have been conformed to  $5 \times 2480\text{MHz} = 12400\text{MHz}$ , and the worst result was report as below:

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	3505.33	46.81	-4.80	42.01	74.00	-31.99	peak
V	3505.33	33.95	-4.80	29.15	54.00	-24.85	AVG
V	4874.18	44.33	1.57	45.90	74.00	-28.10	peak
V	4874.18	32.06	1.57	33.63	54.00	-20.37	AVG
H	3165.02	46.10	-6.00	40.10	74.00	-33.90	peak
H	3165.02	33.02	-6.00	27.02	54.00	-26.98	AVG
H	4865.46	44.51	1.52	46.03	74.00	-27.97	peak
H	4865.46	31.64	1.52	33.16	54.00	-20.84	AVG

**Remark:**

Note: (1) All other emissions more than 20dB below the limit.  
 (2) Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level – Limit

**4. EUT TEST PHOTO****Radiated Measurement Photos**

**Conducted Measurement Photos**