

FCC RADIO TEST REPORT FCC ID: 2AIC3BATC-001

Product: dog training collar

Trade Name: BOSHEL

Model Name: BATC-001

Serial Model: BATC-002, BATC-003, BATC-004

Report No.: POCE-1605248115F

Prepared for

BOSHEL

99 forest rd. #201b, Monroe, New York, USA, 10950

Prepared by

Shenzhen POCE Technology Co.,Ltd.

Room 502, Bldg. 1, Xinghua Garden, Baoan Road Xixiang,
Baoan District,Shenzhen, China



TEST RESULT CERTIFICATION

Report No.: POCE-1605248115F

Applicant's name:	BOSHEL
Address:	99 forest rd. #201b, Monroe, New York, USA, 10950
Manufacture's Name:	
Address:	99 forest rd. #201b, Monroe, New York, USA, 10950
Product description	
Product name:	dog training collar
Model and/or type reference :	BATC-001
Serial Model:	BATC-002, BATC-003 , BATC-004
Standards:	FCC Part15.231a
Test procedure	ANSI C63.10: 2013
	is been tested by POCE, and the test results show that the n compliance with the FCC requirements. And it is applicable only in the report.
document may be altered or rev	ced except in full, without the written approval of POCE, this rised by POCE, personal only, and shall be noted in the revision of
Date of Test	
Date (s) of performance of tests	
Date of Issue	7 May 2016
Test Result	Pass
Testing Engine	eer : Ken Ci (Ken Li)
Technical Man	(Jimmy Yao)
Authorized Sig	gnatory:



Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2. GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTER	D 8
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
3 . ANTENNA REQUIREMENT	11
3.1 STANDARD REQUIREMENT	11
3.2 EUT ANTENNA	11
3.3 CONDUCTED EMISSION MEASUREMENT	12
3.3.1 POWER LINE CONDUCTED EMISSION LIMITS	12
3.3.2 TEST PROCEDURE 3.3.3 DEVIATION FROM TEST STANDARD	13 13
3.3.4 TEST SETUP	13 13
3.2.5 TEST RESULT	14
3.4 RADIATED EMISSION MEASUREMENT	15
3.4.1 RADIATED EMISSION LIMITS	15
3.4.2 TEST PROCEDURE	16
3.4.3 DEVIATION FROM TEST STANDARD	16 46
3.4.4 TEST SETUP 3.4.5 TEST RESULTS (BLOW 30MHZ)	16 18
3.4.6 TEST RESULTS (BETWEEN 30 – 1000 MHZ)	19
4 . BANDWIDTH TEST	23
4.1 TEST PROCEDURE	23
4.2 DEVIATION FROM STANDARD	23
4.3 TEST SETUP	23
4.4 TEST RESULTS	24
5 . PERIODIC RATE EXCEEDING	25
5.1 REQUIREMENTS	25
5.2 TEST PROCEDURE	25
5.3 TEST SETUP 5.4 TEST RESULTS	25 25
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	2 5



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15, Subpart C (15.231)					
Standard Section	Test Item Judgment Remark				
15.207	Conducted Emission	N/A	Note(1)		
15.203	Antenna Requirement	Pass			
15.231	Radiated Spurious Emission	Pass			
15.231	Occupied Bandwidth	Pass			
15.231	Deactivation Time	Pass			

NI	\cap	т		
IV	$\mathbf{\mathcal{C}}$		ᆮ	

(1) " N/A" denotes test is not applicable in this Test Report.



1.1 TEST FACILITY

Shenzhen POCE Technology Co.,Ltd.

Add.: Room 502, Bldg. 1, Xinghua Garden, Baoan Road Xixiang, Baoan District, Shenzhen,

China

FCC-Registration No.: 222278

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 % \circ

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	dog training collar			
Trade Name	BOSHEL			
Model Name	BATC-001			
Serial Model	BATC-002, BATC-003,	BATC-004		
Model Difference	Only model name is diff	ferent.		
Product Description	Only model name is different. The EUT is a dog training collar Product Type Remote Control Operation Frequency: 433.92MHz Modulation Type: FSK Number Of Channel 1CH. Antenna Designation: Built-in wire antenna Antenna Gain(Peak) 0.8dBi Output Power: 68.94 dBuV/m @3m(AV Max.) Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as a ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.			
Channel List	N/A			
Adapter	N/A			
Battery	DC 3.7V,500mAH			

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	Built-in wire antenna	NA	0.8	Antenna



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX

For Conducted Emission		
Final Test Mode	Description	
Mode 1	N/A	

For Radiated Emission		
Final Test Mode	Description	
Mode 1	TX	

Note:

(1) The EUT use new battery.



POCE Technology	Page 8 of 26	Report No.: POCE-1605248115F
2.3 BLOCK DIGRAM	M SHOWING THE CONFIGURATION	N OF SYSTEM TESTED
Radiated Spurious Er	mission Test	
	E-1 EUT	



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	dog training collar	BOSHEL	BATC-001	YT-890,YT-900	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1)
- The support equipment was authorized by Declaration of Confirmation. For detachable type I/O cable should be specified the length in cm in ${}^{\mathbb{F}}$ Length ${}_{\mathbb{F}}$ column. (2)



2.4.1EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

	tadiation root oculpment					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until	
1	Spectrum Analyzer	Agilent	E4407B	160400005	Jul. 06. 2016	
2	Test Receiver	R&S	ESPI	101318	Jul. 06. 2016	
3	Bilog Antenna	TESEQ	CBL6111D	31216	Jul. 06. 2016	
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	Jul. 06. 2016	
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	Jul. 06. 2016	
6	Horn Antenna	EM	EM-AH-10180	2011071402	Jul. 06. 2016	
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	Jul. 06. 2016	
8	Amplifier	EM	EM-30180	060538	Jul. 06. 2016	
9	Loop Antenna	ARA	PLA-1030/B	1029	Jul. 06. 2016	
10	Power Meter	R&S	NRVS	100696	Jul. 06. 2016	

Conduction Test equipment

COIL	Conduction rest equipment							
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until			
1	Test Receiver	R&S	ESCI	101160	Jul. 06. 2016			
2	LISN	R&S	ENV216	101313	Jul. 06. 2016			
3	LISN	EMCO	3816/2	00042990	Jul. 06. 2016			
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	Jul. 06. 2016			
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	Jul. 06. 2016			
6	Absorbing clamp	R&S	MOS-21	100423	Jul. 06. 2016			



3. ANTENNA REQUIREMENT

3.1 STANDARD REQUIREMENT

15.203 requirements: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

3.2 EUT ANTENNA



3.3 CONDUCTED EMISSION MEASUREMENT

3.3.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting	
Attenuation	10 dB	
Start Frequency	0.15 MHz	
Stop Frequency	30 MHz	
IF Bandwidth	9 kHz	




3.3.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes





3.2.5 TEST RESULT

EUT:	dog training collar	Model Name. :	BATC-001
Temperature :	26 ℃	Relative Humidity:	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	N/A	Test Mode:	N/A

Owing to the EUT use battery supply voltage, this test item is not performed.

•



3.4 RADIATED EMISSION MEASUREMENT

3.4.1 Radiated Emission Limits (FCC 15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.231a)

Fundamental Frequency (MHz)	Field Strength of fundamental (microvolts/meter)	Field Strength of Unwanted Emissions (microvolts/meter)
40.66 - 40.70	2.250	225
70 - 130	1250	125
130 - 174	1250 to 3750	125 to 375
174 - 260	3750	375
260 - 470	3750-12500	375 to 1250
Above 470	12500	1250

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, μV/m at 3 meters = 56.81818(F) - 6136.3636; for the band 260-470 MHz, μ V/m at 3 meters = 41.6667(F) - 41.6667(F)7083.3333. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak



Receiver ParameterSettingAttenuationAutoStart ~ Stop Frequency9kHz~150kHz / RB 200Hz for QPStart ~ Stop Frequency150kHz~30MHz / RB 9kHz for QPStart ~ Stop Frequency30MHz~1000MHz / RB 120kHz for QP

Report No.: POCE-1605248115F

3.4.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than AV Mode Limit, the EUT shall be deemed to meet AV Limits and then no additional AV Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos. Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.4.3 DEVIATION FROM TEST STANDARD

No deviation


3.4.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz






(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz





3.4.5 TEST RESULTS (BLOW 30MHz)

EUT:	dog training collar	Model Name. :	BATC-001
Temperature :	20 ℃	Relative Humidtity:	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX	Polarization :	

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				PASS
				PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =40 log (specific distance/test distance)(dB); Limit line = specific limits(dBuv) + distance extrapolation factor.



3.4.6 TEST RESULTS (BETWEEN 30 - 1000 MHZ)

The duty cycle is simply the on time divided by the period:


The duration of one cycle = 73.5ms

On time of one signal=0.425ms,

DC = 0.425ms*37/73.5= 0.214

Therefore, the average factor is found by 20log0.214 = -13.39dB

The duration of one cycle



On time and off time of one signal






Radiated spurious emission(30M-1GHz)

EUT:	dog training collar	Model Name :	BATC-001
Temperature :		Relative Humidity:	
Pressure :	1010 hPa	Test Voltage :	DC 5.0V
Test Mode :	TX	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Datastas Tura
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Detector Type
99.8777	49.60	-16.49	33.11	43.50	-10.39	QP
279.0436	37.32	-13.13	24.19	46.00	-21.81	QP
433.9200	71.60	-9.37	62.23	100.80	-38.57	PK
520.8882	33.99	-7.81	26.18	46.00	-19.82	QP
867.8400	51.55	-2.05	49.50	80.80	-31.30	PK
896.9965	38.54	-1.52	37.02	46.00	-8.98	QP

Remark:

Factor = Antenna Factor + Correct Factor. Correct Factor= Cable Loss – Pre-amplifier






EUT: dog training collar Model Name: BATC-001
Temperature: 20 °C Relative Humidity: 48%
Pressure: 1010 hPa Test Voltage: DC 5.0V
Test Mode: Mode 2 Polarization: Vertical

Report No.: POCE-1605248115F

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Datastas Tura
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Detector Type
99.8777	40.44	-16.49	23.95	43.50	-19.55	QP
239.9874	38.99	-14.49	24.50	46.00	-21.50	QP
279.0436	35.79	-13.13	22.66	46.00	-23.34	QP
433.9200	71.36	-9.37	61.99	100.80	-38.81	PK
867.8400	48.73	-1.85	46.88	80.80	-33.92	PK
896.9964	43.75	-1.48	42.27	46.00	-3.73	QP

Remark:

Factor = Antenna Factor + Correct Factor. Correct Factor= Cable Loss – Pre-amplifier





Radiated spurious emission(1G-10thharmonics)

EUT:	dog training collar	Model Name :	BATC-001
Temperature :	20 ℃	Relative Humidity:	48%
Pressure :	1010 hPa	Test Voltage :	DC 5.0V
Test Mode :	TX	Polarization :	Horizontal

Frequency	Average Factor	Field Strength	Field Strength	Limit(PK)	Limit(AV)	State
MHz	dB	dBuV/m (PK)	dBuV/m (AV)	dBuV/m	dBuV/m	State
433.920	-13.39	62.23	48.84	100.82	80.82	pass
867.84	-13.39	49.50	36.11	80.82	60.82	pass
1737.500	-13.39	52.77	1	74.00	54.00	pass
2175.000	-13.39	48.23		80.82	60.82	pass
				74.00	54.00	pass
				74.00	54.00	pass

EUT:	dog training collar	Model Name :	BATC-001
Temperature :	20 ℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5.0V
Test Mode :	TX	Polarization :	Vertical

Frequency	Average Factor	Field Strength	Field Strength	Limit(PK)	Limit(AV)	State
MHz	dB	dBuV/m (PK)	dBuV/m (AV)	dBuV/m	dBuV/m	State
433.920	-13.39	61.99	48.60	100.82	80.82	pass
867.84	-13.39	46.88	33.49	80.82	60.82	pass
1737.500	-13.39	45.84		74.00	54.00	pass
2175.000	-13.39	52.33		80.82	60.82	pass
				74.00	54.00	pass
				74.00	54.00	pass

Note:

- 1. Emissions attenuated more than 20 dB below the permissible value are not reported.
- 2. *: Denotes restricted band of operation.

Measurements were made using a peak detector and average detector. Any emission falling within the restricted bands of FCC Part 15 Section 15.205 were compliance with the emission limit of FCC Part 15 Section 15.209.

3. FCC Limit for Average Measurement = 41.6667(433.92) – 7083.3333 = 10996.68uV/m = 80.82dBuV/m



4.PK Field Strength -Average factor =AV Field Strength

4. BANDWIDTH TEST

4.1 TEST PROCEDURE

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Limit: 433.92MHz*0.25%=1.08MHz

4.2 DEVIATION FROM STANDARD

No deviation.

4.3 TEST SETUP


EUT	SPECTRUM
	ANALYZER



4.4 TEST RESULTS

EUT:	dog training collar	Model Name :	BATC-001
Temperature :	26 ℃	Relative Humidity:	53%
Pressure :	1020 hPa	Test Power :	DC 3.7V
Test Mode :	TX CH 1		

Test Channel	Frequency	20 dBc Bandwidth	Limit
root orialinoi	(MHz)	(MHz)	(MHz)
CH01	433.92	0.203	1.08





5. PERIODIC RATE EXCEEDING

5.1 REQUIREMENTS

According to FCC 15.231(a) requirement:

- (1)A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released
- (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- (3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.

5.2 TEST PROCEDURE

- (1) Connect the EUT to the Spectrum and Power on.
- (2) Set center frequency of spectrum analyzer = operating frequency.
- (3) Set the spectrum analyzer as RBW=100kHz, VBW=100kHz, Span=0Hz, Adjust Sweep=130s.
- (4) Record the duration time

5.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER


5.4 TEST RESULTS

EUT:	dog training collar	Model Name :	BATC-001
Temperature :	26 ℃	Relative Humidity:	53%
Pressure :	1020 hPa	Test Power :	DC 3.7V
Test Mode :	TX		

Frequency(MHz)	Transmission time(s)
433.92	300ms
Limit	5s
Result	Pass

.





According to FCC 15.231(a) requirement:

- (1)A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released OK, see Above test result.
- (2)A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- OK, see Above test result.
- (3)Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individua transmissions, provided the total transmission time does not exceed two seconds per hour.

OK, not exceed more than two seconds per hour for each transmitter