

No.10 Weiye Rd., Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China

Telephone: 86-512-57355888 Fax: 86-512-57370818 Mail: sgs.china@sgs.com Report No.: CKSEM190700022901

Rev : 01 Page : 1 of 63

# FCC SAR TEST REPORT

Application No: CKSEM1907000229CR

Applicant:Shenzhen Zero Zero Infinity Technology Co.,LtdManufacturer:DONGGUAN LITE STAR INDUSTRY COL.,TDFactory:DONGGUAN LITE STAR INDUSTRY COL.,TD

Product Name: Remote controller

Model No.(EUT): ZR-100A

Trade Mark: ZEROZERO ROBOTICS

FCC ID: 2AIDWZR-100A

Standards: FCC 47CFR §2.1093

**Date of Receipt:** 2019-07-01

**Date of Test:** 2019-07-10 to 2019-07-12

Date of Issue: 2019-07-17
Test conclusion: PASS \*

\* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:

Ina fin

Eric Lin

### Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300

中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300

Member of the SGS Group (SGS SA)

f(86-512)57370818 www.sgsgroup.com.cn

f(86-512)57370818 sgs.china@sgs.com

t(86-512)57355888

t(86-512)57355888



Report No.: CKSEM190700022901

Rev : 01 Page : 2 of 63

# **REVISION HISTORY**

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2019-07-17		Original

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300  $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$ 



Report No.: CKSEM190700022901

Rev : 01 Page : 3 of 63

# **TEST SUMMARY**

Frequency Band	Maximum Reported SAR(W/kg)		
. roquono, zuna	Body (1-g)	Extremity (10-g)	
WI-FI (2.4GHz)	0.57	0.47	
WI-FI (5GHz)	0.40	1.16	
SAR Limited(W/kg)	1.6	4	
Maximum Simultaneous Transmission SAR (W/kg)			
Scenario	Body (1-g)	Extremity (10-g)	
Sum SAR	0.97	2.16	
SAR Limited(W/kg)	1.6	4	

Approved & Released by

En fin

Eric Lin

**SAR Manager** 

**Tested by** 

Richard Kong

Richard. Kong

SAR Engineer



Report No.: CKSEM190700022901

Rev : 01 Page : 4 of 63

# **CONTENTS**

1	GEN	IERAL INFORMATION	6
	1.1	DETAILS OF CLIENT	6
	1.2	TEST LOCATION	6
	1.3	TEST FACILITY	7
	1.4	GENERAL DESCRIPTION OF EUT	8
	1.4.1	DUT Antenna Locations(Back View)	9
	1.5	TEST SPECIFICATION	10
	1.6	RF EXPOSURE LIMITS	11
2	LAB	ORATORY ENVIRONMENT	12
3	SAR	MEASUREMENTS SYSTEM CONFIGURATION	13
	3.1	THE SAR MEASUREMENT SYSTEM	13
	3.2	ISOTROPIC E-FIELD PROBE EX3DV4	14
	3.3	DATA ACQUISITION ELECTRONICS (DAE)	15
	3.4	SAM TWIN PHANTOM	15
	3.5	ELI PHANTOM	16
	3.6	DEVICE HOLDER FOR TRANSMITTERS	17
	3.7	MEASUREMENT PROCEDURE	18
	3.7.1	Scanning procedure	18
	3.7.2	•	
	3.7.3	B Data Evaluation by SEMCAD	20
4	SAR	MEASUREMENT VARIABILITY AND UNCERTAINTY	22
	4.1	SAR MEASUREMENT VARIABILITY	22
	4.2	SAR MEASUREMENT UNCERTAINTY	22
5	DES	CRIPTION OF TEST POSITION	23
	5.1	BODY EXPOSURE CONDITION	23
	5.1.1	Body-worn accessory exposure conditions	23
	5.1.2	2 Extremity exposure conditions	24
6	SAR	SYSTEM VERIFICATION PROCEDURE	25
	6.1	TISSUE SIMULATE LIQUID	25
	6.1.1	Recipes for Tissue Simulate Liquid	25
	6.1.2	P Test Liquids Confirmation	26
	6.1.3	Measurement for Tissue Simulate Liquid	27



Report No.: CKSEM190700022901

Rev : 01 Page : 5 of 63

(	6.2	SAR System Check	28
	6.2.1	Justification for Extended SAR Dipole Calibrations	29
	6.2.2	Summary System Check Result(s)	30
	6.2.3	Detailed System Check Results	30
7	TEST	CONFIGURATION	31
7	7.1	OPERATION CONFIGURATIONS	31
	7.1.1	WiFi Test Configuration	31
8	TEST	RESULT	36
8	3.1	MEASUREMENT OF RF CONDUCTED POWER	36
	8.1.1	Conducted Power Of WIFI	36
8	3.2	STAND-ALONE SAR TEST EVALUATION	38
8	3.3	MEASUREMENT OF SAR DATA	40
	8.3.1	SAR Result Of 2.4GHz WIFI	40
	8.3.2	SAR Result Of 5GHz WIFI	41
8	3.4	MULTIPLE TRANSMITTER EVALUATION	43
	8.4.1	Estimated SAR	43
	8.4.2	Simultaneous SAR test evaluation	43
9	EQUI	PMENT LIST	45
ΑP	PENDIX	( A: DETAILED SYSTEM CHECK RESULTS	46
ΑP	PENDIX	( B: DETAILED TEST RESULTS	50
ΑP	PENDIX	C: CALIBRATION CERTIFICATE	63
ΑP	PENDIX	( D: PHOTOGRAPHS	63



Report No.: CKSEM190700022901

Rev : 01 Page : 6 of 63

# 1 General Information

### 1.1 Details of Client

Applicant:	Shenzhen Zero Zero Infinity Technology Co.,Ltd
Address:	Room A211-B, F2, Shanshui Building, No.4093, Liuxian Avenue, Nanshan District, Shenzhen, Guangdong, China
Manufacturer:	DONGGUAN LITE STAR INDUSTRY COL.,TD
Address:	Xingchen Science.&Technology. Park,Lianbi Road.,Wulian Industry. Area, Fenggang Town, Dongguan, China
Factory:	DONGGUAN LITE STAR INDUSTRY COL.,TD
Address:	Xingchen Science.&Technology. Park,Lianbi Road.,Wulian Industry. Area, Fenggang Town, Dongguan, China

### 1.2 Test Location

Company: Compliance Certification Services Inc. Kun shan Laboratory

Address: No.10 Weiye Rd., Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu,

China

Post code: 215300

 Telephone:
 86-512-57355888

 Fax:
 86-512-57370818

 E-mail:
 sgs.china@sgs.com



Report No.: CKSEM190700022901

Rev : 01 Page : 7 of 63

# 1.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### • CNAS (No. CNAS L4354)

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### A2LA (Certificate No. 2541.01)

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

#### • FCC -Designation Number: CN1172

Compliance Certification Services Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172. Test Firm Registration Number: 995260.

### • Industry Canada (IC) - IC Assigned Code: 2324E CAB ID: CN0072

The 10m and 3m Semi-anechoic chamber of Compliance Certification Services (Kunshan) Inc. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 2324E-1 for 10m chamber, 2324E-2 for 3m chamber.

### • VCCI (Member No.: 1938)

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1600, C-1707, T-1499, G-216 respectively.

Member of the SGS Group (SGS SA)



Report No.: CKSEM190700022901

Rev : 01 Page : 8 of 63

# 1.4 General Description of EUT

Device Type :	portable device	portable device		
Exposure Category:	uncontrolled environme	uncontrolled environment / general population		
Product Name:	Remote controller			
Model No.(EUT):	ZR-100A			
FCC ID:	2AIDWZR-100A			
Trade Mark:	ZEROZERO ROBOTIO	S		
Product Phase:	production unit			
IMEI / SN:	NA	NA		
Hardware Version:	B2	B2		
Software Version:	1.0.5	1.0.5		
Antenna Type:	PIFA Antenna	PIFA Antenna		
Device Operating Configur	ations:			
Modulation Mode:	WIFI: DSSS; OFDM;	WIFI: DSSS; OFDM;		
Device Class:	В			
	Band	Tx (MHz)	Rx (MHz)	
Frequency Bands:	WIFI 2.4G	2412~2462	2412~2462	
rrequeries barias.	WIFI5G	5150~5250	5150~5250	
	VVII 190	5725~5850	5725~5850	
	Model: A83049	Model: A83049		
Battery1 Information:	Rated capacity: 3.7V,1	Rated capacity: 3.7V,1000mA		
	Manufacturer: Donggu	Manufacturer: Dongguan Amperex Technology Limited		


Member of the SGS Group (SGS SA)



Report No.: CKSEM190700022901

Rev : 01 Page : 9 of 63

# 1.4.1 DUT Antenna Locations(Back View)



The test device is a **Remote controller**. The display diagonal dimension is 42mm and the overall diagonal dimension of this device is 136mm.

According to the distance between WiFi antennas and the sides of the EUT we can draw the conclusion that:

EUT Sides for SAR Testing						
Mode	Front	Back	Left	Right	Тор	Bottom
Wifi1 antenna	Yes	Yes	Yes	Yes	Yes	No
Wifi2 antenna	Yes	Yes	Yes	Yes	No	Yes

Table 1: EUT Sides for SAR Testing

Note:

1) Please see the section 8.2.



Report No.: CKSEM190700022901

Rev : 01 Page : 10 of 63

# 1.5 Test Specification

Identity	Document Title	
FCC 47CFR §2.1093	Radiofrequency Radiation Exposure Evaluation: Portable Devices	
ANSI/IEEE Std C95.1 – 1992	Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.	
IEEE 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques	
KDB 248227 D01 802.11 Wi-Fi SAR v02r02	SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS	
KDB447498 D01 General RF Exposure Guidance v06	Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies	
KDB447498 D03 Supplement C Cross-Reference v01	OET Bulletin 65, Supplement C Cross-Reference	
KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04	SAR Measurement Requirements for 100 MHz to 6 GHz	
KDB 865664 D02 RF Exposure Reporting v01r02	RF Exposure Compliance Reporting and Documentation Considerations	



Report No.: CKSEM190700022901

: 01 Rev Page : 11 of 63

# 1.6 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain*Trunk)	1.60 W/kg	8.00 W/kg
Spatial Average SAR** (Whole Body)	0.08 W/kg	0.40 W/kg
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 W/kg	20.00 W/kg

### Notes:

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation.)

t(86-512)57355888

<sup>\*</sup> The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time

<sup>\*\*</sup> The Spatial Average value of the SAR averaged over the whole body.

<sup>\*\*\*</sup> The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.



Report No.: CKSEM190700022901

Rev : 01

Page : 12 of 63

# 2 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C	
Relative humidity	Min. = 30%, Max. = 70%	
Ground system resistance	< 0.5 Ω	
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.		

Table 2: The Ambient Conditions



Report No.: CKSEM190700022901

Rev : 01 Page : 13 of 63

# 3 SAR Measurements System Configuration

# 3.1 The SAR Measurement System

This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY5 professional system). A E-field probe is used to determine the internal electric fields. The SAR can be obtained from the equation SAR=  $\sigma$  (|Ei|2)/  $\rho$  where  $\sigma$  and  $\rho$  are the conductivity and mass density of the tissue-Simulate.


The DASY5 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software .An arm extension for accommodation the data acquisition electronics (DAE).

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.



F-1. SAR Measurement System Configuration



Report No.: CKSEM190700022901

Rev : 01 Page : 14 of 63

- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7.
- DASY5 software.
- Remote controller with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand, right-hand and Body Worn usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validating the proper functioning of the system.

# 3.2 Isotropic E-field Probe EX3DV4

	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available.
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μW/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μW/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI




Report No.: CKSEM190700022901

Rev : 01 Page : 15 of 63

# 3.3 Data Acquisition Electronics (DAE)

Model	DAE4
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY4/5 embedded system (fully <b>Remote controller</b> led). Two step probe touch detector for mechanical surface detection and emergency robot stop.
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV,400mV)
Input Offset Voltage	< 5μV (with auto zero)
Input Bias Current	< 50 f A
Dimensions	60 x 60 x 68 mm



## 3.4 SAM Twin Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)
Dimensions (incl. Wooden Support)	Length: 1000 mm Width: 500 mm Height: adjustable feet
Filling Volume	approx. 25 liters
Wooden Support	SPEAG standard phantom table



The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

Twin SAM V5.0 has the same shell geometry and is manufactured from the same material as Twin SAM V4.0, but has reinforced top structure.



Report No.: CKSEM190700022901

Rev : 01 Page : 16 of 63

### 3.5 ELI Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)
Liquid	Compatible with all SPEAG tissue
Compatibility	simulating liquids (incl. DGBE type)
Shell Thickness	2.0 ± 0.2 mm (bottom plate)
Dimensions	Major axis: 600 mm
Difficusions	Minor axis: 400 mm
Filling Volume	approx. 30 liters
Wooden Support	SPEAG standard phantom table



Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.

ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4, but has reinforced top structure.

Member of the SGS Group (SGS SA)



Report No.: CKSEM190700022901

Rev : 01

Page : 17 of 63

## 3.6 Device Holder for Transmitters



F-2. Device Holder for Transmitters

- The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centres for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.
- The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\varepsilon$ =3 and loss tangent  $\delta$ =0.02. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国•江苏•昆山市留学生创业园伟业路10号 邮编 215300  $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$ 



Report No.: CKSEM190700022901

Rev : 01 Page : 18 of 63

# 3.7 Measurement procedure

## 3.7.1 Scanning procedure

### **Step 1: Power reference measurement**

The "reference" and "drift" measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure.

### Step 2: Area scan

The SAR distribution at the exposed side of the head was measured at a distance of 4mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm\*15mm or 12mm\*12mm or 10mm\*10mm.Based on the area scan data, the area of the maximum absorption was determined by spline interpolation.

### Step 3: Zoom scan

Around this point, a volume of 30mm\*30mm (fine resolution volume scan, zoom scan) was assessed by measuring 5x5x7 points (≤2GHz)and 7x7x7 points (≥2GHz). On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

The data at the surface was extrapolated, since the centre of the dipoles is 2.0mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. (This can be variable. Refer to the probe specification). The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The volume was integrated with the trapezoidal algorithm. One thousand points were interpolated to calculate the average. All neighbouring volumes were evaluated until no neighboring volume with a higher average value was found.

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std. 1528-2003.

Member of the SGS Group (SGS SA)



Report No.: CKSEM190700022901

Rev : 01 Page : 19 of 63

			≤ 3 GHz	> 3 GHz	
Maximum distance from (geometric center of pr		_	5 ± 1 mm	½·δ·ln(2) ± 0.5 mm	
Maximum probe angle surface normal at the n			30° ± 1°	20° ± 1°	
			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm	
Maximum area scan sp	atial resolt	ation: Δx <sub>Area</sub> , Δy <sub>Area</sub>	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.		
Maximum zoom scan s	Maximum zoom scan spatial resolution: $\Delta x_{Zoom}$ , $\Delta y_{Zoom}$			3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*	
	uniform	grid: Δz <sub>Zoom</sub> (n)	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm	
Maximum zoom scan spatial resolution, normal to phantom surface	graded	Δz <sub>Zoom</sub> (1): between 1 <sup>st</sup> two points closest to phantom surface		≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
grid $\Delta z_{Zoom}(n>1)$ : between subsequent points			≤ 1.5·Δz	Zoom(n-1)	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

### Step 4: Power reference measurement (drift)

The Power Drift Measurement job measures the field at the same location as the most recent power reference measurement job within the same procedure, and with the same settings. The indicated drift is mainly the variation of the DUT's output power and should vary max.  $\pm$  5 %

When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.



Report No.: CKSEM190700022901

Rev : 01 Page : 20 of 63

### 3.7.2 Data Storage

The DASY software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DAE3". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated. The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [m W/g], [m W/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

### 3.7.3 Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters: - Sensitivity Normi, ai0, ai1, ai2
- Conversion factor ConvFi
- Diode compression point Dcpi
Device parameters: - Frequency f
- Crest factor cf
Media parameters: - Conductivity ε

- Density

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot c f / d c p_i$$

With Vi = compensated signal of channel i (i = x, y, z)

Ui = input signal of channel i (i = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcp i = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$$

Member of the SGS Group (SGS SA)



Report No.: CKSEM190700022901

Rev : 01 Page : 21 of 63

H-field probes:

$$H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2)/f$$

With Vi = compensated signal of channel i (i = x, y, z)

Normi = sensor sensitivity of channel I (i = x, y, z)

[mV/(V/m)2] for E-field Probes

ConvF = sensitivity enhancement in solution

aij = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

Ei = electric field strength of channel i in V/m

Hi = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (Etot^2 \cdot \sigma) / (\varepsilon \cdot 1000)$$

with SAR = local specific absorption rate in mW/g

Etot = total field strength in V/m

 $\sigma$ = conductivity in [mho/m] or [Siemens/m]

ε= equivalent tissue density in g/cm3

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 \frac{2}{3770} \,_{Of} \, P_{pwe} = H_{tot}^2 \cdot 37.7$$

with Ppwe = equivalent power density of a plane wave in mW/cm2

Etot = total electric field strength in V/m

Htot = total magnetic field strength in A/m



Report No.: CKSEM190700022901

Rev : 01 Page : 22 of 63

# 4 SAR measurement variability and uncertainty

# 4.1 SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is remounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is  $\geq$  1.45 W/kg ( $\sim$  10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

# 4.2 SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



Report No.: CKSEM190700022901

Rev : 01 Page : 23 of 63

# 5 Description of Test Position

# **5.1 Body Exposure Condition**


## 5.1.1 Body-worn accessory exposure conditions

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations.

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration. Per FCC KDB Publication 648474 D04, Bodyworn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.



F-3. Test positions for body-worn devices



Report No.: CKSEM190700022901

Rev : 01 Page : 24 of 63

### 5.1.2 Extremity exposure conditions

Devices that are designed or intended for use on extremities, or mainly operated in extremity only exposure conditions, i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Test Exclusion Thresholds in 8.2 should be applied to determine SAR test requirements. When extremity SAR testing is required, a flat phantom must be used if the exposure condition is more conservative than the actual use conditions; otherwise, a KDB inquiry is required to determine the phantom and test requirements. Body SAR compliance is also tested with a flat phantom. For devices with irregular shapes or form factors that do not conform to a flat phantom, and/or unusual operating configurations and exposure conditions, a KDB inquiry is also required to determine the appropriate SAR measurement procedures. Unless it is specified differently in the published RF exposure KDB procedures, when simultaneous transmission applies to extremity exposure, the simultaneous transmission SAR test exclusion provisions should be applied. When simultaneous transmission SAR measurement is required, the enlarged zoom scan and volume scan post-processing procedures in KDB Publication 865664 D01 should be applied.

#### **Test Distance for SAR Evaluation**

For 10g Extremity SAR the EUT is set directly against the phantom and the test distance is 0mm.

For 1g Body SAR the EUT is set 10mm away from the phantom and the test distance is 10mm.

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国•江苏•昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com



Report No.: CKSEM190700022901

Rev : 01 Page : 25 of 63

# 6 SAR System Verification Procedure

# 6.1 Tissue Simulate Liquid

# 6.1.1 Recipes for Tissue Simulate Liquid

The bellowing tables give the recipes for tissue simulating liquids to be used in different frequency bands:

The bellowing tables give the recipes for tissue simulating liquids to be used in different frequency bands:										
Ingredients	Frequency (MHz)									
(% by weight)	45	50	83	35	915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

HSL5GHz is composed of the following ingredients:

Water: 50-65% Mineral oil: 10-30% Emulsifiers: 8-25%

Sodium salt: 0-1.5%

MSL5GHz is composed of the following ingredients:

Water: 64-78%
Mineral oil: 11-18%
Emulsifiers: 9-15%
Sodium salt: 2-3%

Table 3: Recipe of Tissue Simulate Liquid



Report No.: CKSEM190700022901

Rev : 01 Page : 26 of 63

# 6.1.2 Test Liquids Confirmation

### Simulated tissue liquid parameter confirmation

The dielectric parameters were checked prior to assessment using the SPEAG DAK3.5 dielectric probe kit. The dielectric parameters measured are reported in each correspondent section.

#### IEEE SCC-34/SC-2 P1528 recommended tissue dielectric parameters

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in P1528.

Target Frequency	He	ead	Body		
(MHz)	€r	σ (S/m)	€r	σ (S/m)	
150	52.3	0.76	61.9	0.80	
300	45.3	0.87	58.2	0.92	
450	43.5	0.87	56.7	0.94	
835	41.5	0.90	55.2	0.97	
900	41.5	0.97	55.0	1.05	
915	41.5	0.98	55.0	1.06	
1450	40.5	1.20	54.0	1.30	
1610	40.3	1.29	53.8	1.40	
1800-2000	40.0	1.40	53.3	1.52	
2450	39.2	1.80	52.7	1.95	
3000	38.5	2.40	52.0	2.73	
5800	35.3	5.27	48.2	6.00	

( $\varepsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho$  = 1000 kg/m<sup>3</sup>)



Report No.: CKSEM190700022901

Rev : 01

Page : 27 of 63

# 6.1.3 Measurement for Tissue Simulate Liquid

The dielectric properties for this Tissue Simulate Liquids were measured by using the Agilent Model 85070E Dielectric Probe in conjunction with Agilent E5071C Network Analyzer (300 KHz-8500 MHz). The Conductivity ( $\sigma$ ) and Permittivity ( $\rho$ ) are listed in bellow table. For the SAR measurement given in this report. The temperature variation of the Tissue Simulate Liquids was  $22\pm2^{\circ}$ C.

Tissue	Measured	Target Tiss	sue (±5%)	Measure	d Tissue	Liquid Temp.	Measured
Туре	Frequency (MHz)	<b>ε</b> r	σ(S/m)	$\epsilon_{\rm r}$ $\sigma(S/m)$		(°C)	Date
2450 Body	2450	52.70 (50.07~55.34)	1.95 (1.85~2.05)	52.319	1.994	22	2019/7/10
5250 Body	5250	48.9 (46.46~51.35)	5.36 (5.09~5.63)	48.122	5.426	22.2	2019/7/11
5750 Body	5750	48.3 (45.89~50.72)	5.94 (5.64~6.24)	46.85	6.017	22.2	2019/7/12

Table 4: Measurement result of Tissue electric parameters




Report No.: CKSEM190700022901

Rev : 01 Page : 28 of 63

# 6.2 SAR System Check

The microwave circuit arrangement for system check is sketched in bellow figure. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within +/- 10% from the target SAR values. The tests were conducted on the same days as the measurement of the EUT. The obtained results from the system accuracy verification are displayed in the following table. During the tests, the ambient temperature of the laboratory was in the range 22±2°C, the relative humidity was in the range 60% and the liquid depth above the ear reference points was above 15 cm in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.



F-1. the microwave circuit arrangement used for SAR system verification

t(86-512)57355888

t(86-512)57355888



Report No.: CKSEM190700022901

Rev : 01 Page : 29 of 63

### 6.2.1 Justification for Extended SAR Dipole Calibrations

- 1) Referring to KDB865664 D01 requirements for dipole calibration, instead of the typical annual calibration recommended by measurement standards, longer calibration intervals of up to three years may be considered when it is demonstrated that the SAR target, impedance and return loss of a dipole have remain stable according to the following requirements. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.
- a) There is no physical damage on the dipole;
- b) System check with specific dipole is within 10% of calibrated value;
- c) Return-loss is within 10% of calibrated measurement;
- d) Impedance is within  $5\Omega$  from the previous measurement.
- 2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国•江苏•昆山市留学生创业园伟业路10号 邮编 215300  $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$ 



Report No.: CKSEM190700022901

Rev : 01 Page : 30 of 63

# 6.2.2 Summary System Check Result(s)

	ation (it	Measured SAR 250mW	Measured SAR 250mW	Measured SAR (normalized to 1W)	Measured SAR (normalized to 1W)	Target SAR (normalized to 1W) (±10%)	Target SAR (normalized to 1W) (±10%)	Liquid Temp. (°C)	Measured Date
		1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)	, ,	
D2450 V2	Body	13.3	5.86	53.2	23.44	51.6 (46.44~56.76)	24 (21.6~26.4)	22	2019/7/10
Valid K	ation (it	Measured SAR 100mW	Measured SAR 100mW	Measured SAR (normalized to 1W)	Measured SAR (normalized to 1W)	Target SAR (normalized to 1W) (±10%)	Target SAR (normalized to 1W) (±10%)	Liquid Temp. (°C)	Measured Date
		1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)		
D5GHz	Body	7.7	2.07	77	20.7	74.9 (67.41~82.39)	20.9 (18.81~22.99)	22.2	2019/7/11
V2	Body	7.83	2.17	78.3	21.7	76.8 (69.12~84.48)	21.3 (19.17~23.43)	22.2	2019/7/12

Table 5: SAR System Check Result

## 6.2.3 Detailed System Check Results

Please see the Appendix A

Member of the SGS Group (SGS SA)



Report No.: CKSEM190700022901

Rev : 01 Page : 31 of 63

# 7 Test Configuration

# 7.1 Operation Configurations


## 7.1.1 WiFi Test Configuration

A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement.

#### 7.1.1.1 Duty cycle

1) 2.4GHz Wi-Fi 802.11b:

WIFI 802.11b 1M: Duty cycle=12.4076/12.4675=99.52%




5GHz Wi-Fi 802.11a:

WIFI 802.11a 6M: Duty cycle=2.05794/2.0979=98.10%



Report No.: CKSEM190700022901

Rev : 01 Page : 32 of 63



#### 7.1.1.2 Initial Test Position SAR Test Reduction Procedure

DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. The initial test position procedure is described in the following:

- 1) . When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other (remaining) test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band. SAR is also not required for that exposure configuration in the subsequent test configuration(s).
- 2) . When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest extrapolated or estimated 1-g SAR conditions determined by area scans or next closest/smallest test separation distance and maximum RF coupling test positions based on manufacturer justification, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions (left, right, touch, tilt or subsequent surfaces and edges) are tested.
- 3) . For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested. a) Additional power measurements may be required for this step, which should be limited to those necessary for identifying the subsequent highest output power channels.

#### 7.1.1.3 Initial Test Configuration Procedures

An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. SAR is measured using the highest measured maximum output power channel. For configurations with the same specified or measured maximum output power, additional transmission mode and test channel selection procedures are required. SAR test reduction for subsequent highest output test channels is determined according to *reported* SAR of the initial test configuration. For next to the ear, hotspot mode and UMC mini-tablet exposure configurations where multiple test positions are required, the initial test position procedure is applied to minimize the number of test positions required for SAR measurement using the initial test configuration transmission mode. For fixed exposure conditions that do not have multiple SAR test positions, SAR is measured in the transmission mode determined by the initial test



Report No.: CKSEM190700022901

Rev : 01 Page : 33 of 63

configuration.

When the *reported* SAR of the initial test configuration is > 0.8 W/kg, SAR measurement is required for subsequent next highest measured output power channel(s) in the initial test configuration until *reported* SAR is  $\leq$  1.2 W/kg or all required channels are tested.

#### 7.1.1.4 Subsequent Test Configuration Procedures

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. The initial test position procedure is applied to next to the ear, UMPC mini-tablet and hotspot mode configurations. When the same maximum output power is specified for multiple transmission modes, additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. The subsequent test configuration and SAR measurement procedures are described in the following.

- 1) . When SAR test exclusion provisions of KDB Publication 447498 are applicable and SAR measurement is not required for the initial test configuration, SAR is also not required for the next highest maximum output power transmission mode subsequent test configuration(s) in that frequency band or aggregated band and exposure configuration.
- 2) . When the highest reported SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.
- 3) . The number of channels in the initial test configuration and subsequent test configuration can be different due to differences in channel bandwidth. When SAR measurement is required for a subsequent test configuration and the channel bandwidth is smaller than that in the initial test configuration, all channels in the subsequent test configuration that overlap with the larger bandwidth channel tested in the initial test configuration should be used to determine the highest maximum output power channel. This step requires additional power measurement to identify the highest maximum output power channel in the subsequent test configuration to determine SAR test reduction.
  - SAR should first be measured for the channel with highest measured output power in the subsequent test configuration.
  - b) SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the *reported* SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is > 1.2 W/kg or until all required channels are tested. i) For channels with the same measured maximum output power, SAR should be measured using the channel closest to the center frequency of the larger channel bandwidth channel in the initial test configuration.
- 4) . SAR measurements for the remaining highest specified maximum output power OFDM transmission mode configurations that have not been tested in the initial test configuration (highest maximum output) or subsequent test configuration(s) (subsequent next highest maximum output power) is determined by recursively applying the subsequent test configuration procedures in this section to the remaining configurations according to the following:
  - replace "subsequent test configuration" with "next subsequent test configuration" (i.e., subsequent next highest specified maximum output power configuration)
  - b) replace "initial test configuration" with "all tested higher output power configurations"

#### 7.1.1.5 2.4 GHz WiFi SAR Procedures

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions. When SAR measurement is required for an OFDM configuration, the initial test configuration, subsequent test configuration and initial test position procedures are applied. The SAR test exclusion requirements for 802.11g/n OFDM configurations are described in following.

#### • 802.11b DSSS SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

1) . When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300  $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$ 



Report No.: CKSEM190700022901

Rev : 01 Page : 34 of 63

configuration.

2) . When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

### 2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3, including sub-sections). SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) . When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) . When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

#### 7.1.1.6 5 GHz WiFi SAR Procedures

#### U-NII-1 and U-NII-2A Bands

For devices that operate in only one of the U-NII-1 and U-NII-2A bands, the normally required SAR procedures for OFDM configurations are applied. For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following:

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, both bands are tested independently for SAR.
- When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, both bands are tested independently for SAR.
- 3) The two U-NII bands may be aggregated to support a 160 MHz channel on channel number 50. Without additional testing, the maximum output power for this is limited to the lower of the maximum output power certified for the two bands. When SAR measurement is required for at least one of the bands and the highest reported SAR adjusted by the ratio of specified maximum output power of aggregated to standalone band is > 1.2 W/kg, SAR is required for the 160 MHz channel. This procedure does not apply to an aggregated band with maximum output higher than the standalone band(s); the aggregated band must be tested independently for SAR. SAR is not required when the 160 MHz channel is operating at a reduced maximum power and also qualifies for SAR test exclusion.

#### • U-NII-2C and U-NII-3 Bands

The frequency range covered by these bands is 380 MHz (5.47 - 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. when Terminal Doppler Weather Radar (TDWR) restriction applies, all channels that operate at 5.60 - 5.65 GHz must be included to apply the SAR test reduction and measurement procedures.

When the same transmitter and antenna(s) are used for U-NII-2C band and U-NII-3 band or 5.8 GHz band of §15.247, the bands may be aggregated to enable additional channels with 20, 40 or 80 MHz bandwidth to span across the band gap, as illustrated in Appendix B. The maximum output power for the additional band gap channels is limited to the lower of those certified for the bands. Unless band gap channels are permanently disabled, they must be considered for SAR testing. The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz may be grouped with the 5.8 GHz channels in U-NII-3 or §15.247 band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels. When band gap channels are supported and the bands are not aggregated for SAR testing, band gap channels must be considered independently in each band according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

• OFDM Transmission Mode SAR Test Configuration and Channel Selection Requirements

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300  $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$ 



Report No.: CKSEM190700022901

Rev : 01 Page : 35 of 63

The initial test configuration for 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures. When multiple configurations in a frequency band have the same specified maximum output power, the initial test configuration is determined according to the following steps applied sequentially.

- 1) The largest channel bandwidth configuration is selected among the multiple configurations with the same specified maximum output power.
- 2) If multiple configurations have the same specified maximum output power and largest channel bandwidth, the lowest order modulation among the largest channel bandwidth configurations is selected.
- 3) If multiple configurations have the same specified maximum output power, largest channel bandwidth and lowest order modulation, the lowest data rate configuration among these configurations is selected.
- 4) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n. After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following. These channel selection procedures apply to both the initial test configuration and subsequent test configuration(s), with respect to the default power measurement procedures or additional power measurements required for further SAR test reduction. The same procedures also apply to subsequent highest output power channel(s) selection.
  - a) The channel closest to mid-band frequency is selected for SAR measurement.
  - b) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

#### SAR Test Requirements for OFDM configurations

When SAR measurement is required for 802.11 a/n/ac OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. When the same transmitter and antenna(s) are used for U-NII-1 and U-NII-2A bands, additional SAR test reduction applies. When band gap channels between U-NII-2C band and 5.8 GHz U-NII-3 or §15.247 band are supported, the highest maximum output power transmission mode configuration and maximum output power channel across the bands must be used to determine SAR test reduction, according to the initial test configuration and subsequent test configuration requirements. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.



Report No.: CKSEM190700022901

Rev : 01 Page : 36 of 63

# 8 Test Result

## 8.1 Measurement of RF Conducted Power

### 8.1.1 Conducted Power Of WIFI

		<u> </u>				
Mode	Channel	Frequency (MHz)	Data Rate(Mbps)	Average Power (dBm) Ant1	Average Power (dBm) Ant1	Tune up
	1	2412		17.73	17.69	18.5
802.11b	6	2437	1	17.46	17.51	18.5
	11	2462		17.51	17.56	18.5
	1 2412		17.36	17.33	18	
802.11g	6	2437	6	17.38	17.39	18
	11	2462		17.34	17.41	18
000 44 m	1	2412		17.24	17.22	18
802.11n HT20 SISO	6	2437	6.5	17.25	17.36	18
H120 SISO	11	2462		17.39	17.38	18
Mode	Channel	Frequency (MHz)	Data Rate(Mbps)	(dl	e Power 3m) MO	Tune up
000 11n	1	2412		17	.54	18
802.11n	6	2437	13	17	.47	18
HT20 MIMO	11	2462		17	18	

5GHz	mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Average Power (dBm) Ant1	Average Power (dBm) Ant1	Tune up
	U-	36	5180		13.77	13.69	14
	NII-1	40	5200		13.43	13.71	14
802.11a	INII- I	48	5240	6	13.86	13.88	14
002.11a	1.1	149	5745	O	13.94	13.87	14
	U- NII-3	157	5785		13.45	13.96	14
	1411-2	165	5825		13.91	13.85	14
5GHz	mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Average Power (dBm) MIMO		Tune up
	U-	36 5180		13	.62	14	
000 115	NII-1	40	5200		12.68		14
802.11n- HT20	INII- I	48	5240	MCS0	12.48		14
MIMO	1.1	149	5745	IVICSU	12	.52	14
IVIIIVIO	U- NII-3	157	5785		12	.61	14
	1411-2	165	5825		12	14	

Table 6: Conducted Power Of WIFI

#### Note:

- a) Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.
- b) Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.
- 1) When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300  $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$ 



Report No.: CKSEM190700022901

Rev : 01

Page : 37 of 63

2) When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.

c) For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.



Report No.: CKSEM190700022901

Rev : 01 Page : 38 of 63

# 8.2 Stand-alone SAR test evaluation

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

Freq.	Frequency	Position	Average Power		Test Separation	Calculate	Exclusion	Exclusion	
Band	(GHz)	1 Osition	dBm	mW	(mm)	Value	Threshold	(Y/N)	
Wi-Fi	2.45	Body	18.5	70.8	10	11.1	3	N	
Wi-Fi	5.85	Body	14	25.1	10	6.1	3	N	
Wi-Fi	2.45	Extremity	18.5	70.8	0	22.3	7.5	N	
Wi-Fi	5.85	Extremity	14	25.1	0	7.9	7.5	N	

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot$  [ $\sqrt{f(GHz)}$ ]  $\leq$  3.0 for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

The following SAR test exclusion Thresholds based on KDB 447498 D01 General RF Exposure Guidance v06) 4.3.1)

Exposure	Wireless Interface	2.4GHz WLAN Wifi1	2.4GHz WLAN Wifi2	5GHz WLAN Wifi1	5GHz WLAN Wifi2
Position	Calculated Frequency	2462MHz	2462MHz	5825MHz	5825MHz
	Maximum power (dBm)	18.5	18.5	14	14
	Maximum rated power(mW)	71.0	71.0	25.0	25.0
	Separation distance(mm)	0.0	0.0	0.0	0.0
Front	exclusion threshold	22.3	22.3	12.1	12.1
	Testing required?	Yes	Yes	Yes	Yes
	Separation distance(mm)	0.0	0.0	0.0	0.0
Back	exclusion threshold	22.3	22.3	12.1	12.1
	Testing required?	Yes	Yes	Yes	Yes
	Separation distance(mm)	16.3	27.7	16.3	27.7
Left	exclusion threshold	6.8	4.0	3.7	2.2
	Testing required?	Yes	Yes	Yes	No
	Separation distance(mm)	0.0	0.0	0.0	0.0
Right	exclusion threshold	22.3	22.3	12.1	12.1
	Testing required?	Yes	Yes	Yes	Yes
	Separation distance(mm)	0.0	127.7	0.0	127.7
Тор	exclusion threshold	22.3	873.0	12.1	839.0
	Testing required?	Yes	No	Yes	No
	Separation distance(mm)	123.4	0.0	123.4	0.0
Bottom	exclusion threshold	830.0	22.3	796.0	12.1
	Testing required?	No	Yes	No	Yes

Note:

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)573708 t(86-512)57355888 f(86-512)573708

f(86-512)57370818 www.sgsgroup.com.cn f(86-512)57370818 sgs.china@sgs.com



Report No.: CKSEM190700022901

Rev : 01 Page : 39 of 63

- 1. Maximum power is the source-based time-average power and represents the maximum RF output power among production units
- 2. Per KDB 447498 D01, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
- 3. Per KDB 447498 D01, standalone SAR test exclusion threshold is applied; If the distance of the antenna to the user is < 5mm, 5mm is used to determine SAR exclusion threshold
- 4. Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for

1-g SAR and ≤ 7.5 for 10-g extremity SAR

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

For < 50 mm distance, we just calculate mW of the exclusion threshold value (3.0) to do compare.

This formula is [3.0] /  $[\sqrt{f(GHz)}] \cdot [(min. test separation distance, mm)] = exclusion threshold of mW.$ 

- 5. Per KDB 447498 D01, at 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following
- a) [Threshold at 50 mm in step 1) + (test separation distance 50 mm)·( f(MHz)/150)] mW, at 100 MHz to 1500 MHz
- b) [Threshold at 50 mm in step 1) + (test separation distance 50 mm)·10] mW at > 1500 MHz and ≤ 6 GHz
- 6. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.
- 7. Although the position of Left side is not required, but the customer requires testing.



Report No.: CKSEM190700022901

Rev : 01 Page : 40 of 63

#### 8.3 Measurement of SAR Data

#### 8.3.1 SAR Result Of 2.4GHz WIFI

	Body SAR test Data												
Test position	Test mode	Test Ch./Freq.	Duty Cycle %	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Cond ucted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg) 1-g	Liquid Temp.	SAR limit (W/kg)
	•		В	ody Test d	lata with W	Vifi1 anten	na (Separ	ate 10mm	1)				
Front side	802.11b	1/2412	99.52	1.005	0.209	0.126	0.02	17.73	18.50	1.194	0.251	22.0	1.6
Back side	802.11b	1/2412	99.52	1.005	0.312	0.164	0.06	17.73	18.50	1.194	0.374	22.0	1.6
Left side	802.11b	1/2412	99.52	1.005	0.138	0.076	0.09	17.73	18.50	1.194	0.166	22.0	1.6
Right side	802.11b	1/2412	99.52	1.005	0.118	0.067	0.01	17.73	18.50	1.194	0.142	22.0	1.6
Top side	802.11b	1/2412	99.52	1.005	0.139	0.076	0.08	17.73	18.50	1.194	0.167	22.0	1.6
			В	ody Test d	lata with V	Vifi2 anten	na (Separ	ate 10mm	1)				
Front side	802.11b	1/2412	99.52	1.005	0.203	0.122	0.09	17.69	18.50	1.205	0.246	22.0	1.6
Back side	802.11b	1/2412	99.52	1.005	0.172	0.100	0.02	17.69	18.50	1.205	0.208	22.0	1.6
Left side	802.11b	1/2412	99.52	1.005	0.134	0.074	0.04	17.69	18.50	1.205	0.162	22.0	1.6
Right side	802.11b	1/2412	99.52	1.005	0.192	0.108	0.05	17.69	18.50	1.205	0.233	22.0	1.6
Bottom side	802.11b	1/2412	99.52	1.005	0.471	0.219	0.02	17.69	18.50	1.205	0.570	22.0	1.6
		T	1		xtremit	y SAR t	est Data			ı		ı	ı
Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Cond ucted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg) 10-g	Liquid Temp.	SAR limit (W/kg)
			Ext	remity Tes	st data with	n Wifi1 an	tenna (Se <sub>l</sub>	parate 0m	m)				
Front side	802.11b	1/2412	99.52%	1.005	0.433	0.221	0.04	17.73	18.50	1.194	0.265	22.0	4.0
Back side	802.11b	1/2412	99.52%	1.005	0.415	0.215	0.05	17.73	18.50	1.194	0.258	22.0	4.0
Left side	802.11b	1/2412	99.52%	1.005	0.904	0.395	0.14	17.73	18.50	1.194	0.474	22.0	4.0
Right side	802.11b	1/2412	99.52%	1.005	0.353	0.182	0.02	17.73	18.50	1.194	0.218	22.0	4.0
Top side	802.11b	1/2412	99.52%	1.005	0.722	0.305	0.13	17.73	18.50	1.194	0.366	22.0	4.0
	Extremity Test data with Wifi2 antenna (Separate 0mm)												
Front side	802.11b	1/2412	99.52%	1.005	0.585	0.280	-0.09	17.69	18.50	1.205	0.339	22.0	4.0
Back side	802.11b	1/2412	99.52%	1.005	0.370	0.204	0.06	17.69	18.50	1.205	0.247	22.0	4.0
Left side	802.11b	1/2412	99.52%	1.005	0.743	0.302	-0.02	17.69	18.50	1.205	0.366	22.0	4.0
Right side	802.11b	1/2412	99.52%	1.005	0.355	0.176	0.08	17.69	18.50	1.205	0.213	22.0	4.0
Bottom side	802.11b	1/2412	99.52%	1.005	1.010	0.383	0.07	17.69	18.50	1.205	0.464	22.0	4.0

Table 7: SAR Result of 2.4GHz WIFI.

Test Report Form Version: Rev01

#### Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg(2.0 W/kg for 10g) then testing at the other channels is not required for such test configuration(s).
- 3) Per KDB248227D01, for Body SAR test of WiFi 2.4G, SAR is measured for 2.4 GHz 802.11b DSSS using the initial test position procedure. The highest reported SAR for DSSS is adjusted by the ratio of OFDM 802.11g/n to DSSS specified maximum output power and the adjusted SAR is < 1.2 W/kg, so SAR for 802.11g/n is not required.

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com



Report No.: CKSEM190700022901

Rev : 01 Page : 41 of 63

#### 8.3.2 SAR Result Of 5GHz WIFI

					Body	SAR tes	t Data						
Test position	Test mode	Test Ch ./Freq.	Duty Cycle %	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Cond ucted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg) 10-g	Liquid Temp.	SAR limit (W/kg)
	·		Bod	y Test data	of U-NII-1	with Wifi1	antenna (S	Separate 1	0mm)				
Front side	802.11a	48/5240	98.10	1.019	0.049	0.019	0.02	13.86	14	1.033	0.052	22.2	1.6
Back side	802.11a	48/5240	98.10	1.019	0.261	0.1	0.03	13.86	14	1.033	0.275	22.2	1.6
Left side	802.11a	48/5240	98.10	1.019	0.099	0.039	0.02	13.86	14	1.033	0.104	22.2	1.6
Right side	802.11a	48/5240	98.10	1.019	0.00949	0.0028	0.03	13.86	14	1.033	0.010	22.2	1.6
Top side	802.11a	48/5240	98.10	1.019	0.268	0.089	0.09	13.86	14	1.033	0.282	22.2	1.6
			Bod	y Test data	a of U-NII-1	with Wifi2	antenna (S	Separate 1	0mm)	•			
Front side	802.11a	48/5240	98.10	1.019	0.08	0.03	0.01	13.88	14	1.028	0.084	22.2	1.6
Back side	802.11a	48/5240	98.10	1.019	0.028	0.011	0.01	13.88	14	1.028	0.029	22.2	1.6
Left side	802.11a	48/5240	98.10	1.019	0.071	0.025	0.06	13.88	14	1.028	0.074	22.2	1.6
Right side	802.11a	48/5240	98.10	1.019	0.016	0.007	0.01	13.88	14	1.028	0.017	22.2	1.6
Bottom side	802.11a	48/5240	98.10	1.019	0.144	0.056	-0.05	13.88	14	1.028	0.151	22.2	1.6
	•		Bod	y Test data	a of U-NII-3	with Wifi1	antenna (S	Separate 1	0mm)				
Front side	802.11a	149/5745	98.10	1.019	0.228	0.077	0.05	13.94	14	1.014	0.236	22.2	1.6
Back side	802.11a	149/5745	98.10	1.019	0.352	0.14	0.02	13.94	14	1.014	0.364	22.2	1.6
Left side	802.11a	149/5745	98.10	1.019	0.205	0.078	-0.01	13.94	14	1.014	0.212	22.2	1.6
Right side	802.11a	149/5745	98.10	1.019	0.072	0.027	-0.02	13.94	14	1.014	0.074	22.2	1.6
Top side	802.11a	149/5745	98.10	1.019	0.382	0.136	-0.08	13.94	14	1.014	0.395	22.2	1.6
	•		Bod	y Test data	a of U-NII-3	with Wifi2	antenna (S	Separate 1	0mm)	•			
Front side	802.11a	157/5785	98.10	1.019	0.122	0.049	0.07	13.96	14	1.009	0.125	22.2	1.6
Back side	802.11a	157/5785	98.10	1.019	0.06	0.02	0.01	13.96	14	1.009	0.062	22.2	1.6
Left side	802.11a	157/5785	98.10	1.019	0.116	0.046	0.07	13.96	14	1.009	0.119	22.2	1.6
Right side	802.11a	157/5785	98.10	1.019	0.014	0.005	0.03	13.96	14	1.009	0.014	22.2	1.6
Bottom side	802.11a	157/5785	98.10	1.019	0.262	0.092	0.06	13.96	14	1.009	0.269	22.2	1.6
					Extremi	ty SAR t	est Data	1					
Test position	Test mode	Test Ch ./Freq.	Duty Cycle %	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Cond ucted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg) 10-g	Liquid Temp.	SAR limit (W/kg)
			Extre	mity Test d	lata of U-NI	I-1 with Wit	fi1 antenna						
Front side	802.11a	48/5240	98.10	1.019	0.297	0.082	-0.12	13.86	14	1.033	0.086	22.2	4.0
Back side	802.11a	48/5240	98.10	1.019	0.225	0.083	0.09	13.86	14	1.033	0.087	22.2	4.0
Left side	802.11a	48/5240	98.10	1.019	0.561	0.178	0.12	13.86	14	1.033	0.187	22.2	4.0
Right side	802.11a	48/5240	98.10	1.019	0.045	0.01	0.03	13.86	14	1.033	0.011	22.2	4.0
Top side	802.11a	48/5240	98.10	1.019	4.76	0.765	0.07	13.86	14	1.033	0.805	22.2	4.0
			Extre	mity Test d	lata of U-NI	I-1 with Wit	fi2 antenna	(Separate	e 0mm)			1	ı

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com



Report No.: CKSEM190700022901

Rev : 01

Page : 42 of 63

Front side	802.11a	48/5240	98.10	1.019	0.552	0.149	-0.1	13.88	14	1.028	0.156	22.2	4.0
Back side	802.11a	48/5240	98.10	1.019	0.048	0.019	0.11	13.88	14	1.028	0.020	22.2	4.0
Left side	802.11a	48/5240	98.10	1.019	0.752	0.206	0.02	13.88	14	1.028	0.216	22.2	4.0
Right side	802.11a	48/5240	98.10	1.019	0.033	0.013	0.06	13.88	14	1.028	0.014	22.2	4.0
Bottom side	802.11a	48/5240	98.10	1.019	0.966	0.235	-0.04	13.88	14	1.028	0.246	22.2	4.0
	Extremity Test data of U-NII-3 with Wifi1 antenna (Separate 0mm)												
Front side	802.11a	149/5745	98.10	1.019	0.978	0.272	0.05	13.94	14	1.014	0.281	22.2	4.0
Back side	802.11a	149/5745	98.10	1.019	0.337	0.126	0.08	13.94	14	1.014	0.130	22.2	4.0
Left side	802.11a	149/5745	98.10	1.019	1.1	0.299	0.07	13.94	14	1.014	0.309	22.2	4.0
Right side	802.11a	149/5745	98.10	1.019	0.259	0.095	0.16	13.94	14	1.014	0.098	22.2	4.0
Top side	802.11a	149/5745	98.10	1.019	5.94	1.12	-0.12	13.94	14	1.014	1.157	22.2	4.0
			Extre	mity Test d	ata of U-NI	l-3 with Wif	i2 antenna	(Separate	e 0mm)				
Front side	802.11a	157/5785	98.10	1.019	0.583	0.157	0.03	13.96	14	1.009	0.161	22.2	4.0
Back side	802.11a	157/5785	98.10	1.019	0.109	0.043	0.02	13.96	14	1.009	0.044	22.2	4.0
Left side	802.11a	157/5785	98.10	1.019	0.801	0.226	-0.02	13.96	14	1.009	0.232	22.2	4.0
Right side	802.11a	157/5785	98.10	1.019	0.062	0.025	0.17	13.96	14	1.009	0.026	22.2	4.0
Bottom side	802.11a	157/5785	98.10	1.019	1.1	0.288	0.07	13.96	14	1.009	0.296	22.2	4.0

Table 8: SAR Result of 5GHz WIFI.

#### Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) Per KDB248227D01, if the reported (scaled) 1-g SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg(2.0 W/kg for 10-g) then testing at the other channels is not required for such test configuration(s).
- 3) Each channel was tested at the lowest data rate.
- 4) When the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is  $\leq$  1.2 W/kg, SAR test for the other 802.11 modes are not required.



Report No.: CKSEM190700022901

Rev : 01 Page : 43 of 63

# 8.4 Multiple Transmitter Evaluation

#### 8.4.1 Estimated SAR

When the standalone SAR test exclusion is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to determine simultaneous transmission SAR test exclusion:

• (max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]· $[\sqrt{f(GHz)/x}]$  W/kg for test separation distances  $\leq 50$  mm;

Where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.

• 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

#### **Estimated SAR Result**

Freq. Band	Frequency (MHz)	Test Position	Test Separation (mm)	max. power(dBm)	Estimated 1g SAR (W/kg)
Wifi2.4GHz_Wifi1	2462	Body(Bottom)	133.4	18.5	0.4
Wifi2.4GHz_Wifi2	2462	Body(Top)	137.7	18.5	0.4
Wifi5GHz_Wifi1	5850	Body(Bottom)	133.4	14.0	0.4
Wifi5GHz_Wifi2	5850	Body(Top)	137.7	14.0	0.4

Freq. Band	Frequency (MHz)	Test Position	Test Separation (mm)	max. power(dBm)	Estimated 10g SAR (W/kg)
Wifi2.4GHz_Wifi1	2462	Extremity(Bottom)	123.4	18.5	1.0
Wifi2.4GHz_Wifi2	2462	Extremity(Top)	127.7	18.5	1.0
Wifi5GHz_Wifi1	5850	Extremity(Bottom)	123.4	14.0	1.0
Wifi5GHz_Wifi2	5850	Extremity(Top)	127.7	14.0	1.0

#### 8.4.2 Simultaneous SAR test evaluation

#### **Simultaneous Transmission**

Official Code Transmission									
NO.	Simultaneous Transmission Configuration	Body worn							
1	WiFi1 2.4G+WiFi2 2.4G	Yes							
2	WiFi1 5G+WiFi2 5G	Yes							
3	WiFi1 2.4G+WiFi2 5G	NO							
4	WiFi1 5G+WiFi2 2.4G	NO							



Report No.: CKSEM190700022901

Rev : 01 Page : 44 of 63

Simultaneous Transmission SAR Summation Scenario for Body

Exposure position	①MAX. WLAN 2.4GHz SAR(W/kg) Wifi1	②MAX. WLAN 2.4GHz SAR(W/kg) Wifi2	③MAX. WLAN 5GHz SAR(W/kg) Wifi1	④MAX. WLAN 5GHz SAR(W/kg) Wifi2	Summed SAR ①+②	Summed SAR ③+④	Case NO.
Front	0.251	0.246	0.236	0.125	0.497	0.361	No
Back	0.374	0.208	0.364	0.062	0.582	0.426	No
Left	0.166	0.162	0.212	0.119	0.328	0.331	No
Right	0.142	0.233	0.074	0.017	0.375	0.091	No
Тор	0.167	0.4	0.395	0.4	0.567	0.795	No
Bottom	0.4	0.570	0.4	0.269	0.970	0.669	No

Simultaneous Transmission SAR Summation Scenario for Extremity

Exposure position	①MAX. WLAN 2.4GHz SAR(W/kg) Wifi1	②MAX. WLAN 2.4GHz SAR(W/kg) Wifi2	③MAX. WLAN 5GHz SAR(W/kg) Wifi1	@MAX. WLAN 5GHz SAR(W/kg) Wifi2	Summed SAR ①+②	Summed SAR ③+④	Case NO.
Front	0.265	0.339	0.281	0.161	0.604	0.442	No
Back	0.258	0.247	0.130	0.044	0.505	0.174	No
Left	0.474	0.366	0.309	0.232	0.840	0.541	No
Right	0.218	0.213	0.098	0.026	0.431	0.124	No
Тор	0.366	1.000	1.157	1.000	1.366	2.157	No
Bottom	1.000	0.464	1.000	0.296	1.464	1.296	No



Report No.: CKSEM190700022901

Rev : 01 Page : 45 of 63

# 9 Equipment list

Test Platform	SPEAG DASY5 Professional
Location	SGS-CCS Standards Technical Services Co., Ltd. Kunshan Branch
Description	SAR Test System (Frequency range 300MHz-6GHz)
Software Reference	DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

#### **Hardware Reference**

	Equipment	Manufacturer	Model	Serial Number	Calibration Date	Due date of calibration
$\boxtimes$	PC	HP	Core(rm)3.16 G	CZCO48171H	N/A	N/A
$\boxtimes$	Signal Generator	Agilent	E8257C	US37101915	2019/02/25	2020/02/24
	S-Parameter Network Analyzer	Agilent	E5071B	MY42301382	2019/02/25	2020/02/24
$\boxtimes$	Power sensor	Anritsu	E9327A	Us40441788	2019/02/25	2020/02/24
$\boxtimes$	Power meter	Anritsu	E4416A	GB41292714	2019/02/25	2020/02/24
$\boxtimes$	DAE	SPEAG	DAE4	1245	2019/05/21	2020/05/20
$\boxtimes$	E-field PROBE	SPEAG	EX3DV4	3798	2019/05/24	2020/05/23
$\boxtimes$	Validation Kits	SPEAG	D2450V2	817	2019/06/10	2022/06/09
$\boxtimes$	Validation Kits	SPEAG	D5GHzV2	1095	2019/06/14	2022/06/13
$\boxtimes$	Electro Thermometer	DTM	DTM3000	3030	2018/12/8	2019/12/7
$\boxtimes$	Amplifier	Mini-circuits	ZVE-8G	110405	N/A	N/A
$\boxtimes$	Amplifier	Mini-circuits	ZHL-42	QA1331003	N/A	N/A
	3db ATTENUATOR	MINI	MCL BW- S3W5	0533	N/A	N/A
$\boxtimes$	DUMMY PROBE	SPEAG	DP_2	SPDP2001AA	N/A	N/A
$\boxtimes$	Dual Directional Coupler	Woken	20W couple	DOM2BHW1A1	N/A	N/A
	SAM PHANTOM (ELI4 v4.0)	SPEAG	QDOVA001BB	1102	N/A	N/A
$\boxtimes$	Twin SAM Phantom	SPEAG	QD000P40CD	1609	N/A	N/A
$\boxtimes$	ROBOT	SPEAG	TX60	F10/5E6AA1/A10 1	N/A	N/A
$\boxtimes$	ROBOT KRC	SPEAG	CS8C	F10/5E6AA1/C10 1	N/A	N/A
	LIQUID CALIBRATION KIT	ANTENNESS A	41/05 OCP9	00425167	N/A	N/A

Note: All the equipments are within the valid period when the tests are performed.

All measurement facilities used to collect the measurement data are located at

No.10, Weiye Rd., Innovation Park, Eco & Tec. Development Part, Kunshan City, Jiangsu Province, China.

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300  $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$ 



Report No.: CKSEM190700022901

Rev : 01

Page : 46 of 63

# **Appendix A: Detailed System Check Results**

The plots are showing as followings.

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300  $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$ 

Member of the SGS Group (SGS SA)



Report No.: CKSEM190700022901

Rev : 01 Page : 47 of 63

Date: 2019/07/10

Test Laboratory: Compliance Certification Services Inc.

## SystemPerformanceCheck-Body D2450

DUT: Dipole 2450 MHz D2450V2; Type: D24500V2; Serial: 817

Communication System: UID 0, CW; Frequency: 2450 MHz

Medium parameters used: f = 2450 MHz;  $\sigma$  = 1.994 S/m;  $\epsilon_r$  = 52.319;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(7.37, 7.37, 7.37); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: Twin SAM Phantom: Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

# Body/Pin=250 mW, dist=10mm (EX-Probe)/Area Scan (9x10x1): Measurement grid: dx=12mm, dy=12mm


Maximum value of SAR (measured) = 20.2 W/kg

# Body/Pin=250 mW, dist=10mm (EX-Probe)/Zoom Scan (7x7x7) (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 108.2 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 33.1 W/kg

SAR(1 g) = 13.3 W/kg; SAR(10 g) = 5.86 W/kg Maximum value of SAR (measured) = 22.1 W/kg



0 dB = 22.1 W/kg = 13.44 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 48 of 63

Date: 2019/07/11

Test Laboratory: Compliance Certification Services Inc.

## SystemPerformanceCheck-D5250 Body

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: 1095

Communication System: UID 0, CW (0); Frequency: 5250 MHz

Medium parameters used: f = 5250 MHz;  $\sigma = 5.426 \text{ S/m}$ ;  $\varepsilon_r = 48.122$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(4.5, 4.5, 4.5); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 23.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

# Body/d=10mm, Pin=100mW, f=5250 MHz/Area Scan (10x10x1): Measurement grid:

dx=10mm, dv=10mm

Maximum value of SAR (measured) = 14.5 W/kg


# Body/d=10mm, Pin=100mW, f=5250 MHz/Zoom Scan (4x4x1.4mm, graded),

dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 72.98 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 34.2 W/kg

SAR(1 g) = 7.7 W/kg; SAR(10 g) = 2.07 W/kgMaximum value of SAR (measured) = 20.5 W/kg



0 dB = 20.5 W/kg = 13.12 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 49 of 63

Date: 2019/07/12

Test Laboratory: Compliance Certification Services Inc.

# SystemPerformanceCheck-D5750 Body

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: 1095

Communication System: UID 0, CW (0); Frequency: 5750 MHz

Medium parameters used: f = 5750 MHz;  $\sigma$  = 6.017 S/m;  $\epsilon_r$  = 46.85;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(4.2, 4.2, 4.2); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 23.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

# Body/d=10mm, Pin=100mW, f=5600 MHz 2/Area Scan (9x10x1): Measurement grid: dx=10mm, dv=10mm

Maximum value of SAR (measured) = 20.7 W/kg

# Body/d=10mm, Pin=100mW, f=5600 MHz 2/Zoom Scan (4x4x1.4mm, graded),


dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 74.22 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 40.9 W/kg

Test Report Form Version: Rev01

**SAR(1 g) = 7.83 W/kg; SAR(10 g) = 2.17 W/kg** Maximum value of SAR (measured) = 22.1 W/kg



0 dB = 22.1 W/kg = 13.44 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 50 of 63

# **Appendix B: Detailed Test Results**

The plots of worse case are showing as followings.

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300  $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$ 

Member of the SGS Group (SGS SA)



Report No.: CKSEM190700022901

Rev : 01 Page : 51 of 63

Date: 2019/07/10

Test Laboratory: Compliance Certification Services Inc.

#### WIFI 2.4G 802.11b 1Mbps Back side Ch1 10mm Ant 1

DUT: Remote controller; Type: ZR-100A; Serial: NA

Communication System: UID 0, IEEE 802.11b (0); Frequency: 2412 MHz; Duty Cycle: 1:1 Medium parameters used: f = 2412 MHz;  $\sigma = 1.945$  S/m;  $\epsilon_r = 52.432$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(7.37, 7.37, 7.37); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 31.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (7x14x1): Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (measured) = 0.416 W/kg

# Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm,


dy=5mm, dz=5mm

Reference Value = 11.59 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.582 W/kg

SAR(1 g) = 0.312 W/kg; SAR(10 g) = 0.164 W/kg

Maximum value of SAR (measured) = 0.480 W/kg



0 dB = 0.480 W/kg = -3.19 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 52 of 63

Date: 2019/07/10

Test Laboratory: Compliance Certification Services Inc.

## WIFI 2.4G 802.11b 1Mbps Bottom side Ch1 10mm Ant 2

DUT: Remote controller; Type: ZR-100A; Serial: NA

Communication System: UID 0, IEEE 802.11b (0); Frequency: 2412 MHz; Duty Cycle: 1:1 Medium parameters used: f = 2412 MHz;  $\sigma = 1.945$  S/m;  $\epsilon_r = 52.432$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(7.37, 7.37, 7.37); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 31.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (6x9x1): Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (measured) = 0.635 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm,


dy=5mm, dz=5mm

Reference Value = 19.89 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.974 W/kg

SAR(1 g) = 0.471 W/kg; SAR(10 g) = 0.219 W/kg

Maximum value of SAR (measured) = 0.780 W/kg



0 dB = 0.780 W/kg = -1.08 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 53 of 63

Date: 2019/07/10

Test Laboratory: Compliance Certification Services Inc.

## WIFI 2.4G 802.11b 1Mbps Left side Ch1 0mm Ant 1

DUT: Remote controller; Type: ZR-100A; Serial: NA

Communication System: UID 0, IEEE 802.11b (0); Frequency: 2412 MHz; Duty Cycle: 1:1 Medium parameters used: f = 2412 MHz;  $\sigma = 1.945$  S/m;  $\epsilon_r = 52.432$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(7.37, 7.37, 7.37); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 31.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (5x13x1): Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (measured) = 1.32 W/kg

# Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm,


dy=5mm, dz=5mm

Reference Value = 16.90 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 2.09 W/kg

SAR(1 g) = 0.904 W/kg; SAR(10 g) = 0.395 W/kg

Maximum value of SAR (measured) = 1.56 W/kg



0 dB = 1.56 W/kg = 1.93 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 54 of 63

Date: 2019/07/10

Test Laboratory: Compliance Certification Services Inc.

# WIFI 2.4G 802.11b 1Mbps Bottom side Ch1 0mm Ant 2

DUT: Remote controller; Type: ZR-100A; Serial: NA

Communication System: UID 0, IEEE 802.11b (0); Frequency: 2412 MHz; Duty Cycle: 1:1 Medium parameters used: f = 2412 MHz;  $\sigma = 1.945$  S/m;  $\epsilon_r = 52.432$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(7.37, 7.37, 7.37); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 31.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (5x8x1): Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (measured) = 1.68 W/kg


# Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm

Reference Value = 26.29 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 3.43 W/kg

SAR(1 g) = 1.01 W/kg; SAR(10 g) = 0.383 W/kg Maximum value of SAR (measured) = 2.26 W/kg



0 dB = 2.26 W/kg = 3.54 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 55 of 63

Date: 2019/07/11

Test Laboratory: Compliance Certification Services Inc.

WIFI 5G 802.11a 6Mbps Top side Ch48 10mm Ant 1

DUT: Remote controller; Type: ZR-100A; Serial: NA

Communication System: UID 0, IEEE 802.11 a (0); Frequency: 5240 MHz; Duty Cycle: 1:1 Medium parameters used: f = 5240 MHz;  $\sigma = 5.459$  S/m;  $\varepsilon_r = 48.111$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(4.5, 4.5, 4.5); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 23.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (6x9x1): Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (measured) = 0.516 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm,


dy=4mm, dz=1.4mm

Reference Value = 11.38 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.983 W/kg

SAR(1 g) = 0.268 W/kg; SAR(10 g) = 0.089 W/kg

Maximum value of SAR (measured) = 0.623 W/kg



0 dB = 0.623 W/kg = -2.06 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 56 of 63

Date: 2019/07/11

Test Laboratory: Compliance Certification Services Inc.

## WIFI 5G 802.11a 6Mbps Bottom side Ch48 10mm Ant 2

DUT: Remote controller; Type: ZR-100A; Serial: NA

Communication System: UID 0, IEEE 802.11 a (0); Frequency: 5240 MHz; Duty Cycle: 1:1 Medium parameters used: f = 5240 MHz;  $\sigma = 5.459$  S/m;  $\varepsilon_r = 48.111$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(4.5, 4.5, 4.5); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 23.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (measured) = 0.314 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm,


dy=4mm, dz=1.4mm

Reference Value = 3.667 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.516 W/kg

SAR(1 g) = 0.144 W/kg; SAR(10 g) = 0.056 W/kg

Maximum value of SAR (measured) = 0.310 W/kg



0 dB = 0.310 W/kq = -5.09 dBW/kq



Report No.: CKSEM190700022901

Rev : 01 Page : 57 of 63

Date: 2019/07/12

Test Laboratory: Compliance Certification Services Inc.

WIFI 5G 802.11a 6Mbps Top side Ch149 10mm Ant 1

DUT: Remote controller; Type: ZR-100A; Serial: NA

Communication System: UID 0, IEEE 802.11 a (0); Frequency: 5745 MHz; Duty Cycle: 1:1 Medium parameters used: f = 5745 MHz;  $\sigma = 6.036$  S/m;  $\varepsilon_r = 46.775$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(4.2, 4.2, 4.2); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 23.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (6x9x1): Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (measured) = 0.738 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm,


dy=4mm, dz=1.4mm

Reference Value = 6.916 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.53 W/kg

SAR(1 g) = 0.382 W/kg; SAR(10 g) = 0.136 W/kg

Maximum value of SAR (measured) = 0.900 W/kg



0 dB = 0.900 W/kg = -0.46 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 58 of 63

Date: 2019/07/12

Test Laboratory: Compliance Certification Services Inc.

#### WIFI 5G 802.11a 6Mbps Bottom side Ch157 10mm Ant 2

DUT: Remote controller; Type: ZR-100A; Serial: NA

Communication System: UID 0, IEEE 802.11 a (0); Frequency: 5785 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5785 MHz;  $\sigma$  = 6.038 S/m;  $\varepsilon_r$  = 46.67;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(4.2, 4.2, 4.2); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 23.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (measured) = 0.619 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm,


dy=4mm, dz=1.4mm

Reference Value = 4.517 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.14 W/kg

SAR(1 g) = 0.262 W/kg; SAR(10 g) = 0.092 W/kg

Maximum value of SAR (measured) = 0.638 W/kg



0 dB = 0.638 W/kg = -1.95 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 59 of 63

Date: 2019/07/11

Test Laboratory: Compliance Certification Services Inc.

#### WIFI 5G 802.11a 6Mbps Top side Ch48 0mm Ant 1

DUT: Remote controller; Type: ZR-100A; Serial: NA

Communication System: UID 0, IEEE 802.11 a (0); Frequency: 5240 MHz; Duty Cycle: 1:1 Medium parameters used: f = 5240 MHz;  $\sigma = 5.459 \text{ S/m}$ ;  $\epsilon_r = 48.111$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(4.5, 4.5, 4.5); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 23.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (5x8x1): Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (measured) = 15.1 W/kg


# Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm,

dy=4mm, dz=1.4mm

Reference Value = 7.847 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 42.7 W/kg

SAR(1 g) = 4.76 W/kg; SAR(10 g) = 0.765 W/kgMaximum value of SAR (measured) = 17.7 W/kg



0 dB = 17.7 W/kg = 12.48 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 60 of 63

Date: 2019/07/11

Test Laboratory: Compliance Certification Services Inc.

#### WIFI 5G 802.11a 6Mbps Bottom side Ch48 0mm Ant 2

DUT: Remote controller; Type: ZR-100A; Serial: NA

Communication System: UID 0, IEEE 802.11 a (0); Frequency: 5240 MHz; Duty Cycle: 1:1 Medium parameters used: f = 5240 MHz;  $\sigma = 5.459 \text{ S/m}$ ;  $\epsilon_r = 48.111$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(4.5, 4.5, 4.5); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 23.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (5x8x1): Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (measured) = 1.71 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm,


dy=4mm, dz=1.4mm

Reference Value = 9.611 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 5.08 W/kg

SAR(1 g) = 0.966 W/kg; SAR(10 g) = 0.235 W/kg

Maximum value of SAR (measured) = 2.59 W/kg



0 dB = 2.59 W/kg = 4.13 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 61 of 63

Date: 2019/07/12

Test Laboratory: Compliance Certification Services Inc.

WIFI 5G 802.11a 6Mbps Top side Ch149 0mm Ant 1

DUT: Remote controller; Type: ZR-100A; Serial: NA

Communication System: UID 0, IEEE 802.11 a (0); Frequency: 5745 MHz; Duty Cycle: 1:1 Medium parameters used: f = 5745 MHz;  $\sigma = 6.036$  S/m;  $\varepsilon_r = 46.775$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(4.2, 4.2, 4.2); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 23.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (5x8x1): Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (measured) = 17.0 W/kg

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm,


dy=4mm, dz=1.4mm

Reference Value = 21.74 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 48.5 W/kg

Test Report Form Version: Rev01

SAR(1 g) = 5.94 W/kg; SAR(10 g) = 1.12 W/kg Maximum value of SAR (measured) = 23.0 W/kg



0 dB = 23.0 W/kg = 13.62 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 62 of 63

Date: 2019/07/12

Test Laboratory: Compliance Certification Services Inc.

## WIFI 5G 802.11a 6Mbps Bottom side Ch157 0mm Ant 2

DUT: Remote controller; Type: ZR-100A; Serial: NA

Communication System: UID 0, IEEE 802.11 a (0); Frequency: 5785 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5785 MHz;  $\sigma$  = 6.038 S/m;  $\epsilon_r$  = 46.67;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

# **DASY Configuration:**

- Probe: EX3DV4 SN3798; ConvF(4.2, 4.2, 4.2); Calibrated: 2019/05/24;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = -19.0, 23.0
- Electronics: DAE4 Sn1245; Calibrated: 2019/05/21
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1102
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (6x8x1): Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (measured) = 2.52 W/kg


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm,

dy=4mm, dz=1.4mm

Reference Value = 5.166 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 6.44 W/kg

SAR(1 g) = 1.11 W/kg; SAR(10 g) = 0.288 W/kg Maximum value of SAR (measured) = 3.13 W/kg



0 dB = 3.13 W/kg = 4.96 dBW/kg



Report No.: CKSEM190700022901

Rev : 01 Page : 63 of 63

**Appendix C: Calibration certificate** 

**Appendix D: Photographs** 

---END---