# SAR TESTREPORT

**ISSUED BY** Shenzhen BALUN Technology Co., Ltd.



**FOR** 

## **BLASTOFF CONTROLLER**

**ISSUED TO** Shenzhen Zero Infinity Technology Co., Ltd.

Room A211-B, F2, Shanshui Building, No.4093, Liuxian Avenue, Nanshan District, Shenzhen, China



Tested by: 700

(Engineer)

Approved by

Wei Yanquan (Chief Engineer)

ep 10,2019

Report No.:

BL-SZ1970622-701

EUT Name:

**BLASTOFF CONTROLLER** 

Model Name:

**ZR-100B** 

Brand Name:

**ZERO ZERO** 

FCC ID:

2AIDWZR-100B

Test Standard:

FCC 47 CFR Part 2.1093

ANSI C95.1: 1999, IEEE 1528: 2013

Maximum SAR:

Extremity (10 g): 0.695 W/kg

Body (1 g): 0.428 W/kg

Test Conclusion:

**Pass** 

Test Date:

Sep. 18, 2019

Date of Issue:

Sep. 20, 2019

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong, P. R. China 518055 TEL: +86-755-66850100,FAX: +86-755-61824271



## **Revision History**

Version Issue Date Revisions Content

Rev. 01 Sep. 12, 2019 Initial Issue
Rev. 02 Sep. 20, 2019 Revised low channel frequency to 2405MHz and retested SAR values.

Updated test position configuration in section 6.

Added note for used IEC tissue

Added note for used IEC tissue simulating liquid to perform SAR testing in annex A and annex B.

## **TABLE OF CONTENTS**

1	GENEF	RAL INFORMATION	4
	1.1	Identification of the Testing Laboratory	4
	1.2	Identification of the Responsible Testing Location	4
	1.3	Test Environment Condition	4
	1.4	Announce	5
2	PRODU	JCT INFORMATION	6
	2.1	Applicant Information	6
	2.2	Manufacturer Information	6
	2.3	Factory Information	6
	2.4	General Description for Equipment under Test (EUT)	6
	2.5	Ancillary Equipment	7
	2.6	Technical Information	8
3	SUMM	ARY OF TEST RESULT	9
	3.1	Test Standards	9
	3.2	Device Category and SAR Limit	10
	3.3	Test Result Summary	11
	3.4	Test Uncertainty	12
4	MEASU	JREMENT SYSTEM	13
	4.1	Specific Absorption Rate (SAR) Definition	13
	4.2	DASY SAR System	14
5	SYSTE	M VERIFICATION	21
	5.1	Purpose of System Check	21



	5.2	System Check Setup	. 21
6	TEST F	OSITION CONFIGURATIONS	. 22
	6.1	Body Exposure Condition	. 22
	6.2	Extremity Exposure Condition	. 22
7	MEASU	REMENT PROCEDURE	. 23
	7.1	Measurement Process Diagram	. 23
	7.2	SAR Scan General Requirement	. 24
	7.3	Measurement Procedure	. 25
	7.4	Area & Zoom Scan Procedure	. 25
8	CONDU	JCTED RF OUPUT POWER	. 26
	8.1	2.4G ISM Band (GFSK modulation)	. 26
9	ANTEN	NA LOCATION PHOTOS	. 27
	9.1	TEST RESULT	. 28
	9.2	2.4G ISM Band Extremity SAR (10g)	. 28
	9.3	2.4G ISM Band Body SAR (1g)	. 28
10	SAR M	easurement Variability	. 29
11	SIMUL	TANEOUS TRANSMISSION	. 30
12	TEST E	QUIPMENTS LIST	. 31
ANI	NEX A	SIMULATING LIQUID VERIFICATION RESULT	. 32
ANI	NEX B	SYSTEM CHECK RESULT	. 33
ANI	NEX C	TEST DATA	. 35
ANI	NEX D	EUT EXTERNAL PHOTOS	. 39
ANI	NEX E	SAR TEST SETUP PHOTOS	. 39
ΛNIN	JEY E	CALIDDATION DEDODT	30



# 1 GENERAL INFORMATION

# 1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.	
	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi	
Address	Road, Nanshan District, Shenzhen, Guangdong Province, P. R.	
	China	
Phone Number	+86 755 6685 0100	
Fax Number	+86 755 6182 4271	

# 1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.	
	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi	
Address	Road, Nanshan District, Shenzhen, Guangdong Province, P. R.	
	China	
	The laboratory has been listed by Industry Canada to perform	
	electromagnetic emission measurements. The recognition numbers	
	of test site are 11524A-1.	
	The laboratory is a testing organization accredited by FCC as a	
Accreditation	accredited testing laboratory. The designation number is CN1196.	
Certificate	The laboratory is a testing organization accredited by American	
Certificate	Association for Laboratory Accreditation (A2LA) according to	
	ISO/IEC 17025.The accreditation certificate is 4344.01.	
	The laboratory is a testing organization accredited by China National	
	Accreditation Service for Conformity Assessment (CNAS) according	
	to ISO/IEC 17025. The accreditation certificate number is L6791.	
	All measurement facilities used to collect the measurement data are	
Description	located at Block B, FL 1, Baisha Science and Technology Park,	
Description	Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province,	
	P. R. China 518055	

# 1.3 Test Environment Condition

Ambient Temperature	21°C to 23°C
Ambient Relative Humidity	37% to 48%
Ambient Pressure	100 KPa to 102 KPa



#### 1.4 Announce

- (1) The test report reference to the report template version v2.2.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.



# **2 PRODUCT INFORMATION**

# 2.1 Applicant Information

Applicant	Shenzhen Zero Zero Infinity Technology Co., Ltd.		
Address	Room A211-B, F2, Shanshui Building, No.4093, Liuxian Avenue,		
	Nanshan District, Shenzhen, China		

## 2.2 Manufacturer Information

Manufacturer Shenzhen Zero Zero Infinity Technology Co., Ltd.		
Addross	Room A211-B, F2, Shanshui Building, No.4093, Liuxian Avenue,	
Address	Nanshan District, Shenzhen, China	

# 2.3 Factory Information

Factory	N/A
Address	N/A

# 2.4 General Description for Equipment under Test (EUT)

EUT Name	BLASTOFF CONTROLLER
Model Name Under Test	ZR-100B
Series Model Name	N/A
Description of Model	N/A
Name Differentiation	N/A
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A



# 2.5 Ancillary Equipment

	Battery	
	Brand Name	N/A
	Model No.	ZZTDS87
Ancillary Equipment	Serial No.	N/A
	Capacitance	2200 mAh
	Rated Voltage	3.8 V
	Limit Charge Voltage	4.35 V



# 2.6 Technical Information

Network and Wireless connectivity	2.4G ISM Band ( GFSK modulation)
-----------------------------------	----------------------------------

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	2.4G ISM Band ( GFSK modulation)		
Frequency Range 2.4G ISM Band ( GFSK modulation) 2405 ~ 2473 MHz		2405 ~ 2473 MHz	
Antenna Type	Dipole ( PCB + cable )		
DTM	N/A		
Hotspot Function	N/A		
Exposure Category General Population/Uncontrolled exposure		osure	
EUT Stage	Portable Device		
Draduct	Туре		
Product		☐ Identical prototype	



# **3 SUMMARY OF TEST RESULT**

# 3.1 Test Standards

No.	Identity	Document Title					
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations					
2	ANSI/IEEE Std.	EEE Standard for Safety Levels with Respect to Human Exposure					
	C95.1-1999	to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz					
3	IEEE Std. 1528- 2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques					
4	FCC KDB 447498	Mobile and Portable Device RF Exposure Procedures and					
4	D01 v06	Equipment Authorization Policies					
8	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz					
9	FCC KDB 865664 D02 v01r02	RF Exposure Reporting					
11	KDB 248227 D01 v02r02	SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters					



## 3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user.

Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

#### Table of Exposure Limits:

	SAR Valu	e (W/Kg)
Body Position	General Population/	Occupational/
	Uncontrolled Exposure	ControlledExposure
Whole-Body SAR	0.08	0.4
(averaged over the entire body)	0.08	0.4
Partial-Body SAR	1.60	8.0
(averaged over any 1 gram of tissue)	1.00	8.0
SAR for hands, wrists, feet and		
ankles	4.0	20.0
(averaged over any 10 grams of tissue)		

#### NOTE:

**General Population/Uncontrolled Exposure:** Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.



# 3.3 Test Result Summary

# 3.3.1 Highest SAR

	Maximum Report SAR						
Band	(W/kg)						
	Extremity (0mm)	Body (10mm)					
	10 g (W/Kg)	1 g (W/Kg)					
	0.695	0.428					
Limit (W/kg)	4.0	1.6					
Verdict	Pa	ass					



# 3.4 Test Uncertainty

According to KDB 865664 D01, when the highest measured 1 g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis is not required in SAR reports submitted for equipment approval. The maximum 1 g SAR for the EUT in this report is 0.428 W/kg, which is lower than 1.5 W/kg, and the maximum 10 g SAR for the EUT in this report is 0.695 W/kg, which is lower than 3.75 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.



### **4 MEASUREMENT SYSTEM**

## 4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma E^2}{\rho}$$


Where:  $\sigma$  is the conductivity of the tissue,

pis the mass density of the tissue and E is the RMS electrical field strength.



## 4.2 DASY SAR System

#### 4.2.1 DASY SAR System Diagram



The DASY5 system for performing compliance tests consists of the following items:

- 1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
- 2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, ADconversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- 4. A unit to operate the optical surface detector which is connected to the EOC.
- 5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
- 6. The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.
- 7. DASY5 software and SEMCAD data evaluation software.
- 8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
- 9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
- 10. The device holder for handheld mobile phones.
- 11. Tissue simulating liquid mixed according to the given recipes.
- 12. System validation dipoles allowing to validate the proper functioning of the system.



#### 4.2.2 Robot

The Dasy SAR system uses the high precision robots. Symmetrical design with triangular core Built-in optical fiber for surface detection system For the 6-axis controller system, Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents). The robot series have many features that are important for our application:



- High precision (repeatability ±0.02 mm)
- High reliability

   (industrial design)
  - Low maintenance costs
    (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements
   (brush less synchron motors; no stepper motors)
- Low ELF interference (motor control \_elds shielded via the closed metallic construction shields)



#### 4.2.3 E-Field Probe

The probe is specially designed and calibrated for use in liquids with high permittivities for the measurements the Specific Dosimetric E-Field Probe EX3DV4-SN:7510 with following specifications is used.

Construction Symmetrical design with triangular core Built-in optical fiber for surface detection

systemBuilt-in shielding against static charges PEEK enclosure material (resistant to

organic solvents, e.g., glycolether)

Calibration ISO/IEC 17025 calibration service available

Frequency 10 MHz to 6 GHz; Linearity: ± 0.2 dB (30 MHz to 6 GHz)

Directivity ± 0.2 dB in HSL (rotation around probe axis); ± 0.4 dB in HSL (rotation normal to probe

axis)

Dynamic range  $5 \mu W/g$  to > 100 mW/g; Linearity:  $\pm 0.2 dB$ 

Dimensions Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 10 mm) Distance from

probe tip to dipole centers: 1.0 mm

Application General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic

scanning in arbitrary phantoms (EX3DV4)



#### **E-Field Probe Calibration Process**

Probe calibration is realized, in compliance with CENELEC EN 62209-1/-2 and IEEE 1528 std, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the EN 62209-1/2 annexe technique using reference guide at the five frequencies.



#### 4.2.4 Data Acquisition Electronics

The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converte and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.



- Input Impedance: 200MOhm
- The Inputs: Symmetrical and Floating
- · Commom Mode Rejection: Above 80dB



#### 4.2.5 Phantoms

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



- ·Left hand
- ·Right hand
- ·Flat phantom

#### **Photo of Phantom SN1857**



## **Photo of Phantom SN1859**



Serial Number	Material	Length	Height
SN 1857 SAM1	Vinylester, glass fiber reinforced	1000	500
SN 1859 SAM2	Vinylester, glass fiber reinforced	1000	500



#### 4.2.6 Device Holder

The DASY5 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA"s only. If necessary an additional support of polystyrene material is used. Larger DUT"s (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values. Therefore those devices are normally only tested at the flat part of the SAM.



The positioning system allows obtaining cheek and tilting position with a very good accuracy. Incompliance with CENELEC, the tilt angle uncertainty is lower than 1°.



#### 4.2.7 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

Jan		He	ad (Referen	ice IEEE15	28)		•	•
Frequency	Water	Sugar	Cellulose	Salt	Preventol	DGBE	Conductivity	Permittivity
(MHz)	(%)	(%)	(%)	(%)	(%)	(%)	σ (S/m)	ε
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency	Water	Hexyl Carbitol			Triton	X-100	Conductivity	Permittivity
(MHz)	(%)	(%)			(%	<b>6</b> )	σ (S/m)	3
5200	62.52		17.24 17.24			4.66	36.0	
5800	62.52		17.24		17.	24	5.27	35.3
		Body (F	rom instrun	nent manu	facturer)			
Frequency	Water	Sugar	Cellulose	Salt	Preventol	DGBE	Conductivity	Permittivity
(MHz)	(%)	(%)	(%)	(%)	(%)	(%)	σ (S/m)	ε
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Estate (MILL)	NA/ - (		DGBE		Sa	alt	Conductivity	Permittivity
Frequency(MHz)	Water		(%)		(%	<b>6</b> )	σ (S/m)	ε
5200	78.60		21.40		1		5.54	47.86
5800	78.50		21.40		0.	1	6.0	48.20




## **5 SYSTEM VERIFICATION**

## 5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

## 5.2 System Check Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:





## **6 TEST POSITION CONFIGURATIONS**

According to KDB inquiry the EUT tested for SAR compliance in body and extremity use configurations described in the following subsections.

## **6.1 Body Exposure Condition**

For Close to Body mode(1g Body SAR) the EUT is set 10mm away from the phantom, the test distance is 10mm.


## **6.2 Extremity Exposure Condition**

For Hand-held mode (10g Extremity SAR) the EUT (Equipment Under Test) is set directly against the phantom, the test distance is 0mm.



# 7 MEASUREMENT PROCEDURE

# 7.1 Measurement Process Diagram





## 7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Boththe probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz			
Maximum distance from	closest meas	surement point	5±1 mm	½·δ·ln(2)±0.5 mm			
(geometric center of prob	e sensors) t	o phantom surface	S±1 IIIIII	/2·0·111(2)±0.5 111111			
Maximum probe angle from	om probe ax	is to phantom surface	30°±1°	20°±1°			
normal at the measurement	ent location		30 ±1	20 11			
			≤ 2 GHz: ≤ 15 mm	3–4 GHz: ≤ 12 mm			
			2 – 3 GHz: ≤ 12 mm	4 – 6 GHz: ≤ 10 mm			
			When the x or y dimension of t	the test device, in the			
Maximum area scan spat	tial resolution	n: Δx Area , Δy Area	measurement plane orientation	n, is smaller than the above,			
			the measurement resolution m	ust be ≤ the corresponding x or			
			y dimension of the test device	with at least one measurement			
			point on the test device.				
Maximum zoom scan spa	atial recolution	on: Av Zoom Av Zoom	≤ 2 GHz: ≤ 8 mm	3–4 GHz: ≤ 5 mm*			
waxiinum 200m scan spa	aliai resolulio	л. дх 200т, ду 200т	2 –3 GHz: ≤ 5 mm*	4 – 6 GHz: ≤ 4 mm*			
				3–4 GHz: ≤ 4 mm			
	unifor	m grid: Δz Zoom (n)	≤ 5 mm	4–5 GHz: ≤ 3 mm			
Massinas um magna accum				5–6 GHz: ≤ 2 mm			
Maximum zoom scan spatial resolution,		Δz Zoom (1): between		3–4 GHz: ≤ 3 mm			
normal to phantom		1st two points closest	≤ 4 mm	4–5 GHz: ≤ 2.5 mm			
surface	graded	to phantom surface		5–6 GHz: ≤ 2 mm			
	grid	Δz Zoom (n>1):					
		between subsequent	≤ 1.5·Δz 2	Zoom (n-1)			
		points					
Minimum =====				3–4 GHz: ≥ 28 mm			
Minimum zoom scan volume		x, y, z	≥30 mm	4–5 GHz: ≥ 25 mm			
Jean volume				5–6 GHz: ≥ 22 mm			

#### Note:

- 1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.
- \* When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.



#### 7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm \* 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 \* 30 \* 30 mm or 32 \* 32 \*32 mm is assessed by measuring 5 or 8 \* 5 or 8\*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

#### 7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.



# **8 CONDUCTED RF OUPUT POWER**

# 8.1 2.4G ISM Band (GFSK modulation)

# 8.1.1 2.4G ISM Band (GFSK modulation)

Band	Channal	Frequency	Peak power	Tune-up Limit
(GHz)	Channel	(MHz)	(dBm)	power (dBm)
2.4G ISM Band	Low	2405	23.21	24.00
(2.405~2.473)	Middle	2441	23.17	24.00
(2.405~2.473)	High	2473	23.10	24.00



# 9 ANTENNA LOCATION PHOTOS

Please refer the document "BL-SZ1970622-AS.pdf".



# 9.1 TEST RESULT

# 9.2 2.4G ISM Band Extremity SAR ( 10g )

Mode Extremity (	Band- width (MHz)	Antenna status	DUT Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10 g Meas. SAR (W/kg)	Meas. Power (dBm)	Max. tune- up power (dBm)	Scaling Factor	10g Scaled SAR (W/kg)	Meas. No.
2.4G	1.25	75°	Back Side	0	Low	2405	-0.01	0.038	23.21	24.00	1.199	0.046	1#
ISM Band	1.25	180°	Back Side	0	Low	2405	0.12	0.580	23.21	24.00	1.199	0.695	2#

# 9.3 2.4G ISM Band Body SAR (1g)

Mode	Band- width (MHz)	Antenna status	DUT Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1 g Meas. SAR (W/kg)	Meas. Power (dBm)	Max. tune- up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
2.4G	1.25	75°	Back Side	10	Low	2405	0.05	0.042	23.21	24.00	1.199	0.050	3#
ISM Band	1.25	180°	Back Side	10	Low	2405	-0.15	0.357	23.21	24.00	1.199	0.428	4#



## 10 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are  $\leq 1.45$  W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is  $\leq 1.10$ , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

#### SAR repeated measurement procedure:

- 1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
- 2. When the highest measured SAR is >= 0.80 W/kg, repeat that measurement once.
- 3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20, or when the original or repeated measurement is >= 1.45 W/kg, perform a second repeated measurement.
- 4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20, and the original, first or second repeated measurement is >= 1.5 W/kg, perform a third repeated measurement.

#### Note:

The highest 10g measure is 0.580 W/Kg, which is < 2.0 W/kg, so repeated measurement is not required.

The highest 1g measure is 0.357 W/Kg, which is < 0.80 W/kg, so repeated measurement is not required.



# 11 SIMULTANEOUS TRANSMISSION

Note: The product has only one antenna for 2.4G ISM Band, so simultaneous transmission evaluation is not required in this report.



## 12 TEST EQUIPMENTS LIST

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
PC	Dell	N/A	N/A	N/A	N/A
2450MHz Validation Dipole	Speag	D2450V2	SN: 952	2017/03/21	2020/03/20
E-Field Probe	Speag	EX3DV4	SN: 7510	2019/08/02	2020/08/01
Data Acquisition Electronics	Speag	DAE4	SN: 1454	2019/08/02	2020/08/01
Signal Generator	R&S	SMBV100A	260592	2019/06/13	2020/06/12
Power Meter	Agilent	E4419B	GB40201833	2018/11/01	2019/10/31
Power Sensor	Agilent	E9300A	MY41498012	2018/11/01	2019/10/31
Power Sensor	Agilent	E9300A	MY41499891	2018/11/01	2019/10/31
Network Analyzer	R&S	ZVL-6	101380	2019/06/20	2020/06/19
Thermometer	Elitech	RC-4HC	N/A	2018/11/05	2019/11/04
Power Amplifier	SATIMO	6552B	22374	N/A	N/A
Dielectric Probe Kit	SATIMO	SCLMP	SN 25/13 OCPG56	N/A	N/A
Phantom1	Speag	SAM	SN: 1859	N/A	N/A
Phantom2	Speag	SAM	SN: 1857	N/A	N/A
Attenuator	COM-MW	ZA-S1-31	1305003187	N/A	N/A
Directional coupler	AA-MCS	AAMCS-UDC	000272	N/A	N/A

Note: For dipole antennas, BALUN has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

- 1. There is no physical damage on the dipole;
- 2. System validation with specific dipole is within 10% of calibrated value;
- 3. Return-loss in within 20% of calibrated measurement.
- 4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.



# ANNEX A SIMULATING LIQUID VERIFICATION RESULT

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an SCLMP Dielectric Probe Kit.

Date	Liquid Type	Fre. (MHz)	Temp. (°C)	Meas. Conductivity (σ) (S/m)	Meas. Permittivity (ε)	Target Conductivity (σ) (S/m)	Target Permittivity (ε)	Conductivity Tolerance (%)	Permittivity Tolerance (%)
2019.09.18	Head	2450	21.1	1.78	40.11	1.80	39.20	-1.11	2.32

Note1: The tolerance limit of Conductivity and Permittivity is± 5%.

Note2: According to April 2019 TCB workshop, FCC accept SAR testing with IEC tissue parameters, so this product used IEC tissue parameters to perform SAR testing.



## ANNEX B SYSTEM CHECK RESULT

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 %(for 1 g and 10 g).

#### System check for 10 g

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)	Targeted SAR(W/kg)	Tolerance (%)
2019.09.18	Head	2450	100	2.29	22.90	24.30	-5.76	24.00	4.58

Note1: The tolerance limit of System validation ±10%.

Note2: According to April 2019 TCB workshop, FCC accept SAR testing with IEC tissue parameters, so this product used IEC tissue parameters to perform SAR testing.

#### System check for 1 g

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)	Targeted SAR(W/kg)	Tolerance (%)
2019.09.18	Head	2450	100	5.06	50.60	52.40	-3.44	52.40	-3.44

Note1: The tolerance limit of System validation ±10%.

Note2: According to April 2019 TCB workshop, FCC accept SAR testing with IEC tissue parameters, so this product used IEC tissue parameters to perform SAR testing.



# System Performance Check Data (2450MHz Head)

Date: 2019.09.18

Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Duty Cycle: 1:1 Medium parameters used: f = 2450 MHz;  $\sigma = 1.782$  S/m;  $\epsilon_r = 40.109$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature:22.6 Liquid Temperature:21.1

#### DASY5 Configuration:

- Probe: EX3DV4 SN7510; ConvF(7.81, 7.81, 7.81); Calibrated: 2019.08.02;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2019.08.02
- Phantom: SAM (30deg probe tilt) with CRP v5.0 left 1859; Type: QD000P40CD; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)


**CW2450 Head 100mw/Area Scan (101x101x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 5.78 W/kg

CW2450 Head 100mw/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.72 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 11.1 W/kg

SAR(1 g) = 5.06 W/kg; SAR(10 g) = 2.29 W/kg Maximum value of SAR (measured) = 5.73 W/kg



0 dB = 5.73 W/kg



## ANNEX C TEST DATA

#### MEAS.1 Body Plane with Back Side 0mm on Low Channel in 2.4G DTS mode with Antenna 75°

Date: 2019.09.18

Communication System Band: 2.4G; Frequency: 2405 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): f = 2405 MHz;  $\sigma$  = 1.735 S/m;  $\epsilon_r$  = 40.352;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature:22.6 Liquid Temperature:21.1

#### **DASY5** Configuration:

Probe: EX3DV4 - SN7510; ConvF(7.81, 7.81, 7.81); Calibrated: 2019.08.02;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1454; Calibrated: 2019.08.02

Phantom: SAM (30deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CD; Serial: TP:1859

• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (81x101x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.0458 W/kg


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.242 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.0520 W/kg

SAR(1 g) = 0.049 W/kg; SAR(10 g) = 0.038 W/kg

Maximum value of SAR (measured) = 0.051 W/kg



0 dB = 0.051 W/kg



#### MEAS.2 Body Plane with Back Side 0mm on Low Channel in 2.4G DTS mode Antenna unfold 180°

Date: 2019.09.18

Communication System Band: 2.4G; Frequency: 2405 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): f = 2405 MHz;  $\sigma$  = 1.735 S/m;  $\epsilon_r$  = 40.352;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature:22.6 Liquid Temperature:21.1

#### DASY5 Configuration:

Probe: EX3DV4 - SN7510; ConvF(7.81, 7.81, 7.81); Calibrated: 2019.08.02;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1454; Calibrated: 2019.08.02

Phantom: SAM (30deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CD; Serial: TP:1859

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (81x101x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm


Maximum value of SAR (interpolated) = 1.48 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.197 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 2.44 W/kg

SAR(1 g) = 1.21 W/kg; SAR(10 g) = 0.580 W/kg Maximum value of SAR (measured) = 1.36 W/kg



0 dB = 1.36 W/kg



#### MEAS.3 Body Plane with Back Side 10mm on Low Channel in 2.4G DTS mode Antenna 75°

Date: 2019.09.18

Communication System Band: 2.4G; Frequency: 2405 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): f = 2405 MHz;  $\sigma$  = 1.735 S/m;  $\epsilon_r$  = 40.352;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature:22.6 Liquid Temperature:21.1

#### DASY5 Configuration:

Probe: EX3DV4 - SN7510; ConvF(7.81, 7.81, 7.81); Calibrated: 2019.08.02;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1454; Calibrated: 2019.08.02

Phantom: SAM (30deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CD; Serial: TP:1859

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (81x101x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm


Maximum value of SAR (interpolated) = 0.0397 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.130 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.0530 W/kg

SAR(1 g) = 0.042 W/kg; SAR(10 g) = 0.036 W/kg Maximum value of SAR (measured) = 0.0402 W/kg



0 dB = 0.0402 W/kg



#### MEAS.4 Body Plane with Back Side 10mm on Low Channel in 2.4G DTS mode Antenna unfold 180°

Date: 2019.09.18

Communication System Band: 2.4G; Frequency: 2405 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): f = 2405 MHz;  $\sigma$  = 1.735 S/m;  $\epsilon_r$  = 40.352;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature:22.6 Liquid Temperature:21.1

#### DASY5 Configuration:

Probe: EX3DV4 - SN7510; ConvF(7.81, 7.81, 7.81); Calibrated: 2019.08.02;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1454; Calibrated: 2019.08.02

Phantom: SAM (30deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CD; Serial: TP:1859

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (81x101x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm


Maximum value of SAR (interpolated) = 0.400 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.064 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.624 W/kg

SAR(1 g) = 0.357 W/kg; SAR(10 g) = 0.194 W/kg Maximum value of SAR (measured) = 0.389 W/kg



0 dB = 0.389 W/kg



## ANNEX D EUT EXTERNAL PHOTOS

Please refer the document "BL-SZ1970622-AW.pdf".

# ANNEX E SAR TEST SETUP PHOTOS

Please refer the document "BL-SZ1970622-AS.pdf".

## ANNEX F CALIBRATION REPORT

Please refer the document "CALIBRATION REPORT.pdf".

--END OF REPORT--