

FCC TEST REPORT FCC ID: 2AIEGS1PRO

Product : Alarm Clock Radio Speaker System

Model Name : S1pro

Brand : N/A

Report No. : PTC801186160622E-FC03

Prepared for

All Best Technology Limited

No.9, Yincheng 1st Rd., Xiabian Village, Chang'an Town,

Dongguan City, Guangdong Province, China

Prepared by

DongGuan Precise Testing Service Co.,Ltd.

Building D, Baoding Technology Park, Guangming Road 2, Guangming Community

Dongcheng District, Dongguan, Guangdong, China



TEST RESULT CERTIFICATION

Applicant's name : All Best Technology Limited

Address No.9, Yincheng 1st Rd., Xiabian Village, Chang'an Town, Dongguan

City, Guangdong Province, China

Manufacture's name : All Best Technology Limited

Address No.9, Yincheng 1st Rd., Xiabian Village, Chang'an Town, Dongguan

City, Guangdong Province, China

Product name : Alarm Clock Radio Speaker System

Model name : S1pro

Standards : FCC CFR47 Part 1.1307(b)(1)

Test procedure KDB 447498 D01 General RF Exposure Guidance v05

Test Date : Jun.24. 2016 ~ Jul.14. 2016

Date of Issue : Jul.15. 2016

Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Testing Engineer

August Qiu

Technical Manager

Hack Ye

Authorized Signatory

Chris Du



Contents

			Page	
2	TES	T SUMMARY	4	
3	GEN	GENERAL INFORMATION		
	3.1	GENERAL DESCRIPTION OF EUT	5	
4	RF E	EXPOSURE	6	
	4.1	REQUIREMENTS	6	
	4.2	THE PROCEDURES / LIMIT	6	



2 Test Summary

Test Items	Test Requirement	Result					
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS					
Remark:							
N/A: Not Applicable							



3 General Information

3.1 General Description of EUT

	1	
Product Name		Alarm Clock Radio Speaker System
Model Name		S1pro
Model Description		N/A
Bluetooth Version		V4.0
Operating frequency		2402-2480MHz, 79 channels
Max. RF output power		0.79dBm
Type of Modulation	:	GFSK, Pi/4 DQPSK,8DPSK
Antenna installation:		PCB printed antenna
Antenna Gain:		0.79dBi
Power supply		AC 100-240V 50/60Hz 0.65A Max power by adapter
Adapter		Input AC 100-240V 50/60Hz 0.65A Max, Output 5V 3A



4 RF Exposure

Test Requirement : FCC Part 1.1307

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v05

4.1 Requirements

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [$\sqrt{f(GHz)}$] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR where

- 1. f(GHz) is the RF channel transmit frequency in GHz
- 2. Power and distance are rounded to the nearest mW and mm before calculation
- 3. The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

4.2 The procedures / limit

Conducted Peak power(dBm)	Conducted Peak power(mW)	Minimum test separation distance required for the exposure conditions (mm)	Calculation Value (Note 1)	SAR Test Exclusion Thresholds(mW)
0.79	1.1995	5	0.372	3

The turn up power is 0.79±1dBm.

Remark: Max. duty factor is 100%

Note 1 : Calculation Value = [(max. power of channel, mW)/(min. test separation distance,

mm)] $\cdot [\sqrt{f(GHz)}]$. Fox example: 1.1995/5* $\sqrt{2.402}$ = 0.372 \leq 3.0

Note 2: According to KDB447498 D01 V05, threshold at which no SAR required is ≤3.0 for 1-g SAR, separation distance is 5mm, and no simultaneous SAR measurement is required

*****THE END REPORT*****