

FCC Report (GSM&WCDMA)

Applicant: SHENZHEN XINYI DIGITAL TECHNOLOGY CO.,LTD

Address of Applicant: 4th Floor,2nd Building,BaiShiXia Xintang Industry, Fuyong Street,Bao'an District, Shenzhen, China

Equipment Under Test (EUT)

Product Name: Smart Watch

Model No.: X01, X02, X03, X04, X05, X06, X07, X08, X09, X01(S), X02(S), X03(S), X04(S), X05(S), X06(S), X07(S), X08(S), X09(S), X(Series)

FCC ID: 2AIFM-X01

Applicable standards: FCC CFR Title 47 Part 2: 2015

FCC CFR Title 47 Part22 Subpart H: 2015

FCC CFR Title 47 Part24 Subpart E: 2015

Date of sample receipt: May 17, 2016

Date of Test: May 18-27, 2016

Date of report issued: May 30, 2016

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo

Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS or testing done by GTS in connection with, distribution or use of the product described in this report must be approved by GTS in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	May 30, 2016	Original

Prepared By:

Zhongwei Pan

Date:

May 30, 2016

Project Engineer

Check By:

Andy Wu

Date:

May 30, 2016

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 RELATED SUBMITTAL(S) / GRANT (S)	7
5.4 TEST METHODOLOGY.....	7
5.5 TEST FACILITY.....	7
5.6 TEST LOCATION.....	7
6 TEST INSTRUMENTS LIST	8
7 SYSTEM TEST CONFIGURATION	9
7.1 TEST MODE	9
7.2 CONFIGURATION OF TESTED SYSTEM	10
7.3 CONDUCTED PEAK OUTPUT POWER	11
7.4 OCCUPY BANDWIDTH.....	13
7.5 MODULATION CHARACTERISTIC.....	20
7.6 OUT OF BAND EMISSION AT ANTENNA TERMINALS.....	20
7.7 ERP, EIRP MEASUREMENT	29
7.8 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT.....	36
7.9 FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT.....	41
7.10 FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT	45
8 TEST SETUP PHOTO	47
9 EUT CONSTRUCTIONAL DETAILS	48

4 Test Summary

Test Item	Section in CFR 47	Result
RF Exposure (SAR)	Part 1.1307 Part 2.1093	Pass* (Please refer to SAR Report)
RF Output Power	Part 2.1046 Part 22.913 (a)(2) Part 24.232 (c)	Pass
Modulation Characteristics	Part 2.1047	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917 Part 24.238	Pass
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 22.917 (a) Part 24.238 (a)	Pass
Field Strength of Spurious Radiation	Part 2.1053 Part 22.917 (a) Part 24.238 (a)	Pass
Out of band emission, Band Edge	Part 22.917 (a) Part 24.238 (a)	Pass
Frequency stability vs. temperature	Part 2.1055(a)(1)(b)	Pass
Frequency stability vs. voltage	Part 2.1055(d)(1)(2)	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	SHENZHEN XINYI DIGITAL TECHNOLOGY CO.,LTD
Address of Applicant:	4th Floor,2nd Building,BaiShiXia Xintang Industry, Fuyong Street,Bao'an District, Shenzhen, China
Manufacturer:	SHENZHEN XINYI DIGITAL TECHNOLOGY CO.,LTD
Address of Manufacturer:	4th Floor,2nd Building,BaiShiXia Xintang Industry, Fuyong Street,Bao'an District, Shenzhen, China

5.2 General Description of EUT

Product Name:	Smart Watch
Model No.:	X01, X02, X03, X04, X05, X06, X07, X08, X09, X01(S), X02(S), X03(S), X04(S), X05(S), X06(S), X07(S), X08(S), X09(S), X(Series)
Support Networks:	GSM, GPRS, WCDMA
Support Bands:	GSM850, PCS1900, Band V
TX Frequency:	GSM850: 824.20MHz-848.80MHz PCS1900: 1850.20MHz-1909.80MHz WCDMA Band V: 826.40MHz-846.60MHz
GRPS Class:	12
Modulation type:	GSM/GPRS: GMSK WCDMA Band V: QPSK
Hardware Version:	Android 4.4
Software Version:	V1.3
Antenna type:	PIFA antenna
Antenna gain:	1.0dBi
Power supply:	DC 3.7V 600mAh Li-ion Battery

Operation Frequency List:

GSM 850		PCS1900		WCDMA Band V	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
128	824.20	512	1850.20	4132	826.40
129	824.40	513	1850.40	4133	826.60
⋮	⋮	⋮	⋮	⋮	⋮
189	836.40	660	1879.80	4181	836.20
190	836.60	661	1880.00	4182	836.40
191	836.80	662	1880.20	4183	836.60
⋮	⋮	⋮	⋮	⋮	⋮
250	848.60	809	1909.60	4232	846.40
251	848.80	810	1909.80	4233	846.60

Regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Final test channel:

GSM 850		PCS1900		WCDMA Band V	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
128	824.20	512	1850.20	4132	826.40
190	836.60	661	1880.00	4183	836.60
251	848.80	810	1909.80	4233	846.60

5.3 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is filing to comply with Section Part 22 subpart H and Part 24 subpart E of the FCC CFR 47 Rules.

5.4 Test Methodology

Both conducted and radiated testing were performed according to the procedures document on TIA/EIA 603 and FCC CFR 47.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055 and 2.1057

5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 28, 2013.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, June 26, 2013.

5.6 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China

Tel: 0755-27798480

Fax: 0755-27798960

6 Test Instruments list

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 26 2016	Mar. 25 2017
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June 30 2015	June 29 2016
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June 30 2015	June 29 2016
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 26 2015	June 25 2016
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 26 2016	Mar. 25 2017
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	Mar. 27 2016	Mar. 26 2017
9	Coaxial Cable	GTS	N/A	GTS211	Mar. 27 2016	Mar. 26 2017
10	Coaxial cable	GTS	N/A	GTS210	Mar. 27 2016	Mar. 26 2017
11	Coaxial Cable	GTS	N/A	GTS212	Mar. 27 2016	Mar. 26 2017
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June 30 2015	June 29 2016
13	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	June 30 2015	June 29 2016
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 26 2015	June 25 2016
15	Band filter	Amindeon	82346	GTS219	Mar. 27 2016	Mar. 26 2017
16	Universal radio communication tester	Rohde & Schwarz	CMU200	GTS235	May 07 2016	May 06 2017
17	Signal Generator	Rohde & Schwarz	SML03	GTS236	May 07 2016	May 06 2017
18	Temp. Humidity/ Barometer	Oregon Scientific	BA-888	GTS248	May 07 2016	May 06 2017
19	D.C. Power Supply	Instek	PS-3030	GTS232	NA	NA
20	Splitter	Agilent	11636B	GTS237	May 07 2016	May 06 2017
21	Power meter	Rohde & Schwarz	NRVS	GTS238	May 07 2016	May 06 2017
22	Spectrum Analyzer	Agilent	E4440A	GTS533	Dec. 03 2015	Dec. 02 2016
23	Temp.&Humidity chamber	Chuang wei	GDS-225	GTS005-1	May 05 2016	May 06 2017
24	Highpass filter	Micro-Tronics	HPM50108	GTS549	Mar. 27 2016	Mar. 26 2017
25	Highpass filter	Micro-Tronics	HPM50111	GTS550	Mar. 27 2016	Mar. 26 2017

7 System test configuration

7.1 Test mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Test modes		
Band	Radiated	Conducted
GSM 850	■ GSM link ■ GPRS 1 link	■ GSM link ■ GPRS 1 link
PCS 1900	■ GSM link ■ GPRS 1 link	■ GSM link ■ GPRS 1 link
WCDMA Band V	■ RMC 12.2Kbps link	■ RMC 12.2Kbps link


Note: The maximum power levels are GSM mode for GMSK link, GPRS multi-slot class 4 mode for GMSK link, RMC12.2Kbps mode for WCDMA Band V. only these modes were used for all tests.

The conducted power tables are as follows:


Conducted Power (dBm)						
Band	GSM850			PCS1900		
Channel	128	190	251	512	661	810
Frequency	824.20	836.60	848.80	1850.20	1880.00	1909.80
GSM (GMSK, 1 TX slot)	32.49	32.67	32.53	28.69	28.77	28.58
GPRS (GMSK, 1 TX slot)	32.43	32.65	32.54	28.67	28.78	28.54
GPRS (GMSK, 2 TX slot)	31.55	31.56	31.46	27.59	27.73	27.44
GPRS (GMSK, 3 TX slot)	30.51	30.62	30.47	26.50	26.43	26.58
GPRS (GMSK, 4 TX slot)	29.45	29.53	29.44	25.42	25.41	25.47

Conducted Power (dBm)			
Band	WCDMA Band V		
Channel	4132	4183	4233
Frequency	826.4	836.6	846.6
RMC 12.2Kbps	23.41	23.49	23.34
HSDPA Subtest-1	22.33	22.48	22.57
HSDPA Subtest-2	22.15	22.37	22.47
HSDPA Subtest-3	22.08	22.21	22.31
HSDPA Subtest-4	22.01	22.04	22.15
HSUPA Subtest-1	22.45	22.53	22.54
HSUPA Subtest-2	22.42	22.37	22.42
HSUPA Subtest-3	22.21	22.30	22.17
HSUPA Subtest-4	22.15	22.23	22.11
HSUPA Subtest-5	21.89	21.97	22.01
AMR	23.42	23.51	23.43

7.2 Configuration of Tested System



7.3 Conducted Peak Output Power

Test Requirement:	FCC part22.913(a) and FCC part24.232(b)
Test Method:	FCC part2.1046
Limit:	GSM850,: 7W PCS1900, WCDMA Band V: 2W
Test setup:	 <p><i>Note: Measurement setup for testing on Antenna connector</i></p>
Test Procedure:	<ol style="list-style-type: none"> 1. The transmitter output port was connected to base station. 2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement. 3. Set EUT at maximum power through base station. 4. Select lowest, middle, and highest channels for each band and different modulation. 5. Measure the maximum burst average power.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement Data

EUT Mode	Channel	Frequency (MHz)	PK power (dBm)
GSM 850 (GSM link)	128	824.20	32.49
	190	836.60	32.67
	251	848.80	32.53
GSM 850 (GPRS 1 link)	128	824.20	32.43
	190	836.60	32.65
	251	848.80	32.54
PCS 1900 (GSM link)	512	1850.20	28.69
	661	1880.00	28.77
	810	1909.80	28.58
PCS 1900 (GPRS 1 link)	512	1850.20	28.67
	661	1880.00	28.78
	810	1909.80	28.54
WCDMA Band V (RMC 12.2Kbps link)	4132	826.40	23.41
	4183	836.60	23.49
	4233	846.60	23.34

7.4 Occupy Bandwidth

Test Requirement:	FCC part22.913(a) and FCC part24.232(b)
Test Method:	FCC part2.1049
Test setup:	<p><i>Note: Measurement setup for testing on Antenna connector</i></p>
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer 2. RBW was set to about 1% of emission BW, VBW= 3 times RBW. 3. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement Data

EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (KHz)	-26dB bandwidth (KHz)
GSM 850 (GSM link)	128	824.20	245.009	317.674
	190	836.60	248.983	316.966
	251	848.80	246.717	316.855
GSM 850 (GPRS 1 link)	128	824.20	246.178	306.617
	190	836.60	246.421	314.357
	251	848.80	248.189	319.579
PCS 1900 (GSM link)	512	1850.20	246.943	319.855
	661	1880.00	246.694	325.285
	810	1909.80	244.118	324.335
PCS 1900 (GPRS 1 link)	512	1850.20	244.106	319.991
	661	1880.00	245.283	314.206
	810	1909.80	246.103	308.234
WCDMA Band V (RMC 12.2Kbps link)	4132	826.40	4204.80	4778.00
	4183	836.60	4185.20	4736.00
	4233	846.60	4151.20	4765.00

Test plot as follows:

Test band: **GSM 850 (GSM link)**

Lowest channel

Middle channel

Highest channel

Lowest channel (824.2 MHz):

- Ch Freq: 824.2 MHz
- Occupied Bandwidth: 245.0093 kHz
- Transmit Freq Error: 1.267 kHz
- x dB Bandwidth: 317.674 kHz

Middle channel (836.6 MHz):

- Ch Freq: 836.6 MHz
- Occupied Bandwidth: 248.9832 kHz
- Transmit Freq Error: 1.274 kHz
- x dB Bandwidth: 316.366 kHz

Highest channel (848.8 MHz):


- Ch Freq: 848.8 MHz
- Occupied Bandwidth: 246.7170 kHz
- Transmit Freq Error: 80.334 Hz
- x dB Bandwidth: 316.855 kHz

Copyright 2000-2009 Agilent Technologies


Test band:	GSM 850 (GPRS 1 link)
------------	-----------------------



Lowest channel



Middle channel




Highest channel


Test band:	PCS 1900 (GSM link)
------------	---------------------



Lowest channel



Middle channel



Highest channel

Test band:

PCS 1900 (GPRS 1 link)



Lowest channel




Middle channel




Highest channel

Test band:


WCDMA Band V (RMC 12.2Kbps link)



Lowest channel



Middle channel



Highest channel

7.5 MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

7.6 Out of band emission at antenna terminals



Test Requirement:	FCC part22.917(a) and FCC part24.238(a)
Test Method:	FCC part2.1051
Limit:	-13dBm
Test setup:	<pre> graph LR EUT[EUT] --- Splitter[Splitter] Splitter --- CommTester[Communication Tester] Splitter --- Filter[Filter] Filter --- SPA[SPA] </pre>
<p><i>Note: Measurement setup for testing on Antenna connector</i></p>	
Test Procedure:	<ol style="list-style-type: none"> 1 The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. 2 The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic. 3 For the out of band: Set the RBW, VBW = 1MHz, Start=30MHz, Stop= 10th harmonic. 4 Band Edge Requirements: In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Test plot as follows:



Note: During the conducted spurious emission test, a band filter was used. The information of the filter is reported at section 6.0 (refer to item 24, 25).

Test Mode: Traffic mode



GSM 850 (GSM link)



Lowest channel





Middle channel





Highest channel

Test Mode: Traffic mode



GSM 850 (GPRS 1 link)



Lowest channel





Middle channel





Highest channel

Test Mode: Traffic mode



PCS1900 (GSM link)



Lowest channel





Middle channel





Highest channel

Test Mode: Traffic mode



PCS1900 (GPRS 1 link)



Lowest channel





Middle channel





Highest channel

Test Mode: Traffic mode



WCDMA Band V (RMC 12.2Kbps link)



Lowest channel





Middle channel




Highest channel




Band Edge:







7.7 ERP, EIRP Measurement

Test Requirement:	FCC part22.913(a) and FCC part24.232(b)
Test Method:	FCC part2.1046
Limit:	GSM850 7W ERP PCS1900 2W EIRP
Test setup:	<p>Below 1GHz</p>  <p>Above 1GHz</p>  <p>Substituted method:</p> 

Test Procedure:	<ol style="list-style-type: none">1. The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer.2. During the measurement, the EUT was communication with the station. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna from 4m to 1m. The reading was recorded and the field strength (E in dBuV/m) was calculated.3. ERP in frequency band 824.2 –848.80.8MHz were measured using a substitution method. The EUT was replaced by dipole antenna connected, the S.G. output was recorded and ERP was calculated as follows: $\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable Loss (dB)}$4. EIRP in frequency band 1850.2 –1909.8MHz were measured using a substitution method. The EUT was replaced by or horn antenna connected, the S.G. output was recorded and EIRP was calculated as follows: $\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement Data

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (GSM link)	Lowest	H	V	32.20	38.45	Pass
			H	29.12		
		E1	V	23.79		
			H	29.35		
		E2	V	22.91		
			H	27.04		
	Middle	H	V	32.19	38.45	Pass
			H	29.11		
		E1	V	23.87		
			H	29.47		
		E2	V	24.58		
			H	27.62		
	Highest	H	V	32.61	38.45	Pass
			H	28.88		
		E1	V	23.85		
			H	28.40		
		E2	V	22.74		
			H	28.16		




EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (GPRS 1 link)	Lowest	H	V	31.83	38.45	Pass
			H	28.72		
		E1	V	23.37		
			H	28.90		
		E2	V	22.44		
			H	26.54		
	Middle	H	V	31.73	38.45	Pass
			H	28.60		
		E1	V	23.32		
			H	28.90		
		E2	V	24.07		
			H	27.08		
	Highest	H	V	32.15	38.45	Pass
			H	28.40		
		E1	V	23.35		
			H	27.87		
		E2	V	22.33		
			H	27.72		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (GSM link)	Lowest	H	V	28.42	33.01	Pass
			H	25.65		
		E1	V	20.88		
			H	25.87		
		E2	V	20.09		
			H	23.78		
	Middle	H	V	28.46	33.01	Pass
			H	25.70		
		E1	V	21.01		
			H	26.03		
		E2	V	21.64		
			H	24.36		
	Highest	H	V	28.94	33.01	Pass
			H	25.59		
		E1	V	21.09		
			H	25.16		
		E2	V	20.10		
			H	24.95		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (GPRS 1 link)	Lowest	H	V	27.96	33.01	Pass
			H	25.16		
		E1	V	20.34		
			H	25.30		
		E2	V	19.48		
			H	23.14		
	Middle	H	V	27.87	33.01	Pass
			H	25.02		
		E1	V	20.29		
			H	25.27		
		E2	V	20.97		
			H	23.66		
	Highest	H	V	28.36	33.01	Pass
			H	24.97		
		E1	V	20.44		
			H	24.47		
		E2	V	19.57		
			H	24.39		

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
WCDMA Band V	Lowest	H	V	21.00	38.45	Pass
			H	18.55		
		E1	V	14.66		
			H	17.74		
		E2	V	13.14		
			H	15.30		
	Middle	H	V	19.46	38.45	Pass
			H	16.41		
		E1	V	12.46		
			H	15.55		
		E2	V	13.62		
			H	15.09		
	Highest	H	V	18.45	38.45	Pass
			H	15.59		
		E1	V	11.89		
			H	14.32		
		E2	V	12.87		
			H	15.84		

7.8 Field strength of spurious radiation measurement

Test Requirement:	FCC part22.917(a) and FCC part24.238(a)
Test Method:	FCC part2.1053
Limit:	-13dBm
Test setup:	<p>Below 1GHz</p>  <p>Above 1GHz</p> 
Substituted method:	

Test Procedure:	<ol style="list-style-type: none">1. The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer.2. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.3. The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission was identified, the power of the emission was determined using the substitution method.4. The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency. $\text{ERP / EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain(dB/dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement Data

Test mode:	GSM850		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1648.40	Vertical	-36.00	-13.00	Pass
2472.60	V	-38.73		
3296.80	V	-40.99		
4121.00	V	-43.15		
4945.20	V	---		
1648.40	Horizontal	-41.23		
2472.60	H	-45.10		
3296.80	H	-46.67		
4121.00	H	-49.40		
4945.20	H	---		
Test mode:	GSM850		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1673.20	Vertical	-37.35	-13.00	Pass
2509.80	V	-39.63		
3346.40	V	-41.52		
4183.00	V	-43.33		
5019.60	V	---		
1673.20	Horizontal	-41.72		
2509.80	H	-44.94		
3346.40	H	-46.25		
4183.00	H	-48.53		
5019.60	H	---		
Test mode:	GSM850		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1697.60	Vertical	-37.58	-13.00	Pass
2546.40	V	-39.61		
3395.20	V	-41.28		
4244.00	V	-42.89		
5092.80	V	---		
1697.60	Horizontal	-41.47		
2546.40	H	-44.34		
3395.20	H	-45.50		
4244.00	H	-47.52		
5092.80	H	---		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	PCS1900		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3700.40	Vertical	-36.88	-13.00	Pass
5550.60	V	-39.27		
7400.80	V	-41.25		
9251.00	V	-43.14		
11101.20	V	---		
3700.40	Horizontal	-41.47		Pass
5550.60	H	-44.85		
7400.80	H	-46.21		
9251.00	H	-48.59		
11101.20	H	---		
Test mode:	PCS1900		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3760.00	Vertical	-34.51	-13.00	Pass
5640.00	V	-36.99		
7520.00	V	-39.03		
9400.00	V	-41.00		
11280.00	V	---		
3760.00	Horizontal	-39.27		Pass
5640.00	H	-42.76		
7520.00	H	-44.18		
9400.00	H	-46.65		
11280.00	H	---		
Test mode:	PCS1900		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3819.60	Vertical	-35.73	-13.00	Pass
5729.40	V	-38.13		
7639.20	V	-40.11		
9549.00	V	-42.01		
11458.80	V	---		
3819.60	Horizontal	-40.33		Pass
5729.40	H	-43.73		
7639.20	H	-45.09		
9549.00	H	-47.48		
11458.80	H	---		

Remark:


1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	WCDMA Band V		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1652.80	Vertical	-37.18	-13.00	Pass
2479.20	V	-40.93		
3305.60	V	-43.67		
4132.00	V	-41.21		
4958.40	V	---		
1652.80	Horizontal	-39.99		Pass
2479.20	H	-42.70		
3305.60	H	-48.12		
4132.00	H	-51.76		
4958.40	H	---		
Test mode:	WCDMA Band V		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1672.80	Vertical	-39.25	-13.00	Pass
2509.20	V	-40.56		
3345.60	V	-44.19		
4182.00	V	-46.66		
5018.40	V	---		
1672.80	Horizontal	-41.71		Pass
2509.20	H	-43.63		
3345.60	H	-48.33		
4182.00	H	-50.73		
5018.40	H	---		
Test mode:	WCDMA Band V		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1693.20	Vertical	-37.78	-13.00	Pass
2539.80	V	-40.22		
3386.40	V	-42.85		
4233.00	V	-45.75		
5079.60	V	---		
1693.20	Horizontal	-41.14		Pass
2539.80	H	-43.57		
3386.40	H	-44.95		
4233.00	H	-51.14		
5079.60	H	---		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

7.9 Frequency stability V.S. Temperature measurement

Test Requirement:	FCC Part2.1055(a)(1)(b)
Test Method:	FCC Part2.1055(a)(1)(b)
Limit:	2.5ppm
Test setup:	<p style="text-align: center;">Temperature Chamber</p>  <p style="text-align: center;">Note : Measurement setup for testing on Antenna connector</p>
Test procedure:	<ol style="list-style-type: none"> 1. The equipment under test was connected to an external DC power supply and input rated voltage. 2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to -20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement Data


Reference Frequency: GSM850 (GSM link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	37	0.0445	2.5	Pass
	-20	41	0.0494		
	-10	36	0.0429		
	0	30	0.0364		
	10	35	0.0412		
	20	30	0.0364		
	30	47	0.0559		
	40	43	0.0510		
	50	41	0.0494		

Reference Frequency: GSM850 (GPRS 1 link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	40	0.0484	2.5	Pass
	-20	47	0.0567		
	-10	39	0.0467		
	0	33	0.0399		
	10	38	0.0453		
	20	33	0.0389		
	30	58	0.0688		
	40	50	0.0593		
	50	47	0.0559		

Reference Frequency: PCS1900 (GSM link) Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Result	
		Hz	ppm		
3.70	-30	23	0.0123	2.5	Pass
	-20	29	0.0157		
	-10	23	0.0123		
	0	18	0.0094		
	10	23	0.0123		
	20	19	0.0100		
	30	37	0.0197		
	40	31	0.0162		
	50	28	0.0151		
Reference Frequency: PCS1900 (GPRS 1 link) Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Result	
		Hz	ppm		
3.70	-30	87	0.0461	2.5	Pass
	-20	103	0.0547		
	-10	83	0.0442		
	0	68	0.0360		
	10	84	0.0448		
	20	70	0.0372		
	30	116	0.0616		
	40	96	0.0512		
	50	101	0.0539		

Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	34	0.0401	2.5	Pass
	-20	47	0.0558		
	-10	53	0.0629		
	0	25	0.0302		
	10	37	0.0444		
	20	41	0.0486		
	30	60	0.0714		
	40	56	0.0671		
	50	67	0.0799		

7.10 Frequency stability V.S. Voltage measurement



Test Requirement:	FCC Part2.1055(d)(1)(2)
Test Method:	FCC Part2.1055(d)(1)(2)
Limit:	2.5ppm
Test setup:	<p style="text-align: center;">Temperature Chamber</p>  <p style="text-align: center;">Variable Power Supply</p> <p>Note : Measurement setup for testing on Antenna connector</p>
Test procedure:	<ol style="list-style-type: none"> 1. Set chamber temperature to 25°C. Use a variable DC power source to power the EUT and set the voltage to rated voltage. 2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. 3. Reduce the input voltage to specified extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement Data

Reference Frequency: GSM850 (GSM link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	20	0.0237	2.5	Pass
	3.70	22	0.0265		
	3.40	25	0.0294		
Reference Frequency: GSM850 (GPRS 1 link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	29	0.0343	2.5	Pass
	3.70	33	0.0398		
	3.40	38	0.0451		
Reference Frequency: PCS1900 (GSM link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	15	0.0080	2.5	Pass
	3.70	22	0.0116		
	3.40	22	0.0116		
Reference Frequency: PCS1900 (GPRS 1 link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	65	0.0346	2.5	Pass
	3.70	74	0.0393		
	3.40	74	0.0395		
Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	34	0.0402	2.5	Pass
	3.70	44	0.0523		
	3.40	24	0.0282		

8 Test Setup Photo

Radiated Emission




9 EUT Constructional Details























-----end-----