

RF EXPOSURE EVALUATION REPORT

APPLICANT

Guilin Zhishen Information Technology Co.,Ltd.

PRODUCT NAME

Digital Camera Stabilizer

MODEL NAME

Shining

TRADE NAME

N/A

BRAND NAME

FCC ID

2AIHFZYSL

47CFR 2.1091

STANDARD(S)

KDB 447498 D01 General RF Exposure

Guidance v06

ISSUE DATE

Certificatio

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

FL1-3, Building A, FelYang Science Park, No.o LongOnian Noau,

Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Http://www.morlab.com E-mail: service@morlab.cn FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,

Tel: 86-755-36698555

Fax: 86-755-36698525



TEST REPORT DECLARATION	3
1. TECHNICAL INFORMATION	4
1.1. IDENTIFICATION OF APPLICANT	4
1.2. IDENTIFICATION OF MANUFACTURER	4
1.3. EQUIPMENT UNDER TEST (EUT)	4
1.3.1. PHOTOGRAPHS OF THE EUT	5
1.3.2 IDENTIFICATION OF ALL USED FILT	6
1.4. APPLIED REFERENCE DOCUMENTS	6
SE W SLAE MORLE MOR SE W SLAE MORLE MORLE MORLE	
2. DEVICE CATEGORY AND RF EXPOSURE LIMIT	<u>7</u>
3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER	<u> 8</u>
4. RF EXPOSURE EVALUATION	8
ANNEX C GENERAL INFORMATION	9

	Change History				
Issue	Issue Date Reason for change				
1.0	2016-07-25	First edition			
MORE	4110	E SELAT MORE THE SELAT MORE			



TEST REPORT DECLARATION

Applicant	Guilin Zhishen Information Technology Co.,Ltd.		
Applicant Address	6F,Bldg 13,Creative Industrial Park,Guimo Road		
Manufacturer	Guilin Zhishen Information Technology Co.,Ltd.		
Manufacturer Address	6F,Bldg 13,Creative Industrial Park,Guimo Road		
Product Name	Digital Camera Stabilizer		
Model Name	Shining		
Brand Name	₹		
HW Version	V1.0		
SW Version	V1.0		
Test Standards	47CFR 2.1091; KDB 447498 D01 General RF Exposure Guidance v06		
Issue Date	2016-07-25		
SAR Evaluation	Not Required		

Tested by :	Chen Sheng kui	
March March	Chen Shengkui	
Reviewed by :	Liu Jun	
and the second	Liu Jun	
Approved by :	Zeng Dexin	108
	Zena Dexin	



1. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

1.1. Identification of Applicant

Company Name:	Guilin Zhishen Information Technology Co.,Ltd.
Address:	6F,Bldg 13,Creative Industrial Park,Guimo Road

1.2. Identification of Manufacturer

Company Name:	Guilin Zhishen Information Technology Co.,Ltd.
Address:	6F,Bldg 13,Creative Industrial Park,Guimo Road

1.3. Equipment Under Test (EUT)

Model Name:	Shining
Trade Name:	N/A
Brand Name:	Z Waller Walle
Hardware Version:	V1.0
Software Version:	V1.0
Frequency Bands:	2145-2473MHz Bluetooth 4.0
Modulation Mode:	Bluetooth 4.0:GFSK;
Antenna type:	FPCB Antenna
Development Stage:	Identical prototype



1.3.1. Photographs of the EUT

EUT front view



2. EUT rear view





1.3.2. Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version	
1#	V1.0	V1.0	

1.4. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1 OPLAE	47 CFR§2.1091	Radiofrequency Radiation Exposure Evaluation: mobile devices
2	KDB 447498 D01v06	General RF Exposure Guidance



2. DEVICE CATEGORY AND RF EXPOSURE LIMIT

Per user manual. Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	range strength		ge strength strength		Power density (mW/cm²)	Averaging time (minutes)
(i	B) Limits for General	Population/Uncontro	lled Exposure			
0.3-1.34	614	1.63	*(100)	30		
1.34-30	824/f	2.19/f	*(180/f ²)	30		
30-300	27.5	0.073	0.2	30		
300-1500	-	-	f/1500	30		
1500-100,000	-	-	1.0	30		

f = frequency in MHz



^{* =} Plane-wave equivalent power density



3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER

Bluetooth 4.0 Conducted Average Output Power

Band	Channel	Frequency	Output Power(dBm)
		(MHz)	GFSK
QLAB	0	2402	6.90
ВТ	19	2440	6.72
LAE JOR	39	2480	6.42

4. RF EXPOSURE EVALUATION

Standalone transmission MPE evaluation

Bands	Frequency (MHz)	Antenna Gain (dBi)	Conducted Average Power (dBm)	Time-averaging EIRP (mW)	Power density (mW/cm²)	Limit for MPE (mW/cm²)
Bluetooth 4.0	2402	0	6.90	4.90	0.001	1.0

Note:

1. MPE calculation method

Power Density = EIRP/ 4π R²

Where: EIRP = P·G

P = Peak out power

G = Antenna gain

R = Separation distance (20cm)



ANNEX C GENERAL INFORMATION

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang
	Road, Block 67, BaoAn District, ShenZhen, GuangDong
	Province, P. R. China

***** END OF REPORT *****