Produkte Products

Prüfbericht - Nr.: 50045317 001
Test Report No.

Seite 1 von 2
Page 1 of 2

# **Appendix I- RF Exposure statement**

Evaluate standard : FCC KDB # 447498 D01 V06

RSS-102 Issue 5

## **Calculated Output Power**

The maximum measured transmitter power is the following:

			9		
	Frequency [GHz]	Field Strength of Fundamental Emissions	Field Strength of Fundamental Emissions	Field Strength of Fundamental Emissions	
		[dBuv/m]	[dBm]	[mW]	
	0.908433	93.562	-1.67	0.681	

Note:Relation between power, electric field strength, E

A simple relation can be established for perfect, ideal cases (which means free space, far field conditions) between E(V/m), D distance between the transmitting radio equipment and the point of measurement (m), e.i.r.p.(W).

$$E = \sqrt{\frac{30(e.i.r.p.)}{D}}$$

This represents a site gain of 4dB. The field strength as E(V/m) can be converted to dB(uV/m) as follows:

 $E(dB(uV/m)) = 120 + 20 \log E$ 

#### **Evaluation for FCC**

According to FCC KDB # 447498 D01 V06, Clause 4.3.1

(a) For 100MHz to 6 GHz and test separation distances  $\leq$  50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\frac{\text{(max. power of channel, including tune - up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \times \sqrt{f(GHz)}$$

 $\leq$  3.0, for 1-g SAR, and  $\leq$  7.5, for 10-g extremity SAR

So, the max allowed power for 1-g SAR with distance 5mm at 0.908433GHz is 15.73783mW

And the max allowed power for 10-g extremity SAR with distance 5mm at 0.908433GHz is 39.34457mW

The maximum conducted output power of the EUT is: 0.681mW which is totally lower than the SAR test exclusion thresholds.





 Prüfbericht - Nr.:
 50045317 001
 Seite 2 von 2

 Test Report No.
 Page 2 of 2

### **Evaluation for IC**

According to table 1 and note 4 of RSS-102 Issue 5, March 2015

 ${\bf Table~1:~SAR~evaluation-Exemption~limits~for~routine~evaluation~based} \\ {\bf on~frequency~and~separation~distance}^{4,5}$ 

Frequency		nW)			
(MHz)	At separation				
	distance of				
	≤5 mm	10 mm	15 mm	20 mm	25 mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7  mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7  mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency	quency Exemption Limits (mW)					
(MHz)	At separation	At separation	At separation	At separation	At separation	
	distance of	distance of	distance of	distance of	distance of	
	30 mm	35 mm	40 mm	45 mm	≥50 mm	
≤300	223 mW	254 mW	284 mW	315 mW	345 mW	
450	141 mW	159 mW	177  mW	195 mW	213 mW	
835	80 mW	92 mW	105 mW	117  mW	130 mW	
1900	99 mW	153 mW	225 mW	316 mW	431 mW	
2450	83 mW	123 mW	173 mW	235 mW	309 mW	
3500	86 mW	124 mW	170 mW	225 mW	290 mW	
5800	56 mW	71 mW	85 mW	97 mW	106 mW	

For frequencies (835 MHz to 1900 MHz), the conservative limit of 1900MHz can be used for exemption limits.

So, the max allowed power for 1-g SAR with distance 5mm at 908.433MHz is 7mW

The maximum conducted output power of the EUT is: 0.681mW which is totally lower than the SAR test exclusion thresholds.

#### Conclusion

SAR data is not required for either FCC or IC.