

# RF Exposure Evaluation Report

**Product** : TouchLock Bike BT  
**Trade mark** : BIO-key  
**Model/Type reference** : BL1309  
**Serial Number** : N/A  
**Report Number** : EED32J00175904  
**FCC ID** : 2AIKJ-BL1309  
**Date of Issue** : Sep. 29, 2017  
**Test Standards** : 47 CFR Part 1.1307  
47 CFR Part 1.1310  
KDB447498D01v06  
**Test result** : PASS

Prepared for:

**BIO-key Hong Kong Limited**  
**1806, 18/F, Tower Two, Lippo Centre, 89 Queensway Hong Kong**

Prepared by:

**Centre Testing International Group Co., Ltd.**  
**Hongwei Industrial Zone, Bao'an 70 District,**  
**Shenzhen, Guangdong, China**  
**TEL: +86-755-3368 3668**  
**FAX: +86-755-3368 3385**

Tested By:

TOM-chen

Compiled by:

Mill chen

Tom chen (Test Project)

Mill chen (Project Engineer)

Reviewed by:

Kevin Yang

Approved by:

Sheek Luo

Kevin yang (Reviewer)

Sheek Luo (Lab supervisor)

Date:

Sep. 29, 2017

Check No.: 1022565636



Report No. : EED32J00175904

Page 2 of 7

## 2 Version

Version No.	Date	Description
00	Sep. 29, 2017	Original

Report No. : EED32J00175904

Page 3 of 7

### 3 Contents

	Page
<b>1 COVER PAGE</b> .....	1
<b>2 VERSION</b> .....	2
<b>3 CONTENTS</b> .....	3
<b>4 GENERAL INFORMATION</b> .....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 TEST FACILITY.....	5
4.6 DEVIATION FROM STANDARDS.....	5
4.7 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
<b>5 SAR EVALUATION</b> .....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 Standard Requirement.....	6
5.1.2 Limits.....	6
5.1.3 EUT RF Exposure.....	6
<b>PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS</b> .....	7

Report No. : EED32J00175904

Page 4 of 7

## 4 General Information

### 4.1 Client Information

Applicant:	BIO-key Hong Kong Limited
Address of Applicant:	1806, 18/F, Tower Two, Lippo Centre, 89 Queensway, Hong Kong
Manufacturer:	TOP LEADER ELECTRONIC (SHEN ZHEN) CO., LTD.
Address of Manufacturer:	No.9 NanXin Road, NanLing Village Community, NanWan Street Office, LongGang District, ShenZhen, Guangdong, China
Factory:	TOP LEADER ELECTRONIC (SHEN ZHEN) CO., LTD.
Address of Factory:	No.9 NanXin Road, NanLing Village Community, NanWan Street Office, LongGang District, ShenZhen, Guangdong, China

### 4.2 General Description of EUT

Product Name:	TouchLock Bike BT
Model No.(EUT):	BL1309
Trade mark:	BIO-key
Power Supply:	DC 5V by USB port DC 3.7V by battery
EUT Supports Radios application:	BT 4.1 Signal mode

### 4.3 Product Specification subjective to this standard

Operation Frequency:	2402MHz~2480MHz
Modulation Type:	GFSK
Hardware Version:	5.0 (manufacturer declare)
Software Version:	29 (manufacturer declare)
Test Power Grade:	6
Test Software of EUT:	BLUENRG_GUI.exe
Antenna Type:	Integral
Antenna Gain:	0.49dBi
Test Voltage:	DC 3.7V
Sample Received Date:	Aug. 14, 2017
Sample tested Date:	Aug. 14, 2017 to Sep. 29, 2017
The tested sample and the sample information are provided by the client.	

Report No. : EED32J00175904

Page 5 of 7

#### 4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China 518101

Telephone: +86 (0) 755 3368 3668 Fax:+86 (0) 755 3368 3385

No tests were sub-contracted.

#### 4.5 Test Facility

##### Test location

The test site a is located on *Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China*.

Test site at Centre Testing International Group Co., Ltd has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014.

The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

**FCC Designation No.: CN1164**

**FCC-Registration No.: 886427**

Centre Testing International Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 886427.

#### 4.6 Deviation from Standards

None.

#### 4.7 Abnormalities from Standard Conditions

None.

#### 4.8 Other Information Requested by the Customer

None.

## 5 SAR Evaluation

### 5.1 RF Exposure Compliance Requirement

#### 5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

#### 5.1.3 EUT RF Exposure

The Max Conducted Output Power is 2.444dBm in lowest channel(2.402GHz);

$EIRP = 2.444\text{dBm} + 0.49\text{dBi} = 2.0934\text{dBm}$

2.934dBm logarithmic terms convert to numeric result is nearly 1.965 mW

According to the formula:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

General RF Exposure =  $(1.965\text{mW} / 5\text{ mm}) \times \sqrt{2.402\text{GHz}} = 0.61$  ①

SAR requirement:

$S = 3.0$

② ;

① < ②.

So the SAR report is not required.

Report No. : EED32J00175904

Page 7 of 7

## PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32J00175903 for EUT external and internal photos.

\*\*\* End of Report \*\*\*

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.