

FCC TEST REPORT

Report No: STS1611217F01

Issued for

Legacy Direct

1221 E. Dyer Rd., #110 Santa Ana, CA 92705, USA

L A B

Product Name:	Wireless Microphone
Brand Name:	Legacy Direct
Model Name:	B-KMIC
Series Model:	KMIC, BMIC
FCC ID:	2AIM5BKMIC
Test Standard:	FCC Part 74 Rules

APPROVA

Any reproduction of this document must be done in full. No single part of this document may be reproduced permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.

Shenzhen STS Test Services Co., Ltd. 1/F, Building B, Zhuoke Science Park, No.190, Chongqing Road, Fuyong Street, Bao'an District, Shenzhen, Guangdong, China TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





TEST RESULT CERTIFICATION

-	
Applicant's name	Legacy Direct
Address	1221 E. Dyer Rd., #110 Santa Ana, CA 92705, USA
Manufacture's Name	
Address	Unit 601-605, TaoJinDi Electronic Commercial Plaza B, TengLong Rd, LongHua, Shenzhen, China 518131
Product description	
Product name	Wireless Microphone
Brand name	Legacy Direct
Model and/or type reference	B-KMIC
Series Model	KMIC, BMIC
Standards	FCC Part 74 Rules
Test procedure	ANSI C63.4:2014;TIA/EIA 603
under test (EUT) is in compliant sample identified in the report. This report shall not be reprodu	the seen tested by STS, and the test results show that the equipment on the with the FCC requirements. And it is applicable only to the tested ced except in full, without the written approval of STS, this document TS, personal only, and shall be noted in the revision of the document.
Date of performance of tests	. 25 Nov 2016 ~12 Dec. 2016
Date of Issue	. 13 Dec. 2016
Test Result	Pass
Testing Engineer	: Ching cher
Technical Manager	(Chris chen) (Tony liu)

(Bovey Yang)

Authorized Signatory:





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACTORY	6
1.2 MEASUREMENT UNCERTAINTY	6
2. GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
2.6 TEST EQUIPMENT	11
3.TEST METHODOLOGY	12
3.1 GENERAL TEST PROCEDURES	12
3.2 DESCRIPTION OF TEST MODES	12
4. FCC PART 74 REQUIREMENTS	13
4.1 RADIATED SPURIOUS EMISSION	13
4.2 EMISSION MASK I	13
4.3 EMISSION MASK II	13
4.4 FREQUENCY STABILITY VS. TEMPERATURE & VOLTAGE	21
4.5 OCCUPIED BANDWIDTH	25
4.6 AUDIO FREQUENCY RESPONSE	28
4.7 MODULATION DEVIATION	30
4.8 RF OUTPUT POWER	32
PHOTOS OF TEST SETUP	36







Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	13 Dec. 2016	STS1611217F01	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

The EUT has been tested according to FCC CFR 47:

Part 2: Frequency Allocations and Radio Treaty Matters: General Rules and Regulations (10-1-05 Edition)

Part 74: Experimental Radio, Auxiliary, Special Broadcast and other program distributional services

Emission				
Standard	Item	Limit	Result	
FCC 2.1053; 74.861(e)(b)	Radiated Spurious Emission	Refer to 74.861e(6)	PASS	
FCC 2.1046 (a), 74.861(e)(1)	RF Output Power	250 mW	PASS	
FCC 2.1047 (b), 74.861(e)(3)	Modulation Deviation	Refer to 74.861e(2)	PASS	
FCC 2.1047 (a)	Audio Frequency Response	Refer to 2.1047(a)	PASS	
FCC 74.861 (e)(5)	Occupied Bandwidth	< 200 KHz	PASS	
FCC 74.861 (e)(6)(i) (ii); FCC 2.1049	Emission Mask	Refer to 74.861e(6)	PASS	
2.1055(b); 74.861 e(4)	Frequency Stability vs. Temperature	Refer to 74.861e(4)	PASS	
2.1055(a)(1); 74.861 e(4)	Frequency Stability vs. Voltage	Refer to 74.861e(4)	PASS	

NOTE:

^{(1)&}quot; N/A" denotes test is not applicable in this Test Report



1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add.: 1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,

Fuyong Street, Bao'an District, Shenzhen, Guangdong, China

FCC Registration No.: 842334; IC Registration No.: 12108A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y \pm U , where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2 , providing a level of confidence of approximately 95 % ,

No.	Item	Uncertainty
1	RF power,conducted	±0.70dB
2	Spurious emissions,conducted	±1.19dB
3	Spurious emissions,radiated((>1G)	±2.83dB
4	Spurious emissions,radiated(<1G)	±3.01dB
5	Temperature	±0.5°C
6	Humidity	±2%



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Wireless Microphone
Legacy Direct
B-KMIC
KMIC, BMIC
Only different in model name
81.4KHz
Rated Voltage: DC 3.0V
615.15 MHz-620.85 MHz
0.001878W(2.738dBm)
FM
0.002280%
-30℃-50℃
See Note 6
BKMIC V1.0
WIL-BKMIC V1.0

Note:

- 1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2. Note: The product has the same digital working characters when operating in both two digitized voice/data mode. So only one set of test results for digital modulation modes are provided in this test report.
- 3. Please refer to Appendix B for the photographs of the EUT. For more details, please refer to the User's manual of the EUT.

4	
┰	

Cha	annel List
Channel	Frequency (MHz)
01	615.15
02	618.15
03	620.85

Note, the frequency of a total of 3CH



5. Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	Legacy Direct	B-KMIC	PCB Antenna	NA	1	Antenna

The EUT antenna is PCB Antenna. no antenna other than that furnished by the responsible party shall be used with the device.

6. Test frequency list

Test Channel List		
Test Channel	EUT Channel	Test Frequency (MHz)
lowest	CH01	615.15
middle	CH02	618.15
highest	CH03	620.85

Note:

regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above listed frequency for testing.

New battery is used during all test



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Low Channel
Mode 2	Middle Channel
Mode 3	High Channel
Mode 4	Link Mode

For Radiated Emission			
Final Test Mode Description			
Mode 1	Low Channel		
Mode 2	Middle Channel		
Mode 3	High Channel		
Mode 4	Link Mode		

Note:

⁽¹⁾ Due to the different configuration and test, in this list only some worse mode. The worst test data of the worse modeis reported by this report.



2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

E-1 EUT

2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-1	Wireless Microphone	Legacy Direct	B-KMIC	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
N/A	N/A	N/A	N/A	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>"Length_"</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.



2.6 TEST EQUIPMENT

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Signal Analyzer	Agilent	N9020A	MY49100060	2016.10.23	2017.10.22
Signal Generator	Agilent	N5182A	MY46240556	2016.10.23	2017.10.22
Audio Generator	TRONSON	TAG-101	20030212	2016.10.23	2017.10.22
Spectrum Analyzer	Agilent	E4407B	MY50140340	2016.10.23	2017.10.22
Test Receiver	R&S	ESCI	101427	2016.10.23	2017.10.22
Bilog Antenna	TESEQ	CBL6111D	34678	2014.11.24	2017.11.23
Horn Antenna	Schwarzbeck	BBHA 9120D(1201)	9120D-1343	2015.03.05	2018.03.04
Horn Antenna	Schwarzbeck	BBHA 9170	9170-0741	2016.03.06	2019.03.05
50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2016.10.23	2017.10.22
PreAmplifier	Agilent	8449B	60538	2016.10.23	2017.10.22
Loop Antenna	EMCO	6502	9003-2485	2016.03.06	2019.03.05
Attenuator	HP	215-05-20	DC-3G	2016.10.23	2017.10.22
RF Communications	HP	8920A	3438A05658	2016.10.23	2017.10.22
DC Power source	Zhaoxin	RXN-605D	20140807176	N.C.R	N.C.R
AC Power Source	APC	KDF-11010G	F214050035	N.C.R	N.C.R



3.TEST METHODOLOGY

3.1 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirement of ANSI C63.4:2014. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes. Not Applicable (Since the EUT is powered by battery)

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements ANSI C63.4:2014.

3.2 DESCRIPTION OF TEST MODES

The EUT has been tested under engineering test mode condition and the EUT staying in continuous transmitting mode.



Report No.: STS1611217F01



4. FCC PART 74 REQUIREMENTS

4.1 RADIATED SPURIOUS EMISSION TEST LIMITS

According to CFR 47 section 74.861 e (6)(iii), the mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

- = P(W) [43 + 10log(P)] (dB)
- = [30 + 10log(P)] (dBm) [43 + 10log(P)] (dB)
- = -13dBm.

4.2 EMISSION MASK I

TEST LIMITS

- According to CFR 47 section 74.861 e (6), the mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:
- (1) On any frequency removed from the operating frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth: at least 25 dB;
- a. (2) On any frequency removed from the operating frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth: at least 35 dB;
 - (3) On any frequency removed from the operating frequency by more than 250 percent of the authorized bandwidth: at least 43+10log 10 *(mean output power in watts) dB;

4.3 EMISSION MASK II

TEST LIMITS

- According to ETSI EN 300 422-1 V1.5.1 Clause 8.3.1.2,
- a. The transmitter output spectrum shall be within the mask defined in figure 3 where B is the declared channel bandwidth




TEST PROCEDURE

- a. On a test site, the EUT shall be placed on a turntable and in the position closest to the normal use as declared by the user.
- b. The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- c. The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- d. The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- e. The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- f. The transmitter shall than be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- h The maximum signal level detected by the measuring receiver shall be noted.
- i The measurement shall be repeated with the test antenna set to horizontal polarization.
- j Replace the antenna with a proper Antenna (substitution antenna).
- k The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- I The substitution antenna shall be connected to a calibrated signal generator.
- m If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- n The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- o The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
- p The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
- q The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.

TEST CONFIGURATION


(A) Radiated Emission Test-Up Frequency Above 30MHz
Ground Plane





(B) Radiated Emission Test-Up Frequency Above 1GHz

Ground plane






TEST RESULTS

	30-6300 MHz							
			hannel 61					
Frequency(MHz)	S G.Lev	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity	
1 requericy(ivii iz)	(dBm)	Anti(abi)	L033	(dBm)	(dBm)	(dBm)	1 Clarity	
1230.13	-40.22	7.46	4.72	-37.48	-13.00	-24.48	Н	
1845.14	-39.78	10.35	8.32	-37.75	-13.00	-24.75	Н	
2460.44	-30.12	10.20	11.72	-31.64	-13.00	-18.64	Н	
1230.08	-43.18	7.46	4.72	-40.44	-13.00	-27.44	V	
1845.23	-43.68	10.35	8.32	-41.65	-13.00	-28.65	V	
2460.42	-42.72	10.20	11.72	-44.24	-13.00	-31.24	V	
		Mid C	hannel 61	8.15 MHz				
Francisco (MIII-)	S G.Lev	۸ ۱/ حاD: ۱	1.555	PMea	Limit	Margin	Delevity	
Frequency(MHz)	(dBm)	Ant(dBi)	Loss	(dBm)	(dBm)	(dBm)	Polarity	
1236.20	-36.22	7.46	4.72	-33.48	-13.00	-20.48	Н	
1854.30	-43.18	10.35	8.32	-41.15	-13.00	-28.15	Н	
2472.18	-38.79	10.20	11.72	-40.31	-13.00	-27.31	Н	
1235.87	-37.86	7.46	4.72	-35.12	-13.00	-22.12	V	
1854.29	-31.53	10.35	8.32	-29.50	-13.00	-16.50	V	
2472.46	-36.67	10.20	11.72	-38.19	-13.00	-25.19	V	
		High C	Channel 62	20.85 MHz				
Frequency(MHz)	S G.Lev	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity	
Frequency(MH2)	(dBm)	Anii(ubi)	L088	(dBm)	(dBm)	(dBm)	Polarity	
1241.52	-36.21	7.46	4.72	-33.47	-13.00	-20.47	Н	
1862.27	-43.33	10.35	8.32	-41.30	-13.00	-28.30	Н	
2483.34	-38.56	10.20	11.72	-40.08	-13.00	-27.08	Н	
1241.34	-37.17	7.46	4.72	-34.43	-13.00	-21.43	V	
1862.48	-31.63	10.35	8.32	-29.60	-13.00	-16.60	V	
2483.24	-36.24	10.20	11.72	-37.76	-13.00	-24.76	V	




Emission Mask I

UHF (Analog) Emission Mask Low Channel




UHF (Analog) Emission Mask Mid Channel





UHF (Analog) Emission Mask High Channel






Emission Mask II

ETSI EN 300 422-1 V1.5.1 Clause 8.3.1.2 The Maximum Measurement of Necessary Bandwidth Test Plot:


Frequency	Declared Bandwidth	B/2	0.35B
615.15 MHz	100K	50K	35K
618.15 MHz	100K	50K	35K
620.85 MHz	100K	50K	35K

Low CH






Mid CH



High CH






4.4 FREQUENCY STABILITY VS. TEMPERATURE & VOLTAGE TEST LIMIT

According to CFR 47 section 74.861 e (4), the frequency tolerance of the transmitter shall be 0.005 percent.

TEST CONFIGURATION

Climate Chamber



TEST PROCEDURE

The EUT was connected to an external DC power supply and the RF output was connected to a frequency counter via feed through attenuators. The EUT was placed inside the temperature

- a chamber. The DC leads and the RF output cable, exited the chamber through an opening made for that purpose.
 - After the temperature stabilized the frequency output was recorded form the counter. An external variable DC power supply was connected to the battery terminals of the equipment under test.
- b. For hand carried, battery powered equipment primary supply voltage was reduced to the battery operating end point as specified by the manufacturer. The output frequency was recorded for each battery voltage.



TEST RESULTS

- (1) Frequency stability versus input voltage (Supply Nominal voltage is DC 3.3V)
- (2) Frequency stability versus input voltage (Supply battery operating end point which shall be specified by the manufacturer DC 2.7V)

Reference Frequency: 615.15MHz					
Power Supply Environment Temperature (°C) Frequency Error (Hz) Frequency Error (%)					
2.7V, DC	20	14015	0.002278		
3.0V, DC	20	14000	0.002276		
3.3V, DC	20	14008	0.002277		
END	20	14011	0.002278		

Reference Frequency: 615.15MHz					
Environment	Frequency Deviation measured with time Elapse(30 minutes)				
Temperature(°C)	Frequency Error (Hz)	Frequency Error (%)	Limit (%)	Results	
50	14023	0.002280			
40	14015	0.002278			
30	14009	0.002277	7		
20	14000	0.002276			
10	14011	0.002278	0.00500	PASS	
0	14021	0.002279			
-10	14023	0.002280			
-20	14022	0.002279			
-30	14025	0.002280			



Reference Frequency: 618.150MHz					
Power Supply	Environment Temperature (°C)	Frequency Error (Hz)	Frequency Error (%)		
2.7V, DC	20	3013	0.000487		
3.0V, DC	20	3000	0.000485		
3.3V, DC	20	3006	0.000486		
END	20	3008	0.000487		

Reference Frequency: 618.150MHz					
Environment	Frequency Devia	tion measured with time E	Elapse(30 minut	es)	
Temperature(°C)	Frequency Error (Hz)	Frequency Error (%)	Limit (%)	Results	
50	3021	0.000489			
40	3015	0.000488			
30	3011	0.000487			
20	3000	0.000485			
10	3008	0.000487	0.00500	PASS	
0	3016	0.000488			
-10	3022	0.000489			
-20	3028	0.000490			
-30	3029	0.000490			



Reference Frequency: 620.850MHz					
Power Supply	Environment Temperature (°C)	Frequency Error (Hz)	Frequency Error (%)		
2.7V, DC	20	11017	0.001775		
3.0V, DC	20	11000	0.001772		
3.3V, DC	20	11011	0.001774		
END	20	11013	0.001774		


Reference Frequency: 620.850MHz					
Environment	Frequency Devia	tion measured with time E	lapse(30 minut	tes)	
Temperature(°C)	Frequency Error (Hz)	Frequency Error (%)	Limit (%)	Results	
50	11027	0.001776			
40	11019	0.001775			
30	11015	0.001774			
20	11000	0.001772			
10	11008	0.001773	0.00500	PASS	
0	11013	0.001774			
-10	11021	0.001775			
-20	11029	0.001776			
-30	11031	0.001777	7		



4.5 OCCUPIED BANDWIDTH TEST LIMIT

According to CFR 47 section 74.861 e (5), the operating bandwidth shall no exceed 200 KHz. Near the carrier an emission mask is defined by the standard.

TEST CONFIGURATION




TEST PROCEDURE

- a. The RF output of the transceiver was connected to the input of the spectrum analyzer through sufficient attenuation.
 - Set Occupied Bandwidth was measured with a occupied bandwidth function of the analyzer.
- b. The near the carrier emissions are measured by normal power measurement function of the analyzer.
- c. Set SPA Max hold. Mark peak, 99%.





TEST RESULT

Frequency(MHz)	Occupied Bandwidth(KHz)	Limit(KHz)
615.15	81.394	200
618.15	81.438	200
620.85	81.419	200












4.6 AUDIO FREQUENCY RESPONSE TEST LIMIT

The audio frequency response is the degree of closeness to which the frequency deviation of the transmitter follows a prescribed characteristic. The frequency response of the audio modulation part is measured over a frequency range of 100 Hz to 5000 Hz.

According to CFR 47 section 74.861 e (1), any form of modulation may be used. A maximum deviation of \pm 75 KHz is permitted when frequency modulation is employed.

TEST CONFIGURATION



TEST PROCEDURE


- a. The audio frequency response is the degree of the closeness to which the frequency deviation of the transmitter follows prescribed characteristics.
- b. The frequency response of the audio modulation part is measured over a frequency range of 100Hz to 5000 Hz.
- c. For 1000 Hz tone reference signal the audio generator level is adjusted to get 20% of the rated system deviation.
 - The deviations obtained over the frequency range from 100 HZ to 5000 Hz are recorded and
- d. compared with the reference deviation as follows:Audio Frequency Response= 20 log (DEV freq/ Dev ref)



Audio Frequency Response:

Frequency(KHz)	Deviation(KHz)
0.01	14.91
1	15.74
2	16.97
3	18.07
4	19.27
5	20.21

Frequency Response of Mid Channel



NOTE: ONLY WORSE CASE IS REPORTED




4.7 MODULATION DEVIATION TEST LIMIT

According to CFR 47 section 2.1047 a, for Voice modulation communication equipment, the frequency response of the audio modulation circuit over a range of 100 to 5000 Hz shall be measured.

According to CFR 47 section 74.861 e (3), any form of modulation may be used. A maximum deviation of ± 75 KHz is permitted when frequency modulation is employed.

TEST CONFIGURATION



TEST PROCEDURE

- a. Modulation limits is the transmitter circuit's ability to limit the transmitter form producing deviations in excess of rated system deviation.
- b. The audio signal generator is connected to the audio input of the EUT with its full rating.
- c. The modulation response is measured at certain modulation frequencies, related to 1000 Hz reference signal.
- d. Tests are performed for positive and negative modulation.




TEST RESULT

Modulation Deviation

Level(mv)	100Hz	500Hz	1kHz	2.5kHz	5kHz
0	8.27	6.11	6.56	7.03	7.50
10	14.68	12.65	13.11	13.57	14.05
20	22.72	20.61	21.05	21.50	21.96
30	30.83	26.64	28.12	28.91	29.70
40	30.86	28.74	29.18	30.68	31.14
50	30.87	28.75	29.18	29.62	30.02
60	30.82	28.69	29.13	29.55	30.00
70	30.78	28.72	29.18	29.64	30.12
80	30.82	28.76	29.18	29.59	29.99
90	30.79	28.73	29.17	29.63	30.12
100	30.71	28.62	29.11	29.54	29.94
110	30.75	28.70	29.20	29.68	30.14

Modulation Deviation of Mid Channel



NOTE: ONLY WORSE CASE IS REPORTED





4.8 RF OUTPUT POWER

TEST LIMIT


According to CFR 47 section 74.861 e (1), the power of the measured unmodulated carrier power at the output of the transmitter power amplifier (antenna input power) may not exceed the following:

- (i) 54-72, 76-88, and 174-216 MHz bands: 50 mW EIRP
- (ii) 470-608 and 614-698: 250 mW conducted power
- (iii) 600 MHz duplex gap: 20 mW EIRP

TEST CONFIGURATION

Radiation

Ground Plane



Conduction



TEST PROCEDURE(Radiation)

- a. On a test site, the EUT shall be placed on a turntable and in the position closest to the normal use as declared by the user.
- b. The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- c. The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- d. The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- e. The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- f. The transmitter shall than be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.



- h The maximum signal level detected by the measuring receiver shall be noted.
- i The measurement shall be repeated with the test antenna set to horizontal polarization.
- j Replace the antenna with a proper Antenna (substitution antenna).
- k The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- I The substitution antenna shall be connected to a calibrated signal generator.
- m If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- n The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- o The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
- p The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
- q The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.

TEST PROCEDURE (Conduction)

- a. The RF output of the transceiver was connected to the input of the spectrum analyzer through sufficient attenuation.
- b. Set the RBW >20BW, VBW>3xRBW.
- c. Detector = peak.
- d Sweep time = auto couple.
- e Trace mode = max hold.
- f Allow trace to fully stabilize.
- g Use the peak marker function to determine the maximum amplitude level.



TEST RESULT

Frequency Channel (MHz)	Peak Output Power (dBm)	Transmitter Power (mW)	Limits (mW)
615.15	2.126	1.163	250
618.15	2.381	1.730	250
620.85	2.738	1.878	250

Low Channel





Mid Channel




High Channel






PHOTOS OF TEST SETUP

Radiated Measurement Photos 30MHz- 1GHz



Above 1GHz



*****END OF THE REPORT***