RF EXPOSURE REPORT



Report No.: 16070658-FCC-H2 Supersede Report No.: N/A

Applicant	SMT TELECOMM HK LIMITED			
Product Name	Mobile Phone			
Model No.	X325			
Serial No.	N/A			
Test Standard	FCC 2.109	3:2015		
Test Date	April 23 to I	April 23 to May 06, 2016		
Issue Date	June 07, 2016			
Test Result	Pass Fail			
Equipment complied with the specification				
Equipment did not comply with the specification				
Winnie.Z.	heng	David Huang		
Winnie Zhang Test Engineer		David Huang Checked By		

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn



Test Report	16070658-FCC-H2
Page	2 of 10

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety



Test Report	16070658-FCC-H2
Page	3 of 10

This page has been left blank intentionally.



Test Report	16070658-FCC-H2
Page	4 of 10

CONTENTS

1.	REPORT REVISION HISTORY	.5
	CUSTOMER INFORMATION	
3.	TEST SITE INFORMATION	.5
4.	EQUIPMENT UNDER TEST (EUT) INFORMATION	.6
5.	FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.	8
5.1	RF EXPOSURE	.8
52	TEST RESULT	Ç



Test Report	16070658-FCC-H2
Page	5 of 10

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070658-FCC-H2	NONE	Original	June 07, 2016

2. Customer information

Applicant Name	SMT TELECOMM HK LIMITED	
Applicant Add	Unit C 8/F, CHARMHILL CTR 50 HILLWOOD RD TST KL	
Manufacturer	SMT TELECOMM HK LIMITED	
Manufacturer Add	Unit C 8/F, CHARMHILL CTR 50 HILLWOOD RD TST KL	

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES	
3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park	
Lab Address	South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China	
Lab Address		
	518108	
FCC Test Site No.	718246	
IC Test Site No.	4842E-1	
Test Software Radiated Emission Program-To Shenzhen v2.0		



Test Report	16070658-FCC-H2
Page	6 of 10

4. Equipment under Test (EUT) Information

Description of EUT: Mobile Phone

Main Model: X325

Serial Model: N/A

Date EUT received: April 22, 2016

Test Date(s): April 23 to May 06, 2016

GSM850: -2.22dBi PCS1900: -1.14dBi

UMTS-FDD Band V: -2.22dBi

Antenna Gain: UMTS-FDD Band II: -1.14dBi

Bluetooth/BLE: 2.93dBi

WIFI: 2.93dBi GPS:0 dBi

GSM / GPRS: GMSK

EGPRS: GMSK

UMTS-FDD: QPSK, 16QAM

Type of Modulation: 802.11b/g/n: DSSS, OFDM

Bluetooth: GFSK, π /4DQPSK, 8DPSK

BLE: GFSK GPS:BPSK

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz

PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz

UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;

RF Operating Frequency (ies): RX: 1932.4 ~ 1987.6 MHz

WIFI:802.11b/g/n(20M): 2412-2462 MHz WIFI:802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz

GPS RX:1575.42 MHz



Test Report	16070658-FCC-H2
Page	7 of 10

GSM 850: 124CH PCS1900: 299CH

UMTS-FDD Band V : 102CH

UMTS-FDD Band II: 277CH

Number of Channels: WIFI:802.11b/g/n(20M): 11CH

WIFI:802.11n(40M): 7CH

Bluetooth: 79CH

BLE: 40CH GPS:1CH

Port: Power Port, Earphone Port, USB Port

Adapter:

Model:PC325

Input: AC 100-240V~50/60Hz,0.15A

Output: DC 5.0V,500mA

Input Power: Battery:

Model: BPX325

Spec:3.7V, 4.44Wh

Battery Capacity:1200mAh Limited charger voltage :4.2V

Trade Name: N/A

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: 2AIMEX325



Test Report	16070658-FCC-H2
Page	8 of 10

5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot \sqrt{f_{(GHz)}} \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, 16 where

- f_(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

result = $P\sqrt{F}/D$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm



Test Report	16070658-FCC-H2			
Page	9 of 10			

5.2 Test Result

Bluetooth Mode:

Modulation	СН	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	3.891	4.5±1	5.5	3.548	1.10	3
	Mid	2441	5.012	4.5±1	5.5	3.548	1.11	3
	High	2480	4.960	4.5±1	5.5	3.548	1.12	3
π /4 DQPSK	Low	2402	3.563	4.5±1	5.5	3.548	1.10	3
	Mid	2441	4.834	4.5±1	5.5	3.548	1.11	3
	High	2480	4.740	4.5±1	5.5	3.548	1.12	3
8-DPSK	Low	2402	3.746	4.5±1	5.5	3.548	1.10	3
	Mid	2441	4.933	4.5±1	5.5	3.548	1.11	3
	High	2480	4.887	4.5±1	5.5	3.548	1.12	3

WIFI Mode:

Modulation	СН	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
	Low	2412	9.61	8.8±1	9.8	9.550	2.97	3
802.11b	Mid	2437	9.43	8.8±1	9.8	9.550	2.98	3
	High	2462	8.80	8.8±1	9.8	9.550	3.00	3
802.11g	Low	2412	9.02	8.5±1	9.5	8.913	2.77	3
	Mid	2437	9.63	8.5±1	9.5	8.913	2.78	3
	High	2462	9.05	8.5±1	9.5	8.913	2.80	3
000 445	Low	2412	8.76	8.5±1	9.5	8.913	2.77	3
802.11n (20M)	Mid	2437	9.22	8.5±1	9.5	8.913	2.78	3
	High	2462	9.54	8.5±1	9.5	8.913	2.80	3
802.11n (40M)	Low	2422	9.11	8.5±1	9.5	8.913	2.77	3
	Mid	2437	9.60	8.5±1	9.5	8.913	2.78	3
	High	2452	8.74	8.5±1	9.5	8.913	2.79	3



Test Report	16070658-FCC-H2			
Page	10 of 10			

BLE Mode:

Modulation	СН	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-3.411	-3±1	-2	0.631	0.20	3
	Mid	2440	-2.674	-3±1	-2	0.631	0.20	3
	High	2480	-2.755	-3±1	-2	0.631	0.20	3

Result: Compliance

No SAR measurement is required.