

RF TEST REPORT



Report No.: 16071443-FCC-R3

Supersede Report No.: N/A

Applicant	SMT TELECOMM HK LIMITED	
Product Name	Mobile Phone	
Model No.	X455A	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2015, ANSI C63.10: 2013	
Test Date	Dec 15 to Dec 24, 2016	
Issue Date	Dec 24, 2016	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification		<input checked="" type="checkbox"/>
Equipment did not comply with the specification		<input type="checkbox"/>
Loren Luo	David Huang	
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	16071443-FCC-R3
Page	3 of 54

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	10
6.1 ANTENNA REQUIREMENT.....	10
6.2 DTS (6 DB&20 DB) CHANNEL BANDWIDTH.....	11
6.3 MAXIMUM OUTPUT POWER	17
6.4 POWER SPECTRAL DENSITY.....	21
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS	25
6.6 AC POWER LINE CONDUCTED EMISSIONS.....	31
6.7 RADIATED SPURIOUS EMISSIONS & RESTRICTED BAND	38
ANNEX A. TEST INSTRUMENT.....	45
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	46
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	49
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	53
ANNEX E. DECLARATION OF SIMILARITY	54

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16071443-FCC-R3	NONE	Original	Dec 24, 2016

2. Customer information

Applicant Name	SMT TELECOMM HK LIMITED
Applicant Add	Unit C 8/F, CHARMHILL CTR 50 HILLWOOD RD TST KL
Manufacturer	SMT TELECOMM HK LIMITED
Manufacturer Add	Unit C 8/F, CHARMHILL CTR 50 HILLWOOD RD TST KL

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT: Mobile Phone

Main Model: X455A

Serial Model: N/A

Date EUT received: Dec 14, 2016

Test Date(s): Dec 15 to Dec 24, 2016

Equipment Category : DTS

Antenna Gain: GSM850: 1.0dBi
PCS1900: 0.8dBi
UMTS-FDD Band V: 1.0dBi
UMTS-FDD Band II: 1.0dBi
Bluetooth/BLE/WIFI: 1.0dBi
GPS: 1.0dBi

Antenna Type: PIFA antenna

Type of Modulation: GSM / GPRS: GMSK
EGPRS: GMSK,8PSK
UMTS-FDD: QPSK
802.11b/g/n: DSSS, OFDM
Bluetooth: GFSK, π /4DQPSK, 8DPSK
BLE: GFSK
GPS:BPSK

Test Report No.	16071443-FCC-R3
Page	7 of 54

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
 PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
 UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
 UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz;
 RF Operating Frequency (ies): RX: 1932.4 ~ 1987.6 MHz
 WIFI: 802.11b/g/n(20M): 2412-2462 MHz
 WIFI: 802.11n(40M): 2422-2452 MHz
 Bluetooth& BLE: 2402-2480 MHz
 GPS: 1575.42 MHz

Max. Output Power:
 802.11b: 15.65dBm
 802.11g: 11.74dBm
 802.11n(20M): 12.41dBm
 802.11n(40M): 10.63dBm

Number of Channels:
 GSM 850: 124CH
 PCS1900: 299CH
 UMTS-FDD Band V: 102CH
 UMTS-FDD Band II: 277CH
 WIFI :802.11b/g/n(20M): 11CH
 WIFI :802.11n(40M): 7CH
 Bluetooth: 79CH
 BLE: 40CH
 GPS:1CH

Port: Power Port, Earphone Port, USB Port

Adapter:
 Model: PCX455A
 Input: AC100-240V, 50/60Hz,0.15A
 Output: DC 5.0V-500mA

Input Power:
 Battery:
 Model: BPX455A
 Voltage: 3.7V
 Battery Capacity: 1400mAh
 Charging limit voltage: 4.2V

Trade Name : N/A

Test Report No.	16071443-FCC-R3
Page	8 of 54

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: 2AIMEX455A

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas:

A permanently attached PIFA antenna for Bluetooth/BLE/WIFI/GPS, the gain is 1.0dBi for Bluetooth/BLE/WIFI/GPS.


A permanently attached PIFA antenna for GSM/PCS/UMTS, the gain is 1.0dBi for GSM850, 1.0dBi for PCS1900, 1.0dBi for UMTS-FDD Band V, 1.0dBi for UMTS-FDD Band II.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	24 °C
Relative Humidity	52%
Atmospheric Pressure	1019mbar
Test date :	Dec 19, 2016
Tested By :	Loren Luo

Spec	Item	Requirement	Applicable
§ 15.247(a)(2)	a)	6dB BW \geq 500kHz; 20dB BW \geq 500kHz;	<input checked="" type="checkbox"/>
	b)	99% BW: For FCC reference only; required by IC.	<input checked="" type="checkbox"/>
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 8.1 DTS bandwidth</p> <p><u>6dB bandwidth</u></p> <ol style="list-style-type: none"> Set RBW = 100 kHz. Set the video bandwidth (VBW) \geq 3 \times RBW. Detector = Peak. Trace mode = max hold. Sweep = auto couple. Allow the trace to stabilize. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. <p><u>20dB bandwidth</u></p> <p>C63.10 Occupied Bandwidth (OBW=20dB bandwidth)</p> <ol style="list-style-type: none"> Set RBW = 1%-5% OBW. Set the video bandwidth (VBW) \geq 3 x RBW. Set the span range between 2 times and 5 times of the OBW. Sweep time=Auto, Detector=PK, Trace=Max hold. Once the reference level is established, the equipment is conditioned with typical modulating signals to produce the worst- 		

	case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB levels with respect to the reference level.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A


Test Plot Yes (See below) N/A


Measurement result

Test mode	CH	Freq (MHz)	6dB Bandwidth (MHz)	20dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.598	14.357	≥ 0.5
	Mid	2437	9.594	14.348	≥ 0.5
	High	2462	9.593	14.353	≥ 0.5
802.11g	Low	2412	15.486	19.067	≥ 0.5
	Mid	2437	15.605	19.068	≥ 0.5
	High	2462	15.656	19.107	≥ 0.5
802.11n (20M)	Low	2412	16.214	19.329	≥ 0.5
	Mid	2437	16.054	19.401	≥ 0.5
	High	2462	16.101	19.483	≥ 0.5
802.11n (40M)	Low	2422	35.462	39.626	≥ 0.5
	Mid	2437	35.609	39.793	≥ 0.5
	High	2452	35.567	39.606	≥ 0.5


Test Plots


6dB Bandwidth measurement result





20 dB Bandwidth measurement result






6.3 Maximum Output Power

Temperature	24 °C
Relative Humidity	52%
Atmospheric Pressure	1019mbar
Test date :	Dec 19, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3), RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with \geq 75 channels: \leq 1 Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: \leq 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: \leq 0.125 Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with \geq 50 channels: \leq 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with \geq 25 & < 50 channels: \leq 0.25 Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: \leq 1 Watt	<input checked="" type="checkbox"/>
Test Setup		 Spectrum Analyzer EUT	
Test Procedure		<p>558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method</p> <p>Maximum output power measurement procedure</p> <ul style="list-style-type: none"> - a) Set span to at least 1.5 times the OBW. - b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz. - c) Set VBW \geq 3 x RBW. - d) Number of points in sweep \geq 2 \times span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.) - e) Sweep time = auto. - f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode. - g) If transmit duty cycle $<$ 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum 	

	<p>power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “ free run” .</p> <ul style="list-style-type: none"> - h) Trace average at least 100 traces in power averaging (i.e., RMS) mode. - i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’ s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A


Test Plot Yes (See below) N/A


Output Power measurement result

Type	Test mode	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	802.11b	Low	2412	15.27	30	Pass
		Mid	2437	15.53	30	Pass
		High	2462	15.65	30	Pass
	802.11g	Low	2412	11.64	30	Pass
		Mid	2437	11.74	30	Pass
		High	2462	11.60	30	Pass
	802.11n (20M)	Low	2412	11.42	30	Pass
		Mid	2437	12.41	30	Pass
		High	2462	12.40	30	Pass
	802.11n (40M)	Low	2422	10.63	30	Pass
		Mid	2437	10.41	30	Pass
		High	2452	10.55	30	Pass

Test Plots


The Average Power





6.4 Power Spectral Density

Temperature	24 °C
Relative Humidity	52%
Atmospheric Pressure	1019mbar
Test date :	Dec 19, 2016
Tested By :	Loren Luo

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	<input checked="" type="checkbox"/>
Test Setup		 Spectrum Analyzer EUT	
Test Procedure		<p>558074 D01 DTS MEAS Guidance v03r03, 10.2 power spectral density method power spectral density measurement procedure</p> <ul style="list-style-type: none"> - a) Set analyzer center frequency to DTS channel center frequency. - b) Set the span to 1.5 times the DTS bandwidth. - c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. - d) Set the VBW $\geq 3 \times \text{RBW}$. - e) Detector = peak. - f) Sweep time = auto couple. - g) Trace mode = max hold. - h) Allow trace to fully stabilize. - i) Use the peak marker function to determine the maximum amplitude level within the RBW. - j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat. 	
Remark			
Result		<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	


Test Data Yes N/A
 Test Plot Yes (See below) N/A


Power Spectral Density measurement result

Type	Test mode	CH	Freq (MHz)	PSD	Limit (dBm)	Result
				(dBm)		
PSD	802.11b	Low	2412	-6.152	8	Pass
		Mid	2437	-8.121	8	Pass
		High	2462	-8.145	8	Pass
	802.11g	Low	2412	-11.40	8	Pass
		Mid	2437	-12.11	8	Pass
		High	2462	-11.28	8	Pass
	802.11n	Low	2412	-12.15	8	Pass
	(20M)	Mid	2437	-10.83	8	Pass
		High	2462	-11.09	8	Pass
		Low	2422	-12.25	8	Pass
	802.11n (40M)	Mid	2437	-14.49	8	Pass
		High	2452	-15.02	8	Pass

Test Plots

Power Spectral Density measurement result






6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	24 °C
Relative Humidity	57%
Atmospheric Pressure	1015mbar
Test date :	Dec 15, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>
Test Setup	 <p>The diagram illustrates the test setup. A Turn Table is positioned on a Ground Plane. An EUT & Support Units is placed on the turn table. A vertical Ant. Tower is mounted on the turn table, with a 1-4m Variable height adjustment. A Test Receiver is connected to the Ant. Tower. A dimension of 3m is shown between the EUT & Support Units and the Ant. Tower. A height dimension of 0.8/1.5m is shown for the EUT & Support Units.</p>		
Test Procedure	<p>Radiated Method Only</p> <ul style="list-style-type: none"> - 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. - 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range. 		


	<ul style="list-style-type: none"> - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail




Test Data Yes N/A



Test Plot Yes (See below) N/A



Test Plots

Band Edge measurement result



 <p>* RBW 1 MHz * Att 5 dB Batt Ref 102.0 dBμV 1Pk Max Tdf</p> <p>Limit Check Line Limit 74 90 dBμV 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV</p> <p>M2[1] 52.52 dBμV 2.389520000 GHz M1[1] 58.72 dBμV 2.400000000 GHz</p> <p>F1 F2</p> <p>CF 2.39 GHz Span 80.0 MHz</p>	 <p>* RBW 1 MHz * Att 5 dB Batt Ref 102.0 dBμV 1Pk Max Tdf</p> <p>Limit 74 Limit Check Line Limit 74 90 dBμV 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV</p> <p>M1[1] 50.18 dBμV 2.504740000 GHz M1</p> <p>F1</p> <p>CF 2.4835 GHz Span 80.0 MHz</p>
<p>Date: 15.DEC.2016 16:39:17</p> <p>Band Edge, Left Side (Peak) - 802.11g</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Date: 15.DEC.2016 16:53:51</p> <p>Band Edge, Right Side (Peak) - 802.11g</p> <p>Note: F1 is frequency 2483.5MHz</p>
 <p>* RBW 1 MHz * Att 5 dB Batt Ref 102.0 dBμV 1Pk Max Tdf</p> <p>Limit Check Line Limit 54 90 dBμV 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV</p> <p>M2[1] 40.83 dBμV 2.400000000 GHz M1[1] 37.70 dBμV 2.390000000 GHz</p> <p>F1 F2</p> <p>CF 2.39 GHz Span 80.0 MHz</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p>Date: 15.DEC.2016 16:40:31</p> <p>Band Edge, Left Side (Average) - 802.11g</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Band Edge, Right Side (Average) - 802.11g</p> <p>Note: F1 is frequency 2483.5MHz</p>


 <p>* RBW 1 MHz * Att 5 dB Batt Ref 102.0 dBμV M2[1] 51.72 dBμV 2.387600000 GHz</p> <p>Limit Check Line Limit 74 1Pk Max 90 dBμV Tdf 50 dBμV 80 dBμV 60 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV CF 2.39 GHz Span 80.0 MHz</p> <p>PASS M1[1] M2 M1 F1 F2</p>	 <p>* RBW 1 MHz * Att 5 dB Batt Ref 102.0 dBμV M1[1] 50.72 dBμV 2.488130000 GHz</p> <p>Limit 74 Limit Check Line Limit 74 1Pk Max 90 dBμV Tdf 50 dBμV 80 dBμV 60 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV CF 2.4835 GHz Span 80.0 MHz</p> <p>PASS M1 F1</p>
<p>Date: 15.DEC.2016 16:44:06</p> <p>Band Edge, Left Side (Peak) - 802.11n20</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Date: 15.DEC.2016 16:55:56</p> <p>Band Edge, Right Side (Peak) - 802.11n20</p> <p>Note: F1 is frequency 2483.5MHz</p>
<p>Note: (no need if PK value less than the AV limit)</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p>Band Edge, Left Side (Average) - 802.11n20</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Band Edge, Right Side (Average) - 802.11n20</p> <p>Note: F1 is frequency 2483.5MHz</p>

 <p>* RBW 1 MHz * Att 5 dB Batt Ref 102.0 dBµV 1Pk Max 10 dBµV 20 dBµV 30 dBµV 40 dBµV 50 dBµV 60 dBµV 70 dBµV 80 dBµV 90 dBµV Tdf</p> <p>CF 2.39 GHz Span 120.0 MHz</p> <p>M2[1] 52.27 dBµV 2.389280000 GHz M1[1] 53.85 dBµV 2.400000000 GHz</p> <p>PASS M1[1] PASS Limit Check Line Limit 74 Limit 74</p>	 <p>* RBW 1 MHz * Att 5 dB Batt Ref 102.0 dBµV 1Pk Max 10 dBµV 20 dBµV 30 dBµV 40 dBµV 50 dBµV 60 dBµV 70 dBµV 80 dBµV 90 dBµV Tdf</p> <p>CF 2.4835 GHz Span 120.0 MHz</p> <p>M1[1] 53.11 dBµV 2.483340000 GHz M1 Limit 74 Limit Check Line Limit 74 PASS PASS F1</p>
<p>Date: 15.DEC.2016 16:47:04</p> <p>Band Edge, Left Side (Peak) - 802.11n40</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Date: 15.DEC.2016 16:58:46</p> <p>Band Edge, Right Side (Peak) - 802.11n40</p> <p>Note: F1 is frequency 2483.5MHz</p>
<p>Note: (no need if PK value less than the AV limit)</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p>Band Edge, Left Side (Average) - 802.11n40</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Band Edge, Right Side (Average) - 802.11n40</p> <p>Note: F1 is frequency 2483.5MHz</p>

6.6 AC Power Line Conducted Emissions

Temperature	24 °C
Relative Humidity	57%
Atmospheric Pressure	1015mbar
Test date :	Dec 15, 2016
Tested By :	Loren Luo

Requirement(s):


Spec	Item	Requirement	Applicable														
47CFR§15. 207, RSS210 (A8.1)	a)	<p>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.</p> <table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency ranges (MHz)	Limit (dB μ V)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50	<input checked="" type="checkbox"/>
Frequency ranges (MHz)	Limit (dB μ V)																
	QP	Average															
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															
Test Setup	 <p>Note: 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>																
Procedure	<ol style="list-style-type: none"> 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. 2. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. 3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss 																

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A


Test Mode: Transmitting Mode



Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)
1	L1	0.1851	33.18	QP	10.03	43.21	64.25	-21.04
2	L1	0.1851	16.73	AVG	10.03	26.76	54.25	-27.49
3	L1	0.4191	32.27	QP	10.03	42.30	57.47	-15.17
4	L1	0.4191	22.16	AVG	10.03	32.19	47.47	-15.28
5	L1	0.5049	30.69	QP	10.03	40.72	56.00	-15.28
6	L1	0.5049	11.02	AVG	10.03	21.05	46.00	-24.95
7	L1	0.9456	25.14	QP	10.03	35.17	56.00	-20.83
8	L1	0.9456	6.77	AVG	10.03	16.80	46.00	-29.20
9	L1	2.8839	21.28	QP	10.05	31.33	56.00	-24.67
10	L1	2.8839	9.28	AVG	10.05	19.33	46.00	-26.67
11	L1	3.8196	19.78	QP	10.07	29.85	56.00	-26.15
12	L1	3.8196	9.11	AVG	10.07	19.18	46.00	-26.82

Test Mode: Transmitting Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)
1	N	0.1890	33.76	QP	10.02	43.78	64.08	-20.30
2	N	0.1890	15.72	AVG	10.02	25.74	54.08	-28.34
3	N	0.4659	25.38	QP	10.02	35.40	56.59	-21.19
4	N	0.4659	16.30	AVG	10.02	26.32	46.59	-20.27
5	N	0.5166	25.74	QP	10.02	35.76	56.00	-20.24
6	N	0.5166	16.66	AVG	10.02	26.68	46.00	-19.32
7	N	0.9531	19.33	QP	10.03	29.36	56.00	-26.64
8	N	0.9531	7.72	AVG	10.03	17.75	46.00	-28.25
9	N	1.9011	17.70	QP	10.04	27.74	56.00	-28.26
10	N	1.9011	6.83	AVG	10.04	16.87	46.00	-29.13
11	N	4.6263	17.55	QP	10.07	27.62	56.00	-28.38
12	N	4.6263	7.98	AVG	10.07	18.05	46.00	-27.95

Test Report No.	16071443-FCC-R3
Page	35 of 54

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)
1	L1	0.4035	39.38	QP	10.03	49.41	57.78	-8.37
2	L1	0.4035	32.22	AVG	10.03	42.25	47.78	-5.53
3	L1	0.4932	38.52	QP	10.03	48.55	56.11	-7.56
4	L1	0.4932	32.18	AVG	10.03	42.21	46.11	-3.90
5	L1	0.9729	32.88	QP	10.03	42.91	56.00	-13.09
6	L1	0.9729	26.21	AVG	10.03	36.24	46.00	-9.76
7	L1	2.0337	38.32	QP	10.04	48.36	56.00	-7.64
8	L1	2.0337	28.87	AVG	10.04	38.91	46.00	-7.09
9	L1	4.3884	38.51	QP	10.07	48.58	56.00	-7.42
10	L1	4.3884	27.43	AVG	10.07	37.50	46.00	-8.50
11	L1	5.1177	38.67	QP	10.08	48.75	60.00	-11.25
12	L1	5.1177	30.48	AVG	10.08	40.56	50.00	-9.44

Test Mode: Transmitting Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)
1	N	0.3957	33.66	QP	10.02	43.68	57.94	-14.26
2	N	0.3957	17.60	AVG	10.02	27.62	47.94	-20.32
3	N	0.4971	43.88	QP	10.02	53.90	56.05	-2.15
4	N	0.4971	34.41	AVG	10.02	44.43	46.05	-1.62
5	N	0.6141	31.23	QP	10.02	41.25	56.00	-14.75
6	N	0.6141	17.28	AVG	10.02	27.30	46.00	-18.70
7	N	1.1835	31.66	QP	10.03	41.69	56.00	-14.31
8	N	1.1835	17.65	AVG	10.03	27.68	46.00	-18.32
9	N	2.0922	34.55	QP	10.04	44.59	56.00	-11.41
10	N	2.0922	20.11	AVG	10.04	30.15	46.00	-15.85
11	N	3.6279	33.62	QP	10.06	43.68	56.00	-12.32
12	N	3.6279	18.65	AVG	10.06	28.71	46.00	-17.29

6.7 Radiated Spurious Emissions & Restricted Band

Temperature	24 °C
Relative Humidity	52%
Atmospheric Pressure	1019mbar
Test date :	Dec 19, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15. 247(d), RSS210 (A8.5)	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (µV/m)</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 – 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 – 960	200	Above 960	500	<input checked="" type="checkbox"/>
Frequency range (MHz)	Field Strength (µV/m)												
30 – 88	100												
88 – 216	150												
216 – 960	200												
Above 960	500												
	b)	<p>For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required</p> <p><input checked="" type="checkbox"/> 20 dB down <input type="checkbox"/> 30 dB down</p>	<input checked="" type="checkbox"/>										
	c)	or restricted band, emission must also comply with the radiated	<input checked="" type="checkbox"/>										

		emission limits specified in 15.209	
Test Setup		 <p>The diagram illustrates the test setup. A 'Turn Table' holds the 'EUT & Support Units'. The distance from the turn table to the 'Ant. Tower' is 3m. The 'Ant. Tower' is a vertical mast with a height of '1-4m Variable'. The 'EUT & Support Units' are mounted on a height of '0.8/1.5m'. The entire setup is positioned above a 'Ground Plane'. A 'Test Receiver' is connected to the 'Ant. Tower' to measure emissions.</p>	
Procedure		<ol style="list-style-type: none"> 1. The EUT was switched on and allowed to warm up to its normal operating condition. 2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured. 	
Remark		Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Report No.	16071443-FCC-R3
Page	40 of 54


Test Plot

Yes (See below)

N/A

Test Mode: Transmitting Mode

(Below 1GHz)




Test Data

Vertical Polarity Plot @3m

No	P/L	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)	Height	Degree
1	V	31.3992	26.65	peak	-1.29	25.36	40.00	-14.64	100	159
2	V	49.0145	36.86	peak	-12.74	24.12	40.00	-15.88	100	65
3	V	92.7872	39.17	peak	-12.68	26.49	43.50	-17.01	100	78
4	V	177.5092	33.64	peak	-9.69	23.95	43.50	-19.55	100	247
5	V	477.1694	30.60	peak	-2.33	28.27	46.00	-17.73	100	103
6	V	896.9965	29.64	peak	4.64	34.28	46.00	-11.72	100	92

(Below 1GHz)



Test Data

Horizontal Polarity Plot @3m

No	P/L	Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)	Height	Degree
1	H	31.9546	26.33	peak	-1.71	24.62	40.00	-15.38	100	182
2	H	99.5281	28.93	peak	-10.92	18.01	43.50	-25.49	100	309
3	H	180.0165	30.06	peak	-9.89	20.17	43.50	-23.33	100	264
4	H	290.0172	27.50	peak	-7.36	20.14	46.00	-25.86	100	144
5	H	836.2443	27.40	peak	3.64	31.04	46.00	-14.96	100	156
6	H	896.9965	33.47	peak	4.64	38.11	46.00	-7.89	100	97

Above 1GHz

Test Mode:	Transmitting Mode
-------------------	--------------------------

Low Channel (2412 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4824	39.49	AV	V	33.8	6.86	32.69	47.46	54	-6.54
4824	39.31	AV	H	33.8	6.86	32.69	47.28	54	-6.72
4824	49.11	PK	V	33.8	6.86	32.69	57.08	74	-16.92
4824	48.94	PK	H	33.8	6.86	32.69	56.91	74	-17.09
17931	25.11	AV	V	45.12	11.57	32.11	49.69	54	-4.31
17931	25.08	AV	H	45.12	11.57	32.11	49.66	54	-4.34
17931	42.15	PK	V	45.12	11.57	32.11	66.73	74	-7.27
17931	42.1	PK	H	45.12	11.57	32.11	66.68	74	-7.32

Middle Channel (2437 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4874	39.62	AV	V	33.6	6.82	32.71	47.33	54	-6.67
4874	39.44	AV	H	33.6	6.82	32.71	47.15	54	-6.85
4874	49.23	PK	V	33.6	6.82	32.71	56.94	74	-17.06
4874	49.16	PK	H	33.6	6.82	32.71	56.87	74	-17.13
17940	24.97	AV	V	45.17	11.63	32.18	49.59	54	-4.41
17940	24.88	AV	H	45.17	11.63	32.18	49.5	54	-4.5
17940	41.85	PK	V	45.17	11.63	32.18	66.47	74	-7.53
17940	41.69	PK	H	45.17	11.63	32.18	66.31	74	-7.69

High Channel (2452 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4924	39.42	AV	V	33.83	6.95	32.79	47.41	54	-6.59
4924	39.33	AV	H	33.83	6.95	32.79	47.32	54	-6.68
4924	49.26	PK	V	33.83	6.95	32.79	57.25	74	-16.75
4924	49.22	PK	H	33.83	6.95	32.79	57.21	74	-16.79
17922	24.93	AV	V	45.19	11.61	32.24	49.49	54	-4.51
17922	24.65	AV	H	45.19	11.61	32.24	49.21	54	-4.79
17922	41.86	PK	V	45.19	11.61	32.24	66.42	74	-7.58
17922	41.64	PK	H	45.19	11.61	32.24	66.2	74	-7.8

Note:

- 1, The testing has been conformed to $10 \times 2462\text{MHz} = 24,620\text{MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>

Annex B. EUT and Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Test Report No.	16071443-FCC-R3
Page	47 of 54

Annex B.ii. Photograph: EUT Internal Photo


Test Report No.	16071443-FCC-R3
Page	48 of 54

Annex B.iii. Photograph: Test Setup Photo


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
SMT TELECOMM HK LIMITED	Adapter	PCX455A	D2156273

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	D2156273

Test Report No.	16071443-FCC-R3
Page	53 of 54

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Test Report No.	16071443-FCC-R3
Page	54 of 54

Annex E. DECLARATION OF SIMILARITY

N/A