

## 5.6 BAND EDGE AT ANTENNA TERMINALS

**Test Requirement:** FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 24.238(a)

**Test Method:** ANSI/TIA-603-E-2016 & KDB 971168 D01v03

**Limit:**

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to -13 dBm

**Test Procedure:**

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer.

For each band edge measurement:

- 1) Set the spectrum analyzer span to include the block edge frequency.
- 2) Set a marker to point the corresponding band edge frequency in each test case.
- 3) Set display line at -13 dBm
- 4) Set resolution bandwidth to at least 1% of emission bandwidth.
- 5) Set spectrum analyzer with RMS detector.
- 6) Record the max trace plot into the test report

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.



**Test Setup:** Refer to section 4.2.2 for details.


**Instruments Used:** Refer to section 3 for details

**Test Mode:** Link mode

**Test Results:** Pass

The test plot as follows:





## 5.7 SPURIOUS EMISSIONS AT ANTENNA TERMINALS

**Test Requirement:** FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 24.238(a)(b)

**Test Method:** ANSI/TIA-603-E-2016 & KDB 971168 D01v03

**Limit:**

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to -13 dBm

**Test Procedure:**

The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range. b. Measuring frequency range is from 30 MHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower. Set RBW & VBW to 100 kHz for the measurement below 1 GHz, and 1 MHz for the measurement above 1 GHz.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.


**Test Setup:** Refer to section 4.2.2 for details.


**Instruments Used:** Refer to section 3 for details


**Test Mode:** Link mode

**Test Results:** Pass

The test plot as follows:







## 5.8 FIELD STRENGTH OF SPURIOUS RADIATION

**Test Requirement:** FCC 47 CFR Part 2.1053 & FCC 47 CFR Part 24.238(a)(b)

**Test Method:** ANSI/TIA-603-E-2016 & KDB 971168 D01v03

**Receiver Setup:**

Frequency	Detector	RBW	VBW	Remark
0.009 MHz-30 MHz	Peak	10 kHz	30 KHz	Peak
30 MHz-1 GHz	Quasi-peak	100 kHz	300 KHz	Peak
Above 1 GHz	Peak	1 MHz	3 MHz	Peak

**Limits:**

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to -13 dBm

**Test Setup:** Refer to section 4.2.1 for details.

**Test Procedures:**

1. Scan up to 10th harmonic, find the maximum radiation frequency to measure.
2. The technique used to find the Spurious Emissions of the transmitter was the antenna substitution method. Substitution method was performed to determine the actual ERP/EIRP emission levels of the EUT.

Test procedure as below:

- 1) The EUT was powered ON and placed on a 0.8/1.5m high table at a 3 meter semi/fully Anechoic Chamber. The antenna of the transmitter was extended to its maximum length. Modulation mode and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- 2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- 3) The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 4) Steps 1) to 3) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 5) The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 6) A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 3) is obtained for this set of conditions.
- 7) The output power into the substitution antenna was then measured.
- 8) Steps 6) and 7) were repeated with both antennas polarized.
- 9) Calculate power in dBm by the following formula:

$$\text{ERP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$

$$\text{EIRP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBi)}$$

$$\text{EIRP} = \text{ERP} + 2.15 \text{dB}$$

where:

Pg is the generator output power into the substitution antenna.

- 10) Test the EUT in the lowest channel, the middle channel the Highest channel
- 11) The radiation measurements are performed in X, Y, Z axis positioning for EUT operation mode, and found the Y axis positioning which it is worse case.
- 12) Repeat above procedures until all frequencies measured was complete.

**Equipment Used:** Refer to section 3 for details.


**Test Result:** Pass

**The measurement data as follows:**


## Radiated Emission Test Data


## GSM 1Tx-slot\_Lowest Channel


## Horizontal





No.	Frequency (MHz)	Reading (dBm)	Correction factor (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	3700.400	-107.43	55.96	-51.47	-13.00	-38.47	Peak
2	5550.600	-113.11	63.99	-49.12	-13.00	-36.12	Peak
3	7400.800	453.89	-500.00	-46.11	-13.00	-33.11	Peak
4	9251.000	458.44	-500.00	-41.56	-13.00	-28.56	Peak
5	11101.200	455.56	-500.00	-44.44	-13.00	-31.44	Peak
6	12951.400	456.75	-500.00	-43.25	-13.00	-30.25	Peak














**WCDMA RMC 12.2Kbps\_Lowest Channel**
**Horizontal**



No.	Frequency (MHz)	Reading (dBm)	Correction factor (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	3704.800	-104.76	55.98	-48.78	-13.00	-35.78	Peak
2	5557.200	-104.53	64.03	-40.50	-13.00	-27.50	Peak
3	7409.600	462.39	-500.00	-37.61	-13.00	-24.61	Peak
4	9262.000	455.39	-500.00	-44.61	-13.00	-31.61	Peak
5	11114.400	455.56	-500.00	-44.44	-13.00	-31.44	Peak
6	12966.800	458.20	-500.00	-41.80	-13.00	-28.80	Peak




No.	Frequency (MHz)	Reading (dBm)	Correction factor (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	3704.800	-103.50	55.98	-47.52	-13.00	-34.52	Peak
2	5557.200	-108.87	64.03	-44.84	-13.00	-31.84	Peak
3	7409.600	464.69	-500.00	-35.31	-13.00	-22.31	Peak
4	9262.000	456.53	-500.00	-43.47	-13.00	-30.47	Peak
5	11114.400	456.25	-500.00	-43.75	-13.00	-30.75	Peak
6	12966.800	457.01	-500.00	-42.99	-13.00	-29.99	Peak


**WCDMA RMC 12.2Kbps\_Middle Channel**
**Horizontal**


No.	Frequency (MHz)	Reading (dBm)	Correction factor (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	3760.000	-104.27	56.30	-47.97	-13.00	-34.97	Peak
2	5640.000	-103.61	64.64	-38.97	-13.00	-25.97	Peak
3	7520.000	466.41	-500.00	-33.59	-13.00	-20.59	Peak
4	9400.000	455.04	-500.00	-44.96	-13.00	-31.96	Peak
5	11280.000	455.94	-500.00	-44.06	-13.00	-31.06	Peak
6	13160.000	456.99	-500.00	-43.01	-13.00	-30.01	Peak



**WCDMA RMC 12.2Kbps\_Highest Channel**
**Horizontal**


No.	Frequency (MHz)	Reading (dBm)	Correction factor (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	3815.200	-103.46	56.62	-46.84	-13.00	-33.84	Peak
2	5722.800	-97.68	65.24	-32.44	-13.00	-19.44	Peak
3	7630.400	469.12	-500.00	-30.88	-13.00	-17.88	Peak
4	9538.000	455.90	-500.00	-44.10	-13.00	-31.10	Peak
5	11445.600	456.79	-500.00	-43.21	-13.00	-30.21	Peak
6	13353.200	457.53	-500.00	-42.47	-13.00	-29.47	Peak


**Remark:**

- 1) The disturbance above 18GHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 2) All tested is under the condition of the main wave is filtered out.
- 3) All the above radiation data, the fundamental frequency is not marked, it may exceed the limit, please ignore it.

## 5.9 FREQUENCY STABILITY

**Test Requirement:** FCC 47 CFR Part 2.1055 & FCC 47 CFR Part 24.235

**Test Method:** ANSI/TIA-603-E-2016 & KDB 971168 D01v03

**Limits:** The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

**Test Setup:** Refer to section 4.2.2 for details.

**Test Procedures:**

- 1) Use CMW 500 or CMU 200 with Frequency Error measurement capability.
  - a) Temp. = -30° to + 50°C
  - b) Voltage = low voltage, 3.5 Vdc, Normal, 3.8 Vdc and High voltage, 4.3 Vdc.

- 2) Frequency Stability vs Temperature:

The EUT is place inside a temperature chamber. The temperature is set to 20°C and allowed to stabilize. After sufficient soak time, the transmitting frequency error is measured. The temperature is increased by 10 degrees, allowed to stabilize and soak, and then the measurement is repeated. This is repeated until +50°C is reached.

- 3) Frequency Stability vs Voltage:

The peak frequency error is recorded (worst-case).

**Equipment Used:** Refer to section 3 for details.

**Test Result:** Pass

Modulation	Channel/ Frequency (MHz)	Voltage	Temperature	Deviation	Deviation	Limit	Pass/ Fail
		(Vdc)	(°C)	(Hz)	(ppm)	(ppm)	
<b>GSM 1Tx-slot</b>							
GMSK	661 / 1880.0	VL	TN	19	0.0101	Note 1	Pass
		VN		21	0.0112		Pass
		VH		20	0.0106		Pass
		50	VN	20	0.0106		Pass
		40		20	0.0106		Pass
		30		14	0.0074		Pass
		20		16	0.0085		Pass
		10		14	0.0074		Pass
		0		18	0.0096		Pass
		-10		20	0.0106		Pass
		-20		17	0.0090		Pass
		-30		17	0.0090		Pass

Modulation	Channel/ Frequency	Voltage	Temperature	Deviation	Deviation	Limit	Pass/ Fail
	(MHz)	(Vdc)	(°C)	(Hz)	(ppm)	(ppm)	
<b>WCDMA RMC 12.2Kbps</b>							
BPSK	9400 / 1880.0	VL	TN	23	0.0122	Note 1	Pass
		VN		21	0.0112		Pass
		VH		23	0.0122		Pass
		50		25	0.0133		Pass
		40	VN	24	0.0128		Pass
		30		20	0.0106		Pass
		20		20	0.0106		Pass
		10		24	0.0128		Pass
		0		23	0.0122		Pass
		-10		18	0.0096		Pass
		-20		22	0.0117		Pass
		-30		23	0.0122		Pass

**Note1:** The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

## APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

## APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

\*\*\* End of Report \*\*\*

---

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

---