

FCC RADIO TEST REPORT

FCC ID : 2AIP8-SR00300W
Equipment : Smartphone
Brand Name : SIRIN LABS
Model Name : SR00300-W
Applicant : SIRIN LABS AG
Freier Platz 10, 8200 Schaffhausen, Switzerland
Manufacturer : SIRIN LABS AG
Freier Platz 10, 8200 Schaffhausen, Switzerland
Standard : FCC Part 15 Subpart C §15.247

The product was received on Oct. 05, 2018 and testing was started from Oct. 18, 2018 and completed on Nov. 02, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Joseph Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	9
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	18
3.3 Power Spectral Density Measurement	19
3.4 Conducted Band Edges and Spurious Emission Measurement	26
3.5 Radiated Band Edges and Spurious Emission Measurement	35
3.6 AC Conducted Emission Measurement.....	39
3.7 Antenna Requirements.....	41
4 List of Measuring Equipment	42
5 Uncertainty of Evaluation.....	44
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FR8O0518B	01	Initial issue of report	Nov. 21, 2018

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Peak Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 5.62 dB at 70.770 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 11.91 dB at 0.152 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Reviewed by: Wii Chang

Report Producer: Yimin Ho



1 General Description

1.1 Product Feature of Equipment Under Test

GSM/CDMA/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, NFC, and GNSS.

Product Specification subjective to this standard	
Antenna Type	WWAN: PIFA Antenna WLAN: <Ant. 1>: PIFA Antenna <Ant. 2>: PIFA Antenna Bluetooth: PIFA Antenna GPS/Glonass/BDS/Galileo: PIFA Antenna NFC: Loop Antenna

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH15-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.



1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
AC Conducted Emission	Mode 1: WCDMA Band V Idle + Bluetooth Link + WLAN (2.4GHz) Link + MPEG4 + USB Type C Cable (Charging form Adapter)

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude E3340	FCC DoC/ Contains FCC ID: PD97260NGU	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility "QRCT" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


<1Mbps>

6 dB Bandwidth Plot on Channel 00



Date: 2.NOV.2018 21:27:40


6 dB Bandwidth Plot on Channel 19



Date: 2.NOV.2018 21:32:11




6 dB Bandwidth Plot on Channel 39




<2Mbps>

6 dB Bandwidth Plot on Channel 00






6 dB Bandwidth Plot on Channel 19



6 dB Bandwidth Plot on Channel 39






3.1.6 Test Result of 99% Occupied Bandwidth


Please refer to Appendix A.

<1Mbps>

99% Bandwidth Plot on Channel 00




99% Occupied Bandwidth Plot on Channel 19








99% Occupied Bandwidth Plot on Channel 39



<2Mbps>

99% Bandwidth Plot on Channel 00



99% Occupied Bandwidth Plot on Channel 19

99% Occupied Bandwidth Plot on Channel 39


Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Peak Power, the testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v05 section 9.1.3 PKPM1 Peak power meter method.
2. For Average Power, the testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v05 section 9.2.3.1 Method AVGPM.
3. The RF output of EUT was connected to the power meter by RF cable and attenuator.
4. The path loss was compensated to the results for each measurement.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density


Please refer to Appendix A.



3.3.6 Test Result of Power Spectral Density Plots (100kHz)


<1Mbps>

PSD 100kHz Plot on Channel 00



Date: 2.NOV.2018 21:28:11


PSD 100kHz Plot on Channel 19



Date: 2.NOV.2018 21:33:18




PSD 100kHz Plot on Channel 39




<2Mbps>

PSD 100kHz Plot on Channel 00






PSD 100kHz Plot on Channel 19



PSD 100kHz Plot on Channel 39






3.3.7 Test Result of Power Spectral Density Plots (3kHz)


<1Mbps>

PSD 3kHz Plot on Channel 00



Date: 2.NOV.2018 21:27:58


PSD 3kHz Plot on Channel 19



Date: 2.NOV.2018 21:32:29




PSD 3kHz Plot on Channel 39




<2Mbps>

PSD 3kHz Plot on Channel 00






PSD 3kHz Plot on Channel 19



PSD 3kHz Plot on Channel 39



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup







3.4.5 Test Result of Conducted Band Edges Plots

<1Mbps>

Low Band Edge Plot on Channel 00




High Band Edge Plot on Channel 39






<2Mbps>

Low Band Edge Plot on Channel 00



Date: 2.NOV.2018 21:39:30

High Band Edge Plot on Channel 39



Date: 2.NOV.2018 21:45:45




3.4.6 Test Result of Conducted Spurious Emission Plots

<1Mbps>

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00



Date: 2.NOV.2018 21:30:39

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00




Date: 2.NOV.2018 21:30:53





Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps****GFSK Channel 39****Conducted Spurious Emission Plot on Bluetooth LE 1Mbps****GFSK Channel 39**

<2Mbps>

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps


GFSK Channel 00



Date: 2.NOV.2018 21:40:27

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps


GFSK Channel 00




Date: 2.NOV.2018 21:40:39





Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19



Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19



**Conducted Spurious Emission Plot on Bluetooth LE 2Mbps
GFSK Channel 39****Conducted Spurious Emission Plot on Bluetooth LE 2Mbps
GFSK Channel 39**

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


See list of measuring equipment of this test report.

3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Oct. 29, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Dec. 08, 2017	Oct. 29, 2018	Dec. 07, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Oct. 29, 2018	Nov. 29, 2018	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Oct. 29, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Oct. 29, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Oct. 29, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	Oct. 23, 2018 ~ Oct. 26, 2018	Nov. 22, 2018	Radiation (03CH15-HY)
Preamplifier	Jet-Power	JPA0118-55-303	17100018000550006	1GHz~18GHz	Jul. 10, 2018	Oct. 24, 2018 ~ Oct. 27, 2018	Jul. 09, 2019	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 26, 2017	Oct. 24, 2018 ~ Oct. 27, 2018	Dec. 25, 2018	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL6111D&00800N1D01N-06	41912&05	30MHz to 1GHz	Jan. 10, 2018	Oct. 24, 2018 ~ Oct. 27, 2018	Jan. 09, 2019	Radiation (03CH15-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY54130085	20Hz ~ 8.4GHz	Oct. 31, 2017	Oct. 24, 2018 ~ Oct. 27, 2018	Oct. 30, 2018	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBEC K	BBHA 9120D	9120D-1620	1G~18GHz	Oct. 17, 2018	Oct. 24, 2018 ~ Oct. 27, 2018	Oct. 16, 2019	Radiation (03CH15-HY)
Preamplifier	Keysight	83017A	MY53270195	1GHz~26.5GHz	Aug. 23, 2018	Oct. 24, 2018 ~ Oct. 27, 2018	Aug. 22, 2019	Radiation (03CH15-HY)
Spectrum Analyzer	Agilent	E4446A	MY50180136	3Hz~44GHz	Apr. 25, 2018	Oct. 24, 2018 ~ Oct. 27, 2018	Apr. 24, 2019	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Oct. 24, 2018 ~ Oct. 27, 2018	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Oct. 24, 2018 ~ Oct. 27, 2018	N/A	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBEC K	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 27, 2017	Oct. 24, 2018 ~ Oct. 27, 2018	Nov. 26, 2018	Radiation (03CH15-HY)
Software	Audix	E3 6.2009-8-24	RK-000451	N/A	N/A	Oct. 24, 2018 ~ Oct. 27, 2018	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER / MTJ Cooperation	SUCOFLEX 104 / 000000-MT18A-100	MY36980/4, MY9838/4P E, D3210	30MHz~1GHz	Mar. 15, 2018	Oct. 24, 2018 ~ Oct. 27, 2018	Mar. 14, 2019	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER / MTJ Cooperation	SUCOFLEX 104 / 000000-MT18A-100	MY36980/4, MY9838/4P E, D3210	1GHz~18GHz	Mar. 15, 2018	Oct. 24, 2018 ~ Oct. 27, 2018	Mar. 14, 2019	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30M~40GHz	Mar. 14, 2018	Oct. 24, 2018 ~ Oct. 27, 2018	Mar. 13, 2019	Radiation (03CH15-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB4129234 4	N/A	Dec. 20, 2017	Oct. 18, 2018 ~ Nov. 02, 2018	Dec. 19, 2018	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US4044154 8	50MHz~18GHz	Dec. 20, 2017	Oct. 18, 2018 ~ Nov. 02, 2018	Dec. 19, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2017	Oct. 18, 2018 ~ Nov. 02, 2018	Nov. 20, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV 30	100895	9kHz~30GHz	Apr. 20, 2018	Oct. 18, 2018 ~ Nov. 02, 2018	Apr. 19, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1300484	N/A	Mar. 01, 2018	Oct. 18, 2018 ~ Nov. 02, 2018	Feb. 28, 2019	Conducted (TH05-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.2
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.5
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
---	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Howard Lin and Derek Hsu	Temperature:	21~25	°C
Test Date:	2018/10/18 ~ 2018/11/02	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.023	0.667	0.50	Pass
BLE	1Mbps	1	19	2440	1.019	0.663	0.50	Pass
BLE	1Mbps	1	39	2480	1.025	0.665	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	7.60	30.00	-2.40	5.20	36.00	Pass
BLE	1Mbps	1	19	2440	6.92	30.00	-2.40	4.52	36.00	Pass
BLE	1Mbps	1	39	2480	7.51	30.00	-2.40	5.11	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	0.71	7.32
BLE	1Mbps	1	19	2440	0.71	6.68
BLE	1Mbps	1	39	2480	0.71	7.20

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	5.50	-10.69	-2.40	8.00	Pass
BLE	1Mbps	1	19	2440	4.99	-11.26	-2.40	8.00	Pass
BLE	1Mbps	1	39	2480	5.26	-10.79	-2.40	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Test Engineer:	Howard Lin and Derek Hsu	Temperature:	21~25	°C
Test Date:	2018/10/18 ~ 2018/11/02	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	2.030	1.139	0.50	Pass
BLE5.0	2Mbps	1	19	2440	2.030	1.143	0.50	Pass
BLE5.0	2Mbps	1	39	2480	2.026	1.143	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE5.0	2Mbps	1	0	2402	7.72	30.00	-2.40	5.32	36.00	Pass
BLE5.0	2Mbps	1	19	2440	7.12	30.00	-2.40	4.72	36.00	Pass
BLE5.0	2Mbps	1	39	2480	7.81	30.00	-2.40	5.41	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE5.0	2Mbps	1	0	2402	4.88	7.25
BLE5.0	2Mbps	1	19	2440	4.88	6.56
BLE5.0	2Mbps	1	39	2480	4.88	7.34

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	5.42	-12.74	-2.40	8.00	Pass
BLE5.0	2Mbps	1	19	2440	4.86	-13.23	-2.40	8.00	Pass
BLE5.0	2Mbps	1	39	2480	5.38	-12.72	-2.40	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Jimmy Chang	Temperature :	24~26℃
		Relative Humidity :	51~53%

EUT Information

Report NO : 800518
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.170250	---	29.55	54.95	25.40	L1	OFF	19.5
0.170250	46.09	---	64.95	18.86	L1	OFF	19.5
0.215250	---	27.61	53.00	25.39	L1	OFF	19.5
0.215250	42.33	---	63.00	20.67	L1	OFF	19.5
0.440250	---	26.43	47.06	20.63	L1	OFF	19.5
0.440250	35.54	---	57.06	21.52	L1	OFF	19.5
0.690000	---	25.76	46.00	20.24	L1	OFF	19.6
0.690000	34.41	---	56.00	21.59	L1	OFF	19.6
3.516000	---	26.40	46.00	19.60	L1	OFF	19.7
3.516000	30.48	---	56.00	25.52	L1	OFF	19.7
5.172000	---	26.83	50.00	23.17	L1	OFF	19.7
5.172000	30.32	---	60.00	29.68	L1	OFF	19.7
16.658250	---	26.71	50.00	23.29	L1	OFF	20.1
16.658250	33.60	---	60.00	26.40	L1	OFF	20.1

EUT Information

Report NO : 800518
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	30.90	55.88	24.98	N	OFF	19.5
0.152250	53.97	---	65.88	11.91	N	OFF	19.5
0.159000	---	29.38	55.52	26.14	N	OFF	19.5
0.159000	52.66	---	65.52	12.86	N	OFF	19.5
0.163500	---	28.92	55.28	26.36	N	OFF	19.5
0.163500	51.22	---	65.28	14.06	N	OFF	19.5
0.170250	---	30.02	54.95	24.93	N	OFF	19.5
0.170250	49.14	---	64.95	15.81	N	OFF	19.5
0.179250	---	31.23	54.52	23.29	N	OFF	19.5
0.179250	46.72	---	64.52	17.80	N	OFF	19.5
0.609000	---	26.18	46.00	19.82	N	OFF	19.6
0.609000	33.90	---	56.00	22.10	N	OFF	19.6
4.967250	---	27.23	46.00	18.77	N	OFF	19.7
4.967250	34.08	---	56.00	21.92	N	OFF	19.7
15.598500	---	27.32	50.00	22.68	N	OFF	20.1
15.598500	35.02	---	60.00	24.98	N	OFF	20.1



Appendix C. Radiated Spurious Emission

Test Engineer :	Watt Tseng, Karl Hou, and Big-show Wang	Temperature :	23~26°C
		Relative Humidity :	51~59%

<For 1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		2317.7	53.51	-20.49	74	40.96	27.77	15.67	30.89	100	342	P	H
		2324	43.51	-10.49	54	30.95	27.77	15.68	30.89	100	342	A	H
	*	2402	98.51	-	-	85.97	27.6	15.79	30.85	100	342	P	H
	*	2402	97.92	-	-	85.38	27.6	15.79	30.85	100	342	A	H
													H
													H
		2329.95	53.66	-20.34	74	41.1	27.77	15.68	30.89	383	223	P	V
		2372.265	43.53	-10.47	54	31.01	27.63	15.75	30.86	383	223	A	V
	*	2402	96.45	-	-	83.91	27.6	15.79	30.85	383	223	P	V
	*	2402	95.86	-	-	83.32	27.6	15.79	30.85	383	223	A	V
													V
													V
BLE CH 19 2440MHz		2349.34	53.32	-20.68	74	40.79	27.7	15.71	30.88	120	340	P	H
		2358.72	43.46	-10.54	54	30.94	27.67	15.73	30.88	120	340	A	H
	*	2440	98.71	-	-	86.1	27.6	15.85	30.84	120	340	P	H
	*	2440	98.19	-	-	85.58	27.6	15.85	30.84	120	340	A	H
		2485.58	52.71	-21.29	74	40.15	27.47	15.91	30.82	120	340	P	H
		2492.23	43.34	-10.66	54	30.83	27.4	15.92	30.81	120	340	A	H
		2389.94	53.88	-20.12	74	41.36	27.6	15.77	30.85	400	218	P	V
		2323.58	43.42	-10.58	54	30.86	27.77	15.68	30.89	400	218	A	V
	*	2440	92.59	-	-	79.98	27.6	15.85	30.84	400	218	P	V
	*	2440	92	-	-	79.39	27.6	15.85	30.84	400	218	A	V
		2487.96	53.07	-20.93	74	40.58	27.4	15.91	30.82	400	218	P	V
		2493.63	43.27	-10.73	54	30.76	27.4	15.92	30.81	400	218	A	V



BLE CH 39 2480MHz	*	2480	98.78	-	-	86.23	27.47	15.9	30.82	101	339	P	H
	*	2480	98.05	-	-	85.5	27.47	15.9	30.82	101	339	A	H
		2493.24	53.82	-20.18	74	41.31	27.4	15.92	30.81	101	339	P	H
		2490.24	43.25	-10.75	54	30.75	27.4	15.92	30.82	101	339	A	H
													H
													H
	*	2480	95.57	-	-	83.02	27.47	15.9	30.82	400	232	P	V
	*	2480	95.07	-	-	82.52	27.47	15.9	30.82	400	232	A	V
		2485.12	53.49	-20.51	74	40.93	27.47	15.91	30.82	400	232	P	V
		2483.76	43.29	-10.71	54	30.73	27.47	15.91	30.82	400	232	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		4804	37.46	-36.54	74	55.76	31.3	8.44	58.04	100	0	P	H
													H
													H
													H
		4804	36.18	-37.82	74	54.48	31.3	8.44	58.04	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	36.33	-37.67	74	54.46	31.3	8.67	58.1	100	0	P	H
		7320	41.6	-32.4	74	52.44	36.23	11.27	58.34	100	0	P	H
													H
													H
		4880	37.16	-36.84	74	55.29	31.3	8.67	58.1	100	0	P	V
		7320	41.47	-32.53	74	52.31	36.23	11.27	58.34	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	37.01	-36.99	74	54.81	31.47	8.9	58.17	100	0	P	H
		7440	42.09	-31.91	74	52.47	36.6	11.33	58.31	100	0	P	H
													H
													H
		4960	36.57	-37.43	74	54.37	31.47	8.9	58.17	100	0	P	V
		7440	42	-32	74	52.38	36.6	11.33	58.31	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		70.77	27.64	-12.36	40	46.67	12.47	1.1	32.6	-	-	P	H
		98.31	27.72	-15.78	43.5	43.14	15.85	1.3	32.57	-	-	P	H
		204.69	30.09	-13.41	43.5	45.44	15.31	1.88	32.54	-	-	P	H
		354.6	29.15	-16.85	46	38.55	20.82	2.31	32.53	-	-	P	H
		481.3	31.45	-14.55	46	37.41	23.9	2.69	32.55	-	-	P	H
		944	33.68	-12.32	46	30.24	30.9	3.87	31.33	100	0	P	H
													H
													H
													H
													H
													H
													H
		70.77	34.38	-5.62	40	53.41	12.47	1.1	32.6	100	0	P	V
		94.53	27.03	-16.47	43.5	42.98	15.34	1.29	32.58	-	-	P	V
		197.94	24.11	-19.39	43.5	39.8	14.98	1.87	32.54	-	-	P	V
		528.9	30.5	-15.5	46	35.66	24.53	2.87	32.56	-	-	P	V
		842.5	31.74	-14.26	46	30.85	29.28	3.61	32	-	-	P	V
		970.6	33.62	-20.38	54	29.92	30.85	3.95	31.1	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



<For 2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		2338.665	53.73	-20.27	74	41.22	27.7	15.7	30.89	143	203	P	H
		2387.805	45.96	-8.04	54	33.45	27.6	15.77	30.86	143	203	A	H
	*	2402	97.86	-	-	85.32	27.6	15.79	30.85	143	203	P	H
	*	2402	96.46	-	-	83.92	27.6	15.79	30.85	143	203	A	H
													H
													H
		2310.315	53.17	-20.83	74	40.58	27.83	15.66	30.9	383	64	P	V
		2370.06	45.68	-8.32	54	33.16	27.63	15.75	30.86	383	64	A	V
	*	2402	96.3	-	-	83.76	27.6	15.79	30.85	383	64	P	V
	*	2402	95	-	-	82.46	27.6	15.79	30.85	383	64	A	V
													V
													V
BLE CH 19 2440MHz		2382.52	53.69	-20.31	74	41.16	27.63	15.76	30.86	142	201	P	H
		2336.04	45.72	-8.28	54	33.22	27.7	15.69	30.89	142	201	A	H
	*	2440	97.97	-	-	85.36	27.6	15.85	30.84	142	201	P	H
	*	2440	96.5	-	-	83.89	27.6	15.85	30.84	142	201	A	H
		2499.44	52.41	-21.59	74	39.89	27.4	15.93	30.81	142	201	P	H
		2498.11	45.38	-8.62	54	32.86	27.4	15.93	30.81	142	201	A	H
		2355.78	53.81	-20.19	74	41.3	27.67	15.72	30.88	369	52	P	V
		2379.3	45.92	-8.08	54	33.39	27.63	15.76	30.86	369	52	A	V
	*	2440	95.34	-	-	82.73	27.6	15.85	30.84	369	52	P	V
	*	2440	93.88	-	-	81.27	27.6	15.85	30.84	369	52	A	V
		2491.81	52.46	-21.54	74	39.95	27.4	15.92	30.81	369	52	P	V
		2487.19	45.63	-8.37	54	33.07	27.47	15.91	30.82	369	52	A	V



BLE CH 39 2480MHz	*	2480	98.54	24.54	74	85.99	27.47	5.98	30.82	100	202	P	H
	*	2480	97.13	43.13	54	84.58	27.47	5.98	30.82	100	202	A	H
		2484	53.51	-20.49	74	40.95	27.47	5.99	30.82	100	202	P	H
		2491.56	45.65	-8.35	54	33.15	27.4	6	30.82	100	202	A	H
													H
													H
	*	2480	96.14	22.14	74	83.59	27.47	5.98	30.82	400	52	P	V
	*	2480	94.88	40.88	54	82.33	27.47	5.98	30.82	400	52	A	V
		2497.56	53.05	-20.95	74	40.53	27.4	6.01	30.81	400	52	P	V
		2497.64	45.74	-8.26	54	33.22	27.4	6.01	30.81	400	52	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		4804	36.72	-37.28	74	55.02	31.3	8.44	58.04	100	0	P	H
													H
													H
													H
		4804	36.57	-37.43	74	54.87	31.3	8.44	58.04	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	36.55	-37.45	74	54.68	31.3	8.67	58.1	100	0	P	H
		7320	41.14	-32.86	74	51.98	36.23	11.27	58.34	100	0	P	H
													H
													H
		4880	36.85	-37.15	74	54.98	31.3	8.67	58.1	100	0	P	V
		7320	41.48	-32.52	74	52.32	36.23	11.27	58.34	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	37.52	-36.48	74	55.32	31.47	8.9	58.17	100	0	P	H
		7440	42.98	-31.02	74	53.36	36.6	11.33	58.31	100	0	P	H
													H
													H
		4960	37.99	-36.01	74	55.79	31.47	8.9	58.17	100	0	P	V
		7440	43.21	-30.79	74	53.59	36.6	11.33	58.31	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		103.71	33.85	-9.65	43.5	48.71	16.39	1.32	32.57	100	0	P	H
		170.13	30.96	-12.54	43.5	45.99	15.75	1.77	32.55	-	-	P	H
		206.04	29.46	-14.04	43.5	44.73	15.4	1.87	32.54	-	-	P	H
		483.4	33.63	-12.37	46	39.56	23.93	2.69	32.55	-	-	P	H
		540.1	33.75	-12.25	46	38.37	25.03	2.91	32.56	-	-	P	H
		946.1	33.49	-12.51	46	30	30.93	3.87	31.31	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
		69.96	32.94	-7.06	40	52.05	12.39	1.1	32.6	100	0	P	V
		96.42	32.54	-10.96	43.5	48.22	15.59	1.3	32.57	-	-	P	V
		167.97	28.27	-15.23	43.5	43.17	15.91	1.74	32.55	-	-	P	V
		506.5	32.53	-13.47	46	38.12	24.18	2.78	32.55	-	-	P	V
		825	31.52	-14.48	46	31.39	28.65	3.57	32.09	-	-	P	V
		958.7	33.72	-12.28	46	29.85	31.15	3.92	31.2	-	-	P	V
													V
												V	
												V	
												V	
												V	
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical

A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
- Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Watt Tseng, Karl Hou, and Big-show Wang	Temperature :	23~26°C
		Relative Humidity :	51~59%





Note symbol

-L	Low channel location
-R	High channel location





<For 1Mbps>

2.4GHz 2400~2483.5MHz





BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 800518 Mode : 7	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 800518 Mode : 7
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : 800518 Mode : 7	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : 800518 Mode : 7





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 7	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 7
Avg	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 7	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 7







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 800518 Mode : 8	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 800518 Mode : 8
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:1000KHz SWT:Auto Project : 800518 Mode : 8	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:1000KHz SWT:Auto Project : 800518 Mode : 8





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 800518 Mode : 8	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 800518 Mode : 8	Left blank







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 8	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 8
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 8	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 8







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 800518 Mode : 8	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 800518 Mode : 8	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 9	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 9
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 9	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 9



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 9	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 9
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 9	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 9



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 800518 Mode : 7	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 800518 Mode : 7





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2018-10-26 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 800518 Mode : 8	Level (dBuV/m) Date: 2018-10-26 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 800518 Mode : 8



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 800518 Mode : 9	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 800518 Mode : 9





Emission below 1GHz
2.4GHz BLE (LF)

BLE	2.4GHz 2400~2483.5MHz	
	BLE LF	
	Horizontal	Vertical
QP / Peak	 Site : 03CH15-HY Condition : QP 3m BILOG_15_41912 HORIZONTAL Detector : Peak Project : 800518 Mode : 10	 Site : 03CH15-HY Condition : QP 3m BILOG_15_41912 VERTICAL Detector : Peak Project : 800518 Mode : 10





<For 2Mbps>

2.4GHz 2400~2483.5MHz





BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 11	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 11
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 11	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 11





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 11	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 11
Avg	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 11	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 11







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 800518 Mode : 12	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 800518 Mode : 12
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Project : 800518 Mode : 12	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Project : 800518 Mode : 12





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 800518 Mode : 12	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 800518 Mode : 12	Left blank







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 12	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 12
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 12	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 12







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 800518 Mode : 12	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 800518 Mode : 12	Left blank



BLE		2.4GHz 2400~2483.5MHz Band Edge @ 3m	
		BLE CH39 2480MHz	
		Horizontal	Fundamental
Peak		 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 13	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 13
Avg.		 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 13	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 13



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 13	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 13
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 13	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 800518 Mode : 13



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2018-10-26 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 800518 Mode : 11	Level (dBuV/m) Date: 2018-10-26 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 800518 Mode : 11





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 800518 Mode :	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 800518 Mode :



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 800518 Mode : 13	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 800518 Mode : 13


Emission below 1GHz
2.4GHz BLE (LF)

BLE	2.4GHz 2400~2483.5MHz	
	BLE LF	
	Horizontal	Vertical
QP / Peak	 Site : 03CH15-HY Condition : QP 3m BILOG_15_41912 HORIZONTAL Detector : Peak Project : 800518 Mode : 14	 Site : 03CH15-HY Condition : QP 3m BILOG_15_41912 VERTICAL Detector : Peak Project : 800518 Mode : 14

Appendix E. Duty Cycle Plots

Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor (dB)
Bluetooth – LE for 1Mbps	84.83	2125.00	0.47	1kHz	0.71
Bluetooth – LE for 2Mbps	32.48	204.00	4.90	10kHz	4.88


Bluetooth – LE for 1Mbps



Date: 18.OCT.2018 16:40:57



Bluetooth – LE for 2Mbps




Date: 18.OCT.2018 16:44:35

Appendix F. Setup Photographs

<Conducted Emission>

Remote View





Rear View




<Radiated Emission>

X Plane

LF



HF



————THE END————