



# **FCC Part 15B TEST REPORT**

Report No: STS1606035E01

Issued for

## SHENZHEN BOLIHONG DIGITAL TECHNOLOGY CO.,LTD

1603B, Tianan innovation of science and technology square, Binhe road and xiangmihu road, futian Dist shenzhen, China

Product Name:	Smart phone
Brand Name:	bluesky
Model Name:	M168
Series Model:	N/A
FCC ID:	2AIPJM168-AS
Test Standard:	FCC Part 15B

Any reproduction of this document must be done in full. No single part of this document may be reproduced wipermission from STS, All Test Data Presented in this report is only applicable to presented Test Psan De/AL

Shenzhen STS Test Services Co., Ltd.

1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com



Report No.: STS1606035E01



#### **TEST RESULT CERTIFICATION**

Applicant's name.....: SHENZHEN BOLIHONG DIGITAL TECHNOLOGY CO.,LTD 1603B, Tianan innovation of science and technology square, Binhe road and xiangmihu road ,futian Dist shenzhen,China Manufacture's Name.....: SHENZHEN BOLIHONG DIGITAL TECHNOLOGY CO.,LTD 12A,A building huagiang plaza huagiang north, futian district shenzhen **Product description** Product name .....: Smart phone Brand name.....: bluesky Model and/or type reference..: M168 Standards..... FCC Part 15B Test procedure...... ANSI C63.4-2014 This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report. This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document. Date of Test ..... Date of performance of tests .. 05 June. 2016~16 June. 2016 Date of Issue ...... 17 June. 2016 Test Result ......Pass

Testing Engineer

(Hakim Hou)

Technical Manager :

Authorized Signatory:

(Bovey Yang)







## **Table of Contents**

1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACTORY	5
1.2 MEASUREMENT UNCERTAINTY	5
2. GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	7
2.4 DESCRIPTION OF SUPPORT UNITS	8
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	9
3. EMC EMISSION TEST	10
3.1 CONDUCTED EMISSION MEASUREMENT	10
3.2 RADIATED EMISSION MEASUREMENT	14
4. PHOTOS OF TEST SETUP	20



Page 4 of 21 Report No.: STS1606035E01

## **Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	17 June. 2016 STS1606035E01		ALL	Initial Issue





Report No.: STS1606035E01

#### 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

EMISSION					
Standard	Item	Result	Remarks		
FCC 47 CFR Part 15 Subpart B	Conducted Emission	PASS	Meet Class B limit		
(10-1-05 Edition)	Radiated Emission	PASS	Meet Class B limit		

#### NOTE:

(1) " N/A" denotes test is not applicable in this Test Report

#### 1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add.: 1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,

Fuyong Street, Bao'an District, Shenzhen, Guangdong, China

CNAS Registration No.: L7649;

FCC Registration No.: 842334; IC Registration No.: 12108A-1

#### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	±2.88dB
2	Conducted Emission (150KHz-30MHz)	±2.67dB
3	RF power,conducted	±0.70dB
4	Spurious emissions,conducted	±1.19dB
5	All emissions,radiated(<30M) (9KHz-30MHz)	±2.45dB
6	All emissions,radiated(<1G) 30MHz-200MHz	±2.83dB
7	All emissions,radiated(<1G) 200MHz-1000MHz	±2.94dB
8	All emissions,radiated(>1G)	±3.03dB
9	Temperature	±0.5°C
10	Humidity	±2%



## 2. GENERAL INFORMATION

## 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Smart phone
Trade Name	bluesky
Model Name	M168
Series Model	N/A
Model Difference	N/A
MCU Operating frequency	1.2GHz
Adapter	Input: AC100-240V, 200mA, 50/60 Hz Output: DC 5V, 1000mA
Battery	Rated Voltage: 3.8V capacity :2000mAh
Hardware version number	1490D
Software version number	1490AD_S77
Connecting I/O Port(s)	Please refer to the User's Manual

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



#### 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	USB port communication with PC


For Conducted Test				
Final Test Mode Description				
Mode 1	USB port communication with PC			

For Radiated Test				
Final Test Mode Description				
Mode 1 USB port communication with PC				

#### NOTE:

- 1. Due to the different configuration and test, in this list only some worse mode. The worst test data of the worse modeis reported by this report.
- 2. We have be tested for all avaiable U.S. voltage and frequencies(For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.

#### 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road, Fuyong Street, Bao'an District, Shenzhen, Guangdong, China Tel: 0755-36886288 Fax: 0755-36886277 Http://www.stsapp.com E-mail: sts@stsapp.com



#### 2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-1	Smart phone	bluesky	M168	N/A	EUT
E-2	PC	4CV428DQXR	500-320cx	4CV428DQYN	N/A
E-3	Keyboard	HP	PR1101U	DKUSB1B06Q42209FBK800	N/A
E-4	Mouse	MOTOSPEED	F66	697738-001	N/A
E-5	Printer	LENOVO	LJ2400L	LP02781702	N/A
C-6	AC (PC Adapter)	LITEON	PA-1650-86	3X06399004	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable (FTP)	NO	90cm	N/A
C-2	USB Cable (FTP)	NO	100cm	N/A
C-3	USB Cable (FTP)	NO	100cm	N/A
C-4	USB Cable (FTP)	NO	110cm	N/A
C-5	AC (Printer Cable) (FTP)	NO	100cm	N/A
C-6	AC (PC Cable) (FTP)	NO	120cm	N/A

#### Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>"Length\_"</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".
- (4) PC is the FCC DOC is approved.



#### 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

## Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	101427	2015.10.25	2016.10.24
Loop Antenna	Daze	ZN30900N	SEL0097	2015.10.27	2016.10.26
Bilog Antenna	TESEQ	CBL6111D	34678	2015.11.25	2016.11.24
Horn Antenna	Schwarzbeck	BBHA 9120D(1201)	9120D-1343	2016.03.06	2017.03.05
PreAmplifier	Agilent	8449B	60538	2015.10.25	2016.10.24
Temperature & Humitidy	Mieo	HH660	N/A	2015.10.28	2016.10.27
Unversal radio communication tester	R&S	CMU200	111764	2015.10.25	2016.10.24
Spectrum Analyzer	Agilent	E4407B	MY50140340	2015.10.25	2016.10.24
Low frequency cable	EM	R01	N/A	N/A	N/A
High frequency cable	SCHWARZBE CK	AK9515H	SN-96286/9628 7	N/A	N/A

## Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESPI	102086	2015.11.20	2016.11.19
LISN	R&S	ENV216	101242	2015.10.25	2016.10.24
LISN	EMCO	3810/2NM	000-23625	2015.10.25	2016.10.24
Conduction Cable	EM	C01	N/A	N/A	N/A

Report No.: STS1606035E01



#### 3. EMC EMISSION TEST

## 3.1 CONDUCTED EMISSION MEASUREMENT

#### 3.1.1 POWER LINE CONDUCTED EMISSION Limits

	Conducted Emission Limits (dBuV)					
FREQUENCY (MHz)	Clas	Class A		ss B		
	Quasi-peak	Average	Quasi-peak	Average		
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *		
0.50 -5.0	73.00	60.00	56.00	46.00		
5.0 -30.0	73.00	60.00	60.00	50.00		

#### Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

## The following table is the setting of the receiver

Receiver Parameters	Setting	
Attenuation	10 dB	
Start Frequency	0.15 MHz	
Stop Frequency	30 MHz	
IF Bandwidth	9 kHz	



#### 3.1.2 TEST PROCEDURE


The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support

- a. equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
  - I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the
- cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

#### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

#### 3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

#### 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




## 3.1.6 TEST RESULTS

Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	L
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1780	36.31	9.23	45.54	64.58	-19.04	QP
2	0.1780	19.92	9.23	29.15	54.58	-25.43	AVG
3	0.2140	33.57	9.22	42.79	63.05	-20.26	QP
4	0.2140	15.42	9.22	24.64	53.05	-28.41	AVG
5	0.2460	31.85	9.18	41.03	61.89	-20.86	QP
6	0.2460	16.20	9.18	25.38	51.89	-26.51	AVG
7	1.0260	24.68	9.15	33.83	56.00	-22.17	QP
8	1.0260	-2.96	9.15	6.19	46.00	-39.81	AVG
9	2.5460	29.91	9.26	39.17	56.00	-16.83	QP
10	2.5460	18.72	9.26	27.98	46.00	-18.02	AVG
11	16.4700	27.39	9.60	36.99	60.00	-23.01	QP
12	16.4700	9.17	9.60	18.77	50.00	-31.23	AVG

#### Remark:

1. Margin = Result (Result =Reading + Factor )-Limit 100.0 dBuV






Page 13 of 21 Report No.: STS1606035E01

Temperature:	<b>26</b> ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	Ν
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1760	33.54	9.23	42.77	64.67	-21.90	QP
2	0.1760	23.12	9.23	32.35	54.67	-22.32	AVG
3	0.3840	29.78	9.22	39.00	58.19	-19.19	QP
4	0.3840	21.29	9.22	30.51	48.19	-17.68	AVG
5	0.9092	28.34	9.25	37.59	56.00	-18.41	QP
6	0.9092	18.71	9.25	27.96	46.00	-18.04	AVG
7	2.4850	36.77	9.26	46.03	56.00	-9.97	QP
8	2.4850	25.12	9.26	34.38	46.00	-11.62	AVG
9	16.3822	24.25	9.52	33.77	60.00	-26.23	QP
10	16.3822	14.12	9.52	23.64	50.00	-26.36	AVG
11	18.4318	31.18	9.67	40.85	60.00	-19.15	QP
12	18.4318	26.86	9.67	36.53	50.00	-13.47	AVG

## Remark:

1. Margin = Result (Result =Reading + Factor )-Limit 100.0 dBuV





## 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 Radiated Emission Limits

In case the emission fall within the restricted band specified on 15.105(a)&109(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### LIMITS OF RADIATED EMISSION MEASUREMENT

EDEOLIENCY (MHz)	Class A (d	BuV/m) (at 3M)	Class B (dBuV/m) (at 3M)	
FREQUENCY (MHz)	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

#### Note:

- (1) The limit for radiated test was performed according to FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

## FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper	
frequency of measurement used in the device	Range (MHz)
or on which the device operates or tunes	range (Miliz)
(MHz)	
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower



Page 15 of 21 Report No.: STS1606035E01

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	5th harmonic (Peak/AV)
RB / VB (emission in restricted band)	PK=1 MHz / 1 MHz, AV=1 MHz / 10Hz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	30MHz~1000MHz/RB 120kHz for QP

#### 3.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter b. anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- the height of the antenna shall vary between 1m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector d. mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the e. EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


#### 3.2.3 DEVIATION FROM TEST STANDARD

No deviation




#### 3.2.4 TEST SETUP

## (A) Radiated Emission Test-Up Frequency 30MHz~1GHz



## (B) Radiated Emission Test-Up Frequency Above 1GHz



#### 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



#### 3.2.6 TEST RESULTS


## 30MHz -1000MHz

Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.6202	34.80	-12.02	22.78	40.00	-17.22	QP
2	47.9940	42.87	-20.45	22.42	40.00	-17.58	QP
3	240.8304	54.81	-17.63	37.18	46.00	-8.82	QP
4	293.0842	36.84	-15.24	21.60	46.00	-24.40	QP
5	689.5644	36.02	-5.57	30.45	46.00	-15.55	QP
6	839.1818	38.40	-2.78	35.62	46.00	-10.38	QP

#### Remark:

- 1. All readings are Quasi-Peak and Average values.
- 2. Margin = Result (Result = Reading + Factor )—Limit






Page 18 of 21 Report No.: STS1606035E01

Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	Vertical
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	33.2112	29.94	-12.84	17.10	40.00	-22.90	QP
2	115.7256	34.02	-17.97	16.05	43.50	-27.45	QP
3	138.8735	33.00	-17.51	15.49	43.50	-28.01	QP
4	375.9385	36.78	-12.73	24.05	46.00	-21.95	QP
5	501.1790	32.08	-8.90	23.18	46.00	-22.82	QP
6	750.1083	27.80	-3.56	24.24	46.00	-21.76	QP

#### Remark:

- 1. All readings are Quasi-Peak and Average values.
- 2. Margin = Result (Result = Reading + Factor )-Limit







## (1 GHz to 13GHz.)

Temperature:	26 ℃	Relative Humidity:	54%	
Pressure:	1010hPa	Phase:	Vertical/Horizontal	
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1	

Freq.	Ant. Pol	Peak	AV	Ant./CL	Actual Fs Peak AV		Peak	AV	Peak	AV
(MHz)	H/V	Reading	Reading	CF			Limit	Limit	margin	margin
		(dBuV)	(dBuV)	(dB)			(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)
					(dBuV/m)	(dBuV/m)				
1097.45	Н	57.59	41.28	5.15	62.74	46.43	74.00	54.00	-11.26	-7.57
2866.31	Н	52.27	38.29	9.45	61.72	47.74	74.00	54.00	-12.28	-6.26
N/A										
1069.67	V	52.63	37.55	5.15	57.78	42.70	74.00	54.00	-16.22	-11.30
2896.73	V	49.31	32.14	9.45	58.76	41.59	74.00	54.00	-15.24	-12.41
N/A										

#### Notes:


- 1. Measuring frequencies from 1 GHz to 13GHz.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode of the emission shown in Actual FS column.
- 3. The frequency that above 3GHz is mainly from the environment noise.



## 4. PHOTOS OF TEST SETUP

## Radiated Measurement Photos

30MHz-1GHz



Above 1GHz





## **Conducted Measurement Photos**



\*\* \* \* \* END OF THE REPORT \* \* \* \*