

## TEST REPORT

**Report No.: 17061010HKG-001**

Huajun Toys Company Limited

Application For Certification  
(Original Grant)

**FCC ID: 2A1S6-83657-49**

Transmitter

**PREPARED AND CHECKED BY:**

Signed On File  
Xu Lap Ho, Leo  
Assistant Engineer

**APPROVED BY:**

Wong Kwok Yeung, Kenneth  
Senior Lead Engineer  
Date: June 29, 2017

**TEST REPORT****GENERAL INFORMATION**

<b>Grantee:</b>	Huajun Toys Company Limited
<b>Grantee Address:</b>	Room 503-4, 5/F., Tower A, New Mandarin Plaza, 14 Science Museum Road, Tsim Sha Tsui East, Kowloon, Hong Kong.
<b>Contact Person:</b>	Berry Chan
<b>Tel:</b>	(852) 35655116
<b>Fax:</b>	(852) 81480618
<b>e-mail:</b>	N/A
<b>Manufacturer:</b>	Huajun Toys Company Limited
<b>Manufacturer Address:</b>	Room 503-4, 5/F., Tower A, New Mandarin Plaza, 14 Science Museum Road, Tsim Sha Tsui East, Kowloon, Hong Kong.
<b>Brand Name:</b>	N/A
<b>Model:</b>	83657
<b>Type of EUT:</b>	Transmitter
<b>Description of EUT:</b>	RC Racing Car
<b>Serial Number:</b>	N/A
<b>FCC ID:</b>	2AIS6-83657-49
<b>Date of Sample Submitted:</b>	June 14, 2017
<b>Date of Test:</b>	June 14, 2017 to June 28, 2017
<b>Report No.:</b>	17061010HKG-001
<b>Report Date:</b>	June 29, 2017
<b>Environmental Conditions:</b>	Temperature: +10 to 40°C Humidity: 10 to 90%

**TEST REPORT****SUMMARY OF TEST RESULT**

TEST SPECIFICATION	REFERENCE	RESULTS
Transmitter Field Strength and Bandwidth Requirement	15.235	Pass

The equipment under test is found to be complying with the following standards:  
FCC Part 15, October 1, 2015 Edition

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.

2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

**TEST REPORT****TABLE OF CONTENTS**

<b>1.0 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Product Description .....	5
1.2 Related Submittal(s) Grants .....	5
1.3 Test Methodology .....	5
1.4 Test Facility .....	5
<b>2.0 SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
2.1 Justification.....	6
2.2 EUT Exercising Software .....	6
2.3 Special Accessories .....	6
2.4 Measurement Uncertainty.....	6
2.5 Support Equipment List and Description.....	6
<b>3.0 EMISSION RESULTS .....</b>	<b>7</b>
3.1 Field Strength Calculation .....	7
3.2 Radiated Emission Configuration Photograph .....	8
3.3 Radiated Emission Data .....	8
<b>4.0 EQUIPMENT PHOTOGRAPHS .....</b>	<b>10</b>
<b>5.0 PRODUCT LABELLING .....</b>	<b>10</b>
<b>6.0 TECHNICAL SPECIFICATIONS .....</b>	<b>10</b>
<b>7.0 INSTRUCTION MANUAL.....</b>	<b>10</b>
<b>8.0 MISCELLANEOUS INFORMATION.....</b>	<b>11</b>
8.1 Measured Bandwidth.....	11
8.2 Discussion of Pulse Desensitization .....	12
8.3 Calculation of Average Factor.....	12
8.4 Emissions Test Procedures .....	13
<b>9.0 EQUIPMENT LIST .....</b>	<b>16</b>

**TEST REPORT****1.0 GENERAL DESCRIPTION****1.1 Product Description**

The Equipment Under Test (EUT) is a portable 49MHz Transmitter (Controller Unit) for a RC car. The EUT is powered by 2\*1.5V AA battery. After switch on the EUT, the car can be controlled to move forward/backward and turn left/ right by the controller.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

**1.2 Related Submittal(s) Grants**

This is a single application for certification of a transmitter.

The Declaration of Conformity procedure of corresponding receiver for this transmitter is being processed at the same time.

**1.3 Test Methodology**

Radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

**1.4 Test Facility**

The 3m Chamber facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

**TEST REPORT****2.0 SYSTEM TEST CONFIGURATION****2.1 Justification**

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The device was powered by new 2 x 1.5V AA batteries.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

**2.2 EUT Exercising Software**

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

**2.3 Special Accessories**

There are no special accessories necessary for compliance of this product.

**2.4 Measurement Uncertainty**

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

**2.5 Support Equipment List and Description**

N/A.

**TEST REPORT****3.0 EMISSION RESULTS**

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

**3.1 Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where FS = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

RA = Receiver Amplitude (including preamplifier) in  $\text{dB}\mu\text{V}$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where FS = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

RR = RA - AG - AV in  $\text{dB}\mu\text{V}$

LF = CF + AF in dB

Assume a receiver reading of 52.0  $\text{dB}\mu\text{V}$  is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27  $\text{dB}\mu\text{V}/\text{m}$ . This value in  $\text{dB}\mu\text{V}/\text{m}$  was converted to its corresponding level in  $\mu\text{V}/\text{m}$ .

$$RA = 52.0 \text{ dB}\mu\text{V}/\text{m}$$

$$AF = 7.4 \text{ dB}$$

$$RR = 18.0 \text{ dB}\mu\text{V}$$

$$CF = 1.6 \text{ dB}$$

$$LF = 9.0 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$AV = 5.0 \text{ dB}$$

$$FS = RR + LF$$

$$FS = 18 + 9 = 27 \text{ dB}\mu\text{V}/\text{m}$$

$$\text{Level in } \mu\text{V}/\text{m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V}/\text{m})/20] = 22.4 \mu\text{V}/\text{m}$$

**TEST REPORT****3.2 Radiated Emission Configuration Photograph**

The worst case in radiated emission was found at 99.709 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

**3.3 Radiated Emission Data**

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 7.2 dB

**TEST REPORT**
**RADIATED EMISSIONS**

Model: 83657

Date of Test: June 28, 2017

Worst-Case Operating Mode: Transmitting

**Table 1**  
**Pursuant to FCC Part 15 Section 15.235 Requirement**

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp (dB)	Antenna Factor (dB)	Average Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	49.863	69.3	16	11.0	0.0	64.3	80.0	-15.7
V	99.709	40.3	16	12.0	-	36.3	43.5	-7.2
<b>V</b>	<b>112.994</b>	<b>25.5</b>	<b>16</b>	<b>14.0</b>	-	<b>23.5</b>	<b>43.5</b>	<b>-20.0</b>
<b>V</b>	<b>119.209</b>	<b>22.7</b>	<b>16</b>	<b>14.0</b>	-	<b>20.7</b>	<b>43.5</b>	<b>-22.8</b>
<b>V</b>	<b>125.425</b>	<b>22.4</b>	<b>16</b>	<b>14.0</b>	-	<b>20.4</b>	<b>43.5</b>	<b>-23.1</b>
<b>V</b>	<b>131.763</b>	<b>25.2</b>	<b>16</b>	<b>14.0</b>	-	<b>23.2</b>	<b>43.5</b>	<b>-20.3</b>
V	150.653	20.4	16	14.0	-	18.4	43.5	-25.1
V	200.988	15.3	16	16.0	-	15.3	43.5	-28.2
V	248.275	13.9	16	20.0	-	17.9	46.0	-28.1
H	299.828	12.5	16	22.0	-	18.5	46.0	-27.5
H	348.944	13.7	16	24.0	-	21.7	46.0	-24.3
H	396.841	15.2	16	25.0	-	24.2	46.0	-21.8
V	448.759	13.6	16	26.0	-	23.6	46.0	-22.4
V	495.072	16.2	16	26.0	-	26.2	46.0	-19.8

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
5. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

**TEST REPORT****4.0 EQUIPMENT PHOTOGRAPHS**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

**5.0 PRODUCT LABELLING**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

**6.0 TECHNICAL SPECIFICATIONS**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

**7.0 INSTRUCTION MANUAL**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.


This manual will be provided to the end-user with each unit sold/leased in the United States.

**TEST REPORT****8.0 MISCELLANEOUS INFORMATION**

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

**8.1 Measured Bandwidth**

The plot shows the fundamental emission is confined in the specified band. The field strength of any emission appearing between the band edges and up to 10kHz above and below the band edges (49.81 and 49.91 MHz) is at least 46.05 dB below the carrier level. And at 49.81 & 49.91 MHz, there are at least 44 dB below the carrier level. It meets requirement of Section 15.235(b).



**TEST REPORT****8.2 Discussion of Pulse Desensitization**

Pulse desensitivity is not applicable for this device. Since the transmitter transmits the RF signal continuously.

**8.3 Calculation of Average Factor**

The average factor is not applicable for this device as the transmitted signal is a continuously signal.

**TEST REPORT****8.4 Emissions Test Procedures**

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 1 GHz, whichever is lower.

**TEST REPORT****8.4 Emissions Test Procedures (cont'd)**

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.


Conducted measurements were made as described in ANSI C63.10 (2013).

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 3 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

**TEST REPORT****8.4.1 Radiated Emission Test Setup**

The figure below shows the test setup, which is utilized to make these measurements.



Test setup of radiated emissions up to 1GHz

**TEST REPORT****9.0 EQUIPMENT LIST**

## 1) Radiated Emissions Test

EQUIPMENT	EMI Test Receiver	Spectrum Analyzer
Registration No.	EW-3156	EW-3110
Manufacturer	R&S	R&S
Model No.	ESR26	FSP30
Calibration Date	Dec. 06, 2016	Feb. 06, 2017
Calibration Due Date	Dec. 06, 2017	Feb. 06, 2018

EQUIPMENT	Double Ridged Guide Antenna	Log Periodic Antenna	Biconical Antenna
Registration No.	EW-0194	EW-0447	EW-0571
Manufacturer	EMCO	EMCO	EMCO
Model No.	3115	3146	3104C
Calibration Date	Aug. 10, 2016	May 18, 2016	May 18, 2016
Calibration Due Date	Feb. 10, 2018	Nov. 18, 2017	Nov. 18, 2017

## 2) Bandedge Measurement

EQUIPMENT	SPECTRUM ANALYZER
Registration No.	EW-2329
Manufacturer	R&S
Model No.	FSP3
Calibration Date	Aug. 26, 2016
Calibration Due Date	Aug. 26, 2017

END OF TEST REPORT