

## Analysis Report

**The Equipment Under Test (EUT), is a portable 27MHz Transmitter for a RC Car. The sample supplied operated on a single channel, 27.145MHz.**

**The EUT is powered by 2 x 1.5V AA batteries. After switching on the EUT, the car will be moved forward or backward and turned left and right based on the switches pressed in the controller.**

Antenna Type: External Whip Antenna

Antenna Gain: 0dBi

Nominal rated field strength: 56.6dB $\mu$ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 59.6dB $\mu$ V/m at 3m in frequency 27.145MHz, thus;

The worst case of SAR Exclusion Threshold Level for 27.145MHz when the minimum test separation distance is < 50mm:

$$= [474 * (1 + \log_{10}(100/f(MHz)))]/2$$

$$= 371.2\text{mW}$$

According to the KDB 412172 D01:

$$\text{EIRP} = [(FS \cdot D)^2 \cdot 1000 / 30]$$

Calculated Field Strength for 371.2mW is 120.9dB $\mu$ V/m @3m

Since maximum field strength plus production tolerance <= 120.9dB $\mu$ V/m @3m and antenna gain is >= 0.0dBi, it is concluded that maximum Conducted Power and Field Strength are well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.