




### **Band-edge Measurements for RF Conducted Emissions:**









Report No.: GRCTR250702055-01 Page 35 of 41

## 4.7 Antenna Requirement

#### **Standard Applicable**

#### For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):


(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.


#### **Test Result:**


The maximum gain of antenna was 1.37 dBi.

Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Shenzhen GUOREN Certification Technology Service Co., Ltd. does not assume any responsibility.


# 5 Test Setup Photos of the EUT









Report No.: GRCTR250702055-01 Page 37 of 41




# 6 Photos of the EUT










Report No.: GRCTR250702055-01 Page 39 of 41














Antenna 2 is only receiving function(433.92MHz)

Report No.: GRCTR250702055-01 Page 41 of 41

