

RF Exposure Evaluation Statement

Product Name: Bluetooth speaker

Model No.: RO-01

FCC ID: 2AITS-RO-01

1.1 RF Exposure Compliance Requirement

1.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

1.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$$
$$[\sqrt{f}(\text{GHz})] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- ☐ f(GHz) is the RF channel transmit frequency in GHz
- ☐ Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- ☐ The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

1.1.3 EUT RF Exposure

Operational Mode: $\pi/4$ DQPSK (worst case)						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
2402MHZ	-3.00	± 1	-2.00	0.63	0.20	3.0
2441MHz	-3.53	± 1	-2.53	0.56	0.17	
2480MHz	-3.50	± 1	-2.50	0.56	0.18	
Conclusion: the calculated value ≤ 3.0 , SAR is exempted.						