



Shenzhen CTL Testing Technology Co., Ltd.  
Tel: +86-755-89486194 Fax: +86-755-26636041

# TEST REPORT

## FCC PART 74H

Report Reference No.: **CTL1606172288-WF**

Compiled by:  
( position+printed name+signature)

Jacky Chen  
(File administrators)

*Jacky Chen*

Tested by:  
( position+printed name+signature)

Allen Wang  
(Test Engineer)

*Allen Wang*

Approved by:  
( position+printed name+signature)

Tracy Qi  
(Manager)

*Tracy Qi*

<b>Product Name</b>	Wireless Microphone
<b>Model/Type reference</b>	H-8L
<b>List Model(s)</b>	See next page
<b>Trade Mark</b>	OYILITY / SYLVANIA
<b>FCC ID</b>	2AIU3-MP201
<b>Applicant's name</b>	<b>Kinyu Electronic Co., Limited</b>
<b>Address of applicant</b>	Flat / Rm 1801, 18/F Bonham Trade Center 50 Bonham Strand, Sheung Wan, Hongkong
<b>Test Firm</b>	<b>Shenzhen CTL Testing Technology Co., Ltd.</b>
<b>Address of Test Firm</b>	Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055
<b>Test specification</b>	
<b>Standard</b>	<b>FCC Part 74 Subpart H—Low Power Auxiliary Stations</b>
<b>TRF Originator</b>	Shenzhen CTL Testing Technology Co., Ltd.
<b>Master TRF</b>	Dated 2011-01
<b>Date of Receipt</b>	Jun. 17, 2016
<b>Date of Test Date</b>	Jun. 18, 2016 –Jun. 27, 2016
<b>Date of Issue</b>	Jun. 28, 2016
<b>Result</b>	Pass
<b>Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.</b>	
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	

# TEST REPORT

<b>Test Report No. :</b>	<b>CTL1606172288-WF</b>	Jun. 28, 2016
		Date of issue

Equipment under Test	:	Wireless Microphone
Model /Type	:	H-8L
Listed Models	:	H-12L ,SPA036, SPA040, MP-101V, MP-102V, MP-103V, MP-201V, MP-202V, MP-203V
Applicant	:	<b>Kinyu Electronic Co., Limited</b>
Address	:	Flat / Rm 1801, 18/F Bonham Trade Center 50 Bonham Strand, Sheung Wan, Hongkong
Manufacturer	:	<b>Guangzhou Tianpu Electrical Equipment Co., Ltd.</b>
Address	:	No. 8 Jintian Rd. Jintian Industrial Area Huadong Town, Huadu District, Guangzhou, China

<b>Test result</b>	<b>Pass *</b>
--------------------	---------------

\* In the configuration tested, the EUT complied with the standards specified page 5.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## \*\* Modified History \*\*



	Table of Contents	Page
<u>1</u>	<u>SUM MARY .....</u>	<u>5</u>
1.1	Test Standards	5
1.2	Test Description	5
1.3	Test Facility	6
1.4	Statement of the measurement uncertainty	6
<u>2</u>	<u>GENERAL INFORMATION .....</u>	<u>7</u>
2.1	Environmental conditions	7
2.2	General Description of EUT	7
2.3	Description of Test Modes and Test Frequency	7
2.4	Equipments Used during the Test	8
2.5	Related Submittal(s) / Grant(s)	8
2.6	Modifications	8
<u>3</u>	<u>TEST CONDITIONS AND RESULTS.....</u>	<u>9</u>
3.1	Output Power Measurement	9
3.2	Modulation Characteristics	11
3.3	Operating Bandwidth and Emissions Mask	18
3.4	Field Strength of Emission	21
3.5	Frequency Stability Measurement	23
<u>4</u>	<u>TEST SETUP PHOTOS OF THE EUT .....</u>	<u>25</u>
<u>5</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....</u>	<u>26</u>

# 1 SUMMARY

## 1.1 Test Standards

The tests were performed according to following standards:

**FCC Part 74 Subpart H**—Low Power Auxiliary Stations

**TIA-603-C (2004)**-Land Mobile FM or PM Communications Equipment Measurement and Performance Standards

**FCC Part 2: FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS**

**ANSI C63.10:2013:** –American National Standard for Testing Unlicensed Wireless Devices

**ANSI C63.4: 2014:** –American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz Range of 9 kHz to 40GHz

## 1.2 Test Description

FCC Rules	Description of Test	Test Result
FCC section 74.861(e)(1), FCC part 2, section 2.1046	RF Output Power	Complies
FCC section 74.861(e)(3) , FCC part 2, section 2.1047	Modulation Characteristic	Complies
FCC section 74.861(e)(5) , FCC part 2, section 2.1049	Emission Bandwidth	Complies
FCC section 74.861(e)(6) , FCC part 2, section 2.1053	Field Strength of Spurious Emission	Complies
FCC section 74.861(e)(4) , FCC part 2, section 2.1055	Frequency Stability	Complies

## 1.3 Test Facility

### 1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

### 1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

#### IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

#### FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

## 1.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	Above 1GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

1 This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 2 GENERAL INFORMATION

### 2.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

### 2.2 General Description of EUT

Product Name:	Wireless Microphone
Model/Type reference:	H-8L
Power supply:	DC 3.0V from battery
<b>Wireless microphone</b>	
Alignment range:	174.25MHz-215.75MHz
Channel number:	167
Channel separation:	250KHz
Modulation Type:	FM

Note: For more details, please refer to the user's manual of the EUT.

### 2.3 Description of Test Modes and Test Frequency

This device worked in continuous transmitting (Duty Cycle more than 98%) when it turned on and all test conducted under this mode.

#### Frequency List

Channel	Frequency (MHz)
01	174.25
02	174.50
03	174.75
:	:
84	195.00
:	:
165	215.25
166	215.50
<b>167</b>	<b>215.75</b>

Note: In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middlefrequency, and the highest frequency of channel were selected to perform the test.

## 2.4 Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2016/06/02	2017/06/01
Bilog Antenna	Sunol Sciences Corp.	JB1	A061714	2016/06/02	2017/06/01
EMI Test Receiver	R&S	ESCI	103710	2016/06/02	2017/06/01
Spectrum Analyzer	Agilent	E4407B	MY41440676	2016/05/21	2017/05/20
Spectrum Analyzer	Agilent	N9020	US46220290	2016/01/17	2017/01/16
Controller	EM Electronics	Controller EM 1000	N/A	2016/05/21	2017/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2016/05/19	2017/05/18
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062014	2016/05/19	2017/05/18
Active Loop Antenna	SCHWARZBEC K	FMZB1519	1519-037	2016/05/19	2017/05/18
Amplifier	Agilent	8349B	3008A02306	2016/05/19	2017/05/18
Amplifier	Agilent	8447D	2944A10176	2016/05/19	2017/05/18
Temperature/Humidity Meter	Gangxing	CTH-608	02	2016/05/20	2017/05/19
Radio Communication Tester	HP	8920A	116250	2015/10/11	2016/10/11
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	N/A	2016/05/20	2017/05/19
High-Pass Filter	K&L	41H10-1375/U12750-O/O	N/A	2016/05/20	2017/05/19
Climate Chamber	ESPEC	EL-10KA	A20120523	2016/05/20	2017/05/19
SIGNAL GENERATOR	Agilent	E4421B	US40051744	2016/05/20	2017/05/19
Directional Coupler	Agilent	87300B	3116A03638	2016/05/20	2017/05/19
Coaxial Cables	HUBER+SUHN ER	SUCOFLEX 104PEA-10M	10m	2016/06/02	2017/06/01
Coaxial Cables	HUBER+SUHN ER	SUCOFLEX 104PEA-3M	3m	2016/06/02	2017/06/01
Coaxial Cables	HUBER+SUHN ER	SUCOFLEX 104PEA-3M	3m	2016/06/02	2017/06/01
RF Cable	Megalon	RF-A303	N/A	2016/06/02	2017/06/01

The calibration interval was one year

## 2.5 Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended to comply with FCC Part 74 Subpart H Rules.

## 2.6 Modifications

No modifications were implemented to meet testing criteria.


### 3 TEST CONDITIONS AND RESULTS

#### 3.1 Output Power Measurement

##### Limit

According to §74.861(e)(1)(ii), the output power shall not exceed 50 milliwatts (EIRP).

##### Test Configuration



##### Measurement Procedure

1. EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.0m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all test transmit frequencies were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as ( $P_r$ ).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the

substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

5. An amplifier may be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss ( $P_{cl}$ ), the Substitution Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should be recorded after test.  
The measurement results are obtained as described below:  
$$\text{Power(EIRP)} = P_{Mea} + P_{Ag} - P_{cl} + G_a$$
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.

### **TEST RESULTS**

Note: 1. The field strength of radiation emission was measured in the following position: EUT stand-up position (Zaxis), lie-down position (X, Y axis). The data show in this report only with the worst case setup. After exploratory measurement the worst case of Z axis was reported.

Test Frequency (MHz)	$P_{Mea}$ (dBm)	$P_{cl}$ (dB)	$G_a$ Antenna Gain(dBi)	Correction (dB)	$P_{Ag}$ (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
174.25	-24.89	2.18	7.58	0	34.18	14.69	17	2.31	V
195.00	-25.09	2.18	7.89		34.22	14.84		2.16	V
215.75	-25.43	2.19	7.93		34.31	14.62		2.38	V

Remark:

$$1. \text{ EIRP} = P_{Mea}(\text{dBm}) + P_{Ag}(\text{dB}) - P_{cl}(\text{dB}) + G_a(\text{dBi})$$



## 3.2 Modulation Characteristics

### Limit

Test Standard: FCC Part 74.861(e)(3)


Any form of modulation may be used. A maximum deviation of  $\pm 75$  kHz is permitted when frequency modulation is employed.

Test Standard: FCC Part 2.1047(a) & (b)

(a) Voice modulated communication equipment. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz shall be submitted. For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter or of all circuitry installed between the modulation limiter and the modulated stage shall be submitted.

(b) Equipment which employs modulation limiting. A curve or family of curves showing the percentage of modulation versus the modulation input voltage shall be supplied. The information submitted shall be sufficient to show modulation limiting capability throughout the range of modulating frequencies and input modulating signal levels employed.

### Test Configuration



### Measurement Procedure

#### a) **Audio Frequency Response**

1. Connect the equipment as illustrated.
2. Set the test receiver to measure peak positive deviation. Set the audio bandwidth for  $\leq 50$  Hz to  $\geq 15,000$  Hz. Turn the de-emphasis function off.
3. Adjust the transmitter per the manufacturer's procedure for full rated system deviation.
4. Apply a 1000 Hz tone and adjust the audio frequency generator to produce 20% of the rated system deviation.
5. Set the test receiver to measure rms deviation and record the deviation reading as  $DEV_{REF}$ .
6. Set the audio frequency generator to the desired test frequency between 100Hz and 2000Hz.
7. Record the test receiver deviation reading as  $DEV_{FREQ}$ .
8. Calculate the audio frequency response at the present frequency as:

$$\text{audio frequency response} = 20 \log_{10} \left( \frac{DEV_{FREQ}}{DEV_{REF}} \right)$$

9. Repeat steps 6 through 8 for all the desired test frequencies.

#### b) **Modulation Limiting**

1. Connect the equipment as illustrated.
2. Adjust the transmitter per the manufacturer's procedure for full rated system deviation.
3. Set the test receiver to measure peak positive deviation. Set the audio bandwidth for  $\leq 0.25$  Hz to  $\geq 15,000$  Hz. Turn the de-emphasis function off.
4. Apply a 1000 Hz modulating signal to the transmitter from the audio frequency generator, and adjust the level to obtain 60% of full rated system deviation.
5. Increase the level from the audio frequency generator by 20dB in one step (rise time between the 10% and 90% points shall be 0.1 second maximum).

6. Measure both the instantaneous and steady-state deviation at and after the time of increasing the audio input level.
7. With the level from the audio frequency generator held constant at the level obtained in step 5, slowly vary the audio frequency from 100Hz to 3000Hz and observe the steady-state deviation. Record the maximum deviation.
8. Set the test receiver to measure peak negative deviation and repeat steps 4 through 7.
9. The values recorded in steps 7 and 8 are the modulation limiting.


## **TEST RESULTS**

### **Audio Frequency Response**

**174.25MHZ**

0dB=11mV at 1kHz (20% of the maximum rated system deviation.)


Frequency (KHz)	Frequency Deviation (KHz)	1KHz Reference Deviation (KHz)	Audio Frequency Response (dB)
0.1	5.14	1.59	10.19
0.2	5.15	1.59	10.21
0.3	5.26	1.59	10.39
0.4	4.15	1.59	8.33
0.5	3.22	1.59	6.13
0.6	3.16	1.59	5.97
0.7	2.24	1.59	2.98
0.8	1.98	1.59	1.91
0.9	1.74	1.59	0.78
1.0	1.59	1.59	0.00
1.2	1.63	1.59	0.22
1.4	1.44	1.59	-0.86
1.6	1.25	1.59	-2.09
1.8	1.36	1.59	-1.36
2.0	1.41	1.59	-1.04
2.2	1.01	1.59	-3.94
2.4	0.89	1.59	-5.04
2.6	0.68	1.59	-7.38
2.7	0.74	1.59	-6.64
2.8	0.69	1.59	-7.25
3.0	0.47	1.59	-10.59
3.5	0.38	1.59	-12.43
4.0	0.33	1.59	-13.66
4.5	0.11	1.59	-23.20
5.0	0.11	1.59	-23.20
10.0	0.05	1.59	-30.05
15.0	0.02	1.59	-38.01
20.0	0.03	1.59	-34.49



## 195.00MHZ

0dB=12mV at 1kHz (20% of the maximum rated system deviation.)


Frequency (KHz)	Frequency Deviation (KHz)	1KHz Reference Deviation (KHz)	Audio Frequency Response (dB)
0.1	4.26	1.55	8.78
0.2	5.26	1.55	10.61
0.3	5.11	1.55	10.36
0.4	3.26	1.55	6.46
0.5	3.15	1.55	6.16
0.6	2.98	1.55	5.68
0.7	2.11	1.55	2.68
0.8	1.86	1.55	1.58
0.9	1.66	1.55	0.60
1.0	1.55	1.55	0.00
1.2	1.48	1.55	-0.40
1.4	1.69	1.55	0.75
1.6	1.44	1.55	-0.64
1.8	1.38	1.55	-1.01
2.0	1.56	1.55	0.06
2.2	0.99	1.55	-3.89
2.4	0.87	1.55	-5.02
2.6	0.78	1.55	-5.96
2.7	0.69	1.55	-7.03
2.8	0.55	1.55	-9.00
3.0	0.36	1.55	-12.68
3.5	0.26	1.55	-15.51
4.0	0.33	1.55	-13.44
4.5	0.15	1.55	-20.28
5.0	0.15	1.55	-20.28
10.0	0.21	1.55	-17.36
15.0	0.03	1.55	-34.26
20.0	0.03	1.55	-34.26



## 215.75MHZ

0dB=11mV at 1kHz (20% of the maximum rated system deviation.)


Frequency (KHz)	Frequency Deviation (KHz)	1KHz Refenerce Deviation (KHz)	Audio Frequency Response (dB)
0.1	5.35	1.61	10.43
0.2	4.98	1.61	9.81
0.3	5.14	1.61	10.08
0.4	3.56	1.61	6.89
0.5	3.22	1.61	6.02
0.6	3.30	1.61	6.23
0.7	2.24	1.61	2.87
0.8	1.87	1.61	1.30
0.9	1.56	1.61	-0.27
1.0	1.61	1.61	0.00
1.2	1.21	1.61	-2.48
1.4	1.58	1.61	-0.16
1.6	1.65	1.61	0.21
1.8	1.47	1.61	-0.79
2.0	1.51	1.61	-0.56
2.2	0.98	1.61	-4.31
2.4	0.88	1.61	-5.25
2.6	1.01	1.61	-4.05
2.7	0.75	1.61	-6.64
2.8	0.84	1.61	-5.65
3.0	0.66	1.61	-7.75
3.5	0.54	1.61	-9.49
4.0	0.38	1.61	-12.54
4.5	0.27	1.61	-15.51
5.0	0.12	1.61	-22.55
10.0	0.11	1.61	-23.31
15.0	0.05	1.61	-30.16
20.0	0.03	1.61	-34.59



## Modulation Limit:


174.25MHz

Modulation Level (dB)	Peak Freq. Deviation At 300 Hz (KHz)	Peak Freq. Deviation At 1000Hz (KHz)	Peak Freq. Deviation At 2000Hz (KHz)	Peak Freq. Deviation At 3000 Hz (KHz)
-20	5.26	5.11	5.58	5.69
-15	5.48	6.25	6.69	7.15
-10	5.41	5.41	5.33	6.22
-5	15.26	17.58	18.44	20.11
0	15.86	18.54	18.36	19.68
+5	20.33	22.66	25.22	27.44
+10	21.45	24.56	26.95	28.26
+15	22.78	25.62	27.14	29.33
+20	25.78	26.98	28.25	30.41




195.00MHz

Modulation Level (dB)	Peak Freq. Deviation At 300 Hz (KHz)	Peak Freq. Deviation At 1000Hz (KHz)	Peak Freq. Deviation At 2000Hz (KHz)	Peak Freq. Deviation At 3000 Hz (KHz)
-20	5.35	5.32	5.65	6.11
-15	5.45	5.89	6.18	6.58
-10	5.21	5.41	5.78	6.52
-5	14.99	17.44	18.14	20.41
0	15.85	18.63	19.33	19.89
+5	20.14	21.95	25.52	27.33
+10	21.52	23.56	26.41	28.25
+15	22.89	26.14	27.22	29.47
+20	25.47	27.11	28.87	30.85



215.75MHz

Modulation Level (dB)	Peak Freq. Deviation At 300 Hz (KHz)	Peak Freq. Deviation At 1000Hz (KHz)	Peak Freq. Deviation At 2000Hz (KHz)	Peak Freq. Deviation At 3000 Hz (KHz)
-20	5.69	5.15	5.63	6.21
-15	5.87	5.59	6.52	6.96
-10	5.55	6.25	5.88	6.45
-5	15.01	18.11	18.39	20.31
0	15.98	18.89	19.45	19.79
+5	20.45	20.99	25.69	28.15
+10	21.55	22.69	26.52	29.45
+15	22.74	26.88	27.45	30.25
+20	25.89	28.10	28.66	31.89



### 3.3 Operating Bandwidth and Emissions Mask

#### Limit


Test Standard: FCC Part 74.861(e)(5), (6)

(5) The operating bandwidth shall not exceed 200 kHz.

(6) The mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

- (i) On any frequency removed from the operating frequency by more than 50 percent up to and including 100 per-cent of the authorized bandwidth: at least 25 dB;
- (ii) On any frequency removed from the operating frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth: at least 35 dB;
- (iii) On any frequency removed from the operating frequency by more than 250 percent of the authorized bandwidth: at least  $43 + 10\log_{10}$  (mean output power in watts) dB.

#### Test Configuration



#### Measurement Procedure


1. Connect the equipment as illustrated.
2. Adjust the spectrum analyzer for the following settings:  
RBW = 3kHz, VBW = 30kHz  
Sweep Speed slow enough to maintain measurement calibration.  
Detector Mode = Positive Peak.  
Span that will allow proper viewing of the test bandwidth
3. Set the center frequency of the spectrum analyzer to the assigned transmitter frequency. Turn on the transmitter, and set the level of the unmodulated carrier to a full scale reference line. This is the 0 dB reference for the measurement.
4. Modulate the transmitter with a 2500 Hz sine wave at an input level 16 dB greater than that necessary to produce 50% of rated system deviation. The input level shall be established at the frequency of maximum response of the audio modulating circuit. Transmitters employing digital modulation techniques that bypass the limiter and the audio low-pass filter shall be modulated as specified by the manufacturer.
5. Mark the 99% and 20dBm band bandwidth of peak frequency.
6. Repeat until all the rest channels are investigated.

#### Test Result


##### a) Operating Bandwidth:

Modulation	Frequency (MHz)	99% OBW (KHz)	20dB bandwidth (KHz)	Result
FM	174.25	171.64	179.50	Pass
	195.00	171.62	179.30	
	215.75	171.33	179.20	


174.25MHz



195.00MHz




215.75MHz




## b) Emission Mask:


174.25MHz



195.00MHz



215.75MHz



### 3.4 Field Strength of Emission


#### Limit

According to §2.1053, measurements shall be made to detect spurious emission that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal condition of installation and operation. Information submitted shall include the relative radiated power of spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from a halfwave dipole antenna.

According to §74.861(e)(6), the mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

- (i) on any frequency removed from the operating frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth: at least 25 dB.
- (ii) on any frequency removed from the operating frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth: at least 35 dB.
- (iii) on any frequency removed from the operating frequency by more than 250 percent of the authorized bandwidth shall be attenuated below the unmodulated carrier by at least 43 plus  $10 \log(\text{output power in watts})$  dB.

#### Test Configuration



### Measurement Procedure

- a. EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.0m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all test transmit frequencies were measured with peak detector.
- b. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
- c. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum 100 kHz below 1GHz and 1MHz above 1GHz, Sweep from 30MHz to the 10th harmonic of the fundamental frequency; and recorded the level of the concerned spurious emission point as ( $P_r$ ).
- d. The EUT then replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

The measurement results are obtained as described below:

$$\text{Power}_{(\text{EIRP})} = P_{Mea} - P_{cl} + G_a$$

Where:

$P_{Mea}$  is the recorded signal generator level

$P_{cl}$  is the cable loss connect between instruments

$G_a$  Substitution Antenna Gain

- e. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- f. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .
- g. Test site anechoic chamber refer to ANSI C63.

### Test Result

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency; and worst spurious emissions recorded as below:

Test Frequency (MHz)	Frequency (MHz)	$P_{Mea}$ (dBm)	$P_{cl}$ (dB)	Diatance (m)	$G_a$ Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
174.25	248.50	-27.06	2.05	3.00	10.59	-18.52	-13.00	5.52	V
	522.75	-29.13	2.68	3.00	11.45	-20.36	-13.00	7.36	V
	697.00	-35.23	3.12	3.00	13.14	-25.21	-13.00	12.21	V
	871.25	-36.92	3.91	3.00	13.98	-26.85	-13.00	13.85	V
	--	--	--	--	--	--	--	--	--
195.00	390.00	-27.30	2.11	3.00	10.78	-18.63	-13.00	5.63	V
	585.00	-30.35	2.88	3.00	11.98	-21.25	-13.00	8.25	V
	780.00	-34.49	3.69	3.00	13.66	-24.52	-13.00	11.52	V
	975.00	-36.89	3.14	3.00	14.25	-25.78	-13.00	12.78	V
	--	--	--	--	--	--	--	--	--
215.75	431.50	-26.42	2.43	3.00	11.11	-17.74	-13.00	4.74	V
	647.25	-30.85	3.11	3.00	12.52	-21.44	-13.00	8.44	V
	863.00	-35.42	3.98	3.00	14.17	-25.23	-13.00	12.23	V
	1078.75	-39.07	3.27	3.00	15.36	-26.98	-13.00	13.98	V
	--	--	--	--	--	--	--	--	--

Remark:

1.  $EIRP = P_{Mea}(\text{dBm}) - P_{cl}(\text{dB}) + G_a(\text{dBi})$
2. -- Means other points for values lower than limits and not recorded.
3. Margin = Limit – EIRP
4. H and V polarity all have been tested, only worse case V polarity is reported.

## 3.5 Frequency Stability Measurement

### Limit

Test Standard: FCC Part 74.861(e)(4)

(4) The frequency tolerance of the transmitter shall be 0.005 percent.

### Measurement Procedure

#### a) Frequency stability versus environmental temperature


1. Setup as Test Configuration for frequencies measured at ambient temperature if it is within 15°C to 25°C. Otherwise, an environmental chamber set for a temperature of 20°C shall be used.
2. Turn on EUT and set SA center frequency to the right frequency needs to be measured. Then set SA RBW to 30 kHz, VBW to 100kHz and frequency span to 500 kHz. Record this frequency to be a reference.
3. Set the temperature of chamber to 50°C. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
4. Repeat step 2 with a 10°C decreased per stage until the lowest temperature -30°C is measured, record all measurement frequencies.

#### b) Frequency stability versus input voltage

1. Setup as Test Configuration for frequencies measured at ambient temperature if it is within 15°C to 25°C. Otherwise, an environmental chamber set for a temperature of 20°C shall be used. Install new batteries in the EUT.
2. Set SA center frequency to the right frequency needs to be measured. Then set SA RBW to 30 kHz, VBW to 100kHz and frequency span to 500 kHz. Record this frequency to be a reference.
3. For non hand carried, battery operated device, supply the EUT primary voltage with 85 and 115 percent of the nominal value and record the frequency.

### Test Configuration

Temperature Chamber





**TEST RESULTS**

Reference Frequency: 195.00MHz					
Voltage (V)	Temperature (°C)	Frequency error (MHz)	Frequency Tolerance (%)	Limit (%)	Result
3.00	-30	0.00625	0.00321%	0.005%	Pass
	-20	0.00587	0.00301%		
	-10	0.00612	0.00314%		
	0	0.00547	0.00281%		
	10	0.00552	0.00283%		
	20	0.00611	0.00313%		
	30	0.00578	0.00296%		
	40	0.00565	0.00290%		
	50	0.00532	0.00273%		
	3.45	25	0.00547		
2.55	25	0.00519	0.00266%		




## 4 Test Setup Photos of the EUT





## 5 External and Internal Photos of the EUT

### External Photos





Internal Photos

.....End of Report.....