

RF Exposure evaluation

FCC ID: 2AIUA-UR-008

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 1	Antenna 1	External antenna	902-928MHz	8 dBi
Antenna 2	Antenna 2	External antenna	902-928MHz	8 dBi
Antenna 3	Antenna 3	External antenna	902-928MHz	8 dBi
Antenna 4	Antenna 4	External antenna	902-928MHz	8 dBi
Antenna 5	Antenna 5	External antenna	902-928MHz	8 dBi
Antenna 6	Antenna 6	External antenna	902-928MHz	8 dBi
Antenna 7	Antenna 7	External antenna	902-928MHz	8 dBi
Antenna 8	Antenna 8	External antenna	902-928MHz	8 dBi

5. Standalone MPE Result

The EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, the RF power density can be obtained.

RFID

Antenna Identification in Internal photos	Frequency (MHz)	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
		dBm	mW				
Antenna 1	902.5	21.257	132.3031	8	6.3096	0.1661	0.6017
Antenna 2	902.5	21.464	140.0877	8	6.3096	0.1758	0.6017
Antenna 3	902.5	21.492	140.9938	8	6.3096	0.1770	0.6017
Antenna 4	902.5	21.569	143.5159	8	6.3096	0.1801	0.6017
Antenna 5	902.5	21.464	140.0877	8	6.3096	0.1758	0.6017
Antenna 6	902.5	21.403	138.1338	8	6.3096	0.1734	0.6017
Antenna 7	902.5	21.491	140.9613	8	6.3096	0.1769	0.6017
Antenna 8	902.5	21.255	133.5058	8	6.3096	0.1676	0.6017

Remark:

1. MPE evaluate distance is 20cm from user manual provide by manufacturer.

6. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of Mobile Device.

-----THE END OF REPORT-----