

TEST REPORT

Applicant Name : Inrico Technologies Co., Ltd
Address : 3/F, Building No.118, High Tech Industrial Park, 72 Guowei Road, Luohu District, Shenzhen, China
Report Number : SZGMA210715-29390E-RF-00B
FCC ID: 2AIV6-2-S100

Test Standard (s)

FCC PART 15.247


Sample Description

Product Type: Smart Phone
Model No.: S100
Multiple Model(s) No.: PU1Z81WAE21A
Trade Mark: Inrico
Date Received: 2021/07/15
Date of Test: 2021/07/28~2021/11/19
Report Date: 2021/11/19

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:



Fan Yang
EMC Engineer

Approved By:



Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	10
EXTERNAL I/O CABLE.....	10
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS.....	13
TEST EQUIPMENT LIST	14
FCC§15.247 (I), §1.1307 (B) (1) & §2.1093 – RF EXPOSURE	15
APPLICABLE STANDARD	15
FCC §15.203 - ANTENNA REQUIREMENT.....	16
APPLICABLE STANDARD	16
ANTENNA CONNECTOR CONSTRUCTION	16
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE	17
TRANSD FACTOR & MARGIN CALCULATION.....	18
TEST DATA	18
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS.....	21
APPLICABLE STANDARD	21
EUT SETUP	21
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	22
TEST PROCEDURE	22
FACTOR & MARGIN CALCULATION	22
TEST DATA	22
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	31
APPLICABLE STANDARD	31
TEST PROCEDURE	31
TEST DATA	31
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST DATA	41

FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	43
APPLICABLE STANDARD	43
TEST PROCEDURE	43
TEST DATA	43
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	49
APPLICABLE STANDARD	49
TEST PROCEDURE	49
TEST DATA	49

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	BLE: 2402-2480MHz Wi-Fi: 2412-2472MHz
Maximum Conducted Peak Output Power	BLE: -0.44dBm Wi-Fi: 10.92dBm
Modulation Technique	BLE: GFSK Wi-Fi: DSSS, OFDM
Antenna Specification*	1.5dBi(provided by the applicant)
Voltage Range	DC5V from adapter or DC 3.8V From Battery
Sample serial number	SZGMA210715-29390E-RFA1-S1 (CE&RE) SZGMA210715-29390E-RFA1-S2 (RF Conducted Test) (Assigned by ATC, Shenzhen)
Sample/EUT Status	Good condition
Adapter information	Model: HJ-0502000W2-US Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5.0V, 2000mA

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.
Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
Emissions, Radiated	30MHz - 1GHz	4.28dB
	1GHz- 18GHz	4.98dB
	18GHz- 26.5GHz	5.06dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Wi-Fi

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 7 and 13

For 802.11n-HT40 mode, EUT was tested with Channel 3, 7 and 11

BLE

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software


“SP_META_exe_V1.1824.00” exercise software was used. The power level was provided by the applicant.

The device was tested with the worst case was performed as below:


Mode	Data rate	Power level*		
		Low channel	Middle channel	High channel
802.11b	1Mbps	14	14	14
802.11g	6Mbps	10	10	10
802.11n-HT20	MCS0	10	10	10
802.11n-HT40	MCS0	10	10	10
BLE	1Mbps	Default		

Duty cycle

802.11b mode




802.11g mode




Date: 29.JUL.2021 14:43:46

802.11n-HT20 Mode




Date: 29.JUL.2021 14:41:30

802.11n-HT40 Mode



Date: 29.JUL.2021 14:40:00

BLE



Date: 28.JUL.2021 17:07:59

Mode	T _{on} (us)	T _{on+off} (us)	Duty Cycle (%)
802.11b	/	/	100
802.11g	/	/	100
802.11n-HT20	/	/	100
802.11n-HT40	/	/	100
BLE 1M	391.3	626.09	62.5%

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Inrico	Earphone	Unknown	Unknown
Inrico	MIC	Unknown	Unknown

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielding Un-Detachable AC Cable	1.2	LISN	Receptacle
Un-shielding Detachable USB Cable	1.0	EUT	Adapter
Un-shielding Detachable Earphone Cable	1.0	MIC	Earphone
Un-shielding Detachable MIC Cable	1.0	EUT	MIC

Block Diagram of Test Setup


For conducted emission



For radiated emission: (below 1GHz)



For radiated emission: (above 1GHz)



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde&Schwarz	Test Receiver	ESPI3	100396	2020/12/24	2021/12/23
R & S	L.I.S.N.	ENV216	101314	2020/12/25	2021/12/24
Anritsu Corp	50Ω Coaxial Switch	MP59B	6200506474	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-2m	No.2	2020/12/25	2021/12/24
Conducted Emission Test Software: ES-K1 V1.71					
Radiated Emissions Test					
Rohde&Schwarz	Test Receiver	ESR	101817	2020/12/24	2021/12/23
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2020/12/24	2021/12/23
A.H. Systems, inc.	Preamplifier	PAM-0118P	531	2021/07/08	2022/07/07
SONOMA INSTRUMENT	Amplifier	310 N	186131	2020/12/25	2021/12/24
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2020/11/28	2021/11/27
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2020/01/04	2023/01/03
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Unknown	RF Coaxial Cable	N-5m	No.3	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-5m	No.4	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.5	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.6	2020/12/25	2021/12/24
Radiated Emission Test Software: EZ EMC V 1.1.4.2					
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV40	101495	2020/12/24	2021/12/23
Rohde & Schwarz	Open Switch and Control Unit	OSP120 +OSP-B157	101244 + 100866	2020/12/24	2021/12/23

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

Mode	Frequency (MHz)	Max Tune-up Conducted Power (dBm)	Max Tune-up Conducted Power (mW)	Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
WLAN 2.4G	2472	8	6.31	5	2.0	3	YES
Bluetooth	2480	0	1.00	5	0.3	3	YES

Result: No Standalone SAR test is required

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached and the antenna gain is 1.5dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Transd Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{level}$$

$$\text{Level} = \text{reading level} + \text{Transd Factor}$$


Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Bin Duan on 2021-10-19.

EUT operation mode: Transmitting (Worst case as 802.11n40 low channel)

AC 120V/60 Hz, Line**MEASUREMENT RESULT: "29390-01L_fin"**


2021-10-19 10:08

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.150000	45.40	10.8	66	20.6	QP	L1	GND
0.340000	46.30	10.9	59	12.7	QP	L1	GND
0.725000	51.30	11.1	56	4.7	QP	L1	GND
0.965000	45.10	11.1	56	10.9	QP	L1	GND
3.500000	41.70	11.4	56	14.3	QP	L1	GND
12.150000	40.30	11.6	60	19.7	QP	L1	GND
20.000000	51.40	11.7	60	8.6	QP	L1	GND

MEASUREMENT RESULT: "29390-01L_fin2"

2021-10-19 10:08

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.340000	33.50	10.9	49	15.5	AV	L1	GND
0.720000	39.20	11.1	46	6.8	AV	L1	GND
0.915000	32.60	11.1	46	13.4	AV	L1	GND
3.550000	29.70	11.4	46	16.3	AV	L1	GND
12.225000	29.90	11.6	50	20.1	AV	L1	GND
20.000000	38.80	11.7	50	11.2	AV	L1	GND

AC 120V/60 Hz, Neutral**MEASUREMENT RESULT: "29390-01N_fin"**

2021-10-19 10:18

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.335000	41.60	10.9	59	17.4	QP	N	GND
0.715000	49.70	11.1	56	6.3	QP	N	GND
1.410000	46.00	11.2	56	10.0	QP	N	GND
2.190000	43.00	11.3	56	13.0	QP	N	GND
11.825000	43.10	11.6	60	16.9	QP	N	GND
20.950000	53.50	11.7	60	6.5	QP	N	GND

MEASUREMENT RESULT: "29390-01N_fin2"

2021-10-19 10:11

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.340000	31.40	10.9	49	17.6	AV	N	GND
0.715000	41.50	11.1	46	4.5	AV	N	GND
1.395000	35.70	11.2	46	10.3	AV	N	GND
2.330000	33.80	11.3	46	12.2	AV	N	GND
11.900000	34.70	11.6	50	15.3	AV	N	GND
20.225000	41.20	11.7	50	8.8	AV	N	GND


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned}\text{Margin} &= \text{Result} - \text{Limit} \\ \text{Result} &= \text{Reading} + \text{Factor}\end{aligned}$$

Test Data



Environmental Conditions

Temperature:	23 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Chao Mo on 2021-10-21.

Test mode: Transmitting (Pre-scan in the X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded)

30MHz-1GHz: (Worst case is 802.11n40 low channel)

Horizontal**Vertical**

1-25 GHz:**BLE:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
BLE 1M, Low Channel									
2310	60.2	PK	341	1.3	H	-6.84	53.36	74	-20.64
2310	58.97	PK	79	1.5	V	-6.84	52.13	74	-21.87
2390	65.92	PK	14	1.3	H	-6.44	59.48	74	-14.52
2390	49.93	AV	14	1.3	H	-6.44	43.49	54	-10.51
2390	65.38	PK	59	1.1	V	-6.44	58.94	74	-15.06
2390	49.7	AV	59	1.1	V	-6.44	43.26	54	-10.74
4804	43.88	PK	64	1.7	H	2.81	46.69	74	-27.31
4804	43.06	PK	91	1.7	V	2.81	45.87	74	-28.13
BLE 1M, Middle Channel									
4880	41.25	PK	267	1.6	H	3.04	44.29	74	-29.71
4880	40.28	PK	334	1.6	V	3.04	43.32	74	-30.68
BLE 1M, High Channel									
2483.5	65.44	PK	2	2.0	H	-5.96	59.48	74	-14.52
2483.5	49.74	AV	2	2.0	H	-5.96	43.78	54	-10.22
2483.5	64.32	PK	296	2.2	V	-5.96	58.36	74	-15.64
2483.5	48.29	AV	296	2.2	V	-5.96	42.33	54	-11.67
2500	63.34	PK	317	1.2	H	-5.88	57.46	74	-16.54
2500	47.14	AV	317	1.2	H	-5.88	41.26	54	-12.74
2500	62.66	PK	19	1.8	V	-5.88	56.78	74	-17.22
2500	46.65	AV	19	1.8	V	-5.88	40.77	54	-13.23
4960	40.61	PK	342	2.1	H	3.29	43.9	74	-30.10
4960	39.86	PK	341	1.1	V	3.29	43.15	74	-30.85

Wi-Fi:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Substituted Factor (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
	Reading (dBm)	PK/Ave.		Height (m)	Polar (H/V)				
802.11B, Low Channel									
2310	62.19	PK	148	1.9	H	-6.84	55.35	74	-18.65
2310	51.26	Ave.	148	1.9	H	-6.84	44.42	54	-9.58
2310	61.87	PK	53	1.1	V	-6.84	55.03	74	-18.97
2310	52.1	Ave.	53	1.1	V	-6.84	45.26	54	-8.74
2390	57.6	PK	336	1.5	H	-6.44	51.16	74	-22.84
2390	62.8	PK	206	1.1	V	-6.44	56.36	74	-17.64
2390	51.87	Ave.	206	1.1	V	-6.44	45.43	54	-8.57
4824	40.61	PK	150	1.1	H	2.87	43.48	74	-30.52
4824	42.48	PK	282	1.5	V	2.87	45.35	74	-28.65
802.11B, Middle Channel									
4884	45.02	PK	154	2.2	H	3.04	48.06	74	-25.94
4884	45.26	PK	20	1.4	V	3.04	48.30	74	-25.70
802.11B, High Channel									
2483.5	62.39	PK	173	1.1	H	-5.96	56.43	74	-17.57
2483.5	50.09	Ave.	173	1.1	H	-5.96	44.13	54	-9.87
2483.5	61.32	PK	96	1.3	V	-5.96	55.36	74	-18.64
2483.5	51.32	Ave.	96	1.3	V	-5.96	45.36	54	-8.64
2500	56.31	PK	220	2.2	H	-5.88	50.43	74	-23.57
2500	55.09	PK	103	1.5	V	-5.88	49.21	74	-24.79
4944	41.31	PK	295	1.2	H	3.23	44.54	74	-29.46
4944	42.04	PK	11	1.3	V	3.23	45.27	74	-28.73

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Substituted Factor (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
	Reading (dBm)	PK/Ave		Height (m)	Polar (H/V)				
802.11G, Low Channel									
2310	51.5	PK	100	1.3	H	-6.84	44.66	74	-29.34
2310	51.27	PK	45	2.0	V	-6.84	44.43	74	-29.57
2390	66.58	PK	192	2.2	H	-6.44	60.14	74	-13.86
2390	49.88	Ave.	192	2.2	H	-6.44	43.44	54	-10.56
2390	65.77	PK	44	2.1	V	-6.44	59.33	74	-14.67
2390	69.21	Ave.	44	2.1	V	-6.44	62.77	74	-11.23
4824	41.82	PK	224	1.9	H	2.87	44.69	74	-29.31
4824	41	PK	97	1.2	V	2.87	43.87	74	-30.13
802.11G, Middle Channel									
4884	40.45	PK	113	1.1	H	3.04	43.49	74	-30.51
4884	40.09	PK	316	1.2	V	3.04	43.13	74	-30.87
802.11G, High Channel									
2483.5	67.83	PK	86	1.7	H	-5.96	61.87	74	-12.13
2483.5	50.49	Ave.	86	1.7	H	-5.96	44.53	54	-9.47
2483.5	65.44	PK	183	2.1	V	-5.96	59.48	74	-14.52
2483.5	50.59	Ave.	183	2.1	V	-5.96	44.63	54	-9.37
2500	61.12	PK	166	1.8	H	-5.88	55.24	74	-18.76
2500	45.21	Ave.	166	1.8	H	-5.88	39.33	54	-14.67
2500	60.62	PK	327	1.0	V	-5.88	54.74	74	-19.26
2500	43.65	Ave.	327	1.0	V	-5.88	37.77	54	-16.23
4944	41.64	PK	245	1.6	H	3.23	44.87	74	-29.13
4944	40.89	PK	3	1.1	V	3.23	44.12	74	-29.88

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Substituted Factor (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
	Reading (dBm)	PK/Ave		Height (m)	Polar (H/V)				
802.11N20, Low Channel									
2310	72.32	PK	161	1.9	H	-6.84	65.48	74	-8.52
2310	53.3	Ave.	161	1.9	H	-6.84	46.46	54	-7.54
2310	73.56	PK	321	1.6	V	-6.84	66.72	74	-7.28
2310	53.73	Ave.	321	1.6	V	-6.84	46.89	54	-7.11
2390	66.87	PK	178	1.2	H	-6.44	60.43	74	-13.57
2390	50.21	Ave.	178	1.2	H	-6.44	43.77	54	-10.23
2390	64.51	PK	218	1.7	V	-6.44	58.07	74	-15.93
2390	49.62	Ave.	218	1.7	V	-6.44	43.18	54	-10.82
4824	40.26	PK	321	1.2	H	2.87	43.13	74	-30.87
4824	40.19	PK	293	1.7	V	2.87	43.06	74	-30.94
802.11N20, Middle Channel									
4884	40.45	PK	99	1.4	H	3.04	43.49	74	-30.51
4884	40.1	PK	88	1.7	V	3.04	43.14	74	-30.86
802.11N20, High Channel									
2483.5	74.83	PK	318	1.4	H	-5.96	68.87	74	-5.13
2483.5	51.52	Ave.	318	1.4	H	-5.96	45.56	54	-8.44
2483.5	73.17	PK	65	1.9	V	-5.96	67.21	74	-6.79
2483.5	51.33	Ave.	65	1.9	V	-5.96	45.37	54	-8.63
2500	63.51	PK	236	1.8	H	-5.88	57.63	74	-16.37
2500	48.6	Ave.	236	1.8	H	-5.88	42.72	54	-11.28
2500	62.67	PK	175	1.8	V	-5.88	56.79	74	-17.21
2500	47.51	Ave.	175	1.8	V	-5.88	41.63	54	-12.37
4944	40.66	PK	289	1.7	H	3.23	43.89	74	-30.11
4944	38.95	PK	11	1.1	V	3.23	42.18	74	-31.82

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Substituted Factor (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
	Reading (dBm)	PK/Ave		Height (m)	Polar (H/V)				
802.11N40, Low Channel									
2310	64.02	PK	152	1.0	H	-6.84	57.18	74	-16.82
2310	48.45	Ave.	152	1.0	H	-6.84	41.61	54	-12.39
2310	63.42	PK	166	1.4	V	-6.84	56.58	74	-17.42
2310	46.99	Ave.	166	1.4	V	-6.84	40.15	54	-13.85
2390	66.92	PK	152	2.0	H	-6.44	60.48	74	-13.52
2390	50.56	Ave.	152	2.0	H	-6.44	44.12	54	-9.88
2390	66.22	PK	205	1.5	V	-6.44	59.78	74	-14.22
2390	50.31	Ave.	205	1.5	V	-6.44	43.87	54	-10.13
4844	40.53	PK	54	2.1	H	2.92	43.45	74	-30.55
4844	39.4	PK	39	2.2	V	2.92	42.32	74	-31.68
802.11N40, Middle Channel									
4884	41.38	PK	219	2.2	H	3.04	44.42	74	-29.58
4884	40.27	PK	280	1.6	V	3.04	43.31	74	-30.69
802.11N40, High Channel									
2483.5	66.41	PK	302	1.3	H	-5.96	60.45	74	-13.55
2483.5	50.85	Ave.	302	1.3	H	-5.96	44.89	54	-9.11
2483.5	65.73	PK	87	1.4	V	-5.96	59.77	74	-14.23
2483.5	50.1	Ave.	87	1.4	V	-5.96	44.14	54	-9.86
2500	60.52	PK	117	2.1	H	-5.88	54.64	74	-19.36
2500	44.42	Ave.	117	2.1	H	-5.88	38.54	54	-15.46
2500	59.77	PK	5	1.1	V	-5.88	53.89	74	-20.11
4924	42.16	PK	236	1.7	H	3.17	45.33	74	-28.67
4924	42.98	PK	134	1.1	V	3.17	46.15	74	-27.85

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading


Margin = Corrected. Amplitude - Limit

The other spurious emission which is 20dB to the limit was not recorded.


The test result of peak was less than the limit of average, so just peak values were recorded.

1-18 GHz:

Pre-scan for Peak
802.11B Middle Channel
Horizontal




Vertical




18 -25GHz:

Pre-scan for Peak
802.11B Middle Channel
Horizontal



Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Lya Liu from 2021-07-28 to 2021-11-19.


Test Result: Pass.

Please refer to the following table and plots.

EUT operation mode: Transmitting


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode			
Low	2412	10.014	≥ 500
Middle	2442	9.609	≥ 500
High	2472	9.609	≥ 500
802.11g mode			
Low	2412	16.382	≥ 500
Middle	2442	16.324	≥ 500
High	2472	16.382	≥ 500
802.11n-HT20 mode			
Low	2412	17.656	≥ 500
Middle	2442	17.598	≥ 500
High	2472	17.308	≥ 500
802.11n-HT40 mode			
Low	2422	35.510	≥ 500
Middle	2442	35.890	≥ 500
High	2462	35.920	≥ 500
BLE mode			
Low	2402	0.706	≥ 500
Middle	2440	0.712	≥ 500
High	2480	0.721	≥ 500

6dB Bandwidth, 802.11b Low Channel




Date: 29.JUL.2021 11:35:18

6dB Bandwidth, 802.11b Middle Channel




Date: 29.JUL.2021 11:28:28


6dB Bandwidth, 802.11b High Channel



6dB Bandwidth, 802.11g Low Channel




6dB Bandwidth, 802.11g Middle Channel



Date: 29.JUL.2021 13:12:38

6dB Bandwidth, 802.11g High Channel



Date: 29.JUL.2021 13:14:13

Spectrum

Ref Level 30.00 dBm Offset 10.50 dB RBW 100 kHz
 Att 30 dB SWT 94.8 μ s VBW 300 kHz Mode Auto FFT

1Pk Max

D1[1] -2.10 dBm
 17.6560 MHz
 -14.86 dBm
 2.4032010 GHz

D1 -9.350 dBm
 D2 -15.350 dBm

M1

CF 2.412 GHz 691 pts Span 40.0 MHz

Date: 29.JUL.2021 13:17:11

Spectrum

Ref Level 30.00 dBm Offset 10.50 dB RBW 100 kHz
 Att 30 dB SWT 56.9 μ s VBW 300 kHz Mode Auto FFT

1Pk Max

D1[1] 0.13 dB
 M1[1] 17.5980 MHz
 -14.12 dBm
 2.4332010 GHz


D1 -8.370 dBm
 D2 -14.370 dBm

CF 2.442 GHz 691 pts Span 40.0 MHz

19.11.2021


Date: 19.NOV.2021 14:11:14

6dB Bandwidth, 802.11n-HT20 High Channel




Date: 19.NOV.2021 14:20:06

6dB Bandwidth, 802.11n-HT40 Low Channel




Date: 29.JUL.2021 13:26:16

6dB Bandwidth, 802.11n-HT40 Middle Channel




Date: 29.JUL.2021 13:29:22

6dB Bandwidth, 802.11n-HT40 High Channel




Date: 29.JUL.2021 13:34:25

6dB Bandwidth, BLE Low Channel




Date: 28.JUL.2021 17:01:42

6dB Bandwidth, BLE Middle Channel



Date: 28.JUL.2021 17:00:03

6dB Bandwidth, BLE High Channel



Date: 28.JUL.2021 16:55:58


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by LYA Liu on 2021-07-28 and 2021-07-29.

EUT operation mode: Transmitting

Wi-Fi mode

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)
802.11b mode				
Low	2412	9.75	7.13	30
Middle	2442	9.72	7.08	30
High	2472	9.98	7.45	30
802.11g mode				
Low	2412	10.57	7.23	30
Middle	2442	10.62	7.22	30
High	2472	10.60	7.30	30
802.11n HT20 mode				
Low	2412	10.73	7.37	30
Middle	2442	10.61	7.24	30
High	2472	10.43	7.30	30
802.11n HT40 mode				
Low	2422	10.92	7.48	30
Middle	2442	10.81	7.48	30
High	2462	10.87	7.61	30

BLE mode

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)
BLE 1M			
Low	2402	-0.57	30
Middle	2440	-0.44	30
High	2480	-0.87	30


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by LYA Liu on 2021-07-28 and 2021-07-29.

EUT operation mode: Transmitting

Test Result: Compliant


Please refer to the following plots.

802.11b: Band Edge, Left Side




Date: 29.JUL.2021 14:16:30

802.11b: Band Edge, Right Side




Date: 29.JUL.2021 14:25:49

802.11g: Band Edge, Left Side




Date: 29.JUL.2021 14:18:49

802.11g: Band Edge, Right Side




Date: 29.JUL.2021 14:24:04

802.11n-HT20: Band Edge, Left Side




Date: 29.JUL.2021 14:19:46

802.11n-HT20: Band Edge, Right Side




Date: 29.JUL.2021 14:22:27

802.11n-HT40: Band Edge, Left Side




Date: 29.JUL.2021 14:31:30


802.11n-HT40: Band Edge, Right Side



Date: 29.JUL.2021 14:34:51

BLE: Band Edge, Left Side

Date: 28.JUL.2021 17:03:43

BLE: Band Edge, Right Side

Date: 28.JUL.2021 17:05:05


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Lya Liu on 2021-07-28 and 2021-07-29.


EUT operation mode: Transmitting

Test Result: Pass


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-1.81	≤ 8
Middle	2442	-1.99	≤ 8
High	2472	-2.01	≤ 8
802.11g mode			
Low	2412	-21.50	≤ 8
Middle	2442	-22.38	≤ 8
High	2472	-22.00	≤ 8
802.11n-HT20 mode			
Low	2412	-22.83	≤ 8
Middle	2442	-22.20	≤ 8
High	2472	-21.95	≤ 8
802.11n-HT40 mode			
Low	2422	-20.76	≤ 8
Middle	2442	-23.63	≤ 8
High	2462	-24.29	≤ 8
BLE mode			
Low	2402	-16.07	≤ 8
Middle	2440	-15.83	≤ 8
High	2480	-16.33	≤ 8

Power Spectral Density, 802.11b Low Channel


Date: 29.JUL.2021 15:47:28

Power Spectral Density, 802.11b Middle Channel


Date: 29.JUL.2021 15:49:34

Power Spectral Density, 802.11b High Channel


Date: 29.JUL.2021 15:46:21

Power Spectral Density, 802.11g Low Channel

Date: 29.JUL.2021 15:38:38


Power Spectral Density, 802.11g Middle Channel

Date: 29.JUL.2021 15:39:31

Power Spectral Density, 802.11g High Channel


Date: 29.JUL.2021 15:40:51

Power Spectral Density, 802.11n-HT20 Low Channel




Date: 29.JUL.2021 15:32:58


Power Spectral Density, 802.11n-HT20 Middle Channel





Date: 29.JUL.2021 15:34:44

Power Spectral Density, 802.11n-HT20 High Channel


Date: 29.JUL.2021 15:35:49

Power Spectral Density, 802.11n-HT40 Low Channel

Date: 29.JUL.2021 15:31:15


Power Spectral Density, 802.11n-HT40 Middle Channel**Power Spectral Density, 802.11n-HT40 High Channel**

Power Spectral Density, BLE Low Channel




Date: 28.JUL.2021 17:19:45

Power Spectral Density, BLE Middle Channel



Date: 28.JUL.2021 17:19:11

Power Spectral Density, BLE High Channel



Date: 28.JUL.2021 17:20:18

***** END OF REPORT *****