

# Standalone SAR test exclusion considerations

July 27, 2016

- Device category =  Portable device  Mobile device
- Transmitting mode =  Single Transmitting  Simultaneous Transmitting
- Max. transmitting frequency = **2480** MHz
- Min. test separation distance = **200** mm
- Max. Antenna Gain = **1.99** dBi
- Max. power with turn-up tolerance = **-1.00** dBm = **0.8** mW ( Typical Power = **Max. -1.00** dBm )

Note.

## KDB 447498 D01 clause 4.3.1 Step 2-2) SAR test exclusion thresholds for 1500MHz to 6GHz at test separation distances > 50 mm

[ Threshold at 50 mm + ( test separation distance - 50 mm ) X 10 ] mW

$$= [ 0.01 + ( 200\text{mm} - 50\text{mm} \times 10 ) ] = 1500$$

Note. The calculation result was rounded to one decimal place for comparison.

→ *SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.*

## Maximum Permissible Exposure(MPE) evaluation for mobile device

$$S = P G / ( 4 R^2 \pi ), \text{ mW/cm}^2$$

$$= 0.000252 \text{ mW/cm}^2$$

S = Maximum power density  
P = Maximum power with turn-up tolerance

G = Numeric power gain of the antenna  
R = Distance from transmitting antenna

Conclusion: **The exposure condition of this device is compliant with FCC rules.**

The limit for maximum permissible exposure = **1.000000 mW/cm<sup>2</sup>**