

FCC Part 15B TEST REPORT

Report No: STS1606137E01

Issued for

X Wireless, LLC

PO Box 8667, Gaithersburg, MD 20898, USA

L A B

Product Name:	WCDMA/GSM MOBILE PHONE		
Brand Name:	VORTEX		
Model Name:	MATRIX		
Series Model:	N/A		
FCC ID:	2AIVG-MATRIX		
Test Standard:	FCC Part 15B		

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.





TEST RESULT CERTIFICATION

Applicant's name	· X Wireless	TTC:

Address PO Box 8667, Gaithersburg, MD 20898, USA

Manufacture's Name X Wireless, LLC

Address PO Box 8667, Gaithersburg, MD 20898, USA

Product description

Product name WCDMA/GSM MOBILE PHONE

Brand name VORTEX

Model and/or type reference...: MATRIX

Standards FCC Part 15B

Test procedure...... ANSI C63.4-2014

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test

Date of performance of tests 17 June. 2016~07 July. 2016

Date of Issue 08 July. 2016

Test Result......Pass

Testing Engineer :

(Tony Liu)

Technical Manager

Authorized Signatory:

(Vita Li)

.

(Bovey Yang)







Table of Contents

1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACTORY	5
1.2 MEASUREMENT UNCERTAINTY	5
2. GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	7
2.4 DESCRIPTION OF SUPPORT UNITS	8
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	9
3. EMC EMISSION TEST	10
3.1 CONDUCTED EMISSION MEASUREMENT	10
3.2 RADIATED EMISSION MEASUREMENT	14
4. PHOTOS OF TEST SETUP	20



Page 4 of 21 Report No.: STS1606137E01

Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	08 July. 2016	STS1606137E01	ALL	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

	EMISSION		
Standard	Item	Result	Remarks
FCC 47 CFR Part 15 Subpart B	Conducted Emission	PASS	Meet Class B limit
(10-1-05 Edition)	Radiated Emission	PASS	Meet Class B limit

NOTE:

(1) " N/A" denotes test is not applicable in this Test Report

1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add.: 1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,

Fuyong Street, Bao'an District, Shenzhen, Guangdong, China

CNAS Registration No.: L7649;

FCC Registration No.: 842334; IC Registration No.: 12108A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	±2.88dB
2	Conducted Emission (150KHz-30MHz)	±2.67dB
3	RF power,conducted	±0.70dB
4	Spurious emissions,conducted	±1.19dB
5	All emissions,radiated(<30M) (9KHz-30MHz)	±2.45dB
6	All emissions,radiated(<1G) 30MHz-200MHz	±2.83dB
7	All emissions,radiated(<1G) 200MHz-1000MHz	±2.94dB
8	All emissions,radiated(>1G)	±3.03dB
9	Temperature	±0.5°C
10	Humidity	±2%



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	WCDMA/GSM MOBILE PHONE	
Trade Name	VORTEX	
Model Name	MATRIX	
Series Model	N/A	
Model Difference	N/A	
MCU Operating frequency	1.2GHz	
Adapter	Input: AC 100-240V, 200mA, 50/60 Hz Output: DC 5V, 700mA	
Battery	Rated Voltage: 3.7V Capacity :1300mAh	
Hardware version number	5110DW_MMI_V00	
Software version number	LEAGOO_OS_1.1_Lite	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	USB port communication with PC


For Conducted Test			
Final Test Mode Description			
Mode 1 USB port communication with PC			

For Radiated Test			
Final Test Mode Description			
Mode 1 USB port communication with PC			

NOTE:

- 1. Due to the different configuration and test, in this list only some worse mode. The worst test data of the worse modeis reported by this report.
- 2. We have be tested for all avaiable U.S. voltage and frequencies(For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED





2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-1	WCDMA/GSM MOBILE PHONE	VORTEX	MATRIX	N/A	EUT
E-2	PC	4CV428DQXR	500-320cx	4CV428DQYN	N/A
E-3	Keyboard	HP	PR1101U	DKUSB1B06Q42209FBK800	N/A
E-4	Mouse	MOTOSPEED	F66	697738-001	N/A
E-5	Printer	HP	HP1020	CNBB102765	N/A
C-6	AC (PC Adapter)	LITEON	PA-1650-86	3X06399004	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable (FTP)	NO	90cm	N/A
C-2	USB Cable (FTP)	NO	100cm	N/A
C-3	USB Cable (FTP)	NO	100cm	N/A
C-4	USB Cable (FTP)	NO	110cm	N/A
C-5	AC (Printer Cable) (FTP)	NO	100cm	N/A
C-6	AC (PC Cable) (FTP)	NO	120cm	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>"Length_"</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".
- (4) PC is the FCC DOC is approved.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	101427	2015.10.25	2016.10.24
Loop Antenna	Daze	ZN30900N	SEL0097	2015.10.27	2016.10.26
Bilog Antenna	TESEQ	CBL6111D	34678	2015.11.25	2016.11.24
Horn Antenna	Schwarzbeck	BBHA 9120D(1201)	9120D-1343	2016.03.06	2017.03.05
PreAmplifier	Agilent	8449B	60538	2015.10.25	2016.10.24
Temperature & Humitidy	Mieo	HH660	N/A	2015.10.28	2016.10.27
Unversal radio communication tester	R&S	CMU200	111764	2015.10.25	2016.10.24
Spectrum Analyzer	Agilent	E4407B	MY50140340	2015.10.25	2016.10.24
Low frequency cable	EM	R01	N/A	N/A	N/A
High frequency cable	SCHWARZBE CK	AK9515H	SN-96286/9628 7	N/A	N/A

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESPI	102086	2015.11.20	2016.11.19
LISN	R&S	ENV216	101242	2015.10.25	2016.10.24
LISN	EMCO	3810/2NM	000-23625	2015.10.25	2016.10.24
Conduction Cable	EM	C01	N/A	N/A	N/A



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits

	Conducted Emission Limits (dBuV)					
FREQUENCY (MHz)	Class A Class B			ss B		
	Quasi-peak	Average	Quasi-peak	Average		
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *		
0.50 -5.0	73.00	60.00	56.00	46.00		
5.0 -30.0	73.00	60.00	60.00	50.00		

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting		
Attenuation	10 dB		
Start Frequency	0.15 MHz		
Stop Frequency	30 MHz		
IF Bandwidth	9 kHz		





3.1.2 TEST PROCEDURE


The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support

- a. equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
 - I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the
- cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




3.1.6 TEST RESULTS

Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	L
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1674	39.63	9.23	48.86	65.09	-16.23	QP
2	0.1674	23.46	9.23	32.69	55.09	-22.40	AVG
3	0.2258	32.30	9.20	41.50	62.60	-21.10	QP
4	0.2258	20.90	9.20	30.10	52.60	-22.50	AVG
5	0.3927	32.85	9.42	42.27	58.01	-15.74	QP
6	0.3927	21.39	9.42	30.81	48.01	-17.20	AVG
7	9.7608	28.41	9.48	37.89	60.00	-22.11	QP
8	9.7608	19.73	9.48	29.21	50.00	-20.79	AVG
9	18.4297	33.02	9.80	42.82	60.00	-17.18	QP
10	18.4297	31.95	9.80	41.75	50.00	-8.25	AVG
11	22.5270	27.76	9.83	37.59	60.00	-22.41	QP
12	22.5270	26.73	9.83	36.56	50.00	-13.44	AVG

Remark:

- 1. All readings are Quasi-Peak and Average values.
- 2. Margin = Result (Result = Reading + Factor)-Limit 100.0 dBuV






Page 13 of 21 Report No.: STS1606137E01

Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	Ν
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1822	41.43	9.23	50.66	64.38	-13.72	QP
2	0.1822	25.76	9.23	34.99	54.38	-19.39	AVG
3	0.2496	34.83	9.18	44.01	61.77	-17.76	QP
4	0.2496	20.21	9.18	29.39	51.77	-22.38	AVG
5	3.9456	26.29	9.26	35.55	56.00	-20.45	QP
6	3.9456	17.01	9.26	26.27	46.00	-19.73	AVG
7	9.9910	32.98	9.40	42.38	60.00	-17.62	QP
8	9.9910	24.94	9.40	34.34	50.00	-15.66	AVG
9	18.4314	35.62	9.67	45.29	60.00	-14.71	QP
10	18.4314	34.82	9.67	44.49	50.00	-5.51	AVG
11	22.5280	31.69	9.83	41.52	60.00	-18.48	QP
12	22.5280	28.44	9.83	38.27	50.00	-11.73	AVG

Remark:

- 1. All readings are Quasi-Peak and Average values.
- 2. Margin = Result (Result = Reading + Factor)-Limit 100.0 dBuV





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 Radiated Emission Limits

In case the emission fall within the restricted band specified on 15.105(a)&109(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (d	BuV/m) (at 3M)	Class B (dBuV/m) (at 3M)		
FREQUENCT (IVITIZ)	PEAK AVERAGE		PEAK	AVERAGE	
Above 1000	80	60	74	54	

Note:

- (1) The limit for radiated test was performed according to FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper	
frequency of measurement used in the device	Range (MHz)
or on which the device operates or tunes	ixarige (ivii iz)
(MHz)	
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz,
	whichever is lower



Page 15 of 21 Report No.: STS1606137E01

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	5th harmonic (Peak/AV)
DD ///D (omission in rectricted band)	30MHz to 1000MHz: 100 KHz / 300 KHz
RB / VB (emission in restricted band)	Above 1000MHz: 1 MHz / 3 MHz

Receiver Parameter	Setting			
Attenuation	Auto			
Start Stan Fraguency	30MHz to 1000MHz: 100 KHz / 300 KHz			
Start ~ Stop Frequency	Above 1000MHz: 1 MHz / 3 MHz			

3.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter b. anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- the height of the antenna shall vary between 1m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector d. mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the e. EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


3.2.3 DEVIATION FROM TEST STANDARD

No deviation




3.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency 30MHz~1GHz



(B) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



3.2.6 TEST RESULTS


30MHz -1000MHz

Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	59.0251	57.27	-24.06	33.21	40.00	-6.79	QP
2	165.4866	55.24	-18.95	36.29	43.50	-7.21	QP
3	180.0165	55.77	-19.44	36.33	43.50	-7.17	QP
4	269.4284	54.47	-15.45	39.02	46.00	-6.98	QP
5	480.5276	47.55	-9.38	38.17	46.00	-7.83	QP
6	798.9796	38.48	-3.45	35.03	46.00	-10.97	QP

Remark:

1. Margin = Result (Result = Reading + Factor)—Limit






Page 18 of 21 Report No.: STS1606137E01

Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	Vertical
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	59.8588	57.33	-24.30	33.03	40.00	-6.97	QP
2	134.5592	52.90	-17.54	35.36	43.50	-8.14	QP
3	166.0680	56.27	-19.00	37.27	43.50	-6.23	QP
4	239.9873	56.66	-17.76	38.90	46.00	-7.10	QP
5	269.4284	54.47	-15.45	39.02	46.00	-6.98	QP
6	480.5276	47.81	-9.38	38.43	46.00	-7.57	QP

Remark:

1. Margin = Result (Result = Reading + Factor)-Limit







(1 GHz to 13GHz.)

Temperature:	26 ℃	Relative Humidity:	54%	
Pressure:	1010hPa	Phase:	Vertical/Horizontal	
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1	

Freq.	Ant. Pol	Peak	AV	Ant./CL	Actual Fs -		Peak	AV	Peak	AV
(MHz)	H/V	Reading	Reading	CF			Limit	Limit	margin	margin
		(dBuV)	(dBuV)	(dB)			(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)
					(dBuV/m)	(dBuV/m)				
1097.86	Н	57.56	41.28	5.15	62.71	46.43	74.00	54.00	-11.29	-7.57
2866.75	Н	52.96	38.29	9.45	62.41	47.74	74.00	54.00	-11.59	-6.26
N/A										
1069.85	V	52.34	37.55	5.15	57.49	42.70	74.00	54.00	-16.51	-11.30
2896.31	V	49.87	32.14	9.45	59.32	41.59	74.00	54.00	-14.68	-12.41
N/A		·	-							

Notes:


- 1. Measuring frequencies from 1 GHz to 13GHz.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode of the emission shown in Actual FS column.
- 3. The frequency that above 3GHz is mainly from the environment noise.




4. PHOTOS OF TEST SETUP

Radiated Measurement Photos

30MHz-1GHz



Above 1GHz





Conducted Measurement Photos



****END OF THE REPORT*