

RF Exposure evaluation

Report Reference No.....: CTA-01-160600303

FCC ID.....: 2AIXQDA323

Compiled by

(position+printed name+signature)... File administrators Kevin Liu

Supervised by

(position+printed name+signature)..: Project Engineer Kevin Liu

Approved by

kevim Lin kevim Lin Evic Wang RF Manager Eric Wang (position+printed name+signature)...:

Date of issue..... Jun. 28, 2016

Representative Laboratory Name: Shenzhen CTA Testing Technology Co., Ltd.

Room 105, 1st Floor, Nangang Business Building, Qianhai Road, Address.....:

Nanshan Street, Nanshan District, Shenzhen, China

Testing Laboratory Name: Dongguan Yaxu (AiT) Technology Limited

No. 22, JinQianLing Street 3, JiTiGang Village, Huang-Jiang Town, Address.....

DongGuan, Guangdong, 523757 China

Applicant's name..... Shenzhen Dejiang Innovation Technology., Co. Ltd

2108, B. Fenglinguoji Mansion, Longcheng Street, Longgang Address.....

Central, Longgang District, Shenzhen, china

Test specification:

47CFR §2.1093(d)/KDB447498 v06 Standard:

TRF Originator...... Shenzhen CTA Testing Technology Co., Ltd.

Master TRF.....: Dated 2014-12

Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Intelligent Vehicle-based Bluetooth Earphone

Trade Mark:

Manufacturer: Shenzhen Dejiang Innovation Technology., Co, Ltd

Model/Type reference..... **DA323**

Listed Models /

Operation Frequency...... From 2402MHz to 2480MHz

Exposure category...... General population/uncontrolled environment

EUT Type: **Production Unit**

Device Type...... Portable Device

Rating: DC 3.70V

Result..... PASS

TEST REPORT

Test Report No. :	CTA-01-160600303	Jun. 28, 2016
	O1A-01-100000303	Date of issue

Equipment under Test : Intelligent Vehicle-based Bluetooth Earphone

Model /Type : DA323

Listed Models : /

Applicant : Shenzhen Dejiang Innovation Technology., Co, Ltd

Address : 2108, B, Fenglinguoji Mansion, Longcheng Street,

Longgang Central, Longgang District, Shenzhen, china

Report No.: CTA-01-160600303

Manufacturer : Shenzhen Dejiang Innovation Technology., Co, Ltd

Address : 2108, B, Fenglinguoji Mansion, Longcheng Street,

Longgang Central, Longgang District, Shenzhen, china

Test Result: PASS

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revison History

Revision	Issue Date	Revisions	Revised By
V1.0	2016-06-28	Initial Issue	Eric Wang

Report No.: CTA-01-160600303

Contents

<u>1.</u>	SUMMARY	<u> </u>
1.1.	EUT configuration	5
1.1.	EO1 comiguration	5
<u>2.</u>	TEST ENVIRONMENT	6
2.1.	Address of the test laboratory	6
2.2.	Test Facility	6
2.3.	Environmental conditions	6
2.4.	Statement of the measurement uncertainty	6
<u>3 .</u>	METHOD OF MEASUREMENT	7
3.1.	Applicable Standard	7
3.2.	Requirement	7
3.3.	Conducted Power Results	7
<u>4 .</u>	EVALUATION RESULT	8
5.	CONCLUSION	8

1. SUMMARY

1.1. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer
- $\ensuremath{\bigcirc}$ supplied by the lab

O Power Cable	Length (m):	1
	Shield :	1
	Detachable :	1

V1.0 Page 6 of 8 Report No.: CTA-01-160600303

2. TEST ENVIRONMENT

2.1. Address of the test laboratory

Asia Institute Technology (DongGuan) Limited

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

2.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS- Registration No: L6177

Dongguan Yaxu (AiT) technology Limited is accredited to ISO/IEC 17025:2005 general Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the competence of testing and calibration laboratories) on Apr. 18, 2013

FCC- Registration No: 248337

The 3m Semi-Anechoic Chamber, 3m/10m Open Area Test Site and Shielding Room of Dongguan Yaxu (AiT) Technology Limited have been registered by Federal Communications Commission (FCC) on Aug.29, 2014.

Industry Canada(IC)-Registration No: IC6819A

The 3m Semi-Anechoic Chamber and 3m/10m Open Area Test Site of Dongguan Yaxu (AiT) Technology Limited have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing on Oct. 01, 2014.

VCCI- Registration No: 2705

The 3m/10m Open Area Test Site, Shielding Room and 3m Chamber of Dngguan Yaxu (AiT) technology Limited have been registered by Voluntary Control Council for Interference on Nov. 21, 2012. The Telecommunication Ports Conducted Disturbance Measurement of Asia Institute Technology (Dongguan) Limited have been registered by Voluntary Control Council for Interference on May. 13, 2013.

2.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01" Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Dongguan Yaxu (AiT) Technology Limited quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Dongguan Yaxu (AiT) Technology Limited is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

⁽¹⁾ This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

V1.0 Page 7 of 8 Report No.: CTA-01-160600303

3. Method of measurement

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1093 RF exposure requirement

KDB447498 v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2. Requirement

According to KDB447498 D01 General RF Exposure Guidance v05r01Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.22 The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.23 "

[(max. power of channel, including tune-up tolerance, mW)/ (min. test separation distance, mm)] \cdot [\sqrt f (GHz)] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR, where:

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

3.3. Conducted Power Results

BT4.0

Mode	Channel	Frequency (MHz)	Conducted PeakOutput Power (dBm)	Conducted Average Output Power (dBm)
	00	2402	-6.565	-8.076
GFSK	39	2440	-6.461	-7.965
	78	2480	-5.928	-7.431

BT3.0

Mode	Channel	Frequency (MHz)	Conducted PeakOutput Power (dBm)	Conducted Average Output Power (dBm)
	00	2402	0.751	-0.756
GFSK	39	2440	1.414	-0.091
	78	2480	2.019	0.516
	00	2402	0.573	-0.937
π/4DQPSK	39	2440	0.899	-0.605
	78	2480	1.465	-0.040
ODDCK	00	2402	0.733	-0.759
8DPSK	39	2440	1.078	-0.089

V1.0 Page 8 of 8 Report No.: CTA-01-160600303

78	2480	1.672	-0.715

Manufacturing tolerance

Bluetooth 4.0

BLE-GFSK (Average)						
Channel Channel 00 Channel 19 Channel 39						
Target (dBm)	-8.0	-8.0	-8.0			
Tolerance ±(dB)	1.0	1.0	1.0			

Bluetooth 3.0

GFSK (Average)						
Channel	Channel 00	Channel 19	Channel 39			
Target (dBm)	0.0	0.0	0.0			
Tolerance ±(dB)	1.0	1.0	1.0			
	π/4DQPSk	(Average)				
Channel	Channel 00	Channel 19	Channel 39			
Target (dBm)	0.0	0.0	0.0			
Tolerance ±(dB)	1.0	1.0	1.0			
	8DPSK (Average)					
Channel	Channel 00	Channel 19	Channel 39			
Target (dBm)	0.0	0.0	0.0			
Tolerance ±(dB)	1.0	1.0	1.0			

4. Evaluation Result

Evaluation Results

Band/Mode	f (GHz)	Antenna Distance (mm)		ut power g tune-up ance) mW	SAR Test Exclusion Threshold	SAR Test Exclusion
BT3.0	2450	5	1.00	1.26	0.4<3.0	Yes

Band/Mode	f (GHz)	Antenna Distance	RF output power (including tune-up tolerance)		SAR Test Exclusion	SAR Test Exclusion
		(mm)	dBm	mW	Threshold	
BT 4.0	2450	5	-7.00	0.20	0.1<3.0	Yes

5. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

End	l of	Repo	ort	
LIIU	ı Oı	izebr	JI L	