

# RADIO TEST REPORT

**No. 1718488STO-002, Ed. 1**

## RF Performance

### EQUIPMENT UNDER TEST

Equipment: Thermostat  
Type/Model: ViCare Radiator Thermostat Valve  
Manufacturer: Viessmann Werke GmbH & Co.  
Tested by request of: Danfoss A/S

### SUMMARY

Referring to the emission limits, and the operating mode during the tests specified in this report, the equipment complies with the requirements according to the following standards:

47 CFR Part 15 (2016): Subpart C: Intentional radiators. Section 15.247

47 CFR Part 15 (2016): Subpart B: Unintentional radiators

RSS-GEN Issue 4 (2014): General requirements of compliance of radio apparatus (2014)

RSS-247 Issue 2 (2017): Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

For details, see clause 2 – 4.

Date of issue: 2018-03-19

Tested by: *Per Larsson*  
Per Larsson

Approved by:  
*Matti Virkki*  
Matti Virkki

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**Revision History**

<b>Edition</b>	<b>Date</b>	<b>Description</b>	<b>Changes</b>
1	2018-03-19	First release	

**CONTENTS**

	<b>Page</b>
1 Client Information .....	5
2 Equipment under test (EUT).....	5
2.1 Identification of the EUT.....	5
2.2 Additional information about the EUT .....	6
2.3 Peripheral equipment.....	6
2.4 Test signals and operation modes .....	6
3 Test Specifications .....	7
3.1 Standards .....	7
3.2 Additions, deviations and exclusions from standards and accreditation .....	7
3.3 Test site.....	7
4 Test Summary .....	8
5 radiated Band Edge .....	9
5.1 Test set-up and test procedure.....	9
5.2 Test conditions .....	9
5.3 Requirement.....	10
5.4 Test results.....	11
6 Radiated rf Emission in the frequency-range 30 MHz to 26.5 GHz .....	12
6.1 Test set-up and test procedure.....	12
6.2 Test conditions .....	12
6.3 Requirements.....	12
6.4 Test results 30 MHz – 1000 MHz, TX .....	13
6.5 Test results 30 MHz – 1000 MHz, RX.....	16
6.6 Test results 1 GHz – 26.5 GHz, TX .....	17
6.7 Test results 1 GHz – 18 GHz, RX .....	23
7 Conducted band edge measurement.....	24
7.1 Test set-up and test procedure.....	24
7.2 Test conditions .....	24
7.3 Requirement.....	24
7.4 Test results.....	25
8 Maximum conducted output power .....	27
8.1 Test set-up and test procedure.....	27
8.2 Test conditions .....	27
8.3 Requirements.....	27
8.4 Test results.....	28
9 Occupied 6 dB bandwidth .....	29
9.1 Test set-up and test procedure.....	29
9.2 Test conditions .....	29
9.3 Requirements.....	29
9.4 Test results.....	30
10 99 % bandwidth .....	33
10.1 Test set-up and test procedure.....	33
10.2 Test conditions .....	33
10.3 Test results.....	33
11 Peak power spectral density .....	36
11.1 Test set-up and test procedure.....	36
11.2 Test conditions .....	36
11.3 Requirements.....	36
11.4 Test results.....	37
12 Test equipment.....	40

13 Measurement uncertainty.....	40
14 Test set up and EUT photos.....	41

## 1 CLIENT INFORMATION

The EUT has been tested by request of

Company Danfoss A/S

Nordborgvej 81  
DK-6430 Nordborg  
DENMARK  
Hans Schou Christensen  
Phone +45 74882114

## 2 EQUIPMENT UNDER TEST (EUT)

## 2.1 Identification of the EUT

Equipment:	Thermostat
Type/Model:	ViCare Radiator Thermostat Valve
Brand name:	Viessmann Werke GmbH & Co.
Serial number:	No visible
Manufacturer:	Viessmann Werke GmbH & Co .

Transmitter frequency range: 2400–2480 MHz

Receiver frequency range: 2405 – 2480 MHz

Frequency agile or hopping:	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No
Antenna:	<input checked="" type="checkbox"/> Internal antenna	<input type="checkbox"/> External antenna
Antenna connector:	<input checked="" type="checkbox"/> None, internal antenna	<input type="checkbox"/> Yes, type xxx
Antenna gain:	0 dBi	
Rating RF output power:	11 dBm	
Type of modulation:	DSSS (Zigbee)	
Temperature range:	<input type="checkbox"/> Category I (General): -20°C to +55°C <input type="checkbox"/> Category II (Portable equipment): -10°C to +55°C <input type="checkbox"/> Category III (Equipment for normal indoor use): +5°C to +35°C <input checked="" type="checkbox"/> Other: 0°C to +40°C	
Transmitter stand by mode supported:	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No

## 2.2 Additional information about the EUT

The EUT consists of the following units:

Unit	Type	Serial number
Thermostat	ViCare Radiator Thermostat Valve	No visible

## 2.3 Peripheral equipment

Peripheral equipment is equipment needed for correct operation of the EUT, but not included as part of the testing and evaluation of the EUT.

Equipment	Type / Model	Manufacturer	Serial no.
Laptop	HP Elite Book 850	HP	HP5CG54451CL
USB to serial programming cable	Not known	Not known	Not known
USB Zigbee dongle	Not known	Not known	Not known

## 2.4 Test signals and operation modes

Continuous signal

### 3 TEST SPECIFICATIONS

#### 3.1 Standards

Requirements:

47 CFR Part 15 (2016): Subpart C: Intentional radiators. Section 15.247

47 CFR Part 15 (2016): Subpart B: Unintentional radiators

RSS-GEN Issue 4 (2014): General requirements of compliance of radio apparatus (2014).

RSS-247 Issue 2 (2017): Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

Test methods:

ANSI C63.10-2013: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

#### 3.2 Additions, deviations and exclusions from standards and accreditation

No additions, deviations or exclusions have been made from standards and accreditation.

#### 3.3 Test site

Measurements were performed at:

Intertek Semko AB.  
Torshamnsgatan 43,  
P.O. Box 1103  
SE-164 22 Kista

Intertek Semko AB is a FCC listed test site with site registration number 90913  
Intertek Semko AB is a FCC accredited conformity assessment body with designation number SE0002  
Intertek Semko AB is an Industry Canada listed test facility with IC assigned code 2042G

Measurement chambers

Measurement Chamber	Type of chamber	IC Site filing #
5 m CHAMBER	Semi-anechoic 5 m	2042G-3

#### 4 TEST SUMMARY

The results in this report apply only to sample tested:

Requirement	Description	Result
<b>FCC §15.203 RSS-GEN 8.3</b>	<b>Antenna requirement</b> The EUT has integrated non detachable antenna which can't be removed without breaking the EUT.	<b>PASS</b>
<b>FCC §15.207, 15.107 RSS-GEN 8.8 table 3</b>	<b>Conducted continuous emission in the frequency range 150 kHz to 30 MHz, AC Power input port</b> Battery operated equipment.	<b>NA</b>
<b>FCC §15.247 (b)(4) RSS-247 5.4(4), 5.4(5)</b>	<b>Antenna gain</b> Antenna gain is less than 6 dBi.	<b>PASS</b>
<b>FCC §15.247 (d), 15.209(a) RSS-GEN 8.9 RSS-247 5.5</b>	<b>Radiated emission of electromagnetic fields in the frequency range 30 – 1000 MHz</b> The EUT complies with the limits. The margin to the limit was more than 20 dB See clause 6.4 – 6.5.	<b>PASS</b>
<b>FCC §15.247(d), 15.209(a) RSS-GEN 8.9 RSS-247 5.5</b>	<b>Radiated emission of electromagnetic fields in the frequency range above 1 GHz</b> The EUT complies with the limits. The margin to the limit was at least 1.3 dB at 4811.0 MHz. See clause 6.6 – 6.7. The measured result is below the upper limit, but by a margin less than half of the uncertainty interval. It is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance is more probable than non-compliance.	<b>PASS</b>
<b>FCC §15.247(a)(2) RSS-GEN 6.6 RSS-247 5.2(1)</b>	<b>Occupied bandwidth</b> The EUT complies with the limits. The margin to the limit was more than 1 MHz See clause 8.4.	<b>PASS</b>
<b>FCC §15.247(b) RSS-247 5.4(4)</b>	<b>Conducted output power</b> The EUT complies with the limits. The margin to the limit was more than 10 dB. See clause 8.4.	<b>PASS</b>
<b>FCC §15.247(e) RSS-247 5.2(2)</b>	<b>Peak power spectral density</b> The EUT complies with the limits. The margin to the limit was at least 9.9 dB at 2445 MHz. See clause 10.4.	<b>PASS</b>
<b>FCC §15.247(e) RSS-247 5.5</b>	<b>Radiated band edge</b> The EUT complies with the limits. The margin to the limit was at least 1.4 dB at 2484 MHz. See clause 5.4.	<b>PASS</b>
<b>FCC §15.247(e) RSS-247 5.5</b>	<b>Band edge</b> The EUT complies with the limits. The margin to the limit was at least 18.8 dB at 2402 MHz. See clause 7.4.	<b>PASS</b>

## 5 RADIATED BAND EDGE

<b>Date of test:</b>	2017-12-05	<b>Test location:</b>	5mSAC
<b>EUT Serial:</b>	V60	<b>Ambient temp:</b>	21 °C
<b>Tested by:</b>	PLA	<b>Relative humidity:</b>	35 %
<b>Test result:</b>	Pass	<b>Margin:</b>	1.4 dB

### 5.1 Test set-up and test procedure.

The test method is in accordance with ANSI C63.10-2013.  
The EUT was set up in order to emit maximum disturbances.

The EUT was placed on an insulating support 1.5 m above the turntable which is part of the reference ground plane.

Overview sweeps were performed with the measurement receiver in max-hold mode and the peak and average detector was activated.

EUT was evaluated in three orthogonal orientations.

### 5.2 Test conditions

<b>Test set-up:</b>	<b>1 GHz – 26.5 GHz</b>		
Test receiver set-up:			
Preview test:	Peak,	RBW 1 MHz	VBW 3 MHz
Final test:	Peak,	RBW 1 MHz	VBW 3 MHz
	Average	Peak value + 20 x LOG (Duty cycle) / RBW 1	
MHz. VBW 3 MHz			
Measuring distance:	3 m		
Measuring angle:	0 – 359°		
Antenna			
Height above ground plane:	1 – 4 m		
Polarisation:	Vertical and Horizontal		
Type:	Horn		
Antenna tilt:	Activated		

### 5.3 Requirement

Outside the restricted bands:

Reference: CFR 47 §15.247(d), RSS-247 5.5,

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.


Within restricted bands:

Reference: CFR 47 §15.209, RSS-Gen section 8.9

Field strength of emissions must comply with limits shown in table below

Frequency range [MHz]	Field strength at 3 m (dB $\mu$ V/m)	Field strength at 10 m (dB $\mu$ V/m)	Detector (dB $\mu$ V/m)
30 – 88	40.0	29.5	Quasi Peak
88 – 216	43.5	33.0	Quasi Peak
216 – 960	46.0	35.5	Quasi Peak
960 – 1000	54.0	43.5	Quasi Peak
Above 1000	54.0 / 74.0	43.5 / 63.5	Average / Peak

## 5.4 Test results



### Upper band edge sweep

#### Field strength of band edge, high channel

Frequency [MHz]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Detector	EUT Orientation	Polarization H/V	Margin [dB]
2484.0	52.6	54.0	Average	Vertical	H	1.4*
2484.0	66.1	73.9	Peak	Vertical	H	7.8

\* The measured result is below the upper limit, but by a margin less than half of the uncertainty interval. It is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance is more probable than non-compliance.

## 6 RADIATED RF EMISSION IN THE FREQUENCY-RANGE 30 MHZ TO 26.5 GHZ

<b>Date of test:</b>	2017-12-05	<b>Test location:</b>	5mSAC
<b>EUT Serial:</b>	V60	<b>Ambient temp:</b>	21 °C
<b>Tested by:</b>	PLA	<b>Relative humidity:</b>	35 %
<b>Test result:</b>	Pass	<b>Margin:</b>	1.3 dB

### 6.1 Test set-up and test procedure.

The test method is in accordance with ANSI C63.10-2013.

The EUT was set up in order to emit maximum disturbances.

The EUT was placed on an insulating support 0.8 and 1.5 m above the turntable which is part of the reference ground plane.

Overview sweeps were performed with the measurement receiver in max-hold mode and the peak detector activated in the frequency-range 30 – 1000 MHz. Above 1 GHz additionally the average detector was activated.

Pre scan was made in three orthogonal EUT orientations.

Results from vertical orientation are presented below, which was found to give worst spurious emissions.

### 6.2 Test conditions

#### Test set-up:

#### 30 MHz to 1000 MHz

Test receiver set-up:

Preview test:	Peak,	RBW 120 kHz	VBW 1 MHz
Final test:	Quasi-Peak,	RBW 120 kHz	VBW 1 MHz
EUT height above ground plane:	0.8 m		
Measuring distance:	3 m		
Measuring angle:	0 – 359°		
Antenna			
Height above ground plane:	1 – 4 m		
Polarisation:	Vertical and Horizontal		
Type:	Bilog		

#### Test set-up:

#### 1 GHz – 26.5 GHz

Test receiver set-up:

Preview test:	Peak,	RBW 1 MHz	VBW 3 MHz
Final test:	Average,	RBW 1 MHz	VBW 3 MHz
	Peak,	RBW 1 MHz	VBW 3 MHz
	Average	Peak value + 20 x LOG (Duty cycle) / RBW 1	
MHz VBW 3 MHz			
EUT height above ground plane:	1.5 m		
Measuring distance:	3 m		
Measuring angle:	0 – 359°		
Antenna			
Height above ground plane:	1 – 4 m		
Polarisation:	Vertical and Horizontal		
Type:	Horn		
Antenna tilt:	Activated		

### 6.3 Requirements

Within restricted bands and receive mode:

Reference: CFR 47 §15.209, RSS-Gen section 8.9

Field strength of emissions must comply with limits shown in table below

Frequency range [MHz]	Field strength at 3 m (dB $\mu$ V/m)	Field strength at 10 m (dB $\mu$ V/m)	Detector (dB $\mu$ V/m)
30 – 88	40.0	29.5	Quasi Peak
88 – 216	43.5	33.0	Quasi Peak
216 – 960	46.0	35.5	Quasi Peak
960 – 1000	54.0	43.5	Quasi Peak
Above 1000	54.0 / 74.0	43.5 / 63.5	Average / Peak

The values for 10 m measuring distance are calculated by subtracting 10.5 dB from the 3 m limit.  
(i.e. an extrapolation factor of 20 dB/decade according to CFR 47 §15.31(f)(1))


Outside the restricted bands:

Reference: CFR 47 §15.247(d), RSS-247 5.5,

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.


#### 6.4 Test results 30 MHz – 1000 MHz, TX

Full Spectrum




Diagram, Peak overview sweep, 30 – 1000 MHz at 3 m distance. TX low channel

## Full Spectrum

**Diagram, Peak overview sweep, 30 – 1000 MHz at 3 m distance. TX mid channel**

## Full Spectrum




Diagram, Peak overview sweep, 30 – 1000 MHz at 3 m distance. TX mid channel

#### Measurement results, Quasi Peak

No emissions are found above noise floor or closer than 20 dB from limit.

Result [dB $\mu$ V/m] = Analyser reading [dB $\mu$ V] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB]

## 6.5 Test results 30 MHz – 1000 MHz, RX



Diagram, Peak overview sweep, 30 – 1000 MHz at 3 m distance. RX mid channel.


### Measurement results, Quasi Peak

No emissions are found above noise floor or closer than 20 dB from limit.

Result [dB $\mu$ V/m] = Analyser reading [dB $\mu$ V] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB]

## 6.6 Test results 1 GHz – 26.5 GHz, TX

Full Spectrum



Diagram, Peak overview sweep, 1– 18 GHz at 3 m distance. TX low channel.

### Measurement results, Peak, TX low channel


Frequency [MHz]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Polarization H/V	Margin [dB]
4811.0	60.7	73.9	V	13.2
7216.6	51.0	73.9	V	22.9
9618.0	55.7	73.9	V	18.2

### Measurement results, Average, TX low channel

Frequency [MHz]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Polarization H/V	Margin [dB]
4811.0	52.7	54.0	V	1.3*
7216.6	40.3	54.0	V	13.7
9618.0	46.5	54.0	V	7.6

Note\*: The measured result is below the upper limit, but by a margin less than half of the uncertainty interval. It is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance is more probable than non-compliance.

Full Spectrum




Diagram, Peak overview sweep, 1– 18 GHz at 3 m distance. TX mid channel.

Measurement results, Peak, TX middle channel

Frequency [MHz]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Polarization H/V	Margin [dB]
4881.2	56.3	73.9	V	17.6
7321.6	52.1	73.9	V	21.8
9757.7	55.2	73.9	V	18.8

Measurement results, Average, TX mid channel

Frequency [MHz]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Polarization H/V	Margin [dB]
4879.0	50.8	54.0	V	3.2
7321.6	41.9	54.0	V	12.1



Diagram, Peak overview sweep, 1– 18 GHz at 3 m distance. TX high channel.

Measurement results, Peak, TX high channel


Frequency [MHz]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Polarization H/V	Margin [dB]
4961.1	56.0	73.9	V	17.9
7441.7	55.8	73.9	V	18.1
9917.8	53.2	73.9	V	20.7

Measurement results, Average, TX high channel

Frequency [MHz]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Polarization H/V	Margin [dB]
4958.9	43.7	54.0	V	10.3
7438.5	47.2	54.0	V	6.8
9917.8	42.1	54.0	V	11.9

Result [dB $\mu$ V/m] = Analyser reading [dB $\mu$ V] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB]

Full Spectrum

**Diagram. Peak overview sweep. 18– 26.5 GHz at 3 m distance. TX low channel.**

## Full Spectrum





Diagram. Peak overview sweep. 18– 26.5 GHz at 3 m distance. TX mid channel.

## Full Spectrum



**Diagram. Peak overview sweep. 18– 26.5 GHz at 3 m distance. TX high channel.**

## 6.7 Test results 1 GHz – 18 GHz. RX




Diagram. Peak overview sweep. 1– 18 GHz at 3 m distance. RX mid channel.

No emissions are found above noise floor.

Result [dB $\mu$ V/m] = Analyser reading [dB $\mu$ V] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB]

## 7 CONDUCTED BAND EDGE MEASUREMENT

<b>Date of test:</b>	2018-01-15	<b>Test location:</b>	Wireless center
<b>EUT Serial:</b>	V56	<b>Ambient temp:</b>	21 °C
<b>Tested by:</b>	PLA	<b>Relative humidity:</b>	35 %
<b>Test result:</b>	Pass	<b>Margin:</b>	>10 dB

### 7.1 Test set-up and test procedure.

The test method is in accordance with ANSI C63.10-2013 section 6.10.4.

The EUT was connected to spectrum analyser via rf-cable and attenuator.

The EUT was set up in order to emit maximum disturbances.

### 7.2 Test conditions


Detector: Peak,  
RBW: 100 kHz  
VBW: 300 kHz  
Span: 20 MHz

### 7.3 Requirement


Reference: CFR 47 §15.247(d), RSS-247 5.5,

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

## 7.4 Test results



## Screenshot: Lower band edge sweep, low channel channel



Screenshot: Upper band edge sweep, high channel

## Test results

Band edge	Delta [dBc]	Limit [dBc]	Margin [dB]
Lower	46,7	30,0	16,7
Upper	46,1	30,0	16,1

## 8 MAXIMUM CONDUCTED OUTPUT POWER

<b>Date of test:</b>	2018-01-15	<b>Test location:</b>	Wireless center
<b>EUT Serial:</b>	V56	<b>Ambient temp:</b>	21 °C
<b>Tested by:</b>	PLA	<b>Relative humidity:</b>	35 %
<b>Test result:</b>	Pass	<b>Margin:</b>	>10 dB

### 8.1 Test set-up and test procedure.

The test method is in accordance with ANSI C63.10-2013 section 11.9.2.

The EUT was connected to spectrum analyser via rf-cable and attenuator.

### 8.2 Test conditions

Detector: Peak.  
RBW: >OBW  
VBW: 3 x RBW  
Span: >3 x OBW

The EUT was set up in order to emit maximum disturbances.

### 8.3 Requirements

Reference: CFR 47§15.247(b)(3). RSS-247 5.4

For DTSs employing digital modulation techniques operating in the bands 902 – 128 MHz. 2400 – 2483.5 MHz and 5725 – 5850 MHz. the maximum peak conducted output power shall not exceed 1W.

**8.4 Test results****Test result**

Channel [MHz]	Output power [dBm]
2405	11.2
2445	11
2480	10.8

## 9 OCCUPIED 6 DB BANDWIDTH

<b>Date of test:</b>	2018-01-15	<b>Test location:</b>	Wireless center
<b>EUT Serial:</b>	V56	<b>Ambient temp:</b>	21 °C
<b>Tested by:</b>	PLA	<b>Relative humidity:</b>	35 %
<b>Test result:</b>	Pass	<b>Margin:</b>	>1 MHz

### 9.1 Test set-up and test procedure.

The test method is in accordance with ANSI C63.10-2013 section 11.8.1.

The EUT was connected to spectrum analyser via rf-cable and attenuator.

### 9.2 Test conditions

Detector: Peak.  
RBW: 100 kHz  
VBW: 3 x RBW  
Span: >1.5 x OBW


The EUT was set up in order to emit maximum disturbances.

### 9.3 Requirements


Reference: CFR 47§15.247(a)(2). RSS-247 5.2(1)

The minimum 6 dB bandwidth shall be 500 kHz.


#### 9.4 Test results



Screenshot: Occupied 6 dB bandwidth Measurement. low channel



Screenshot: Occupied 6 dB bandwidth Measurement. middle channel



Screenshot: Occupied 6 dB bandwidth Measurement. high channel

**Test result**

Channel [MHz]	6 dB BW [MHz]
2405	1.98
2445	1.95
2480	1.98

## 10 99 % BANDWIDTH

<b>Date of test:</b>	2018-01-15	<b>Test location:</b>	Wireless center
<b>EUT Serial:</b>	V56	<b>Ambient temp:</b>	21 °C
<b>Tested by:</b>	PLA	<b>Relative humidity:</b>	35 %
<b>Test result:</b>	Pass	<b>Margin:</b>	N/A

## 10.1 Test set-up and test procedure.

The test method is in accordance with RSS-GEN section 6.6.


The EUT was connected to spectrum analyser via rf-cable and attenuator. Spectrum analyser with occupied bandwidth measurement function is used to determine the occupied bandwidth.

## 10.2 Test conditions


Detector: Peak.  
RBW: 1 – 5 % of OBW  
VBW: 3 x RBW

The EUT was set up in order to emit maximum disturbances.


### 10.3 Test results



## Screenshot: 99 % bandwidth Measurement, low channel



Screenshot: 99 % bandwidth Measurement. middle channel



Screenshot: 99 % bandwidth Measurement. high channel

**Test result**

Channel [MHz]	99 % BW [MHz]
2405	2.26
2445	2.26
2480	2.26

## 11 PEAK POWER SPECTRAL DENSITY

<b>Date of test:</b>	2018-01-15	<b>Test location:</b>	Wireless center
<b>EUT Serial:</b>	V56	<b>Ambient temp:</b>	21 °C
<b>Tested by:</b>	PLA	<b>Relative humidity:</b>	35 %
<b>Test result:</b>	Pass	<b>Margin:</b>	9.9 dB

### 11.1 Test set-up and test procedure.

The test method is in accordance with ANSI C63.10-2013 section 11.10.2.

The EUT was connected to spectrum analyser via rf-cable and attenuator.

### 11.2 Test conditions

Detector: Peak.  
RBW: 3 kHz  
VBW: >3 x RBW  
Span: 1.5 x 6 dB bandwidth


The EUT was set up in order to emit maximum disturbances.

### 11.3 Requirements


Reference: CFR 47§15.247(3). RSS-247 5.2(2)

For digitally modulated systems. the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


## 11.4 Test results



Screenshot: Peak power spectral density. low channel



Screenshot: Peak power spectral density. middle channel



Screenshot: Peak power spectral density. high channel

**Test result**

Channel [MHz]	PSD [dBm/3kHz]
2405	-10.0
2445	-1.9
2480	-9.4

## 12 TEST EQUIPMENT

### Conducted measurements

Equipment type	Manufacturer	Model	Inv. No.	Last Cal. date	Cal. interval
Receiver	Rohde & Schwarz	ESCI	12798	July-2017	1 year
Attenuator 10 dB	Narda	J1	9444	June-2017	1 year
Coaxial cable	Huber + Suhner	Sucoflex 100	39094	Mars-2017	1 year
Signal analyzer	Rohde & Schwarz	FSV	32594	July-2017	1 year

### 5m SAC

Equipment type	Manufacturer	Model	Inv. No.	Last Cal. date	Cal. interval
Measurement software	Rohde & Schwarz	EMC32 - 9	--	--	--
Receiver	Rohde & Schwarz	ESU40	13178	July-2017	1 year
Receiver	Rohde & Schwarz	ESIB26	32286	July-2017	1 year
Horn antenna with preamplifier	Bonn	31247		Jan-2017	3 years
Antenna	Rohde & Schwarz	HL562	32310	Mars-2017	3 years
Coaxial cable	Rosenberger	FP1-2/X1	39053	April-2017	1 year
Coaxial cable	Rohde & Schwarz	40 GHz	39127	July-2017	1 year
Preamplifier	Rohde & Schwarz	TS-PRE1	32306	July-2017	1 year
Horn antenna	Bonn	BLMA	31247	Jan-2017	3 years
Coaxial cable	Huber+Suhner	Sucoflex	39141	Nov-2017	1 year
Coaxial cable	Huber+Suhner	Sucoflex	39142	Nov-2017	1 year
Horn antenna	Rohde & Schwarz	HF907	32296	July-2017	3 years
Preamplifier	Rohde & Schwarz	TS-Pre1	32297	July-2017	3 years

## 13 MEASUREMENT UNCERTAINTY

Continuous conducted disturbances with AMN in the frequency range 9 kHz to 30 MHz  $\pm 3.7$  dB

Measurement uncertainty for radiated disturbance

Uncertainty for the frequency range 30 to 1000 MHz at 3 m  $\pm 5.1$  dB

Uncertainty for the frequency range 1.0 to 18 GHz at 3 m  $\pm 4.7$  dB

Uncertainty for the frequency range 18 to 26 GHz at 3 m  $\pm 4.8$  dB

Measurement uncertainty is calculated in accordance with CISPR 16-4-2:2011.  
The measurement uncertainty is given with a confidence of 95 %.

**14 TEST SET UP AND EUT PHOTOS**

EUT photos and test set up photos are in separate documents. EUT photo is in 1718488STOAnnex1-003. Ed 1 and test set up photos are in 1718488STOAnnex2-004. Ed 1.