

16 General SAR test reduction & exclusion guidance

KDB 447498

Section 4.3 General SAR test reduction and exclusion guidance

For Standalone SAR exclusion consideration, when SAR Exclusion Threshold requirement in KDB 447498 is satisfied, standalone SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.

The SAR Test Exclusion Threshold for frequencies in the range 100 MHz to 6 GHz, and for test separation distance of ≤ 50 mm, is determined as follows.

$$\text{SAR Exclusion Threshold (SARET)} = (NT \times TSD_A) / \sqrt{f_{GHz}}$$

Where,

NT = Numeric Threshold (3.0 for 1-g SAR and 7.5 for 10-g SAR)

TSD_A = Minimum Test separation distance or 50 mm (whichever is lower)

f_{GHz} = Transmit frequency in GHz

Radio	Channel Frequency (MHz)	Maximum Conducted Power (mW)	Duty Cycle (%)	Time Averaged Maximum Conducted Power (mW)	SAR Exclusion Threshold at 5 mm (mW)	SAR Evaluation
802.11 b/g/n	2412	100.000	0.33	0.330	9.658	Not Required
802.11 b/g/n	2462	100.000	0.33	0.330	9.560	Not Required

Therefore standalone SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.