

RF EXPOSURE REPORT



Report No.: 17070376-FCC-H2

Supersede Report No.: N/A

Applicant	INFINIX MOBILITY LIMITED	
Product Name	Mobile phone	
Model No.	X572	
Serial No.	N/A	
Test Standard	FCC 2.1093:2016	
Test Date	May 19 to June 08, 2017	
Issue Date	June 09, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
Vera Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES. 9	
5.1 RF EXPOSURE.....	9
5.2 TEST RESULT	10

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070376-FCC-H2	NONE	Original	June 09, 2017

2. Customer information

Applicant Name	INFINIX MOBILITY LIMITED
Applicant Add	RMS 05-15, 13A/F SOUTH TOWER WORLD FINANCE CTR HARBOUR CITY 17 CANTON RD TST KLN HONG KONG
Manufacturer	SHENZHEN TECNO TECHNOLOGY CO.,LTD.
Manufacturer Add	1-4th Floor,3rd Building,Pacific Industrial Park,No.2088,Shenyan Road,Yantian District,Shenzhen,Guangdong,China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT: Mobile phone

Main Model: X572

Serial Model: N/A

Date EUT received: May 18, 2017

Test Date(s): May 19 to June 08, 2017

GSM850:-3.2dBi

PCS1900:-0.29dBi

UMTS-FDD Band V: -3.2dBi

UMTS-FDD Band IV: -2.98dBi

UMTS-FDD Band II: -0.29dBi

LTE Band II: 1.7dBi

LTE Band IV: -2.98dBi

Antenna Gain: LTE Band VII: 2.5dBi

WIFI(2.4G): 1.35dBi

WIFI(5150-5250MHz): -2.2 dBi

WIFI(5250-5350MHz): -2.2 dBi

WIFI(5725-5850MHz): -2.2 dBi

Bluetooth/BLE: 1.35dBi

GPS: -0.29dBi

Antenna Type: PIFA antenna

GSM / GPRS: GMSK

EGPRS: GMSK,8PSK

UMTS-FDD: QPSK

LTE Band: QPSK, 16QAM

Type of Modulation: 802.11b: DSSS

802.11a/g/n20/n40: OFDM

Bluetooth: GFSK, π /4DQPSK, 8DPSK

BLE: GFSK

GPS: BPSK

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
UMTS-FDD Band IV TX: 1712.4 ~ 1752.6 MHz;
RX : 2112.4 ~ 2152.6 MHz
UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz;
RX: 1932.4 ~ 1987.6 MHz

RF Operating Frequency (ies):

LTE Band II TX: 1850.7~1909.3 MHz; RX : 1930.7 ~ 1989.3 MHz
LTE Band IV TX: 1710.7 ~ 1754.3 MHz; RX : 2110.7 ~ 2154.3 MHz
LTE Band VII TX: 2502.5 ~ 2567.5 MHz; RX : 2622.5 ~ 2687.5 MHz
802.11b/g: 2412-2462 MHz (TX/RX)
802.11n20: 2412-2462MHz ;5180-5320 MHz;
5745-5825 MHz; (TX/RX)
802.11n40: 2422-2452 MHz (TX/RX); 5190-5310 MHz;
5755-5795 MHz; (TX/RX)
802.11 a: 5180-5320 MHz; 5745-5825 MHz (TX/RX)
Bluetooth& BLE: 2402-2480 MHz
GPS: 1575.42 MHz

GSM 850: 124CH
PCS1900: 299CH
UMTS-FDD Band V: 102CH
UMTS-FDD Band IV: 202CH
UMTS-FDD Band II: 277CH

Number of Channels:

WIFI :802.11b/g: 11CH
WIFI :802.11a: 24CH
WIFI :802.11n20: 11CH(2.4GHz); 24CH(5GHz)
WIFI :802.11n40: 9CH(2.4GHz); 12CH(5GHz)
Bluetooth: 79CH
BLE: 40CH
GPS:1CH

Port: USB Port, Earphone Port

Adapter:

Model: CQ-18KX

Input: AC100-240V~50/60Hz,600mA

Output: DC 5.0V-9V,2A

DC 9V-12V,1.5A

Input Power:

Battery :

Model: BL-42AX

Spec: 3.85V,4200mAh/4300mAh (min/typ)

16.17Wh/16.55Wh (min/typ)

Limited Charge Voltage: 4.4V

Trade Name : Infinix

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: 2AIZN-X572

5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16}$ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

5.2 Test Result

Bluetooth Mode:

Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-0.099	-1±1	0	1.000	0.31	3
	Mid	2441	-1.405	-1±1	0	1.000	0.31	3
	High	2480	-1.983	-1±1	0	1.000	0.31	3
$\pi/4$ DQPSK	Low	2402	-1.019	-2±1	-1	0.794	0.25	3
	Mid	2441	-1.738	-2±1	-1	0.794	0.25	3
	High	2480	-2.354	-2±1	-1	0.794	0.25	3
8-DPSK	Low	2402	-0.836	-1.5±1	-0.5	0.891	0.28	3
	Mid	2441	-1.439	-1.5±1	-0.5	0.891	0.28	3
	High	2480	-2.271	-1.5±1	-0.5	0.891	0.28	3

BLE Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-0.249	-1.5±1	-0.5	0.891	0.28	3
	Mid	2440	-1.494	-1.5±1	-0.5	0.891	0.28	3
	High	2480	-1.566	-1.5±1	-0.5	0.891	0.28	3

Result: Compliance

No SAR measurement is required.