

FCC REPORT

(UNII)

Applicant: INFINIX MOBILITY LIMITED

Address of Applicant: FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35
SHAN MEI STREET FOTAN NT

Equipment Under Test (EUT)

Product Name: Mobile Phone

Model No.: X670

Trade mark: Infinix

FCC ID: 2AIZN-X670

Applicable standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407

Date of sample receipt: 22 Dec., 2021

Date of Test: 23 Dec., 2021 to 14 Feb., 2022

Date of report issued: 16 Feb., 2022

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the JYT product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	16 Feb., 2022	Original

Tested by: Mike.ou
Test Engineer

Date: 16 Feb., 2022

Reviewed by: Winner Zhang
Project Engineer

Date: 16 Feb., 2022

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST ENVIRONMENT AND MODE, AND TEST SAMPLES PLANS	7
5.4 DESCRIPTION OF SUPPORT UNITS.....	7
5.5 MEASUREMENT UNCERTAINTY.....	7
5.6 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD	7
5.7 RELATED SUBMITTAL(S) / GRANT (S)	7
5.8 LABORATORY FACILITY	8
5.9 LABORATORY LOCATION	8
5.10 TEST INSTRUMENTS LIST	9
6 TEST RESULTS AND MEASUREMENT DATA.....	10
6.1 ANTENNA REQUIREMENT	10
6.2 CONDUCTED EMISSION	11
6.3 CONDUCTED OUTPUT POWER	14
6.4 OCCUPY BANDWIDTH	15
6.5 POWER SPECTRAL DENSITY	16
6.6 BAND EDGE	17
6.7 SPURIOUS EMISSION.....	27
6.7.1 Restricted Band	27
6.7.2 Unwanted Emissions out of the Restricted Bands	28
6.8 FREQUENCY STABILITY.....	38
7 TEST SETUP PHOTO	39
8 EUT CONSTRUCTIONAL DETAILS	41

4 Test Summary

Test Item	Section in CFR 47	Test Data	Test Result
Antenna requirement	15.203 & 15.407 (a)	See Section 6.1	Pass
AC Power Line Conducted Emission	15.207	See Section 6.2	Pass
Duty Cycle	ANSI C63.10-2013	Appendix A – 5G Wi-Fi	Pass
Conducted Peak Output Power	15.407 (a) (1) (iv) & (a) (3)	Appendix A – 5G Wi-Fi	Pass
26dB Occupied Bandwidth	15.407 (a) (12)	Appendix A – 5G Wi-Fi	Pass
6dB Emission Bandwidth	15.407(e)	Appendix A – 5G Wi-Fi	Pass
Power Spectral Density	15.407 (a) (1) (iv) & (a) (3)	Appendix A – 5G Wi-Fi	Pass
Band Edge	15.407(b)	See Section 6.6	Pass
Spurious Emission	15.407 (b) & 15.205 & 15.209	See Section 6.7	Pass
Frequency Stability	15.407(g)	Appendix A – 5G Wi-Fi	Pass
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: Not Applicable. 3. The cable insertion loss used by “RF Output Power” and other conduction measurement items is 0.5dB (provided by the customer).			
Test Method:	ANSI C63.10-2013 KDB 789033 D02 General UNII Test Procedures New Rules v02r01		

5 General Information

5.1 Client Information

Applicant:	INFINIX MOBILITY LIMITED
Address:	FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35 SHAN MEI STREET FOTAN NT
Manufacturer:	INFINIX MOBILITY LIMITED
Address:	FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35 SHAN MEI STREET FOTAN NT
Factory:	SHENZHEN TECNO TECHNOLOGY CO., LTD.
Address:	101, Building 24, Waijing Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen City, P.R.China

5.2 General Description of E.U.T.

Product Name:	Mobile Phone				
Model No.:	X670				
Operation Frequency:	Band 1: 5150MHz-5250MHz			Band 4: 5725MHz-5825MHz	
Channel numbers:	Band 1:	802.11a/802.11n20: 4	802.11n40: 2	802.11ac: 1	
	Band 4:	802.11a/802.11n20: 5	802.11n40: 2	802.11ac: 1	
Channel separation:	20MHz:	802.11a/802.11n-HT20/802.11ac-HT20			
	40MHz:	802.11n-HT40/802.11ac-HT40			
	80MHz:	802.11ac-HT80			
Modulation technology (IEEE 802.11a):	BPSK, QPSK, 16-QAM, 64-QAM				
Modulation technology (IEEE 802.11n):	BPSK, QPSK, 16-QAM, 64-QAM				
Modulation technology (IEEE 802.11ac):	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM				
Data speed (IEEE 802.11a):	6Mbps, 9Mbps,12Mbps,18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps				
Data speed (IEEE 802.11n20):	MCS0: 6.5Mbps, MCS1:13Mbps,MCS2:19.5Mbps, MCS3:26Mbps, MCS4:39Mbps, MCS5:52Mbps, MCS6:58.5Mbps, MCS7:65Mbps				
Data speed (IEEE 802.11n40):	MCS0:15Mbps, MCS1:30Mbps, MCS2:45Mbps, MCS3:60Mbps, MCS4:90Mbps, MCS5:120Mbps, MCS6:135Mbps, MCS7:150Mbps				
Data speed (IEEE 802.11ac):	Up to 433.3Mbps				
Antenna Type:	Internal Antenna				
Antenna gain:	-0.9 dBi				
Power supply:	Rechargeable Li-ion Polymer Battery DC3.87V, 4900mAh				
AC adapter:	Model: U330XSA				
	Input: AC100-240V, 50/60Hz, 1.5A				
	Output: DC 5.0V, 3.0A 15.0W or DC 10.0V, 3.3A 33.0W MAX				
Test Sample Condition:	The test samples were provided in good working order with no visible defects.				

Operation Frequency each of channel					
Band 1					
802.11a/802.11n/ac-HT20		802.11n/ac-HT40		802.11ac-HT80	
Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180MHz	38	5190MHz	42	5210MHz
40	5200MHz	46	5230MHz		
44	5220MHz				
48	5240MHz				
Band 4					
802.11a/802.11n/ac-HT20		802.11n/ac-HT40		802.11ac-HT80	
Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745MHz	151	5755MHz	155	5775MHz
153	5765MHz	159	5795MHz		
157	5785MHz				
161	5805MHz				
165	5825MHz				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Band 1					
802.11a/802.11n/ac-HT20		802.11n/ac-HT40		802.11ac-HT80	
Channel	Frequency	Channel	Frequency	Channel	Frequency
Lowest	5180MHz	Lowest	5190MHz	Middle	5210MHz
Middle	5200MHz	Highest	5230MHz		
Highest	5240MHz				
Band 4					
802.11a/802.11n/ac-HT20		802.11n/ac-HT40		802.11ac-HT80	
Channel	Frequency	Channel	Frequency	Channel	Frequency
Lowest	5745MHz	Lowest	5755MHz	Middle	5775MHz
Middle	5785MHz	Highest	5795MHz		
Highest	5825MHz				

5.3 Test environment and mode, and test samples plans

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Continuously transmitting mode	Keep the EUT in 100% duty cycle transmitting with modulation.
We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Per-scan all kind of data rate, and found the follow list were the worst case.	
Mode	Data rate
802.11a	6 Mbps
802.11n/ac20	6.5 Mbps
802.11n/ac40	13.5 Mbps
802.11ac80	29.3 Mbps
Test Samples Plans:	
Samples Number	Used for Test Items
3#	Conducted measurements test method
1#	Radiated measurements test method
2#	EUT constructional details
<i>Remark: JianYan Testing Group Shenzhen Co., Ltd. is only responsible for the test project data of the above samples, and will keep the above samples for a month.</i>	

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
The EUT has been tested as an independent unit.				

5.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%)
Conducted Emission (9kHz ~ 150KHz) for V-AMN	3.11 dB
Conducted Emission (150kHz ~ 30MHz) for V-AMN	2.62 dB
Radiated Emission (9kHz ~ 30MHz electric field) for 3m SAC	3.13 dB
Radiated Emission (9kHz ~ 30MHz magnetic field) for 3m SAC	3.13 dB
Radiated Emission (30MHz ~ 1GHz) for 3m SAC	4.45 dB
Radiated Emission (1GHz ~ 18GHz) for 3m SAC	5.34 dB
Radiated Emission (18GHz ~ 40GHz) for 3m SAC	5.34 dB

5.6 Additions to, deviations, or exclusions from the method

No

5.7 Related Submittal(s) / Grant (s)

This is an original grant, no related submittals and grants.
--

5.8 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.9 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

5.10 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
3m SAC	ETS	RFD-100	Q1984	04-14-2021	04-13-2024
BiConiLog Antenna	SCHWARZBECK	VULB9163	9163-1246	03-07-2021	03-06-2022
Biconical Antenna	SCHWARZBECK	VUBA 9117	9117#359	06-17-2021	06-17-2022
Horn Antenna	SCHWARZBECK	BBHA9120D	912D-916	03-07-2021	03-06-2022
Broad-Band Horn Antenna	SCHWARZBECK	BBHA9170	1067	04-02-2021	04-01-2022
Broad-Band Horn Antenna	SCHWARZBECK	BBHA9170	1068	04-02-2021	04-01-2022
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-03-2021	03-02-2022
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-03-2021	03-02-2022
Spectrum analyzer	Keysight	N9010B	MY60240202	10-27-2021	10-26-2022
Low Pre-amplifier	SCHWARZBECK	BBV9743B	00305	03-07-2021	03-06-2022
High Pre-amplifier	SKET	LNPA_0118G-50	MF280208233	03-07-2021	03-06-2022
Cable	Qualwave	JYT3M-1G-NN-8M	JYT3M-1	03-07-2021	03-06-2022
Cable	Qualwave	JYT3M-18G-NN-8M	JYT3M-2	03-07-2021	03-06-2022
Cable	Qualwave	JYT3M-1G-BB-5M	JYT3M-3	03-07-2021	03-06-2022
Cable	Bost	JYT3M-40G-SS-8M	JYT3M-4	04-02-2021	04-01-2022
EMI Test Software	Tonscend	TS+	Version:3.0.0.1		

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI 3	101189	03-03-2021	03-02-2022
LISN	Schwarzbeck	NSLK 8127	QCJ001-13	03-18-2021	03-17-2022
LISN	Rohde & Schwarz	ESH3-Z5	843862/010	06-18-2020	06-17-2022
RF Switch	TOP PRECISION	RSU0301	N/A	03-03-2021	03-02-2022
Cable	Bost	JYTCE-1G-NN-2M	JYTCE-1	03-03-2021	03-02-2022
Cable	Bost	JYTCE-1G-BN-3M	JYTCE-2	03-03-2021	03-02-2022
EMI Test Software	AUDIX	E3	Version: 6.110919b		

Conducted method:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
Spectrum Analyzer	Keysight	N9010B	MY60240202	10-27-2021	10-26-2022
Vector Signal Generator	Keysight	N5182B	MY59101009	10-27-2021	10-26-2022
Analog Signal Generator	Keysight	N5173B	MY59100765	10-27-2021	10-26-2022
Power Detector Box	MWRF-test	MW100-PSB	MW201020JYT	11-19-2021	11-18-2022
Simulated Station	Rohde & Schwarz	CMW270	102335	10-27-2021	10-26-2022
RF Control Box	MWRF-test	MW100-RFCB	MW200927JYT	N/A	N/A
PDU	MWRF-test	XY-G10	N/A	N/A	N/A
DC Power Supply	Keysight	E3642A	MY60296194	11-27-2020	11-26-2023
Temperature Humidity Chamber	Deli	8840	N/A	03-08-2021	03-07-2022
Test Software	MWRF-tes	MTS 8310	Version: 2.0.0.0		

6 Test results and Measurement Data

6.1 Antenna requirement


Standard requirement:	FCC Part15 E Section 15.203 /407(a)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.	
E.U.T Antenna:	
The Wi-Fi antenna is an Internal antenna which cannot replace by end-user, the best case gain of the antenna is -0.9 dBi.	

6.2 Conducted Emission

Test Requirement:	FCC Part15 C Section 15.207		
Test Frequency Range:	150kHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9kHz, VBW=30kHz		
Limit:	Frequency range (MHz)	Limit (dBUV)	
		Quasi-peak	
	0.15-0.5	66 to 56*	0.15-0.5
	0.5-5	56	0.5-5
	5-30	60	5-30
* Decreases with the logarithm of the frequency.			
Test procedure	- The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). It provides a 50ohm/50uH coupling impedance for the measuring equipment. - The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). - Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10(latest version) on conducted measurement.		
Test setup:	 Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test Instruments:	Refer to section 5.10 for details		
Test mode:	Refer to section 5.3 for details.		
Test results:	Passed		

Measurement Data:


Product name:	Mobile Phone	Product model:	X670
Test by:	Mike	Test mode:	5G Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 19.1℃ Humi: 53%



Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

Product name:	Mobile Phone	Product model:	X670
Test by:	Mike	Test mode:	5G Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 19.1℃ Humi: 53%



	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.166	39.18	0.05	0.01	39.24	65.16	-25.92	QP
2	0.174	28.66	0.04	0.01	28.71	54.77	-26.06	Average
3	0.249	38.77	0.04	0.01	38.82	61.78	-22.96	QP
4	0.270	26.30	0.04	0.02	26.36	51.12	-24.76	Average
5	0.466	35.95	0.04	0.03	36.02	46.58	-10.56	Average
6	0.466	42.51	0.04	0.03	42.58	56.58	-14.00	QP
7	0.948	23.26	0.05	0.05	23.36	46.00	-22.64	Average
8	1.296	30.95	0.05	0.11	31.11	56.00	-24.89	QP
9	8.235	25.10	0.16	0.10	25.36	50.00	-24.64	Average
10	8.367	32.76	0.16	0.10	33.02	60.00	-26.98	QP
11	12.384	21.75	0.22	0.10	22.07	50.00	-27.93	Average
12	13.197	28.90	0.23	0.11	29.24	60.00	-30.76	QP


Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.


6.3 Conducted Output Power

Test Requirement:	FCC Part15 E Section 15.407 (a) (1) (iv) & (a) (3)
Limit:	Band 1: 24dBm Band 4: 30dBm
Test setup:	
Test Instruments:	Refer to section 5.10 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Measurement Data:	Refer to Appendix A - 5G WIFI


6.4 Occupy Bandwidth

Test Requirement:	FCC Part15 E Section 15.407 (a) (12) and Section 15.407 (e)
Limit:	Band 1/4: N/A (26dB Emission Bandwidth and 99% Occupy Bandwidth) Band 4: >500kHz (6dB Bandwidth)
Test setup:	
Test Instruments:	Refer to section 5.10 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Measurement Data:	Refer to Appendix A - 5G WIFI

6.5 Power Spectral Density

Test Requirement:	FCC Part15 E Section 15.407 (a) (1) (iv) & (a)(3)
Limit:	Band 1: 11 dBm/MHz Band 4: 30 dBm/500kHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, shown with a grid and a green curve on its screen, is connected to an E.U.T. (Equipment Under Test) by a red cable. Both the Spectrum Analyzer and the E.U.T. are positioned on a Non-Conducted Table, which is supported by two vertical legs. Below the table, a Ground Reference Plane is indicated.
Test Instruments:	Refer to section 5.10 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Measurement Data:	Refer to Appendix A - 5G WIFI

6.6 Band Edge

Test Requirement:	FCC Part 15 E Section 15.407 (b)			
Receiver setup:	Detector	RBW	VBW	Remark
	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	RMS	1MHz	3MHz	Average Value
Limit:	Band	Limit (dBuV/m @3m)		Remark
	Band 1/2/3	68.20		Peak Value
		54.00		Average Value
		Band 4 limit: For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. Remark: 1. Band 1/2/3 limit: $E[dB\mu V/m] = EIRP[dBm] + 95.2 = 68.2 \text{ dBuV/m}$, for $EIPR[dBm] = -27 \text{ dBm}$. 2. Band 4 limit: $E[dB\mu V/m] = EIRP[dBm] + 95.2 = 68.2 \text{ dBuV/m}$, for $EIPR[dBm] = -27 \text{ dBm}$. $E[dB\mu V/m] = EIRP[dBm] + 95.2 = 105.2 \text{ dBuV/m}$, for $EIPR[dBm] = 10 \text{ dBm}$. $E[dB\mu V/m] = EIRP[dBm] + 95.2 = 110.8 \text{ dBuV/m}$, for $EIPR[dBm] = 15.6 \text{ dBm}$. $E[dB\mu V/m] = EIRP[dBm] + 95.2 = 122.2 \text{ dBuV/m}$, for $EIPR[dBm] = 27 \text{ dBm}$.		
	Test Procedure:	- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.		
Test setup:				
Test Instruments:	Refer to section 5.10 for details			
Test mode:	Refer to section 5.3 for details			
Test results:	Passed			

Measurement Data (worst case):
Band 1:

Band 1 – 802.11a							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Polarity
5150.00	37.33	15.49	52.82	68.20	15.38	Horizontal	Peak
5150.00	35.68	15.49	51.17	68.20	17.03	Vertical	Peak
5150.00	30.53	15.49	46.02	54.00	7.98	Horizontal	Average
5150.00	28.04	15.49	43.53	54.00	10.47	Vertical	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Polarity
5350.00	36.12	16.44	52.56	68.20	15.64	Horizontal	Peak
5350.00	35.01	16.44	51.45	68.20	16.75	Vertical	Peak
5350.00	27.74	16.44	44.18	54.00	9.82	Horizontal	Average
5350.00	27.63	16.44	44.07	54.00	9.93	Vertical	Average
Band 1 – 802.11n(HT20)							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Polarity
5150.00	37.62	15.49	53.11	68.20	15.09	Horizontal	Peak
5150.00	36.08	15.49	51.57	68.20	16.63	Vertical	Peak
5150.00	30.34	15.49	45.83	54.00	8.17	Horizontal	Average
5150.00	27.61	15.49	43.10	54.00	10.9	Vertical	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Polarity
5350.00	36.54	16.44	52.98	68.20	15.22	Horizontal	Peak
5350.00	34.61	16.44	51.05	68.20	17.15	Vertical	Peak
5350.00	27.64	16.44	44.08	54.00	9.92	Horizontal	Average
5350.00	28.11	16.44	44.55	54.00	9.45	Vertical	Average
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.							

Band 1 – 802.11n(HT40)							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Polarity
5150.00	37.63	15.49	53.12	68.20	15.08	Horizontal	Peak
5150.00	36.06	15.49	51.55	68.20	16.65	Vertical	Peak
5150.00	30.69	15.49	46.18	54.00	7.82	Horizontal	Average
5150.00	27.64	15.49	43.13	54.00	10.87	Vertical	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Polarity
5350.00	36.00	16.44	52.44	68.20	15.76	Horizontal	Peak
5350.00	35.08	16.44	51.52	68.20	16.68	Vertical	Peak
5350.00	28.02	16.44	44.46	54.00	9.54	Horizontal	Average
5350.00	27.54	16.44	43.98	54.00	10.02	Vertical	Average
Band 1 – 802.11ac(HT20)							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Polarity
5150.00	37.63	15.49	53.12	68.20	15.08	Horizontal	Peak
5150.00	35.86	15.49	51.35	68.20	16.85	Vertical	Peak
5150.00	30.04	15.49	45.53	54.00	8.47	Horizontal	Average
5150.00	28.19	15.49	43.68	54.00	10.32	Vertical	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Polarity
5350.00	35.78	16.44	52.22	68.20	15.98	Horizontal	Peak
5350.00	35.39	16.44	51.83	68.20	16.37	Vertical	Peak
5350.00	28.19	16.44	44.63	54.00	9.37	Horizontal	Average
5350.00	27.75	16.44	44.19	54.00	9.81	Vertical	Average
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.							

Band 1 – 802.11ac(HT40)							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Polarity
5150.00	46.77	15.49	62.26	68.20	5.94	Horizontal	Peak
5150.00	41.23	15.49	56.72	68.20	11.48	Vertical	Peak
5150.00	35.11	15.49	50.60	54.00	3.4	Horizontal	Average
5150.00	29.75	15.49	45.24	54.00	8.76	Vertical	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Polarity
5350.00	35.24	16.44	51.68	68.20	16.52	Horizontal	Peak
5350.00	35.04	16.44	51.48	68.20	16.72	Vertical	Peak
5350.00	27.68	16.44	44.12	54.00	9.88	Horizontal	Average
5350.00	26.92	16.44	43.36	54.00	10.64	Vertical	Average
Band 1 – 802.11ac(HT80)							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Polarity
5150.00	45.26	15.49	60.75	68.20	7.45	Horizontal	Peak
5150.00	37.40	15.49	52.89	68.20	15.31	Vertical	Peak
5150.00	36.31	15.49	51.80	54.00	2.2	Horizontal	Average
5150.00	29.27	15.49	44.76	54.00	9.24	Vertical	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Polarity
5350.00	34.81	16.44	51.25	68.20	16.95	Horizontal	Peak
5350.00	34.35	16.44	50.79	68.20	17.41	Vertical	Peak
5350.00	27.50	16.44	43.94	54.00	10.06	Horizontal	Average
5350.00	27.77	16.44	44.21	54.00	9.79	Vertical	Average
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.							

Band 4:

Band 4 – 802.11a						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization
5650.00	34.94	17.02	51.96	68.20	16.24	Horizontal
5700.00	34.29	17.13	51.42	105.20	53.78	Horizontal
5720.00	33.80	17.21	51.01	110.80	59.79	Horizontal
5725.00	34.38	17.23	51.61	122.20	70.59	Horizontal
5650.00	35.06	17.02	52.08	68.20	16.12	Vertical
5700.00	34.74	17.13	51.87	105.20	53.33	Vertical
5720.00	36.29	17.21	53.50	110.80	57.30	Vertical
5725.00	35.22	17.23	52.45	122.20	69.75	Vertical
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization
5850.00	33.31	17.55	50.86	122.20	71.34	Horizontal
5855.00	34.34	17.55	51.89	110.80	58.91	Horizontal
5875.00	34.76	17.57	52.33	105.20	52.87	Horizontal
5925.00	34.44	17.37	51.81	68.20	16.39	Horizontal
5850.00	33.71	17.55	51.26	122.20	70.94	Vertical
5855.00	34.48	17.55	52.03	110.80	58.77	Vertical
5875.00	35.09	17.57	52.66	105.20	52.54	Vertical
5925.00	35.03	17.37	52.40	68.20	15.80	Vertical
Remark: 1. <i>Final Level = Receiver Read level + Factor.</i> 2. <i>The emission levels of other frequencies are lower than the limit 20dB and not show in test report.</i>						

Band 4 – 802.11n(HT20)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization
5650.00	35.36	17.02	52.38	68.20	15.82	Horizontal
5700.00	34.35	17.13	51.48	105.20	53.72	Horizontal
5720.00	33.42	17.21	50.63	110.80	60.17	Horizontal
5725.00	34.53	17.23	51.76	122.20	70.44	Horizontal
5650.00	34.92	17.02	51.94	68.20	16.26	Vertical
5700.00	34.77	17.13	51.90	105.20	53.30	Vertical
5720.00	35.83	17.21	53.04	110.80	57.76	Vertical
5725.00	35.51	17.23	52.74	122.20	69.46	Vertical
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization
5850.00	33.64	17.55	51.19	122.20	71.01	Horizontal
5855.00	34.20	17.55	51.75	110.80	59.05	Horizontal
5875.00	34.88	17.57	52.45	105.20	52.75	Horizontal
5925.00	34.57	17.37	51.94	68.20	16.26	Horizontal
5850.00	33.71	17.55	51.26	122.20	70.94	Vertical
5855.00	34.58	17.55	52.13	110.80	58.67	Vertical
5875.00	35.11	17.57	52.68	105.20	52.52	Vertical
5925.00	34.66	17.37	52.03	68.20	16.17	Vertical
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						

Band 4 – 802.11n(HT40)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization
5650.00	35.07	17.02	52.09	68.20	16.11	Horizontal
5700.00	34.45	17.13	51.58	105.20	53.62	Horizontal
5720.00	35.19	17.21	52.40	110.80	58.40	Horizontal
5725.00	35.51	17.23	52.74	122.20	69.46	Horizontal
5650.00	34.81	17.02	51.83	68.20	16.37	Vertical
5700.00	34.73	17.13	51.86	105.20	53.34	Vertical
5720.00	34.86	17.21	52.07	110.80	58.73	Vertical
5725.00	34.13	17.23	51.36	122.20	70.84	Vertical
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization
5850.00	33.75	17.55	51.30	122.20	70.90	Horizontal
5855.00	33.38	17.55	50.93	110.80	59.87	Horizontal
5875.00	34.80	17.57	52.37	105.20	52.83	Horizontal
5925.00	34.02	17.37	51.39	68.20	16.81	Horizontal
5850.00	33.78	17.55	51.33	122.20	70.87	Vertical
5855.00	34.16	17.55	51.71	110.80	59.09	Vertical
5875.00	34.85	17.57	52.42	105.20	52.78	Vertical
5925.00	34.96	17.37	52.33	68.20	15.87	Vertical
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						


Band 4 – 802.11ac(HT20)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization
5650.00	35.83	17.02	52.85	68.20	15.35	Horizontal
5700.00	34.37	17.13	51.50	105.20	53.70	Horizontal
5720.00	33.07	17.21	50.28	110.80	60.52	Horizontal
5725.00	34.52	17.23	51.75	122.20	70.45	Horizontal
5650.00	35.39	17.02	52.41	68.20	15.79	Vertical
5700.00	34.32	17.13	51.45	105.20	53.75	Vertical
5720.00	35.67	17.21	52.88	110.80	57.92	Vertical
5725.00	35.12	17.23	52.35	122.20	69.85	Vertical
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization
5850.00	33.16	17.55	50.71	122.20	71.49	Horizontal
5855.00	34.66	17.55	52.21	110.80	58.59	Horizontal
5875.00	34.77	17.57	52.34	105.20	52.86	Horizontal
5925.00	34.89	17.37	52.26	68.20	15.94	Horizontal
5850.00	33.56	17.55	51.11	122.20	71.09	Vertical
5855.00	34.81	17.55	52.36	110.80	58.44	Vertical
5875.00	35.26	17.57	52.83	105.20	52.37	Vertical
5925.00	34.77	17.37	52.14	68.20	16.06	Vertical
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						

Band 4 – 802.11ac(HT40)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization
5650.00	35.29	17.02	52.31	68.20	15.89	Horizontal
5700.00	34.46	17.13	51.59	105.20	53.61	Horizontal
5720.00	35.22	17.21	52.43	110.80	58.37	Horizontal
5725.00	35.26	17.23	52.49	122.20	69.71	Horizontal
5650.00	34.76	17.02	51.78	68.20	16.42	Vertical
5700.00	35.05	17.13	52.18	105.20	53.02	Vertical
5720.00	34.54	17.21	51.75	110.80	59.05	Vertical
5725.00	33.64	17.23	50.87	122.20	71.33	Vertical
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization
5850.00	33.97	17.55	51.52	122.20	70.68	Horizontal
5855.00	33.74	17.55	51.29	110.80	59.51	Horizontal
5875.00	34.94	17.57	52.51	105.20	52.69	Horizontal
5925.00	33.54	17.37	50.91	68.20	17.29	Horizontal
5850.00	33.92	17.55	51.47	122.20	70.73	Vertical
5855.00	34.14	17.55	51.69	110.80	59.11	Vertical
5875.00	34.56	17.57	52.13	105.20	53.07	Vertical
5925.00	34.86	17.37	52.23	68.20	15.97	Vertical
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						


Band 4 – 802.11ac(HT80)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization
5650.00	34.39	17.02	51.41	68.20	16.79	Horizontal
5700.00	34.55	17.13	51.68	105.20	53.52	Horizontal
5720.00	34.51	17.21	51.72	110.80	59.08	Horizontal
5725.00	34.18	17.23	51.41	122.20	70.79	Horizontal
5650.00	33.78	17.02	50.80	68.20	17.40	Vertical
5700.00	33.98	17.13	51.11	105.20	54.09	Vertical
5720.00	35.22	17.21	52.43	110.80	58.37	Vertical
5725.00	34.08	17.23	51.31	122.20	70.89	Vertical
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization
5850.00	34.99	17.55	52.54	122.20	69.66	Horizontal
5855.00	35.66	17.55	53.21	110.80	57.59	Horizontal
5875.00	35.34	17.57	52.91	105.20	52.29	Horizontal
5925.00	35.44	17.37	52.81	68.20	15.39	Horizontal
5850.00	34.21	17.55	51.76	122.20	70.44	Vertical
5855.00	33.66	17.55	51.21	110.80	59.59	Vertical
5875.00	34.57	17.57	52.14	105.20	53.06	Vertical
5925.00	33.66	17.37	51.03	68.20	17.17	Vertical
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						


6.7 Spurious Emission

6.7.1 Restricted Band

Test Requirement:	FCC Part15 E Section 15.407(b)				
Test Frequency Range:	4.5 GHz to 5.15 GHz and 5.35GHz to 5.46GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	Above 1GHz		74.00		Peak Value
			54.00		Average Value
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test setup:					
Test Instruments:	Refer to section 5.10 for details				
Test mode:	Refer to section 5.3 for details				
Test results:	Passed(Refer to section 6.6)				


6.7.2 Unwanted Emissions out of the Restricted Bands

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Frequency Range:	30MHz to 40GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	100kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		68.20		Peak Value
			54.00		Average Value
	Remark:				
	Above 1GHz limit:				
$E[dB\mu V/m] = EIRP[dBm] + 95.2=68.2 \text{ dBuV/m}$, for $EIPR[dBm]=-27dBm$.					
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8m(below 1GHz)/1.5m(above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.				
	2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.				
	3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.				
	4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.				
	5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.				
	6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test setup:	Below 1GHz				
					
	Above 1GHz				

	
Test Instruments:	Refer to section 5.10 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data (worst case):
Below 1GHz

Product Name:	Mobile Phone	Product Model:	X670
Test By:	Mike	Test mode:	5G Wi-Fi Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 22.1℃ Humi: 55%



Suspected Data List

NO.	Freq. [MHz]	Reading[d BuV/m]	Level [dBuV/m]	Factor [dB]	Limit [dBuV/m]	Margin [dB]	Trace	Polarity
1	41.3501	30.72	16.10	-14.62	40.00	23.90	PK	Vertical
2	69.1919	42.89	26.16	-16.73	40.00	13.84	PK	Vertical
3	107.898	32.12	16.18	-15.94	43.50	27.32	PK	Vertical
4	301.142	29.61	16.93	-12.68	46.00	29.07	PK	Vertical
5	519.705	30.56	23.65	-6.91	46.00	22.35	PK	Vertical
6	909.684	30.14	28.77	-1.37	46.00	17.23	PK	Vertical

Remark:

- Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Mobile Phone	Product Model:	X670
Test By:	Mike	Test mode:	5G Wi-Fi Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 22.1℃ Humi: 55%



Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	51.3421	28.77	14.09	-14.68	40.00	25.91	PK	Horizontal
2	57.8418	28.37	13.52	-14.85	40.00	26.48	PK	Horizontal
3	107.995	29.91	13.97	-15.94	43.50	29.53	PK	Horizontal
4	301.627	28.67	16.01	-12.66	46.00	29.99	PK	Horizontal
5	526.010	30.04	23.15	-6.89	46.00	22.85	PK	Horizontal
6	958.867	30.57	29.68	-0.89	46.00	16.32	PK	Horizontal

Remark:

- Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Above 1GHz:

Band 1:

Band 1 – 802.11a							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10360.00	52.77	5.48	58.25	68.20	9.95	Vertical	Peak
10360.00	53.53	5.48	59.01	68.20	9.19	Horizontal	Peak
10360.00	44.98	5.48	50.46	54.00	3.54	Vertical	Average
10360.00	45.02	5.48	50.50	54.00	3.50	Horizontal	Average
Test channel: Middle channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10400.00	52.27	5.31	57.58	68.20	10.62	Vertical	Peak
10400.00	53.53	5.31	58.84	68.20	9.36	Horizontal	Peak
10400.00	44.67	5.31	49.98	54.00	4.02	Vertical	Average
10400.00	44.63	5.31	49.94	54.00	4.06	Horizontal	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10480.00	53.11	5.98	59.09	68.20	9.11	Vertical	Peak
10480.00	53.78	5.98	59.76	68.20	8.44	Horizontal	Peak
10480.00	44.91	5.98	50.89	54.00	3.11	Vertical	Average
10480.00	45.46	5.98	51.44	54.00	2.56	Horizontal	Average
Band 1 – 802.11n(HT20)							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10360.00	52.88	5.48	58.36	68.20	9.84	Vertical	Peak
10360.00	53.15	5.48	58.63	68.20	9.57	Horizontal	Peak
10360.00	45.31	5.48	50.79	54.00	3.21	Vertical	Average
10360.00	44.61	5.48	50.09	54.00	3.91	Horizontal	Average
Test channel: Middle channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10400.00	53.01	5.31	58.32	68.20	9.88	Vertical	Peak
10400.00	53.40	5.31	58.71	68.20	9.49	Horizontal	Peak
10400.00	45.31	5.31	50.62	54.00	3.38	Vertical	Average
10400.00	44.17	5.31	49.48	54.00	4.52	Horizontal	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10480.00	52.58	5.98	58.56	68.20	9.64	Vertical	Peak
10480.00	53.24	5.98	59.22	68.20	8.98	Horizontal	Peak
10480.00	45.34	5.98	51.32	54.00	2.68	Vertical	Average
10480.00	44.62	5.98	50.60	54.00	3.40	Horizontal	Average
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.							

Band 1 – 802.11n(HT40)							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10380.00	52.65	5.39	58.04	68.20	10.16	Vertical	Peak
10380.00	53.11	5.39	58.50	68.20	9.70	Horizontal	Peak
10380.00	45.43	5.39	50.82	54.00	3.18	Vertical	Average
10380.00	45.08	5.39	50.47	54.00	3.53	Horizontal	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10460.00	53.05	5.81	58.86	68.20	9.34	Vertical	Peak
10460.00	52.89	5.81	58.70	68.20	9.50	Horizontal	Peak
10460.00	45.26	5.81	51.07	54.00	2.93	Vertical	Average
10460.00	45.54	5.81	51.35	54.00	2.65	Horizontal	Average
Band 1 – 802.11ac(HT20)							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10360.00	52.96	5.48	58.44	68.20	9.76	Vertical	Peak
10360.00	54.00	5.48	59.48	68.20	8.72	Horizontal	Peak
10360.00	45.08	5.48	50.56	54.00	3.44	Vertical	Average
10360.00	45.24	5.48	50.72	54.00	3.28	Horizontal	Average
Test channel: Middle channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10400.00	52.65	5.31	57.96	68.20	10.24	Vertical	Peak
10400.00	53.53	5.31	58.84	68.20	9.36	Horizontal	Peak
10400.00	45.60	5.31	50.91	54.00	3.09	Vertical	Average
10400.00	44.42	5.31	49.73	54.00	4.27	Horizontal	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10480.00	52.24	5.98	58.22	68.20	9.98	Vertical	Peak
10480.00	53.90	5.98	59.88	68.20	8.32	Horizontal	Peak
10480.00	45.18	5.98	51.16	54.00	2.84	Vertical	Average
10480.00	44.27	5.98	50.25	54.00	3.75	Horizontal	Average
Remark:							
1. Final Level = Receiver Read level + Factor.							
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.							

Band 1 – 802.11ac(HT40)							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10380.00	52.88	5.39	58.27	68.20	9.93	Vertical	Peak
10380.00	53.60	5.39	58.99	68.20	9.21	Horizontal	Peak
10380.00	44.98	5.39	50.37	54.00	3.63	Vertical	Average
10380.00	45.57	5.39	50.96	54.00	3.04	Horizontal	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10460.00	53.37	5.81	59.18	68.20	9.02	Vertical	Peak
10460.00	52.51	5.81	58.32	68.20	9.88	Horizontal	Peak
10460.00	45.47	5.81	51.28	54.00	2.72	Vertical	Average
10460.00	45.90	5.81	51.71	54.00	2.29	Horizontal	Average
Band 1 – 802.11ac(HT80)							
Test channel: Middle channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
10420.00	53.09	5.48	58.57	68.20	9.63	Vertical	Peak
10420.00	53.25	5.48	58.73	68.20	9.47	Horizontal	Peak
10420.00	45.19	5.48	50.67	54.00	3.33	Vertical	Average
10420.00	45.54	5.48	51.02	54.00	2.98	Horizontal	Average
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.							


Band 4:

Band 4 – 802.11a							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11490.00	53.36	7.21	60.57	74.00	13.43	Vertical	Peak
11490.00	52.97	7.21	60.18	74.00	13.82	Horizontal	Peak
11490.00	44.30	7.21	51.51	54.00	2.49	Vertical	Average
11490.00	44.64	7.21	51.85	54.00	2.15	Horizontal	Average
Test channel: Middle channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11570.00	53.72	6.88	60.60	74.00	13.40	Vertical	Peak
11570.00	52.78	6.88	59.66	74.00	14.34	Horizontal	Peak
11570.00	44.50	6.88	51.38	54.00	2.62	Vertical	Average
11570.00	44.56	6.88	51.44	54.00	2.56	Horizontal	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11650.00	53.07	7.09	60.16	74.00	13.84	Vertical	Peak
11650.00	53.02	7.09	60.11	74.00	13.89	Horizontal	Peak
11650.00	43.50	7.09	50.59	54.00	3.41	Vertical	Average
11650.00	44.56	7.09	51.65	54.00	2.35	Horizontal	Average
Band 4 – 802.11n(HT20)							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11490.00	52.97	7.21	60.18	74.00	13.82	Vertical	Peak
11490.00	52.63	7.21	59.84	74.00	14.16	Horizontal	Peak
11490.00	43.15	7.21	50.36	54.00	3.64	Vertical	Average
11490.00	44.75	7.21	51.96	54.00	2.04	Horizontal	Average
Test channel: Middle channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11570.00	53.11	6.88	59.99	74.00	14.01	Vertical	Peak
11570.00	52.23	6.88	59.11	74.00	14.89	Horizontal	Peak
11570.00	43.60	6.88	50.48	54.00	3.52	Vertical	Average
11570.00	45.00	6.88	51.88	54.00	2.12	Horizontal	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11650.00	53.43	7.09	60.52	74.00	13.48	Vertical	Peak
11650.00	52.48	7.09	59.57	74.00	14.43	Horizontal	Peak
11650.00	44.23	7.09	51.32	54.00	2.68	Vertical	Average
11650.00	44.26	7.09	51.35	54.00	2.65	Horizontal	Average
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.							

Band 4 – 802.11n(HT40)							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11510.00	53.68	7.20	60.88	74.00	13.12	Vertical	Peak
11510.00	53.35	7.20	60.55	74.00	13.45	Horizontal	Peak
11510.00	44.07	7.20	51.27	54.00	2.73	Vertical	Average
11510.00	44.68	7.20	51.88	54.00	2.12	Horizontal	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11590.00	53.74	6.77	60.51	74.00	13.49	Vertical	Peak
11590.00	53.66	6.77	60.43	74.00	13.57	Horizontal	Peak
11590.00	43.77	6.77	50.54	54.00	3.46	Vertical	Average
11590.00	45.01	6.77	51.78	54.00	2.22	Horizontal	Average
Band 4 – 802.11ac(HT20)							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11490.00	53.38	7.21	60.59	74.00	13.41	Vertical	Peak
11490.00	52.12	7.21	59.33	74.00	14.67	Horizontal	Peak
11490.00	44.27	7.21	51.48	54.00	2.52	Vertical	Average
11490.00	44.57	7.21	51.78	54.00	2.22	Horizontal	Average
Test channel: Middle channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11570.00	50.65	6.88	57.53	74.00	16.47	Vertical	Peak
11570.00	51.38	6.88	58.26	74.00	15.74	Horizontal	Peak
11570.00	43.98	6.88	50.86	54.00	3.14	Vertical	Average
11570.00	43.60	6.88	50.48	54.00	3.52	Horizontal	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11650.00	53.82	7.09	60.91	74.00	13.09	Vertical	Peak
11650.00	52.45	7.09	59.54	74.00	14.46	Horizontal	Peak
11650.00	43.78	7.09	50.87	54.00	3.13	Vertical	Average
11650.00	43.96	7.09	51.05	54.00	2.95	Horizontal	Average
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.							

Band 4 – 802.11ac(HT40)							
Test channel: Lowest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11510.00	53.33	7.20	60.53	74.00	13.47	Vertical	Peak
11510.00	53.17	7.20	60.37	74.00	13.63	Horizontal	Peak
11510.00	44.02	7.20	51.22	54.00	2.78	Vertical	Average
11510.00	44.77	7.20	51.97	54.00	2.03	Horizontal	Average
Test channel: Highest channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11590.00	53.12	6.77	59.89	74.00	14.11	Vertical	Peak
11590.00	53.26	6.77	60.03	74.00	13.97	Horizontal	Peak
11590.00	44.20	6.77	50.97	54.00	3.03	Vertical	Average
11590.00	44.33	6.77	51.10	54.00	2.90	Horizontal	Average
Band 4 – 802.11ac(HT80)							
Test channel: Middle channel							
Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin [dB]	Polarization	Trace
11550.00	53.13	6.99	60.12	74.00	13.88	Vertical	Peak
11550.00	52.76	6.99	59.75	74.00	14.25	Horizontal	Peak
11550.00	44.03	6.99	51.02	54.00	2.98	Vertical	Average
11550.00	44.62	6.99	51.61	54.00	2.39	Horizontal	Average
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.							

6.8 Frequency stability

Test Requirement:	FCC Part15 E Section 15.407 (g)
Limit:	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.
Test setup:	 The diagram illustrates the test setup. On the left is a rack of test equipment including a spectrum analyzer (NS175B), a signal generator (NS182B), a network analyzer (NS100B), a microwave power source (CMW270), a microwave power splitter (MW100-PSB), a microwave power combiner (MW100-RFCB), a power distribution unit (PDU), and a signal processor (SPD). On the right is a Temperature Humidity Chamber containing the Equipment Under Test (EUT). A blue line connects the spectrum analyzer to the EUT, and a red line connects the signal generator to the EUT.
Test procedure:	1. The EUT is installed in an environment test chamber with external power source. 2. Set the chamber to operate at 50 centigrade and external power source to output at nominal voltage of EUT. 3. A sufficient stabilization period at each temperature is used prior to each frequency measurement. 4. When temperature is stabled, measure the frequency stability. 5. The test shall be performed under -30 to 50 centigrade and 85 to 115 percent of the nominal voltage. Change setting of chamber and external power source to complete all conditions.
Test Instruments:	Refer to section 5.10 for details
Test mode:	Refer to section 5.3 for details
Test results:	Refer to Appendix A - 5G WIFI

8 EUT Constructional Details

Reference to the test report No.: JYTSZB-R12-2102928.

-----End of report-----