

FCC EMC Test Report

Applicant: INFINIX MOBILITY LIMITED

Address of Applicant: FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE
19-25 SHAN MEI STREET FOTAN NT HONGKONG

Equipment Under Test (EUT)

Product Name: Mobile Phone

Model No.: X6710

Trade Mark: Infinix

FCC ID: 2AIZN-X6710

Applicable Standards: FCC CFR Title 47 Part 15B


Date of Sample Receipt: 28 Dec., 2022

Date of Test: 29 Dec., 2022 to 13 Mar., 2023

Date of report Issued: 14 Mar., 2023

Test Result: PASS

Tested by:	<u>Mike.Ou</u>	Date:	<u>14 Mar., 2023</u>
Reviewed by:	<u>Wenwen Zhang</u>	Date:	<u>14 Mar., 2023</u>
Approved by:	<u>Manager</u>	Date:	<u>14 Mar., 2023</u>



This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

1 Version

Version No.	Date	Description
00	14 Mar., 2023	Original

2 Contents

	Page
Cover Page	1
1 Version	2
2 Contents.....	3
3 General Information.....	4
3.1 Client Information	4
3.2 General Description of E.U.T.	4
3.3 Test Mode	4
3.4 Description of Test Auxiliary Equipment	5
3.5 Description of Cable Used.....	5
3.6 Measurement Uncertainty	5
3.7 Additions to, Deviations, or Exclusions from the Method	5
3.8 Laboratory Facility	5
3.9 Laboratory Location.....	5
3.10 Test Instruments List.....	6
4 Measurement Setup and Procedure	7
4.1 Test Setup	7
4.2 Test Procedure	9
5 Test Results.....	10
5.1 Summary	10
5.1.1 Clause and data summary	10
5.1.2 Test Limit.....	10
5.2 Conducted Emission	11
5.3 Radiated Emission	15

3 General Information

3.1 Client Information

Applicant:	INFINIX MOBILITY LIMITED
Address:	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG
Manufacturer:	INFINIX MOBILITY LIMITED
Address:	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG
Factory:	SHENZHEN TECNO TECHNOLOGY CO., LTD.
Address:	101, Building 24, Waijing Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen City, P.R.China

3.2 General Description of E.U.T.

Product Name:	Mobile Phone
Model No.:	X6710
Power Supply:	Rechargeable Li-ion Polymer Battery DC3.87V, 4900mAh
AC Adapter:	Model:U680XSA Input: AC100-240V, 50/60Hz, 2.0A Output: DC 5.0V, 2.0A or 11.0V, 6.2A or 4.0-21.0V, 3.25A 68.0W MAX
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

3.3 Test Mode

Operating Mode	Detail Description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+Recording mode	Keep the EUT in Charging+Recording mode
Charging+Playing mode	Keep the EUT in Charging+Playing mode
FM mode	Keep the EUT in FM receiver mode
GPS mode	Keep the EUT in GPS receiver mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

3.4 Description of Test Auxiliary Equipment

Manufacturer	Description	Model	S/N	FCC ID/DoC
Lenovo	Laptop	ThinkPad T14 Gen 1	SL10Z47277	DoC
HP	Printer	HP LaserJet P1007	VNFP409729	DoC

3.5 Description of Cable Used

Cable Type	Description	Length	From	To
Detached USB Cable	Shielding	1.0m	EUT	PC/Adapter
Detached headset cable	Unshielded	1.2m	EUT	Headset

3.6 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Conducted Emission for LISN (9kHz ~ 10MHz)	1.9 dB
Conducted Emission for LISN (10MHz ~ 30MHz)	2.6 dB
Radiated Emission (30MHz ~ 1GHz) (3m SAC)	3.8 dB
Radiated Emission (1GHz ~ 18GHz) (3m SAC)	3.6 dB

Note: All the measurement uncertainty value were shown with a coverage $k=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

3.7 Additions to, Deviations, or Exclusions from the Method

No

3.8 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

3.9 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

3.10 Test Instruments List


Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	04-14-2021	04-13-2024
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	03-08-2022	03-07-2023
				02-09-2023	02-08-2024
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-2	03-08-2022	03-07-2023
				02-09-2023	02-08-2024
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXJ001-2	01-20-2022	01-19-2023
				02-09-2023	02-08-2024
Pre-amplifier (1GHz ~ 18GHz)	SKET	LNPA_0118G-50	WXJ001-3	01-20-2022	01-19-2023
				01-10-2023	01-09-2024
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	03-05-2022	03-04-2023
				01-10-2023	01-09-2024
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	01-20-2022	01-19-2023
				01-10-2023	01-09-2024
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	01-20-2022	01-19-2023
				01-18-2023	01-17-2024
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG001-5	01-20-2022	01-19-2023
				01-18-2023	01-17-2024
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Test Software	Tonscend	TS+	Version: 3.0.0.1		

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESR3	WXJ003-2	07-12-2022	07-11-2023
LISN	Schwarzbeck	NSLK 8127	QCJ001-13	02-24-2022	02-23-2023
				01-10-2023	01-09-2024
LISN	Rohde & Schwarz	ESH3-Z5	WXJ005-1	03-30-2022	03-29-2023
LISN Coaxial Cable (9kHz ~ 30MHz)	JYTSZ	JYTCE-1G-NN-2M	WXG003-1	02-24-2022	02-23-2023
				02-22-2023	02-21-2024
RF Switch	TOP PRECISION	RSU0301	WXG003	N/A	
Test Software	AUDIX	E3	Version: 6.110919b		

4 Measurement Setup and Procedure

4.1 Test Setup

1) Conducted emission measurement:



Note: The detailed descriptions please refer to Figure 8 of ANSI C63.4:2014.

2) Radiated emission measurement:

Below 1GHz (3m SAC)






4.2 Test Procedure

Test method	Test step
Conducted emission	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 on conducted measurement.
Radiated emission	For below 1GHz: 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data. For above 1GHz: 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.

5.2 Conducted Emission

No light effect:

Product name:	Mobile Phone	Product model:	X6710
Test by:	Mike	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz		




	Freq	Read Level	LISN Factor	Aux2 Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.150	31.64	0.04	10.50	0.01	42.19	56.00	-13.81	Average
2	0.150	43.96	0.04	10.50	0.01	54.51	66.00	-11.49	QP
3	0.249	33.26	0.06	10.50	0.01	43.83	61.78	-17.95	QP
4	0.346	30.54	0.06	10.50	0.02	41.12	59.05	-17.93	QP
5	0.471	26.72	0.05	10.50	0.03	37.30	56.49	-19.19	QP
6	0.497	23.46	0.05	10.50	0.03	34.04	46.05	-12.01	Average
7	0.958	14.58	0.07	10.50	0.05	25.20	46.00	-20.80	Average
8	1.503	14.57	0.08	10.50	0.14	25.29	46.00	-20.71	Average
9	4.622	27.28	0.12	10.50	0.09	37.99	56.00	-18.01	QP
10	4.848	15.53	0.12	10.50	0.09	26.24	46.00	-19.76	Average
11	14.907	11.76	0.29	10.50	0.14	22.69	50.00	-27.31	Average
12	14.907	21.02	0.29	10.50	0.14	31.95	60.00	-28.05	QP

Remark:

1. Level = Read level + LISN Factor + Cable Loss.

Product name:	Mobile Phone	Product model:	X6710
Test by:	Mike	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz		



Trace: 7


	Freq	Read Level	LISN Factor	Aux2 Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.170	41.57	0.06	10.50	0.01	52.14	64.94	-12.80	QP
2	0.194	23.24	0.05	10.50	0.03	33.82	53.84	-20.02	Average
3	0.253	33.47	0.05	10.50	0.01	44.03	61.64	-17.61	QP
4	0.497	19.30	0.04	10.50	0.03	29.87	46.05	-16.18	Average
5	0.505	24.61	0.04	10.50	0.03	35.18	56.00	-20.82	QP
6	1.495	8.44	0.07	10.50	0.14	19.15	46.00	-26.85	Average
7	4.269	22.55	0.10	10.50	0.08	33.23	56.00	-22.77	QP
8	4.574	10.16	0.11	10.50	0.09	20.86	46.00	-25.14	Average
9	10.620	12.97	0.22	10.50	0.12	23.81	50.00	-26.19	Average
10	11.559	23.01	0.23	10.50	0.11	33.85	60.00	-26.15	QP
11	15.226	14.53	0.27	10.50	0.14	25.44	50.00	-24.56	Average
12	15.307	24.42	0.27	10.50	0.15	35.34	60.00	-24.66	QP

Remark:

1. Level = Read level + LISN Factor + Cable Loss.

Orange light effect:

Product name:	Mobile Phone	Product model:	X6710
Test by:	Mike	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz		




Trace: 33

	Freq	Read Level	LISN Factor	Aux2 Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.182	42.82	0.05	10.50	0.01	53.38	64.42	-11.04	QP
2	0.194	31.11	0.05	10.50	0.03	41.69	53.84	-12.15	Average
3	0.262	24.65	0.06	10.50	0.01	35.22	51.38	-16.16	Average
4	0.385	35.44	0.06	10.50	0.03	46.03	58.17	-12.14	QP
5	0.398	15.75	0.05	10.50	0.04	26.34	47.90	-21.56	Average
6	0.447	35.18	0.05	10.50	0.03	45.76	56.93	-11.17	QP
7	0.614	32.22	0.06	10.50	0.02	42.80	56.00	-13.20	QP
8	0.918	17.33	0.07	10.50	0.04	27.94	46.00	-18.06	Average
9	1.593	29.05	0.08	10.50	0.16	39.79	56.00	-16.21	QP
10	4.454	31.35	0.11	10.50	0.08	42.04	56.00	-13.96	QP
11	4.622	18.56	0.12	10.50	0.09	29.27	46.00	-16.73	Average
12	15.226	13.50	0.29	10.50	0.14	24.43	50.00	-25.57	Average

Remark:

1. Level = Read level + LISN Factor + Cable Loss.

Product name:	Mobile Phone	Product model:	X6710
Test by:	Mike	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz		



	Freq	Read Level	LISN Factor	Aux2 Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.154	30.98	0.06	10.50	0.01	41.55	55.78	-14.23	Average
2	0.154	48.00	0.06	10.50	0.01	58.57	65.78	-7.21	QP
3	0.202	26.75	0.05	10.50	0.04	37.34	53.54	-16.20	Average
4	0.277	20.41	0.05	10.50	0.02	30.98	50.90	-19.92	Average
5	0.346	39.51	0.05	10.50	0.02	50.08	59.05	-8.97	QP
6	0.466	39.61	0.04	10.50	0.03	50.18	56.58	-6.40	QP
7	0.953	18.38	0.06	10.50	0.05	28.99	46.00	-17.01	Average
8	1.229	28.65	0.06	10.50	0.10	39.31	56.00	-16.69	QP
9	4.797	14.81	0.11	10.50	0.09	25.51	46.00	-20.49	Average
10	4.926	26.76	0.11	10.50	0.09	37.46	56.00	-18.54	QP
11	11.257	18.74	0.23	10.50	0.11	29.58	50.00	-20.42	Average
12	11.498	27.49	0.23	10.50	0.11	38.33	60.00	-21.67	QP

Remark:


1. Level = Read level + LISN Factor + Cable Loss.

5.3 Radiated Emission

No light effect:

Below 1GHz:

Product Name:	Mobile Phone	Product Model:	X6710
Test By:	Mike	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	48.0420	31.65	18.87	-12.78	40.00	21.13	PK	Vertical
2	65.2110	37.22	22.36	-14.86	40.00	17.64	PK	Vertical
3	107.988	44.26	29.53	-14.73	43.50	13.97	PK	Vertical
4	249.996	35.84	21.84	-14.00	46.00	24.16	PK	Vertical
5	500.013	37.66	28.67	-8.99	46.00	17.33	PK	Vertical
6	890.002	34.66	31.89	-2.77	46.00	14.11	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6710
Test By:	Mike	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Suspected Data List


NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	65.5020	34.42	19.43	-14.99	40.00	20.57	PK	Horizontal
2	107.988	33.57	18.84	-14.73	43.50	24.66	PK	Horizontal
3	246.407	43.03	28.96	-14.07	46.00	17.04	PK	Horizontal
4	399.424	40.20	29.39	-10.81	46.00	16.61	PK	Horizontal
5	705.459	46.81	41.34	-5.47	46.00	4.66	PK	Horizontal
6	960.036	42.19	40.07	-2.12	54.00	13.93	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Above 1GHz:

Product Name:	Mobile Phone	Product Model:	X6710
Test By:	Mike	Test mode:	PC mode
Test Frequency:	1000 MHz ~ 6000 MHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1598.75	69.57	-22.45	47.12	74.00	26.88	PK	Vertical
2	1598.75	60.30	-22.45	37.85	54.00	16.15	AV	Vertical
3	5100.62	56.02	-7.60	48.42	74.00	25.58	PK	Vertical
4	5128.75	48.26	-7.48	40.78	54.00	13.22	AV	Vertical
5	5816.25	55.19	-4.72	50.47	74.00	23.53	PK	Vertical
6	5836.87	46.93	-4.61	42.32	54.00	11.68	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6710
Test By:	Mike	Test mode:	PC mode
Test Frequency:	1000 MHz ~ 6000 MHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1725.62	57.58	-22.09	35.49	54.00	18.51	AV	Horizontal
2	1740.00	64.83	-22.06	42.77	74.00	31.23	PK	Horizontal
3	4926.87	48.10	-8.21	39.89	54.00	14.11	AV	Horizontal
4	4966.87	56.66	-7.99	48.67	74.00	25.33	PK	Horizontal
5	5751.87	55.97	-4.91	51.06	74.00	22.94	PK	Horizontal
6	5751.87	49.16	-4.91	44.25	54.00	9.75	AV	Horizontal


Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Orange light effect:

Below 1GHz:

Product Name:	Mobile Phone	Product Model:	X6710
Test By:	Mike	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	47.9450	32.60	19.82	-12.78	40.00	20.18	PK	Vertical
2	65.2595	36.51	21.63	-14.88	40.00	18.37	PK	Vertical
3	107.988	41.47	26.74	-14.73	43.50	16.76	PK	Vertical
4	394.477	37.14	26.26	-10.88	46.00	19.74	PK	Vertical
5	500.013	37.70	28.71	-8.99	46.00	17.29	PK	Vertical
6	960.036	32.61	30.49	-2.12	54.00	23.51	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6710
Test By:	Mike	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Suspected Data List


NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	65.2110	33.74	18.88	-14.86	40.00	21.12	PK	Horizontal
2	254.943	43.02	29.08	-13.94	46.00	16.92	PK	Horizontal
3	398.357	39.42	28.60	-10.82	46.00	17.40	PK	Horizontal
4	500.013	37.07	28.08	-8.99	46.00	17.92	PK	Horizontal
5	870.796	36.65	33.62	-3.03	46.00	12.38	PK	Horizontal
6	960.036	42.40	40.28	-2.12	54.00	13.72	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Above 1GHz:

Product Name:	Mobile Phone	Product Model:	X6710
Test By:	Mike	Test mode:	PC mode
Test Frequency:	1000 MHz ~ 6000 MHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1599.37	68.47	-22.45	46.02	74.00	27.98	PK	Vertical
2	1754.37	59.94	-22.02	37.92	54.00	16.08	AV	Vertical
3	5305.62	55.97	-6.52	49.45	74.00	24.55	PK	Vertical
4	5324.37	47.49	-6.40	41.09	54.00	12.91	AV	Vertical
5	5819.37	55.90	-4.70	51.20	74.00	22.80	PK	Vertical
6	5825.00	46.96	-4.67	42.29	54.00	11.71	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6710
Test By:	Mike	Test mode:	PC mode
Test Frequency:	1000 MHz ~ 6000 MHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1345.62	62.87	-22.47	40.40	74.00	33.60	PK	Horizontal
2	1365.00	55.61	-22.44	33.17	54.00	20.83	AV	Horizontal
3	5080.62	46.27	-7.64	38.63	54.00	15.37	AV	Horizontal
4	5080.62	55.82	-7.64	48.18	74.00	25.82	PK	Horizontal
5	5791.87	55.35	-4.83	50.52	74.00	23.48	PK	Horizontal
6	5791.87	46.21	-4.83	41.38	54.00	12.62	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

-----End of report-----