



For Question,  
Please Contact with WSCT  
www.wsct-cert.com

# TEST REPORT

FCC ID: 2A1ZN-X6720B

Product: Mobile Phone

Model No.: X6720B

Trade Mark: Infinix

Report No.: WSCT-ANAB-R&E240700032A-Part96

Issued Date: 12 August 2024

Issued for:

INFINIX MOBILITY LIMITED  
FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI  
STREET FOTAN NT HONGKONG

Issued By:

World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.  
Building A-B, Baoli'an Industrial Park, No. 58 Tangtou Avenue, Shiyuan Street,  
Bao'an District, Shenzhen, Guangdong, China


TEL: +86-755-26996192

FAX: +86-755-86376605



**Note:** This report shall not be reproduced except in full, without the written approval of World

Standardization Certification & Testing Group (Shenzhen) Co., Ltd. This document may be altered  
or revised by World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. personnel  
only, and shall be noted in the revision section of the document. The test results in the report only  
apply to the tested sample.



世标检测认证股份  
World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.

**TABLE OF CONTENTS**

|   |           |
|---|-----------|
| <b>1. GENERAL INFORMATION .....</b>                         | <b>3</b>  |
| <b>2. GENERAL DESCRIPTION OF EUT .....</b>                  | <b>4</b>  |
| <b>3. FACILITIES AND ACCREDITATIONS.....</b>                | <b>5</b>  |
| 3.1. FACILITIES .....                                       | 5         |
| 3.2. ACCREDITATIONS .....                                   | 5         |
| 3.3. EUT SYSTEM CONFIGURATION .....                         | 6         |
| 3.4. DESCRIPTION OF TEST CHANNELS AND TEST MODES .....      | 7         |
| 3.5. EQUIPMENT MODIFICATIONS .....                          | 8         |
| <b>4. SUMMARY OF TEST REQUIREMENTS AND RESULTS .....</b>    | <b>9</b>  |
| <b>5. MEASUREMENT INSTRUMENTS .....</b>                     | <b>10</b> |
| <b>6. Transmitter Radiated Power (EIRP/ERP) .....</b>       | <b>11</b> |
| <b>7. Peak to Average Ratio .....</b>                       | <b>14</b> |
| 7.2. TEST RESULT .....                                      | 16        |
| <b>8. SPURIOUS EMISSION (Conducted and Radiated) .....</b>  | <b>17</b> |
| 8.1. MEASUREMENT RESULT (PRE-MEASUREMENT).....              | 17        |
| <b>9. OCCUPIED BANDWIDTH&amp; EMISSION BANDWIDTH .....</b>  | <b>28</b> |
| 9.1. MEASUREMENT RESULT .....                               | 30        |
| <b>10. BAND EDGE .....</b>                                  | <b>31</b> |
| 10.1. MEASUREMENT RESULT .....                              | 32        |
| <b>11. SPURIOUS EMISSION (Conducted and Radiated) .....</b> | <b>33</b> |
| 11.1. MEASUREMENT RESULT .....                              | 34        |
| <b>12. FREQUENCY STABILITY .....</b>                        | <b>35</b> |
| 12.1. MEASUREMENT RESULT (WORST).....                       | 36        |
| <b>13. Test Setup Photographs .....</b>                     | <b>37</b> |



For Question,  
Please Contact with WSCT  
[www.wsct-cert.com](http://www.wsct-cert.com)

## 1. GENERAL INFORMATION

|                       |  |
|-----------------------|--|
| Product:              | Mobile Phone   |
| Model No.:            | X6720B   |
| Additional Model:     | Infinix  |
| Applicant:            | <b>INFINIX MOBILITY LIMITED</b><br>FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG |
| Manufacturer:         | <b>INFINIX MOBILITY LIMITED</b><br>FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG |
| Date of receipt:      | 16 June 2024   |
| Date of Test:         | 17 June 2024 to 09 August 2024   |
| Applicable Standards: | FCC CFR Title 47 Part 96<br>ANSI C63.26-2015   |

The above equipment has been tested by World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. And found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: Wang Xiang  
( Wang Xiang)

Checked By: Qin Shuiquan  
( Qin Shuiquan)

Approved By: Liu Fuxin  
(Liu Fuxin)

Date: 12 August 2024



世标检测认证股份

World Standardization Certification &amp; Testing Group (Shenzhen) Co.,Ltd.

ADD:Building A-B, Baol'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com [Http://www.wsct-cert.com](http://www.wsct-cert.com)

Member of the WSCT INC.



## 2. GENERAL DESCRIPTION OF EUT

|                                 |   |
|---------------------------------|---|
| Equipment Type:                 | Mobile Phone  |
| Model                           | X6720B  |
| Trade Mark                      | Infinix   |
| Software version:               | X6720-H353RS-U-OP-240531V276  |
| Hardware version:               | V1.2  |
| Operating Bands                 | TDD 5G NR Band 77/78  |
| Antenna Type:                   | FIPA Antenna  |
| Antenna gain:                   | 5G NR 77/78: -2.92dbi   |
| Radiated Power (EIRP/ERP) Limit | 5G NR 77/78: 1.00W(30.00dBm)  |
| Operation Frequency Range:      | NR Band77:3550-3700 MHz(TX), 3700-3980 MHz(RX);<br>NR Band78:3550-3700 MHz(TX), 3700-3800 MHz(RX);  |
| Modulation Type                 | NR: BPSK/ QPSK/16QAM/64QAM/256QAM   |
| Operating Voltage:              | Adapter: U180XSA<br>Input: 100-240V~50/60Hz 0.6A<br>Output: 5.0V~2.4A or 7.5V~2.4A 18.0W MAX<br>Rechargeable Li-ion Polymer Battery Model: BL-5ABX<br>Rated Voltage: 3.87V<br>Rated Capacity: 4900mAh/18.97Wh<br>Typical Capacity: 5000mAh/19.35Wh<br>Limited Charge Voltage: 4.45V |
| Max power:                      | See Table 2.1   |
| Remark:                         | N/A.  |

Note: 1. The EUT is a Mobile Phone, supporting dual SIM card slots under the same transceiver. Both SIM card slots support NR and both SIM card slots share the same transceiver, so only SIM1 is tested in this report.

2. The antenna gain provided by the applicant, and the laboratory will not be responsible for the accumulated calculation results which covers the information provided by the applicant.

3. N/A stands for no applicable.

4. Antenna gain provided by the customer.





For Question,  
Please Contact with WSCT  
[www.wsct-cert.com](http://www.wsct-cert.com)

### 3. FACILITIES AND ACCREDITATIONS

#### 3.1. Facilities

All measurement facilities used to collect the measurement data are located at **Building A-B, Baoli'an Industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District, Shenzhen, Guangdong, China** of the World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

#### 3.2. ACCREDITATIONS

##### CNAS - Registration Number: L3732

China National Accreditation Service for Conformity Assessment, The test firm Registration Number: L3732

##### FCC - Designation Number: CN1303

World Standardization Certification & Testing Group(Shenzhen) CO., LTD. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Designation Number: CN1303.

##### ANAB - Certificate Number: AT-3951

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (ANAB).Certification Number: AT-3951



世标检测认证股份

World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong china  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: [www.wsct-cert.com](http://www.wsct-cert.com)


Member of the WSCT INC.



### 3.3. EUT System Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

**Fig. 3.2-1 Configuration of EUT System**



**Table 3.2-1 Equipment Used in EUT System**

| Item | Equipment | Model No. | ID or Specification | Note        |
|------|-----------|-----------|---------------------|-------------|
| 1    | Adapter   | U180XSA   |                     | Accessories |

\*\*\*Note: All the accessories have been used during the test. The following "EUT" in setup diagram means EUT system.



### 3.4. Description Of Test Channels And Test Modes

#### Test channels:

| NR n77(3550-3700Mhz) |           |            |                |
|----------------------|-----------|------------|----------------|
| Test Channel         | BW(MHz)   | UL Channel | Frequency(MHz) |
| Low Range            | 10        | 637000     | 3560           |
|                      | 50        | 638334     | 3575           |
|                      | 100       | 640000     | 3600           |
| Mid Range            | 10/50/100 | 641666     | 3625           |
| High Range           | 10        | 646332     | 3695           |
|                      | 50        | 645000     | 3675           |
|                      | 100       | 643332     | 3650           |

| NR n78(3550-3700Mhz) |           |            |                |
|----------------------|-----------|------------|----------------|
| Test Channel         | BW(MHz)   | UL Channel | Frequency(MHz) |
| Low Range            | 10        | 637000     | 3560           |
|                      | 50        | 638334     | 3575           |
|                      | 100       | 640000     | 3600           |
| Mid Range            | 10/50/100 | 641666     | 3625           |
| High Range           | 10        | 646332     | 3695           |
|                      | 50        | 645000     | 3675           |
|                      | 100       | 643332     | 3650           |

Note 1: BPSK&QPSK&16QAM&QAM64&QAM256 modulation has been measured;

Note 2: The worst condition was recorded in the test report if no other modes test data.



世标检测认证股份

World Standardization Certification &amp; Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com



For Question,  
Please Contact with WSCT  
[www.wsct-cert.com](http://www.wsct-cert.com)

### 3.5. Equipment Modifications

Not available for this EUT intended for grant.



世标检测认证股份

World Standardization Certification & Testing Group (Shenzhen) Co.,Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen, Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: [www.wsct-cert.com](http://www.wsct-cert.com)

Member of the WSCT INC.



## 4. SUMMARY OF TEST REQUIREMENTS AND RESULTS

| No. | Description                            | FCC Part No.   | Test Verdict | Remark |
|-----|--|--|--------------|--------|
| 1   | Conducted RF Output Power              | 2.1046   | Pass         | --     |
| 2   | Effective (Isotropic) Radiated Power   | 2.1046<br>22.913(a)<br>24.232(c)<br>27.50<br>90.635(b)<br>90.542(a)<br>§90.1321(a) | Pass         | --     |
| 3   | Peak to Average Radio                  | 2.1046<br>22.913(d)<br>24.232(d)<br>27.50(d)                                       | Pass         | --     |
| 4   | Occupied Bandwidth                     | 2.1049<br>22.917(b)<br>24.238(b)<br>27.53<br>90.209                                | Pass         | --     |
| 5   | Frequency Stability                    | 2.1055<br>22.355<br>24.235<br>27.54<br>90.213                                      | Pass         | --     |
| 6   | Spurious Emission at Antenna Terminals | 2.1051<br>22.917<br>24.238<br>27.53<br>90.691<br>90.543                            | Pass         | --     |
| 7   | Band Edge                              | 2.1051<br>22.917<br>24.238<br>27.53<br>90.691<br>90.543                            | Pass         | --     |
| 8   | Field Strength of Spurious Radiation   | 2.1053<br>22.917<br>24.238<br>27.53<br>90.691<br>90.543                            | Pass         | --     |





## 5. MEASUREMENT INSTRUMENTS

| NAME OF EQUIPMENT                    | MANUFACTURER           | MODEL        | SERIAL NUMBER | Calibration Date | Calibration Due. |
|--------------------------------------|------------------------|--------------|---------------|------------------|------------------|
| EMI Test Receiver                    | R&S                    | ESCI         | 100005        | 11/05/2023       | 11/04/2024       |
| LISN                                 | AFJ                    | LS16         | 16010222119   | 11/05/2023       | 11/04/2024       |
| LISN(EUT)                            | Mestec                 | AN3016       | 04/10040      | 11/05/2023       | 11/04/2024       |
| Universal Radio Communication Tester | R&S                    | CMU 200      | 1100.0008.02  | 11/05/2023       | 11/04/2024       |
| Coaxial cable                        | Megalon                | LMR400       | N/A           | 11/05/2023       | 11/04/2024       |
| GPIO cable                           | Megalon                | GPIB         | N/A           | 11/05/2023       | 11/04/2024       |
| Spectrum Analyzer                    | R&S                    | FSU          | 100114        | 11/05/2023       | 11/04/2024       |
| Pre Amplifier                        | H.P.                   | HP8447E      | 2945A02715    | 11/05/2023       | 11/04/2024       |
| Pre-Amplifier                        | CDSI                   | PAP-1G18-38  | --            | 11/05/2023       | 11/04/2024       |
| Loop Antenna                         | R&S                    | HFH2-Z2      | 100296        | 11/05/2023       | 11/04/2024       |
| Bi-log Antenna                       | SCHWARZBECK            | VULB9168     | 01488         | 7/29/2024        | 7/28/2025        |
| 9*6*6 Anechoic                       | --                     | --           | --            | 11/05/2023       | 11/04/2024       |
| Horn Antenna                         | COMPLIANCE ENGINEERING | CE18000      | --            | 11/05/2023       | 11/04/2024       |
| Horn Antenna                         | SCHWARZBECK            | BBHA9120D    | 9120D-631     | 11/05/2023       | 11/04/2024       |
| Power meter                          | Anritsu                | ML2487A      | 6K00003613    | 11/05/2023       | 11/04/2024       |
| Power meter                          | Anritsu                | MA2491A      | 32263         | 11/05/2023       | 11/04/2024       |
| Cable                                | TIME MICROWAVE         | LMR-400      | N-TYPE04      | 11/05/2023       | 11/04/2024       |
| System-Controller                    | CCS                    | N/A          | N/A           | N.C.R            | N.C.R            |
| Turn Table                           | CCS                    | N/A          | N/A           | N.C.R            | N.C.R            |
| Antenna Tower                        | CCS                    | N/A          | N/A           | N.C.R            | N.C.R            |
| RF cable                             | Murata                 | MXHQ87WA3000 | -             | 11/05/2023       | 11/04/2024       |
| Loop Antenna                         | EMCO                   | 6502         | 00042960      | 11/05/2023       | 11/04/2024       |
| Wideband Radio Communication Tester  | R&S                    | CMW 500      | 103974        | 11/05/2023       | 11/04/2024       |
| Horn Antenna                         | SCHWARZBECK            | BBHA 9170    | 1123          | 11/05/2023       | 11/04/2024       |
| H & T Chamber                        | Guangzhou gongwen      | GDJS-500-40  | 0329          | 11/05/2023       | 11/04/2024       |
| UXM 5G Wireless Test Platform        | KEYSIGHT               | E7515B       | MY60192341    | 11/05/2023       | 11/04/2024       |
| Anechoic chamber                     | SAEMC                  | 966          | -             | 11/05/2023       | 11/04/2024       |
| Spectrum Analyzer                    | KEYSIGHT               | N9010B       | MY60241089    | 11/05/2023       | 11/04/2024       |



For Question,  
Please Contact with WSCT  
www.wsct-cert.com

## 6. Transmitter Radiated Power (EIRP/ERP)

### Test limit:

FCC § 2.1046 & 22.913(a) & 24.232(c) & 27.50(a) & 27.50(b) & 27.50(c) & 27.50(d) & 27.50(h) & 27.50(j) & 27.50(k) & 90.635(b) & 90.542(a)

According to FCC section 22.913(a) (5), the Effective Radiated Power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC section 24.232(c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to FCC section 27.50(a) (3), for mobile and portable stations transmitting in the 2305-2315MHz band or the 2350-2360MHz band, the average EIRP must not exceed 50 mill watts within any 1 megahertz of authorized bandwidth, except that for mobile and portable stations compliant with 3GPP LTE standards. For mobile and portable stations using time division depleting (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands.

FCC section 27.50(b) (10), portable stations (hand-held devices) transmitting in the 746-757MHz, 776-788MHz, and 805-806MHz bands are limited to 3 watts ERP.

FCC section 27.50(c) (10), portable stations (hand-held devices) in the 600MHz uplink band and the 698-746MHz band, and fixed and mobile stations in the 600MHz uplink band are limited to 3 watts ERP.

FCC section 27.50(d) (4), fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

(7) Fixed, mobile, and portable (hand-held) stations operating in the 2000-2020 MHz band are limited to 2 watts EIRP.

And FCC section 27.50(h) (2), for mobile and other user stations, mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

FCC section 27.50(j) (3), for mobile, and portable (hand-held) stations operating in the 3700-3980 MHz band are limited to 1 watt EIRP.

FCC section 27.50(k) (3), Mobile devices are limited to 1Watt (30 dBm) EIRP in the 3450-3550 MHz band.

### Test procedure:

#### Description of the Conducted Output Power Measurement

The EUT is coupled to the SS with attenuator through power splitter; the RF load attached to EUT antenna terminal is 50Ω; the path loss as the factor is calibrated to correct the reading. A system simulator is used to establish communication with the EUT, and its parameters are set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The relevant equation for determining the conducted measured value is:

Conducted Output Power Value (dBm) = Measured Value (dBm) + Path Loss (dB)

where:

Conducted Output Power Value = final conducted measured value in the conducted power test, in dBm;

Measured Value = measured conducted power received by spectrum analyzer or power meter, in dBm;

Path Loss = signal attenuation in the connecting cable between the transmitter and spectrum analyzer or power meter, including external cable loss, in dB;

During the test, the data of Path Loss (dB) is added in the spectrum analyzer or power meter, so Measured Value (dBm) is the final values which contains the data of Path Loss (dB).



世标检测认证股份

World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.

**Description of the Transmitter Radiated Power Measurement**

In many cases, the RF output power limits for licensed digital transmission devices is specified in terms of effective radiated power (ERP) or equivalent isotropic radiated power (EIRP). Typically, ERP is specified when the operating frequency is less than or equal to 1 GHz and EIRP is specified when the operating frequency is greater than 1 GHz. Both are determined by adding the transmit antenna gain to the conducted RF output power with the primary difference between the two being that when determining the ERP, the transmit antenna gain is referenced to a dipole antenna (i.e., dBd) whereas when determining the EIRP, the transmit antenna gain is referenced to an isotropic antenna (dBi).

**Final measurement calculation as below**

The relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP/EIRP} = \text{PMeas} + \text{GT} - \text{LC}$$

where:

ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as PMeas, typically dBW or dBm);

PMeas = measured transmitter output power or PSD, in dBm or dBW;

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

dBd (ERP)=dBi (EIRP) -2.15 dB

LC = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

For devices utilizing multiple antennas, KDB 662911 provides guidance for determining the effective array transmit antenna gain term to be used in the above equation.

The relevant equation for determining the ERP/EIRP from the radiated RF output power is:

$$\text{ERP/EIRP (dBm)} = \text{SA Read Value (dBm)} + \text{Correction Factor (dB)}$$

where:

ERP/EIRP = effective or equivalent radiated power, in dBm;

SA Read Value = measured transmitter power received by EMI receiver or spectrum analyzer, in dBm;

Correction Factor = total correction factor including cable loss, in dB;

During the test, the data of Correction Factor (dB) is added in the EMI receiver or spectrum analyzer, so SA Read Value (dBm) is the final values which contains the data of Correction Factor (dB).



世标检测认证股份

World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.

Report No.: WSCT-ANAB-R&E240700032A-Part96  
**Test Result**

Note 1: For the HSDPA and HSUPA mode, all subtests were tested and just the worst data we rerecorded in this table.

Note 2:  $ERP/EIRP = PMeas + GT - LC$ 

ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as PMeas, typically dBW or dBm);

PMeas = measured transmitter output power or PSD, in dBm or dBW;

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

LC = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

ERP = EIRP - 2.15; where ERP and EIRP are expressed in consistent units.

| Operation Band (s)        | Power Class | Modulation Type | Maximum conducted output power (dBm) | ERP/EIRP (dBm) |
|---------------------------|-------------|-----------------|--------------------------------------|----------------|
| NR n77<br>(3550-3700 Mhz) | Class 3     | BPSK            | 25.91                                | 22.99          |
|                           | Class 3     | QPSK            | 25.99                                | 22.98          |
|                           | Class 3     | 16QAM           | 25.59                                | 22.67          |
|                           | Class 3     | 64QAM           | 24.17                                | 21.25          |
|                           | Class 3     | 256QAM          | 21.92                                | 19.00          |
| NR n78<br>(3550-7000 Mhz) | Class 3     | BPSK            | 25.85                                | 22.93          |
|                           | Class 3     | QPSK            | 25.77                                | 22.85          |
|                           | Class 3     | 16QAM           | 25.4                                 | 22.48          |
|                           | Class 3     | 64QAM           | 24.04                                | 21.12          |
|                           | Class 3     | 256QAM          | 22.14                                | 19.22          |

Note: Please refer to Annex (NR Chapter 1 Transmitter Radiated Power) for more test data



世标检测认证股份

World Standardization Certification &amp; Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.



For Question,  
Please Contact with WSCT  
www.wsct-cert.com

## 7. Peak to Average Ratio

### 7.1.1. Limit

FCC § 2.1046 & 24.232(d) & 27.50(d) & 27.50(j) & 27.50(k)

In addition, when the transmitter power is measured in terms of average value, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.

According to FCC section 24.232(d), power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with 24.232 (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of § 24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

FCC section 24.232(e), peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

According to FCC section 27.50(d) (5) & 27.50(j) & 27.50(k), in measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13dB.

### 7.1.2. Test Procedure

Here the lowest, middle and highest channels are selected to perform testing to verify the peak-to-average ratio.

According to KDB 971168 D01, there is CCDF procedure for PAPR:

- Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
- Set the number of counts to a value that stabilizes the measured CCDF curve;
- Set the measurement interval as follows:  
1) for continuous transmissions, set to 1 ms,



世标检测认证股份

World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.



2) for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.

e) Record the maximum PAPR level associated with a probability of 0.1%.





For Question,  
Please Contact with WSCT  
[www.wsct-cert.com](http://www.wsct-cert.com)

## 7.2. Test Result

Note: Please refer to Annex (NR Chapter 2 Peak-to-Average Ratio) for more test data





## 8. SPURIOUS EMISSION (Conducted and Radiated)

## 8.1. Measurement Result (Pre-measurement)



| Bandwidth | UL Channel | Frequency | Modulation | RB Size | RB Offset | Judgment |
|-----------|------------|-----------|------------|---------|-----------|----------|
| 10        | 637000     | 3560      | BPSK       | 50      | LOW       | Pass     |
| 10        | 637000     | 3560      | QPSK       | 50      | LOW       | Pass     |
| 10        | 637000     | 3560      | 16QAM      | 50      | LOW       | Pass     |
| 10        | 637000     | 3560      | 64QAM      | 50      | LOW       | Pass     |
| 10        | 637000     | 3560      | 256QAM     | 50      | LOW       | Pass     |
| 10        | 641666     | 3625      | BPSK       | 50      | LOW       | Pass     |
| 10        | 641666     | 3625      | QPSK       | 50      | LOW       | Pass     |
| 10        | 641666     | 3625      | 16QAM      | 50      | LOW       | Pass     |
| 10        | 641666     | 3625      | 64QAM      | 50      | LOW       | Pass     |
| 10        | 641666     | 3625      | 256QAM     | 50      | LOW       | Pass     |
| 10        | 665000     | 3975      | BPSK       | 50      | LOW       | Pass     |
| 10        | 665000     | 3975      | QPSK       | 50      | LOW       | Pass     |
| 10        | 665000     | 3975      | 16QAM      | 50      | LOW       | Pass     |
| 10        | 665000     | 3975      | 64QAM      | 50      | LOW       | Pass     |
| 10        | 665000     | 3975      | 256QAM     | 50      | LOW       | Pass     |
| 50        | 638334     | 3575      | BPSK       | 75      | LOW       | Pass     |
| 50        | 638334     | 3575      | QPSK       | 75      | LOW       | Pass     |
| 50        | 638334     | 3575      | 16QAM      | 75      | LOW       | Pass     |
| 50        | 638334     | 3575      | 64QAM      | 75      | LOW       | Pass     |
| 50        | 638334     | 3575      | 256QAM     | 75      | LOW       | Pass     |
| 50        | 641666     | 3625      | BPSK       | 75      | LOW       | Pass     |
| 50        | 641666     | 3625      | QPSK       | 75      | LOW       | Pass     |
| 50        | 641666     | 3625      | 16QAM      | 75      | LOW       | Pass     |
| 50        | 641666     | 3625      | 64QAM      | 75      | LOW       | Pass     |
| 50        | 641666     | 3625      | 256QAM     | 75      | LOW       | Pass     |
| 50        | 645000     | 3675      | BPSK       | 75      | LOW       | Pass     |
| 50        | 645000     | 3675      | QPSK       | 75      | LOW       | Pass     |
| 50        | 645000     | 3675      | 16QAM      | 75      | LOW       | Pass     |
| 50        | 645000     | 3675      | 64QAM      | 75      | LOW       | Pass     |
| 50        | 645000     | 3675      | 256QAM     | 75      | LOW       | Pass     |
| 100       | 640000     | 3600      | BPSK       | 100     | LOW       | Pass     |
| 100       | 640000     | 3600      | QPSK       | 100     | LOW       | Pass     |
| 100       | 640000     | 3600      | 16QAM      | 100     | LOW       | Pass     |
| 100       | 640000     | 3600      | 64QAM      | 100     | LOW       | Pass     |
| 100       | 640000     | 3600      | 256QAM     | 100     | LOW       | Pass     |
| 100       | 641666     | 3625      | BPSK       | 100     | LOW       | Pass     |
| 100       | 641666     | 3625      | QPSK       | 100     | LOW       | Pass     |
| 100       | 641666     | 3625      | 16QAM      | 100     | LOW       | Pass     |
| 100       | 641666     | 3625      | 64QAM      | 100     | LOW       | Pass     |
| 100       | 641666     | 3625      | 256QAM     | 100     | LOW       | Pass     |
| 100       | 643332     | 3650      | BPSK       | 100     | LOW       | Pass     |
| 100       | 643332     | 3650      | QPSK       | 100     | LOW       | Pass     |
| 100       | 643332     | 3650      | 16QAM      | 100     | LOW       | Pass     |
| 100       | 643332     | 3650      | 64QAM      | 100     | LOW       | Pass     |
| 100       | 643332     | 3650      | 256QAM     | 100     | LOW       | Pass     |





## NR n78(3550-3700Mhz):

| Bandwidth | UL Channel | Frequency | Modulation | RB Size | RB Offset | Judgment |
|-----------|------------|-----------|------------|---------|-----------|----------|
| 10        | 637000     | 3560      | BPSK       | 50      | LOW       | Pass     |
| 10        | 637000     | 3560      | QPSK       | 50      | LOW       | Pass     |
| 10        | 637000     | 3560      | 16QAM      | 50      | LOW       | Pass     |
| 10        | 637000     | 3560      | 64QAM      | 50      | LOW       | Pass     |
| 10        | 637000     | 3560      | 256QAM     | 50      | LOW       | Pass     |
| 10        | 641666     | 3625      | BPSK       | 50      | LOW       | Pass     |
| 10        | 641666     | 3625      | QPSK       | 50      | LOW       | Pass     |
| 10        | 641666     | 3625      | 16QAM      | 50      | LOW       | Pass     |
| 10        | 641666     | 3625      | 64QAM      | 50      | LOW       | Pass     |
| 10        | 641666     | 3625      | 256QAM     | 50      | LOW       | Pass     |
| 10        | 665000     | 3975      | BPSK       | 50      | LOW       | Pass     |
| 10        | 665000     | 3975      | QPSK       | 50      | LOW       | Pass     |
| 10        | 665000     | 3975      | 16QAM      | 50      | LOW       | Pass     |
| 10        | 665000     | 3975      | 64QAM      | 50      | LOW       | Pass     |
| 10        | 665000     | 3975      | 256QAM     | 50      | LOW       | Pass     |
| 50        | 638334     | 3575      | BPSK       | 75      | LOW       | Pass     |
| 50        | 638334     | 3575      | QPSK       | 75      | LOW       | Pass     |
| 50        | 638334     | 3575      | 16QAM      | 75      | LOW       | Pass     |
| 50        | 638334     | 3575      | 64QAM      | 75      | LOW       | Pass     |
| 50        | 638334     | 3575      | 256QAM     | 75      | LOW       | Pass     |
| 50        | 641666     | 3625      | BPSK       | 75      | LOW       | Pass     |
| 50        | 641666     | 3625      | QPSK       | 75      | LOW       | Pass     |
| 50        | 641666     | 3625      | 16QAM      | 75      | LOW       | Pass     |
| 50        | 641666     | 3625      | 64QAM      | 75      | LOW       | Pass     |
| 50        | 641666     | 3625      | 256QAM     | 75      | LOW       | Pass     |
| 50        | 645000     | 3675      | BPSK       | 75      | LOW       | Pass     |
| 50        | 645000     | 3675      | QPSK       | 75      | LOW       | Pass     |
| 50        | 645000     | 3675      | 16QAM      | 75      | LOW       | Pass     |
| 50        | 645000     | 3675      | 64QAM      | 75      | LOW       | Pass     |
| 50        | 645000     | 3675      | 256QAM     | 75      | LOW       | Pass     |
| 100       | 640000     | 3600      | BPSK       | 100     | LOW       | Pass     |
| 100       | 640000     | 3600      | QPSK       | 100     | LOW       | Pass     |
| 100       | 640000     | 3600      | 16QAM      | 100     | LOW       | Pass     |
| 100       | 640000     | 3600      | 64QAM      | 100     | LOW       | Pass     |
| 100       | 640000     | 3600      | 256QAM     | 100     | LOW       | Pass     |
| 100       | 641666     | 3625      | BPSK       | 100     | LOW       | Pass     |
| 100       | 641666     | 3625      | QPSK       | 100     | LOW       | Pass     |
| 100       | 641666     | 3625      | 16QAM      | 100     | LOW       | Pass     |
| 100       | 641666     | 3625      | 64QAM      | 100     | LOW       | Pass     |
| 100       | 641666     | 3625      | 256QAM     | 100     | LOW       | Pass     |
| 100       | 643332     | 3650      | BPSK       | 100     | LOW       | Pass     |
| 100       | 643332     | 3650      | QPSK       | 100     | LOW       | Pass     |
| 100       | 643332     | 3650      | 16QAM      | 100     | LOW       | Pass     |
| 100       | 643332     | 3650      | 64QAM      | 100     | LOW       | Pass     |
| 100       | 643332     | 3650      | 256QAM     | 100     | LOW       | Pass     |

Test Plot(s)



世标检测认证股份

World Standardization Certification &amp; Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong china  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.


**Conducted method****Test limit:**

The spurious (unwanted) emission limits specified in the individual FCC rule parts applicable to licensed digital transmitters (typically referred to under the heading 'emission limits') normally apply to any and all emissions that are present outside of the authorized frequency band/block and apply to emissions in both the out-of-band and spurious domains. In some rule parts, the unwanted emission limits are specified by an emission mask that defines the applicable limit as a function of the frequency range relative to the authorized frequency block.

Typically, unwanted emissions are required by the licensed rule parts to be attenuated below the transmitter power by a factor of at least  $X + 10\log(P)$  dB, where  $P$  represents the transmitter power expressed in watts and  $X$  is a specified scalar value (e.g., 43). This specification can be interpreted in one of two equivalent ways. First, the required attenuation can be construed to be relative to the mean carrier power, with the resultant of the equation  $X + 10\log(P)$  being expressed in dBc (dB relative to the maximum carrier power). Alternatively, the specification can be interpreted as an absolute limit when the specified attenuation is actually subtracted from the maximum permissible transmitter power [i.e.,  $10\log(P) - \{X + 10\log(P)\}$ ], resulting in an absolute level of  $-X$  dBW [or  $(-X + 30)$  dBm]. See section 4.

**Test procedure:**

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz below 1 GHz and 1 MHz above 1 GHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonics.

**Conducted Emission Test-Up:**

世标检测认证股份

World Standardization Certification &amp; Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong China  
 TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.



## Radiated method

### Test limit:

The spurious (unwanted) emission limits specified in the individual FCC rule parts applicable to licensed digital transmitters (typically referred to under the heading 'emission limits') normally apply to any and all emissions that are present outside of the authorized frequency band/block and apply to emissions in both the out-of-band and spurious domains. In some rule parts, the unwanted emission limits are specified by an emission mask that defines the applicable limit as a function of the frequency range relative to the authorized frequency block.

Typically, unwanted emissions are required by the licensed rule parts to be attenuated below the transmitter power by a factor of at least  $X + 10\log(P)$  dB, where  $P$  represents the transmitter power expressed in watts and  $X$  is a specified scalar value (e.g., 43). This specification can be interpreted in one of two equivalent ways. First, the required attenuation can be construed to be relative to the mean carrier power, with the resultant of the equation  $X + 10\log(P)$  being expressed in dBc (dB relative to the maximum carrier power). Alternatively, the specification can be interpreted as an absolute limit when the specified attenuation is actually subtracted from the maximum permissible transmitter power [i.e.,  $10\log(P) - \{X + 10\log(P)\}$ ], resulting in an absolute level of  $-X$  dBW [or  $(-X + 30)$  dBm]. See section 4.


For Question,  
Please Contact with WSCT  
[www.wsct-cert.com](http://www.wsct-cert.com)

### Test procedure:

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site. The resolution bandwidth of the spectrum analyzer was set at 100 kHz below 1 GHz and 1 MHz above 1 GHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonics.

### Test setup:

#### (A) Radiated Emission Test-Up Frequency 30MHz~1GHz



世标检测认证股份


World Standardization Certification &amp; Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: [www.wsct-cert.com](http://www.wsct-cert.com)

Member of the WSCT INC.



## (B) Radiated Emission Test-Up Frequency Above 1GHz

**Note:**

- 1, Below 30MHz no Spurious found.
- 2, UE is positioned at 3 axis at the pre-scan stage, and only the measurement of the worst case is reported in this part.



世标检测认证股份

World Standardization Certification &amp; Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong China  
 TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.



## List of final test modes:

n77(3550-3700Mhz):

| Channel | Bandwidth | UL Channel | Frequency | Modulation | RB Size | RB Offset | Judgment |
|---------|-----------|------------|-----------|------------|---------|-----------|----------|
| Middle  | 100       | 641666     | 3625      | QPSK       | 100     | LOW       | Pass     |

n78(3550-3700Mhz):

| Channel | Bandwidth | UL Channel | Frequency | Modulation | RB Size | RB Offset | Judgment |
|---------|-----------|------------|-----------|------------|---------|-----------|----------|
| Middle  | 100       | 641666     | 3625      | QPSK       | 100     | LOW       | Pass     |

Test record:

Note:

1. The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the  $A_{Rpl}$  is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below:

$$\text{Power} = P_{\text{Mea}} + A_{Rpl}$$

2.  $A_{Rpl} = \text{Cable loss} + \text{Antenna gain}$



世标检测认证股份

World Standardization Certification &amp; Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong china  
 TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com


Member of the WSCT INC.



n77(3550-3700Mhz):

Horizontal:

For Question,  
Please Contact with WSCT  
www.wsct-cert.com



| Suspected Data List |             |                 |             |               |            |             |         |            |       |         |  |
|---------------------|-------------|-----------------|-------------|---------------|------------|-------------|---------|------------|-------|---------|--|
| NO.                 | Freq. [MHz] | Reading [dB(m)] | Factor [dB] | Level [dB(m)] | Limit [dB] | Margin [dB] | Deg [°] | Polarity   | Trace | Verdict |  |
| 1                   | 1744.3750   | -57.03          | 0.76        | -57.79        | -13        | -44.03      | 0       | Horizontal | PK    | Pass    |  |
| 2                   | 3504.3750   | -46.3           | 10.47       | -56.77        | -13        | -33.3       | 0       | Horizontal | PK    | Pass    |  |
| 3                   | 4248.1250   | -52.59          | 17.6        | -70.19        | -13        | -39.59      | 201.9   | Horizontal | PK    | Pass    |  |
| 4                   | 8650.5000   | -64.96          | 37.26       | -102.22       | -13        | -51.96      | 360     | Horizontal | PK    | Pass    |  |
| 5                   | 10915.5000  | -61.06          | 39.38       | -100.44       | -13        | -48.06      | 16.6    | Horizontal | PK    | Pass    |  |
| 6                   | 14013.0000  | -56.82          | 41.48       | -98.3         | -13        | -43.82      | 264.6   | Horizontal | PK    | Pass    |  |




世标检测认证股份

World Standardization Certification &amp; Testing Group (Shenzhen) Co.,Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com



Vertical:



## Suspected Data List

| NO. | Freq. [MHz] | Reading [dB(m)] | Factor [dB] | Level [dB(m)] | Limit [dB] | Margin [dB] | Deg [°] | Polarity | Trace | Verdict |
|-----|-------------|-----------------|-------------|---------------|------------|-------------|---------|----------|-------|---------|
| 1   | 1752.5000   | -65.83          | 0.83        | -66.66        | -13        | -52.83      | 328.5   | Vertical | PK    | Pass    |
| 2   | 3404.3750   | -54.66          | 10.4        | -65.06        | -13        | -41.66      | 352.9   | Vertical | PK    | Pass    |
| 3   | 4250.6250   | -52.63          | 17.48       | -70.11        | -13        | -39.63      | 176.6   | Vertical | PK    | Pass    |
| 4   | 7671.0000   | -65.79          | 36.51       | -102.3        | -13        | -52.79      | 18.2    | Vertical | PK    | Pass    |
| 5   | 10237.5000  | -62.06          | 38.43       | -100.49       | -13        | -49.06      | 77      | Vertical | PK    | Pass    |
| 6   | 13908.0000  | -56.95          | 41.26       | -98.21        | -13        | -43.95      | 201.4   | Vertical | PK    | Pass    |



世标检测认证股份

World Standardization Certification &amp; Testing Group (Shenzhen) Co., Ltd.


ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com



n78(3550-3700Mhz):

Horizontal:

For Question,  
Please Contact with WSCT  
www.wsct-cert.com



## Suspected Data List

| NO. | Freq. [MHz] | Reading [dB(m)] | Factor [dB] | Level [dB(m)] | Limit [dB] | Margin [dB] | Deg [°] | Polarity   | Trace | Verdict |
|-----|-------------|-----------------|-------------|---------------|------------|-------------|---------|------------|-------|---------|
| 1   | 1981.8750   | -64.46          | 2.56        | -67.02        | -13        | -51.46      | 306     | Horizontal | PK    | Pass    |
| 2   | 3441.8750   | -53.46          | 10.43       | -63.89        | -13        | -40.46      | 144.6   | Horizontal | PK    | Pass    |
| 3   | 4243.1250   | -52.6           | 17.7        | -70.3         | -13        | -39.6       | 207.9   | Horizontal | PK    | Pass    |
| 4   | 7948.5000   | -65.7           | 36.92       | -102.62       | -13        | -52.7       | 92.6    | Horizontal | PK    | Pass    |
| 5   | 11424.0000  | -59.79          | 39.12       | -98.91        | -13        | -46.79      | 360.1   | Horizontal | PK    | Pass    |
| 6   | 15109.5000  | -57.62          | 39.86       | -97.48        | -13        | -44.62      | 209.7   | Horizontal | PK    | Pass    |



世标检测认证股份


World Standardization Certification &amp; Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen,Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.



Vertical:



## Suspected Data List

| NO. | Freq. [MHz] | Reading [dB(m)] | Factor [dB] | Level [dB(m)] | Limit [dB] | Margin [dB] | Deg [°] | Polarity | Trace | Verdict |
|-----|-------------|-----------------|-------------|---------------|------------|-------------|---------|----------|-------|---------|
| 1   | 2094.3750   | -64.26          | 3.27        | -67.53        | -13        | -51.26      | 114.6   | Vertical | PK    | Pass    |
| 2   | 3233.1250   | -58.42          | 10.3        | -68.72        | -13        | -45.42      | 0.1     | Vertical | PK    | Pass    |
| 3   | 4260.0000   | -51.99          | 17.03       | -69.02        | -13        | -38.99      | 173.2   | Vertical | PK    | Pass    |
| 4   | 9058.5000   | -65.2           | 37.44       | -102.64       | -13        | -52.2       | 1.3     | Vertical | PK    | Pass    |
| 5   | 10990.5000  | -60.21          | 39.49       | -99.7         | -13        | -47.21      | 1.3     | Vertical | PK    | Pass    |
| 6   | 14359.5000  | -57.28          | 41.03       | -98.31        | -13        | -44.28      | 36.2    | Vertical | PK    | Pass    |



For Question,  
Please Contact with WSCT  
www.wsct-cert.com

## 9. OCCUPIED BANDWIDTH & EMISSION BANDWIDTH

### Test limit:

The occupied bandwidth (OBW), that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission, shall be measured when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudo-random generators or other devices required in normal service. Additionally, the occupied bandwidth shall be shown for operation with any devices used for modifying the spectrum when such devices are optional at the discretion of the user. [§2.1049(h)]

Many of the individual rule parts specify a relative OBW in lieu of the 99% OBW. In such cases, the OBW is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated by at least X dB below the transmitter power, where the value of X is typically specified as 26.

The relative OBW must be measured and reported when it is specified in the applicable rule part; otherwise, the 99% OBW shall be measured and reported. The test report shall specify which OBW is reported.

A spectrum/signal analyzer or other instrument providing a spectral display is recommended for these measurements and the video bandwidth shall be set to a value at least three times greater than the IF/resolution bandwidth to avoid any amplitude smoothing. Video filtering shall not be used during occupied bandwidth tests.

The OBW shall be measured for all operating conditions that will affect the bandwidth results (e.g. variable modulations, coding, or channel bandwidth settings). See section 4.


### Test procedure:

#### Occupied bandwidth – relative measurement procedure

The reference value is the highest level of the spectral envelope of the modulated signal.

- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
- The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- Set the reference level of the instrument as required to prevent the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least  $10\log(\text{OBW} / \text{RBW})$  below the reference level.
- NOTE—Steps a) through c) may require iteration to adjust within the specified tolerances.
- The dynamic range of the spectrum analyzer at the selected RBW shall be at least 10 dB below the target “-X dB down” requirement (i.e., if the requirement calls for measuring the -26 dB OBW, the spectrum analyzer noise floor at the selected RBW shall be at least 36 dB below the reference value).

- Set the detection mode to peak, and the trace mode to max hold.
- Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- Determine the “-X dB down amplitude” as equal to (Reference Value – X). Alternatively, this calculation can be performed by the analyzer by using the marker-delta function.
- Place two markers, one at the lowest and the other at the highest frequency of the





Report No.: WSCT-ANAB-R&amp;E240700032A-Part96

envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step g). If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.

j) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display. The frequency and amplitude axes and scale shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Occupied bandwidth – power bandwidth (99%) measurement procedure

The following procedure shall be used for measuring (99 %) power bandwidth

a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).

b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.

c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least 10log (OBW / RBW) below the reference level.

d) NOTE—Steps a) through c) may require iteration to adjust within the specified tolerances.


e) Set the detection mode to peak, and the trace mode to max hold..

f) Use the 99 % power bandwidth function of the spectrum analyzer (if available) and report the measured bandwidth.

g) If the instrument does not have a 99 % power bandwidth function, the trace data points are to be recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99 % power bandwidth is the difference between these two frequencies.

h) The OBW shall be reported by providing plot(s) of the measuring instrument display. The frequency and amplitude axes and scale shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Test setup:





## 9.1. Measurement Result

Note: Please refer to Annex (NR 4 Occupied Bandwidth) for more test data





## 10. BAND EDGE


### Test Limit:

The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in §2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified. See section 4.

### Test procedure:

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

### Test setup:





For Question,  
Please Contact with WSCT  
[www.wsct-cert.com](http://www.wsct-cert.com)

## 10.1. Measurement Result

Note: Please refer to Annex (NR 5 Band Edge) for more test data



世标检测认证股份

World Standardization Certification & Testing Group (Shenzhen) Co.,Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen, Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: [www.wsct-cert.com](http://www.wsct-cert.com)



## 11. SPURIOUS EMISSION (Conducted and Radiated)

### Conducted method

#### Test limit:


The spurious (unwanted) emission limits specified in the individual FCC rule parts applicable to licensed digital transmitters (typically referred to under the heading 'emission limits') normally apply to any and all emissions that are present outside of the authorized frequency band/block and apply to emissions in both the out-of-band and spurious domains. In some rule parts, the unwanted emission limits are specified by an emission mask that defines the applicable limit as a function of the frequency range relative to the authorized frequency block.

Typically, unwanted emissions are required by the licensed rule parts to be attenuated below the transmitter power by a factor of at least  $X + 10\log(P)$  dB, where  $P$  represents the transmitter power expressed in watts and  $X$  is a specified scalar value (e.g., 43). This specification can be interpreted in one of two equivalent ways. First, the required attenuation can be construed to be relative to the mean carrier power, with the resultant of the equation  $X + 10\log(P)$  being expressed in dBc (dB relative to the maximum carrier power). Alternatively, the specification can be interpreted as an absolute limit when the specified attenuation is actually subtracted from the maximum permissible transmitter power [i.e.,  $10\log(P) - \{X + 10\log(P)\}$ ], resulting in an absolute level of  $-X$  dBW [or  $(-X + 30)$  dBm]. See section 4.

#### Test procedure:

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz below 1 GHz and 1 MHz above 1 GHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonics.

#### Conducted Emission Test-Up:





For Question,  
Please Contact with WSCT  
[www.wsct-cert.com](http://www.wsct-cert.com)

## 11.1. Measurement Result

Note: Please refer to Annex (NR 6 Out-of-band emissions) for more test data



世标检测认证股份

World Standardization Certification & Testing Group (Shenzhen) Co.,Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen, Guangdong China  
TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com [Http://www.wsct-cert.com](http://www.wsct-cert.com)



## 12. FREQUENCY STABILITY


### Test limit:

The frequency stability of the transmitter shall be measured while varying the ambient temperatures and supply voltages over the ranges specified in §2.1055. The specific frequency stability limits are provided in the relevant rules section(s). see section 4.

### Test procedure:

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

### Test setup:



世标检测认证股份

World Standardization Certification &amp; Testing Group (Shenzhen) Co., Ltd.

ADD:Building A-B, Baoli'an industrial Park, No. 58 Tangtou Avenue, Shiyuan Street, Bao'an District Shenzhen, Guangdong China  
 TEL: 86-755-26996192 226996053 Fax: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.



## 12.1. Measurement Result (Worst)

Note: Please refer to Annex (NR 2 Frequency Error against) for more test data

For Question,  
Please Contact with WSCT  
[www.wsct-cert.com](http://www.wsct-cert.com)





For Question,  
Please Contact with WSCT  
[www.wsct-cert.com](http://www.wsct-cert.com)

## 13. Test Setup Photographs

Please refer to Annex "Set Up Photos-RF" for test setup photos

---END OF REPORT---

