

TEST REPORT

Applicant: INFINIX MOBILITY LIMITED

Address: FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL
CENTRE 19-25 SHAN MEI STREET FOTAN NT,
Hong Kong

Equipment Type: Mobile Phone

Model Name: X6728

Brand Name: INFINIX

FCC ID: 2AIZN-X6728

Test Standard: 47 CFR Part 15 Subpart E
(refer to section 3.1)

Sample Arrival Date: Apr. 07, 2025

Test Date: Apr. 14, 2025 - May 08, 2025

Date of Issue: May 23, 2025

ISSUED BY:

Shanghai Tejet Communications Technology Co., Ltd. Testing Center

Prepared by: Zhang Rujie

Reviewed by: Hai Su

Approved by: Zhang Yanqing
(Laboratory Manager)

Zhang Rujie

Hai Su

Zhang Yanqing

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>May 23, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Technical Information	6
2.5	Channel List	7
3	SUMMARY OF TEST RESULTS	10
3.1	Test Standards	10
3.2	Test Verdict	10
4	GENERAL TEST CONFIGURATIONS	11
4.1	Test Environments	11
4.2	Test Equipment List	11
4.3	Test Software List	11
4.4	Decision Rule	12
4.5	Measurement Uncertainty	12
4.6	Description of Test Setup	13
5	TEST ITEMS	16
5.1	RF Output Power	16
5.2	Emission Bandwidth and 6 dB Bandwidth	18
5.3	Power Spectral density (PSD)	19
5.4	Conducted Emission	20
5.5	Radiated Spurious Emissions and Band Edge (Restricted-band)	21

ANNEX A	TEST RESULT	26
A.1	RF Output Power.....	26
A.2	Emission Bandwidth & 99% Bandwidth.....	29
A.3	6 dB Bandwidth	31
A.4	Power Spectral Density	32
A.5	Conducted Emission	34
A.6	Radiated Spurious Emissions and Band Edge (Restricted-band).....	36
ANNEX B	TEST SETUP PHOTOS	101
ANNEX C	EUT EXTERNAL PHOTOS	101
ANNEX D	EUT INTERNAL PHOTOS	101

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Address	1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China

1.2 Test Location

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Location	1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1352.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	INFINIX MOBILITY LIMITED
Address	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT, Hong Kong

2.2 Manufacturer Information

Manufacturer	INFINIX MOBILITY LIMITED
Address	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT, Hong Kong

2.3 Factory Information

Factory	SHENZHEN TECNO TECHNOLOGY CO., LTD.
Address	101, Building 24, Waijing Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen City, P.R. China

2.4 General Description for Equipment under Test (EUT)

EUT Name	Mobile Phone
Model Name Under Test	X6728
Series Model Name	N/A
Description of Model name differentiation	N/A
Sample Number	SC-SH2540016-S06(conducted) SC-SH2540016-S04(radiated)
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	L: 166.02mm* W: 76.61mm* H: 7.77mm*
Weight (Approx.)	N/A

2.5 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EDGE 850/1900 MHz 3G Network WCDMA/HSDPA/HSUPA Band 2/4/5 4G Network LTE FDD Band 2/4/5/7 LTE TDD Band 38/41 Bluetooth (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n HT20 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80) GPS, GLONASS, BDS, Galileo, NFC
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Frequency Range	U-NII-1: 5150 MHz to 5250 MHz, U-NII-2A: 5250 MHz to 5350 MHz, U-NII-2C: 5470 MHz to 5725 MHz, U-NII-3: 5725 MHz to 5850 MHz
Modulation technology	OFDM
Modulation Type	256QAM, 64QAM, 16QAM, BPSK, QPSK
Transfer Rate (Mbps) (Single RF path)	802.11a: 54/ 48/ 36/ 24/ 18/ 12/ 9/ 6 Mbps 802.11n: up to 150 Mbps 802.11ac: up to VHT-MCS9
Channel Bandwidth	802.11a: 20 MHz 802.11n: 20 MHz, 40 MHz 802.11ac: 20 MHz, 40 MHz, 80 MHz, 160 MHz
Maximum Output Power	U-NII-1: 17.59 dBm U-NII-2A: 17.64 dBm U-NII-2C: 16.88 dBm U-NII-3: 17.44 dBm
Antenna System (eg., MIMO, Smart Antenna)	N/A
Categorization as Correlated or Completely Uncorrelated	N/A
Antenna Type	PIFA Antenna
Antenna Gain	U-NII-1: 5150 MHz to 5250 MHz: -0.61 dBi U-NII-2A: 5250 MHz to 5350 MHz: -0.61 dBi U-NII-2C: 5470 MHz to 5725 MHz: -0.61 dBi U-NII-3: 5725 MHz to 5850 MHz: -0.61 dBi
About the Product	The equipment is Mobile Phone, intended for used with information technology equipment.

2.6 Channel List

20 MHz		40 MHz		80 MHz	
Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230	58	5290
44	5220	54	5270	106	5530
48	5240	62	5310	122	5610
52	5260	102	5510	155	5775
56	5280	110	5550		
60	5300	118	5590		
64	5320	126	5630		
100	5500	134	5670		
104	5520	151	5755		
108	5540	159	5795		
112	5560				
116	5580				
120	5600				
124	5620				
128	5640				
132	5660				
136	5680				
140	5700				
149	5745				
153	5765				
157	5785				
161	5805				
165	5825				

The Lowest frequency, the middle frequency and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11a/n(HT20)/ac(VHT20)

U-NII-1 (5150 - 5250 MHz)			U-NII-2A (5250 - 5350 MHz)		
Channel Number	Channel	Frequency (MHz)	Channel Number	Channel	Frequency (MHz)
36	Low	5180	52	Low	5260
44	Mid	5220	60	Mid	5300
48	High	5240	64	High	5320

U-NII-2C (5470 - 5725 MHz)			U-NII-3 (5725 - 5850 MHz)		
Channel Number	Channel	Frequency (MHz)	Channel Number	Channel	Frequency (MHz)
100	Low	5500	149	Low	5745
116	Mid	5580	157	Mid	5785
140	High	5700	165	High	5825

For 802.11n(HT40)/ac(VHT40)

U-NII-1 (5150 - 5250 MHz)			U-NII-2A (5250 - 5350 MHz)		
Channel Number	Channel	Frequency (MHz)	Channel Number	Channel	Frequency (MHz)
38	Low	5190	54	Low	5270
46	High	5230	62	High	5310

U-NII-2C (5470 - 5725 MHz)			U-NII-3 (5725 - 5850 MHz)		
Channel Number	Channel	Frequency (MHz)	Channel Number	Channel	Frequency (MHz)
102	Low	5510	151	Low	5755
118	Mid	5590	159	High	5795
134	High	5670			

For 802.11ac(VHT80)

U-NII-1 (5150 - 5250 MHz)			U-NII-2A (5250 - 5350 MHz)		
Channel Number	Channel	Frequency (MHz)	Channel Number	Channel	Frequency (MHz)
42	Mid	5210	58	Mid	5290

U-NII-2C (5470 - 5725 MHz)			U-NII-3 (5725 - 5850 MHz)		
Channel Number	Channel	Frequency (MHz)	Channel Number	Channel	Frequency (MHz)
106	Low	5530	155	Mid	5775
122	High	5610			

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Modulation Type	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
				Channel	Channel	Channel	Channel
RF Output Power	11a	6	BPSK	48/44/36	64/60/52	140/116/100	165/157/149
	11n(20 MHz)	6.5		48/44/36	64/60/52	140/116/100	165/157/149
	11n(40 MHz)	13.5		46/38	62/54	134/118/102	159/151
	11ac(20 MHz)	6.5		48/44/36	64/60/52	140/116/100	165/157/149
	11ac(40 MHz)	13.5		46/38	62/54	134/118/102	159/151
	11ac(80 MHz)	29.3		42	58	122/106	155
Emission Bandwidth & 99% Occupied Bandwidth	11a	6	BPSK	48/44/36	64/60/52	140/116/100	165/157/149
	11n(20 MHz)	6.5		48/44/36	64/60/52	140/116/100	165/157/149
	11n(40 MHz)	13.5		46/38	62/54	134/118/102	159/151
	11ac(20 MHz)	6.5		48/44/36	64/60/52	140/116/100	165/157/149
	11ac(40 MHz)	13.5		46/38	62/54	134/118/102	159/151
	11ac(80 MHz)	29.3		42	58	122/106	155
6 dB bandwidth	11a	6	BPSK	N/A	N/A	N/A	165/157/149
	11n(20 MHz)	6.5		N/A	N/A	N/A	165/157/149
	11n(40 MHz)	13.5		N/A	N/A	N/A	159/151
	11ac(20 MHz)	6.5		N/A	N/A	N/A	165/157/149
	11ac(40 MHz)	13.5		N/A	N/A	N/A	159/151
	11ac(80 MHz)	29.3		N/A	N/A	N/A	155
Power Spectral Density	11a	6	BPSK	48/44/36	64/60/52	140/116/100	165/157/149
	11n(20 MHz)	6.5		48/44/36	64/60/52	140/116/100	165/157/149
	11n(40 MHz)	13.5		46/38	62/54	134/118/102	159/151
	11ac(20 MHz)	6.5		48/44/36	64/60/52	140/116/100	165/157/149
	11ac(40 MHz)	13.5		46/38	62/54	134/118/102	159/151
	11ac(80 MHz)	29.3		42	58	122/106	155
Radiated Spurious Emissions	11a	6	BPSK	48/44/36	64/60/52	140/116/100	165/157/149
	11n(20 MHz)	6.5		48/44/36	64/60/52	140/116/100	165/157/149
	11n(40 MHz)	13.5		46/38	62/54	134/118/102	159/151
	11ac(20 MHz)	6.5		48/44/36	64/60/52	140/116/100	165/157/149
	11ac(40 MHz)	13.5		46/38	62/54	134/118/102	159/151
	11ac(80 MHz)	29.3		42	58	122/106	155
Band Edge (Restricted-band)	11a	6	BPSK	48/36	64/52	140/100	165/149
	11n(20 MHz)	6.5		48/36	64/52	140/100	165/149
	11n(40 MHz)	13.5		46/38	62/54	134/102	159/151
	11ac(20 MHz)	6.5		48/36	64/52	140/100	165/149
	11ac(40 MHz)	13.5		46/38	62/54	134/102	159/151
	11ac(80 MHz)	29.3		42	58	122/106	155

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart E	Unlicensed National Information Infrastructure Devices
2	KDB Publication 789033 D02v02r01	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

3.2 Test Verdict

No.	Description	FCC Part No.	RSS Part No.	Test Result	Verdict
1	Antenna Requirement	15.203	N/A	--	Pass ^{Note1}
2	RF Output Power	15.407(a)	N/A	ANNEX A.1	Pass
3	Emission Bandwidth & 99% Occupied Bandwidth	15.407(a)	N/A	ANNEX A.2	Pass
4	6 dB bandwidth	15.407(e)	N/A	ANNEX A.3	Pass
5	Power Spectral Density	15.407(a)	N/A	ANNEX A.4	Pass
6	Conducted Emission	15.207	N/A	ANNEX A.5	Pass
7	Radiated Spurious Emissions and Band Edge (Restricted-band)	15.407(b)	N/A	ANNEX A.6	Pass

Note ¹: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	51% to 59%	
Atmospheric Pressure	101 kPa	
Temperature	NT (Normal Temperature)	+21.8℃ to +24.2℃
Working Voltage of the EUT	NV (Normal Voltage)	3.92 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY54420147	2025.02.12	2026.02.11
Spectrum Analyzer	KEYSIGHT	N9010B	MY60240977	2025.02.12	2026.02.11
Signal Generator	Anritsu	MG3710E	6262063515	2025.02.12	2026.02.11
Wideband Radio Communication Tester	R&S	CMW500	168792	2025.02.11	2026.02.10
EMI Receiver	KEYSIGHT	N9038A	MY55330122	2024.07.09	2025.07.08
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-177	2024.03.11	2027.03.10
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-1203	2024.03.11	2027.03.10
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-2134	2024.03.11	2027.03.10
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400-KF	J211060307	2024.03.11	2027.03.10
Anechoic Chamber	YiHeng	9m*6m*6m	EMC001	2024.04.18	2027.04.17
EMI Receiver	KEYSIGHT	N9038A	MY55330115	2025.02.12	2026.02.11
LISN	SCHWARZBECK	NSLK 8127	8127-940	2025.02.11	2026.02.10
10dB Limiter	SCHWARZBECK	VTSD 9561-F	9561-F N00409	2025.02.11	2026.02.10
Shielded Room	YiHeng	5m*4m*3.2 m	EMC006	2024.02.22	2027.02.21

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable Test Setup
BL410R	BALUN	V2.1.1.496	N/A	The section 4.6.1
BL410E	BALUN	V21.919	N/A	The section 4.6.2&4.6.3&4.6.4&4.6.5

4.4 Decision Rule

☐ No Need

☒ Use General conformity decision rule (Consider uncertainty or not ☒No ☐Yes)

☐ Use Special Conformity Decision Rule (Consider uncertainty or not ☐No ☐Yes)

4.5 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.4 %
RF output power, conducted	0.41 dB
Power Spectral Density, conducted	1.73 dB
Unwanted Emissions, conducted	1.73 dB
All emissions, radiated	4.57 dB
Temperature	0.82 °C
Humidity	4.1 %


4.6 Description of Test Setup

4.6.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5 dB used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.6.2 For AC Power Supply Port Test




(Diagram 2)

4.6.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.6.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.6.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

5 TEST ITEMS

5.1 RF Output Power

5.1.1 Test Limit

FCC §15.407(a)

The maximum conducted output power should not exceed:

Frequency Band (MHz)	Limit
5150-5250	250 mW
5250-5350	250 mW or 11 dBm + 10log B, whichever is less.
5470-5725	250 mW or 11 dBm + 10log B, whichever is less.
5725-5850	1 W
Note: Where "B" is the 26 dB emissions bandwidth in MHz.	

5.1.2 Test Setup

The section 4.6.1 (Diagram 1) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.1.3 Test Procedure

Maximum conducted (average) output power

a) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

- 1) The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
- 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal.
- c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- d) Adjust the measurement in dBm by adding 10 log (1/x) where x is the duty cycle.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value.

Set VBW ≥ RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T ≤ 16.7 microseconds.)

The E.I.R.P used radiated test method. At a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space

environment.

5.1.4 Test Result

Please refer to ANNEX A.1.

5.2 Emission Bandwidth and 6 dB Bandwidth

5.2.1 Limit

FCC §15.407(a)

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

5.2.2 Test Setup

The test setup photo please refer to 4.6.1 (Diagram 1) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Emission bandwidth

1. Set RBW = approximately 1% of the emission bandwidth.
2. Set VBW $\geq 3 \times$ RBW,
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is 26 dB down from the peak of the emission.

Occupied Bandwidth

1. Set Span = 1.5 times to 5.0 times the OBW
2. Set RBW = 1% to 5% of the OBW.
3. Set VBW $\geq 3 \times$ RBW,
4. Detector = Peak.
5. Trace mode = Max hold.
6. Use the 99% power bandwidth function of the instrument.

6 dB bandwidth

1. Set RBW = 100 kHz, VBW = 300 kHz.
2. Detector = Peak.
3. Trace mode = Max hold.
4. Allow the trace to stabilize.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.2.4 Test Result

Please refer to ANNEX A.2 and ANNEX A.3.

5.3 Power Spectral density (PSD)

5.3.1 Limit

FCC §15.407(a)

The maximum power spectral density should not exceed:

Frequency Band (MHz)	Limit
5150-5250	11 dBm/MHz
5250-5350	11 dBm/MHz
5470-5725	11 dBm/MHz
5725-5850	30 dBm/500kHz

5.3.2 Test Setup

The section 4.6.1 (Diagram 1) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth.

1. Set RBW = 510 kHz/1 MHz, VBW $\geq 3 \times$ RBW, Sweep time = Auto, Detector = RMS.
2. Allow the sweeps to continue until the trace stabilizes.
3. Use the peak marker function to determine the maximum amplitude level.
4. The E.I.R.P spectral density used radiated test method. At a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment.

5.3.4 Test Result

Please refer to ANNEX A.4.

5.4 Conducted Emission

5.4.1 Limit

FCC §15.207, RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the U-NII-150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.4.2 Test Setup

The section 4.6.2 (Diagram 2) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

5.4.4 Test Result

Please refer to ANNEX A.5.

5.5 Radiated Spurious Emissions and Band Edge (Restricted-band)


5.5.1 Limit

FCC §15.209 & 15.407(b)

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note ¹: The Limit for radiated test was performed according to FCC Part 15C

Note ²: The tighter limit applies at the band edge.

Un-restricted band emissions	
Out Operating Band (MHz)	Limit
5150 - 5250	e.i.r.p. -27 dBm (68.2 dBuV/m@3m)
5250 - 5350	e.i.r.p. -27 dBm (68.2 dBuV/m@3m)
5470 - 5725	e.i.r.p. -27 dBm (68.2 dBuV/m@3m)
5725 - 5850	All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. 

Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength.

5.5.2 Test Setup

The section 4.6.3-4.6.5 (Diagram 3 - Diagram 5) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:
$$E = \text{EIRP} - 20 \log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW $\geq 3 * \text{RBW}$.
- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq 3 * \text{RBW}$.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on

and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.5.4 Test Result

Please refer to ANNEX A.6.

ANNEX A TEST RESULT

A.1 RF Output Power

Note 1: For FCC standard, if transmitting antennas of directional gain greater than 6 dBi are used, all band maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note 2: All the configurations were tested, but only the worst data was shown in this report.

Duty Cycle

Test Mode	On Time (ms)	On+Off time (ms)	Duty Cycle
11a	1.39	1.44	96.87%
11n (HT20)/11ac (VHT20)	1.31	1.35	96.75%
11n (HT40)/11ac (VHT40)	0.65	0.70	93.24%
11ac (VHT80)	0.32	0.37	87.52%

Test Data

Conducted Power

U-NII-1 (5150 - 5250 MHz)					
Mode	Channel	Conducted Power (dBm)	Conducted Power (mW)	FCC Limit (mW)	Verdict
11a	CH36	16.71	46.86	250	Pass
11a	CH44	17.59	57.39	250	Pass
11a	CH48	17.49	56.08	250	Pass
11n (HT20)	CH36	16.66	46.38	250	Pass
11n (HT20)	CH44	17.38	54.75	250	Pass
11n (HT20)	CH48	17.50	56.28	250	Pass
11n (HT40)	CH38	15.69	37.10	250	Pass
11n (HT40)	CH46	17.45	55.64	250	Pass
11ac (VHT20)	CH36	16.30	42.69	250	Pass
11ac (VHT20)	CH44	16.21	41.82	250	Pass
11ac (VHT20)	CH48	16.30	42.69	250	Pass
11ac (VHT40)	CH38	15.63	36.59	250	Pass
11ac (VHT40)	CH46	16.37	43.39	250	Pass
11ac (VHT80)	CH42	14.58	28.70	250	Pass

U-NII-2A (5250 - 5350 MHz)					
Mode	Channel	Conducted Power (dBm)	Conducted Power (mW)	FCC Limit (mW)	Verdict
11a	CH52	17.56	56.99	250	Pass
11a	CH60	17.42	55.19	250	Pass
11a	CH64	17.54	56.73	250	Pass
11n (HT20)	CH52	17.40	55.00	250	Pass
11n (HT20)	CH60	17.36	54.49	250	Pass
11n (HT20)	CH64	16.85	48.46	250	Pass
11n (HT40)	CH54	17.64	58.13	250	Pass
11n (HT40)	CH62	15.78	37.88	250	Pass
11ac (VHT20)	CH52	16.25	42.20	250	Pass
11ac (VHT20)	CH60	16.23	42.01	250	Pass
11ac (VHT20)	CH64	16.39	43.59	250	Pass
11ac (VHT40)	CH54	16.27	36.59	250	Pass
11ac (VHT40)	CH62	15.75	43.39	250	Pass
11ac (VHT80)	CH58	13.63	23.06	250	Pass

U-NII-2C (5470 - 5725 MHz)					
Mode	Channel	Conducted Power (dBm)	Conducted Power (mW)	FCC Limit (mW)	Verdict
11a	CH100	14.75	29.84	250	Pass
11a	CH116	16.88	48.73	250	Pass
11a	CH140	14.33	27.09	250	Pass
11n (HT20)	CH100	14.81	30.29	250	Pass
11n (HT20)	CH116	14.56	28.60	250	Pass
11n (HT20)	CH140	12.25	16.80	250	Pass
11n (HT40)	CH102	12.64	18.38	250	Pass
11n (HT40)	CH118	14.48	28.08	250	Pass
11n (HT40)	CH134	14.32	27.06	250	Pass
11ac (VHT20)	CH100	14.73	29.74	250	Pass
11ac (VHT20)	CH116	14.54	28.47	250	Pass
11ac (VHT20)	CH140	12.12	16.31	250	Pass
11ac (VHT40)	CH102	12.61	55.19	250	Pass
11ac (VHT40)	CH118	14.64	56.73	250	Pass
11ac (VHT40)	CH134	14.28	26.82	250	Pass
11ac (VHT80)	CH106	13.64	23.11	250	Pass
11ac (VHT80)	CH122	15.71	37.23	250	Pass

U-NII-3 (5725 - 5850 MHz)					
Mode	Channel	Conducted Power (dBm)	Conducted Power (mW)	FCC Limit (mW)	Verdict
11a	CH149	17.41	55.06	1000	Pass
11a	CH157	17.44	55.44	1000	Pass
11a	CH165	17.40	54.93	1000	Pass
11n (HT20)	CH149	17.37	54.62	1000	Pass
11n (HT20)	CH157	17.34	54.24	1000	Pass
11n (HT20)	CH165	17.21	52.64	1000	Pass
11n (HT40)	CH151	17.29	53.63	1000	Pass
11n (HT40)	CH159	17.19	52.41	1000	Pass
11ac (VHT20)	CH149	16.28	42.50	1000	Pass
11ac (VHT20)	CH157	16.30	42.69	1000	Pass
11ac (VHT20)	CH165	15.90	38.94	1000	Pass
11ac (VHT40)	CH151	16.30	42.70	1000	Pass
11ac (VHT40)	CH159	16.33	42.99	1000	Pass
11ac (VHT80)	CH155	16.35	43.14	1000	Pass

A.2 Emission Bandwidth & 99% Bandwidth

Note: Test plots please refer to the document "Annex No.: BL-SH2540336-604 Data Part 1.pdf".

Test Data

U-NII-1 (5150 - 5250 MHz)			
Mode	Channel	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)
11a	CH36	20.09	16.55
11a	CH44	22.22	16.60
11a	CH48	23.86	16.60
11n (HT20)	CH36	20.74	17.66
11n (HT20)	CH44	21.17	17.67
11n (HT20)	CH48	22.93	17.69
11n (HT40)	CH38	40.66	36.08
11n (HT40)	CH46	42.08	36.20
11ac (VHT20)	CH36	20.35	17.63
11ac (VHT20)	CH44	20.49	17.64
11ac (VHT20)	CH48	20.36	17.61
11ac (VHT40)	CH38	40.68	36.04
11ac (VHT40)	CH46	40.57	36.06
11ac (VHT80)	CH42	80.98	75.16

U-NII-2A (5250 - 5350 MHz)			
Mode	Channel	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)
11a	CH52	20.25	16.53
11a	CH60	21.30	16.56
11a	CH64	20.62	16.57
11n (HT20)	CH52	22.08	17.65
11n (HT20)	CH60	21.78	17.66
11n (HT20)	CH64	22.01	17.64
11n (HT40)	CH54	41.46	36.17
11n (HT40)	CH62	40.68	36.08
11ac (VHT20)	CH52	20.30	17.60
11ac (VHT20)	CH60	20.39	17.61
11ac (VHT20)	CH64	20.51	17.61
11ac (VHT40)	CH54	40.40	36.03
11ac (VHT40)	CH62	40.60	36.03
11ac (VHT80)	CH58	80.79	75.20

U-NII-2C (5470 - 5725 MHz)			
Mode	Channel	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)
11a	CH100	19.90	16.46
11a	CH116	20.99	16.59
11a	CH140	19.88	16.49
11n (HT20)	CH100	20.21	17.59
11n (HT20)	CH116	20.30	17.62
11n (HT20)	CH140	20.31	17.56
11n (HT40)	CH102	40.70	35.98
11n (HT40)	CH118	40.57	36.04
11n (HT40)	CH134	40.72	36.06
11ac (VHT20)	CH100	20.27	17.57
11ac (VHT20)	CH116	20.27	17.57
11ac (VHT20)	CH140	20.35	17.56
11ac (VHT40)	CH102	40.63	36.02
11ac (VHT40)	CH118	40.48	36.02
11ac (VHT40)	CH134	40.68	36.01
11ac (VHT80)	CH106	81.03	75.23
11ac (VHT80)	CH122	81.46	75.25

U-NII-3 (5725 - 5850 MHz)			
Mode	Channel	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)
11a	CH149	20.01	16.54
11a	CH157	21.46	16.55
11a	CH165	23.22	16.57
11n (HT20)	CH149	22.30	17.66
11n (HT20)	CH157	20.68	17.64
11n (HT20)	CH165	21.77	17.68
11n (HT40)	CH151	42.13	36.20
11n (HT40)	CH159	48.41	36.22
11ac (VHT20)	CH149	20.33	17.61
11ac (VHT20)	CH157	20.21	17.61
11ac (VHT20)	CH165	20.69	17.59
11ac (VHT40)	CH151	40.58	36.03
11ac (VHT40)	CH159	40.45	36.03
11ac (VHT80)	CH155	81.35	75.38

A.3 6 dB Bandwidth

Note: Test plots please refer to the document "Annex No.: BL-SH2540336-604 Data Part 2.pdf".

Test Data

U-NII-3 (5725 - 5850 MHz)				
Mode	Channel	6 dB Bandwidth (MHz)	Limit (kHz)	Verdict
11a	CH149	15.40	500.00	Pass
11a	CH157	15.20	500.00	Pass
11a	CH165	15.20	500.00	Pass
11n (HT20)	CH149	15.30	500.00	Pass
11n (HT20)	CH157	15.40	500.00	Pass
11n (HT20)	CH165	15.40	500.00	Pass
11n (HT40)	CH151	35.20	500.00	Pass
11n (HT40)	CH159	35.30	500.00	Pass
11ac (VHT20)	CH149	15.40	500.00	Pass
11ac (VHT20)	CH157	15.30	500.00	Pass
11ac (VHT20)	CH165	15.40	500.00	Pass
11ac (VHT40)	CH151	35.20	500.00	Pass
11ac (VHT40)	CH159	35.20	500.00	Pass
11ac (VHT80)	CH155	75.30	500.00	Pass

A.4 Power Spectral Density

Note¹: Test plots please refer to the document "Annex No.: BL-SH2540336-604 Data Part 3.pdf".

Note²: The RBW used in U-NII-3 is 1 MHz, and the PSD factor is: $10 \cdot \log(500 \text{ kHz/RBW}) = -3 \text{ dBm}$.

Test Data

U-NII-1 (5150 - 5250 MHz)				
Mode	Channel	PSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
11a	CH36	6.19	11.00	Pass
11a	CH44	7.48	11.00	Pass
11a	CH48	7.70	11.00	Pass
11n (HT20)	CH36	5.44	11.00	Pass
11n (HT20)	CH44	6.73	11.00	Pass
11n (HT20)	CH48	6.89	11.00	Pass
11n (HT40)	CH38	1.36	11.00	Pass
11n (HT40)	CH46	3.85	11.00	Pass
11ac (VHT20)	CH36	5.93	11.00	Pass
11ac (VHT20)	CH44	5.58	11.00	Pass
11ac (VHT20)	CH48	5.65	11.00	Pass
11ac (VHT40)	CH38	1.51	11.00	Pass
11ac (VHT40)	CH46	2.69	11.00	Pass
11ac (VHT80)	CH42	-2.86	11.00	Pass

U-NII-2A (5250 - 5350 MHz)				
Mode	Channel	PSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
11a	CH52	7.13	11.00	Pass
11a	CH60	7.31	11.00	Pass
11a	CH64	7.22	11.00	Pass
11n (HT20)	CH52	6.84	11.00	Pass
11n (HT20)	CH60	7.03	11.00	Pass
11n (HT20)	CH64	6.10	11.00	Pass
11n (HT40)	CH54	3.87	11.00	Pass
11n (HT40)	CH62	1.89	11.00	Pass
11ac (VHT20)	CH52	5.76	11.00	Pass
11ac (VHT20)	CH60	5.87	11.00	Pass
11ac (VHT20)	CH64	5.87	11.00	Pass
11ac (VHT40)	CH54	3.46	11.00	Pass
11ac (VHT40)	CH62	2.41	11.00	Pass
11ac (VHT80)	CH58	-2.98	11.00	Pass

U-NII-2C (5470 - 5725 MHz)				
Mode	Channel	PSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
11a	CH100	4.34	11.00	Pass
11a	CH116	6.35	11.00	Pass
11a	CH140	3.35	11.00	Pass
11n (HT20)	CH100	3.45	11.00	Pass
11n (HT20)	CH116	3.41	11.00	Pass
11n (HT20)	CH140	1.16	11.00	Pass
11n (HT40)	CH102	-1.63	11.00	Pass
11n (HT40)	CH118	0.27	11.00	Pass
11n (HT40)	CH134	0.26	11.00	Pass
11ac (VHT20)	CH100	3.38	11.00	Pass
11ac (VHT20)	CH116	3.20	11.00	Pass
11ac (VHT20)	CH140	1.03	11.00	Pass
11ac (VHT40)	CH102	-1.87	11.00	Pass
11ac (VHT40)	CH118	0.19	11.00	Pass
11ac (VHT40)	CH134	0.22	11.00	Pass
11ac (VHT80)	CH106	-3.78	11.00	Pass
11ac (VHT80)	CH122	-2.14	11.00	Pass

U-NII-3 (5725 - 5850 MHz)				
Mode	Channel	PSD (dBm/500kHz)	Limit (dBm/500kHz)	Verdict
11a	CH149	3.94	30.00	Pass
11a	CH157	3.91	30.00	Pass
11a	CH165	3.98	30.00	Pass
11n (HT20)	CH149	3.72	30.00	Pass
11n (HT20)	CH157	3.63	30.00	Pass
11n (HT20)	CH165	3.67	30.00	Pass
11n (HT40)	CH151	0.63	30.00	Pass
11n (HT40)	CH159	0.50	30.00	Pass
11ac (VHT20)	CH149	2.71	30.00	Pass
11ac (VHT20)	CH157	2.63	30.00	Pass
11ac (VHT20)	CH165	2.55	30.00	Pass
11ac (VHT40)	CH151	-0.53	30.00	Pass
11ac (VHT40)	CH159	-0.48	30.00	Pass
11ac (VHT80)	CH155	-3.68	30.00	Pass


A.5 Conducted Emission

Note 1: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.

Note 2: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Test Data and Plots


PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.162	40.39	9.82	65.36	24.97	Peak	L	Pass
1**	0.162	26.09	9.82	55.36	29.27	AV	L	Pass
2	0.546	37.02	9.76	56.00	18.98	Peak	L	Pass
2**	0.546	24.93	9.76	46.00	21.07	AV	L	Pass
3	1.496	42.21	9.72	56.00	13.79	Peak	L	Pass
3**	1.496	34.01	9.72	46.00	11.99	AV	L	Pass
4	2.996	36.48	9.63	56.00	19.52	Peak	L	Pass
4**	2.996	26.30	9.63	46.00	19.70	AV	L	Pass
5	8.732	43.56	9.24	60.00	16.44	Peak	L	Pass
5**	8.732	31.34	9.24	50.00	18.66	AV	L	Pass
6	14.006	40.23	8.97	60.00	19.77	Peak	L	Pass
6**	14.006	28.77	8.97	50.00	21.23	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.200	36.03	9.78	63.61	27.58	Peak	N	Pass
1**	0.200	23.34	9.78	53.61	30.27	AV	N	Pass
2	0.518	42.78	9.77	56.00	13.22	Peak	N	Pass
2**	0.518	31.09	9.77	46.00	14.91	AV	N	Pass
3	1.704	34.76	9.69	56.00	21.24	Peak	N	Pass
3**	1.704	20.82	9.69	46.00	25.18	AV	N	Pass
4	3.588	34.32	9.61	56.00	21.68	Peak	N	Pass
4**	3.588	20.92	9.61	46.00	25.08	AV	N	Pass
5	9.002	47.23	9.22	60.00	12.77	Peak	N	Pass
5**	9.002	36.72	9.22	50.00	13.28	AV	N	Pass
6	15.372	38.96	8.92	60.00	21.04	Peak	N	Pass
6**	15.372	27.47	8.92	50.00	22.53	AV	N	Pass

A.6 Radiated Spurious Emissions and Band Edge (Restricted-band)

A.6.1 Radiated Spurious Emissions

Test Data


Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, According the ANSI C63.4, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


Note 4: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	33.346	29.18	-28.32	40.0	10.82	Peak	244.00	100	Vertical	Pass
2	40.961	28.67	-25.61	40.0	11.33	Peak	148.00	100	Vertical	Pass
3	62.883	30.87	-26.74	40.0	9.13	Peak	187.00	200	Vertical	Pass
4	109.346	24.00	-26.53	43.5	19.50	Peak	360.00	100	Vertical	Pass
5	218.034	26.86	-25.95	46.0	19.14	Peak	109.00	100	Vertical	Pass
6	338.072	26.94	-22.05	46.0	19.06	Peak	190.00	100	Vertical	Pass


30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	63.271	26.51	-26.83	40.0	13.49	Peak	297.00	200	Horizontal	Pass
2	109.637	32.14	-26.54	43.5	11.36	Peak	254.00	200	Horizontal	Pass
3	113.856	32.38	-27.13	43.5	11.12	Peak	254.00	200	Horizontal	Pass
4	218.422	27.22	-25.93	46.0	18.78	Peak	62.00	100	Horizontal	Pass
5	340.885	23.97	-21.83	46.0	22.03	Peak	273.00	100	Horizontal	Pass
6	749.740	28.77	-11.95	46.0	17.23	Peak	202.00	200	Horizontal	Pass

Note: The spurious above 18G is noise only, do not show on the report.


11a, U-NII-1, 1 GHz to 18 GHz, Middle Channel, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1819.250	39.48	-16.03	74.0	34.52	Peak	154.00	150	Horizontal	Pass
1**	1819.250	27.81	-16.03	54.0	26.19	AV	154.00	150	Horizontal	Pass
2	2633.500	43.92	-9.90	74.0	30.08	Peak	168.00	150	Horizontal	Pass
2**	2633.500	32.02	-9.90	54.0	21.98	AV	168.00	150	Horizontal	Pass
3	3745.000	46.06	-4.67	74.0	27.94	Peak	326.00	150	Horizontal	Pass
3**	3745.000	35.27	-4.67	54.0	18.73	AV	326.00	150	Horizontal	Pass
4	5223.500	101.98	-2.34	74.0	-27.98	Peak	343.00	150	Horizontal	N/A
4**	5223.500	94.07	-2.34	54.0	-40.07	AV	343.00	150	Horizontal	N/A
5	7856.500	53.96	1.63	74.0	20.04	Peak	307.00	150	Horizontal	Pass
5**	7856.500	42.82	1.63	54.0	11.18	AV	307.00	150	Horizontal	Pass
6	11746.326	48.99	-2.76	74.0	25.01	Peak	229.00	150	Horizontal	Pass
6**	11746.326	38.44	-2.76	54.0	15.56	AV	229.00	150	Horizontal	Pass

11a, U-NII-1, 1 GHz to 18 GHz, Middle Channel, ANT V


RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1412.250	39.42	-15.96	74.0	34.58	Peak	38.00	150	Vertical	Pass
1**	1412.250	28.05	-15.96	54.0	25.95	AV	38.00	150	Vertical	Pass
2	2562.250	42.28	-11.09	74.0	31.72	Peak	0.00	150	Vertical	Pass
2**	2562.250	31.35	-11.09	54.0	22.65	AV	0.00	150	Vertical	Pass
3	4013.500	47.29	-4.14	74.0	26.71	Peak	133.00	150	Vertical	Pass
3**	4013.500	35.87	-4.14	54.0	18.13	AV	133.00	150	Vertical	Pass
4	5217.000	101.47	-2.34	74.0	-27.47	Peak	105.00	150	Vertical	N/A
4**	5217.000	93.16	-2.34	54.0	-39.16	AV	105.00	150	Vertical	N/A
5	7994.000	54.35	1.81	74.0	19.65	Peak	225.00	150	Vertical	Pass
5**	7994.000	43.27	1.81	54.0	10.73	AV	225.00	150	Vertical	Pass
6	12687.300	48.62	-3.09	74.0	25.38	Peak	6.00	150	Vertical	Pass
6**	12687.300	38.19	-3.09	54.0	15.81	AV	6.00	150	Vertical	Pass

11n20, U-NII-1, 1 GHz to 18 GHz, Middle Channel, ANT H


RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1515.000	38.60	-16.07	74.0	35.40	Peak	322.00	150	Vertical	Pass
1**	1515.000	27.42	-16.07	54.0	26.58	AV	322.00	150	Vertical	Pass
2	2590.500	42.71	-10.78	74.0	31.29	Peak	308.00	150	Vertical	Pass
2**	2590.500	31.51	-10.78	54.0	22.49	AV	308.00	150	Vertical	Pass
3	3959.000	46.86	-4.10	74.0	27.14	Peak	301.00	150	Vertical	Pass
3**	3959.000	35.90	-4.10	54.0	18.10	AV	301.00	150	Vertical	Pass
4	5218.500	101.67	-2.37	74.0	-27.67	Peak	104.00	150	Vertical	N/A
4**	5218.500	93.33	-2.37	54.0	-39.33	AV	104.00	150	Vertical	N/A
5	7999.500	54.19	1.92	74.0	19.81	Peak	282.00	150	Vertical	Pass
5**	7999.500	43.73	1.92	54.0	10.27	AV	282.00	150	Vertical	Pass
6	12629.826	48.70	-2.99	74.0	25.30	Peak	0.00	150	Vertical	Pass
6**	12629.826	37.57	-2.99	54.0	16.43	AV	0.00	150	Vertical	Pass

11n20, U-NII-1, 1 GHz to 18 GHz, Middle Channel, ANT V


RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1384.000	39.10	-15.97	74.0	34.90	Peak	45.00	150	Horizontal	Pass
1**	1384.000	27.54	-15.97	54.0	26.46	AV	45.00	150	Horizontal	Pass
2	2472.000	41.55	-11.09	74.0	32.45	Peak	184.00	150	Horizontal	Pass
2**	2472.000	30.62	-11.09	54.0	23.38	AV	184.00	150	Horizontal	Pass
3	4003.000	46.71	-4.82	74.0	27.29	Peak	340.00	150	Horizontal	Pass
3**	4003.000	35.80	-4.82	54.0	18.20	AV	340.00	150	Horizontal	Pass
4	5218.000	102.44	-2.38	74.0	-28.44	Peak	340.00	150	Horizontal	N/A
4**	5218.000	94.62	-2.38	54.0	-40.62	AV	340.00	150	Horizontal	N/A
5	7744.500	54.09	1.37	74.0	19.91	Peak	204.00	150	Horizontal	Pass
5**	7744.500	43.07	1.37	54.0	10.93	AV	204.00	150	Horizontal	Pass
6	12908.026	48.87	-2.84	74.0	25.13	Peak	143.00	150	Horizontal	Pass
6**	12908.026	37.94	-2.84	54.0	16.06	AV	143.00	150	Horizontal	Pass


11n40, U-NII-1, 1 GHz to 18 GHz, Low Channel, ANT H

RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1472.250	38.73	-16.32	74.0	35.27	Peak	289.00	150	Horizontal	Pass
1**	1472.250	27.14	-16.32	54.0	26.86	AV	289.00	150	Horizontal	Pass
2	2379.750	41.23	-11.93	74.0	32.77	Peak	125.00	150	Horizontal	Pass
2**	2379.750	29.69	-11.93	54.0	24.31	AV	125.00	150	Horizontal	Pass
3	3878.500	46.26	-4.69	74.0	27.74	Peak	355.00	150	Horizontal	Pass
3**	3878.500	35.48	-4.69	54.0	18.52	AV	355.00	150	Horizontal	Pass
4	5228.000	104.87	-2.30	74.0	-30.87	Peak	59.00	150	Horizontal	N/A
4**	5228.000	96.85	-2.30	54.0	-42.85	AV	59.00	150	Horizontal	N/A
5	7982.500	53.81	1.97	74.0	20.19	Peak	78.00	150	Horizontal	Pass
5**	7982.500	42.88	1.97	54.0	11.12	AV	78.00	150	Horizontal	Pass
6	13216.987	48.72	-2.52	74.0	25.28	Peak	0.00	150	Horizontal	Pass
6**	13216.987	37.40	-2.52	54.0	16.60	AV	0.00	150	Horizontal	Pass


11n40, U-NII-1, 1 GHz to 18 GHz, Low Channel, ANT V

RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz
1.2E+2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1707.250	39.23	-16.39	74.0	34.77	Peak	360.00	150	Vertical	Pass
1**	1707.250	27.16	-16.39	54.0	26.84	AV	360.00	150	Vertical	Pass
2	2689.750	42.75	-10.50	74.0	31.25	Peak	360.00	150	Vertical	Pass
2**	2689.750	31.66	-10.50	54.0	22.34	AV	360.00	150	Vertical	Pass
3	4232.000	47.86	-3.73	74.0	26.14	Peak	216.00	150	Vertical	Pass
3**	4232.000	36.06	-3.73	54.0	17.94	AV	216.00	150	Vertical	Pass
4	5231.000	97.90	-2.31	74.0	-23.90	Peak	107.00	150	Vertical	N/A
4**	5231.000	87.74	-2.31	54.0	-33.74	AV	107.00	150	Vertical	N/A
5	7919.500	53.82	1.97	74.0	20.18	Peak	129.00	150	Vertical	Pass
5**	7919.500	43.87	1.97	54.0	10.13	AV	129.00	150	Vertical	Pass
6	12353.849	49.40	-1.95	74.0	24.60	Peak	360.00	150	Vertical	Pass
6**	12353.849	37.31	-1.95	54.0	16.69	AV	360.00	150	Vertical	Pass

11ac80, U-NII-1, 1 GHz to 18 GHz, Middle Channel, ANT H


RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1631.500	38.94	-16.07	74.0	35.06	Peak	292.00	150	Horizontal	Pass
1**	1631.500	27.47	-16.07	54.0	26.53	AV	292.00	150	Horizontal	Pass
2	2616.500	42.57	-10.39	74.0	31.43	Peak	88.00	150	Horizontal	Pass
2**	2616.500	31.87	-10.39	54.0	22.13	AV	88.00	150	Horizontal	Pass
3	4007.500	46.13	-4.60	74.0	27.87	Peak	40.00	150	Horizontal	Pass
3**	4007.500	36.11	-4.60	54.0	17.89	AV	40.00	150	Horizontal	Pass
4	5216.500	102.08	-2.33	74.0	-28.08	Peak	59.00	150	Horizontal	N/A
4**	5216.500	92.75	-2.33	54.0	-38.75	AV	59.00	150	Horizontal	N/A
5	7802.000	54.64	1.52	74.0	19.36	Peak	0.00	150	Horizontal	Pass
5**	7802.000	42.79	1.52	54.0	11.21	AV	0.00	150	Horizontal	Pass
6	12266.450	49.17	-2.59	74.0	24.83	Peak	0.00	150	Horizontal	Pass
6**	12266.450	37.90	-2.59	54.0	16.10	AV	0.00	150	Horizontal	Pass


11ac80, U-NII-1, 1 GHz to 18 GHz, Middle Channel, ANT V

RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1311.250	38.56	-15.77	74.0	35.44	Peak	43.00	150	Vertical	Pass
1**	1311.250	27.53	-15.77	54.0	26.47	AV	43.00	150	Vertical	Pass
2	2409.000	41.22	-12.64	74.0	32.78	Peak	2.00	150	Vertical	Pass
2**	2409.000	30.21	-12.64	54.0	23.79	AV	2.00	150	Vertical	Pass
3	3690.000	46.33	-5.79	74.0	27.67	Peak	157.00	150	Vertical	Pass
3**	3690.000	35.53	-5.79	54.0	18.47	AV	157.00	150	Vertical	Pass
4	5203.500	94.29	-2.39	74.0	-20.29	Peak	107.00	150	Vertical	N/A
4**	5203.500	85.51	-2.39	54.0	-31.51	AV	107.00	150	Vertical	N/A
5	7921.500	54.37	1.95	74.0	19.63	Peak	176.00	150	Vertical	Pass
5**	7921.500	43.27	1.95	54.0	10.73	AV	176.00	150	Vertical	Pass
6	13108.838	48.82	-2.00	74.0	25.18	Peak	82.00	150	Vertical	Pass
6**	13108.838	37.84	-2.00	54.0	16.16	AV	82.00	150	Vertical	Pass


11a, U-NII-2A, 1 GHz to 18 GHz, Middle Channel, ANT H

RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz
1.2E+2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1584.250	38.65	-16.15	74.0	35.35	Peak	81.00	150	Horizontal	Pass
1**	1584.250	27.52	-16.15	54.0	26.48	AV	81.00	150	Horizontal	Pass
2	2568.000	42.86	-11.05	74.0	31.14	Peak	211.00	150	Horizontal	Pass
2**	2568.000	31.50	-11.05	54.0	22.50	AV	211.00	150	Horizontal	Pass
3	3943.500	46.66	-4.26	74.0	27.34	Peak	148.00	150	Horizontal	Pass
3**	3943.500	35.56	-4.26	54.0	18.44	AV	148.00	150	Horizontal	Pass
4	5296.000	106.68	-2.00	74.0	-32.68	Peak	50.00	150	Horizontal	N/A
4**	5296.000	98.09	-2.00	54.0	-44.09	AV	50.00	150	Horizontal	N/A
5	7967.500	54.05	2.15	74.0	19.95	Peak	0.00	150	Horizontal	Pass
5**	7967.500	42.84	2.15	54.0	11.16	AV	0.00	150	Horizontal	Pass
6	12493.975	47.94	-2.71	74.0	26.06	Peak	76.00	150	Horizontal	Pass
6**	12493.975	37.32	-2.71	54.0	16.68	AV	76.00	150	Horizontal	Pass

11a, U-NII-2A, 1 GHz to 18 GHz, Middle Channel, ANT V


RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1582.250	38.41	-16.12	74.0	35.59	Peak	294.00	150	Vertical	Pass
1**	1582.250	27.25	-16.12	54.0	26.75	AV	294.00	150	Vertical	Pass
2	2529.500	43.37	-11.43	74.0	30.63	Peak	360.00	150	Vertical	Pass
2**	2529.500	30.90	-11.43	54.0	23.10	AV	360.00	150	Vertical	Pass
3	3998.500	46.87	-4.79	74.0	27.13	Peak	248.00	150	Vertical	Pass
3**	3998.500	35.89	-4.79	54.0	18.11	AV	248.00	150	Vertical	Pass
4	5297.000	100.72	-2.01	74.0	-26.72	Peak	89.00	150	Vertical	N/A
4**	5297.000	92.18	-2.01	54.0	-38.18	AV	89.00	150	Vertical	N/A
5	7922.500	54.63	1.94	74.0	19.37	Peak	0.00	150	Vertical	Pass
5**	7922.500	43.26	1.94	54.0	10.74	AV	0.00	150	Vertical	Pass
6	14597.737	49.58	-2.23	74.0	24.42	Peak	82.00	150	Vertical	Pass
6**	14597.737	38.68	-2.23	54.0	15.32	AV	82.00	150	Vertical	Pass


11n20, U-NII-2A, 1 GHz to 18 GHz, Middle Channel, ANT H

RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1464.500	38.49	-16.21	74.0	35.51	Peak	40.00	150	Horizontal	Pass
1**	1464.500	27.31	-16.21	54.0	26.69	AV	40.00	150	Horizontal	Pass
2	2543.500	42.34	-11.07	74.0	31.66	Peak	360.00	150	Horizontal	Pass
2**	2543.500	31.37	-11.07	54.0	22.63	AV	360.00	150	Horizontal	Pass
3	4049.000	46.63	-4.17	74.0	27.37	Peak	0.00	150	Horizontal	Pass
3**	4049.000	35.62	-4.17	54.0	18.38	AV	0.00	150	Horizontal	Pass
4	5297.500	107.16	-2.03	74.0	-33.16	Peak	50.00	150	Horizontal	N/A
4**	5297.500	99.00	-2.03	54.0	-45.00	AV	50.00	150	Horizontal	N/A
5	7951.500	54.36	2.15	74.0	19.64	Peak	209.00	150	Horizontal	Pass
5**	7951.500	42.83	2.15	54.0	11.17	AV	209.00	150	Horizontal	Pass
6	13227.225	48.38	-2.52	74.0	25.62	Peak	47.00	150	Horizontal	Pass
6**	13227.225	37.48	-2.52	54.0	16.52	AV	47.00	150	Horizontal	Pass


11n20, U-NII-2A, 1 GHz to 18 GHz, Middle Channel, ANT V

RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz
1.2E+2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1585.000	39.37	-16.14	74.0	34.63	Peak	285.00	150	Vertical	Pass
1**	1585.000	27.40	-16.14	54.0	26.60	AV	285.00	150	Vertical	Pass
2	2615.250	43.13	-10.46	74.0	30.87	Peak	121.00	150	Vertical	Pass
2**	2615.250	31.96	-10.46	54.0	22.04	AV	121.00	150	Vertical	Pass
3	4214.500	46.94	-3.63	74.0	27.06	Peak	11.00	150	Vertical	Pass
3**	4214.500	35.72	-3.63	54.0	18.28	AV	11.00	150	Vertical	Pass
4	5302.000	98.27	-2.05	74.0	-24.27	Peak	32.00	150	Vertical	N/A
4**	5302.000	90.94	-2.05	54.0	-36.94	AV	32.00	150	Vertical	N/A
5	7861.500	54.00	1.70	74.0	20.00	Peak	139.00	150	Vertical	Pass
5**	7861.500	42.93	1.70	54.0	11.07	AV	139.00	150	Vertical	Pass
6	12933.224	48.64	-2.11	74.0	25.36	Peak	49.00	150	Vertical	Pass
6**	12933.224	38.60	-2.11	54.0	15.40	AV	49.00	150	Vertical	Pass

11n40, U-NII-2A, 1 GHz to 18 GHz, Low Channel, ANT H


RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1652.250	38.01	-16.24	74.0	35.99	Peak	0.00	150	Horizontal	Pass
1**	1652.250	27.46	-16.24	54.0	26.54	AV	0.00	150	Horizontal	Pass
2	2564.250	42.41	-11.06	74.0	31.59	Peak	212.00	150	Horizontal	Pass
2**	2564.250	31.14	-11.06	54.0	22.86	AV	212.00	150	Horizontal	Pass
3	3879.000	46.71	-4.68	74.0	27.29	Peak	179.00	150	Horizontal	Pass
3**	3879.000	35.81	-4.68	54.0	18.19	AV	179.00	150	Horizontal	Pass
4	5272.500	103.78	-2.42	74.0	-29.78	Peak	41.00	150	Horizontal	N/A
4**	5272.500	96.23	-2.42	54.0	-42.23	AV	41.00	150	Horizontal	N/A
5	7768.500	54.70	1.28	74.0	19.30	Peak	360.00	150	Horizontal	Pass
5**	7768.500	42.44	1.28	54.0	11.56	AV	360.00	150	Horizontal	Pass
6	12602.276	49.06	-2.79	74.0	24.94	Peak	50.00	150	Horizontal	Pass
6**	12602.276	37.99	-2.79	54.0	16.01	AV	50.00	150	Horizontal	Pass


11n40, U-NII-2A, 1 GHz to 18 GHz, Low Channel, ANT V

RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1321.750	39.23	-15.88	74.0	34.77	Peak	0.00	150	Vertical	Pass
1**	1321.750	27.44	-15.88	54.0	26.56	AV	0.00	150	Vertical	Pass
2	2368.500	41.36	-12.48	74.0	32.64	Peak	306.00	150	Vertical	Pass
2**	2368.500	29.52	-12.48	54.0	24.48	AV	306.00	150	Vertical	Pass
3	3969.500	46.53	-4.03	74.0	27.47	Peak	132.00	150	Vertical	Pass
3**	3969.500	35.57	-4.03	54.0	18.43	AV	132.00	150	Vertical	Pass
4	5267.000	96.77	-2.39	74.0	-22.77	Peak	83.00	150	Vertical	N/A
4**	5267.000	88.83	-2.39	54.0	-34.83	AV	83.00	150	Vertical	N/A
5	7714.000	54.03	1.10	74.0	19.97	Peak	360.00	150	Vertical	Pass
5**	7714.000	41.83	1.10	54.0	12.17	AV	360.00	150	Vertical	Pass
6	12579.000	48.29	-2.63	74.0	25.71	Peak	6.00	150	Vertical	Pass
6**	12579.000	37.51	-2.63	54.0	16.49	AV	6.00	150	Vertical	Pass

11ac80, U-NII-2A, 1 GHz to 18 GHz, Middle Channel, ANT H

RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz
1.2E+2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1743.000	38.70	-16.13	74.0	35.30	Peak	248.00	150	Horizontal	Pass
1**	1743.000	27.47	-16.13	54.0	26.53	AV	248.00	150	Horizontal	Pass
2	2668.000	42.57	-10.85	74.0	31.43	Peak	255.00	150	Horizontal	Pass
2**	2668.000	31.07	-10.85	54.0	22.93	AV	255.00	150	Horizontal	Pass
3	3944.000	46.08	-4.28	74.0	27.92	Peak	259.00	150	Horizontal	Pass
3**	3944.000	35.84	-4.28	54.0	18.16	AV	259.00	150	Horizontal	Pass
4	5283.500	101.71	-2.19	74.0	-27.71	Peak	50.00	150	Horizontal	N/A
4**	5283.500	92.40	-2.19	54.0	-38.40	AV	50.00	150	Horizontal	N/A
5	7859.500	54.54	1.65	74.0	19.46	Peak	209.00	150	Horizontal	Pass
5**	7859.500	42.65	1.65	54.0	11.35	AV	209.00	150	Horizontal	Pass
6	12920.887	48.36	-2.42	74.0	25.64	Peak	278.00	150	Horizontal	Pass
6**	12920.887	38.15	-2.42	54.0	15.85	AV	278.00	150	Horizontal	Pass


11ac80, U-NII-2A, 1 GHz to 18 GHz, Middle Channel, ANT V

RE Test case_FCC Part 15E_FCC 15.407(5.15-5.35)_1GHz-18GHz
1.2E+2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1632.750	38.58	-16.11	74.0	35.42	Peak	0.00	150	Vertical	Pass
1**	1632.750	27.39	-16.11	54.0	26.61	AV	0.00	150	Vertical	Pass
2	2614.250	42.86	-10.54	74.0	31.14	Peak	0.00	150	Vertical	Pass
2**	2614.250	31.75	-10.54	54.0	22.25	AV	0.00	150	Vertical	Pass
3	3923.500	45.94	-3.70	74.0	28.06	Peak	242.00	150	Vertical	Pass
3**	3923.500	35.37	-3.70	54.0	18.63	AV	242.00	150	Vertical	Pass
4	5288.500	94.20	-2.04	74.0	-20.20	Peak	105.00	150	Vertical	N/A
4**	5288.500	86.33	-2.04	54.0	-32.33	AV	105.00	150	Vertical	N/A
5	7976.500	54.27	1.89	74.0	19.73	Peak	35.00	150	Vertical	Pass
5**	7976.500	42.72	1.89	54.0	11.28	AV	35.00	150	Vertical	Pass
6	12399.925	48.52	-2.30	74.0	25.48	Peak	332.00	150	Vertical	Pass
6**	12399.925	37.59	-2.30	54.0	16.41	AV	332.00	150	Vertical	Pass

11a, U-NII-2C, 1 GHz to 18 GHz, Middle Channel, ANT H


RE Test case_FCC Part 15E_FCC 15.407(5.47-5.725)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1197.000	38.31	-15.71	74.0	35.69	Peak	78.00	150	Horizontal	Pass
1**	1197.000	27.34	-15.71	54.0	26.66	AV	78.00	150	Horizontal	Pass
2	2163.250	40.89	-13.22	74.0	33.11	Peak	302.00	150	Horizontal	Pass
2**	2163.250	29.98	-13.22	54.0	24.02	AV	302.00	150	Horizontal	Pass
3	3410.000	48.09	-5.33	74.0	25.91	Peak	251.00	150	Horizontal	Pass
3**	3410.000	38.99	-5.33	54.0	15.01	AV	251.00	150	Horizontal	Pass
4	5579.000	108.65	-2.87	74.0	-34.65	Peak	53.00	150	Horizontal	N/A
4**	5579.000	101.16	-2.87	54.0	-47.16	AV	53.00	150	Horizontal	N/A
5	7788.000	54.52	1.59	74.0	19.48	Peak	359.00	150	Horizontal	Pass
5**	7788.000	42.91	1.59	54.0	11.09	AV	359.00	150	Horizontal	Pass
6	13104.113	47.92	-2.03	74.0	26.08	Peak	82.00	150	Horizontal	Pass
6**	13104.113	37.54	-2.03	54.0	16.46	AV	82.00	150	Horizontal	Pass

11a, U-NII-2C, 1 GHz to 18 GHz, Middle Channel, ANT V


RE Test case_FCC Part 15E_FCC 15.407(5.47-5.725)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1359.000	38.73	-15.86	74.0	35.27	Peak	181.00	150	Vertical	Pass
1**	1359.000	27.78	-15.86	54.0	26.22	AV	181.00	150	Vertical	Pass
2	2269.000	41.20	-13.15	74.0	32.80	Peak	257.00	150	Vertical	Pass
2**	2269.000	29.65	-13.15	54.0	24.35	AV	257.00	150	Vertical	Pass
3	3450.000	48.17	-4.99	74.0	25.83	Peak	93.00	150	Vertical	Pass
3**	3450.000	35.53	-4.99	54.0	18.47	AV	93.00	150	Vertical	Pass
4	5578.000	150.92	-2.89	74.0	-26.92	Peak	83.00	150	Vertical	N/A
4**	5578.000	93.01	-2.89	54.0	-39.01	AV	83.00	150	Vertical	N/A
5	7995.500	54.06	1.79	74.0	19.94	Peak	63.00	150	Vertical	Pass
5**	7995.500	43.05	1.79	54.0	10.95	AV	63.00	150	Vertical	Pass
6	12913.013	48.28	-2.74	74.0	25.72	Peak	0.00	150	Vertical	Pass
6**	12913.013	37.33	-2.74	54.0	16.67	AV	0.00	150	Vertical	Pass

11n20, U-NII-2C, 1 GHz to 18 GHz, Middle Channel, ANT H


RE Test case_FCC Part 15E_FCC 15.407(5.47-5.725)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1059.250	38.15	-15.33	74.0	35.85	Peak	257.00	150	Horizontal	Pass
1**	1059.250	26.93	-15.33	54.0	27.07	AV	257.00	150	Horizontal	Pass
2	1966.500	39.26	-14.92	74.0	34.74	Peak	290.00	150	Horizontal	Pass
2**	1966.500	29.28	-14.92	54.0	24.72	AV	290.00	150	Horizontal	Pass
3	3312.000	46.65	-6.59	74.0	27.35	Peak	54.00	150	Horizontal	Pass
3**	3312.000	34.77	-6.59	54.0	19.23	AV	54.00	150	Horizontal	Pass
4	5582.500	108.59	-2.84	74.0	-34.59	Peak	34.00	150	Horizontal	N/A
4**	5582.500	150.79	-2.84	54.0	-46.79	AV	34.00	150	Horizontal	N/A
5	7937.000	54.89	1.99	74.0	19.11	Peak	352.00	150	Horizontal	Pass
5**	7937.000	43.76	1.99	54.0	10.24	AV	352.00	150	Horizontal	Pass
6	12379.500	48.53	-2.32	74.0	25.47	Peak	360.00	150	Horizontal	Pass
6**	12379.500	37.54	-2.32	54.0	16.46	AV	360.00	150	Horizontal	Pass

11n20, U-NII-2C, 1 GHz to 18 GHz, Middle Channel, ANT V


RE Test case_FCC Part 15E_FCC 15.407(5.47-5.725)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1159.750	38.16	-15.50	74.0	35.84	Peak	360.00	150	Vertical	Pass
1**	1159.750	27.21	-15.50	54.0	26.79	AV	360.00	150	Vertical	Pass
2	2005.250	39.96	-14.22	74.0	34.04	Peak	249.00	150	Vertical	Pass
2**	2005.250	29.48	-14.22	54.0	24.52	AV	249.00	150	Vertical	Pass
3	3360.000	46.55	-5.81	74.0	27.45	Peak	291.00	150	Vertical	Pass
3**	3360.000	36.04	-5.81	54.0	17.96	AV	291.00	150	Vertical	Pass
4	5583.500	101.05	-2.83	74.0	-27.05	Peak	74.00	150	Vertical	N/A
4**	5583.500	92.73	-2.83	54.0	-38.73	AV	74.00	150	Vertical	N/A
5	7922.500	54.24	1.94	74.0	19.76	Peak	133.00	150	Vertical	Pass
5**	7922.500	43.03	1.94	54.0	10.97	AV	133.00	150	Vertical	Pass
6	12674.950	48.28	-2.92	74.0	25.72	Peak	241.00	150	Vertical	Pass
6**	12674.950	37.14	-2.92	54.0	16.86	AV	241.00	150	Vertical	Pass

11n40, U-NII-2C, 1 GHz to 18 GHz, Middle Channel, ANT H


RE Test case_FCC Part 15E_FCC 15.407(5.47-5.725)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1205.750	38.51	-15.78	74.0	35.49	Peak	247.00	150	Horizontal	Pass
1**	1205.750	27.41	-15.78	54.0	26.59	AV	247.00	150	Horizontal	Pass
2	1993.500	40.67	-14.63	74.0	33.33	Peak	290.00	150	Horizontal	Pass
2**	1993.500	28.95	-14.63	54.0	25.05	AV	290.00	150	Horizontal	Pass
3	3963.500	46.70	-3.81	74.0	27.30	Peak	84.00	150	Horizontal	Pass
3**	3963.500	35.84	-3.81	54.0	18.16	AV	84.00	150	Horizontal	Pass
4	5594.000	107.31	-2.82	74.0	-33.31	Peak	53.00	150	Horizontal	N/A
4**	5594.000	98.86	-2.82	54.0	-44.86	AV	53.00	150	Horizontal	N/A
5	7931.000	53.33	2.06	74.0	20.67	Peak	0.00	150	Horizontal	Pass
5**	7931.000	43.41	2.06	54.0	10.59	AV	0.00	150	Horizontal	Pass
6	14489.850	48.79	-2.78	74.0	25.21	Peak	359.00	150	Horizontal	Pass
6**	14489.850	37.99	-2.78	54.0	16.01	AV	359.00	150	Horizontal	Pass

11n40, U-NII-2C, 1 GHz to 18 GHz, Middle Channel, ANT V


RE Test case_FCC Part 15E_FCC 15.407(5.47-5.725)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1375.500	38.67	-16.00	74.0	35.33	Peak	319.00	150	Vertical	Pass
1**	1375.500	27.24	-16.00	54.0	26.76	AV	319.00	150	Vertical	Pass
2	2281.500	40.81	-12.74	74.0	33.19	Peak	153.00	150	Vertical	Pass
2**	2281.500	29.52	-12.74	54.0	24.48	AV	153.00	150	Vertical	Pass
3	3814.000	45.90	-4.63	74.0	28.10	Peak	359.00	150	Vertical	Pass
3**	3814.000	35.32	-4.63	54.0	18.68	AV	359.00	150	Vertical	Pass
4	5592.000	97.93	-2.80	74.0	-23.93	Peak	204.00	150	Vertical	N/A
4**	5592.000	90.27	-2.80	54.0	-36.27	AV	204.00	150	Vertical	N/A
5	7869.000	53.80	1.79	74.0	20.20	Peak	0.00	150	Vertical	Pass
5**	7869.000	42.89	1.79	54.0	11.11	AV	0.00	150	Vertical	Pass
6	12946.612	49.09	-2.48	74.0	24.91	Peak	359.00	150	Vertical	Pass
6**	12946.612	38.65	-2.48	54.0	15.35	AV	359.00	150	Vertical	Pass

11ac80, U-NII-2C, 1 GHz to 18 GHz, Low Channel, ANT H


RE Test case_FCC Part 15E_FCC 15.407(5.47-5.725)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1176.250	38.36	-15.66	74.0	35.64	Peak	310.00	150	Horizontal	Pass
1**	1176.250	27.17	-15.66	54.0	26.83	AV	310.00	150	Horizontal	Pass
2	1950.250	39.42	-14.84	74.0	34.58	Peak	196.00	150	Horizontal	Pass
2**	1950.250	28.37	-14.84	54.0	25.63	AV	196.00	150	Horizontal	Pass
3	3871.500	46.43	-5.10	74.0	27.57	Peak	115.00	150	Horizontal	Pass
3**	3871.500	35.48	-5.10	54.0	18.52	AV	115.00	150	Horizontal	Pass
4	5523.000	101.82	-2.47	74.0	-27.82	Peak	53.00	150	Horizontal	N/A
4**	5523.000	92.15	-2.47	54.0	-38.15	AV	53.00	150	Horizontal	N/A
5	7965.500	54.04	2.26	74.0	19.96	Peak	115.00	150	Horizontal	Pass
5**	7965.500	43.09	2.26	54.0	10.91	AV	115.00	150	Horizontal	Pass
6	12667.112	48.33	-3.06	74.0	25.67	Peak	192.00	150	Horizontal	Pass
6**	12667.112	37.52	-3.06	54.0	16.48	AV	192.00	150	Horizontal	Pass

11ac80, U-NII-2C, 1 GHz to 18 GHz, Low Channel, ANT V


RE Test case_FCC Part 15E_FCC 15.407(5.47-5.725)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1218.750	39.26	-15.96	74.0	34.74	Peak	262.00	150	Vertical	Pass
1**	1218.750	26.85	-15.96	54.0	27.15	AV	262.00	150	Vertical	Pass
2	2120.750	41.78	-13.34	74.0	32.22	Peak	322.00	150	Vertical	Pass
2**	2120.750	32.39	-13.34	54.0	21.61	AV	322.00	150	Vertical	Pass
3	3427.500	47.46	-4.93	74.0	26.54	Peak	15.00	150	Vertical	Pass
3**	3427.500	36.60	-4.93	54.0	17.40	AV	15.00	150	Vertical	Pass
4	5526.000	91.14	-2.44	74.0	-17.14	Peak	82.00	150	Vertical	N/A
4**	5526.000	82.82	-2.44	54.0	-28.82	AV	82.00	150	Vertical	N/A
5	7920.500	53.40	1.94	74.0	20.60	Peak	94.00	150	Vertical	Pass
5**	7920.500	43.09	1.94	54.0	10.91	AV	94.00	150	Vertical	Pass
6	14455.725	48.35	-2.64	74.0	25.65	Peak	117.00	150	Vertical	Pass
6**	14455.725	38.77	-2.64	54.0	15.23	AV	117.00	150	Vertical	Pass


11a, U-NII-3, 1 GHz to 18 GHz, Middle Channel, ANT H

RE Test case_FCC Part 15E_FCC 15.407(5.725-5.85)_1GHz-18GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1751.750	38.52	-15.96	74.0	35.48	Peak	135.00	150	Horizontal	Pass
1**	1751.750	27.37	-15.96	54.0	26.63	AV	135.00	150	Horizontal	Pass
2	2917.500	43.96	-8.82	74.0	30.04	Peak	94.00	150	Horizontal	Pass
2**	2917.500	32.71	-8.82	54.0	21.29	AV	94.00	150	Horizontal	Pass
3	4339.000	47.40	-3.09	74.0	26.60	Peak	305.00	150	Horizontal	Pass
3**	4339.000	36.77	-3.09	54.0	17.23	AV	305.00	150	Horizontal	Pass
4	5784.000	109.57	-1.54	74.0	-35.57	Peak	32.00	150	Horizontal	N/A
4**	5784.000	102.09	-1.54	54.0	-48.09	AV	32.00	150	Horizontal	N/A
5	8370.737	47.14	-4.44	74.0	26.86	Peak	360.00	150	Horizontal	Pass
5**	8370.737	36.86	-4.44	54.0	17.14	AV	360.00	150	Horizontal	Pass
6	13910.513	48.78	-2.60	74.0	25.22	Peak	284.00	150	Horizontal	Pass
6**	13910.513	37.97	-2.60	54.0	16.03	AV	284.00	150	Horizontal	Pass

11a, U-NII-3, 1 GHz to 18 GHz, Middle Channel, ANT V

RE Test case_FCC Part 15E_FCC 15.407(5.725-5.85)_1GHz-18GHz
1.2E+2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1289.500	38.41	-15.87	74.0	35.59	Peak	298.00	150	Vertical	Pass
1**	1289.500	27.40	-15.87	54.0	26.60	AV	298.00	150	Vertical	Pass
2	2201.750	40.75	-13.34	74.0	33.25	Peak	176.00	150	Vertical	Pass
2**	2201.750	29.65	-13.34	54.0	24.35	AV	176.00	150	Vertical	Pass
3	3918.500	46.11	-3.95	74.0	27.89	Peak	99.00	150	Vertical	Pass
3**	3918.500	35.24	-3.95	54.0	18.76	AV	99.00	150	Vertical	Pass
4	5786.500	104.59	-1.53	74.0	-30.59	Peak	197.00	150	Vertical	N/A
4**	5786.500	96.59	-1.53	54.0	-42.59	AV	197.00	150	Vertical	N/A
5	9518.812	47.10	-2.80	74.0	26.90	Peak	215.00	150	Vertical	Pass
5**	9518.812	36.54	-2.80	54.0	17.46	AV	215.00	150	Vertical	Pass
6	15308.063	49.29	-1.93	74.0	24.71	Peak	0.00	150	Vertical	Pass
6**	15308.063	38.32	-1.93	54.0	15.68	AV	0.00	150	Vertical	Pass


11n20, U-NII-3, 1 GHz to 18 GHz, Middle Channel, ANT H

RE Test case_FCC Part 15E_FCC 15.407(5.725-5.85)_1GHz-18GHz
1.2E+2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1584.000	38.67	-16.15	74.0	35.33	Peak	268.00	150	Horizontal	Pass
1**	1584.000	27.34	-16.15	54.0	26.66	AV	268.00	150	Horizontal	Pass
2	2634.750	42.61	-9.95	74.0	31.39	Peak	358.00	150	Horizontal	Pass
2**	2634.750	32.23	-9.95	54.0	21.77	AV	358.00	150	Horizontal	Pass
3	4062.000	46.51	-4.08	74.0	27.49	Peak	0.00	150	Horizontal	Pass
3**	4062.000	35.86	-4.08	54.0	18.14	AV	0.00	150	Horizontal	Pass
4	5782.500	109.71	-1.53	74.0	-35.71	Peak	43.00	150	Horizontal	N/A
4**	5782.500	101.32	-1.53	54.0	-47.32	AV	43.00	150	Horizontal	N/A
5	9304.350	47.03	-5.41	74.0	26.97	Peak	2.00	150	Horizontal	Pass
5**	9304.350	36.62	-5.41	54.0	17.38	AV	2.00	150	Horizontal	Pass
6	14719.537	49.16	-1.88	74.0	24.84	Peak	0.00	150	Horizontal	Pass
6**	14719.537	38.65	-1.88	54.0	15.35	AV	0.00	150	Horizontal	Pass


11n20, U-NII-3, 1 GHz to 18 GHz, Middle Channel, ANT V

RE Test case_FCC Part 15E_FCC 15.407(5.725-5.85)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1686.000	38.35	-16.42	74.0	35.65	Peak	360.00	150	Vertical	Pass
1**	1686.000	27.24	-16.42	54.0	26.76	AV	360.00	150	Vertical	Pass
2	2618.250	42.82	-10.24	74.0	31.18	Peak	315.00	150	Vertical	Pass
2**	2618.250	31.82	-10.24	54.0	22.18	AV	315.00	150	Vertical	Pass
3	3930.500	46.44	-3.51	74.0	27.56	Peak	93.00	150	Vertical	Pass
3**	3930.500	35.28	-3.51	54.0	18.72	AV	93.00	150	Vertical	Pass
4	5783.500	101.99	-1.54	74.0	-27.99	Peak	0.00	150	Vertical	N/A
4**	5783.500	94.04	-1.54	54.0	-40.04	AV	0.00	150	Vertical	N/A
5	9671.999	47.64	-3.54	74.0	26.36	Peak	333.00	150	Vertical	Pass
5**	9671.999	35.17	-3.54	54.0	18.83	AV	333.00	150	Vertical	Pass
6	14592.750	49.20	-2.06	74.0	24.80	Peak	182.00	150	Vertical	Pass
6**	14592.750	38.78	-2.06	54.0	15.22	AV	182.00	150	Vertical	Pass


11n40, U-NII-3, 1 GHz to 18 GHz, Low Channel, ANT H

RE Test case_FCC Part 15E_FCC 15.407(5.725-5.85)_1GHz-18GHz
1.2E+2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1569.250	39.42	-16.07	74.0	34.58	Peak	94.00	150	Horizontal	Pass
1**	1569.250	27.34	-16.07	54.0	26.66	AV	94.00	150	Horizontal	Pass
2	2572.000	42.22	-10.96	74.0	31.78	Peak	360.00	150	Horizontal	Pass
2**	2572.000	31.14	-10.96	54.0	22.86	AV	360.00	150	Horizontal	Pass
3	4008.500	46.41	-4.50	74.0	27.59	Peak	179.00	150	Horizontal	Pass
3**	4008.500	35.69	-4.50	54.0	18.31	AV	179.00	150	Horizontal	Pass
4	5752.000	107.33	-2.10	74.0	-33.33	Peak	40.00	150	Horizontal	N/A
4**	5752.000	99.53	-2.10	54.0	-45.53	AV	40.00	150	Horizontal	N/A
5	9014.125	46.86	-4.67	74.0	27.14	Peak	122.00	150	Horizontal	Pass
5**	9014.125	36.19	-4.67	54.0	17.81	AV	122.00	150	Horizontal	Pass
6	14460.713	49.43	-2.70	74.0	24.57	Peak	286.00	150	Horizontal	Pass
6**	14460.713	37.95	-2.70	54.0	16.05	AV	286.00	150	Horizontal	Pass


11n40, U-NII-3, 1 GHz to 18 GHz, Low Channel, ANT V

RE Test case_FCC Part 15E_FCC 15.407(5.725-5.85)_1GHz-18GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1369.000	38.34	-15.93	74.0	35.66	Peak	353.00	150	Vertical	Pass
1**	1369.000	27.59	-15.93	54.0	26.41	AV	353.00	150	Vertical	Pass
2	2301.750	40.98	-12.95	74.0	33.02	Peak	18.00	150	Vertical	Pass
2**	2301.750	29.94	-12.95	54.0	24.06	AV	18.00	150	Vertical	Pass
3	3806.000	46.74	-4.33	74.0	27.26	Peak	0.00	150	Vertical	Pass
3**	3806.000	35.11	-4.33	54.0	18.89	AV	0.00	150	Vertical	Pass
4	5753.000	99.61	-2.09	74.0	-25.61	Peak	353.00	150	Vertical	N/A
4**	5753.000	92.00	-2.09	54.0	-38.00	AV	353.00	150	Vertical	N/A
5	9646.349	47.09	-3.35	74.0	26.91	Peak	360.00	150	Vertical	Pass
5**	9646.349	36.43	-3.35	54.0	17.57	AV	360.00	150	Vertical	Pass
6	14853.937	48.94	-0.83	74.0	25.06	Peak	0.00	150	Vertical	Pass
6**	14853.937	37.63	-0.83	54.0	16.37	AV	0.00	150	Vertical	Pass

11ac80, U-NII-3, 1 GHz to 18 GHz, Middle Channel, ANT H

RE Test case_FCC Part 15E_FCC 15.407(5.725-5.85)_1GHz-18GHz
1.2E+2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1612.750	38.54	-16.20	74.0	35.46	Peak	263.00	150	Horizontal	Pass
1**	1612.750	27.21	-16.20	54.0	26.79	AV	263.00	150	Horizontal	Pass
2	2606.250	43.01	-11.09	74.0	30.99	Peak	169.00	150	Horizontal	Pass
2**	2606.250	31.97	-11.09	54.0	22.03	AV	169.00	150	Horizontal	Pass
3	3876.500	46.67	-4.77	74.0	27.33	Peak	210.00	150	Horizontal	Pass
3**	3876.500	35.61	-4.77	54.0	18.39	AV	210.00	150	Horizontal	Pass
4	5768.500	103.93	-1.70	74.0	-29.93	Peak	32.00	150	Horizontal	N/A
4**	5768.500	95.51	-1.70	54.0	-41.51	AV	32.00	150	Horizontal	N/A
5	9268.250	47.07	-5.20	74.0	26.93	Peak	285.00	150	Horizontal	Pass
5**	9268.250	36.49	-5.20	54.0	17.51	AV	285.00	150	Horizontal	Pass
6	15264.750	50.25	-1.02	74.0	23.75	Peak	150.00	150	Horizontal	Pass
6**	15264.750	39.00	-1.02	54.0	15.00	AV	150.00	150	Horizontal	Pass

11ac80, U-NII-3, 1 GHz to 18 GHz, Middle Channel, ANT V

RE Test case_FCC Part 15E_FCC 15.407(5.725-5.85)_1GHz-18GHz
1.2E+2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1596.750	38.36	-16.22	74.0	35.64	Peak	21.00	150	Vertical	Pass
1**	1596.750	27.45	-16.22	54.0	26.55	AV	21.00	150	Vertical	Pass
2	2522.250	42.58	-11.99	74.0	31.42	Peak	206.00	150	Vertical	Pass
2**	2522.250	31.46	-11.99	54.0	22.54	AV	206.00	150	Vertical	Pass
3	3909.500	47.05	-4.45	74.0	26.95	Peak	190.00	150	Vertical	Pass
3**	3909.500	34.85	-4.45	54.0	19.15	AV	190.00	150	Vertical	Pass
4	5780.000	96.60	-1.51	74.0	-22.60	Peak	355.00	150	Vertical	N/A
4**	5780.000	88.83	-1.51	54.0	-34.83	AV	355.00	150	Vertical	N/A
5	9285.112	47.22	-5.55	74.0	26.78	Peak	192.00	150	Vertical	Pass
5**	9285.112	35.56	-5.55	54.0	18.44	AV	192.00	150	Vertical	Pass
6	15254.776	49.29	-1.20	74.0	24.71	Peak	319.00	150	Vertical	Pass
6**	15254.776	38.57	-1.20	54.0	15.43	AV	319.00	150	Vertical	Pass


A.6.2 Band Edge (Restricted-band)

Test Band	Mode	Channel	Verdict
U-NII-1	802.11a	Low	Pass
		High	Pass
	802.11n(HT20)	Low	Pass
		High	Pass
	802.11n(HT40)	Low	Pass
		High	Pass
	802.11ac(VHT20)	Low	Pass
		High	Pass
U-NII-2A	802.11a	Low	Pass
		High	Pass
	802.11n(HT20)	Low	Pass
		High	Pass
	802.11n(HT40)	Low	Pass
		High	Pass
	802.11ac(VHT20)	Low	Pass
		High	Pass
U-NII-2C	802.11a	Low	Pass
		High	Pass
	802.11n(HT20)	Low	Pass
		High	Pass
	802.11n(HT40)	Low	Pass
		High	Pass
	802.11ac(VHT20)	Low	Pass
		High	Pass
U-NII-3	802.11a	Low	Pass
		High	Pass
	802.11n(HT20)	Low	Pass
		High	Pass
	802.11n(HT40)	Low	Pass
		High	Pass
	802.11ac(VHT80)	Low	Pass
		High	Pass

		High	Pass
	802.11ac(VHT20)	Low	Pass
		High	Pass
	802.11ac(VHT40)	Low	Pass
		High	Pass
	802.11ac(VHT80)	Middle	Pass


Test Data and Plots

U-NII-1 11a CH36




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5150.000	62.46	3.82	74.0	11.54	Peak	41.00	150	Horizontal	Pass
1**	5150.000	48.99	3.82	54.0	5.01	AV	41.00	150	Horizontal	Pass
2	5146.100	62.80	3.93	74.0	11.20	Peak	51.00	150	Horizontal	Pass
2**	5146.100	48.89	3.93	54.0	5.11	AV	51.00	150	Horizontal	Pass

U-NII-1 11a CH48



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5350.000	54.99	4.04	74.0	19.01	Peak	197.00	150	Horizontal	Pass
1**	5350.000	44.68	4.04	54.0	9.32	AV	197.00	150	Horizontal	Pass
2	5405.110	56.62	3.92	74.0	17.38	Peak	26.00	150	Horizontal	Pass
2**	5405.110	44.61	3.92	54.0	9.39	AV	26.00	150	Horizontal	Pass

U-NII-1 11n20 CH36




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5150.000	66.15	3.82	74.0	7.85	Peak	44.00	150	Horizontal	Pass
1**	5150.000	49.19	3.82	54.0	4.81	AV	44.00	150	Horizontal	Pass
2	5149.350	65.91	3.84	74.0	8.09	Peak	44.00	150	Horizontal	Pass
2**	5149.350	49.19	3.84	54.0	4.81	AV	44.00	150	Horizontal	Pass

U-NII-1 11n20 CH48



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5350.000	55.20	4.04	74.0	18.80	Peak	62.00	150	Horizontal	Pass
1**	5350.000	44.69	4.04	54.0	9.31	AV	62.00	150	Horizontal	Pass
2	5435.910	56.65	3.70	74.0	17.35	Peak	13.00	150	Horizontal	Pass
2**	5435.910	44.18	3.70	54.0	9.82	AV	13.00	150	Horizontal	Pass

U-NII-1 11n40 CH38




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5150.000	69.72	3.82	74.0	4.28	Peak	46.00	150	Horizontal	Pass
1**	5150.000	49.25	3.82	54.0	4.75	AV	46.00	150	Horizontal	Pass
2	5149.350	68.71	3.84	74.0	5.29	Peak	53.00	150	Horizontal	Pass
2**	5149.350	48.83	3.84	54.0	5.17	AV	53.00	150	Horizontal	Pass

U-NII-1 11n40 CH46




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5350.000	55.04	4.04	74.0	18.96	Peak	27.00	150	Horizontal	Pass
1**	5350.000	44.75	4.04	54.0	9.25	AV	27.00	150	Horizontal	Pass
2	5389.710	56.52	4.00	74.0	17.48	Peak	25.00	150	Horizontal	Pass
2**	5389.710	44.38	4.00	54.0	9.62	AV	25.00	150	Horizontal	Pass

U-NII-1 11ac80 CH42




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5150.000	63.74	3.82	74.0	10.26	Peak	54.00	150	Horizontal	Pass
1**	5150.000	49.49	3.82	54.0	4.51	AV	54.00	150	Horizontal	Pass
2	5142.850	64.55	4.02	74.0	9.45	Peak	50.00	150	Horizontal	Pass
2**	5142.850	48.53	4.02	54.0	5.47	AV	50.00	150	Horizontal	Pass

U-NII-2A 11a CH52




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5150.000	54.84	3.82	74.0	19.16	Peak	359.94	150	Horizontal	Pass
1**	5150.000	44.41	3.82	54.0	9.59	AV	359.94	150	Horizontal	Pass
2	5137.000	55.73	4.01	74.0	18.27	Peak	360.00	150	Horizontal	Pass
2**	5137.000	44.41	4.01	54.0	9.59	AV	360.00	150	Horizontal	Pass

U-NII-2A 11a CH64




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5350.000	64.04	4.04	74.0	9.96	Peak	50.00	150	Horizontal	Pass
1**	5350.000	49.88	4.04	54.0	4.12	AV	50.00	150	Horizontal	Pass
2	5350.110	69.28	4.04	74.0	4.72	Peak	46.00	150	Horizontal	Pass
2**	5350.110	49.30	4.04	54.0	4.70	AV	46.00	150	Horizontal	Pass

U-NII-2A 11n20 CH52




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5150.000	54.34	3.82	74.0	19.66	Peak	51.01	150	Horizontal	Pass
1**	5150.000	44.60	3.82	54.0	9.40	AV	51.01	150	Horizontal	Pass
2	5029.750	56.30	3.64	74.0	17.70	Peak	222.00	150	Horizontal	Pass
2**	5029.750	44.06	3.64	54.0	9.94	AV	222.00	150	Horizontal	Pass

U-NII-2A 11n20 CH64




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5350.000	67.27	4.04	74.0	6.73	Peak	44.00	150	Horizontal	Pass
1**	5350.000	47.87	4.04	54.0	6.13	AV	44.00	150	Horizontal	Pass
2	5350.660	67.45	4.05	74.0	6.55	Peak	44.00	150	Horizontal	Pass
2**	5350.660	48.23	4.05	54.0	5.77	AV	44.00	150	Horizontal	Pass

U-NII-2A 11n40 CH54




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5150.000	54.00	3.82	74.0	20.00	Peak	241.97	150	Horizontal	Pass
1**	5150.000	44.57	3.82	54.0	9.43	AV	241.97	150	Horizontal	Pass
2	5088.900	56.55	3.45	74.0	17.45	Peak	211.00	150	Horizontal	Pass
2**	5088.900	44.09	3.45	54.0	9.91	AV	211.00	150	Horizontal	Pass

U-NII-2A 11n40 CH62




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5350.000	69.41	4.04	74.0	4.59	Peak	44.00	150	Horizontal	Pass
1**	5350.000	49.70	4.04	54.0	4.30	AV	44.00	150	Horizontal	Pass
2	5350.330	68.75	4.05	74.0	5.25	Peak	46.00	150	Horizontal	Pass
2**	5350.330	49.76	4.05	54.0	4.24	AV	46.00	150	Horizontal	Pass

U-NII-2A 11ac80 CH58




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5350.000	58.86	4.04	74.0	15.14	Peak	54.00	150	Horizontal	Pass
1**	5350.000	49.19	4.04	54.0	4.81	AV	54.00	150	Horizontal	Pass
2	5350.770	62.03	4.06	74.0	11.97	Peak	40.00	150	Horizontal	Pass
2**	5350.770	48.93	4.06	54.0	5.07	AV	40.00	150	Horizontal	Pass

U-NII-2C 11a CH100




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5460.000	56.51	3.78	68.2	11.69	Peak	38.65	150	Horizontal	Pass
1**	5460.000	46.63	3.78	54.0	7.37	AV	38.65	150	Horizontal	Pass
2	5469.760	63.79	4.09	68.2	4.41	Peak	50.00	150	Horizontal	Pass
2**	5469.760	47.38	4.09	--	-47.38	AV	50.00	150	Horizontal	N/A

U-NII-2C 11a CH140




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5725.000	63.32	4.31	68.2	4.88	Peak	77.00	150	Horizontal	Pass
2	5726.500	64.83	4.26	68.2	3.37	Peak	50.00	150	Horizontal	Pass

U-NII-2C 11n20 CH100




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5460.000	58.66	3.78	68.2	9.54	Peak	51.00	150	Horizontal	Pass
1**	5460.000	46.63	3.78	54.0	7.37	AV	51.00	150	Horizontal	Pass
2	5463.520	62.71	3.89	68.2	5.49	Peak	64.00	150	Horizontal	Pass
2**	5463.520	46.95	3.89	--	-46.95	AV	64.00	150	Horizontal	N/A

U-NII-2C 11n20 CH140




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5725.000	60.94	4.31	68.2	7.26	Peak	53.00	150	Horizontal	Pass
2	5725.875	61.89	4.28	68.2	6.31	Peak	53.00	150	Horizontal	Pass

U-NII-2C 11n40 CH102




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5460.000	58.54	3.78	68.2	9.66	Peak	253.44	150	Horizontal	Pass
1**	5460.000	45.94	3.78	54.0	8.06	AV	253.44	150	Horizontal	Pass
2	5468.680	61.67	4.06	68.2	6.53	Peak	41.00	150	Horizontal	Pass
2**	5468.680	46.46	4.06	--	-46.46	AV	41.00	150	Horizontal	N/A

U-NII-2C 11n40 CH134




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5725.000	64.32	4.31	68.2	3.88	Peak	17.00	150	Horizontal	Pass
2	5726.000	64.61	4.27	68.2	3.59	Peak	17.00	150	Horizontal	Pass

U-NII-2C 11ac80 CH106




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5460.000	57.83	3.78	68.2	10.37	Peak	49.00	150	Horizontal	Pass
1**	5460.000	48.53	3.78	54.0	5.47	AV	49.00	150	Horizontal	Pass
2	5464.120	62.79	3.91	68.2	5.41	Peak	16.00	150	Horizontal	Pass
2**	5464.120	48.77	3.91	--	-48.77	AV	16.00	150	Horizontal	N/A

U-NII-2C 11ac80 CH122




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5725.000	60.57	4.31	68.2	7.63	Peak	45.00	150	Horizontal	Pass
2	5725.875	64.71	4.28	68.2	3.49	Peak	45.00	150	Horizontal	Pass

U-NII-3 11a CH149




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5650.000	57.15	3.81	68.2	11.05	Peak	29.01	150	Horizontal	Pass
2	5636.250	57.33	3.71	68.2	10.87	Peak	13.00	150	Horizontal	Pass

U-NII-3 11a CH165




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5925.000	56.83	6.44	68.2	11.37	Peak	307.86	150	Vertical	Pass
2	5975.700	59.09	6.15	68.2	9.11	Peak	134.00	150	Vertical	Pass

U-NII-3 11n20 CH149




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5650.000	55.86	3.81	68.2	12.34	Peak	184.86	150	Horizontal	Pass
2	5640.125	57.03	3.74	68.2	11.17	Peak	35.00	150	Horizontal	Pass

U-NII-3 11n20 CH165




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5925.000	55.86	6.44	68.2	12.34	Peak	308.60	150	Vertical	Pass
2	5927.550	58.56	6.38	68.2	9.64	Peak	247.00	150	Vertical	Pass

U-NII-3 11n40 CH151




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5650.000	56.61	3.81	68.2	11.59	Peak	50.17	150	Horizontal	Pass
2	5641.250	58.42	3.74	68.2	9.78	Peak	32.00	150	Horizontal	Pass

U-NII-3 11n40 CH159



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5925.000	57.24	6.44	68.2	10.96	Peak	44.40	150	Vertical	Pass
2	5965.350	58.57	6.22	68.2	9.63	Peak	67.00	150	Vertical	Pass

U-NII-3 11ac80 CH155



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	5650.000	59.16	3.81	68.2	9.04	Peak	22.01	150	Horizontal	Pass
2	5643.875	61.66	3.76	68.2	6.54	Peak	27.00	150	Horizontal	Pass

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SH2540336-AR-1.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SH2540336-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SH2540336-AI.PDF”.

Statement

1. The Testing Center guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. For the report with Accreditation Symbol, the items marked with "☆" are not within the accredited scope.
3. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the test report stamp.
4. The test data and results are only valid for the tested samples provided by the customer.
5. This report shall not be partially reproduced without the written permission of the Testing Center.
6. Any objection shall be raised to the Testing Center within 30 days after receiving the report.

--END OF REPORT--